

Draft **ETSI EN 300 113-2** V1.4.1 (2006-08)

Candidate Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Land mobile service;
Radio equipment intended for the transmission
of data (and/or speech) using constant or non-constant
envelope modulation and having an antenna connector;
Part 2: Harmonized EN covering essential requirements
under article 3.2 of the R&TTE Directive**



Reference

REN/ERM-TGDMR-062-2

Keywords

antenna, data, radio, regulation, speech, mobile,
PMR, TDD, TDMA

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2006.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the TIPHON logo are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	5
1 Scope	6
2 References	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions	7
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Technical requirements specifications	8
4.1 Environmental profile.....	8
4.2 Transmitter requirements	8
4.2.1 Frequency error.....	8
4.2.1.1 Definition	8
4.2.1.2 Limit.....	8
4.2.1.3 Conformance.....	8
4.2.2 Carrier power (conducted)	8
4.2.2.1 Definition	8
4.2.2.2 Limit.....	8
4.2.2.3 Conformance.....	8
4.2.3 Effective radiated power	8
4.2.3.1 Definition	8
4.2.3.2 Limit.....	8
4.2.3.3 Conformance.....	8
4.2.4 Adjacent channel power.....	9
4.2.4.1 Definition	9
4.2.4.2 Limit.....	9
4.2.4.3 Conformance.....	9
4.2.5 Spurious emissions	9
4.2.5.1 Definition	9
4.2.5.2 Limit.....	9
4.2.5.3 Conformance.....	9
4.2.6 Intermodulation attenuation	9
4.2.6.1 Definition	9
4.2.6.2 Limit.....	9
4.2.6.3 Conformance.....	9
4.2.7 Transient power	9
4.2.7.1 Definition	9
4.2.7.2 Limit.....	9
4.2.7.3 Conformance.....	9
4.3 Receiver requirements.....	10
4.3.1 Maximum usable sensitivity	10
4.3.1.1 Definition	10
4.3.1.2 Limit.....	10
4.3.1.3 Conformance.....	10
4.3.2 Co-channel rejection	10
4.3.2.1 Definition	10
4.3.2.2 Limit.....	10
4.3.2.3 Conformance.....	10
4.3.3 Adjacent channel selectivity	10
4.3.3.1 Definition	10
4.3.3.2 Limit.....	10
4.3.3.3 Conformance.....	10
4.3.4 Spurious response rejection	10

4.3.4.1	Definition	10
4.3.4.2	Limit.....	11
4.3.4.3	Conformance.....	11
4.3.5	Intermodulation response rejection.....	11
4.3.5.1	Definition	11
4.3.5.2	Limit.....	11
4.3.5.3	Conformance.....	11
4.3.6	Blocking or desensitization.....	11
4.3.6.1	Definition	11
4.3.6.2	Limit.....	11
4.3.6.3	Conformance.....	11
4.3.7	Spurious radiations	11
4.3.7.1	Definition	11
4.3.7.2	Limit.....	11
4.3.7.3	Conformance.....	11
5	Testing for compliance with technical requirements.....	12
5.1	Environmental conditions for testing	12
5.1.1	Normal and extreme test-conditions	12
5.1.2	Test power source	12
5.1.3	Choice of samples for test suites.....	12
5.2	Interpretation of the measurement results	12
5.3	Essential radio test suites.....	13
5.3.1	Frequency error.....	13
5.3.2	Carrier power (conducted).....	13
5.3.3	Effective radiated power.....	13
5.3.4	Adjacent channel power.....	13
5.3.5	Spurious emissions	13
5.3.6	Intermodulation attenuation.....	13
5.3.7	Transient power	13
5.3.8	Receiver Spurious radiations	13
5.4	Other radio test suites	14
5.4.1	Maximum usable sensitivity.....	14
5.4.2	Co-channel rejection	14
5.4.3	Adjacent channel selectivity	14
5.4.4	Spurious response rejection	14
5.4.5	Intermodulation response rejection.....	14
5.4.6	Blocking or desensitization.....	14
Annex A (normative):	HS Requirement & conformance Test specifications Table (HS-RTT)....	15
Annex B (informative):	The EN title in the official languages	18
History		19

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Candidate Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [4] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC are given in annex A.

The present document is part 2 of a multi-part deliverable covering the Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector, as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [5].

1 Scope

The present document covers the technical requirements for radio transmitters and receivers used in stations in the Private Mobile Radio (PMR) service.

It applies to use in the land mobile service, operating on radio frequencies in all or in any part of the frequencies as given below, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, intended for speech and/or data.

Table 1: Radiocommunications service frequency bands

	Radiocommunications service frequency bands
Transmit	30 MHz to 1 000 MHz
Receive	30 MHz to 1 000 MHz

It applies to equipment for continuous and/or discontinuous transmission of data and/or digital speech.

The equipment comprises a transmitter and associated encoder and modulator and/or a receiver and associated demodulator and decoder. The types of equipment covered by the present document are as follows:

- base station (equipment fitted with an antenna socket, intended for use in a fixed location);
- mobile station (equipment fitted with an antenna socket, normally used in a vehicle or as a transportable);
- and those hand portable stations:
 - a) fitted with an antenna socket; or
 - b) without an external antenna socket (integral antenna equipment), but fitted with a permanent internal or a temporary internal 50 Ω Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Hand portable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document.

The present document is intended to cover the provisions of article 3.2 of Directive 1999/5/EC (R&TTE Directive) [1], which states that "..... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [1] may apply to equipment within the scope of the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [2] ETSI EN 300 113-1 (V1.6.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".
- [3] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [4] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations. .
- [5] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [1] and EN 300 113-1 [2] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in EN 300 113-1 [2] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in EN 300 113-1 [2] apply.

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer of the equipment. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Transmitter requirements

4.2.1 Frequency error

4.2.1.1 Definition

The frequency error is defined in EN 300 113-1 [2], clause 7.1.1.

4.2.1.2 Limit

The frequency error shall not exceed the limits in EN 300 113-1 [2], clause 7.1.3.

4.2.1.3 Conformance

Conformance tests as defined in clause 5.3.1 shall be carried out.

4.2.2 Carrier power (conducted)

4.2.2.1 Definition

The carrier power (conducted) is defined in EN 300 113-1 [2], clause 7.2.1.

4.2.2.2 Limit

The carrier power (conducted) shall not exceed the limits in EN 300 113-1 [2], clause 7.2.3.

4.2.2.3 Conformance

Conformance tests as defined in clause 5.3.2 shall be carried out.

4.2.3 Effective radiated power

4.2.3.1 Definition

The effective radiated power is defined in EN 300 113-1 [2], clause 7.3.1.

4.2.3.2 Limit

The effective radiated power shall not exceed the limits in EN 300 113-1 [2], clause 7.3.3.

4.2.3.3 Conformance

Conformance tests as defined in clause 5.3.3 shall be carried out.

4.2.4 Adjacent channel power

4.2.4.1 Definition

The adjacent channel power is defined in EN 300 113-1 [2], clause 7.4.1.

4.2.4.2 Limit

The adjacent channel power shall not exceed the limits in EN 300 113-1 [2], clause 7.4.3.

4.2.4.3 Conformance

Conformance tests as defined in clause 5.3.4 shall be carried out.

4.2.5 Spurious emissions

4.2.5.1 Definition

The spurious emissions are defined in EN 300 113-1 [2], clause 7.5.1.

4.2.5.2 Limit

The spurious emissions shall not exceed the limits in EN 300 113-1 [2], clause 7.5.4.

4.2.5.3 Conformance

Conformance tests as defined in clause 5.3.5 shall be carried out.

4.2.6 Intermodulation attenuation

4.2.6.1 Definition

The intermodulation attenuation is defined in EN 300 113-1 [2], clause 7.6.1.

4.2.6.2 Limit

The intermodulation attenuation shall not exceed the limits in EN 300 113-1 [2], clause 7.6.3.

4.2.6.3 Conformance

Conformance tests as defined in clause 5.3.6 shall be carried out.

4.2.7 Transient power

4.2.7.1 Definition

The transient frequency behaviour of the transmitter is defined in EN 300 113-1 [2], clause 7.9.1.

4.2.7.2 Limit

The transient frequency behaviour of the transmitter shall not exceed the limits in EN 300 113-1 [2], clause 7.9.4.

4.2.7.3 Conformance

Conformance tests as defined in clause 5.3.7 shall be carried out.

4.3 Receiver requirements

4.3.1 Maximum usable sensitivity

4.3.1.1 Definition

The sensitivity is defined in EN 300 113-1 [2], clause 8.1.1 (conducted) and clause 8.2.1 (field strength).

In addition, for duplex equipment (equipment providing simultaneous transmission and reception), the receiver desensitization is defined in EN 300 113-1 [2], clause 9.1.1.

4.3.1.2 Limit

The sensitivity shall not exceed the limits in EN 300 113-1 [2] clause 8.1.3 (conducted) and clause 8.2.3 (field strength).

In addition, for duplex equipment (equipment providing simultaneous transmission and reception), the receiver desensitization shall meet the requirements of EN 300 113-1 [2], clause 9.1.3.

4.3.1.3 Conformance

Conformance tests as defined in clause 5.4.1 may be carried out.

4.3.2 Co-channel rejection

4.3.2.1 Definition

The co-channel rejection is defined in EN 300 113-1 [2], clause 8.5.1.

4.3.2.2 Limit

The co-channel rejection shall not exceed the limits in EN 300 113-1 [2], clause 8.5.3.

4.3.2.3 Conformance

Conformance tests as defined in clause 5.4.2 may be carried out.

4.3.3 Adjacent channel selectivity

4.3.3.1 Definition

The adjacent channel selectivity is defined in EN 300 113-1 [2], clause 8.6.1.

4.3.3.2 Limit

The adjacent channel selectivity shall not exceed the limits in EN 300 113-1 [2], clause 8.6.3.

4.3.3.3 Conformance

Conformance tests as defined in clause 5.4.3 may be carried out.

4.3.4 Spurious response rejection

4.3.4.1 Definition

The spurious response rejection is defined in EN 300 113-1 [2], clause 8.7.1.

In addition, in the case of duplex equipment (equipment providing simultaneous transmission and reception), the receiver spurious response rejection is defined in EN 300 113-1 [2], clause 9.2.1.

4.3.4.2 Limit

The spurious response rejection shall not exceed the limits in EN 300 113-1 [2], clause 8.7.6.

In addition, in the case of duplex equipment (equipment providing simultaneous transmission and reception), the receiver spurious response rejection shall not exceed the limits in EN 300 113-1 [2], clause 9.2.3.

4.3.4.3 Conformance

Conformance tests as defined in clause 5.4.4 may be carried out.

4.3.5 Intermodulation response rejection

4.3.5.1 Definition

The intermodulation response rejection is defined in EN 300 113-1 [2], clause 8.8.1.

4.3.5.2 Limit

The intermodulation response rejection shall not exceed the limits in EN 300 113-1 [2], clause 8.8.3.

4.3.5.3 Conformance

Conformance tests as defined in clause 5.4.5 may be carried out.

4.3.6 Blocking or desensitization

4.3.6.1 Definition

The blocking or desensitization is defined in EN 300 113-1 [2], clause 8.9.1.

4.3.6.2 Limit

The blocking or desensitization shall not exceed the limits in EN 300 113-1 [2], clause 8.9.3.

4.3.6.3 Conformance

Conformance tests as defined in clause 5.4.6 may be carried out.

4.3.7 Spurious radiations

4.3.7.1 Definition

The spurious radiations are defined in EN 300 113-1 [2], clause 8.10.1.

4.3.7.2 Limit

The spurious radiations shall not exceed the limits in EN 300 113-1 [2], clause 8.10.4.

4.3.7.3 Conformance

Conformance tests as defined in clause 5.3.8 shall be carried out.

5 Testing for compliance with technical requirements

5.1 Environmental conditions for testing

Tests defined in the present document shall be carried out at representative points within the boundary limits of the declared operational environmental profile.

Where technical performance varies subject to environmental conditions, tests shall be carried out under a sufficient variety of environmental conditions (within the boundary limits of the declared operational environmental profile) to give confidence of compliance for the affected technical requirements.

5.1.1 Normal and extreme test-conditions

Measurements shall be made under normal test conditions, and also, where stated, under extreme test conditions.

The test conditions and procedures shall be as specified in EN 300 113-1 [2], clauses 5.3, 5.4 and 5.5.

5.1.2 Test power source

The test power source shall meet the requirements of EN 300 113-1 [2], clause 5.2.

5.1.3 Choice of samples for test suites

Measurement shall be performed, according to the present document, on samples of equipment defined in EN 300 113-1 [2], clause 4.1.

5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 1.

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028 [3] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 1 is based on such expansion factors.

The particular expansion factor used for the evaluation of the measurement uncertainty shall be stated.

Table 1: Absolute measurement uncertainties: maximum values

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-7}$
RF Power, conducted (up to 160 W)	$\pm 0,75$ dB
Radiated RF power	± 6 dB
Adjacent channel power	± 5 dB
Sensitivity	± 3 dB
Two-signal measurement, valid up to 4 GHz	± 4 dB
Three-signal measurement	± 3 dB
Conducted spurious emission of transmitter, valid up to 12,75 GHz	± 4 dB
Conducted spurious emission of receiver, valid up to 12,75 GHz	± 3 dB
Radiated emission of the transmitter, valid up to 4 GHz	± 6 dB
Radiated emission of receiver, valid up to 4 GHz	± 6 dB
Transmitter transient frequency (frequency difference)	± 250 Hz
Transmitter transient time	± 20 %
Temperature	$\pm 1^\circ$ K
Humidity	± 10 %
NOTE: Values valid up to 1 GHz for the RF parameters unless otherwise stated.	

5.3 Essential radio test suites

Essential test suites are referred to in annex III of R&TTE Directive [1].

The following essential test suites shall be used to assess the performance of equipment.

5.3.1 Frequency error

The measurements specified in EN 300 113-1 [2], clause 7.1.2 shall be carried out.

5.3.2 Carrier power (conducted)

The measurements specified in EN 300 113-1 [2], clause 7.2.2 shall be carried out.

5.3.3 Effective radiated power

The measurements specified in EN 300 113-1 [2], clause 7.3.2 shall be carried out.

5.3.4 Adjacent channel power

The measurements specified in EN 300 113-1 [2], clause 7.4.2 shall be carried out.

5.3.5 Spurious emissions

The measurements specified in EN 300 113-1 [2], clauses 7.5.2 and 7.5.3 shall be carried out.

5.3.6 Intermodulation attenuation

The measurements specified in EN 300 113-1 [2], clause 7.6.2 shall be carried out.

5.3.7 Transient power

The measurements specified in EN 300 113-1 [2], clause 7.9.3 shall be carried out.

5.3.8 Receiver Spurious radiations

The measurements specified in EN 300 113-1 [2], clauses 8.10.2 and 8.10.3 shall be carried out.

5.4 Other radio test suites

The requirements in clauses 4.3.1 to 4.3.7 inclusive have been set on the assumption that the measurements in clauses 5.4.1 to 5.4.6 are used in order to assess the performance of the equipment.

5.4.1 Maximum usable sensitivity

The measurements specified in EN 300 113-1 [2] clause 8.1.2 (conducted) and clause 8.2.2 (field strength) shall be carried out.

In addition, in the case of duplex equipment (equipment providing simultaneous transmission and reception), the measurements specified in EN 300 113-1 [2] clause 9.1.2 shall be carried out.

5.4.2 Co-channel rejection

The measurements specified in EN 300 113-1 [2], clause 8.5.2 shall be carried out.

5.4.3 Adjacent channel selectivity

The measurements specified in EN 300 113-1 [2], clause 8.6.2 shall be carried out.

5.4.4 Spurious response rejection

The measurements specified in EN 300 113-1 [2], clauses 8.7.2, 8.7.3, and either 8.7.4 or 8.7.5 shall be carried out.

In addition, in the case of duplex equipment (equipment providing simultaneous transmission and reception), the measurements specified in EN 300 113-1 [2], clause 9.2.2 shall be carried out.

5.4.5 Intermodulation response rejection

The measurements specified in EN 300 113-1 [2], clause 8.8.2 shall be carried out.

5.4.6 Blocking or desensitization

The measurements specified in EN 300 113-1 [2], clause 8.9.2 shall be carried out.

Annex A (normative): HS Requirement & conformance Test specifications Table (HS-RTT)

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the HS_RTT table in this annex so that it can be used for its intended purposes and may further publish the completed HS-RTT.

The HS Requirements & conformance Test specifications Table (HS-RTT) in table A.1 below serves a number of purposes, as follows:

- it provides a statement of all the essential requirements in words and by cross reference to a specific clause in the present document or to a specific clause in a specific referenced document;
- it provides a statement of all the test procedure corresponding to those essential requirements by cross reference to specific clause(s) in the present document or to a specific clause(s) in specific referenced document(s);
- it qualifies each requirement to be either:
 - Unconditional - meaning that the requirement applies in all circumstances; or
 - Conditional - meaning that the requirement is dependent on the supplier having chosen to support optional functionality defined within the schedule;
- in the case of Conditional requirements, it associates the requirement with the particular optional service or functionality;
- it qualifies each test procedure to be either:
 - Essential: meaning that it is included with the Essential Radio Test Suite and therefore the requirement shall be demonstrated to be met in accordance with the referenced procedures;
 - Other: meaning that the test procedure is illustrative but other means of demonstrating compliance with the requirement are permitted;
- when the schedule is completed in respect of a particular equipment including the testing outcomes, including a completed version of Table A1 it provides a means to assert the "presumption of conformity" with the HS.

Table A.1: HS Requirements & conformance Test specifications Table (HS-RTT)

Harmonized Standard EN EN 300 113-2							
The following essential requirements and test specifications are relevant to the presumption of conformity under Article 3.2 of the R&TTE Directive							
Technical Requirement reference			Technical Requirement Conditionality		Test Specification		
No	Description	Reference: Clause No	U/C	Condition	E/O	Reference: Clause No	
1	Transmitter frequency error	4.2.1	U		E	5.3.1	
2	Transmitter carrier power conducted	4.2.2	U		E	5.3.2	
3	Transmitter maximum effective radiated power	4.2.3	C	Applies only to equipment without an external antenna connector.	E	5.3.3	
4	Transmitter adjacent channel power	4.2.4	U		E	5.3.4	
5	Transmitter spurious emissions	4.2.5	U		E	5.3.5	
6	Transmitter intermodulation attenuation	4.2.6	C	Applies only to transmitters to be used in base stations.	E	5.3.6	
7	Transmitter transient power	4.2.7	U		E	5.3.7	
8	Receiver spurious radiations	4.3.3	U		E	5.3.8	
9	Receiver maximum useable sensitivity	4.3.1	C	Applies only to equipment using listen-before-transmit.	O	5.4.1	
10	Receiver co-channel rejection	4.3.2	C	Applies only to equipment using listen-before-transmit.	O	5.4.2	
11	Receiver adjacent channel selectivity	4.3.3	C	Applies only to equipment using listen-before-transmit.	O	5.4.3	
12	Receiver spurious response rejection	4.3.4	C	Applies only to equipment using listen-before-transmit.	O	5.4.4	
13	Receiver inter-modulation response	4.3.5	C	Applies only to equipment using listen-before-transmit.	O	5.4.5	
14	Receiver blocking or desensitization	4.3.6	C	Applies only to equipment using listen-before-transmit.	O	5.4.6	

Key to columns:**Essential Requirement:**

No A unique identifier for one row of the table which may be used to identify an essential requirement or its test specification.

Description A textual reference to the Essential Requirement

Reference: Clause Number

Identification of clause(s) defining the essential requirement in the present document unless another document is referenced explicitly

Conditionality:

U/C Indicates whether the requirement is to be *unconditionally* applicable (U) or is *conditional* upon the suppliers claimed functionality of the equipment (C)

Condition Explains the conditions when the requirement shall or shall not be applicable for a requirement which is classified "conditional"

Test Specification:

E/O Indicates whether the test specification forms part of the *Essential Radio Test Suite* (E) or whether it is one of the *Other Test Suite* (O)

NOTE: All tests whether "E" or "O" are relevant to technical requirements. Rows designated "E" collectively make up the Essential Radio Test Suite; those designated "O" make up the Other Test Suite; for those designated "X" there is no test specified corresponding to the technical requirements. All tests classified "E" shall be performed as specified with satisfactory outcomes is a necessary condition for a presumption of conformity. Technical requirements associated with tests classified "O" or "X" must be complied with as a necessary condition for presumption of conformity, although conformance with the requirement may be claimed by an equivalent test or by manufacturer's assertion supported by appropriate entries in the technical construction file.

Reference: Clause Number

Identification of clause(s) defining the test specification in the present, document unless another document is referenced explicitly. Where no test is specified (that is, where the previous field is "X") this field remains blank.

Annex B (informative): The EN title in the official languages

Language	EN title
Czech	
Danish	
Dutch	
English	Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive
Estonian	
Finnish	
French	
German	
Greek	
Hungarian	
Icelandic	
Italian	
Latvian	
Lithuanian	
Maltese	
Norwegian	
Polish	
Portuguese	
Slovak	
Slovenian	
Spanish	
Swedish	

History

Document history		
V1.1.1	March 2001	Publication
V1.2.1	April 2002	Publication
V1.3.1	December 2003	Publication
V1.4.1	August 2006	Public Enquiry PE 20061208: 2006-08-09 to 2006-12-08