

Draft **EN 300 138-5** V1.3.3 (1998-02)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);
Closed User Group (CUG) supplementary service;
Digital Subscriber Signalling System No. one (DSS1) protocol;
Part 5: Test Suite Structure and Test Purposes (TSS&TP)
specification for the network**



European Telecommunications Standards Institute

Reference

REN/SPS-05145-H-5 (1a190j20.PDF)

Keywords

ISDN, DSS1, supplementary service, CUG,
testing, TSS&TP, network

ETSI Secretariat

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

X.400

c= fr; a=atlas; p=etsi; s=secretariat

Internet

secretariat@etsi.fr
<http://www.etsi.fr>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

Contents

Intellectual Property Rights.....	4
Foreword	4
1 Scope.....	5
2 Normative references	5
3 Definitions.....	6
3.1 Definitions related to conformance testing	6
3.2 Definitions related to EN 300 138-1	6
4 Abbreviations	7
5 Test Suite Structure (TSS)	7
6 Test Purposes (TP).....	7
6.1 Introduction.....	7
6.1.1 Test purpose naming convention.....	8
6.1.2 Source of TP definition	8
6.1.3 TP structure.....	8
6.1.4 Test strategy	9
6.1.5 Test of call states.....	9
6.2 Network TPs for CUG	9
6.2.1 Calling user interface.....	9
6.2.1.1 Explicit request.....	9
6.2.1.1.1 CUG call successful at originating network side and at destination network side.....	9
6.2.1.1.2 CUG call failed at originating network side.....	12
6.2.1.1.3 CUG call failed at destination network side.....	16
6.2.1.2 Default request.....	17
6.2.1.2.1 CUG call successful at originating network side and at destination network side.....	17
6.2.1.2.2 CUG call failed at originating network side.....	18
6.2.1.2.3 CUG call failed at destination network side.....	19
6.2.1.3 User without CUG	21
6.2.1.3.1 CUG call successful at originating network side and at destination network side.....	21
6.2.1.3.2 CUG call failed at originating network side.....	21
6.2.1.3.3 CUG call failed at destination network side.....	22
6.2.2 Called user interface.....	22
7 Compliance	23
8 Requirements for a comprehensive testing service.....	23
Annex A (informative): Changes with respect to the previous ETS 300 138-5	24
History	25

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETR 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.fr/ipr>).

Pursuant to the ETSI Interim IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETR 314 (or the updates on <http://www.etsi.fr/ipr>) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 5 of a multi-part standard covering the Digital Subscriber Signalling System No. one (DSS1) protocol specification for the Integrated Services Digital Network (ISDN) Closed User Group (CUG) supplementary service, as described below:

- Part 1: "Protocol specification";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";**
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

The present version updates the references to the basic call specifications.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

This fifth part of EN 300 138 specifies the Test Suite Structure and Test Purposes (TSS&TP) for the Network side of the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [6]) of implementations conforming to the stage three standard for the Closed User Group (CUG) supplementary service for the pan-European Integrated Services Digital Network (ISDN) by means of the Digital Subscriber Signalling System No. one (DSS1) protocol, EN 300 138-1 [1].

A further part of this EN specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma based on the present document. Other parts specify the TSS&TP and the ATS and partial PIXIT proforma for the User side of the T reference point or coincident S and T reference point of implementations conforming to EN 300 138-1 [1].

2 Normative references

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply; or
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity); or
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] EN 300 138-1 (V1.3): "Integrated Services Digital Network (ISDN); Closed User Group (CUG) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [2] EN 300 138-2 (V1.3): "Integrated Services Digital Network (ISDN); Closed User Group (CUG) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] ISO/IEC 9646-1: "Information technology - OSI Conformance Testing Methodology and Framework; Part 1: General Concepts".
- [4] ISO/IEC 9646-2: "Information technology - OSI Conformance Testing Methodology and Framework; Part 2: Abstract Test Suite specification".
- [5] ISO/IEC 9646-3: "Information technology - OSI Conformance Testing Methodology and Framework; Part 3: The Tree and Tabular Combined Notation".
- [6] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces - Reference configurations".
- [7] EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".
- [8] ITU-T Recommendation I.112: "Vocabulary and terms for ISDNs".
- [9] CCITT Recommendation E.164: "Numbering plan for the ISDN era".
- [10] ITU-T Recommendation I.210: "Principles of the telecommunication services supported by an ISDN and the means to describe them".

3 Definitions

For the purposes of the present document, the following definitions apply:

3.1 Definitions related to conformance testing

abstract test case: Refer to ISO/IEC 9646-1 [3].

Abstract Test Suite (ATS): Refer to ISO/IEC 9646-1 [3].

active test: A test case where the IUT is required to send a particular message, but not in reaction to a received message. This would usually involve the use of PIXIT information to see how this message can be generated and quite often is specified in an ATS using an implicit send event.

Implementation Under Test (IUT): Refer to ISO/IEC 9646-1 [3].

implicit send event: Refer to ISO/IEC 9646-3 [5].

lower tester: Refer to ISO/IEC 9646-1 [3].

passive test: A test case where the IUT is required to respond to a protocol event (e.g. received message) with another protocol event (e.g. send message) which normally does not require any special operator intervention as associated with the implicit send event.

point of control and observation: Refer to ISO/IEC 9646-1 [3].

Protocol Implementation Conformance Statement (PICS): Refer to ISO/IEC 9646-1 [3].

PICS proforma: Refer to ISO/IEC 9646-1 [3].

Protocol Implementation eXtra Information for Testing (PIXIT): Refer to ISO/IEC 9646-1 [3].

PIXIT proforma: Refer to ISO/IEC 9646-1 [3].

system under test: Refer to ISO/IEC 9646-1 [3].

Test Purpose (TP): Refer to ISO/IEC 9646-1 [3].

3.2 Definitions related to EN 300 138-1

Integrated Services Digital Network (ISDN): See ITU-T Recommendation I.112 [8], definition 308.

ISDN number: A number conforming to the numbering and structure specified in CCITT Recommendation E.164 [9].

network: The DSS1 protocol entity at the Network side of the user-network interface where a T reference point or coincident S and T reference point applies.

network (S/T): The DSS1 protocol entity at the Network side of the user-network interface where a coincident S and T reference point applies.

network (T): The DSS1 protocol entity at the Network side of the user-network interface where a T reference point applies (Network connected to Private ISDN).

service; telecommunication service: See ITU-T Recommendation I.112 [8], definition 201.


supplementary service: See ITU-T Recommendation I.210 [10], subclause 2.4.

4 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
CUG	Closed User Group
DNF	call at Destination Network Failed
IA	Incoming Access
ICB	Incoming Calls Barred
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
N00	Null call state
N01	Call Initiated call state
N03	Outgoing Call Proceeding call state
N04	Call Delivered call state
N06	Call Present call state
N07	Call Received call state
N08	Connect Request call state
N09	Incoming Call Proceeding call state
N12	Disconnect Indication call state
N19	Release Request call state
OA	Outgoing Access
OCB	Outgoing Calls Barred
ODNS	call at Originating and at Destination Network Successful
ONF	call at Originating Network Failed
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
TP	Test Purpose
TSS	Test Suite Structure

5 Test Suite Structure (TSS)



NOTE: Numbers in brackets represent group numbers and are used in TP identifiers.

Figure 1: Test suite structure

6 Test Purposes (TP)

6.1 Introduction

For each test requirement a TP is defined.

6.1.1 Test purpose naming convention

The TPs are numbered, starting at 001, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite and whether it applies to the network or the user (see table 1).

Table 1: TP identifier naming convention scheme

Identifier: <ss>_<iut><group>_<nnn>			
<ss>	=	supplementary service:	e.g. "CUG"
<iut>	=	type of IUT:	U User N Network
<group>	=	group	2 digit field representing group reference according to TSS
<nnn>	=	sequential number	(001-999)

6.1.2 Source of TP definition

The TPs are based on EN 300 138-1 [1].

6.1.3 TP structure

Each TP has been written in a manner which is consistent with all other TPs. The intention of this is to make the TPs more readable and checkable. A particular structure has been used and this is illustrated in table 2. This table should be read in conjunction with any TP i.e. use a TP as an example to fully understand the table.

Table 2: Structure of a single TP

TP part	Text	Example
Header	<Identifier> <i>tab</i> <paragraph number in base ETS> <i>CR</i>	see table 1 subclause 0.0.0
Stimulus	Ensure that the IUT in the <basic call state> <trigger> <i>see below for message structure</i> <i>or</i> <goal>	N00, N10, etc. receiving a XXXX message to request a ...
Reaction	<action> <conditions> <i>if the action is sending</i> <i>see below for message structure</i> <next action>, <i>etc.</i> and enters <supplementary service state> <i>and/or</i> and remains in the same state(s) <i>or</i> and enters state <state> with CR<number(s)>	sends, saves, does, etc. using en bloc sending, ...
Message structure	<message type> message containing a a) <info element> information element with b) a <field name> encoded as <i>or</i> including <coding of the field> and <i>back to a or b</i> ,	SETUP, FACILITY, CONNECT, ... Bearer capability, Facility, ...
NOTE:	Text in italics will not appear in TPs and text between <> is filled in for each TP and may differ from one TP to the next.	

6.1.4 Test strategy

As the base standard EN 300 138-1 [1] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the PICS specification EN 300 138-2 [2]. The criteria applied include the following:

- only the requirements from the point of view of the T or coincident S and T reference point are considered;
- whether or not a test case can be built from the TP is not considered.

6.1.5 Test of call states

Many TPs include a reference to the IUT's final call state after the realization of the TP. In these cases the TP includes the requirement to ensure that the IUT has entered this particular final call state. Ensuring that the IUT is in a particular call state shall be realized by following the procedures described in subclause 5.8.10 of EN 300 403-1 [7]. According to these procedures, the IUT on receipt of a STATUS ENQUIRY message, shall respond with a STATUS message indicating, in the third octet of the Call state information element, the current call state of the IUT. This exchange of messages is not mentioned explicitly in each TP but is considered to be implicit in the reference to the final call state. This way of phrasing the TPs has been used to avoid over-complicating the text and structure of the TPs and to improve the readability.

6.2 Network TPs for CUG

All PICS items referred to in this subclause are as specified in EN 300 138-2 [2] unless indicated otherwise by another numbered reference.

6.2.1 Calling user interface

6.2.1.1 Explicit request

6.2.1.1.1 CUG call successful at originating network side and at destination network side

NOTE: For all TPs in this subclause, the network (IUT) is to be configured so that the called user has subscribed to the CUG service and has the options Incoming Access (IA) set to allowed and not Incoming Calls Barred (ICB). This combination is only tested in this subclause as the "normal call" output is the subject of the TPs in subclause 6.2.1.2 (Default request).

CUG_N01_001 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03, and the calling user has subscribed to the CUG supplementary service and has the options Outgoing Access (OA) is not allowed, not Outgoing Calls Barred (OCB) and not preferential CUG, and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and there is a match between CUG index and CUG interlock code, to indicate that the called user has entered the alerting phase, responds with an ALERTING message and enters call state N04.

CUG_N01_002 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, and there is a match between CUG index and CUG interlock code, to indicate that the called user has entered the alerting phase, responds with an ALERTING message and enters call state N04.

CUG_N01_003 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and there is a match between CUG index and CUG interlock code, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_004 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, and there is a match between CUG index and CUG interlock code, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_005 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex is not included, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_006 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex is not included, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_007 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and not preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex is not included, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_008 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and not preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex is not included, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_009 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and there is a match between CUG index and CUG interlock code, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_010 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, and there is a match between CUG index and CUG interlock code, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_011 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex not included, the CUG interlock code is set to preferential CUG, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_012 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and there is a match between CUG index and CUG interlock code, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_013 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, and there is a match between CUG index and CUG interlock code, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_014 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex not included, the CUG interlock code is set to preferential CUG, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_015 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex not included, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N01_016 subclause 9.2.1.1 and tables 5&6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and preferential CUG and the called user has subscribed to the CUG service and has the options IA set to allowed and not ICB, after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex not included, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

6.2.1.1.2 CUG call failed at originating network side

NOTE: For all the TPs in this subclause, the CUG has the options IA set to allowed and not ICB.

CUG_N02_001 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index is not appropriate to the requested basic service, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "requestedBasicServiceViolatesCUGConstraints".

CUG_N02_002 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_003 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, but the CUG index is not appropriate to the requested basic service, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "requestedBasicServiceViolatesCUGConstraints".

CUG_N02_004 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_005 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex is not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "inconsistencyInDesignatedFacilityAndSubscriberClass".

CUG_N02_006 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex is not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "inconsistencyInDesignatedFacilityAndSubscriberClass".

CUG_N02_007 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_008 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_009 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex is not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "inconsistencyInDesignatedFacilityAndSubscriberClass".

CUG_N02_010 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex is not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "inconsistencyInDesignatedFacilityAndSubscriberClass".

CUG_N02_011 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index is not appropriate to the requested basic service, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "requestedBasicServiceViolatesCUGConstraints".

CUG_N02_012 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_013 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, but the CUG index is not appropriate to the requested basic service, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "requestedBasicServiceViolatesCUGConstraints".

CUG_N02_014 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_015 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and not preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_016 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and not preferential CUG, rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_017 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index is not appropriate to the requested basic service, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "requestedBasicServiceViolatesCUGConstraints".

CUG_N02_018 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_019 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, but the CUG index is not appropriate to the requested basic service, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "requestedBasicServiceViolatesCUGConstraints".

CUG_N02_020 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_021 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "notSubscribed".

CUG_N02_022 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex is included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and preferential CUG, rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_023 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex is included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and preferential CUG, rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_024 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_025 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "notSubscribed".

CUG_N02_026 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index is not appropriate to the requested basic service, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "requestedBasicServiceViolatesCUGConstraints".

CUG_N02_027 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_028 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, but the CUG index is not appropriate to the requested basic service, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "requestedBasicServiceViolatesCUGConstraints".

CUG_N02_029 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_030 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex is included, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_031 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex is included, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_032 subclause 9.2.1.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex is not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and preferential CUG,

rejects the call with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "outgoingCallsBarredWithinCUG".

CUG_N02_033 subclause 9.2.1.2 last paragraph

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Channel identification information element coded as "B1 exclusive" and B1-channel is already occupied, and a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, but the CUG index does not exist, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG,

rejects the call with Cause #44 "requested circuit/channel not available", and with a Facility information element containing a cUGCall return error component indicating "invalidOrUnregisteredCUGIndex".

CUG_N02_034 subclause 9.2.1.2 last paragraph

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and the calling user has not subscribed to the CUG supplementary service,

rejects the call with Cause #29 "facility rejected", and with a Facility information element containing a cUGCall return error component indicating "notSubscribed".

CUG_N02_035 subclause 9.2.1.2 last paragraph

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, and the calling user has not subscribed to the CUG supplementary service,

rejects the call with Cause #29 "facility rejected", and with a Facility information element containing a cUGCall return error component indicating "notSubscribed".

CUG_N02_036 subclause 9.2.1.2 last paragraph

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex not included, and the calling user has not subscribed to the CUG supplementary service,

rejects the call with Cause #29 "facility rejected", and with a Facility information element containing a cUGCall return error component indicating "notSubscribed".

CUG_N02_037 subclause 9.2.1.2 last paragraph

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex not included, and the calling user has not subscribed to the CUG supplementary service,

rejects the call with Cause #29 "facility rejected", and with a Facility information element containing a cUGCall return error component indicating "notSubscribed".

6.2.1.1.3 CUG call failed at destination network side**CUG_N03_001 subclause 9.2.1.2 and table 6**

Ensure that the IUT in the Call Initiated call state N01 after receiving a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and there is a match between CUG index and CUG interlock code and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "IncomingCallsBarredWithinCUG" and enters call state N12 or N00, respectively.

Selection: IUT supports option to offer ICB. PICS: MC 3.

CUG_N03_002 subclause 9.2.1.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after receiving a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and there is a match between CUG index and CUG interlock code and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "IncomingCallsBarredWithinCUG" and enters call state N12 or N00, respectively.

CUG_N03_003 subclause 9.2.1.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after receiving a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and there is a match between CUG index and CUG interlock code and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has not subscribed to the CUG supplementary service, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and a Facility information element containing a cUGCall return error component indicating "userNotMemberOfCUG" and enters call state N12 or N00, respectively.

CUG_N03_004 subclause 9.2.1.2 and table 6

Ensure that the IUT in the Call Initiated call state N01, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, ICB, after receiving a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex is not included, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not member of CUG" and enters call state N12 or N00, respectively.

CUG_N03_005 subclause 9.2.1.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after receiving a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex is not included, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, not ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not member of CUG" and enters call state N12 or N00, respectively.

CUG_N03_006 subclause 9.2.1.2, 2nd last paragraph

Ensure that the IUT in the Call Initiated call state N01 and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, not ICB after the receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and there is a match between CUG index and CUG interlock code, on the second expiry of timer T303, and allowing for the possibility of a CALL PROCEEDING message being received,

sends a DISCONNECT or RELEASE COMPLETE message with Cause #18 "no user responding" and with a Facility information element containing a cUGCall return error component indicating "basicServiceNotProvided" and enters call state N12 or N00, respectively.

6.2.1.2 Default request**6.2.1.2.1 CUG call successful at originating network side and at destination network side****CUG_N04_001 subclause 9.2.2.1 and table 5**

Ensure that the IUT in the Outgoing Call Proceeding call state N03 after receiving a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, not ICB, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N04_002 subclause 9.2.2.1 and table 5

Ensure that the IUT in the Outgoing Call Proceeding call state N03 after receiving a SETUP message without a Facility information element containing a cUGCall invoke component and the CUG interlock code is set to preferential CUG, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, not ICB, to indicate that the called user has entered the alerting phase,
responds with an ALERTING message and enters call state N04.

CUG_N04_003 subclause 9.2.2.1 and table 5

Ensure that the IUT in the Outgoing Call Proceeding call state N03 after receiving a SETUP message without a Facility information element containing a cUGCall invoke component and the CUG interlock code is set to preferential CUG, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, not ICB, to indicate that the called user has entered the alerting phase,
responds with an ALERTING message and enters call state N04.

CUG_N04_004 subclause 9.2.2.1 and table 5

Ensure that the IUT in the Outgoing Call Proceeding call state N03 after receiving a SETUP message without a Facility information element containing a cUGCall invoke component and the CUG interlock code is set to preferential CUG, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, not ICB, to indicate that the called user has entered the alerting phase,
responds with an ALERTING message and enters call state N04.

CUG_N04_005 subclause 9.2.2.1 and table 5

Ensure that the IUT in the Outgoing Call Proceeding call state N03 after receiving a SETUP message without a Facility information element containing a cUGCall invoke component and the CUG interlock code is set to preferential CUG, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, not ICB, to indicate that the called user has entered the alerting phase,
responds with an ALERTING message and enters call state N04.

CUG_N04_006 subclause 9.2.2.1 and table 6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has not subscribed to the CUG supplementary service, to indicate that the called user has entered the alerting phase,
responds with an ALERTING message and enters call state N04.

6.2.1.2.2 CUG call failed at originating network side**CUG_N05_001 subclause 9.2.2.2 and table 5**

Ensure that the IUT in the Call Initiated call state N01, after receiving a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and not preferential CUG, and allowing for the possibility of a CALL PROCEEDING message being received,
responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and enters call state N12 or N00, respectively.

CUG_N05_002 subclause 9.2.2.2 and table 5

Ensure that the IUT in the Call Initiated call state N01, after receiving a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and not preferential CUG, and allowing for the possibility of a CALL PROCEEDING message being received,
responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and enters call state N12 or N00, respectively.

CUG_N05_003 subclause 9.2.2.2 and table 5

Ensure that the IUT in the Call Initiated call state N01, after receiving a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, OCB and preferential CUG, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" enters call state N12 or N00, respectively.

CUG_N05_004 subclause 9.2.2.2 and table 5

Ensure that the IUT in the Call Initiated call state N01, after receiving a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and preferential CUG, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and enters call state N12 or N00, respectively.

CUG_N05_005 subclause 9.2.2.1 and table 5

Ensure that the IUT in the Call Initiated call state N01 after receiving a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, not ICB, allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with cause #29 "facility rejected" and enters call state N12 or N00, respectively.

CUG_N05_006 subclause 9.2.2.1 and table 5

Ensure that the IUT in the Call Initiated call state N01 after receiving a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with cause #29 "facility rejected" and enters call state N12 or N00, respectively.

6.2.1.2.3 CUG call failed at destination network side**CUG_N06_001 subclause 9.2.2.2 and table 6**

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, not ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not a member of CUG" and enters call state N12 or N00, respectively.

CUG_N06_002 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, ICB and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not a member of CUG" and enters call state N12 or N00, respectively.

CUG_N06_003 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, not ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not a member of CUG" and enters call state N12 or N00, respectively.

CUG_N06_004 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not a member of CUG" and enters call state N12 or N00, respectively.

CUG_N06_005 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and there is a match between the CUG index and interlock code, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and enters call state N12 or N00, respectively.

CUG_N06_006 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and there is a match between the CUG index and interlock code, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" enters call state N12 or N00, respectively.

CUG_N06_007 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and there is a match between the CUG index and interlock code, and the calling user has subscribed to the CUG supplementary service and has the options OA is not allowed, not OCB and preferential CUG, and the called user has not subscribed to the CUG supplementary service, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not a member of CUG" and enters call state N12 or N00, respectively.

CUG_N06_008 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and there is a match between the CUG index and interlock code, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and enters call state N12 or N00, respectively.

CUG_N06_009 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and there is a match between the CUG index and interlock code, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, ICB, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #29 "facility rejected" and enters call state N12 or N00, respectively.

CUG_N06_010 subclause 9.2.2.2 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and there is a match between the CUG index and interlock code, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and preferential CUG, and the called user has not subscribed to the CUG supplementary service, and allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not a member of CUG" and enters call state N12 or N00, respectively.

CUG_N06_011 subclause 9.2.2.1 and table 5

Ensure that the IUT in the Call Initiated call state N01 after receiving a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has subscribed to the CUG supplementary service and has the options OA is allowed, not OCB and not preferential CUG, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, ICB, allowing for the possibility of a CALL PROCEEDING message being received,

responds with a DISCONNECT or RELEASE COMPLETE message with cause #29 "facility rejected" and enters call state N12 or N00, respectively.

6.2.1.3 User without CUG**6.2.1.3.1 CUG call successful at originating network side and at destination network side****CUG_N07_001 subclause 9.2.3.1 and table 6**

Ensure that the IUT in the Outgoing Call Proceeding call state N03 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has not subscribed to the CUG supplementary service, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, ICB, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

CUG_N07_002 subclause 9.2.3.1 and table 6

Ensure that the IUT in the Outgoing Call Proceeding call state N03 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the calling user has not subscribed to the CUG supplementary service, and the called user has subscribed to the CUG supplementary service and has the options IA is allowed, not ICB, to indicate that the called user has entered the alerting phase,

responds with an ALERTING message and enters call state N04.

6.2.1.3.2 CUG call failed at originating network side**CUG_N08_001 subclause 9.2.3.2 and table 5**

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex included, and the calling user has not subscribed to the CUG supplementary service,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #50 "requested facility not subscribed" and a Facility information element containing a cUGCall return error component indicating "notSubscribed" and enters call state N12 or N00, respectively.

CUG_N08_002 subclause 9.2.3.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to TRUE and CUGIndex included, and the calling user has not subscribed to the CUG supplementary service,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #50 "requested facility not subscribed" and a Facility information element containing a cUGCall return error component indicating "notSubscribed" and enters call state N12 or N00, respectively.

CUG_N08_003 subclause 9.2.3.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARequested set to FALSE and CUGIndex not included, and the calling user has not subscribed to the CUG supplementary service,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #50 "requested facility not subscribed" and a Facility information element containing a cUGCall return error component indicating "notSubscribed" and enters call state N12 or N00, respectively.

CUG_N08_004 subclause 9.2.3.2 and table 5

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component with OARRequested set to TRUE and CUGIndex not included, and the calling user has not subscribed to the CUG supplementary service,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #50 "requested facility not subscribed" and a Facility information element containing a cUGCall return error component indicating "notSubscribed" and enters call state N12 or N00, respectively.

CUG_N08_005 subclause 9.2.3.2, 2nd paragraph

Ensure that the IUT in the Null call state N00 on receipt of a SETUP message with a Facility information element containing a cUGCall invoke component but the network cannot recognize this supplementary service request, and the calling user has not subscribed to the CUG supplementary service,

responds with a FACILITY, SETUP ACKNOWLEDGE or CALL PROCEEDING message with a Facility information element containing a reject component and continues normal call handling.

6.2.1.3.3 CUG call failed at destination network side**CUG_N09_001 subclause 9.2.3.1 and table 6**

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, not ICB, and allowing for receipt of a CALL PROCEEDING message,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not a member of CUG" and enters call state N12 or N00, respectively.

CUG_N09_002 subclause 9.2.3.1 and table 6

Ensure that the IUT in the Call Initiated call state N01 after the receipt of a SETUP message without a Facility information element containing a cUGCall invoke component, and the called user has subscribed to the CUG supplementary service and has the options IA is not allowed, ICB, and allowing for receipt of a CALL PROCEEDING message,

responds with a DISCONNECT or RELEASE COMPLETE message with Cause #87 "user not a member of CUG" and enters call state N12 or N00, respectively.

6.2.2 Called user interface**CUG_N10_001 subclause 9.2.4.1**

Ensure that the IUT in the Null call state N00, and both the calling user and the called user have subscribed to the CUG supplementary service,

is able to send a SETUP message with a Facility information element containing a cUGCall invoke component to the called user and enters call state N06.

CUG_N10_002 subclause 9.2.4.1

Ensure that the IUT in the Incoming Call Proceeding call state N09, after sending a SETUP message with a Facility information element containing a cUGCall invoke component, and both the calling user and the called user have subscribed to the CUG supplementary service, on receipt of an ALERTING message,

continues normal call handling and enters call state N07.

CUG_N10_003 subclause 9.2.4.1

Ensure that the IUT in the Incoming Call Proceeding call state N09, after sending a SETUP message with a Facility information element containing a cUGCall invoke component, and both the calling user and the called user have subscribed to the CUG supplementary service, on receipt of a CONNECT message,

continues normal call handling and enters call state N08.

CUG_N10_004 subclause 9.2.4.1 b

Ensure that the IUT in the Incoming Call Proceeding call state N09, after sending a SETUP message with a Facility information element containing a cUGCall invoke component, on receipt of a DISCONNECT message containing a Facility information element with a cUGCall return error,

responds with a RELEASE message and enters call state N19.

7 Compliance

An ATS which complies with this TSS&TP specification shall:

- a) consist of a set of test cases corresponding to the set or to a subset of the TPs specified in clause 6;
- b) use a TSS which is an appropriate subset of the whole of the TSS specified in clause 5;
- c) use the same naming conventions for the test groups and test cases;
- d) maintain the relationship specified in clause 6 between the test groups and TPs and the entries in the PICS proforma to be used for test case deselection;
- e) comply with ISO/IEC 9646-2 [4].

In the case of a) or b) above, a subset shall be used only where a particular Abstract Test Method (ATM) makes some TPs untestable. All testable TPs from clause 6 shall be included in a compliant ATS.

8 Requirements for a comprehensive testing service

As a minimum the Remote test method, as specified in ISO/IEC 9646-2 [4], shall be used by any organization claiming to provide a comprehensive testing service for network equipment claiming conformance to EN 300 138-1 [1].

Annex A (informative): Changes with respect to the previous ETS 300 138-5

The following changes have been done:

- conversion to EN layout;
- replacement of references to ETS 300 102 with EN 300 403;
- substitution of non-specific references to basic standards where the intention is to refer to the latest version.

History

Document history		
Edition 1	May 1997	Publication as ETS 300 138-5
V1.3.3	February 1998	One-step Approval Procedure OAP 9824: 1998-02-13 to 1998-06-12