

EN 300 185-2 V1.2.4 (1998-06)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);
Conference call, add-on (CONF) supplementary service;
Digital Subscriber Signalling System No. one (DSS1) protocol;
Part 2: Protocol Implementation Conformance
Statement (PICS) proforma specification**



Reference

REN/SPS-05145-J1-2 (1poi0iqo.PDF)

Keywords

ISDN, CONF, DSS1, supplementary service,
PICS

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
<http://www.etsi.fr>
<http://www.etsi.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.
All rights reserved.

Contents

Intellectual Property Rights.....	5
Foreword	5
1 Scope.....	6
2 Normative references	6
3 Definitions.....	7
4 Abbreviations.....	7
5 Conformance	8
Annex A (normative): PICS proforma.....	9
A.1 Instructions for completing the PICS proforma	9
A.1.1 Identification of the implementation	9
A.1.2 Global statement of conformance	9
A.1.3 Explanation of PICS proforma subclauses.....	9
A.1.4 Symbols, abbreviations and terms.....	10
A.2 Identification of the implementation.....	10
A.2.1 Implementation Under Test (IUT) identification	10
A.2.2 System Under Test (SUT) identification.....	10
A.2.3 Product supplier	11
A.2.4 Client	11
A.2.5 PICS contact person.....	11
A.3 PICS/System Conformance Statement (SCS).....	12
A.4 Identification of the protocol	12
A.5 Global statement of conformance	12
A.6 Roles.....	13
A.7 User.....	13
A.7.1 Major capabilities	14
A.7.2 Subsidiary capabilities	14
A.7.3 Protocol data units	14
A.7.4 Protocol data unit parameters.....	15
A.7.5 Timers.....	16
A.7.6 Call states.....	16
A.8 Network.....	16
A.8.1 Major capabilities	17
A.8.2 Subsidiary capabilities	17
A.8.3 Protocol data units	17
A.8.4 Protocol data unit parameters.....	18
A.8.5 Timers.....	20
A.8.6 Call states.....	20
Annex B (normative): Requirements list.....	21
B.1 User	21
B.1.1 Requirements on items used in the basic call PICS	21
B.1.2 Requirements on items used in the generic functional protocol PICS	21
B.1.3 Requirements on items used in the supplementary service interactions PICS.....	22
B.2 Network.....	23
B.2.1 Requirements on items used in the basic call PICS	23
B.2.2 Requirements on items used in the generic functional protocol PICS	23

B.2.3	Requirements on items used in the supplementary service interactions PICS.....	24
Annex C (informative):	Changes with respect to the previous ETS 300 185-2	25
History		26

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.fr/ipr> or <http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 2 of a multi-part standard covering the Digital Subscriber Signalling System No. one (DSS1) protocol specification for the Integrated Services Digital Network (ISDN) Conference call, add-on (CONF) supplementary service, as described below:

Part 1: "Protocol specification";

Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";

Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";

Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";

Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a given Open Systems Interconnection (OSI) protocol. Such a statement is called a Protocol Implementation Conformance Statement (PICS).

The present version updates the references to the basic call specifications.

National transposition dates	
Date of adoption of this EN:	19 June 1998
Date of latest announcement of this EN (doa):	30 September 1998
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 1999
Date of withdrawal of any conflicting National Standard (dow):	31 March 1999

1 Scope

This second part of EN 300 185 is applicable to the stage three of the Conference call, add-on (CONF) supplementary service for the pan-European Integrated Services Digital Network (ISDN) as provided by European public telecommunications operators at the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [9]) by means of the Digital Subscriber Signalling System No. one (DSS1) protocol. Stage three identifies the protocol procedures and switching functions needed to support a telecommunications service (see CCITT Recommendation I.130 [8]).

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for the ISDN DSS1 CONF supplementary service protocol as specified in EN 300 185-1 [2] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [7].

The supplier of a protocol implementation which is claimed to conform to EN 300 185-1 [2] is required to complete a copy of the PICS proforma provided in annex A of the present document and is required to provide the information necessary to identify both the supplier and the implementation.

2 Normative references

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply; or
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity); or
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".
- [2] EN 300 185-1 (V1.2): "Integrated Services Digital Network (ISDN); Conference call add-on (CONF) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [3] EN 300 195-2: "Integrated Services Digital Network (ISDN); Supplementary service interactions; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [4] EN 300 196-2: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [5] EN 300 403-3: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 3: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [6] ISO/IEC 9646-1: "Information technology - Open systems interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [7] ISO/IEC 9646-7: "Information technology - Open systems interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

- [8] CCITT Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [9] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces - Reference configurations".

3 Definitions

For the purposes of the present document, the following definitions apply, in addition to those given in EN 300 185-1 [2]:

Protocol Implementation Conformance Statement (PICS): A statement made by the supplier of an Open Systems Interconnection (OSI) implementation or system, stating which capabilities have been implemented for a given OSI protocol (see ISO/IEC 9646-1 [6]).

PICS proforma: A document, in the form of a questionnaire, designed by the protocol specifier or conformance test suite specifier, which, when completed for an OSI implementation or system, becomes the PICS (see ISO/IEC 9646-1 [6]).

static conformance review: A review of the extent to which the static conformance requirements are met by the IUT, accomplished by comparing the PICS with the static conformance requirements expressed in the relevant standard(s) (see ISO/IEC 9646-1 [6]).

4 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AND	Boolean "and"
C	Conditional requirement (to be observed if the relevant conditions apply)
CONF	Conference call, add-on
DSS1	Digital Subscriber Signalling System No. one
IER	Information Elements Received
IET	Information Elements Transmitted
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
M	Mandatory requirement (to be observed in all cases)
MC	Major Capabilities
MR	Messages Received
MT	Messages Transmitted
N/A	Not applicable, not supported or the conditions for status are not met
No	not supported
NOT	Boolean "not"
O	Option (may be selected to suit the implementation, provided that any requirements applicable to the option are observed)
O.n	Options, but support required for either at least one or only one of the options in the group labelled with the same numeral "n"
OR	Boolean "or"
OSI	Open Systems Interconnection
P	Parameters
PICS	Protocol Implementation Conformance Statement
R	Roles
RL	Requirements List
SCS	System Conformance Statement
SS	Supplementary Service
SUT	System Under Test
Yes	supported

5 Conformance

A PICS proforma which conforms to this PICS proforma specification shall be technically equivalent to annex A, and shall preserve the numbering and ordering of the items in annex A.

A PICS which conforms to this PICS proforma specification shall:

- a) describe an implementation which claims to conform to EN 300 185-1 [2];
- b) be a conforming ICS proforma which has been completed in accordance with the instructions for completion given in clause A.1;
- c) include the information necessary to uniquely identify both the supplier and the implementation.

Annex A (normative): PICS proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.

A.1 Instructions for completing the PICS proforma

A.1.1 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

The SCS as defined in ISO/IEC 9646-1 [6] is a document supplied by the client or product supplier that summarizes which OSI International Standards, ITU-T (CCITT) Recommendations, ETSs or other standards are implemented and to which conformance is claimed. The PICS/SCS subclause should describe the relationship of the PICS to the SCS.

A.1.2 Global statement of conformance

If the answer to the statement in this subclause is "Yes", all subsequent subclauses should be completed to facilitate selection of test cases for optional functions.

If the answer to the statement in this subclause is "No", all subsequent subclauses should be completed, and all non-supported mandatory capabilities should be identified and explained. Explanations may be entered in the comments field at the bottom of each table or on attached sheets of paper.

A.1.3 Explanation of PICS proforma subclauses

The PICS proforma contains a Roles clause and thereafter is presented in two parts (for user and network) with the following subclauses, as required:

- major capabilities;
- subsidiary capabilities;
- protocol data unit support;
- protocol data unit parameters;
- timers;
- call states.

The User clause shall only be completed for user implementations (including private network implementations) while the Network clause shall only be completed for network implementations. The Roles subclause shall be completed for all implementations.

The relationship between this PICS proforma and other related PICS proforma (e.g. the basic call PICS proforma) is expressed in the Requirements List (RL) contained in annex B. This provides the additional restrictions placed on the related proforma (different conditions, different status, etc.).

A.1.4 Symbols, abbreviations and terms

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [7].

The reference column contained in the tables gives reference to the appropriate part(s) of EN 300 185-1 [2] describing the particular item. Note, however, that a reference merely indicates the place where the core of a description of an item can be found. Any additional information contained in EN 300 185-1 [2] has to be taken into account when making a statement about the conformance of that particular item.

The following common notations, defined in ISO/IEC 9646-7 [7], are used for the status column:

M	mandatory
O	optional
N/A	not applicable
O.<integer>	for mutually exclusive or selectable options from a set

The following common notations, defined in ISO/IEC 9646-7 [7], are used for the support column:

Y	for supported/implemented
N	for not supported/not implemented

A.2 Identification of the implementation

A.2.1 Implementation Under Test (IUT) identification

IUT name:

.....

IUT version:

.....

A.2.2 System Under Test (SUT) identification

SUT name:

.....

Hardware configuration:

.....

Operating system:

.....

A.2.3 Product supplier

Name:

.....

Address:

.....

.....

.....

Telephone number:

.....

Facsimile number:

.....

Additional information:

.....

.....

.....

A.2.4 Client

Name:

.....

Address:

.....

.....

.....

Telephone number:

.....

Facsimile number:

.....

Additional information:

.....

.....

.....

A.2.5 PICS contact person

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

Additional information:

.....
.....
.....

A.3 PICS/System Conformance Statement (SCS)

Provide the relationship of the PICS with the SCS for the system:

.....
.....
.....
.....

A.4 Identification of the protocol

This PICS proforma applies to the following standard:

EN 300 185-1 (V1.2): "Integrated Services Digital Network (ISDN); Conference call, add-on (CONF) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

A.5 Global statement of conformance

The implementation described in this PICS meets all the mandatory requirements of the referenced standard?

Yes

No

NOTE: Answering "No" to this question indicates non-conformance to the protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming. Explanations may be entered in the comments field at the bottom of each table or on attached pages.

In the tabulations which follow, all references are to EN 300 185-1 [2] unless another numbered reference is explicitly indicated.

A.6 Roles

Table A.1: Type of implementation

Item	Major role: Does the implementation...	Conditions for status	Status	Reference	Support
Type of implementation					
R 1	not used				
R 2.1	support user requirements?		O.1	9	<input type="checkbox"/> Yes <input type="checkbox"/> No
R 2.2	support network requirements?		O.1	9	<input type="checkbox"/> Yes <input type="checkbox"/> No
R 3.1	support requirements at the coincident S and T reference point?		O.2	9	<input type="checkbox"/> Yes <input type="checkbox"/> No
R 3.2	support requirements for interworking with private ISDNs at the T reference point?		O.2	10	<input type="checkbox"/> Yes <input type="checkbox"/> No
R 4.1	support user requirements at the interface of the served user?	R 2.1 AND R 3.1 R 2.1 AND R 3.2 NOT R 2.1	M O.3 N/A	9.2, 10	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
R 4.2	support user requirements at the interface of the remote user?		N/A		N/A
R 4.3	support network requirements at the interface of the served user?	R 2.2 NOT R 2.2	M N/A	9.3	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
R 4.4	support network requirements at the interface of the remote user?	R 2.2 NOT R 2.2	M N/A		<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
O.1	Support of one and only one of these options is required.				
O.2	Support of at least one of these options is required.				
O.3	See table A.2				
Comments:					

A.7 User

The tables provided in this clause need only to be completed for user implementation where item R 2.1 in table A.1 is supported.

A.7.1 Major capabilities

Table A.2: Major capabilities - user

Item	Major capability: Does the implementation support ...	Conditions for status	Status	Reference	Support
MC 1	General capabilities				
MC 1.1	CONF invocation from the idle state?	R 4.1 NOT R 4.1	M N/A	9.2.1, 10	[]Yes []No []N/A
MC 1.2	CONF invocation from an existing active call?	R 4.1 NOT R 4.1	O N/A	9.2.2, 10	[]Yes []No []N/A
MC 1.3	adding of a party?	R 4.1 NOT R 4.1	M N/A	9.2.3, 10	[]Yes []No []N/A
MC 1.4	isolation of a party?	R 4.1 NOT R 4.1	M N/A	9.2.4, 10	[]Yes []No []N/A
MC 1.5	reattachment of a party?	R 4.1 NOT R 4.1	M N/A	9.2.5, 10	[]Yes []No []N/A
MC 1.6	splitting of a party?	R 4.1 NOT R 4.1	M N/A	9.2.6, 10	[]Yes []No []N/A
MC 1.7.1	disconnection of a remote user?	R 4.1 NOT R 4.1	M N/A	9.2.7, 10	[]Yes []No []N/A
MC 1.7.2	served user procedures on disconnection by a remote user?	R 4.1 NOT R 4.1	M N/A	9.2.8, 10	[]Yes []No []N/A
MC 1.8	termination of the conference?	R 4.1 NOT R 4.1	M N/A	9.2.9, 10	[]Yes []No []N/A
MC 2	Additional procedures for private ISDNs				
MC 2.1	generation of notifications to be delivered to remote users (when the service provider is on a private ISDN)?	R 2.1 AND R 3.2 NOT (R 2.1 AND R 3.2)	O.3 N/A	10	[]Yes []No []N/A
MC 3	Additional procedures for the Hold/Retrieve functions				
MC 3.1	CONF invocation from the Call Held auxiliary state?	MC 1.2 NOT MC1.2	O N/A	9.2.2	[]Yes []No []N/A
MC 3.2	the adding of a party from the Call Held auxiliary state?	MC 1.3 NOT MC1.3	O N/A	9.2.3	[]Yes []No []N/A
MC 3.3	the adding of a party with the Conference call in the Call Held auxiliary state?	MC 1.3 NOT MC1.3	O N/A	9.2.3	[]Yes []No []N/A
O.3	Support of at least one of these options is required.				
Comments:					

A.7.2 Subsidiary capabilities

No items requiring response.

A.7.3 Protocol data units

No items requiring response.

A.7.4 Protocol data unit parameters

Table A.3: Facility information element components received - user

Item	Facility information element components: Does the implementation support...	Conditions for status	Status	Reference	Support
P 1	BeginCONF				
P 1.1	BeginCONF return result component	R 4.1 NOT R 4.1	M N/A	9.2.1, 9.2.2	[]Yes []No []N/A
P 1.2	BeginCONF return error component	R 4.1 NOT R 4.1	M N/A	9.2.1, 9.2.2	[]Yes []No []N/A
P 2	AddCONF				
P 2.1	AddCONF return result component	R 4.1 NOT R 4.1	M N/A	9.2.3	[]Yes []No []N/A
P 2.2	AddCONF return error component	R 4.1 NOT R 4.1	M N/A	9.2.3	[]Yes []No []N/A
P 3	SplitCONF				
P 3.1	SplitCONF return result component	R 4.1 NOT R 4.1	M N/A	9.2.6	[]Yes []No []N/A
P 3.2	SplitCONF return error component	R 4.1 NOT R 4.1	M N/A	9.2.6	[]Yes []No []N/A
P 4	DropCONF				
P 4.1	DropCONF return result component	R 4.1 NOT R 4.1	M N/A	9.2.7	[]Yes []No []N/A
P 4.2	DropCONF return error component	R 4.1 NOT R 4.1	M N/A	9.2.7	[]Yes []No []N/A
P 5	ReattachCONF				
P 5.1	IsolateCONF return result component	R 4.1 NOT R 4.1	M N/A	9.2.4	[]Yes []No []N/A
P 5.2	IsolateCONF return error component	R 4.1 NOT R 4.1	M N/A	9.2.4	[]Yes []No []N/A
P 6	ReattachCONF				
P 6.1	ReattachCONF return result component	R 4.1 NOT R 4.1	M N/A	9.2.5	[]Yes []No []N/A
P 6.2	ReattachCONF return error component	R 4.1 NOT R 4.1	M N/A	9.2.5	[]Yes []No []N/A
P 7	PartyDISC invoke component	R 4.1 NOT R 4.1	M N/A	9.2.8	[]Yes []No []N/A
Comments:					

Table A.4: Facility information element components transmitted - user

Item	Facility information element components: Does the implementation support...	Conditions for status	Status	Reference	Support
P 8	BeginCONF invoke component	R 4.1 NOT R 4.1	M N/A	9.2.1, 9.2.2	[]Yes []No []N/A
P 9	AddCONF invoke component	R 4.1 NOT R 4.1	M N/A	9.2.3	[]Yes []No []N/A
P 10	SplitCONF invoke component	R 4.1 NOT R 4.1	M N/A	9.2.6	[]Yes []No []N/A
P 11	DropCONF invoke component	R 4.1 NOT R 4.1	M N/A	9.2.7	[]Yes []No []N/A
P 12	IsolateCONF invoke component	R 4.1 NOT R 4.1	M N/A	9.2.4	[]Yes []No []N/A
P 13	ReattachCONF invoke component	R 4.1 NOT R 4.1	M N/A	9.2.5	[]Yes []No []N/A
Comments:					

Table A.5: Notification indicator information element codepoints transmitted - user

Item	Notification indicator information element codepoints: Does the implementation support the value...	Conditions for status	Status	Reference	Support
P 14.1	Conference established	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.2.1, 9.2.3.1, 10	[]Yes []No []N/A
P 14.2	Conference disconnected	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.6.1, 10	[]Yes []No []N/A
P 14.3	Other party added	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.3.1, 10	[]Yes []No []N/A
P 14.4	Isolated	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.4.1, 10	[]Yes []No []N/A
P 14.5	Reattached	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.5.1, 10	[]Yes []No []N/A
P 14.6	Other party isolated	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.4.1, 10	[]Yes []No []N/A
P 14.7	Other party reattached	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.5.1, 10	[]Yes []No []N/A
P 14.8	Other party split	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.6.1, 10	[]Yes []No []N/A
P 14.9	Other party disconnected	MC 2.1 NOT MC 2.1	M N/A	7, 9.2.7.1, 9.2.8.1, 10	[]Yes []No []N/A
Comments:					

A.7.5 Timers

No items requiring response.

A.7.6 Call states

No items requiring response.

A.8 Network

The tables provided in this clause need only to be completed for network implementation where item R 2.2 in table A.1 is supported.

A.8.1 Major capabilities

Table A.6: Major capabilities - network

Item	Major capability: Does the implementation support...	Conditions for status	Status	Reference	Support
MC 4	General capabilities				
MC 4.1	CONF invocation from the idle state?	R 4.3 NOT R 4.3	M N/A	9.2.1, 10	[]Yes []No []N/A
MC 4.2	CONF invocation from an existing active call?	R 4.3 NOT R 4.3	O N/A	9.2.2, 10	[]Yes []No []N/A
MC 4.3	support adding of a party?	R 4.3 NOT R 4.3	M N/A	9.2.3, 10	[]Yes []No []N/A
MC 4.4	isolation of a party?	R 4.3 NOT R 4.3	M N/A	9.2.4, 10	[]Yes []No []N/A
MC4.5	reattachment of a party?	R 4.3 NOT R 4.3	M N/A	9.2.5, 10	[]Yes []No []N/A
MC 4.6	splitting of a party?	R 4.3 NOT R 4.3	M N/A	9.2.6, 10	[]Yes []No []N/A
MC 4.7.1	disconnection of a remote user?	R 4.3 NOT R 4.3	M N/A	9.2.7, 10	[]Yes []No []N/A
MC 4.7.2	served user procedures on disconnection by a remote user?	R 4.3 NOT R 4.3	M N/A	9.2.8, 10	[]Yes []No []N/A
MC 4.8	termination of the conference?	R 4.3 NOT R 4.3	M N/A	9.2.9, 10	[]Yes []No []N/A
MC 4.9	delivery of notifications to remote users?	R 4.4 NOT R 4.4	M N/A	9.2, 10	[]Yes []No []N/A
MC 5	Additional procedures for interworking with private ISDNs				
MC 5.1	acceptance of notifications from private ISDN for delivery to remote user(s) (when the service provider is on a private ISDN)?	R 2.2 AND R 3.2 NOT (R 2.2 AND R 3.2)	M N/A	10	[]Yes []No []N/A
MC 6	Additional procedures for the Hold/Retrieve functions				
MC 6.1	CONF invocation from the Call Held auxiliary state?	MC 4.2 NOT MC 4.2	O N/A	9.2.2	[]Yes []No []N/A
MC 6.2	the adding of a party from the Call Held auxiliary state?	MC 4.3 NOT MC 4.3	O N/A	9.2.3	[]Yes []No []N/A
Comments:					

A.8.2 Subsidiary capabilities

No items requiring response.

A.8.3 Protocol data units

No items requiring response.

A.8.4 Protocol data unit parameters

Table A.7: Facility information element components received - network

Item	Facility information element components: Does the implementation support...	Conditions for status	Status	Reference	Support
P 15	BeginCONF invoke component	R 4.3 AND MC 4.1 NOT (R 4.3 AND MC 4.1)	M N/A	9.2.1, 9.2.2	[]Yes []No []N/A
P 16	AddCONF invoke component	R 4.3 AND MC 4.3 NOT (R 4.3 AND MC 4.3)	M N/A	9.2.3	[]Yes []No []N/A
P 17	SplitCONF invoke component	R 4.3 AND MC 4.6 NOT (R 4.3 AND MC 4.6)	M N/A	9.2.6	[]Yes []No []N/A
P 18	DropCONF invoke component	R 4.3 AND MC 4.7.1 NOT (R 4.3 AND MC 4.7.1)	M N/A	9.2.7	[]Yes []No []N/A
P 19	IsolateCONF invoke component	R 4.3 AND MC 4.4 NOT (R 4.3 AND MC 4.4)	M N/A	9.2.4	[]Yes []No []N/A
P 20	ReattachCONF invoke component	R 4.3 AND MC 4.5 NOT (R 4.3 AND MC 4.5)	M N/A	9.2.5	[]Yes []No []N/A
Comments:					

Table A.8: Facility information element components transmitted - network

Item	Facility information element components: Does the implementation support the interpretation of...	Conditions for status	Status	Reference	Support
P 21	BeginCONF				
P 21.1	BeginCONF return result component	R 4.3 AND MC 4.1 NOT (R 4.3 AND MC 4.1)	M N/A	9.2.1, 9.2.2	[]Yes []No []N/A
P 21.2	BeginCONF return error component	R 4.3 AND MC 4.1 NOT (R 4.3 AND MC 4.1)	M N/A	9.2.1, 9.2.2	[]Yes []No []N/A
P 22	AddCONF				
P 22.1	AddCONF return result component	R 4.3 AND MC 4.3 NOT (R 4.3 AND MC 4.3)	M N/A	9.2.3	[]Yes []No []N/A
P 22.2	AddCONF return error component	R 4.3 AND MC 4.3 NOT (R 4.3 AND MC 4.3)	M N/A	9.2.3	[]Yes []No []N/A
P 23	SplitCONF				
P 23.1	SplitCONF return result component	R 4.3 AND MC 4.6 NOT (R 4.3 AND MC 4.6)	M N/A	9.2.6	[]Yes []No []N/A
P 23.2	SplitCONF return error component	R 4.3 AND MC 4.6 NOT (R 4.3 AND MC 4.6)	M N/A	9.2.6	[]Yes []No []N/A
P 24	DropCONF				
P 24.1	DropCONF return result component	R 4.3 AND MC 1.5.1 NOT (R 4.3 AND MC 1.5.1)	M N/A	9.2.7	[]Yes []No []N/A
P 24.2	DropCONF return error component	R 4.3 AND MC 1.5.1 NOT (R 4.3 AND MC 1.5.1)	M N/A	9.2.7	[]Yes []No []N/A
P 25	IsolateCONF				
P 25.1	IsolateCONF return result component	R 4.3 AND MC 4.4 NOT (R 4.3 AND MC 4.4)	M N/A	9.2.4	[]Yes []No []N/A
P 25.2	IsolateCONF return error component	R 4.3 AND MC 4.4 NOT (R 4.3 AND MC 4.4)	M N/A	9.2.4	[]Yes []No []N/A
P 26	ReattachCONF				
P 26.1	ReattachCONF return result component	R 4.3 AND MC 4.5 NOT (R 4.3 AND MC 4.5)	M N/A	9.2.5	[]Yes []No []N/A
P 26.2	ReattachCONF return error component	R 4.3 AND MC 4.5 NOT (R 4.3 AND MC 4.5)	M N/A	9.2.5	[]Yes []No []N/A
P 27	PartyDISC invoke component	R 4.3 AND MC 4.7.2 NOT (R 4.3 AND MC 4.7.2)	M N/A	9.2.8	[]Yes []No []N/A
Comments:					

Table A.9: Notification indicator information element codepoints transmitted - network

Item	Notification indicator information element codepoints: Does the implementation support the value...	Conditions for status	Status	Reference	Support
P 28.1	Conference established	R 4.4 NOT R 4.4	M N/A	7, 9.2.2.1, 9.2.3.1, 10	[]Yes []No []N/A
P 28.2	Conference disconnected	R 4.4 NOT R 4.4	M N/A	7, 9.2.6.1, 10	[]Yes []No []N/A
P 28.3	Other party added	R 4.4 NOT R 4.4	M N/A	7, 9.2.3.1, 10	[]Yes []No []N/A
P 28.4	Isolated	R 4.4 NOT R 4.4	M N/A	7, 9.2.4.1, 10	[]Yes []No []N/A
P 28.5	Reattached	R 4.4 NOT R 4.4	M N/A	7, 9.2.5.1, 10	[]Yes []No []N/A
P 28.6	Other party isolated	R 4.4 NOT R 4.4	M N/A	7, 9.2.4.1, 10	[]Yes []No []N/A
P 28.7	Other party reattached	R 4.4 NOT R 4.4	M N/A	7, 9.2.5.1, 10	[]Yes []No []N/A
P 28.8	Other party split	R 4.4 NOT R 4.4	M N/A	7, 9.2.6.1, 10	[]Yes []No []N/A
P 28.9	Other party disconnected	R 4.4 NOT R 4.4	M N/A	7, 9.2.7.1, 9.2.8.1, 10	[]Yes []No []N/A
Comments:					

A.8.5 Timers

No items requiring response.

A.8.6 Call states

No items requiring response.

Annex B (normative): Requirements list

This annex repeats in the form of a requirements list some items of the basic call, generic functional protocol and supplementary service interactions PICS proforma required for support of EN 300 185-1 [2]. No support column is provided as the answers are to be entered in the relevant base PICS proforma.

In the tables which follow in this annex, the status of the base PICS proforma is indicated as "C" (conditional) or "O" (optional). The "C" status is used where the base PICS proforma contains a number of interdependent items which need not be repeated in the present document. "O" indicates that the item in the base PICS proforma is dependent on one or more other items, at least one of which has an optional status. The exact interdependency is fully specified in the base PICS proforma specification.

B.1 User

B.1.1 Requirements on items used in the basic call PICS

In the tabulations which follow all item numbers are as contained in EN 300 403-3 [5]. All references are to EN 300 185-1 [2] unless otherwise stated.

Table B.1: Major capabilities - user

Item	Major capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MCu 1	outgoing calls?	O	R 4.1 NOT R 4.1	M N/A	9.2

Table B.2: Messages transmitted - user

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTu 9	the inclusion of NOTIFY?	O	MC 2.1 NOT MC 2.1	M N/A	10 [1] 3.1.7

Table B.3: Information elements - user to network (transmitted by the user)

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTu9-IE19	the inclusion of the Notification indicator?	O	MC 2.1 NOT MC 2.1	M N/A	10 [1] 4.5.22

B.1.2 Requirements on items used in the generic functional protocol PICS

In the tabulations which follow all item numbers are as contained in EN 300 196-2 [4]. All references are to EN 300 185-1 [2] unless otherwise stated.

Table B.4: Major capabilities - user

Item	Major capability: Does the implementation...	Status base	SS conditions for status	SS status	Reference
MCu 2	support the functional protocol (common information element category) for the control of supplementary services?	O	R 4.1 NOT R 4.1	M N/A	7, 9
MCu 2.1	support bearer related supplementary services procedure?	O	R 4.1 NOT R 4.1	M N/A	7, 9
MCu 2.3	support point-to-point (bearer related) transport mechanism?	O	R 4.1 NOT R 4.1	M N/A	7, 9
MCu 3	support notification category procedures?	O	MC 2.1 NOT MC 2.1	M N/A	7, 9
MCu 3.1	support transport of bearer related notifications?	O	MC 2.1 NOT MC 2.1	M N/A	7, 9

Table B.5: Subsidiary capabilities - user

Item	Subsidiary capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
SCu 2.1	the use of the invocation procedure?	O	R 4.1 NOT R 4.1	M N/A	7
SCu 2.2	the use of the return result procedure?	O	R 4.1 NOT R 4.1	M N/A	7
SCu 2.3	the use of the return-error procedure?	O	R 4.1 NOT R 4.1	M N/A	7
SCu 2.4	the use of the reject procedure?	O	R 4.1 NOT R 4.1	M N/A	7
SCu 3.1	the transport of notification information in simple notification "indicators"?	O	MC 2.1 NOT MC 2.1	M N/A	9.2

Table B.6: Messages transmitted - user

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTu 1	the inclusion of FACILITY?	C	R 4.1 NOT R 4.1	M N/A	9.2

Table B.7: SETUP PDU parameters transmitted - user

Item	SETUP PDU parameters: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
IETu 21.1	Facility?	O	R 4.1 NOT R 4.1	M N/A	9.2.1

B.1.3 Requirements on items used in the supplementary service interactions PICS

In the tabulations which follow in this subclause all item numbers are as contained in EN 300 195-2 [3]. All references are to EN 300 185-1 [2] unless otherwise stated.

Table B.8: Major capabilities - user

Item	Major capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MC 1.18	the CONF supplementary service interactions with other implemented supplementary services?	O	R 2.1 NOT R 2.1	M N/A	12

B.2 Network

B.2.1 Requirements on items used in the basic call PICS

In the tabulations which follow in this subclause all item numbers are as contained in EN 300 403-3 [5]. All references are to EN 300 185-1 [2] unless otherwise stated.

Table B.9: Messages received - network

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MRn 9	the interpretation of NOTIFY?	O	MC 5.1 NOT MC 5.1	M N/A	10 [1] 3.1.7

Table B.10: Messages transmitted - network

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTn 9	the inclusion of NOTIFY?	O	R 4.4 NOT R 4.4	M N/A	9, 10 [1] 3.1.7

Table B.11: Information elements - user to network (received by the network)

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MRn9-IE19	the inclusion of the Notification indicator?	O	MC 5.1 NOT MC 5.1	M N/A	10 [1] 4.5.22

Table B.12: Information elements - network to user (transmitted by the network)

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTn9-IE19	the inclusion of the Notification indicator?	O	R 4.4 NOT R 4.4	M N/A	9, 10 [1] 4.5.22

B.2.2 Requirements on items used in the generic functional protocol PICS

In the tabulations which follow all item numbers are as contained in EN 300 196-2 [4]. All references are to EN 300 185-1 [2] unless otherwise stated.

Table B.13: Major capabilities - network

Item	Major capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MCn 2	the functional protocol (common information element category) for the control of supplementary services?	O	R 4.3 NOT R 4.3	M N/A	7
MCn 2.1	bearer related supplementary services procedure?	O	R 4.3 NOT R 4.3	M N/A	7
MCn 2.3	point-to-point (bearer related) transport mechanism?	O	R 4.3 NOT R 4.3	M N/A	7
MCn 3	notification category procedures?	O	R 4.4 NOT R 4.4	M N/A	7, 9
MCn 3.1	transport of bearer related notifications?	O	R 4.4 NOT R 4.4	M N/A	7, 9

Table B.14: Subsidiary capabilities - network

Item	Subsidiary capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
SCn 2.1	the use of the invocation procedure?	O	R 4.3 NOT R 4.3	M N/A	7
SCn 2.2	the use of the return result procedure?	O	R 4.3 NOT R 4.3	M N/A	7
SCn 2.3	the use of the return-error procedure?	O	R 4.3 NOT R 4.3	M N/A	7
SCn 2.4	the use of the reject procedure?	O	R 4.3 NOT R 4.3	M N/A	7
SCn 3.1	the transport of notification information in simple notification "indicators"?	O	R 4.4 NOT R 4.4	M N/A	9.2

Table B.15: Messages transmitted - network

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTn 1	the inclusion of FACILITY?	C	R 4.3 NOT R 4.3	M N/A	9.2.2, 9.2.4

Table B.16: CONNECT PDU parameters transmitted - network

Item	CONNECT PDU parameters: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
IETn 11.1	Facility?	O	MC 4.1 OR MC 4.6 NOT MC 4.1 OR MC 4.6	M N/A	9.2.1, 9.2.6

Table B.17: DISCONNECT PDU parameters transmitted - network

Item	DISCONNECT PDU parameters: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
IETn 13.1	Facility?	O	MC 4.3 NOT MC 4.3	M N/A	9.2.3

B.2.3 Requirements on items used in the supplementary service interactions PICS

In the tabulations which follow in this subclause all item numbers are as contained in EN 300 195-2 [3]. All references are to EN 300 185-1 [2] unless otherwise stated.

Table B.18: Major capabilities - network

Item	Major capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MC 2.18	the CONF supplementary service interactions with other implemented supplementary services?	O	R 2.2 NOT R 2.2	M N/A	12

Annex C (informative): Changes with respect to the previous ETS 300 185-2

The following changes have been done:

- conversion to EN layout;
- replacement of references to ETS 300 102 with EN 300 403;
- replacement of references to I-ETSs with EN 300 403;
- substitution of non-specific references to basic standards where the intention is to refer to the latest version.

History

Document history		
Edition 1	September 1995	Publication as ETS 300 185-2
V1.2.3	February 1998	One-step Approval Procedure OAP 9824: 1998-02-13 to 1998-06-12
V1.2.4	June 1998	Publication