

**Integrated Services Digital Network (ISDN);
Supplementary service interactions;
Digital Subscriber Signalling System No. one (DSS1) protocol;
Part 1: Protocol specification**



Reference

REN/SPAN-130220-1

Keywords

ISDN, DSS1, supplementary service, interaction

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Contents

Intellectual Property Rights	12
Foreword.....	12
1 Scope.....	13
2 References	14
3 Definitions.....	16
4 Abbreviations	17
5 Description of supplementary service interactions	19
5.1 The AOC-D and AOC-E supplementary services	20
5.2 The AOC and ECT supplementary services.....	20
5.2.1 Coding requirements	20
5.2.2 Signalling procedures at the coincident S and T reference point	21
5.2.2.1 Delivery of charging information to the transferring user.....	21
5.2.2.1.1 Normal procedures	21
5.2.2.1.2 Exceptional procedures.....	22
5.2.3 Procedures for interworking with private ISDNs.....	22
5.3 The AOC and CCBS supplementary services	22
5.3.1 Coding requirements	22
5.3.2 Signalling procedures at the coincident S and T reference point	22
5.3.2.1 Requesting an AOC supplementary service	22
5.3.2.1.1 Normal operation	22
5.3.2.1.2 Exceptional procedures.....	23
5.3.2.2 Delivery of charging information to the user	23
5.3.2.2.1 Normal operation	23
5.3.2.2.2 Exceptional procedures.....	23
5.3.3 Procedures for interworking with private ISDNs.....	23
5.3.3.1 Requesting an AOC supplementary service by the private network	23
5.3.3.1.1 Normal operation	23
5.3.3.1.2 Exceptional procedures.....	23
5.3.3.2 Delivery of charging information to the private network.....	23
5.3.3.2.1 Normal operation	23
5.3.3.2.2 Exceptional procedures.....	23
5.4 The AOC and CD supplementary services	23
5.4.1 Coding requirements	23
5.4.2 Signalling procedures at the coincident S and T reference point	24
5.4.2.1 Delivery of charging information to the deflecting user	24
5.4.2.1.1 Normal operation	24
5.4.2.1.2 Exceptional procedures.....	24
5.4.3 Procedures for interworking with private ISDNs.....	24
5.4.3.1 Delivery of charging information to the private network when the CD supplementary service is provided to the private ISDN	25
5.4.3.2 Delivery of charging information to the private network when partial rerouteing applies	25
5.4.3.2.1 Normal operation	25
5.4.3.2.2 Exceptional procedures.....	26
5.5 The AOC and CFB supplementary services.....	26
5.5.1 Coding requirements	26
5.5.2 Signalling procedures at the coincident S and T reference point	26
5.5.2.1 Delivery of charging information to the forwarding user.....	26
5.5.2.1.1 Normal operation	26
5.5.2.1.2 Exceptional procedures.....	26
5.5.3 Procedures for interworking with private ISDNs.....	26
5.5.3.1 Delivery of charging information to the private network when the CFB supplementary service is provided to the private ISDN	27
5.5.3.2 Delivery of charging information to the private network when partial rerouteing applies	27

5.6	The AOC and CFNR supplementary services	27
5.7	The AOC and CFU supplementary services	27
5.8	The AOC and 3PTY supplementary services.....	27
5.8.1	Coding requirements	27
5.8.2	Signalling procedures at the coincident S and T reference point	27
5.8.2.1	Normal operation.....	27
5.8.2.2	Exceptional procedures	27
5.8.3	Procedures for interworking with private ISDNs.....	27
5.9	The AOC and CONF supplementary services.....	28
5.9.1	Coding requirements	28
5.9.2	Signalling procedures at the coincident S and T reference point	28
5.9.2.1	Normal operation.....	28
5.9.2.2	Exceptional procedures	28
5.9.3	Procedures for interworking with private ISDNs.....	28
5.10	The AOC and TP supplementary services	28
5.10.1	Coding requirements	28
5.10.2	Signalling procedures at the coincident S and T reference point	29
5.10.2.1	In the call suspension phase	29
5.10.2.1.1	Normal operation	29
5.10.2.1.2	Exceptional procedures.....	29
5.10.2.2	In the call resume phase.....	29
5.10.2.2.1	Normal operation	29
5.10.2.2.2	Exceptional procedures.....	30
5.10.3	Procedures for interworking with private ISDNs.....	30
5.11	The CONF and HOLD supplementary services	30
5.11.1	Coding requirements	30
5.11.2	Signalling procedures at the coincident S and T reference point	31
5.11.2.1	Invocation of the HOLD supplementary service by the served user of the CONF supplementary service	31
5.11.2.1.1	Normal operation	31
5.11.2.1.2	Exceptional procedures.....	31
5.11.2.2	Invocation of the HOLD supplementary service by the remote user of the CONF supplementary service	31
5.11.2.2.1	Normal operation	31
5.11.2.2.2	Exceptional procedures.....	31
5.11.3	Procedures for interworking with private ISDNs.....	31
5.12	The CONF and CUG supplementary service	32
5.12.1	Coding requirements	32
5.12.2	Signalling procedures at the coincident S and T reference point	32
5.12.2.1	Adding a call	32
5.12.2.1.1	Normal operation	32
5.12.2.1.2	Exceptional procedures.....	32
5.12.3	Procedures for interworking with private ISDNs.....	32
5.13	The CONF and CONF supplementary services	32
5.13.1	Coding requirements	32
5.13.2	Signalling procedures at the coincident S and T reference point	32
5.13.2.1	Re-invoking the CONF supplementary service	32
5.13.2.1.1	Normal operation	32
5.13.2.1.2	Exceptional procedures.....	32
5.13.2.2	Adding a conference call to a conference.....	33
5.13.2.2.1	Normal operation	33
5.13.2.2.2	Exceptional procedures.....	33
5.13.2.3	Notification of the served user	33
5.13.2.3.1	Normal procedures	33
5.13.2.3.2	Exceptional procedures.....	33
5.13.3	Procedures for interworking with private ISDNs.....	33
5.14	The CONF and TP supplementary services	33
5.14.1	Coding requirements	33
5.14.2	Signalling procedures at the coincident S and T reference point	33
5.14.2.1	Served user of CONF supplementary service uses TP supplementary service	33
5.14.2.1.1	Normal operation	33
5.14.2.1.2	Exceptional procedures.....	34

5.14.2.2	Remote user of CONF supplementary service uses TP supplementary service.....	34
5.14.2.2.1	Normal operation	34
5.14.2.2.2	Exceptional procedures.....	34
5.14.2.3	Remote user of the TP supplementary service uses the CONF supplementary service.....	34
5.14.2.3.1	Normal operation	34
5.14.2.3.2	Exceptional procedures.....	34
5.15	The CONF and 3PTY supplementary services.....	34
5.15.1	Coding requirements	34
5.15.2	Signalling procedures at the coincident S and T reference point	35
5.15.2.1	Requesting a three-way conversation where one of the connections belongs to a conference call.....	35
5.15.2.1.1	Normal operation	35
5.15.2.1.2	Exceptional procedures.....	35
5.15.2.2	Adding a three-way conversation to a conference	35
5.15.2.2.1	Normal operation	35
5.15.2.2.2	Exceptional procedures.....	35
5.15.2.3	Invocation of the CONF supplementary service for a connection in a three-way conversation	35
5.15.2.3.1	Normal operation	35
5.15.2.3.2	Exceptional procedures.....	35
5.15.2.4	Remote user uses the 3PTY supplementary service.....	36
5.15.2.4.1	Normal operation	36
5.15.2.4.2	Exceptional procedures.....	36
5.15.3	Procedures for interworking with private ISDNs.....	36
5.16	The CONF and UUS service 3 supplementary services	36
5.16.1	Coding requirements	36
5.16.2	Signalling procedures at the coincident S and T reference point	36
5.16.2.1	Service 3 activation	36
5.16.2.1.1	Normal operation	36
5.16.2.1.2	Exceptional procedures.....	36
5.16.2.2	Transfer of user information.....	37
5.16.2.2.1	Normal operation	37
5.16.2.2.2	Exceptional procedures.....	37
5.16.2.3	Flow control	37
5.16.2.3.1	Normal operation	37
5.16.2.3.2	Exceptional procedures.....	37
5.16.3	Procedures for interworking with private ISDNs.....	37
5.17	The CONF and ECT supplementary services	38
5.17.1	Coding requirements	38
5.17.2	Signalling procedures at the coincident S and T reference point	38
5.17.2.1	Served user uses the ECT supplementary service.....	38
5.17.2.1.1	Normal operation	38
5.17.2.1.2	Exceptional procedures.....	38
5.17.2.2	Remote user uses the ECT supplementary service	38
5.17.2.2.1	Normal operation	38
5.17.2.2.2	Exceptional procedures.....	39
5.17.3	Procedures for interworking with private ISDNs.....	39
5.18	The CD and COLP supplementary services.....	39
5.18.1	Coding requirements	39
5.18.2	Signalling procedures at the coincident S and T reference point	39
5.18.2.1	Normal operation.....	39
5.18.2.2	Exceptional procedures.....	39
5.18.3	Procedures for interworking with private ISDNs.....	39
5.19	The CD and COLR supplementary services	39
5.20	The CD and UUS supplementary services	40
5.20.1	Coding requirements	40
5.20.2	Signalling procedures at the coincident S and T reference point	40
5.20.2.1	Procedures at the served user when deflection takes place before alerting	40
5.20.2.1.1	Normal operation	40
5.20.2.1.2	Exceptional procedures.....	40
5.20.2.2	Procedures at the served user when deflection takes place after alerting	40
5.20.2.2.1	Service 1 implicitly requested.....	40
5.20.2.2.1.1	Normal operation	40
5.20.2.2.1.2	Exceptional procedures	41

5.20.2.2.2	Service 1 explicitly requested	41
5.20.2.2.2.1	Normal operation	41
5.20.2.2.2.2	Exceptional procedure.....	41
5.20.2.2.3	Service 2	42
5.20.2.2.3.1	Normal operation	42
5.20.2.2.3.2	Exceptional procedures	42
5.20.2.2.4	Service 3	42
5.20.2.2.4.1	Normal operation	42
5.20.2.2.4.2	Exceptional procedures	42
5.20.3	Procedures for interworking with private ISDNs.....	42
5.20.3.1	Procedures where the CD supplementary service applies to the whole private ISDN	42
5.20.3.2	Procedures where partial rerouteing takes place.....	43
5.21	The CFB and COLP supplementary services.....	43
5.22	The CFB and COLR supplementary services	43
5.23	The CFB and UUS supplementary services	43
5.23.1	Coding requirements	43
5.23.2	Signalling procedures at the coincident S and T reference point	43
5.23.2.1	Normal operation.....	44
5.23.2.2	Exceptional procedures	44
5.23.3	Procedures for interworking with private ISDNs.....	44
5.23.3.1	Procedures where the CFB supplementary service applies to the whole private ISDN	44
5.23.3.2	Procedures where partial rerouteing takes place.....	44
5.23.3.2.1	Normal operation	44
5.23.3.2.2	Exceptional procedures.....	45
5.24	The CFNR and COLP supplementary services	45
5.25	The CFNR and COLR supplementary services.....	45
5.26	The CFNR and UUS supplementary services	45
5.26.1	Coding requirements	45
5.26.2	Signalling procedures at the coincident S and T reference point	46
5.26.2.1	Service 1 implicitly requested	46
5.26.2.1.1	Normal operation	46
5.26.2.1.2	Exceptional procedures.....	46
5.26.2.2	Service 1 explicitly requested.....	46
5.26.2.2.1	Normal operation	46
5.26.2.2.2	Exceptional procedures.....	47
5.26.2.3	Service 2	47
5.26.2.3.1	Normal operation	47
5.26.2.3.2	Exceptional procedures.....	47
5.26.2.4	Service 3	47
5.26.2.4.1	Normal operation	47
5.26.2.4.2	Exceptional procedures.....	48
5.26.3	Procedures for interworking with private ISDNs.....	48
5.26.3.1	Procedures where the CFNR supplementary services applies to the whole private ISDN	48
5.26.3.2	Procedures where partial rerouteing takes place.....	48
5.27	The CFU and COLP supplementary services.....	48
5.28	The CFU and COLR supplementary services	48
5.29	The CFU and UUS supplementary services.....	48
5.29.1	Coding requirements	48
5.29.2	Signalling procedures at the coincident S and T reference point	48
5.29.2.1	Normal operation.....	48
5.29.2.2	Exceptional procedures	49
5.29.3	Procedures for interworking with private ISDNs.....	49
5.29.3.1	Procedures where the CFU supplementary service applies to the whole private ISDN	49
5.29.3.2	Procedures where partial rerouteing takes place.....	49
5.30	The TP and 3PTY supplementary services	49
5.30.1	Coding requirements	49
5.30.2	Signalling procedures at the coincident S and T reference point	49
5.30.2.1	Served user uses the TP supplementary service	49
5.30.2.1.1	Normal operation	49
5.30.2.1.2	Exceptional procedures.....	49
5.30.2.2	Remote user of the TP supplementary service uses the 3PTY supplementary service.....	50
5.30.2.2.1	Normal operation	50

5.30.2.2.2	Exceptional procedures.....	50
5.30.3	Procedures for interworking with private ISDNs.....	50
5.31	The HOLD and TP supplementary services.....	50
5.31.1	Coding requirements.....	50
5.31.2	Signalling procedures at the coincident S and T reference point	50
5.31.2.1	Served user of the HOLD supplementary service uses the TP supplementary service	50
5.31.2.1.1	Normal operation	50
5.31.2.1.2	Exceptional procedures.....	50
5.31.2.2	Remote user of the HOLD supplementary service uses the TP supplementary service	50
5.31.2.3	Remote user of the TP supplementary service uses the HOLD supplementary service	50
5.31.2.3.1	Normal operation	50
5.31.2.3.2	Exceptional procedures.....	51
5.31.3	Procedures for interworking with private ISDNs.....	51
5.32	The HOLD and 3PTY supplementary services	51
5.32.1	Coding requirements.....	51
5.32.2	Signalling procedures at the coincident S and T reference point	51
5.32.2.1	Creating a three-way conversation from a held call.....	51
5.32.2.2	Holding a three-way conversation	51
5.32.2.3	Retrieving a three-way conversation.....	51
5.32.3	Procedures for interworking with private ISDNs.....	51
5.33	The CUG and 3PTY supplementary services.....	52
5.33.1	Coding requirements	52
5.33.2	Signalling procedures at the coincident S and T reference point	52
5.33.2.1	Creating a three-way conversation	52
5.33.2.1.1	Normal operation	52
5.33.2.1.2	Exceptional procedures.....	52
5.33.3	Procedures for interworking with private ISDNs.....	52
5.34	The ECT and MCID supplementary services.....	52
5.34.1	Coding requirements	52
5.34.2	Signalling procedures at the coincident S and T reference point	52
5.34.2.1	Normal operation.....	52
5.34.2.2	Exceptional procedures.....	52
5.35	The ECT and 3PTY supplementary services	52
5.35.1	Coding requirements	52
5.35.2	Signalling procedures at the coincident S and T reference point	53
5.35.2.1	Transfer of a three-way conversation.....	53
5.35.2.1.1	Normal operation	53
5.35.2.1.2	Exceptional procedures.....	53
5.35.3	Procedures for interworking with private ISDNs.....	53
5.36	The ECT and UUS supplementary services	53
5.37	The CCBS and UUS supplementary services	53
5.37.1	Coding requirements	53
5.37.2	Signalling procedures at the coincident S and T reference point	54
5.37.2.1	Normal operation.....	54
5.37.2.2	Exceptional procedures.....	54
5.37.3	Procedures for interworking with private ISDNs.....	54
5.38	The CCBS and CLIP supplementary services.....	54
5.38.1	Coding requirements	54
5.38.2	Signalling procedures at the coincident S and T reference point	54
5.38.2.1	Normal operation.....	54
5.38.2.2	Exceptional procedures.....	54
5.38.3	Procedures for interworking with private ISDNs.....	54
5.38.3.1	Procedures for the originating T reference point	54
5.38.3.1.1	Normal operation	54
5.38.3.1.2	Exceptional procedures.....	54
5.38.3.2	Procedures for the destination T reference point	55
5.38.3.2.1	Normal operation	55
5.38.3.2.2	Exceptional procedures.....	55
5.39	The CCBS and CLIR supplementary services	55
5.39.1	Coding requirements	55
5.39.2	Signalling procedures at the coincident S and T reference point	55
5.39.2.1	Normal operation.....	55

5.39.2.2	Exceptional procedures	55
5.39.3	Procedures for interworking with private ISDNs.....	55
5.39.3.1	Procedures for the originating T reference point	55
5.39.3.1.1	Normal operation	55
5.39.3.1.2	Exceptional procedures.....	56
5.39.3.2	Procedures for the destination T reference point	56
5.39.3.2.1	Normal operation	56
5.39.3.2.2	Exceptional procedures.....	56
5.40	The CCBS and CUG supplementary services	56
5.40.1	Coding requirements	56
5.40.2	Signalling procedures at the coincident S and T reference point	56
5.40.2.1	Normal operation.....	56
5.40.2.2	Exceptional procedures.....	56
5.40.3	Procedures for interworking with private ISDNs.....	57
5.40.3.1	Procedure for the originating T reference point.....	57
5.40.3.1.1	Normal operation	57
5.40.3.1.2	Exceptional procedures.....	57
5.40.3.2	Procedures for the destination T reference point	57
5.41	The CCBS and MSN supplementary services	57
5.41.1	Coding requirements	57
5.41.2	Signalling procedures at the coincident S and T reference point	57
5.41.2.1	Procedures for the originating network.....	57
5.41.2.1.1	Normal operation	57
5.41.2.1.2	Exceptional procedures.....	58
5.41.2.2	Procedures for the remote network	58
5.41.2.2.1	Normal operation	58
5.41.2.2.2	Exceptional procedures.....	58
5.41.3	Procedures for interworking with private ISDNs.....	58
5.42	The CCBS and SUB supplementary services.....	58
5.42.1	Coding requirements	58
5.42.2	Signalling procedures at the coincident S and T reference point	58
5.42.2.1	Normal operation.....	58
5.42.2.2	Exceptional procedures.....	58
5.42.3	Procedures for interworking with private ISDNs.....	58
5.43	The FPH and COLP supplementary services	58
5.43.1	Coding requirements	58
5.43.2	Signalling procedures at the coincident S and T reference point	59
5.43.2.1	Procedure at the called user's network	59
5.43.2.1.1	Normal operation	59
5.43.2.1.2	Exceptional procedures.....	59
5.43.3	Procedures for interworking with private ISDNs.....	59
5.44	The ECT and CUG supplementary services.....	59
5.44.1	Coding requirements	59
5.44.2	Signalling procedures at the coincident S and T reference point	59
5.44.2.1	Invocation of the ECT supplementary service.....	59
5.44.2.1.1	Normal operation	59
5.44.2.1.2	Exceptional procedures.....	59
5.44.3	Procedures for interworking with private ISDNs.....	59
5.45	The ECT and TP supplementary services	60
5.45.1	Coding requirements	60
5.45.2	Signalling procedures at the coincident S and T reference point	60
5.45.2.1	Remote user of the TP supplementary service uses the ECT supplementary service.....	60
5.45.2.1.1	Normal operation	60
5.45.2.1.2	Exceptional procedures.....	60
5.45.3	Procedures for interworking with private ISDNs.....	60
5.46	The CONF and MCID supplementary services.....	60
5.46.1	Coding requirements	60
5.46.2	Signalling procedures at the coincident S and T reference point	60
5.46.2.1	Normal operation.....	60
5.46.2.2	Exceptional procedures.....	60
5.46.3	Procedures for interworking with private ISDNs.....	60
5.47	The CCBS and CW supplementary services	61

5.47.1	Coding requirements	61
5.47.2	Signalling procedures at the coincident S and T reference point	61
5.47.2.1	Normal operation.....	61
5.47.2.2	Exceptional procedures.....	61
5.47.3	Procedures for interworking with private ISDNs.....	61
5.48	The UUS and TP supplementary services.....	61
5.48.1	Coding requirements	61
5.48.2	Signalling procedures at the coincident S and T reference point	61
5.48.2.1	Normal operation.....	61
5.48.2.2	Exceptional procedures.....	61
5.48.3	Procedures for interworking with private ISDNs.....	61
5.49	The MWI and MSN supplementary services	62
5.49.1	Coding requirements	62
5.49.2	Signalling procedures at the coincident S and T reference point	62
5.49.2.1	Normal operation.....	62
5.49.2.2	Exceptional procedures.....	62
5.49.3	Procedures for interworking with private ISDNs.....	62
5.50	The OCB and CCBS supplementary services	62
5.50.1	Coding requirements	62
5.50.2	Procedures at the coincident S and T reference point.....	62
5.50.2.1	Normal operation.....	62
5.50.2.2	Exceptional procedures.....	62
5.50.3	Procedures for interworking with privateISDNs.....	63
5.50.3.1	Normal operation.....	63
5.50.3.2	Exceptional procedures.....	63
5.51	The OCB and MSN supplementary services.....	63
5.51.1	Coding requirements	63
5.51.2	Procedures at the coincident S and T reference point.....	63
5.51.2.1	Normal operation.....	63
5.51.2.2	Exceptional procedures.....	63
5.51.3	Procedures for interworking with privateISDNs.....	63
5.52	The OCB and CFB supplementary services.....	63
5.52.1	Coding requirements	63
5.52.2	Procedures at the coincident S and T reference point.....	63
5.52.2.1	Normal operation.....	63
5.52.2.2	Exceptional procedures.....	64
5.52.3	Procedures for interworking with privateISDNs.....	64
5.52.3.1	Procedures when the CFB supplementary service applies to the whole private ISDN	64
5.52.3.2	Procedures where partial rerouting takes place.....	64
5.53	The OCB and CFNR supplementary services	64
5.54	The OCB and CFU supplementary services.....	64
5.55	Call deflection.....	64
5.55.1	Coding requirements	64
5.55.2	Procedures at the coincident S and T reference point.....	64
5.55.2.1	Normal operation.....	64
5.55.2.2	Exceptional procedures.....	64
5.55.3	Procedures for interworking with privateISDNs.....	65
5.55.3.1	Procedures when the CD supplementary service applies to the whole private ISDN	65
5.55.3.2	Procedures where partial rerouting takes place.....	65
5.56	The OCB-UC and the OCB-F supplementary services.....	65
5.57	The CCNR and AOC supplementary services	65
5.58	The CCNR and CW supplementary services	65
5.59	The CCNR and CLIP supplementary services	65
5.59.1	Coding requirements	65
5.59.2	Signalling procedures at the coincident S and T reference point	65
5.59.3	Procedures for interworking with private ISDNs.....	65
5.59.3.1	Procedures for the originating T reference point	65
5.59.3.1.1	Normal operation	65
5.59.3.1.2	Exceptional procedures.....	65
5.59.3.2	Procedures for the destination T reference point	66
5.59.3.2.1	Normal operation	66
5.59.3.2.2	Exceptional procedures.....	66

5.60	The CCNR and CLIR supplementary services.....	66
5.60.1	Coding requirements	66
5.60.2	Signalling procedures at the coincident S and T reference point	66
5.60.3	Procedures for interworking with private ISDNs.....	66
5.60.3.1	Procedures for the originating T reference point	66
5.60.3.1.1	Normal operation	66
5.60.3.1.2	Exceptional procedures.....	66
5.60.3.2	Procedures for the destination T reference point	67
5.60.3.2.1	Normal operation	67
5.60.3.2.2	Exceptional procedures.....	67
5.61	The CCNR and CUG supplementary services	67
5.62	The CCNR and CCBS supplementary services.....	67
5.62.1	Coding requirements	67
5.62.2	Signalling procedures at the coincident S and T reference point	67
5.62.2.1	Normal operation.....	67
5.62.2.2	Exceptional procedures.....	67
5.62.3	Procedures for interworking with private ISDNs.....	68
5.62.3.1	Normal operation.....	68
5.62.3.2	Exceptional procedures.....	68
5.63	The CCNR and MSN supplementary services	68
5.63.1	Coding requirements	68
5.63.2	Signalling procedures at the coincident S and T reference point	68
5.63.2.1	Normal operation.....	68
5.63.2.2	Exceptional procedures.....	69
5.63.3	Procedures for the remote network	69
5.63.3.1	Normal operation.....	69
5.63.3.2	Exceptional procedures.....	69
5.63.4	Procedures for interworking with private ISDNs.....	69
5.64	The CCNR and SUB supplementary services	69
5.65	The CCNR and UUS supplementary services.....	69
5.66	The CCNR and OCB supplementary services.....	69
5.67	The OCB and SCF supplementary services	69
5.67.1	Coding requirements	69
5.67.2	Procedures at the coincident S and T reference point.....	69
5.67.2.1	Normal operation.....	69
5.67.2.2	Exceptional procedures.....	70
5.67.3	Procedures for interworking with private networks	70
5.68	The LH and the CCBS supplementary services	70
5.68.1	Coding requirements	70
5.68.2	Procedures at the coincident S and T reference point.....	70
5.68.2.1	Normal operation.....	70
5.68.2.2	Exceptional procedures.....	70
5.68.3	Procedures for interworking with private networks	70
5.69	The LH and the CCNR supplementary services.....	70
5.69.1	Coding requirements	70
5.69.2	Procedures at the coincident S and T reference point.....	70
5.69.2.1	Normal operation.....	70
5.69.2.2	Exceptional procedures.....	71
5.69.3	Procedures for interworking with private networks	71
5.70	The LH and the CFU supplementary services.....	71
5.70.1	Coding requirements	71
5.70.2	Procedures at the coincident S and T reference point.....	71
5.70.2.1	Normal operation.....	71
5.70.2.2	Exceptional procedures.....	71
5.70.3	Procedures for interworking with private networks	71
5.71	The LH and the CFB supplementary services	71
5.71.1	Coding requirements	71
5.71.2	Procedures at the coincident S and T reference point.....	71
5.71.2.1	Normal operation.....	71
5.71.2.2	Exceptional procedures.....	72
5.71.3	Procedures for interworking with private networks	72
5.72	The LH and the CFNR supplementary services	72

5.72.1	Coding requirements	72
5.72.2	Procedures at the coincident S and T reference point.....	72
5.72.2.1	Normal operation.....	72
5.72.2.2	Exceptional procedures	72
5.72.3	Procedures for interworking with private networks	72
5.73	The LH and the SCF supplementary services	72
5.73.1	Coding requirements	72
5.73.2	Procedures at the coincident S and T reference point.....	72
5.73.2.1	Normal operation.....	72
5.73.2.2	Exceptional procedures	73
5.73.3	Procedures for interworking with private networks	73
5.74	The LH and TP supplementary services	73
5.74.1	Coding requirements	73
5.74.2	Procedures at the coincident S and T reference point.....	73
5.74.2.1	Normal operation.....	73
5.74.2.2	Exceptional procedures	73
5.74.3	Procedures for interworking with private networks	73
5.75	The RC and the other supplementary services	73
6	General procedures	74
6.1	Identification of charge.....	74
6.1.1	Normal operation	74
6.1.2	Exceptional procedures	74
6.2	Ordering of checks	74
Annex A (informative):	Signalling flows	75
Annex B (informative):	Example of the interaction between the AOC-E and CONF supplementary services	78
Annex C (informative):	Changes of this edition with respect to edition 1 of ETS 300 195-1.....	80
History		81

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 1 of a multi-part deliverable covering the Integrated Services Digital Network (ISDN); Supplementary service interactions; Digital Subscriber Signalling System No. one (DSS1) protocol, as identified below:

Part 1: "Protocol specification";

Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";

Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";

Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";

Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

The present document is an extended and updated version of ETS 300 195-1 (1995) to cover the additional supplementary services Message Waiting Indication (MWI), Outgoing Call Barring (OCB), Completion of Calls on No Reply (CCNR) and Selective Call Forwarding (SCF).

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document specifies the stage three of the supplementary service interactions for the pan-European Integrated Services Digital Network (ISDN) as provided by European public telecommunications operators at the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [32]) by means of the Digital Subscriber Signalling System No. one (DSS1) protocol. Stage three identifies the protocol procedures and switching functions needed to support a telecommunication service (see ITU-T Recommendation I.130 [29]).

The present document specifies the interactions between the Advice of Charge (AOC), Completion of Calls to Busy Subscriber (CCBS), Completion of Calls on No Reply (CCNR), Call Deflection (CD), Call Forwarding Busy (CFB), Call Forwarding No Reply (CFNR), Call Forwarding Unconditional (CFU), Calling Line Identification Presentation (CLIP), Calling Line Identification Restriction (CLIR), Connected Line Identification Presentation (COLP), Connected Line Identification Restriction (COLR), Conference call, add-on (CONF), Explicit Call Transfer (ECT), Closed User Group (CUG), Call Waiting (CW), Direct Dialling In (DDI), Freephone (FPH), Call Hold (HOLD), Line Hunting, Malicious Call Identification (MCID), Multiple Subscriber Number (MSN), Message Waiting Indication (MWI), Outgoing Call Barring (OCB), Remote Control, Selective Call Forwarding (SCF), Sub-addressing (SUB), Terminal Portability (TP), User-to-User Signalling (UUS) and Three-Party (3PTY) supplementary services.

In addition, the present document specifies the protocol requirements at the T reference point where the supplementary services are provided to the user via a private ISDN.

The present document does not specify the additional protocol requirements where the supplementary services are provided to the user via a telecommunications network that is not an ISDN.

The protocol for individual supplementary services is specified in other ENs:

AOC	EN 300 182-1 [13];
CCBS	EN 300 359-1 [20];
CCNR	EN 301 065-1 [26];
CLIP	EN 300 092-1 [6];
CLIR	EN 300 093-1 [7];
COLP	EN 300 097-1 [8];
COLR	EN 300 098-1 [9];
CONF	EN 300 185-1 [14];
ECT	EN 300 369-1 [21];
CUG	EN 300 138-1 [11];
CW	EN 300 058-1 [3];
DDI	EN 300 064-1 [5];
FPH	EN 300 210-1 [18];
HOLD	EN 300 141-1 [12];
LH	EN 301 484-1 [36];
MCID	EN 300 130-1 [10];
MSN	EN 300 052-1 [1];
MWI	EN 300 745-1 [24];
OCB	EN 301 001-1 [25];
RC	EN 301 799-1 [35];
SUB	EN 300 061-1 [4];
TP	EN 300 055-1 [2];
UUS	EN 300 286-1 [19];
3PTY	EN 300 188-1 [15].

When two or more supplementary services are implemented, the protocol interactions are defined in the present document. These interactions are applicable to the telecommunication services as specified for the individual supplementary services.

The present document is applicable to equipment supporting supplementary services, to be attached at either side of the T reference point or coincident S and T reference point when used as an access to the public ISDN.

Further parts of the present document specify the method of testing required to identify conformance to the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] ETSI EN 300 052-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Multiple Subscriber Number (MSN) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [2] ETSI EN 300 055-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Terminal Portability (TP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [3] ETSI EN 300 058-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Call Waiting (CW) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [4] ETSI EN 300 061-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Subaddressing (SUB) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [5] ETSI EN 300 064-1 (V1.3.4): "Integrated Services Digital Network (ISDN); Direct Dialling In (DDI) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [6] ETSI EN 300 092-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Calling Line Identification Presentation (CLIP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [7] ETSI EN 300 093-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Calling Line Identification Restriction (CLIR) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [8] ETSI EN 300 097-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Connected Line Identification Presentation (COLP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification". including amendment A1 (1994)
- [9] ETSI EN 300 098-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Connected Line Identification Restriction (COLR) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [10] ETSI EN 300 130-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Malicious Call Identification (MCID) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [11] ETSI EN 300 138-1 (V1.3.4): "Integrated Services Digital Network (ISDN); Closed User Group (CUG) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [12] ETSI EN 300 141-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Call Hold (HOLD) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [13] ETSI EN 300 182-1 (V1.3.6): "Integrated Services Digital Network (ISDN); Advice of Charge (AOC) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

- [14] ETSI EN 300 185-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Conference call, add-on (CONF) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [15] ETSI EN 300 188-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Three-Party (3PTY) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [16] ETSI EN 300 196-1 (V1.3.1): "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [17] ETSI EN 300 207-1 (V2.0.1): "Integrated Services Digital Network (ISDN); Diversion supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [18] ETSI EN 300 210-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Freephone (FPH) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [19] ETSI EN 300 286-1 (V1.2.4): "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [20] ETSI EN 300 359-1 (V1.3.2): "Integrated Services Digital Network (ISDN); Completion of Calls to Busy Subscriber (CCBS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [21] ETSI EN 300 369-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [22] ETSI ETS 300 402-1 (1995): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Data link layer; Part 1: General aspects [ITU-T Recommendation Q.920 (1993), modified]".
- [23] ETSI EN 300 403-1 (V1.3.2): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".
- [24] ETSI EN 300 745-1 (V1.2.4): "Integrated Services Digital Network (ISDN); Message Waiting Indication (MWI) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [25] ETSI EN 301 001-1 (V1.2.2): "Integrated Services Digital Network (ISDN); Outgoing Call Barring (OCB) supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [26] ETSI EN 301 065-1 (V1.2.2): "Integrated Services Digital Network (ISDN); Completion of Calls on No Reply (CCNR) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [27] ITU-T Recommendation E.164 (1997): "The international public telecommunications numbering plan".
- [28] ITU-T Recommendation I.112 (1993): "Vocabulary of terms for ISDNs".
- [29] ITU-T Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [30] ITU-T Recommendation I.210 (1993): "Principles of telecommunication services supported by an ISDN and the means to describe them".
- [31] ITU-T Recommendation I.221 (1993): "Common specific characteristics of services".
- [32] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces - Reference configurations".

- [33] ITU-T Recommendation X.208 (1988): "Specification of Abstract Syntax Notation One (ASN.1)".
- [34] ITU-T Recommendation X.219 (1988): "Remote operations: Model, notation and service definition".
- [35] ETSI EN 301 799-1(V1.1.1): "Integrated Services Digital Network (ISDN) ; Remote Control (RC) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Functional protocol specification".
- [36] ETSI EN 301 484-1(V1.1.1): "Integrated Services Digital Network (ISDN); Line Hunting (LH) supplementary service; Digital Subscriber Signalling System No. one (DSS1); Part 1: Protocol specification".
- [37] ITU-T Recommendation X.680: "Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation".
- [38] ITU-T Recommendation X.690: "Information technology - ASN.1 encoding rules - Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)".

3 Definitions

For the purposes of the present document, the following terms and definitions apply.

auxiliary state: may exist for a call reference in parallel with the call state. Refer to EN 300 196-1 [16], clause 7.1.2.

call control message: message as defined in clause 3.1 of ITU-T Recommendation Q.931 modified by EN 300 403-1 [23], which on sending or receipt causes a change of the call state at either the network or the user. Call control messages also include the INFORMATION and PROGRESS message.

call state: state as defined in clause 3.1 of ITU-T Recommendation Q.931 as modified by EN 300 403-1 [23], for either the user or the network, as appropriate. A call state may exist for each call reference (and for each additional responding CEI in the incoming call states).

calling user: user that initiated a call that has been diverted using the call forwarding or call deflection supplementary services

CCBS call: call which is established under control of the CCBS supplementary service

channels busy: ITU-T Recommendation I.221 [31]

Connection Endpoint Identifier (CEI): see clause 3.4.1 of ITU-T Recommendation Q.920 modified by ETS 300 402-1 [22]

deflected-to user: user to which a call shall be deflected using the CD supplementary service

diverted-to network: network to which the forwarded-to or diverted-to user is attached

forwarded-to user: user to which a call shall be forwarded using one of the call forwarding supplementary services

Integrated Services Digital Network (ISDN): see ITU-T Recommendation I.112 [28] definition 308

invoke component: see EN 300 196-1 [16], clause 8.2.2.1. Where reference is made to a "xxxx" invoke component, an invoke component is meant with its operation value set to the value of operation "xxxx".

ISDN number: number conforming to the numbering plan and structure specified in ITU-T Recommendation E.164 [27]

local interaction: interaction of the protocol for two or more supplementary services where the served user (of all supplementary services) is on the same access

local interaction for the access: calls for which the local interaction exists are at the same access

local interaction for the call: exists on a single call, i.e. both supplementary services are invoked for the same call

local interaction for the CEI: calls for which the local interaction exists are at the same access, and are identified by the same CEI

multiple subscriber number: ISDN number which is part of a set of ISDN numbers assigned to a user

network: DSS1 protocol entity at the network side of the user-network interface

network determined user busy: see ITU-T Recommendation I.221 [31]

No Impact (NI): interaction between the two identified supplementary services contains no requirements for the protocol over and above the requirements of the specification for each individual supplementary service

NOTE: Other aspects of interactions that do not affect the DSS1 protocol are covered in the service description for the relevant supplementary services.

Not Applicable (NA): interaction between the two identified supplementary services is outside the scope of the present document, e.g. the interaction is between the supplementary service and itself, and is therefore covered in the specification for the individual supplementary service.

private network: DSS1 protocol entity at the user side of the user-network interface when a T reference point applies

reject component: see EN 300 196-1 [16], clause 8.2.2.4

remote interaction: interaction of the protocol for two or more supplementary services where one user is the served user for one supplementary service and (for the same call) the remote user for another supplementary service. The interaction for the served user's supplementary service exists at the remote user.

remote user: DSS1 protocol entity at the user side of the user-network interface which is involved in an instance of an identified supplementary service, but which has no control of it

return error component: see EN 300 196-1 [16], clause 8.2.2.3. Where reference is made to a "xxxx" return error component, a return error component is meant which is related to a "xxxx" invoke component.

return result component: see EN 300 196-1 [16], clause 8.2.2.2. Where reference is made to a "xxxx" return result component, a return result component is meant which is related to a "xxxx" invoke component.

served user: DSS1 protocol entity at the user side of the user-network interface used to request and control an identified supplementary service

service; telecommunication service: see ITU-T Recommendation I.112 [28], definition 201

supplementary service: see ITU-T Recommendation I.210 [30], clause 2.4

user: DSS1 protocol entity at the user side of the user-network interface when a coincident S and T reference point applies

4 Abbreviations

For the purposes of the present document, the following abbreviations apply:

3PTY	Three-Party
AOC	Advice of Charge
AOC-E	Advice of Charge at the End of the call
AOC-D	Advice of Charge During the call
AOC-S	Advice of Charge at call Set-up time
ASN.1	Abstract Syntax Notation one
CCBS	Completion of Calls to Busy Subscriber
CCNR	Completion of Calls on No Reply
CD	Call Deflection
CEI	Connection Endpoint Identifier
CFB	Call Forwarding Busy
CFNR	Call Forwarding on No Reply
CFU	Call Forwarding Unconditional
CLIP	Calling Line Identification Presentation

CLIR	Calling Line Identification Restriction
COLP	Connected Line Identification Presentation
COLR	Connected Line Identification Restriction
CONF	Conference call, add-on
CUG	Closed User Group
CW	Call Waiting
DCR	Dummy Call Reference
DDI	Direct Dialling In
DSS1	Digital Subscriber Signalling System No. one
ECT	Explicit Call Transfer
FPH	Freephone
GAT	General Addressing and Transport protocol
GFP	Generic Functional Protocol
HOLD	Call Hold
LH	Line Hunting
ISDN	Integrated Services Digital Network
MCID	Malicious Call Identification
MSN	Multiple Subscriber Number
MWI	Message Waiting Indication
NA	Not Applicable
NI	No Impact
OCB	Outgoing Call Barring
OCB-F	Outgoing Call Barring: Fixed
OCB-UC	Outgoing Call Barring: User Controlled
RC	Remote Control
SCF	Selective Call Forwarding
SUB	Sub-addressing
TP	Terminal Portability
UUI	User-to-User Information
UUS	User-to-User Signalling

5 Description of supplementary service interactions

Figure 1 gives an overview of the interactions between pairs of supplementary services. Only if the interaction is other than "Not Applicable (NA)" or "No Impact (NI)", a reference is given to a clause in the present document which details this particular interaction.

AOC-S	NA																
AOC-D	NI	NA															
AOC-E	NI	5.1	NA														
CCBS	5.3	5.3	5.3	NA													
CD	5.4	5.4	5.4	NI	NA												
CFB	5.5	5.5	5.5	NI	NA	NA											
CFNR	5.6	5.6	5.6	NI	NA	NA	NA										
CFU	5.7	5.7	5.7	NI	NA	NA	NA	NA									
CLIP	NI	NI	NI	5.38	NI	NI	NI	NI	NA								
CLIR	NI	NI	NI	5.39	NI	NI	NI	NI	NI	NA							
COLP	NI	NI	NI	NI	5.18	5.21	5.24	5.27	NI	NI	NA						
COLR	NI	NI	NI	NI	5.19	5.22	5.25	5.28	NI	NI	NI	NA					
CONF	5.9	5.9	5.9	NI	NI	NI	NI	NI	NI	NI	NI	NI	5.13				
ECT	5.2	5.2	5.2	NI	NI	NI	NI	NI	NI	NI	NI	NI	5.17	NA			
CUG	NI	NI	NI	5.40	NI	NI	NI	NI	NI	NI	NI	NI	5.12	5.44	NA		
CW	NI	NI	NI	5.47	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NA
DDI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI
FPH	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	5.43	NI	NI	NI	NI	NI	NI
HOLD	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	5.11	NI	NI	NI	NI
LH	NI	NI	NI	5.68	NI	5.71	5.72	5.70	NI	NI	NI	NI	NI	NI	NI	NI	NA
MCID	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	5.46	5.34	NI	NI	NI
MSN	NI	NI	NI	5.41	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI
MWI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI
OCB	NI	NI	NI	5.50	5.55	5.52	5.53	5.54	NI	NI	NI	NI	NI	NI	NI	NI	NI
RC	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI
SUB	NI	NI	NI	5.42	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI
TP	5.10	5.10	5.10	NI	NI	NI	NI	NI	NI	NI	NI	NI	5.14	5.45	NI	NI	NI
UUS	NI	NI	NI	5.37	5.20	5.23	5.26	5.29	NI	NI	NI	NI	5.16	5.36	NI	NI	NI
3PTY	5.8	5.8	5.8	NI	NI	NI	NI	NI	NI	NI	NI	NI	5.15	5.35	5.33	NI	NI
CCNR (Note 1)	5.57	5.57	5.57	5.62	NI	NI	NI	NI	5.59	5.60	NI	NI	NI	NI	5.61	5.58	NI
SCF (Note 2)	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI
	AOC-S	AOC-D	AOC-E	CCBS	CD	CFB	CFNR	CFU	CLIP	CLIR	COLP	COLR	CONF	ECT	CUG	CW	

NOTE 1: The procedures for the CCNR supplementary service are similar to the procedures specified in the CCBS standard. Therefore, where possible, the terms (e.g. CCBSErase invoke component or CCBSReference parameter) as defined for the CCBS supplementary service are used and in some cases a reference to the clauses for the interactions between the CCBS and other supplementary services has been made.

NOTE 2: "NI" in the case of SCF is to be interpreted as follows: depending on the type of forwarding which is performed, the interactions between other supplementary services and CFU or CFB or CFNR apply.

Figure 1 (part 1 of 2): Overview of supplementary service interactions

Figure 1 gives an overview of the interactions between pairs of supplementary services. Only if the interaction is other than "Not Applicable (NA)" or "No Impact (NI)", a reference is given to a clause in the present document which details this particular interaction.

DDI	NA														
FPH	NI	NA													
HOLD	NI	NI	NA	NI											
LH	NA	NI	NI	NA	NI										
MCID	NI	NI	NI	NI	NA	NI									
MSN	NI	NI	NI	NI	NI	NA	NI								
MWI	NI	NI	NI	NI	NI	5.49	NA	NI							
OCB	NI	NI	NI	NI	NI	5.51	NI	5.56	NI						
RC	NI	NI	NI	NI	NI	NI	NI	NI	NA	NI					
SUB	NI	NI	NI	NI	NI	NI	NI	NI	NI	NA	NI				
TP	NI	NI	5.31	5.74	NI	NI	NI	NI	NI	NI	NA	NI			
UUS	NI	NI	NI	NI	NI	NI	NI	NI	NI	NI	5.48	NA	NI		
3PTY	NI	NI	5.32	NI	NI	NI	NI	NI	NI	NI	5.30	NI	NA	NI	
CCNR (Note 1)	NI	NI	NI	5.69	NI	5.63	NI	5.66	NI	5.64	NI	5.65	NI	NA	NI
SCF (Note 2)	NI	NI	NI	5.73	NI	NI	NI	5.67	NI	NI	NI	NI	NI	NI	NA
	DDI	FPH	HOLD	LH	MCID	MSN	MWI	OCB	RC	SUB	TP	UUS	3PTY	CCNR (Note 1)	SCF (Note 2)

NOTE 1: The procedures for the CCNR supplementary service are similar to the procedures specified in the CCBS standard. Therefore, where possible, the terms (e.g. CCBS~~E~~rase invoke component or CCBS~~R~~eference parameter) as defined for the CCBS supplementary service are used and in some cases a reference to the clauses for the interactions between the CCBS and other supplementary services has been made.

NOTE 2: "NI" in the case of SCF is to be interpreted as follows: depending on the type of forwarding which is performed, the interactions between other supplementary services and CFU or CFB or CFNR apply.

Figure 1 (part 2 of 2): Overview of supplementary service interactions

5.1 The AOC-D and AOC-E supplementary services

If the AOC-D and AOC-E supplementary services are activated for the same call, the network shall only send AOC-E type charging information when the call is released. AOC-E information is sent according to clause 9.2.3.1 of EN 300 182-1 [13].

5.2 The AOC and ECT supplementary services

5.2.1 Coding requirements

Table 1 shows the definition of the operation and errors required for the interaction between the AOC and the diversion and between the AOC and ECT supplementary services, using Abstract Syntax Notation one (ASN.1) as defined in either ITU-T Recommendation X.208 [33] or ITU-T Recommendation X.680 [37] and using the OPERATION macro as defined in either ITU-T Recommendation X.219 [34] or ITU-T Recommendation X.690 [38], figure 4/X.219.

The formal definition of the component types to encode this operation and the errors is provided in EN 300 196-1 [16], annex D, clause D.1.

The inclusion of components in Facility information elements is defined in EN 300 196-1 [16], clause 11.2.2.1.

Table 1: ASN.1 description of the IdentificationOfCharge operation

```

Advice-of-Charge-Interaction-Operations {ITU-T identified-organization etsi(0) 195
                                         operations-and-errors(1)}

DEFINITIONS EXPLICIT TAGS ::=

BEGIN

EXPORTS
    IdentificationOfCharge;

IMPORTS
    OPERATION
    FROM Remote-Operation-Notation
        {joint-iso-ITU-T remote-operations(4) notation(0)}

    notSubscribed,
    notAvailable,
    supplementaryServiceInteractionNotAllowed
    FROM General-Errors
        {ITU-T identified-organization etsi(0) 196 general-errors(2)}

    ChargingAssociation
    FROM Advice-of-Charge-Operations
        {ITU-T identified-organization etsi(0) 182 operations-and-errors(1)};

IdentificationOfCharge ::= OPERATION
    ARGUMENT      ChargingAssociation
    ERRORS {
        notSubscribed,
        notAvailable,
        supplementaryServiceInteractionNotAllowed}

identificationOfCharge IdentificationOfCharge ::= localValue 37

END -- of Advice-of-Charge-Interaction-Operations

```

5.2.2 Signalling procedures at the coincident S and T reference point

5.2.2.1 Delivery of charging information to the transferring user

5.2.2.1.1 Normal procedures

For each call for which the AOC-D supplementary service is activated, the network shall not send any charging information to the served user after that call has been transferred. When the call transfer is completed and the network releases the served user, the network shall send AOC-D charging information in one of the call control messages clearing that call. If the served user is charged for a part of the transferred call, the network shall set the TypeOfChargingInfo = "subTotal".

If the AOC-S supplementary service is activated and if the charging rate is changed after the call has been transferred, the network shall not send any information about the changed charging rate to the served user.

As a network option, the network shall send AOC-E type charging information pertaining to a transferred call, after the transferred call is released. In this case, the charging information shall be transferred using the procedures specified in clause 9.2.4 of EN 300 182-1 [13]. If the served user activates the AOC-E supplementary service or if the AOC-E supplementary service is activated for all calls and the user invokes the ECT supplementary service, the user may in addition send an IdentificationOfCharge invoke component containing the argument ChargingAssociation to the network. In order to associate the IdentificationOfCharge invoke component with the call to be transferred, the user shall include the IdentificationOfCharge invoke component within the same FACILITY message that contains either the EctExecute or the ExplicitEctExecute invoke component, as defined in clause 7.2 of EN 300 369-1 [21].

The user shall choose for each call either the PartyNumber or the ChargeIdentifier type of the ChargingAssociation, when the ChargingAssociation parameter is used.

If the network receives the IdentificationOfCharge invoke component and the network supports the option to send AOC-E charging information in connection with the ECT supplementary service, the network shall retain the provided ChargingAssociation parameter.

When the transferred call is released, the network shall send the retained ChargingAssociation parameter together with the AOC-E charging information to the served user and subsequently release the retained ChargingAssociation parameter. The ChargingAssociation parameter provides additional information for the user to identify the call to which a specific AOC-E charging information is related.

In the case that the user has subscribed to the MSN supplementary service, the network shall return the served user's number associated with the call reference on which the EctExecute or ExplicitEctExecute invoke component was sent in the Called party number information element when the AOC-E charging information is sent to the user.

When the network offers the option of sending charging information for the transferred call and if the served user is charged for both calls (before the ECT supplementary service is invoked) and if the AOC-E supplementary service is activated for each call, then the network shall send the overall charges for both calls to the served user when the transferred call is released. If the AOC-E supplementary service is only activated for one call, then the network shall only send the charge for this call to the served user when the transferred call is released.

The network shall send the charging information in the Facility information element and indicate the following information:

- AOCECurrencyInfo, and optionally the AOCEBillingId = "callTransfer", in an AOCECurrency invoke component; or
- AOCEChargingUnitInfo, and optionally the AOCEBillingId = "callTransfer", in an AOCEChargingUnit invoke component.

5.2.2.1.2 Exceptional procedures

If, on receipt of an IdentificationOfCharge invoke component, the user has not subscribed to the AOC-E supplementary service, the network shall send an IdentificationOfCharge return error component indicating "notSubscribed" to the user according to the procedures of clause 8.3.1.1.2 of EN 300 196-1 [16].

If a user sends an IdentificationOfCharge invoke component to the network and the user has subscribed to AOC-E supplementary service on a per call basis but the user has not activated the AOC-E supplementary service for this particular call, the network shall send an IdentificationOfCharge return error component to the user according to the procedures of clause 8.3.1.1.2 of EN 300 196-1 [16] "notAvailable".

5.2.3 Procedures for interworking with private ISDNs

The procedures of clause 5.2.2 shall apply.

5.3 The AOC and CCBS supplementary services

5.3.1 Coding requirements

No impact.

5.3.2 Signalling procedures at the coincident S and T reference point

5.3.2.1 Requesting an AOC supplementary service

5.3.2.1.1 Normal operation

The network shall store the accepted request for the AOC supplementary service for the original call and apply it to the CCBS call established by this particular CCBS instance as identified for this user.

When this particular CCBS instance is completed (e.g. the CCBS call is successfully established, or the CCBS supplementary service is cancelled by the user), the network shall release the retained AOC request.

5.3.2.1.2 Exceptional procedures

The procedures specified in clause 9.1.2 of EN 300 182-1 [13] shall apply.

5.3.2.2 Delivery of charging information to the user

5.3.2.2.1 Normal operation

No impact.

NOTE: Charging information sent by the network to the user for the original call and the CCBS call will follow the procedures specified for the relevant AOC supplementary services according to clauses 9.2.1.1, 9.2.2.1 and 9.2.3.1 of EN 300 182-1 [13].

5.3.2.2.2 Exceptional procedures

No impact.

NOTE: The procedures defined in clauses 9.2.1.2, 9.2.2.2 and 9.2.3.2 of EN 300 182-1 [13] will apply.

5.3.3 Procedures for interworking with private ISDNs

5.3.3.1 Requesting an AOC supplementary service by the private network

5.3.3.1.1 Normal operation

To request an AOC supplementary service for the CCBS call the private network shall apply the procedures as defined in clause 9.1.1 of EN 300 182-1 [13].

NOTE: If an AOC supplementary service was requested for the original call, then the private network will include a ChargingRequest invoke component indicating the same service in the SET-UP message used to establish the CCBS call.

The network shall, upon receiving the ChargingRequest invoke component, check if the user has access to the requested AOC supplementary service and, if so, send a ChargingRequest return result component in a FACILITY message or an appropriate call control message to the private network.

5.3.3.1.2 Exceptional procedures

The procedures defined in clause 9.1.2 of EN 300 182-1 [13] shall apply.

5.3.3.2 Delivery of charging information to the private network

5.3.3.2.1 Normal operation

When the network sends charging information to the private network, the procedures specified in clauses 9.2.1.1, 9.2.2.1 and 9.2.3.1 of EN 300 182-1 [13] shall apply.

5.3.3.2.2 Exceptional procedures

The procedures defined in clauses 9.2.1.2, 9.2.2.2 and 9.2.3.2 of EN 300 182-1 [13] shall apply.

5.4 The AOC and CD supplementary services

5.4.1 Coding requirements

See clause 5.2.1.

5.4.2 Signalling procedures at the coincident S and T reference point

The invocation of the following supplementary services is not applicable in combination with the invocation of the CD supplementary service:

- the AOC-S supplementary service; and
- the AOC-D supplementary service.

As a network option, if the AOC-E supplementary service is activated for all calls, the network shall send charging information to the deflecting (served) user when a deflected call is released.

5.4.2.1 Delivery of charging information to the deflecting user

5.4.2.1.1 Normal operation

If the AOC-E supplementary service is activated for all calls and the user invokes the CD supplementary service, the user may in addition send an IdentificationOfCharge invoke component containing the argument ChargingAssociation to the network. In order to associate the IdentificationOfCharge invoke component with the call to be deflected, the user shall include the IdentificationOfCharge invoke component within the same message that contains the CallDeflection invoke component as defined in clause 7.2 of EN 300 207-1 [17].

The user shall choose for each call either the PartyNumber or the ChargeIdentifier type of the ChargingAssociation, when the ChargingAssociation parameter is used.

If the network receives the IdentificationOfCharge invoke component and the network supports the option to send AOC-E charging information in connection with the CD supplementary service, the network shall retain the provided ChargingAssociation parameter.

When the deflected call is released, and the network supports the option to send charging information to the deflecting user when a deflected call is released then the network shall send the retained ChargingAssociation parameter to the user, together with the AOC-E charging information and subsequently release the retained ChargingAssociation parameter. The ChargingAssociation parameter provides additional information for the user to identify the call to which a specific AOC-E charging information is related.

The network shall include the charging information in an invoke component within the Facility information element, to be conveyed in a FACILITY message, as specified in clause 9.2.4 of EN 300 182-1 [13].

The invoke component shall contain the following charging information:

- AOCECurrencyInfo and optionally the AOCEBillingId, in an AOCECurrency invoke component; or
- AOCEChargingUnitInfo and optionally the AOCEBillingId, in an AOCEChargingUnit invoke component.

The network shall set the AOCEBillingId = "callDeflection".

In the case that the user has subscribed to the MSN supplementary service, the network shall return the called party number of the deflected call in the Called party number information element when the AOC-E charging information is sent to the user.

5.4.2.1.2 Exceptional procedures

See clause 5.2.2.1.2.

5.4.3 Procedures for interworking with private ISDNs

The invocation of the following supplementary services is not applicable in combination with the invocation of the CD supplementary service:

- the AOC-S supplementary service; and
- the AOC-D supplementary service.

5.4.3.1 Delivery of charging information to the private network when the CD supplementary service is provided to the private ISDN

As a network option, if the AOC-E supplementary service is activated for all calls, the network shall send charging information to the deflecting (served) user when a deflected call is released.

If the network supports the option to send charging information to the deflecting private network when a deflected call is released and the private network has invoked the CD supplementary service by sending a CallDeflection invoke component to the network, then the procedure of clause 5.4.2.1 shall apply. In addition, if the DDI supplementary service applies, the network shall return the called party number of the deflected call in the Called party number information element when the AOC-E charging information is sent to the user.

5.4.3.2 Delivery of charging information to the private network when partial rerouteing applies

As a network option, if the AOC-E supplementary service is activated for all calls or activated on a per-call basis, the network shall send charging information to the deflecting (served) user when a deflected call is released.

5.4.3.2.1 Normal operation

If the private network activates the AOC-E supplementary service on a per-call basis, the ChargingRequest invoke component (as defined in clause 7.2 of EN 300 182-1 [13]) shall also be included within the same FACILITY message that contains the CallRerouteing invoke component as defined in clause 7.2 of EN 300 207-1 [17], with the ChargingCase parameter indicating "chargingAtTheEndOfACall".

If the AOC-E supplementary service is activated and the private network invokes the partial rerouteing procedures, the private network may in addition send an IdentificationOfCharge invoke component containing the argument ChargingAssociation to the network. In order to associate the IdentificationOfCharge invoke component with the call to be diverted, the private network shall include the IdentificationOfCharge invoke component within the same FACILITY message that contains the CallRerouteing invoke component as defined in clause 7.2 of EN 300 207-1 [17].

When the ChargingAssociation parameter is used, the private network shall, on a per-call basis, choose either the PartyNumber or the ChargeIdentifier type of the ChargingAssociation.

If the network receives the IdentificationOfCharge invoke component and the network supports the option to send AOC-E charging information in connection with the CD supplementary service, the network shall retain the provided ChargingAssociation parameter.

When the diverted call is released, and the network supports the option to send charging information to the deflecting user when a deflected call is released, then the network shall send the retained ChargingAssociation parameter to the private network, together with the AOC-E charging information and subsequently release the retained ChargingAssociation parameter. The ChargingAssociation parameter provides additional information for the user to identify the call to which a specific AOC-E charging information is related.

The network shall include the charging information in an invoke component within the Facility information element, to be conveyed in a FACILITY message, as specified in clause 9.2.4 of EN 300 182-1 [13].

The invoke component shall contain the following charging information:

- AOCECurrencyInfo and optionally the AOCEBillingId, in an AOCECurrency invoke component; or
- AOCEChargingUnitInfo and optionally the AOCEBillingId, in an AOCEChargingUnit invoke component.

If the RerouteingReason parameter received in the CallRerouteing invoke component indicated "cfu" or "unknown", then the network shall set the AOCEBillingId = "callForwardingUnconditional".

If the RerouteingReason parameter received in the CallRerouteing invoke component indicated "cfb", then the network shall set the AOCEBillingId = "callForwardingBusy".

If the RerouteingReason parameter received in the CallRerouteing invoke component indicated "cfnr", then the network shall set the AOCEBillingId = "callForwardingNoReply".

If the RerouteingReason parameter received in the CallRerouteing invoke component indicated "cd" or "cdImmediate", then the network shall set the AOCEBillingId = "callDeflection".

5.4.3.2.2 Exceptional procedures

See clause 5.2.2.1.2.

5.5 The AOC and CFB supplementary services

5.5.1 Coding requirements

See clause 5.2.1.

5.5.2 Signalling procedures at the coincident S and T reference point

The invocation of the following supplementary services is not applicable in combination with the invocation of the CFB supplementary service:

- the AOC-S supplementary service; and
- the AOC-D supplementary service.

As a network option, if the AOC-E supplementary service is activated for all calls and the CFB supplementary service has been activated, the network shall send charging information to the forwarding (served) user when a forwarded call is released.

5.5.2.1 Delivery of charging information to the forwarding user

5.5.2.1.1 Normal operation

If the network supports the option to send charging information to the forwarding user when a forwarded call is released, then the network shall include the charging information in an invoke component within the Facility information element, to be conveyed in a FACILITY message, as specified in clause 9.2.4 of EN 300 182-1 [13].

The invoke component shall contain the following charging information:

- AOCECurrencyInfo and optionally the AOCEBillingId, in an AOCECurrency invoke component; or
- AOCEChargingUnitInfo and optionally the AOCEBillingId, in an AOCEChargingUnit invoke component.

The network shall set the AOCEBillingId = "callForwardingBusy".

In the case that the user has subscribed to the MSN supplementary service, the network shall return the called party number of the diverted call in the Called party number information element when the AOC-E charging information is sent to the user.

5.5.2.1.2 Exceptional procedures

No impact.

5.5.3 Procedures for interworking with private ISDNs

The invocation of the following supplementary services is not applicable in combination with the invocation of the CFB supplementary service:

- the AOC-S supplementary service; and
- the AOC-D supplementary service.

5.5.3.1 Delivery of charging information to the private network when the CFB supplementary service is provided to the private ISDN

As a network option, if the AOC-E supplementary service is activated for all calls and the CFB supplementary service has been activated, the network shall send charging information to the forwarding (served) user when a forwarded call is released.

If the network supports the option to send charging information to the forwarding private network when a forwarded call is released and the private network has activated the CFB supplementary service for the whole private network, then the procedures of clause 5.5.2.1 shall apply. In addition, if the DDI supplementary service applies, the network shall return the called party number of the diverted call in the Called party number information element when the AOC-E charging information is sent to the user.

5.5.3.2 Delivery of charging information to the private network when partial rerouting applies

The procedures of clause 5.4.3.2 shall apply.

5.6 The AOC and CFNR supplementary services

The procedures of clause 5.5 shall apply with the exception that the network shall set the AOCEBillingId = "callForwardingNoReply".

5.7 The AOC and CFU supplementary services

The procedures of clause 5.5 shall apply with the exception that the network shall set the AOCEBillingId = "callForwardingUnconditional".

5.8 The AOC and 3PTY supplementary services

5.8.1 Coding requirements

No impact.

5.8.2 Signalling procedures at the coincident S and T reference point

5.8.2.1 Normal operation

If the served user has activated any of the AOC supplementary services, the network shall send charging information as for a normal call to the user, i.e. for those calls originated by the served user as defined in clauses 9.2.1.1, 9.2.2.1 and 9.2.3.1 of EN 300 182-1 [13].

If the network option to indicate charges for the use of the conference bridge applies, then the network shall send this charging information to the user, only when an AOC supplementary service is activated for the call (identified by its call reference) that is used to convey the Begin3PTY invoke component.

5.8.2.2 Exceptional procedures

No impact.

5.8.3 Procedures for interworking with private ISDNs

No impact.

5.9 The AOC and CONF supplementary services

5.9.1 Coding requirements

No impact.

5.9.2 Signalling procedures at the coincident S and T reference point

5.9.2.1 Normal operation

The network shall use the call reference of the conference call when it sends charging information to a conference-controlling user (local interaction for the call). In this case, the network shall send charging information related to the whole conference.

If the user invokes the CONF supplementary service from a call in the (Active call state, Idle auxiliary state) or (Active call state, Call Held auxiliary state) and an AOC supplementary service is requested for the resulting conference call, the user shall include the ChargingRequest invoke component in the same FACILITY message that contains the BeginCONF invoke component as defined in clause 7 of EN 300 185-1 [14]. The user shall indicate in the ChargingCase parameter which AOC supplementary service is requested.

If a remote user is split from the conference, the network shall use the call reference established for the private communication when sending charging information for that connection if an AOC supplementary service is activated. When the private communication is terminated, the network shall send the relevant charging information as for a call in the clearing phase (see clause 9.2.3 of EN 300 182-1 [13]). If the AOC-D supplementary service is activated for the private communication, the network shall set the TypeOfChargingInfo = "total" when charging information is sent in a call control message terminating the private communication.

5.9.2.2 Exceptional procedures

If a user sends a ChargingRequest invoke component requesting an AOC supplementary service in the FACILITY message together with any invoke component defined for the CONF supplementary service (see clause 7 of EN 300 185-1 [14]) except the BeginCONF invoke component, then the network shall respond with a ChargingRequest return error component indicating "notAvailable" to the user.

If the network receives a ChargingRequest invoke component together with a BeginCONF invoke component and the network does not support the AOC supplementary service in conjunction with the CONF supplementary service, then the network shall respond with a ChargingRequest return error component indicating "notAvailable" to the user.

If a user sends a ChargingRequest invoke component requesting an AOC supplementary service in the FACILITY message together with the BeginCONF invoke component and invocation of the CONF supplementary service is not accepted by the network (e.g. no resources are available), then the network shall not activate the requested AOC supplementary service and respond with a ChargingRequest return error component indicating "notAvailable" to the user.

5.9.3 Procedures for interworking with private ISDNs

The procedures of clause 5.9.2 shall apply.

5.10 The AOC and TP supplementary services

5.10.1 Coding requirements

No impact.

5.10.2 Signalling procedures at the coincident S and T reference point

5.10.2.1 In the call suspension phase

5.10.2.1.1 Normal operation

If a served user of the AOC-D supplementary service suspends a call (local interaction for the call), then as a network option, the network shall send charging information to the served user in the SUSPEND ACKNOWLEDGE message. In that case, the Facility information element shall be included in the SUSPEND ACKNOWLEDGE message containing the cumulative charge (i.e. the sub-total charge incurred up to the moment when the call is suspended).

The network shall send one of the following types of charging information to the served user:

- AOCDCurrencyInfo in an AOCDCurrency invoke component; or
- AOCDChargingUnitInfo in an AOCDChargingUnit invoke component.

The TypeOfChargingInfo shall be set to "subtotal".

NOTE 1: Charging can continue during the time the call is suspended (while timer T307 is running). If the served user does not resume the call before T307 expires, the charging information recorded for this call may be different from the charging information sent to the served user either prior to or during the sending of the SUSPEND ACKNOWLEDGE message. This also applies if the remote user clears the call during the period of suspension.

In some cases the charging information cannot be available in time to be included in the SUSPEND ACKNOWLEDGE message sent to the served user.

NOTE 2: This may happen when the charging information resides in an ISDN entity that is remote from the network generating the SUSPEND ACKNOWLEDGE message.

In this case the network shall send the Facility information element in the SUSPEND ACKNOWLEDGE message to indicate to the served user that the charging information is not available (i.e. "chargeNotAvailable") and the call suspension shall continue as defined in EN 300 055-1 [2].

5.10.2.1.2 Exceptional procedures

No impact.

5.10.2.2 In the call resume phase

5.10.2.2.1 Normal operation

When a served user resumes a call, the network shall also resume sending of charging information to the user if the AOC-D supplementary service is activated for the call. In addition, charging information may, as a network option, be sent to the served user in the RESUME ACKNOWLEDGE message. In that case, the network shall include the Facility information element in the RESUME ACKNOWLEDGE message, containing one of the following types of charging information:

- AOCDCurrencyInfo in an AOCDCurrency invoke component; or
- AOCDChargingUnitInfo in an AOCDChargingUnit invoke component.

The TypeOfChargingInfo shall be set to "subtotal".

In some cases the charging information cannot be available in time to be included in the RESUME ACKNOWLEDGE message sent to the served user.

NOTE: This may happen when the charging information resides in an ISDN entity that is remote from the network generating the RESUME ACKNOWLEDGE message.

In this case the network shall send the Facility information element in the RESUME ACKNOWLEDGE message to indicate to the served user that the charging information is not available (i.e. "chargeNotAvailable") and normal call handling shall continue. When the charging information has become available after a call has been resumed, the network shall send a FACILITY message to the served user containing the charging information shown above.

If the AOC-S supplementary service is activated for the call, the network shall send charging rates applied to the call in the first message sent to the served user after call resumption, if the charging rate has been changed during the time the call was suspended.

As a network option, the network shall transfer charging information to the served user even though the network cannot resume a suspended call (within the time the network retains the call identity of the suspended call). The network shall include the Facility information element in the RESUME REJECT message if the served user attempts to resume the call before timer T307 expires. The network shall retain the charging information for the suspended call as long as it retains the call identity of the suspended call. The following cases are applicable:

- a) if the remote user disconnects while the call is suspended:

Either the AOC-D or the AOC-E type charging information can be provided, if the supplementary service is activated for the call. If the AOC-D supplementary service is activated, the network shall set the TypeOfChargingInfo = "total" when charging information is sent to the served user.

- b) if resumption is rejected for any other reason:

Only cumulative charging during a call can be provided, if the supplementary service is activated for the call (i.e. the served user attempts to resume the call a number of times before the call retention timer expires). If the AOC-D supplementary service is activated, the network shall set the TypeOfChargingInfo = "subTotal" when charging information is sent to the served user.

5.10.2.2 Exceptional procedures

No impact.

5.10.3 Procedures for interworking with private ISDNs

No impact.

5.11 The CONF and HOLD supplementary services

5.11.1 Coding requirements

Table 2 shows the definition of the operation IdentifyConferee using ASN.1 as defined in either ITU-T Recommendation X.208 [33] or ITU-T Recommendation X.680 [37] and using the OPERATION macro as defined either ITU-T Recommendation X.219 [34] or ITU-T Recommendation X.690 [38], figure 4/X.219.

The formal definition of the component type to encode this operation is provided in EN 300 196-1 [16], annex D, clause D.1.

The inclusion of components in Facility information elements is defined in EN 300 196-1 [16], clause 11.2.2.1.

Table 2: ASN.1 description of the IdentifyConferee operation

Conference-Add-On-Operations {ITU-T identified-organization etsi(0) 195 conference-add-on-operations(3)}		
DEFINITIONS EXPLICIT TAGS ::=		
BEGIN		
EXPORTS	IdentifyConferee;	
IMPORTS	OPERATION FROM Remote-Operation-Notation {joint-iso-ITU-T remote-operations(4) notation(0)} PartyId FROM Conference-Add-On-Operations {ITU-T identified-organization etsi(0) 185 operations-and-errors(1)};	
IdentifyConferee	::= OPERATION	
	ARGUMENT	PartyId
identifyConferee	IdentifyConferee	::= localValue 49
END -- of Conference-Add-On-Operations		

5.11.2 Signalling procedures at the coincident S and T reference point

5.11.2.1 Invocation of the HOLD supplementary service by the served user of the CONF supplementary service

5.11.2.1.1 Normal operation

If the conference call is held or retrieved by the served user of the CONF supplementary service (local interaction for the call), the network shall not apply the notification procedures specified in EN 300 141-1 [12], clauses 9.2.1 and 9.4.1.

5.11.2.1.2 Exceptional procedures

No impact.

5.11.2.2 Invocation of the HOLD supplementary service by the remote user of the CONF supplementary service

5.11.2.2.1 Normal operation

If, during operation of the CONF supplementary service, a remote user uses the HOLD supplementary service (remote interaction), then notifications concerning the HOLD supplementary service shall be sent as normal to the served user, with the following addition:

- the network shall send the Notification indicator information to the served user in a FACILITY message according to the procedures of clause 8.3.1.1 of EN 300 196-1 [16];
- the network shall include in the same message a Facility information element containing an IdentifyConferee invoke component. The IdentifyConferee operation is specified in table 2. The PartyId parameter shall indicate the remote user pertaining to the provided notification.

5.11.2.2.2 Exceptional procedures

No impact.

5.11.3 Procedures for interworking with private ISDNs

The procedures of clause 5.11.2 shall apply.

5.12 The CONF and CUG supplementary service

5.12.1 Coding requirements

No impact.

5.12.2 Signalling procedures at the coincident S and T reference point

5.12.2.1 Adding a call

5.12.2.1.1 Normal operation

No impact.

5.12.2.1.2 Exceptional procedures

If, within the CONF supplementary service, the network refuses a request to add a call because this call is not a member of the closed user group of the conference, the AddCONF return error component shall contain the error "supplementaryServiceInteractionNotAllowed".

The closed user group of the conference is the closed user group of the first call in the conference. If this call is not a member of a closed user group, then the conference is not a member of a closed user group.

NOTE: If the conference is created from the Null state, the closed user group information cannot be included in the SET-UP message. Therefore the closed user group of the conference is undefined until the first call is added to the conference.

5.12.3 Procedures for interworking with private ISDNs

The procedure of clause 5.12.2.1 shall apply.

5.13 The CONF and CONF supplementary services

5.13.1 Coding requirements

No impact.

5.13.2 Signalling procedures at the coincident S and T reference point

5.13.2.1 Re-invoking the CONF supplementary service

5.13.2.1.1 Normal operation

No impact.

5.13.2.1.2 Exceptional procedures

If, within the CONF supplementary service, the network refuses a request to invoke the CONF supplementary service, because the call is part of a conference controlled by the same served user (local interaction for the call), the network shall apply the error handling specified in clause 9.2.2.2 of EN 300 185-1 [14], using the error value "notAvailable".

5.13.2.2 Adding a conference call to a conference

5.13.2.2.1 Normal operation

No impact.

5.13.2.2.2 Exceptional procedures

If, within the CONF supplementary service, the network refuses a request to add a call to a conference, because the call is part of a conference controlled by the same served user (local interaction for the same call), the network shall apply the error handling specified in clause 9.2.3.2 of EN 300 185-1 [14], using the error value "notAllowed".

5.13.2.3 Notification of the served user

5.13.2.3.1 Normal procedures

If, during operation of the CONF supplementary service, a remote user uses the CONF supplementary service (remote interaction), then notifications concerning the CONF supplementary service shall be sent as normal to the served user of the CONF supplementary service, with the following addition:

- the network shall send the Notification indicator information to the served user in a FACILITY message according to the procedures of clause 8.3.1.1 of EN 300 196-1 [16];
- the network shall include in the same message a Facility information element containing an IdentifyConferee invoke component. The IdentifyConferee operation is specified in table 2. The PartyId parameter shall indicate the remote user pertaining to the provided notification.

5.13.2.3.2 Exceptional procedures

No impact.

5.13.3 Procedures for interworking with private ISDNs

The procedures of clause 5.13.2 shall apply.

5.14 The CONF and TP supplementary services

5.14.1 Coding requirements

See clause 5.11.1.

5.14.2 Signalling procedures at the coincident S and T reference point

5.14.2.1 Served user of CONF supplementary service uses TP supplementary service

5.14.2.1.1 Normal operation

No impact.

NOTE: The invocation of the TP supplementary service is not allowed for the served user of the CONF supplementary service.

5.14.2.1.2 Exceptional procedures

If, within the TP supplementary service, the network refuses a request to suspend a call, because the call is part of a conference controlled by the same served user (local interaction for the call), or because another call for that CEI is part of a conference for which the served user is located at that CEI (local interaction for the CEI), the SUSPEND REJECT message shall contain cause value #29, "facility rejected".

5.14.2.2 Remote user of CONF supplementary service uses TP supplementary service

5.14.2.2.1 Normal operation

If, during operation of the CONF supplementary service, a remote user uses the TP supplementary service (remote interaction), then notifications concerning the TP supplementary service shall be sent as normal to the served user of the CONF supplementary service, with the following addition:

- the network shall send the Notification indicator information to the served user in a FACILITY message according to the procedures of clause 8.3.1.1 of EN 300 196-1 [16];
- the network shall include in the same message a Facility information element containing an IdentifyConferee invoke component. The IdentifyConferee operation is specified in table 2. The PartyId parameter shall indicate the remote user pertaining to the provided notification.

5.14.2.2.2 Exceptional procedures

No impact.

5.14.2.3 Remote user of the TP supplementary service uses the CONF supplementary service

5.14.2.3.1 Normal operation

If, within the TP supplementary service, the served user has suspended a call, the network cannot send notifications to the served user that are caused by operation of the CONF supplementary service (remote interaction).

The network shall discard these notifications and shall not retain these for later delivery.

5.14.2.3.2 Exceptional procedures

No impact.

5.15 The CONF and 3PTY supplementary services

5.15.1 Coding requirements

No impact.

5.15.2 Signalling procedures at the coincident S and T reference point

5.15.2.1 Requesting a three-way conversation where one of the connections belongs to a conference call

5.15.2.1.1 Normal operation

No impact.

NOTE: The invocation of the 3PTY supplementary service is not allowed for the served user of the CONF supplementary service.

5.15.2.1.2 Exceptional procedures

If, within the 3PTY supplementary service, the network refuses a request to join two calls, because one of the calls is part of a conference controlled by the same served user (local interaction for the call), the network shall send a Begin3PTY return error component to the served user, indicating "supplementaryServiceInteractionNotAllowed".

5.15.2.2 Adding a three-way conversation to a conference

5.15.2.2.1 Normal operation

No impact.

NOTE: The invocation of the 3PTY supplementary service is not allowed for the served user of the CONF supplementary service.

5.15.2.2.2 Exceptional procedures

If, within the CONF supplementary service, the network refuses a request to add a call to a conference, because the call is part of a three-way conversation controlled by the same served user (local interaction for the same call), the network shall send an AddCONF return error component to the served user, indicating "supplementaryServiceInteractionNotAllowed".

5.15.2.3 Invocation of the CONF supplementary service for a connection in a three-way conversation

5.15.2.3.1 Normal operation

No impact.

NOTE: The invocation of the CONF supplementary service is not allowed for the served user of the 3PTY supplementary service.

5.15.2.3.2 Exceptional procedures

If, within the CONF supplementary service, the network refuses a request to invoke the CONF supplementary service, because the call is part of a three-way conversation controlled by the same served user (local interaction for the call), the network shall send a BeginCONF return error component to the served user, indicating "supplementaryServiceInteractionNotAllowed".

5.15.2.4 Remote user uses the 3PTY supplementary service

5.15.2.4.1 Normal operation

If, during operation of the CONF supplementary service, a remote user uses the 3PTY supplementary service (remote interaction), then notifications concerning the 3PTY supplementary service shall be sent as normal to the served user, with the following addition:

- the network shall send the Notification indicator information to the served user in a FACILITY message according to the procedures of clause 8.3.1.1 of EN 300 196-1 [16];
- the network shall include in the same message a Facility information element containing an IdentifyConferee invoke component. The IdentifyConferee operation is specified in table 2. The PartyId parameter shall indicate the remote user pertaining to the provided notification.

5.15.2.4.2 Exceptional procedures

No impact.

5.15.3 Procedures for interworking with private ISDNs

See clause 5.15.2.4.

5.16 The CONF and UUS service 3 supplementary services

5.16.1 Coding requirements

See clause 5.11.1.

5.16.2 Signalling procedures at the coincident S and T reference point

The served user and each individual remote user can exchange USER INFORMATION messages by use of service 3. Furthermore, the served user can send USER INFORMATION messages as broadcast to all remote users.

5.16.2.1 Service 3 activation

5.16.2.1.1 Normal operation

Before exchange of USER INFORMATION messages service 3 shall be activated for the initial call to each individual remote user which at a later time will become a conferee by being added to the conference, i.e. the activation procedure shall be performed outside the conference call. Consequently, service 3 cannot be activated to a user already acting as a conferee.

The activation of service 3 between the served user and a user which at a later time will become a remote user shall be performed according to the procedures in EN 300 286-1 [19], clause 9.3.1.

When a remote user is added to the conference the network shall retain knowledge of whether service 3 is active to this remote user and whether service 3 was activated by the served user or the remote user.

When a private communication is created with a remote user to which service 3 was activated, the service 3 shall remain available in association with the private communication.

When a private communication is created with a remote user for which service 3 was not available during the conference, service 3 can be activated in association with the private communication by use of the procedure described in EN 300 286-1 [19], clause 9.3.1.

5.16.2.1.2 Exceptional procedures

No impact.

5.16.2.2 Transfer of user information

5.16.2.2.1 Normal operation

When USER INFORMATION messages are to be exchanged between the served user and an individual remote user, the procedures described in clause 9.3.2 of EN 300 286-1 [19] shall apply with the following exceptions for the served user's user-network interface:

- the served user shall include a Facility information element with an IdentifyConferee invoke component in the USER INFORMATION message sent to the network. The component shall include the PartyId parameter to identify the remote user. The network shall not include this Facility information element in the USER INFORMATION message sent to the remote user;
- when the network receives a USER INFORMATION message from a remote user, this USER INFORMATION message shall be sent to the served user including a Facility information element with an IdentifyConferee invoke component including the PartyId parameter identifying the remote user.

If the served user sends a USER INFORMATION message to the network without the above-mentioned Facility information element, the network shall treat this as a request for the broadcast capability and shall send a USER INFORMATION message to each individual remote user.

If a remote user is isolated, individual exchange of USER INFORMATION messages can be performed between that remote user and the served user provided service 3 is activated for that remote user. In case of broadcast sending from the served user, the isolated remote user shall not receive USER INFORMATION messages.

If private communication is created with a remote user, the exchange of USER INFORMATION messages shall be as described in EN 300 286-1 [19], clause 9.3.2. The broadcast capability is not applicable.

5.16.2.2.2 Exceptional procedures

No impact.

5.16.2.3 Flow control

5.16.2.3.1 Normal operation

For the sending of USER INFORMATION messages from the served user, the flow control procedures described in EN 300 286-1 [19], clause 9.3.3 shall apply for the conference controller's connection to the conference. Consequently, the served user can send up to the maximum limit of USER INFORMATION messages to the remote users in common, including broadcast sending.

Since more than one remote user can send USER INFORMATION messages to the conference controller at the same time, the normal maximum limit can be exceeded at the served user's network side. In this case, the network shall deliver the received USER INFORMATION messages to the served user without any restrictions.

Normal flow control procedures shall be followed at the remote user's network.

5.16.2.3.2 Exceptional procedures

No impact.

5.16.3 Procedures for interworking with private ISDNs

The procedures of clause 5.16.2 shall apply.

5.17 The CONF and ECT supplementary services

5.17.1 Coding requirements

See clause 5.11.1.

5.17.2 Signalling procedures at the coincident S and T reference point

5.17.2.1 Served user uses the ECT supplementary service

5.17.2.1.1 Normal operation

No impact.

NOTE: The invocation of the ECT supplementary service is not allowed for the served user of the CONF supplementary service.

5.17.2.1.2 Exceptional procedures

If the user invokes the ECT supplementary service using the implicit linkage procedures according to clause 9.2.1.1 of EN 300 369-1 [21], and the call is also the controlling call in the CONF supplementary service (local interaction for the call), then the network shall reject the EctExecute invoke component according to clause 9.2.1.2 of EN 300 369-1 [21]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

If the user invokes the ECT supplementary service using the implicit linkage procedures according to clause 9.2.1.1 of EN 300 369-1 [21], and the call not on hold is also the controlling call in the CONF supplementary service (local interaction for the call), then the network shall reject the EctExecute invoke component according to clause 9.2.1.2 of EN 300 369-1 [21]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

If the user invokes the ECT supplementary service using the explicit linkage procedures according to clause 9.2.2.1 of EN 300 369-1 [21], and either call is also the controlling call in the CONF supplementary service (local interaction for the call), then the network shall reject the ExplicitEctExecute invoke component according to clause 9.2.2.2 of EN 300 369-1 [21]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

The network shall not reject an EctLinkIdRequest invoke component due to the user being the served user in the CONF supplementary service.

5.17.2.2 Remote user uses the ECT supplementary service

5.17.2.2.1 Normal operation

Conferees can invoke the ECT supplementary service in order to transfer their connection to the conference to another user after that call is answered.

If, during operation of the CONF supplementary service, a remote user uses the ECT supplementary service (remote interaction), then notifications concerning the ECT supplementary service shall be sent as normal to the served user of the CONF supplementary service, with the following addition:

- the network shall send the Notification indicator information to the served user in a FACILITY message according to the procedures of clause 8.3.1.1 of EN 300 196-1 [16];
- the network shall include in the same message a Facility information element containing an IdentifyConferee invoke component. The IdentifyConferee operation is specified in table 2. The PartyId parameter shall indicate the remote user pertaining to the provided notification.

NOTE: This implies that the served user of the CONF supplementary service and the other remote user will be notified but no notification is given to the other conferees taking part in the conference.

If, during operation of the CONF supplementary service, a remote user uses the ECT supplementary service (remote interaction), then the procedures of clauses 9.2.4 and 9.2.5 of EN 300 369-1 [21] shall apply for the served user of the CONF supplementary service, with the following addition:

- on sending the RequestSubaddress invoke component to the served user of the CONF supplementary service, the network shall include in the same message an IdentifyConferee invoke component indicating the PartyId of the party performing the transfer;
- on sending the SubaddressTransfer invoke component to the network, the served user of the CONF supplementary service shall include in the same message an IdentifyConferee invoke component indicating the PartyId of the party performing the transfer.

A message shall only contain one IdentifyConferee invoke component and hence shall only contain components pertaining to one party.

5.17.2.2.2 Exceptional procedures

No impact.

5.17.3 Procedures for interworking with private ISDNs

No impact.

5.18 The CD and COLP supplementary services

5.18.1 Coding requirements

No impact.

5.18.2 Signalling procedures at the coincident S and T reference point

5.18.2.1 Normal operation

For the presentation of the connected line identification to the calling user the same conditions shall apply as for the presentation of the redirection number as specified in EN 300 207-1 [17], clause 9.2.3.1:

- if the value of the summary condition "calling user is notified of diversion" is "no" or "yes, without diverted-to number", the presentation shall be considered as restricted;
- if the value of the summary condition "calling user is notified of diversion" is "yes, with diverted-to number", the presentation shall be according to the received presentation indicator.

5.18.2.2 Exceptional procedures

No impact.

5.18.3 Procedures for interworking with private ISDNs

See clause 5.18.2.

5.19 The CD and COLR supplementary services

See clause 9.2.3.1 of EN 300 207-1 [17].

5.20 The CD and UUS supplementary services

The following procedures apply for incoming calls to a user subscribing to the CD supplementary service. This user is identified as the served user.

5.20.1 Coding requirements

See clause 5.23.1.

5.20.2 Signalling procedures at the coincident S and T reference point

Any User-to-User Information (UII) and/or UUS supplementary service request shall be delivered to the served user in the SET-UP message.

5.20.2.1 Procedures at the served user when deflection takes place before alerting

If the served user invokes call deflection before the ALERTING message has been received by the network, the following procedures apply.

5.20.2.1.1 Normal operation

Any UII and/or UUS supplementary service request that is contained in the incoming call request shall be deflected with the call.

However, as a network provider option, the deflection of the UII and/or UUS supplementary service request can be restricted to deflecting users who subscribe to the relevant UUS supplementary service.

If the network supports this option, and the deflecting user is not subscribed to the requested UUS supplementary service, and the calling user requested the service as essential, then the CD supplementary service shall not be invoked.

If the network supports this option, and the deflecting user is not subscribed to the requested UUS supplementary service, and the calling user requested the service as preferred or requested the service implicitly, the network shall not forward any UII and/or UUS supplementary service request with the deflected call.

NOTE: In the case of explicit request, since the request for the UUS supplementary service is not delivered to the deflected-to user, no response is received on the request. Consequently, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clauses 9.1.1.2.2, 9.2.1.2 or 9.3.1.1.2 of EN 300 286-1 [19].

5.20.2.1.2 Exceptional procedures

If the served user invokes call deflection in a situation where this is not allowed according to the procedures specified in clause 5.20.2.1.1, the network shall reject the request for invocation using the procedures described in clause 9.2.4.5.2 of EN 300 207-1 [17] with the error value "supplementaryServiceInteractionNotAllowed".

5.20.2.2 Procedures at the served user when deflection takes place after alerting

If the served user invokes call deflection after the ALERTING message has been received by the network, the following procedures apply.

5.20.2.2.1 Service 1 implicitly requested

5.20.2.2.1.1 Normal operation

The implicit service 1 request (i.e. the UII) that is contained in the incoming call request shall be deflected with the call.

However, as a network provider option, the deflection of the UII can be restricted to deflecting users who subscribe to the UUS service 1 supplementary service.

If the network supports this option, and the forwarding user is not subscribed to the UUS service 1 supplementary service, and the calling user requested the service implicitly, the network shall not forward any UII with the deflected call.

NOTE: If the deflected-to user provides UII together with the alerting indication, the UII will not be delivered to the calling user.

5.20.2.2.1.2 Exceptional procedures

No impact.

5.20.2.2.2 Service 1 explicitly requested

5.20.2.2.2.1 Normal operation

If the service is requested as required, the CD supplementary service shall not be invoked for this call.

If the service is requested as preferred, the following procedures apply:

- if the served user accepts the service request in the ALERTING message, then as a network provider option:
 - a) the service acceptance, received from the served user, shall be delivered to the calling user and the CD supplementary service shall not be invoked for this call; or
 - b) the service acceptance, received from the served user, shall be delivered to the calling user and the CD supplementary service can be invoked. When the CD supplementary service is invoked, the UUS supplementary service request and the UII, if any, shall be deflected with the call.

NOTE 1: If the deflected-to user includes service acceptance or rejection in the alerting or connect indication, this acceptance/rejection will not be delivered to the calling user.

NOTE 2: If the deflected-to user does not accept the UUS request, any UII sent by the calling user during call clearing will be discarded by the diverted-to network as the UUS supplementary service is not activated.

NOTE 3: If the deflected-to user provides UII together with the alerting indication, the UII will not be delivered to the calling user.

NOTE 4: If the deflected-to user provides UII together with the connect indication, the UII will be delivered to the calling user according to procedures specified in clause 9.1.2.1 of EN 300 286-1 [19].

However, as a network provider option, the deflection of the UUS supplementary service request and the UII, if any, can be restricted to deflecting users who subscribe to the UUS service 1 supplementary service.

If the network supports this option, and the deflecting user is not subscribed to the UUS service 1 supplementary service, the network shall not invoke the CD supplementary service.

- if the served user rejects the service request in the ALERTING message, then the rejection shall be delivered to the calling user and the CD supplementary service can be invoked. The call shall be deflected without the UUS supplementary service request and UII, if any;
- if the served user does not include a response related to the UUS supplementary service request in the ALERTING message, then the CD supplementary service can be invoked. The call shall be deflected without the UUS supplementary service request and UII, if any.

NOTE 5: As the UUS supplementary service request is ignored, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clause 9.1.1.2.2 of EN 300 286-1 [19].

5.20.2.2.2.2 Exceptional procedure

If the served user invokes call deflection in a situation where this is not allowed according to the procedures specified in clause 5.20.2.2.2.1, the network shall reject the request for invocation using the procedures described in clause 9.2.4.5.2 of EN 300 207-1 [17] with the error value "supplementaryServiceInteractionNotAllowed".

5.20.2.2.3 Service 2

5.20.2.2.3.1 Normal operation

If the service is requested as required, the CD supplementary service shall not be invoked for this call.

If the service is requested as preferred, the following procedures apply:

- if the served user accepts the service request in the ALERTING message, then the service acceptance, received from the served user, shall be delivered to the calling user and the CD supplementary service shall not be invoked for this call;
- if the served user rejects the service request in the ALERTING message, then the rejection shall be delivered to the calling user and the CD supplementary service can be invoked. The call shall be deflected without the UUS supplementary service request;
- if the served user ignores the UUS service request in the ALERTING message, then the CD supplementary service can be invoked. The call shall be deflected without the UUS supplementary service request.

NOTE: As the UUS supplementary service request is ignored, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clause 9.2.1.2 of EN 300 286-1 [19].

5.20.2.2.3.2 Exceptional procedures

If the served user invokes call deflection in a situation where this is not allowed according to the procedures specified in clause 5.20.2.2.3.1, the network shall reject the request for invocation using the procedures described in clause 9.2.4.5.2 of EN 300 207-1 [17] with the error value "supplementaryServiceInteractionNotAllowed".

5.20.2.2.4 Service 3

5.20.2.2.4.1 Normal operation

A UUS supplementary service request that is contained in the incoming call request shall be deflected with the call.

However, as a network provider option, the deflection of the UUS supplementary service request can be restricted to deflecting users who subscribe to the UUS service 3 supplementary service.

If the network supports this option, and the deflecting user is not subscribed to the UUS service 3 supplementary service, and the calling user requested the service as essential, the CD supplementary service shall not be invoked.

If the network supports this option, and the deflecting user is not subscribed to the UUS service 3 supplementary service, and the calling user requested the service as preferred, the network shall not forward the UUS service 3 supplementary service request with the deflected call.

NOTE: In this case, since the request for the UUS service 3 supplementary service is not given to the deflected-to user, no response is received on the request. Consequently, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clause 9.3.1.1.2 of EN 300 286-1 [19].

5.20.2.2.4.2 Exceptional procedures

If the served user invokes call deflection in a situation where this is not allowed according to the procedures specified in clause 5.20.2.2.4.1, the network shall reject the request for invocation using the procedures described in clause 9.2.4.5.2 of EN 300 207-1 [17] with the error value "supplementaryServiceInteractionNotAllowed".

5.20.3 Procedures for interworking with private ISDNs

5.20.3.1 Procedures where the CD supplementary service applies to the whole private ISDN

The procedures in clauses 5.20.2 shall apply.

5.20.3.2 Procedures where partial rerouteing takes place

When a call from the public network is diverted within or beyond the private network, and partial rerouteing takes place in the public network, then the procedures in clause 5.23.3.2 shall apply.

5.21 The CFB and COLP supplementary services

See clause 5.18.

5.22 The CFB and COLR supplementary services

See clause 9.2.3.1 of EN 300 207-1 [17].

5.23 The CFB and UUS supplementary services

The following procedures apply for calls incoming to a user with the CFB supplementary service activated. This user is identified as the served user.

5.23.1 Coding requirements

Table 3 shows the definition of the operation UUSRequest using ASN.1 as defined in either ITU-T Recommendation X.208 [33] or ITU-T Recommendation X.680 [37] and using the OPERATION macro as defined in either ITU-T Recommendation X.219 [34] or ITU-T Recommendation X.690 [38], figure 4/X.219.

The formal definition of component type to encode this operation is provided in EN 300 196-1 [16], annex D, clause D.1.

The inclusion of components in Facility information elements is defined in EN 300 196-1 [16], clause 11.2.2.1.

Table 3: ASN.1 description of the UUSRequest operation

Diversion-Operations {ITU-T identified-organization etsi(0) 195 diversion-operations(4)}		
DEFINITIONS EXPLICIT TAGS ::=		
BEGIN		
EXPORTS	UUSRequest;	
IMPORTS	OPERATION FROM Remote-Operation-Notation {joint-iso-ITU-T remote-operation(4) notation(0)}	
	Service, Preferred FROM UUS-Operations {ITU-T identified-organization etsi(0) 286 operations-and-errors(1)};	
UUSRequest	::= OPERATION ARGUMENT SEQUENCE { [1] IMPLICIT Service, [2] IMPLICIT Preferred}	
uUSRequest	UUSRequest	::= localValue 66
END -- of Diversion-Operations		

5.23.2 Signalling procedures at the coincident S and T reference point

If the served user is not network determined user busy, any UII and/or request for a UUS supplementary service shall be delivered to the served user in the SET-UP message.

5.23.2.1 Normal operation

Any UII and/or request for a UUS supplementary service that is contained in the incoming call request shall be forwarded with the call.

However, as a network provider option, the forwarding of the UII and/or UUS supplementary service request can be restricted to forwarding users who subscribe to the relevant UUS supplementary service.

If the network supports this option, and the forwarding user is not subscribed to the requested UUS supplementary service, and the calling user requested the service as essential, the CFB supplementary service shall not be invoked. The network shall initiate call clearing to the calling user using cause #29, "facility rejected".

If the network supports this option, and the forwarding user is not subscribed to the requested UUS supplementary service, and the calling user requested the service as preferred or requested the service implicitly, the network shall not forward any UII and/or UUS supplementary service request with the forwarded call.

NOTE: In the case of explicit request, since the request for the UUS supplementary service request is not delivered to the forwarded-to user, no response is received on the request. Consequently, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clauses 9.1.1.2.2, 9.2.1.2 or 9.3.1.1.2 of EN 300 286-1 [19].

If, in case of user determined user busy, the served user includes UII and/or UUS service 1 supplementary service response in one or more DISCONNECT, RELEASE or RELEASE COMPLETE messages, the UII and/or UUS service 1 supplementary service response shall be discarded by the network without any indication to the served user.

5.23.2.2 Exceptional procedures

No impact.

5.23.3 Procedures for interworking with private ISDNs

5.23.3.1 Procedures where the CFB supplementary service applies to the whole private ISDN

The procedures in clause 5.23.2 shall apply.

5.23.3.2 Procedures where partial rerouting takes place

When a call from the public network is diverted within or beyond the private network, and partial rerouting takes place in the public network, then the following procedures shall apply.

5.23.3.2.1 Normal operation

When a private network invokes the partial rerouting, the private network sends a FACILITY message to the network including a CallRerouting invoke component according to the procedures specified in clause 10.5 of EN 300 207-1 [17].

If the private network wants to divert a request for the implicitly requested UUS service 1 supplementary service along with the call, the private network shall include the UII in the q931InfoElement parameter contained in the CallRerouting invoke component.

When the network receives the UII in the CallRerouting invoke component, it shall include the UII in the call request towards the diverted-to user.

If the private network wants to divert a request for an explicitly requested UUS supplementary service along with the call, the private network shall send the UUSRequest invoke component to the network. In order to associate the UUSRequest invoke component with the call to be diverted, the private network shall include the UUSRequest invoke component in the same FACILITY message that contains the CallRerouting component.

The UUSRequest invoke component shall include:

- in the Service parameter the type of UUS supplementary service, i.e. service 1 (value "service1"), service 2 (value "service2") or service 3 (value "service3");
- in the Preferred parameter whether the UUS supplementary service request is preferred (value "TRUE") or required (value "FALSE").

In addition, in the case of explicitly requested service 1, the UI, if any, shall be included in the q931InfoElement parameter contained in the CallRerouting invoke component.

When the network receives the UUSRequest invoke component, it shall include the request for the UUS supplementary service in the call request towards the diverted-to user.

NOTE 1: It is the responsibility of the private network to ensure that the interaction between the relevant diversion supplementary service and the relevant UUS supplementary service is appropriate.

If the private network does not want to divert an explicit request for the UUS supplementary service, the UUSRequest invoke component shall not be sent to the network. If the network does not receive a UUSRequest invoke component, it shall not include a request for the UUS supplementary service in the call request towards the diverted-to user.

NOTE 2: If, in this case, the calling user has not received a response on the UUS request, the network will reject the UUS supplementary service request according to clauses 9.1.1.2.2, 9.2.1.2 or 9.3.1.1.2 of EN 300 286-1 [19] since no request is sent to the diverted-to user.

However, as a network provider option, the rerouting of the UI and/or request of the UUS supplementary service can be restricted to users who subscribe to the relevant UUS supplementary service.

If the network supports this option, and the private network that invoked call rerouting is not subscribed to the requested UUS supplementary service, then the public network shall ignore the UUS service request and shall not forward it with the deflected call.

NOTE 3: In the case of explicit request, since the request for the UUS supplementary service request is not delivered to the forwarded-to user, no response is received on the request. Consequently, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clauses 9.1.1.2.2, 9.2.1.2 or 9.3.1.1.2 of EN 300 286-1 [19].

5.23.3.2.2 Exceptional procedures

Not applicable.

5.24 The CFNR and COLP supplementary services

See clause 5.18.

5.25 The CFNR and COLR supplementary services

See clause 9.2.3.1 of EN 300 207-1 [17].

5.26 The CFNR and UUS supplementary services

The following procedures apply for calls incoming to a user with the CFNR supplementary service activated. This user is identified as the served user.

5.26.1 Coding requirements

See clause 5.23.1.

5.26.2 Signalling procedures at the coincident S and T reference point

Any UUI and/or UUS supplementary service request that is contained in the incoming call request shall be delivered to the served user in the SET-UP message.

5.26.2.1 Service 1 implicitly requested

5.26.2.1.1 Normal operation

The implicit service 1 request (i.e. the UUI) that is contained in the incoming call request shall be forwarded with the call.

However, as a network provider option, the forwarding of the UUI can be restricted to forwarding users who subscribe to the UUS service 1 supplementary service.

If the network supports this option, and the forwarding user is not subscribed to the UUS service 1 supplementary service, and the calling user requested the service implicitly, the network shall not forward UUI with the forwarded call.

NOTE: If the forwarded-to user provides UUI together with the alerting indication, the UUI will not be delivered to the calling user.

5.26.2.1.2 Exceptional procedures

No impact.

5.26.2.2 Service 1 explicitly requested

5.26.2.2.1 Normal operation

If the service is requested as required, the CFNR supplementary service shall not be invoked for this call.

If the service is requested as preferred, the following procedures apply:

- if the served user accepts the service request in the ALERTING message, then as a network provider option:
 - a) the service acceptance, received from the served user, shall be delivered to the calling user and the CFNR supplementary service shall not be invoked for this call; or
 - b) the service acceptance, received from the served user, shall be delivered to the calling user and the CFNR supplementary service can be invoked. When the CFNR supplementary service is invoked, the UUS supplementary service request and the UUI, if any, shall be forwarded with the call.

NOTE 1: If the forwarded-to user includes service acceptance or rejection in the alerting or connect indication, this acceptance/rejection will not be delivered to the calling user.

NOTE 2: If the forwarded-to user does not accept the UUS request, any UUI sent by the calling user during call clearing will be discarded by the diverted-to network as the UUS supplementary service is not activated at the forwarded-to user.

NOTE 3: If the forwarded-to user provides UUI together with the alerting indication, the UUI will not be delivered to the calling user.

NOTE 4: If the forwarded-to user provides UUI together with the connect indication, the UUI will be delivered to the calling user according to the procedures specified in clause 9.1.2.1 of EN 300 286-1 [19].

However, as a network provider option, the forwarding of the UUS supplementary service request and the UI, if any, can be restricted to forwarding users who subscribe to the UUS service 1 supplementary service.

If the network supports this option, and the forwarding user is not subscribed to the requested UUS supplementary service, the network shall not invoke the CFNR supplementary service.

- if the served user rejects the service request in the ALERTING message, then the rejection shall be delivered to the calling user and the CFNR supplementary service can be invoked. The call shall be forwarded without the UUS supplementary service request and UI, if any;
- if the served user does not include a response related to the UUS supplementary service request in the ALERTING message, then the CFNR supplementary service can be invoked. The call shall be forwarded without the UUS supplementary service request and UI, if any.

NOTE 5: As the UUS supplementary service request is ignored, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clause 9.1.1.2.2 of EN 300 286-1 [19].

5.26.2.2.2 Exceptional procedures

No impact.

5.26.2.3 Service 2

5.26.2.3.1 Normal operation

If the service is requested as required, the CFNR supplementary service shall not be invoked for this call.

If the service is requested as preferred, the following procedures apply:

- if the served user accepts the service request in the ALERTING message, then the service acceptance, received from the served user, shall be delivered to the calling user and the CFNR supplementary service shall not be invoked for this call;
- if the served user rejects the service request in the ALERTING message, then the rejection shall be delivered to the calling user and the CFNR supplementary service can be invoked. The call shall be forwarded without the UUS supplementary service request;
- if the served user ignores the UUS service request in the ALERTING message, then the CFNR supplementary service can be invoked. The call shall be forwarded without the UUS supplementary service request.

NOTE: As the UUS supplementary service request is ignored, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clause 9.2.1.2 of EN 300 286-1 [19].

5.26.2.3.2 Exceptional procedures

No impact.

5.26.2.4 Service 3

5.26.2.4.1 Normal operation

Any UUS supplementary service request that is contained in the incoming call request shall be forwarded with the call.

However, as a network provider option, the forwarding of the UUS supplementary service request can be restricted to forwarding users who subscribe to the UUS service 3 supplementary service.

If the network supports this option, and the forwarding user is not subscribed to the UUS service 3 supplementary service, and the calling user requested the service as essential, the network shall not invoke the CFNR supplementary service.

If the network supports this option, and the forwarding user is not subscribed to the UUS service 3 supplementary service, and the calling user requested the service as preferred or requested the service implicitly, the network shall not forward any UI and/or UUS supplementary service request with the forwarded call.

NOTE: In this case, since the request for the UUS service 3 supplementary service is not given to the forwarded-to user, no response is received on the request. Consequently, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clause 9.3.1.1.2 of EN 300 286-1 [19].

5.26.2.4.2 Exceptional procedures

No impact.

5.26.3 Procedures for interworking with private ISDNs

5.26.3.1 Procedures where the CFNR supplementary services applies to the whole private ISDN

The procedures in clause 5.26.2 shall apply.

5.26.3.2 Procedures where partial rerouteing takes place

When a call from the public network is diverted within or beyond the private network, and partial rerouteing takes place in the public network, then the procedures in clause 5.23.3.2 shall apply.

5.27 The CFU and COLP supplementary services

See clause 5.18.

5.28 The CFU and COLR supplementary services

See clause 9.2.3.1 of EN 300 207-1 [17].

5.29 The CFU and UUS supplementary services

The following procedures apply for calls incoming to a user with the CFU supplementary service activated. This user is identified as the served user.

5.29.1 Coding requirements

See clause 5.23.1.

5.29.2 Signalling procedures at the coincident S and T reference point

5.29.2.1 Normal operation

Any UI and/or request for a UUS supplementary service that is contained in the incoming call request shall be forwarded with the call.

However, as a network provider option, the forwarding of the UI and/or UUS supplementary service request can be restricted to forwarding users who subscribe to the relevant UUS supplementary service.

If the network supports this option, and the forwarding user is not subscribed to the requested UUS supplementary service, and the calling user requested the service as essential, the network shall not invoke the CFU supplementary service. The network shall initiate call clearing towards the calling user using the cause #29, "facility rejected".

If the network supports this option, and the forwarding user is not subscribed to the requested UUS supplementary service, and the calling user requested the service as preferred or requested the service implicitly, the network shall not forward any UI and/or UUS supplementary service request with the forwarded call.

NOTE: In the case of explicit request, since the request for the UUS supplementary service request is not delivered to the forwarded-to user, no response is received on the request. Consequently, the network will reject the UUS supplementary service request towards the calling user according to the procedures specified in clauses 9.1.1.2.2, 9.2.1.2 or 9.3.1.1.2 of EN 300 286-1 [19].

5.29.2.2 Exceptional procedures

No impact.

5.29.3 Procedures for interworking with private ISDNs

5.29.3.1 Procedures where the CFU supplementary service applies to the whole private ISDN

The procedures in clause 5.29.2 shall apply.

5.29.3.2 Procedures where partial rerouteing takes place

When a call from the public network is diverted within or beyond the private network, and partial rerouteing takes place in the public network, then the procedures in clause 5.23.3.2 shall apply.

5.30 The TP and 3PTY supplementary services

5.30.1 Coding requirements

No impact.

5.30.2 Signalling procedures at the coincident S and T reference point

5.30.2.1 Served user uses the TP supplementary service

5.30.2.1.1 Normal operation

No impact.

NOTE: The invocation of the TP supplementary service is not allowed for the served user of the 3PTY supplementary service.

5.30.2.1.2 Exceptional procedures

If, within the TP supplementary service, the network refuses a request to suspend a call, because the call is part of a three-way conversation controlled by the same served user (local interaction for the call), or because another call for that CEI is part of a three-way conversation controlled by the same served user (local interaction for the CEI), the SUSPEND REJECT message shall contain cause value #29, "facility rejected".

5.30.2.2 Remote user of the TP supplementary service uses the 3PTY supplementary service

5.30.2.2.1 Normal operation

If, within the TP supplementary service, the served user has suspended a call, the network cannot send notifications to the served user that are caused by operation of the 3PTY supplementary service (remote interaction).

The network shall discard these notifications and shall not retain these for later delivery.

5.30.2.2.2 Exceptional procedures

No impact.

5.30.3 Procedures for interworking with private ISDNs

No impact.

5.31 The HOLD and TP supplementary services

5.31.1 Coding requirements

No impact.

5.31.2 Signalling procedures at the coincident S and T reference point

5.31.2.1 Served user of the HOLD supplementary service uses the TP supplementary service

5.31.2.1.1 Normal operation

No impact.

NOTE: The invocation of the TP supplementary service is not allowed for the served user of the HOLD supplementary service.

5.31.2.1.2 Exceptional procedures

If, within the TP supplementary service, the network refuses a request to suspend a call e.g., because the call is in the Call Held auxiliary state (local interaction for the call), or because another call for that CEI is in the Call Held auxiliary state (local interaction for the CEI), the SUSPEND REJECT message shall contain cause value #29, "facility rejected".

5.31.2.2 Remote user of the HOLD supplementary service uses the TP supplementary service

No impact.

5.31.2.3 Remote user of the TP supplementary service uses the HOLD supplementary service

5.31.2.3.1 Normal operation

If, within the TP supplementary service, the served user has suspended a call, the network cannot send notifications to the served user that are caused by operation of the HOLD supplementary service (remote interaction).

The network shall discard these notifications and shall not retain these for later delivery.

5.31.2.3.2 Exceptional procedures

No impact.

5.31.3 Procedures for interworking with private ISDNs

No impact.

NOTE: The invocation of the HOLD and TP supplementary service by the private network is not possible.

5.32 The HOLD and 3PTY supplementary services

Any party involved in a three-way conversation is able to put the connection to the three-way conversation on hold and later retrieve it.

5.32.1 Coding requirements

No impact.

5.32.2 Signalling procedures at the coincident S and T reference point

5.32.2.1 Creating a three-way conversation from a held call

No impact.

5.32.2.2 Holding a three-way conversation

In order to hold a three-way conversation (local interaction for the call), the procedures of EN 300 141-1 [12], clauses 9.1 and 9.2 shall apply with the following exceptions:

- a) the Hold function shall be used only for the Active-Idle connection; and
- b) the NOTIFY message, containing a Notification indicator information element with a description of "Remote hold" shall be sent to neither of the remote users.

5.32.2.3 Retrieving a three-way conversation

In order to retrieve a three-way conversation (local interaction for the call), the procedures of EN 300 141-1 [12], clauses 9.3 and 9.4 shall apply with the following exceptions:

- a) the Retrieve function shall be used on only one of the two Active-Held connections;
- b) the NOTIFY message, containing a Notification indicator description information element with a notification description of "Remote retrieval", shall be sent to neither of the remote users; and
- c) if an attempt is made to perform the Retrieve function on the remaining Active-Held connection, then the Retrieve function shall be rejected according to the procedures of EN 300 196-1 [16], clause 7.4.2.2, with cause #29 "Facility rejected".

5.32.3 Procedures for interworking with private ISDNs

No impact.

5.33 The CUG and 3PTY supplementary services

5.33.1 Coding requirements

No impact.

5.33.2 Signalling procedures at the coincident S and T reference point

5.33.2.1 Creating a three-way conversation

5.33.2.1.1 Normal operation

No impact.

5.33.2.1.2 Exceptional procedures

If, within the 3PTY supplementary service, the network refuses a request to join two calls because the constituent calls were requested using different closed user groups, the Begin3PTY return error component shall contain the error "supplementaryServiceInteractionNotAllowed".

5.33.3 Procedures for interworking with private ISDNs

No impact.

5.34 The ECT and MCID supplementary services

5.34.1 Coding requirements

No impact.

5.34.2 Signalling procedures at the coincident S and T reference point

5.34.2.1 Normal operation

No impact.

5.34.2.2 Exceptional procedures

If the served user of the ECT supplementary service invokes the MCID supplementary service, according to clause 9.2.1 of EN 300 130-1 [10], after the call has been transferred (local interaction for the same call), then the network shall reject the request according to clause 9.2.2 of EN 300 130-1 [10]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

5.35 The ECT and 3PTY supplementary services

5.35.1 Coding requirements

No impact.

5.35.2 Signalling procedures at the coincident S and T reference point

5.35.2.1 Transfer of a three-way conversation

5.35.2.1.1 Normal operation

No impact.

NOTE: The served user can transfer the two calls involved in the three-way conversation by first terminating the three-way conversation and subsequently transferring the two calls.

5.35.2.1.2 Exceptional procedures

If the user invokes the ECT supplementary service using the implicit linkage procedures according to clause 9.2.1.1 of EN 300 369-1 [21], and the call is part of a three-way conversation controlled by the same served user (local interaction for the call), then the network shall reject the EctExecute invoke component according to clause 9.2.1.2 of EN 300 369-1 [21]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

If the user invokes the ECT supplementary service using the implicit linkage procedures according to clause 9.2.1.1 of EN 300 369-1 [21], and the call not on hold is part of a three-way conversation controlled by the same served user (local interaction for the call), then the network shall reject the EctExecute invoke component according to clause 9.2.1.2 of EN 300 369-1 [21]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

If the user invokes the ECT supplementary service using the explicit linkage procedures according to clause 9.2.2.1 of EN 300 369-1 [21], and either or both calls are part of a three-way conversation controlled by the same served user (local interaction for the call), then the network shall reject the ExplicitEctExecute invoke component according to clause 9.2.2.2 of EN 300 369-1 [21]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

The network shall not reject the EctLinkIdRequest invoke component due to the call being part of a three-way conversation controlled by the same user.

5.35.3 Procedures for interworking with private ISDNs

Not applicable.

5.36 The ECT and UUS supplementary services

When the networks serving the remote users (user B and user C) perform the procedures specified in EN 300 369-1 [21], clause 9.2.4.1 first paragraph, clause 9.2.5.1 first paragraph and clause 10.2.1 third paragraph, then, in addition to those procedures, any UUS supplementary service that has previously been activated shall be cancelled by the networks.

If, in this case, the remote network receives a call control message or a USER INFORMATION message with a User-user information element from the remote user, this UUS supplementary service related information shall be discarded by the network without any indication to the remote user.

If the transferred call is in the active state, UUS service 3 may be renegotiated by the remote users according to the procedures specified in EN 300 286-1 [19] clause 9.3.1.2.

5.37 The CCBS and UUS supplementary services

5.37.1 Coding requirements

No impact.

5.37.2 Signalling procedures at the coincident S and T reference point

5.37.2.1 Normal operation

The network shall not store any information related to the UUS supplementary service provided by the calling user in the original call, neither the request(s) for activation nor the user-to-user information for UUS service 1.

If the SET-UP message received from user A for invocation of the CCBS call contains information related to the UUS supplementary service, this shall be treated as normal handling of the UUS supplementary service procedures.

5.37.2.2 Exceptional procedures

No impact.

5.37.3 Procedures for interworking with private ISDNs

The procedures as described in clause 5.37.2 shall apply.

5.38 The CCBS and CLIP supplementary services

5.38.1 Coding requirements

No impact.

5.38.2 Signalling procedures at the coincident S and T reference point

5.38.2.1 Normal operation

The use of the calling line identity at the originating network, although provided as part of basic call, is documented in EN 300 092-1 [6], clauses 9.3 and 9.4. The following interaction exists with these procedures.

The calling line identity, whether network provided, user provided and screened, or user provided and not screened (i.e. a special arrangement exists) from the original call shall be retained by the originating network and used when the CCBS call is completed. Furthermore the calling line identity shall be used by the network to determine duplicate calls as specified in clause 9.1.2 of EN 300 359-1 [20].

5.38.2.2 Exceptional procedures

The network shall ignore any calling line identification provided by the calling user in the CCBS call.

5.38.3 Procedures for interworking with private ISDNs

5.38.3.1 Procedures for the originating T reference point

5.38.3.1.1 Normal operation

If the private network provides an originatingAddress in the CCBS-T-Request invoke component, and the public network supports the originatingAddress, then the public network shall transfer the originatingAddress parameter to the destination network.

5.38.3.1.2 Exceptional procedures

Not applicable.

5.38.3.2 Procedures for the destination T reference point

5.38.3.2.1 Normal operation

If a calling party address is available, and the network supports the originatingAddress in the CCBS-T-Request invoke component, and the user subscribes to the CLIR supplementary service, then the network shall include the originatingAddress in the CCBS-T-Request invoke component, subject to any CLIR supplementary service restriction.

5.38.3.2.2 Exceptional procedures

Not applicable.

5.39 The CCBS and CLIR supplementary services

5.39.1 Coding requirements

No impact.

5.39.2 Signalling procedures at the coincident S and T reference point

5.39.2.1 Normal operation

The CLIR supplementary service requirements from the original call shall be retained by the originating network and used when the CCBS call is completed.

5.39.2.2 Exceptional procedures

Not applicable.

5.39.3 Procedures for interworking with private ISDNs

5.39.3.1 Procedures for the originating T reference point

5.39.3.1.1 Normal operation

If the public network supports the originatingAddress parameter, then the following procedures shall apply:

- if the CLIR supplementary service is not provided, then the network shall ignore any PresentationAllowedIndicator in the CCBS-T-Request invoke component and shall not apply restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in permanent mode, then the network shall ignore any PresentationAllowedIndicator in the CCBS-T-Request invoke component and shall apply the appropriate restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in temporary mode and the PresentationAllowedIndicator is provided in the CCBS-T-Request invoke component and set to "true", then the network shall not apply restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in temporary mode and the PresentationAllowedIndicator is provided in the CCBS-T-Request invoke component and set to "false", then the network shall apply the appropriate restriction to the transfer of the calling address;

- if the CLIR supplementary service is provided in temporary mode and the PresentationAllowedIndicator is not provided in the CCBS-T-Request invoke component and the default is "presentation restricted", then the network shall apply the appropriate restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in temporary mode and the PresentationAllowedIndicator is not provided in the CCBS-T-Request invoke component and the default is "presentation allowed", then the network shall not apply restriction to the transfer of the calling address.

5.39.3.1.2 Exceptional procedures

Not applicable.

5.39.3.2 Procedures for the destination T reference point

5.39.3.2.1 Normal operation

If a calling party address is available in the public network and the network supports the originatingAddress in the CCBS-T-Request invoke component, and presentation is allowed, then the network shall include the originatingAddress and PresentationAllowedIndicator set to "true" in the CCBS-T-Request invoke component.

If a calling party address is available in the public network and the network supports the originatingAddress in the CCBS-T-Request invoke component, and presentation is not allowed, then the network shall not include the originatingAddress and PresentationAllowedIndicator in the CCBS-T-Request invoke component.

5.39.3.2.2 Exceptional procedures

Not applicable.

5.40 The CCBS and CUG supplementary services

5.40.1 Coding requirements

No impact.

5.40.2 Signalling procedures at the coincident S and T reference point

5.40.2.1 Normal operation

If the user subscribes to the CUG supplementary service, then the CUG requirements from the original call shall be retained by the served user's network and used when the call is completed.

The user shall not include a CUGCall invoke component in the SET-UP message used to establish the CCBS call.

5.40.2.2 Exceptional procedures

If the SET-UP message used to establish the CCBS call contains a CUGCall invoke component, this component shall be processed by the served user's network:

- if the CUG requirements of the original call and the CCBS call are identical, the CCBS call shall be established using the CUG supplementary service related information;
- if the CUG requirements of the original call and the CCBS call are not identical, the CCBS call shall be released. The first clearing message send to the served user shall contain a Facility information element containing a return error component indicating "invalidOrUnregisteredCUGIndex" and a Cause information element indicating cause #29 "facility rejected".

5.40.3 Procedures for interworking with private ISDNs

5.40.3.1 Procedure for the originating T reference point

5.40.3.1.1 Normal operation

If the original call was subject to CUG requirements, then the private network shall include the CUGCall invoke component in the SET-UP message used to establish the CCBS call.

On receipt of this invoke component the public network shall follow CUG supplementary service procedures according to EN 300 138-1 [11].

5.40.3.1.2 Exceptional procedures

No impact.

5.40.3.2 Procedures for the destination T reference point

No impact.

5.41 The CCBS and MSN supplementary services

5.41.1 Coding requirements

No impact.

5.41.2 Signalling procedures at the coincident S and T reference point

5.41.2.1 Procedures for the originating network

5.41.2.1.1 Normal operation

The CCBS supplementary service shall be provided to a user per multiple subscriber number.

If user A subscribes to the MSN supplementary service, and the user provides a valid multiple subscriber number in the Calling party number information element of the original call, then the network shall include the calling user's identity in a Called party number information element in the FACILITY message containing the CCBSErase, CCBSRemoteUserFree, CCBSBFree, and CCBSStatusRequest invoke components. Users not addressed by the calling user's identity shall ignore the FACILITY messages.

If user A subscribes to the MSN supplementary service, and has not provided a multiple subscriber number or has provided an invalid multiple subscriber number in the Calling party number information element of the original call, then the network shall include the calling user's identity as used for the original call in a Called party number information element in the FACILITY message containing the CCBSErase, CCBSRemoteUserFree, CCBSBFree, and CCBSStatusRequest invoke components. Users not addressed by the calling user's identity shall ignore the FACILITY messages.

If user A subscribes to the MSN supplementary service and interrogates the CCBS supplementary service related to a specific multiple subscriber number, then the user shall include the appropriate number in the "partyNumberOfA" parameter in the CCBSInterrogate invoke component. The CCBSInterrogate invoke component shall be included in the Facility information element, within the FACILITY message. The network shall only provide information on CCBS activations related to the number provided in the partyNumberOfA parameter.

NOTE: The information provided relates to the A queue to which CCBS activations are assigned which contained that calling party number in the original set-up request or were assigned to that number by default because no calling party number was provided.

5.41.2.1.2 Exceptional procedures

If the partyNumberOfA parameter is not provided, or if the content of the partyNumberOfA parameter is not valid in the CCBSInterrogate invoke component, then the information provided shall relate to the A queue to which also CCBS activations are assigned where the original SET-UP contained no calling party number.

5.41.2.2 Procedures for the remote network

5.41.2.2.1 Normal operation

If user B subscribes to the MSN supplementary service, then the network shall provide an incoming CCBS queue per multiple subscriber number, but the buffer is processed on a per-access basis (see EN 300 359-1 [20], clause 3).

5.41.2.2.2 Exceptional procedures

No impact.

5.41.3 Procedures for interworking with private ISDNs

No impact.

5.42 The CCBS and SUB supplementary services

5.42.1 Coding requirements

No impact.

5.42.2 Signalling procedures at the coincident S and T reference point

5.42.2.1 Normal operation

If user B subscribes to the SUB supplementary service, and called party subaddresses in the incoming call and the queued CCBS requests are available, then the network shall use the subaddresses in determining whether an incoming call and a queued CCBS request have identical destination selection information as given in clause 9.5.4.1 of EN 300 359-1 [20].

5.42.2.2 Exceptional procedures

No impact.

5.42.3 Procedures for interworking with private ISDNs

No impact.

5.43 The FPH and COLP supplementary services

5.43.1 Coding requirements

No impact.

5.43.2 Signalling procedures at the coincident S and T reference point

5.43.2.1 Procedure at the called user's network

5.43.2.1.1 Normal operation

The number digits, the screening indicator and the connected subaddress as determined by the procedures of clauses 9.3 and 9.4 of EN 300 210-1 [18] shall not be forwarded to the originating local exchange. Instead, the number digits in the connected number information element shall contain an ISDN number consisting of a service access code and the freephone number. The screening indicator shall indicate "network provided". No Connected subaddress information element shall be provided.

5.43.2.1.2 Exceptional procedures

No impact.

5.43.3 Procedures for interworking with private ISDNs

The procedures of clause 5.43.2 shall apply.

5.44 The ECT and CUG supplementary services

5.44.1 Coding requirements

No impact.

5.44.2 Signalling procedures at the coincident S and T reference point

5.44.2.1 Invocation of the ECT supplementary service

5.44.2.1.1 Normal operation

No impact.

5.44.2.1.2 Exceptional procedures

If the user requests a transfer of two calls using the implicit linkage procedures according to clause 9.2.1.1 of EN 300 369-1 [21], and the two calls were established with different closed user group requirements, then the network shall reject the request according to clause 9.2.1.2 of EN 300 369-1 [21]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

If the user requests a transfer of two calls using the explicit linkage procedures according to clause 9.2.2.1 of EN 300 369-1 [21], and the two calls were established with different closed user group requirements, then the network shall reject the request according to clause 9.2.2.2 of EN 300 369-1 [21]. The error shall indicate "supplementaryServiceInteractionNotAllowed".

The network shall not take into account any closed user group requirements on receiving an EctLinkIdRequest invoke component.

5.44.3 Procedures for interworking with private ISDNs

No impact.

5.45 The ECT and TP supplementary services

5.45.1 Coding requirements

No impact.

5.45.2 Signalling procedures at the coincident S and T reference point

5.45.2.1 Remote user of the TP supplementary service uses the ECT supplementary service

5.45.2.1.1 Normal operation

If, within the TP supplementary service, the served user has suspended a call, the network cannot send notifications to the served user that are caused by operation of the ECT supplementary service (remote interaction).

The network shall discard these notifications and shall not retain these for later delivery.

5.45.2.1.2 Exceptional procedures

No impact.

5.45.3 Procedures for interworking with private ISDNs

No impact.

5.46 The CONF and MCID supplementary services

5.46.1 Coding requirements

No impact.

5.46.2 Signalling procedures at the coincident S and T reference point

5.46.2.1 Normal operation

No impact.

5.46.2.2 Exceptional procedures

If, within the MCID supplementary service, the network is unable to identify and register the source of the incoming call, because this call is a conference call controlled by the same served user (local interaction for the call), the network shall send a MCIDRequest return error component to the served user, indicating the error "supplementaryServiceInteractionNotAllowed".

NOTE: Other error values are possible if supplementary service interactions are not checked first (e.g. a check for an incoming call is performed prior to any supplementary service interaction check).

5.46.3 Procedures for interworking with private ISDNs

See clause 5.46.2.

5.47 The CCBS and CW supplementary services

5.47.1 Coding requirements

No impact.

5.47.2 Signalling procedures at the coincident S and T reference point

5.47.2.1 Normal operation

CCBS requests in the destination CCBS queue shall only be processed if there are no calls waiting.

When an incoming CCBS call arrives at the access of user B and encounters the channels busy condition and a network determined user busy condition does not result, network B shall offer the CCBS call as a waiting call.

5.47.2.2 Exceptional procedures

If the CCBS call cannot be offered as a waiting call (e.g. a network determined user busy condition would result), destination B shall be considered busy again.

5.47.3 Procedures for interworking with private ISDNs

No impact.

5.48 The UUS and TP supplementary services

5.48.1 Coding requirements

No impact.

5.48.2 Signalling procedures at the coincident S and T reference point

5.48.2.1 Normal operation

If the served user of the UUS supplementary service sends a SUSPEND message to the network while UUS service 3 supplementary service is active, then the network shall acknowledge the TP request by sending a SUSPEND ACKNOWLEDGE message to the user. The network shall maintain the flow control procedure, i.e. timer T2-UUS3 shall continue to run. Any CONGESTION CONTROL message which should have been sent to the user while the call is suspended shall be sent after the RESUME ACKNOWLEDGE message has been sent.

5.48.2.2 Exceptional procedures

If the network receives a SUSPEND message after having received the UserUserService invoke component indicating the UUS service 3 supplementary service but having not yet responded to that UUS3 request, then the network shall reject the TP supplementary service request by sending a SUSPEND REJECT message with cause #29 "facility rejected" to the user (local interaction for the same call).

If the remote network (i.e. the network of the user who has activated the TP supplementary service) receives a request for activating the UUS service 3 supplementary service from the network serving the UUS user, then the remote network shall reject the UUS service 3 supplementary service request towards the network serving the user of the UUS service 3 supplementary service (remote interaction).

5.48.3 Procedures for interworking with private ISDNs

No impact.

5.49 The MWI and MSN supplementary services

5.49.1 Coding requirements

No impact.

5.49.2 Signalling procedures at the coincident S and T reference point

5.49.2.1 Normal operation

If the receiving user is subscribed to the MSN supplementary service, the MWI supplementary service can be activated and deactivated for each multiple subscriber number individually. The invocation of the MWI supplementary service shall take place individually for each multiple subscriber number. When invocation takes place and the receiving user is subscribed to the MSN supplementary service, the network shall include the Called party number information element in the FACILITY message used to convey the MWIIndicate invoke component(s) as specified in clause 8.3.2.4 of EN 300 196-1 [16]. The Called party number information element shall contain the ISDN number of the receiving user.

If the controlling user is subscribed to the MSN supplementary service, the MWI supplementary service can be activated and deactivated by each multiple subscriber number individually. The controlling user can indicate the ISDN number in the controllingUserNr parameter in the MWIActivate or MWIDeactivate invoke components.

5.49.2.2 Exceptional procedures

Not applicable.

5.49.3 Procedures for interworking with private ISDNs

No impact.

5.50 The OCB and CCBS supplementary services

5.50.1 Coding requirements

Not applicable.

5.50.2 Procedures at the coincident S and T reference point

5.50.2.1 Normal operation

When the OCB-F or OCB-UC supplementary service is activated after the served user activates the CCBS supplementary service, the normal OCB invocation procedures as described in clause 9.2 of EN 301 001-1 [25] shall be applied to the CCBS call.

When the OCB-UC supplementary service is activated before the served user activates the CCBS supplementary service, then the OCB-UC requirements (i.e. disabling) from the original call shall be retained by the served user's network and used when the call is completed.

The served user shall not include a DisableOcb invoke component in the SET-UP message used to establish the CCBS call.

When the served user performs a CCBS activation while OCB-F or OCB-UC is activated, the OCB invocation procedures shall not be applied to this CCBS activation request.

5.50.2.2 Exceptional procedures

If the SET-UP message used to establish the CCBS call contains a DisableOcb invoke component, this component shall be ignored.

5.50.3 Procedures for interworking with private ISDNs

5.50.3.1 Normal operation

When the OCB-F or OCB-UC supplementary service is activated after the served user activates the CCBS supplementary service, the normal OCB invocation procedures as described in clause 10 of EN 301 001-1 [25] shall be applied to the CCBS call.

If the SET-UP message of the original call contained a DisableOcb invoke component, then the private network shall include this same component in the SET-UP message used to establish the CCBS call.

5.50.3.2 Exceptional procedures

Not applicable.

5.51 The OCB and MSN supplementary services

5.51.1 Coding requirements

Not applicable.

5.51.2 Procedures at the coincident S and T reference point

5.51.2.1 Normal operation

If the OCB-F or OCB-UC supplementary service is provided on a per ISDN number basis, the network shall use the ISDN number resulting from the MSN supplementary service.

5.51.2.2 Exceptional procedures

Not applicable.

5.51.3 Procedures for interworking with private ISDNs

Not applicable.

5.52 The OCB and CFB supplementary services

5.52.1 Coding requirements

Not applicable.

5.52.2 Procedures at the coincident S and T reference point

5.52.2.1 Normal operation

When the network receives an ActivationDiversioN invoke component containing in the forwardedToAddress parameter an address that is to be barred according to the activated barring program for (any of) the instance(s) identified by the servedUserNr and basicService parameters, then the network shall reject the call forwarding activation request using the procedure in clause 9.1.1.2 of EN 300 207-1 [17]. The indicated error value shall be "supplementaryServiceInteractionNotAllowed".

NOTE: Activation of the OCB-UC supplementary service has no effect on currently active call forwarding supplementary services.

5.52.2.2 Exceptional procedures

Not applicable.

5.52.3 Procedures for interworking with private ISDNs

5.52.3.1 Procedures when the CFB supplementary service applies to the whole private ISDN

The procedures of clause 5.52.2 shall apply.

5.52.3.2 Procedures where partial rerouteing takes place

The procedures of clause 5.52.2 shall apply with the exception that the partial rerouteing invocation request shall be rejected using the procedures in clause 10.5.2 of EN 300 207-1 [17].

5.53 The OCB and CFNR supplementary services

See clause 5.52.

5.54 The OCB and CFU supplementary services

See clause 5.52.

5.55 Call deflection

5.55.1 Coding requirements

Not applicable.

5.55.2 Procedures at the coincident S and T reference point

5.55.2.1 Normal operation

When the network receives a CallDeflection invoke component containing in the deflectionAddress parameter an address that is to be barred according to the activated barring program for the instance identified by the call reference in the FACILITY message, then the network shall reject the call deflection invocation request using the procedure in clause 9.2.4.5.2 of EN 300 207-1 [17]. The indicated error value shall be "supplementaryServiceInteractionNotAllowed".

NOTE: The call reference in the FACILITY message containing the CallDeflection invoke component provides the means to find the basic service and the ISDN number the network has to use to check if a barring program is activated. The Called party number, Bearer capability and High layer compatibility information elements of the initial, related SET-UP message will be used for this purpose.

5.55.2.2 Exceptional procedures

Not applicable.

5.55.3 Procedures for interworking with private ISDNs

5.55.3.1 Procedures when the CD supplementary service applies to the whole private ISDN

The procedures of clause 5.55.2 shall apply.

5.55.3.2 Procedures where partial rerouteing takes place

The procedures of clause 5.55.2 shall apply with the exception that the partial rerouteing invocation request shall be rejected using the procedures in clause 10.5.2 of EN 300 207-1 [17].

5.56 The OCB-UC and the OCB-F supplementary services

No protocol impact.

If both the OCB-UC and the OCB-F supplementary services are activated, then an outgoing call shall be tested against the active barring program of each supplementary service before being allowed to proceed.

5.57 The CCNR and AOC supplementary services

The procedures in clause 5.3 shall apply.

5.58 The CCNR and CW supplementary services

The procedures in clause 5.47 shall apply.

5.59 The CCNR and CLIP supplementary services

5.59.1 Coding requirements

The procedures in clause 5.38.1 shall apply.

5.59.2 Signalling procedures at the coincident S and T reference point

The procedures in clause 5.38.2 shall apply.

5.59.3 Procedures for interworking with private ISDNs

5.59.3.1 Procedures for the originating T reference point

5.59.3.1.1 Normal operation

If the private network provides an originatingAddress in the CCNR-T-Request invoke component, and the public network supports the originatingAddress, then the public network shall transfer the originatingAddress parameter to the destination network.

5.59.3.1.2 Exceptional procedures

Not applicable.

5.59.3.2 Procedures for the destination T reference point

5.59.3.2.1 Normal operation

If a calling party address is available, and the network supports the `originatingAddress` in the `CCNR-T-Request` invoke component, and the user subscribes to the CLIP supplementary service, then the network shall include the `originatingAddress` in the `CCNR-T-Request` invoke component, subject to any CLIR supplementary service restriction.

5.59.3.2.2 Exceptional procedures

Not applicable.

5.60 The CCNR and CLIR supplementary services

5.60.1 Coding requirements

The procedures in clause 5.39.1 shall apply.

5.60.2 Signalling procedures at the coincident S and T reference point

The procedures in clause 5.39.2 shall apply.

5.60.3 Procedures for interworking with private ISDNs

5.60.3.1 Procedures for the originating T reference point

5.60.3.1.1 Normal operation

If the public network supports the `originatingAddress` parameter, then the following procedures shall apply:

- if the CLIR supplementary service is not provided, then the network shall ignore any `PresentationAllowedIndicator` in the `CCNR-T-Request` invoke component and shall not apply restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in permanent mode, then the network shall ignore any `PresentationAllowedIndicator` in the `CCNR-T-Request` invoke component and shall apply the appropriate restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in temporary mode and the `PresentationAllowedIndicator` is provided in the `CCNR-T-Request` invoke component and set to "true", then the network shall not apply restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in temporary mode, and the `PresentationAllowedIndicator` is provided in the `CCNR-T-Request` invoke component and set to "false", then the network shall apply the appropriate restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in temporary mode and the `PresentationAllowedIndicator` is not provided in the `CCNR-T-Request` invoke component and the default is "presentation restricted", then the network shall apply the appropriate restriction to the transfer of the calling address;
- if the CLIR supplementary service is provided in temporary mode and the `PresentationAllowedIndicator` is not provided in the `CCNR-T-Request` invoke component and the default is "presentation allowed", then the network shall not apply restriction to the transfer of the calling address.

5.60.3.1.2 Exceptional procedures

Not applicable.

5.60.3.2 Procedures for the destination T reference point

5.60.3.2.1 Normal operation

If a calling party address is available in the public network and the network supports the originatingAddress in the CCNR-T-Request invoke component, and presentation is allowed, then the network shall include the originatingAddress and PresentationAllowedIndicator set to "true" in the CCNR-T-Request invoke component.

If a calling party address is available in the public network and the network supports the originatingAddress in the CCNR-T-Request invoke component, and presentation is not allowed, then the network shall not include the originatingAddress and PresentationAllowedIndicator in the CCNR-T-Request invoke component.

5.60.3.2.2 Exceptional procedures

Not applicable.

5.61 The CCNR and CUG supplementary services

The procedures in clause 5.40 shall apply.

5.62 The CCNR and CCBS supplementary services

5.62.1 Coding requirements

No impact.

5.62.2 Signalling procedures at the coincident S and T reference point

5.62.2.1 Normal operation

NOTE 1: In addition to the definition of 'CCBS busy' given in clause 3 of EN 300 359-1 [20], the 'CCBS busy' condition is also caused when a CCNR recall is pending on user A.

NOTE 2: Only one network option "check for identical calls" exists for the CCNR and the CCBS supplementary service.

NOTE 3: Only one network option "CCBS request retention" exists for the CCNR and the CCBS supplementary service.

The cCBSReference parameter shall have significance on the whole access, i.e. a cCBSReference parameter value shall not be reused for subsequent CCNR or CCBS requests on an access before it is released.

5.62.2.2 Exceptional procedures

If the network A option "check for identical calls" is set to "yes", network A shall check if the call for which CCNR or CCBS is requested and a call in queue A are identical. If network A cannot accept the CCNR request because user A has already activated the CCBS supplementary service for an identical call placed in queue A, then network A shall send a CCNRRequest return error component indicating "cCBSIsAlreadyActivated" to user A, using the procedure in clause 10.2.2.2 of EN 300 196-1 [16]. If network A cannot accept the CCBS request because user A has already activated the CCNR supplementary service for an identical call placed in queue A, then network A shall send a CCBSRequest return error component indicating "cCBSIsAlreadyActivated" to user A, using the procedure in clause 10.2.2.2 of EN 300 196-1 [16].

NOTE 1: If the network option "check for identical calls" is set to "no", network A does not check if CCNR is requested for a call identical to a call for which CCBS is already activated and vice versa.

If network B cannot establish the CCNR call because user B is busy and the network option "CCBS request retention" is either set to "yes" or to "no", then in addition to the procedures described in clause 9.4.3.2 of EN 301 065-1 [26], for the activation of the CCBS supplementary service the procedures in clause 9.1.1 of EN 300 359-1 [20] shall apply.

NOTE 2: If the network option "CCBS request retention" is set to "no", then the CCBS supplementary service can be activated independent of the value set for the network option "check for identical calls."

NOTE 3: On receiving in response to a CCBS call an indication that user alerting has been initiated at the called address, the CCNR supplementary service can be activated according to the procedures described in clause 9.1.1 of EN 301 065-1 [26] independent of the value set for the network option "check for identical calls."

5.62.3 Procedures for interworking with private ISDNs

5.62.3.1 Normal operation

Not applicable.

5.62.3.2 Exceptional procedures

Not applicable.

5.63 The CCNR and MSN supplementary services

5.63.1 Coding requirements

No impact.

5.63.2 Signalling procedures at the coincident S and T reference point

5.63.2.1 Normal operation

The CCNR supplementary service shall be provided to a user per multiple subscriber number.

If user A subscribes to the MSN supplementary service, and the user provides a valid multiple subscriber number in the Calling party number information element of the original call, then the network shall include the calling user's identity in a Called party number information element in the FACILITY message containing the CCBSERase, CCBSRemoteUserFree, CCBSBFree and CCBSStatusRequest invoke components. Users not addressed by the calling user's identity shall ignore the FACILITY messages.

If user A subscribes to the MSN supplementary service, and has not provide a multiple subscriber number or has provided an invalid multiple subscriber number in the Calling party number information element of the original call, then the network shall include the calling user's identity as used for the original call in a Called party number information element in the FACILITY message containing the CCBSERase, CCBSRemoteUserFree, CCBSBFree and CCBSStatusRequest invoke components. Users not addressed by the calling user's identity shall ignore the FACILITY messages.

If user A subscribes to the MSN supplementary service and interrogates the CCNR supplementary service related to a specific multiple subscriber number, then the user shall include the appropriate number in the "partyNumberOfA" parameter in the CCNRInterrogate invoke component. The CCNRInterrogate invoke component shall be included in the Facility Information element, within the FACILITY message. The network shall only provide information on CCNR activations related to the number provided in the partyNumberOfA parameter.

NOTE: The information provided relates to the A queue to which CCNR activations are assigned which contained that calling party number in the original set-up request or were assigned to that number by default because no calling party number was provided.

5.63.2.2 Exceptional procedures

If the partyNumberOfA parameter is not provided, or if the content of the partyNumberOfA parameter is not valid in the CCNRInterrogate invoke component, then the information provided shall relate to the A queue to which also CCNR activations are assigned where the original SET-UP message contained no calling party number.

5.63.3 Procedures for the remote network

5.63.3.1 Normal operation

If user B subscribes to the MSN supplementary service, then the network shall apply queue B of the CCNR supplementary service per multiple subscriber number, but the buffer is processed on a per-access basis (see EN 301 065-1 [26], clause 3).

5.63.3.2 Exceptional procedures

No impact.

5.63.4 Procedures for interworking with private ISDNs

No impact.

5.64 The CCNR and SUB supplementary services

The procedures in clause 5.42 shall apply.

5.65 The CCNR and UUS supplementary services

The procedures in clause 5.37 shall apply.

5.66 The CCNR and OCB supplementary services

The procedures in clause 5.50 shall apply.

5.67 The OCB and SCF supplementary services

5.67.1 Coding requirements

Not applicable.

5.67.2 Procedures at the coincident S and T reference point

5.67.2.1 Normal operation

When the network receives an ActivationSCF invoke component containing in the forwardedToAddress parameter an address that is to be barred according to the activated barring program for (any of) the instance(s) identified by the servedUserNr and basicService parameters, then the network shall reject the selective call forwarding activation request using the procedure in clause 9.1.1.4 of EN 300 207-1 [17]. The indicated error value shall be "supplementaryServiceInteractionNotAllowed".

NOTE: Activation of the OCB-UC supplementary service has no effect on currently active call forwarding supplementary services.

5.67.2.2 Exceptional procedures

Not applicable.

5.67.3 Procedures for interworking with private networks

The procedures of clause 5.67.2 shall apply.

5.68 The LH and the CCBS supplementary services

5.68.1 Coding requirements

Not applicable.

5.68.2 Procedures at the coincident S and T reference point

5.68.2.1 Normal operation

The completion of calls to busy subscriber supplementary service can be activated on calls towards a hunt group, or to the individual access defined by its individual number. A hunt group member who originates a call with the individual number as the calling party number will be able to activate the CCBS supplementary service if it is subscribed to. It should not be possible to subscribe a hunt group number to the CCBS supplementary service.

NOTE: If completion of calls on busy supplementary service is invoked from a hunt group member and the hunt group number is given as the calling party number then the CCBS recall may not be returned to the originator of the CCBS request.

5.68.2.2 Exceptional procedures

Not applicable.

5.68.3 Procedures for interworking with private networks

The procedures of clause 5.68.2 shall apply.

5.69 The LH and the CCNR supplementary services

5.69.1 Coding requirements

Not applicable.

5.69.2 Procedures at the coincident S and T reference point

5.69.2.1 Normal operation

The completion of calls on no reply supplementary service can be activated on calls towards a hunt group, or to the individual access defined by its individual number. A hunt group member who originates a call with the individual number as the calling party number will be able to activate the CCNR supplementary service if it is subscribed to. It should not be possible to subscribe a hunt group number to the CCNR supplementary service.

NOTE: If completion of calls on no reply supplementary service is invoked from a hunt group member and the hunt group number is given as the calling party number then the CCNR recall may not be returned to the originator of the CCNR request.

5.69.2.2 Exceptional procedures

Not applicable.

5.69.3 Procedures for interworking with private networks

The procedures of clause 5.69.2 shall apply.

5.70 The LH and the CFU supplementary services

5.70.1 Coding requirements

Not applicable.

5.70.2 Procedures at the coincident S and T reference point

5.70.2.1 Normal operation

When the call forwarding unconditional supplementary service has been activated, then the call forwarding unconditional supplementary service shall take precedence over the LH supplementary service.

If the call forwarding unconditional supplementary service has been activated, a notification that the call has been forwarded shall not be given to the served user.

5.70.2.2 Exceptional procedures

Not applicable.

5.70.3 Procedures for interworking with private networks

The procedures of clause 5.70.2 shall apply.

5.71 The LH and CFB supplementary services

5.71.1 Coding requirements

Not applicable.

5.71.2 Procedures at the coincident S and T reference point

5.71.2.1 Normal operation

When the call forwarding busy supplementary service has been activated, then the call forwarding busy supplementary service shall be invoked, when:

- all accesses are either network determined user busy or withdrawn from the hunt group; or
- the selected access is user determined user busy.

If the call forwarding busy supplementary service has been activated as result of network determined user busy, a notification that the call has been forwarded shall not be given to the served user.

If the call forwarding busy supplementary service has been activated as result of user determined user busy, a notification that the call has been forwarded shall be sent to the access to which the call has been presented.

5.71.2.2 Exceptional procedures

Not applicable.

5.71.3 Procedures for interworking with private networks

The procedures of clause 5.71.2 shall apply.

5.72 The LH and the CFNR supplementary services

5.72.1 Coding requirements

Not applicable.

5.72.2 Procedures at the coincident S and T reference point

5.72.2.1 Normal operation

No impact, i.e. neither supplementary service shall affect the operation of the other supplementary service.

If the call forwarding no reply supplementary service has been activated, a notification that the call has been forwarded shall be sent to the access to which the call has been presented.

5.72.2.2 Exceptional procedures

Not applicable.

5.72.3 Procedures for interworking with private networks

The procedures of clause 5.72.2 shall apply.

5.73 The LH and the SCF supplementary services

5.73.1 Coding requirements

Not applicable.

5.73.2 Procedures at the coincident S and T reference point

5.73.2.1 Normal operation

When the selective call forwarding supplementary service has been activated unconditionally and if an incoming call matches the selection conditions, then the selective call forwarding supplementary service shall take precedence over the LH supplementary service.

When the selective call forwarding supplementary service has been activated on busy and if an incoming call matches the selection conditions, then the selective call forwarding supplementary service shall be invoked, when:

- all accesses are either network determined user busy or withdrawn from the hunt group; or
- the selected access is user determined user busy.

If the selective call forwarding supplementary service has been activated on busy as result of network determined user busy, a notification that the call has been forwarded shall not be given to the served user.

If the selective call forwarding supplementary service has been activated on busy as result of user determined user busy, a notification that the call has been forwarded shall be sent to the access to which the call has been presented.

When the selective call forwarding supplementary service has been activated on no reply, then there is no impact, i.e. neither supplementary service shall affect the operation of the other supplementary service.

5.73.2.2 Exceptional procedures

Not applicable.

5.73.3 Procedures for interworking with private networks

The procedures of clause 5.73.2 shall apply.

5.74 The LH and TP supplementary services

5.74.1 Coding requirements

Not applicable.

5.74.2 Procedures at the coincident S and T reference point

5.74.2.1 Normal operation

When the network receives an ActivationSCF invoke component containing in the forwardedToAddress parameter an address that is to be barred according to the activated barring program for (any of) the instance(s) identified by the servedUserNr and basicService parameters, then the network shall reject the selective call forwarding activation request using the procedure in clause 9.1.1.4 of EN 300 207-1 [17]. The indicated error value shall be "supplementaryServiceInteractionNotAllowed".

NOTE: Activation of the OCB-UC supplementary service has no effect on currently active call forwarding supplementary services.

5.74.2.2 Exceptional procedures

Not applicable.

5.74.3 Procedures for interworking with private networks

The procedures of clause 5.67.2 shall apply.

5.75 The RC and the other supplementary services

According to EN 301 691 (V1.1.1), there is no interaction with supplementary services.

Control of supplementary services which apply to the remote access at the remote location by users other than the remote control user while the remote control user has invoked the RC service shall be treated as totally independent of the RC service and shall apply to the remote access.

NOTE: The use of RC service does not imply the setting up of a call. Therefore, interactions with supplementary services cannot occur.

The following (supplementary) services have been identified as being able to be remotely controlled:

- call forwarding unconditional;
- call forwarding busy;
- call forwarding no reply;
- outgoing call barring-User Controlled;
- selective call forwarding;
- line hunting;
- trunk hunting.

As a service provider option, the list may be extended to other (supplementary) services.

NOTE: The control of the Remote Control service from a remote location is part of the Remote control service (see clause 5.2.1).

6 General procedures

6.1 Identification of charge

6.1.1 Normal operation

No impact.

6.1.2 Exceptional procedures

If a user sends an IdentificationOfCharge invoke component to the network and the user has not subscribed to the AOC-E supplementary service, the network shall return an IdentificationOfCharge return error component indicating "notSubscribed" to the user. The network shall include the IdentificationOfCharge return error component in a Facility information element, either in an appropriate call control message or in a FACILITY message.


If a user sends an IdentificationOfCharge invoke component to the network and the user has subscribed to the AOC-E supplementary service except when in combination with the ECT and CD supplementary services and partial rerouting in conjunction with the diversion supplementary services, the network shall return an IdentificationOfCharge return error component indicating "supplementaryServiceInteractionNotAllowed" to the user. The network shall include the IdentificationOfCharge return error component in a Facility information element, either in an appropriate call control message or in a FACILITY message.

6.2 Ordering of checks

When two or more supplementary services interact and for each of these supplementary services a condition has to be met to allow the related basic call procedures to proceed, the order in which these conditions are checked is an option as long as not demanded by service requirements. Similarly the procedure(s) to be followed when one of the conditions is not met is an option.


Annex A (informative): Signalling flows

The signalling flows in figures A.1, A.2 and A.3 show the interaction between the AOC and TP supplementary service.



NOTE: Cumulative charging information can be sent to the served user, as a network option.


Figure A.1: Transfer of charging information in the call suspension phase



NOTE 1: Only provided if there is a change in the charging rate during suspension time.

NOTE 2: The first FACILITY message following the RESUME ACKNOWLEDGE message is only used if the charging information has not already been sent in the RESUME ACKNOWLEDGE message. This is a network provider option.

Figure A.2: Transfer of charging information in the call resumption phase



NOTE: It is a network provider option to provide this capability. The network has retained the call identity of the suspended call. If the network shall send charging information, the charging information needs to be available for the duration of the call retention timer.

Figure A.3: Transfer of charging information in the case of a call resume reject

Annex B (informative):

Example of the interaction between the AOC-E and CONF supplementary services

Figure B.1 shows a configuration with four conferees connected to a conference bridge together with the CONF-served user. Figure B.2 shows at what point in time the AOC-E charging information is sent to user A and the content of this information, during the time the connection is established.

User A has activated the AOC-E supplementary service "for all calls". For this particular case, user A requests the CONF supplementary service from an already existing call (established to user B1).




Figure B.1: Served user (user A) of the CONF supplementary service, and conferees

Figure B.2 shows the sequence of events which occur at certain moments in time, as indicated by t0 through t8.

- At time t0: User A establishes a call to user B1.
- At time t1: User A requests the CONF supplementary service in the active state using the call established to user B1.
- At time t2: User A places the conference on hold, and establishes a new connection to user B2.
- At time t3: User A adds the call to user B2 to the conference. The network sends AOC-E information about the connection between user A and user B2.
- At time t4: User A places the conference on hold, and establishes a new connection to user B3.
- At time t5: User A adds the call to user B3 to the conference. The network sends AOC-E information about the connection between user A and user B3.
- At time t6: User A places the conference on hold, and establishes a new connection to user B4.
- At time t7: User A adds the call to user B4 to the conference. The network sends AOC-E information about the connection between user A and user B4.
- At time t8: User A releases the conference call. The network sends AOC-E information about the conference call to user A.

When user A releases the conference call at time t8, the network sends the accumulated sum of the following charges to user A:

AOC-E at t8: $A - B1(t0 \text{ to } t8) + A - B2(t3 \text{ to } t8) + A - B3(t5 \text{ to } t8) + A - B4(t7 \text{ to } t8)$

NOTE: $A - B1(t0 \text{ to } t8)$ means the charges applied for the connection between user A and user B1 during the time period from t0 to t8.

If the user wants to indicate the total charges applied by the network on all calls from user A during the time period from t0 to t8, the following applies:

Total cost: $[AOC-E \text{ at } t8] + A - B2(t2 \text{ to } t3) + A - B3(t4 \text{ to } t5) + A - B4(t6 \text{ to } t7)$




Figure B.2: Sending charging information to user A

Annex C (informative):

Changes of this edition with respect to edition 1 of ETS 300 195-1

- Additions of supplementary service interactions with Line Hunting and Remote Control.
- Updates of reference dates.
- Conversion to EN format.
- Replacement of CCITT by ITU-T.

History

Document history		
Edition 1	February 1995	Publication as ETS 300 195-1
V1.4.3	October 1998	Publication
V2.1.1	February 2001	One-step Approval Procedure OAP 20010608: 2001-02-07 to 2001-06-08