

**Electromagnetic compatibility and
Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Radio equipment to be used in the 25 MHz to 1 000 MHz
frequency range with power levels ranging up to 500 mW;
Part 2: Supplementary parameters not intended
for conformity purposes**



Reference

REN/ERM-RP08-0403-2

Keywords

radio, testing, SRD

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
<http://www.etsi.org>
If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions, symbol and abbreviations.....	6
3.1 Definitions	6
3.2 Symbol.....	6
3.3 Abbreviations	6
4 Receiver parameters	7
4.1 Maximum usable sensitivity (conducted)	7
4.1.1 Definition.....	7
4.1.2 Limits.....	7
4.2 Average usable sensitivity (field strength).....	7
4.2.1 Definition.....	7
4.2.2 Limits.....	7
4.3 Co-channel rejection.....	8
4.3.1 Definition.....	8
4.3.2 Limits.....	8
4.4 Adjacent channel selectivity	8
4.4.1 Definition.....	8
4.4.2 Limits.....	8
4.5 Spurious response rejection	9
4.5.1 Definition.....	9
4.5.2 Limits.....	9
4.6 Intermodulation response rejection.....	9
4.6.1 Definition.....	9
4.6.2 Limits.....	9
4.7 Blocking or desensitization	9
4.7.1 Definition.....	9
4.7.2 Limits.....	9
Annex A (normative): Application: Social alarm systems	10
A.1 General	10
A.2 Minimum effective radiated power	10
A.2.1 Definition.....	10
A.2.2 Method of measurement	10
A.2.3 Classification of effective radiated power levels	10
A.3 Receiver parameters	11
History	12

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document consists of three parts as follows:

- Part 1: "Technical characteristics and test methods";
- Part 2: "Supplementary parameters not intended for conformity purposes";**
- Part 3: "Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".

This part specifies supplementary parameters in general and for specific applications, not for the purpose of conformity to the R&TTE Directive.

Annex A provides specifications concerning social alarm systems. Requirements for equipment to be used in Social Alarm systems, are specified in EN 300 220-1 [5].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The term "the present document" refers to EN 300 220-2 only.

The present document covers parameters not intended to be measured for conformity or regulatory purposes. However, they are provided to give guidance to manufacturers and users regarding reasonable reliability of the radio link and performance of the receiver.

The present document contains the technical characteristics for radio equipment referencing relevant CEPT/ERC Decisions and Recommendation CEPT ERC/Recommendation 70-03 [1].

The present document does not necessarily include all the characteristics which may be required by a user, nor does it necessarily represent the optimum performance achievable. It is a product family standard which may be completely or partially superseded by specific standards covering specific applications.

The present document applies to short range devices:

- either with a Radio Frequency (RF) output connection and/or with an integral antenna;
- for alarms, identification, telecommand, telemetry, etc., applications;
- with or without speech;
- operating on radio frequencies between 25 MHz and 1 000 MHz, with power levels up to 500 mW, radiated or conducted.

The present document covers fixed stations, mobile stations and portable stations. In the present document basic requirements are given for the different frequency bands, channel separation etc., where appropriate.

The present document does not require measurements for radiated emissions below 25 MHz.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] CEPT/ERC Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".
- [2] ETS 300 113: "Radio Equipment and Systems (RES); Land mobile service; Technical characteristics and test conditions for radio equipment intended for the transmission of data (and speech) and having an antenna connector".
- [3] ETS 300 390: "Radio Equipment and Systems (RES); Land mobile service; Technical characteristics and test conditions for radio equipment intended for the transmission of data (and speech) and using an integral antenna".
- [4] ITU-T Recommendation O.41: "Psophometer for use on telephone-type circuits".
- [5] EN 300 220-1: "Electromagnetic compatibility and Radio spectrum matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical characteristics and test methods".

[6] ETR 027: "Radio Equipment and Systems (RES); Methods of measurement for private mobile radio equipment".

3 Definitions, symbol and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

alarm: use of radio communication for indicating an alarm condition at a distant location

conducted measurements: measurements which are made using a direct 50 Ω connection to the equipment under test

dedicated antenna: removable antenna supplied and type tested with the radio equipment, designed as an indispensable part of the equipment

fixed station: equipment intended for use in a fixed location

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

mobile station: equipment normally fixed in a vehicle

portable station: equipment intended to be carried, attached or implanted

radiated measurements: measurements which involve the absolute measurement of a radiated field

telecommand: use of radio communication for the transmission of signals to initiate, modify or terminate functions of equipment at a distance

telemetry: use of radio communication for indicating or recording data at a distance

3.2 Symbol

For the purposes of the present document, the following symbol applies:

SND/ND Signal + Noise + Distortion / Noise + Distortion

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

emf	electromotive force
EMC	ElectroMagnetic Compatibility
ERP	Effective Radiated Power
PSTN	Public Switched Telephone Network
RF	Radio Frequency
SRD	Short Range Device

4 Receiver parameters

For the method of measurement of the receiver parameters, reference should be made to the appropriate subclauses in ETS 300 113 [2], ETS 300 390 [3] or ETR 027 [6].

4.1 Maximum usable sensitivity (conducted)

4.1.1 Definition

The maximum usable sensitivity is minimum level of signal (electromotive force (emf)) at the receiver input, produced by a carrier at the nominal frequency of the receiver, modulated with the normal test signal modulation, which produces:

- a SND/ND ratio of 20 dB, measured at the receiver output through a telephone psophometric weighting network as described in ITU-T Recommendation O.41 [4]; or
- after demodulation, a data signal with a bit error ratio of 10^{-2} ; or
- after demodulation, a message acceptance ratio of 80 %.

4.1.2 Limits

The maximum usable sensitivity shall not exceed an emf of +6 dB μ V under normal test conditions.

4.2 Average usable sensitivity (field strength)

This measurement only applies to equipment with an integral or dedicated antenna.

The average, E_{mean} , is calculated from eight measurements of field strength, where the receiver is rotated in 45° increments, starting at an arbitrary orientation.

$$E_{mean} = 20 \log_{10} \sqrt{\frac{8}{\sum_{i=1}^{i=8} x_i^2}}$$

Where x_i represents the eight field strengths in μ V/m.

4.2.1 Definition

The average usable sensitivity of the receiver is the average field strength, expressed in dB μ V/m, produced by a carrier at the nominal frequency of the receiver, modulated with the normal test signal which produces:

- a SND/ND ratio of 20 dB, measured at the receiver output through a telephone psophometric weighting network as described in ITU-T Recommendation O.41 [4]; or
- after demodulation, a data signal with a bit error ratio of 10^{-2} ; or
- after demodulation, a message acceptance ratio of 80 %.

4.2.2 Limits

The average radiated usable sensitivity is given in table 1.

Table 1

Frequency range (MHz)	Average usable sensitivity dB μ V/m
Integral antenna fully within the case	
30 to 400	27,0
> 400 to 750	28,5
> 750 to 1 000	30,0
Integral or dedicated antenna with an external length \leq 20 cm to the case	
30 to 130	18,0
> 130 to 300	19,5
> 300 to 440	21,5
> 440 to 600	23,5
> 600 to 800	25,5
> 800 to 1 000	28,0
Integral or dedicated antenna with an external length > 20 cm to the case	
30 to 130	18,0 - k
> 130 to 300	19,5 - k
> 300 to 375	21,5 - k
> 375 to 440	21,5
> 440 to 600	23,5
> 600 to 800	25,5
> 800 to 1 000	28,0

Where:

$$k = 20 \log_{10} ((l + 20)/40); \text{ and}$$

l is the length of the external part of the antenna in cm.

4.3 Co-channel rejection

4.3.1 Definition

The co-channel rejection is a measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted modulated signal, both signals being at the nominal frequency of the receiver.

4.3.2 Limits

The value of the co-channel rejection ratio, expressed in dB, shall be:

- between -8 and 0 dB, for a channel spacing of 20 or 25 kHz;
- between -12 and 0 dB, for a channel spacing of \leq 12,5 kHz.

4.4 Adjacent channel selectivity

4.4.1 Definition

The adjacent channel selectivity is a measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted signal which differs in frequency from the wanted signal by an amount equal to the adjacent channel separation for which the equipment is intended.

4.4.2 Limits

The adjacent channel selectivity of the equipment under specified conditions shall not exceed the levels of the unwanted signal as stated in table 2.

Table 2

Test conditions	Channel spacing $\leq 12,5$ kHz	Channel spacing 20 kHz or 25 kHz
Normal	60,0 dB	70,0 dB

4.5 Spurious response rejection

4.5.1 Definition

The spurious response rejection is a measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted modulated signal at any other frequency, at which a response is obtained.

4.5.2 Limits

At any frequency separated from the nominal frequency of the receiver by more than one channel spacing, the spurious response rejection shall not be less than 70,0 dB.

4.6 Intermodulation response rejection

4.6.1 Definition

The intermodulation response is a measure of the capability of the receiver to receive a wanted modulated signal, without exceeding a given degradation due to the presence of two or more unwanted signals with a specific frequency relationship to the wanted signal frequency.

4.6.2 Limits

The intermodulation response rejection ratio shall not be less than 65 dB.

4.7 Blocking or desensitization

4.7.1 Definition

Blocking is a measure of the capability of the receiver to receive a wanted modulated signal without exceeding a given degradation due to the presence of an unwanted input signal at any frequencies other than those of the spurious responses or the adjacent channels.

4.7.2 Limits

The blocking ratio, for any frequency within the specified ranges, shall not be less than 84 dB, except at frequencies on which spurious responses are found.

Annex A (normative): Application: Social alarm systems

A.1 General

This annex covers equipment operating in a domestic or residential environment. It covers fixed, mobile or portable transmitters working into fixed receivers.

This annex assumes a certain path loss if the equipment has to operate with adequate reliability. The minimum power level recommended in this annex takes into account the effects of:

- non uniform radiation patterns of the transmitter and receiver antennas;
- reflections caused by the construction of the building, moveable objects and persons;
- attenuation by commonly used building materials;
- path loss assuming a distance of typically 10 m;
- operating frequency.

A.2 Minimum effective radiated power

The minimum required radiated power is based on the factors stated above and the receiver limits stated in clause 4.

A.2.1 Definition

For the definition of effective radiated power see subclause 8.3.1 of EN 300 220-1 [5]. The minimum level is the maximum value measured in accordance with the method of measurement stated in subclause 8.3.2 of EN 300 220-1 [5].

A.2.2 Method of measurement

For the method of measurement see subclause 8.3.2 of EN 300 220-1 [5].

A.2.3 Classification of effective radiated power levels

There are four classes of Effective Radiated Power (ERP) as detailed in table A.1.

For frequencies above 500 MHz the effective radiated power range for additional classes are given in table A.1. For frequencies between 137 and 500 MHz, the values given in table A.1 are modified as follows:

$$p \times (f/500)^4,$$

where p is equal to the effective radiated power.

Table A.1

Class	Radiated level ERP
A	≥ 2 mW to 10 mW
B	≥ 100 μ W to 2 mW
C	≥ 10 μ W to < 100 μ W
D	< 10 μ W

A.3 Receiver parameters

The receiver parameters limits are stated in subclauses 4.1 to 4.5 of the present document. For the method of measurement of the receiver parameters, reference shall be made to the appropriate subclauses in ETS 300 113 [2] or ETS 300 390 [3].

History

Document history		
Edition 1	October 1993	Publication as I-ETS 300 220
V1.2.1	November 1997	Publication
V1.3.1	January 2000	Public Enquiry PE 200020: 2000-01-19 to 2000-05-19