

EN 300 369-2 V1.2.4 (1998-10)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);
Explicit Call Transfer (ECT) supplementary service;
Digital Subscriber Signalling System No. one (DSS1) protocol;
Part 2: Protocol Implementation Conformance
Statement (PICS) proforma specification**



Reference

REN/SPS-05116-2 (3f0i0iqo.PDF)

Keywords

ISDN, DSS1, supplementary service, ECT, PICS

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
<http://www.etsi.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.
All rights reserved.

Contents

Intellectual Property Rights.....	5
Foreword	5
1 Scope.....	6
2 References.....	6
2.1 Normative references	6
2.2 Informative references	7
3 Definitions, symbols and abbreviations.....	7
3.1 Definitions	7
3.2 Symbols	7
3.3 Abbreviations.....	8
4 Conformance.....	8
Annex A (normative): PICS proforma for EN 300 369-1	9
A.1 Instructions for completing the PICS proforma.....	9
A.1.1 Identification of the implementation	9
A.1.2 Global statement of conformance	9
A.1.3 Explanation of PICS proforma subclauses.....	9
A.1.4 Symbols, abbreviations and terms.....	10
A.2 Identification of the implementation.....	10
A.2.1 Implementation Under Test (IUT) identification	10
A.2.2 System Under Test (SUT) identification.....	10
A.2.3 Product supplier	11
A.2.4 Client	11
A.2.5 PICS contact person.....	11
A.3 PICS / System Conformance Statement (SCS) relationship.....	12
A.4 Identification of the protocol	12
A.5 Global statement of conformance	12
A.6 Roles.....	13
A.7 User	13
A.7.1 Major capabilities	14
A.7.2 Subsidiary capabilities	14
A.7.3 Protocol data units	14
A.7.4 Protocol data unit parameters.....	15
A.7.5 Timers.....	16
A.7.6 Call states.....	16
A.8 Network.....	17
A.8.1 Major capabilities	17
A.8.2 Subsidiary capabilities	17
A.8.3 Protocol data units	17
A.8.4 Protocol data unit parameters.....	18
A.8.5 Timers.....	20
A.8.6 Call states.....	20
Annex B (normative): Requirements list.....	21
B.1 User	21
B.1.1 Requirements on items used in the basic call PICS	21
B.1.2 Requirements on items used in the generic functional protocol PICS	21

B.1.3	Requirements on items used in the supplementary service interactions PICS.....	22
B.2	Network.....	22
B.2.1	Requirements on items used in the basic call PICS	22
B.2.2	Requirements on items used in the generic functional protocol PICS	22
B.2.3	Requirements on items used in the supplementary service interactions PICS.....	23
History	24

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.fr/ipr> or <http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 2 of a multi-part standard covering the Digital Subscriber Signalling System No. one (DSS1) protocol specification for the Integrated Services Digital Network (ISDN) Explicit Call Transfer (ECT) supplementary service, as described below:

Part 1: "Protocol specification";

Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";

Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";

Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";

Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a given Open Systems Interconnection (OSI) protocol. Such a statement is called a Protocol Implementation Conformance Statement (PICS).

National transposition dates	
Date of adoption of this EN:	9 October 1998
Date of latest announcement of this EN (doa):	31 January 1999
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 1999
Date of withdrawal of any conflicting National Standard (dow):	31 July 1999

1 Scope

This second part of EN 300 369 is applicable to the stage three of the Explicit Call Transfer (ECT) supplementary service for the pan-European Integrated Services Digital Network (ISDN) as provided by European public telecommunications operators at the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [11]) by means of the Digital Subscriber Signalling System No. one (DSS1) protocol. Stage three identifies the protocol procedures and switching functions needed to support a telecommunications service (see CCITT Recommendation I.130 [10]).

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for the ISDN DSS1 ECT supplementary service protocol as specified in EN 300 369-1 [5] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [9].

The supplier of a protocol implementation which is claimed to conform to EN 300 369-1 [5] is required to complete a copy of the PICS proforma provided in annex A of the present document and is required to provide the information necessary to identify both the supplier and the implementation.

2 References

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply; or
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity); or
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

2.1 Normative references

- [1] EN 300 195-1: "Integrated Services Digital Network (ISDN); Supplementary service interactions; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [2] EN 300 195-2: "Integrated Services Digital Network (ISDN); Supplementary service interactions; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] EN 300 196-1: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1 Protocol specification".
- [4] ETS 300 196-2: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [5] EN 300 369-1 (V1.2): "Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [6] EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".

- [7] EN 300 403-3: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 3: Protocol Implementation Conformance Statement (PICS) proforma specification".

2.2 Informative references

- [8] ISO/IEC 9646-1: "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 1: General concepts".
- [9] ISO/IEC 9646-7: "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 7: Implementation Conformance Statements".
- [10] CCITT Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [11] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces; Reference configurations".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document the following definitions, in addition to those given in EN 300 369-1 [5] apply:

Protocol Implementation Conformance Statement (PICS): A statement made by the supplier of an Open Systems Interconnection (OSI) implementation or system, stating which capabilities have been implemented for a given OSI protocol (see ISO/IEC 9646-1 [8]).

PICS proforma: A document, in the form of a questionnaire, designed by the protocol specifier or conformance test suite specifier, which, when completed for an OSI implementation or system becomes the PICS (see ISO/IEC 9646-1 [8]).

static conformance review: A review of the extent to which the static conformance requirements are met by the IUT, accomplished by comparing the PICS with the static conformance requirements expressed in the relevant standard(s) (see ISO/IEC 9646-1 [8]).

3.2 Symbols

For the purposes of the present document the following symbols apply:

AND	Boolean "and"
C	Conditional requirement (to be observed if the relevant conditions apply)
M	Mandatory requirement (to be observed in all cases)
N/A	Not applicable, not supported or the conditions for status are not met
No	not supported
NOT	Boolean "not"
O	Option (may be selected to suit the implementation, provided that any requirements applicable to the option are observed)
O.n	Options, but support required for either at least one or only one of the options in the group labelled with the same numeral "n"
OR	Boolean "or"
Yes	supported

3.3 Abbreviations

For the purposes of the present document the following abbreviations apply:

ECT	Explicit Call Transfer
DSS1	Digital Subscriber Signalling System No. one
IET	Information Elements Transmitted
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
MC	Major Capabilities
MT	Messages Transmitted
OSI	Open Systems Interconnection
P	Parameters
PICS	Protocol Implementation Conformance Statement
R	Role
SC	Subsidiary Capabilities
SCS	System Conformance Statement
SUT	System Under Test

4 Conformance

A PICS proforma which conforms to this PICS proforma specification shall be technically equivalent to annex A, and shall preserve the numbering and ordering of the items in annex A.

A PICS which conforms to this PICS proforma specification shall:

- a) describe an implementation which claims to conform to EN 300 369-1 [5];
- b) be a conforming ICS proforma which has been completed in accordance with the instructions for completion given in annex A, clause A.1;
- c) include the information necessary to uniquely identify both the supplier and the implementation.

Annex A (normative): PICS proforma for EN 300 369-1

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.
--

A.1 Instructions for completing the PICS proforma

A.1.1 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

The System Conformance Statement (SCS) as defined in ISO/IEC 9646-1 [8] is a document supplied by the client or product supplier that summarizes which OSI standards are implemented and to which conformance is claimed. The PICS/SCS clause should describe the relationship of the PICS to the SCS.

A.1.2 Global statement of conformance

If the answer to the statement in this subclause is "Yes", all subsequent subclauses should be completed to facilitate selection of test cases for optional functions.

If the answer to the statement in this subclause is "No", all subsequent subclauses should be completed, and all non-supported mandatory capabilities should be identified and explained. Explanations may be entered in the comments field at the bottom of each table or on attached sheets of paper.

A.1.3 Explanation of PICS proforma subclauses

The PICS proforma contains a Roles clause and thereafter is presented in two parts (for user and network) with the following subclauses, as required:

- major capabilities;
- subsidiary capabilities;
- protocol data unit support;
- protocol data unit parameters;
- timers;
- call states.

The User clause shall only be completed for user implementations (including private network implementations) while the Network clause shall only be completed for network implementations. The Roles clause shall be completed for all implementations.

The relationship between this PICS proforma and other related PICS proforma (e.g. the basic call PICS proforma) is expressed in the requirements list contained in annex B. This provides the additional restrictions placed on the related proforma (different conditions, different status, etc.).

A.1.4 Symbols, abbreviations and terms

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [9].

The reference column contained in the tables gives reference to the appropriate part(s) of EN 300 369-1 [5] (unless another numbered reference is explicitly indicated) describing the particular item. Note, however, that a reference merely indicates the place where the core of a description of an item can be found. Any additional information contained in EN 300 369-1 [5] (or any other possibly used reference) has to be taken into account when making a statement about the conformance of that particular item.

The following common notations, defined in ISO / IEC 9646-7 [9], are used for the status column:

M	mandatory
O	optional
N/A	not applicable
O.<integer>	for mutually exclusive or selectable options from a set

The following common notations, defined in ISO / IEC 9646-7 [9], are used for the support column:

Yes	for supported / implemented
No	for not supported / not implemented

A.2 Identification of the implementation

A.2.1 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

A.2.2 System Under Test (SUT) identification

SUT name:

.....

.....

Hardware configuration:

.....

.....

.....

Operating system:

.....

.....

A.2.3 Product supplier

Name:

.....

Address:

.....

.....

.....

Telephone number:

.....

Facsimile number:

.....

Additional information:

.....

.....

.....

A.2.4 Client

Name:

.....

Address:

.....

.....

.....

Telephone number:

.....

Facsimile number:

.....

Additional information:

.....

.....

.....

A.2.5 PICS contact person

Name:

.....

Address:

.....

Telephone number:

.....

Facsimile number:

.....

Additional information:

.....

A.3 PICS / System Conformance Statement (SCS) relationship

Provide the relationship of the PICS with the SCS for the system:

.....

A.4 Identification of the protocol

This PICS proforma applies to the following standard:

EN 300 369-1 (V1.2): "Integrated Services Digital Network (ISDN); Explicit Call Transfer (ECT) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

A.5 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No)

NOTE: Answering "No" to this question indicates non-conformance to the protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming. Explanations may be entered in the comments field at the bottom of each table or on attached pages.

A.6 Roles

Table A.1: Type of implementation

Item	Major role: Does the implementation...	Conditions for status	Status	Reference	Support
Type of implementation					
R 1	not used				
R 2.1	support user requirements?		O.1	9, 10	<input type="checkbox"/> Yes <input type="checkbox"/> No
R 2.2	support network requirements?		O.1	9, 10	<input type="checkbox"/> Yes <input type="checkbox"/> No
R 3.1	support requirements at the coincident S and T reference point?	R 2.1 R 2.2	O.2 O.3	9	<input type="checkbox"/> Yes <input type="checkbox"/> No
R 3.2	support requirements for interworking with private ISDNs at the T reference point?	R 2.1 R 2.2	O.2 O.3	10	<input type="checkbox"/> Yes <input type="checkbox"/> No
R 4.1	support user requirements at the interface of the served user?	R 2.1 NOT R 2.1	O.4 N/A	9, 10	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
R 4.2	support user requirements at the interface of a remote user?	R 2.1 NOT R 2.1	O.4 N/A	9, 10	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
R 4.3	support network requirements at the interface of the served user?	R 2.2 NOT R 2.2	M N/A	9, 10	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
R 4.4	support network requirements at the interface of a remote user?	R 2.2 NOT R 2.2	M N/A	9, 10	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
O.1	Support of one and only one of these options is required.				
O.2	Support of one and only one of these options is required.				
O.3	Support of at least one of these options is required.				
O.4	Support of at least one of these options is required.				
Comments:					

A.7 User

The tables provided in this clause need only to be completed for user implementations, where item R 2.1 above is supported.

A.7.1 Major capabilities

Table A.2: Major capabilities - user

Item	Major capability: Does the implementation support...	Conditions for status	Status	Reference	Support
MC 1	the explicit call transfer request using implicit linkage procedures?	R 3.1 AND R 4.1 NOT (R 3.1 AND R 4.1)	M N/A	9.2.1	[]Yes []No []N/A
MC 2	the explicit call transfer request using explicit linkage procedures?	R 3.1 AND R 4.1 NOT (R 3.1 AND R 4.1)	O N/A	9.2.2	[]Yes []No []N/A
MC 3	the procedures for invocation of an explicit call transfer for one answered and one alerting call?	R 3.1 AND R 4.1 NOT (R 3.1 AND R 4.1)	O N/A	9.2.1, 9.2.2, 9.2.3	[]Yes []No []N/A
MC 4	the provision of subaddress information?	R 4.2 NOT R 4.2	O N/A	9.2.4, 9.2.5, 10.2	[]Yes []No []N/A
MC 5	the procedures associated with the provision of ECT in a private network?	R 3.2 NOT R 3.2	M N/A	10.1	[]Yes []No []N/A
MC 6	the procedures for the mechanism to avoid looping of uncontrolled circuits?	R 3.2 NOT R3.2	O N/A	10.3	[]Yes []No []N/A
MC 7	the procedures to invoke call transfer in the public ISDN?	R 3.2 NOT R3.2	O N/A	10.4	[]Yes []No []N/A
MC 8	the procedures to invoke call transfer without entering any call in the held state	MC 2 NOT MC 2	O N/A	9.2.2	[]Yes []No []N/A
Comments:					

A.7.2 Subsidiary capabilities

No items requiring response.

A.7.3 Protocol data units

No items requiring response.

A.7.4 Protocol data unit parameters

Table A.3: Facility information element components received by the user

Item	Facility information element components: Does the implementation support...	Conditions for Status	Status	Reference	Support
P 1.1	EctLinkIdRequest return result?	MC 2 OR MC 7 NOT (MC 2 OR MC 7)	M N/A	7.1, 9.2.2.1.1, 10.4	[]Yes []No []N/A
P 1.2	EctLinkIdRequest return error?	MC 2 OR MC7 NOT (MC 2 OR MC 7)	M N/A	7.1, 9.2.2.1.2, 10.4	[]Yes []No []N/A
P 2.1	EctExecute return result?	R 3.1 AND R 4.1 NOT (R3.1 AND R 4.1)	M N/A	7.1, 9.2.3.1	[]Yes []No []N/A
P 2.2	EctExecute return error?	R 3.1 AND R 4.1 NOT (R3.1 AND R 4.1)	M N/A	7.1, 9.2.1.2	[]Yes []No []N/A
P 3.1	ExplicitEctExecute return result?	MC 2 OR MC7 NOT (MC 2 OR MC 7)	M N/A	7.1, 9.2.3.1, 10.4	[]Yes []No []N/A
P 3.2	ExplicitEctExecute return error?	MC 2 OR MC 7 NOT (MC 2 OR MC 7)	M N/A	7.1, 9.2.2.2.2, 10.4	[]Yes []No []N/A
P 4	RequestSubaddress invoke?	R 4.2 NOT R 4.2	M N/A	7.1, 9.2.4.1, 9.2.5.1, 10.1.1	[]Yes []No []N/A
P 5	SubaddressTransfer invoke?	(R 3.1 AND R 4.2) OR R 3.2 NOT ((R 3.1 AND R 4.2) OR R 3.2)	M N/A	7.1, 9.2.4.1, 9.2.5.1, 10.1.1, 10.2.1	[]Yes []No []N/A
P 6	EctInform invoke?	R 3.2 AND R 4.2 NOT (R 3.2 AND R 4.2)	M N/A	7.1, 10.2.1	[]Yes []No []N/A
P 7.1	EctLoopTest invoke?	MC 5 AND MC 6 NOT (MC 5 AND MC 6)	M N/A	7.1, 10.3.2.1	[]Yes []No []N/A
P 7.2	EctLoopTest return result?	MC 5 AND MC 6 NOT (MC 5 AND MC 6)	M N/A	7.1, 10.3.1.1	[]Yes []No []N/A
P 7.3	EctLoopTest return error?	MC 5 AND MC 6 NOT (MC 5 AND MC 6)	M N/A	7.1, 10.3.1.2	[]Yes []No []N/A
Comments:					

Table A.4: Facility information element components transmitted by the user

Item	Facility information element components: Does the implementation support...	Conditions for status	Status	Reference	Support
P 8	EctLinkIdRequest invoke?	MC 2 OR MC 7 NOT (MC 2 OR MC 7)	M N/A	7.1, 9.2.2.1.1, 10.4	[]Yes []No []N/A
P 9	EctExecute invoke?	R 3.1 AND R 4.1 NOT (R 3.1 AND R 4.1)	M N/A	7.1, 9.2.1.1	[]Yes []No []N/A
P 10	ExplicitEctExecute invoke?	MC 2 OR MC 7 NOT (MC 2 OR MC 7)	M N/A	7.1, 9.2.2.2.1, 10.4	[]Yes []No []N/A
P 11	SubaddressTransfer invoke?	R 3.2 OR (R 3.1 AND MC 4) NOT (R 3.2 OR (R 3.1 AND MC 4))	M N/A	7.1, 9.2.4.1, 10.1.1, 10.2.1	[]Yes []No []N/A
P 12	EctInform invoke?	R 3.2 NOT R 3.2	M N/A	7.1, 10.1.1	[]Yes []No []N/A
P 13.1	EctLoopTest invoke?	MC 5 AND MC 6 NOT (MC 5 AND MC 6)	M N/A	7.1, 10.3.1.1	[]Yes []No []N/A
P 13.2	EctLoopTest return result?	MC 5 AND MC 6 NOT (MC 5 AND MC 6)	M N/A	7.1, 10.3.2.1	[]Yes []No []N/A
P 13.3	EctLoopTest return error?	MC 5 AND MC 6 NOT (MC 5 AND MC 6)	M N/A	7.1, 10.3.2.2	[]Yes []No []N/A
Comments:					

A.7.5 Timers

No items requiring response.

A.7.6 Call states

No items requiring response.

A.8 Network

The tables provided in this clause need only to be completed for network implementations, where item R 2.2 above is supported.

A.8.1 Major capabilities

Table A.5: Major capabilities - network

Item	Major capability: Does the implementation support...	Conditions for status	Status	Reference	Support
MC 9	the implicit linkage procedures for invocation of an explicit call transfer?	R 3.1 AND R 4.3 NOT (R 3.1 AND R 4.3)	M N/A	9.2.1, 9.2.3	[]Yes []No []N/A
MC 10	the explicit linkage procedures for invocation of an explicit call transfer?	R 3.1 AND R 4.3 NOT (R 3.1 AND R 4.3)	O N/A	9.2.2, 9.2.3	[]Yes []No []N/A
MC 11	the procedures for invocation of an explicit call transfer for one answered and one alerting call?	R 3.1 AND R 4.3 NOT (R 3.1 AND R 4.3)	O N/A	9.2.1, 9.2.2, 9.2.3	[]Yes []No []N/A
MC 12	the provision of notifications to a remote user?	R 4.4 NOT R 4.4	M N/A	9.2.4, 9.2.5, 10.2	[]Yes []No []N/A
MC 13	the procedures associated with the provision of ECT in a private network?	R 3.2 NOT R 3.2	M N/A	10.1, 10.2	[]Yes []No []N/A
MC 14	the procedures for the mechanism to avoid looping of uncontrolled circuits?	R 3.2 NOT R 3.2	O N/A	10.3	[]Yes []No []N/A
MC 15	the procedures to invoke call transfer in the public ISDN?	R 3.2 NOT R3.2	O N/A	10.4	[]Yes []No []N/A
MC 16	the procedures to invoke call transfer without entering any call in the held state?	MC 10 NOT MC 10	O N/A	9.2.2	[]Yes []No []N/A
Comments:					

A.8.2 Subsidiary capabilities

No items requiring response.

A.8.3 Protocol data units

No items requiring response.

A.8.4 Protocol data unit parameters

Table A.6: Facility information element components received by the network

Item	Facility information element components: Does the implementation support...	Conditions for status	Status	Reference	Support
P 14	EctLinkIdRequest invoke?	MC 10 OR MC 15 NOT (MC 10 OR MC 15)	M N/A	7.1, 9.2.2.1.1, 10.4	[]Yes []No []N/A
P 15	EctExecute invoke?	R 3.1 AND R 4.3 NOT (R 3.1 AND R 4.3)	M N/A	7.1, 9.2.1.1	[]Yes []No []N/A
P 16	ExplicitEctExecute invoke?	MC 10 OR MC 15 NOT (MC 10 OR MC 15)	M N/A	7.1, 9.2.2.2.1, 10.4	[]Yes []No []N/A
P 17	SubaddressTransfer invoke?	(R 3.1 AND R 4.4) OR R 3.2 NOT ((R 3.1 AND R 4.4) OR R 3.2)	M N/A	7.1, 9.2.4.1, 10.1.1, 10.2.1	[]Yes []No []N/A
P 18	EctInform invoke?	R 3.2 AND R 4.3 NOT (R 3.2 AND R 4.3)	M N/A	7.1, 10.1.1	[]Yes []No []N/A
P 19.1	EctLoopTest invoke?	MC 13 AND MC 14 NOT (MC 13 AND MC 14)	M N/A	7.1, 10.3.1.1	[]Yes []No []N/A
P 19.2	EctLoopTest return result?	MC 13 AND MC 14 NOT (MC 13 AND MC 14)	M N/A	7.1, 10.3.2.1	[]Yes []No []N/A
P 19.3	EctLoopTest return error?	MC 13 AND MC 14 NOT (MC 13 AND MC 14)	M N/A	7.1, 10.3.2.2	[]Yes []No []N/A
Comments:					

Table A.7: Facility information element components transmitted by the network

Item	Facility information element components: Does the implementation support...	Conditions for status	Status	Reference	Support
P 20.1	EctLinkIdRequest return result?	MC 10 OR MC 15 NOT (MC 10 OR MC 15)	M N/A	7.1, 9.2.2.1.1, 10.4	[]Yes []No []N/A
P 20.2	EctLinkIdRequest return error?	MC 10 OR MC 15 NOT (MC 10 OR MC 15)	M N/A	7.1, 9.2.2.1.2, 10.4	[]Yes []No []N/A
P 21.1	EctExecute return result?	R 3.1 AND R 4.3 NOT (R 3.1 AND R 4.3)	M N/A	7.1, 9.2.3.1	[]Yes []No []N/A
P 21.2	EctExecute return error?	R 3.1 AND R 4.3 NOT (R 3.1 AND R 4.3)	M N/A	7.1, 9.2.1.2	[]Yes []No []N/A
P 22.1	ExplicitEctExecute return result?	MC 10 OR MC 15 NOT (MC 10 OR MC 15)	M N/A	7.1, 9.2.3.1, 10.4	[]Yes []No []N/A
P 22.2	ExplicitEctExecute return error?	MC 10 OR MC 15 NOT (MC 10 OR MC 15)	M N/A	7.1, 9.2.2.2.2, 10.4	[]Yes []No []N/A
P 23	RequestSubaddress invoke?	R 4.4 NOT R 4.4	M N/A	7.1, 9.2.4.1, 9.2.5.1, 10.1.1	[]Yes []No []N/A
P 24	SubaddressTransfer invoke?	(R 3.1 AND R 4.4) OR R 3.2 NOT ((R 3.1 AND R 4.4) OR R 3.2)	M N/A	7.1, 9.2.4.1, 9.2.5.1, 10.1.1, 10.2.1	[]Yes []No []N/A
P 25	EctInform invoke?	R 3.2 AND R 4.4 NOT (R 3.2 AND R 4.4)	M N/A	7.1, 10.2.1	[]Yes []No []N/A
P 26.1	EctLoopTest invoke?	MC 13 AND MC 14 NOT (MC 13 AND MC 14)	M N/A	7.1, 10.3.2.1	[]Yes []No []N/A
P 26.2	EctLoopTest return result?	MC 13 AND MC 14 NOT (MC 13 AND MC 14)	M N/A	7.1, 10.3.1.1	[]Yes []No []N/A
P 26.3	EctLoopTest return error?	MC 13 AND MC 14 NOT (MC 13 AND MC 14)	M N/A	7.1, 10.3.1.2	[]Yes []No []N/A
Comments:					

Table A.8: Notification indicator information element values transmitted by the network

Item	Notification indicator information element values: Does the implementation support...	Conditions for Status	Status	Reference	Support
P 27.1	call transferred, alerting?	R 4.4 NOT R 4.4	M N/A	7.2, 9.2.4.1, 9.2.5.1	[]Yes []No []N/A
P 27.2	call transferred, active?	R 4.4 NOT R 4.4	M N/A	7.2, 9.2.4.1, 9.2.5.1	[]Yes []No []N/A
Comments:					

Table A.9: FACILITY PDU information elements transmitted by the network

Item	FACILITY PDU information elements: Does the implementation support...	Conditions for status	Status	Reference	Support
P 28	Redirection number?	R 4.4 NOT R 4.4	M N/A	7.2, 9.2.4.1, 9.2.5.1, 10.1.1	[]Yes []No []N/A
NOTE: This parameter is additional to those required for support of the generic functional protocol (EN 300 196-1 [3]).					
Comments:					

Table A.10: NOTIFY PDU information elements transmitted by the network

Item	NOTIFY PDU information elements: Does the implementation support...	Conditions for status	Status	Reference	Support
P 29	Redirection number?	R 4.4 NOT R 4.4	M N/A	7.2, 9.2.5.1, 10.1.1	[]Yes []No []N/A
NOTE: This parameter is additional to those required for support of basic call (EN 300 403-1 [6]).					
Comments:					

A.8.5 Timers

No items requiring response.

A.8.6 Call states

No items requiring response.

Annex B (normative): Requirements list

This annex repeats in the form of a requirements list some items of the basic call, generic functional protocol and supplementary service interactions PICS proforma required for support of EN 300 369-1 [5]. No support column is provided as the answers are to be entered in the relevant base PICS proforma.

In the tables which follow in this annex, the status of the base PICS proforma is indicated as "C" (conditional) or "O" (optional). The "C" status is used where the base PICS proforma contains a number of interdependent items which need not be repeated in the present document. "O" indicates that the item in the base PICS proforma is dependent on one or more other items, at least one of which has an optional status. The exact interdependency is fully specified in the base PICS proforma specification.

B.1 User

B.1.1 Requirements on items used in the basic call PICS

No additional requirements.

B.1.2 Requirements on items used in the generic functional protocol PICS

In the tabulations which follow in this subclause, all item numbers are as contained in ETS 300 196-2 [4]. All references are to EN 300 369-1 [5] unless otherwise stated.

Table B.1: Major capabilities - user

Item	Major capability: Does the implementation...	Status base	SS conditions for status	SS status	Reference
MCu 1	support the functional protocol (separate message category) for the control of supplementary services?	O	R 4.1 R 4.2 NOT R 2.1	M O N/A	9, 10 [3] 7
MCu 2.3	support point-to-point (bearer related) transport mechanism?	C	R 4.1 R 4.2 NOT R 2.1	M O N/A	9, 10 [3] 8.3.1.1

Table B.2: Messages transmitted - user

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTu 1	the inclusion of FACILITY?	O	R 4.1 OR R 3.2 R 4.2 AND R 3.1 NOT R 2.1	M O N/A	9, 10 [3] 8.3, 11.1.1.1

B.1.3 Requirements on items used in the supplementary service interactions PICS

In the tabulations which follow in this subclause, all item numbers are as contained in EN 300 195-2 [2]. All references are to EN 300 369-1 [5] unless otherwise stated.

Table B.3: Major capabilities - user

Item	Major capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MC 1.20	the ECT supplementary service interactions with other implemented supplementary services?	O	R 4.1 NOT R 4.1	M N/A	12 [1] 5.2, 5.17, 5.34, 5.35, 5.36, 5.44, 5.45

B.2 Network

B.2.1 Requirements on items used in the basic call PICS

In the tabulations which follow in this subclause, all item numbers are as contained in EN 300 403-3 [7]. All references are to EN 300 369-1 [5] unless otherwise stated.

Table B.4: Messages transmitted - network

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MT 9	the inclusion of NOTIFY?	O	R 4.4 NOT R 4.4	M N/A	9.2.5.1, 10.1.1 [6] 3.1.9

Table B.5: Information elements - network to user (transmitted by the network)

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTn 9-IET 19	the inclusion of Notification indicator?	O	R 4.4 NOT R 4.4	M N/A	9.2.4.1, 9.2.5.1, 10.1.1 [6] 4.5.21

B.2.2 Requirements on items used in the generic functional protocol PICS

In the tabulations which follow in this subclause, all item numbers are as contained in ETS 300 196-2 [4]. All references are to EN 300 369-1 [5] unless otherwise stated.

Table B.6: Major capabilities - network

Item	Major capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MCn 1	the functional protocol (separate message category) for the control of supplementary services?	O	R 2.2 NOT R 2.2	M N/A	9, 10 [3] 7
MCn 2.3	point-to-point (bearer related) transport mechanism?	C	R 2.2 NOT R 2.2	M N/A	9, 10 [3] 8.3.1.1
MCn 3	notification category procedures?	O	R 4.4 NOT R 4.4	M N/A	9.2.5.1, 10.1.1 [3] 9.3

Table B.7: Messages transmitted - network

Item	Message: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MTn 1	the inclusion of FACILITY?	O	R 2.2 NOT R 2.2	M N/A	9, 10 [3] 8.3, 11.1.1.1

B.2.3 Requirements on items used in the supplementary service interactions PICS

In the tabulations which follow in this subclause, all item numbers are as contained in EN 300 195-2 [2]. All references are to EN 300 369-1 [5] unless otherwise stated.

Table B.8: Major capabilities - network

Item	Major capability: Does the implementation support...	Status base	SS conditions for status	SS status	Reference
MC 2.20	the ECT supplementary service interactions with other implemented supplementary services?	O	R 4.1 NOT R 4.1	M N/A	12, [1] 5.2, 5.17, 5.34, 5.35, 5.36, 5.44, 5.45

History

Document history		
Edition 1	September 1996	Publication as ETS 300 369-2
V1.2.1	December 1997	Public Enquiry PE 9815: 1997-12-12 to 1998-04-10
V1.2.3	August 1998	Vote V 9840: 1998-08-04 to 1998-10-02
V1.2.4	October 1998	Publication