
# Draft ETSI EN 300 440-2 V1.1.1 (2000-07)

Candidate Harmonized European Standard (Telecommunications series)

Electromagnetic compatibility and Radio spectrum Matters (ERM);
Short range devices;
Radio equipment to be used in the 1 GHz to 40 GHz frequency range;
Part 2: Harmonized EN under article 3.2 of the R&TTE Directive



# Reference REN/ERM-RP08-0406-2 Keywords

radio, regulation, SRD, testing

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <a href="http://www.etsi.org/tb/status/">http://www.etsi.org/tb/status/</a>

If you find errors in the present document, send your comment to: editor@etsi.fr

#### **Copyright Notification**

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

## Contents

Intelle	ectual Property Rights	4
Forev	vord	4
Introd	luction	5
1	Scope	7
2	References	8
3	Definitions, symbols and abbreviations	8
3.1	Definitions	
3.2	Symbols	
3.3	Abbreviations	
4	Technical requirements specifications	8
4.1	Transmitter requirements	8
4.1.1	Effective radiated power	
4.1.2	Permitted range of operating frequencies	
4.1.3	Spurious emissions	
4.1.4	Duty cycle	
4.2	Receiver requirements	
4.2.1	Adjacent channel selectivity-in-band	
4.2.2	Adjacent band selectivity	
4.2.3	Blocking or desensitization	
4.2.4	Spurious radiations	9
5	Testing for compliance with technical requirements	10
5.1	Essential radio test suites	
5.1.1	Environmental conditions for testing	10
5.1.1.1	Normal and extreme test-conditions	10
5.1.1.2	1	
5.1.2	Choice of samples for test suites	10
5.1.3	Transmitter test suites	
5.1.3.	· · · · · · · · · · · · · · · · · · ·	
5.1.3.2	3 · · · · · · · · · · · · · · · · · · ·	
5.1.3.3		
5.1.4	Receiver test suites	
5.1.4.1	- <b>r</b>	
5.2	Other test specifications	
6	Interpretation of measurement results	11
Anne	ex A (informative): Subclauses of the present document relevant for essential	
	requirements of relevant EC Council Directives	13
A.1	Compliance with 99/5/EC (R&TTE Directive) article 3.3e	13
A.2	Compliance with 99/5/EC (R&TTE Directive) article 3.3f	13
Biblio	ography	14
Histo	rv	15

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## **Foreword**

This Candidate Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The present document is Part 2 of a two-part deliverable covering the Electromagnetic compatibility and Radio spectrum Matters (ERM); Short range devices; Radio equipment to be used in the 1 GHz to 40 GHz frequency range, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN under article 3.2 of the R&TTE Directive".

Proposed national transposition dates			
Date of latest announcement of this EN (doa):	3 months after ETSI publication		
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa		
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa		

## Introduction

The present document is part of a set of standards designed to fit in a modular structure to cover all radio and telecommunications terminal equipment under the R&TTE Directive [1]. Each standard is a module in the structure. The modular structure is shown in figure 1.




Figure 1: Modular structure for the various standards used under the R&TTE Directive

The left hand edge of the figure shows the different subclauses of Article 3 of the Directive.

The vertical boxes show the standards under article 3.2 for the use of the radio spectrum. The scopes of these standards are specified either by frequency (normally in the case where frequency bands are harmonized) or by radio equipment type.

For article 3.3 various horizontal boxes are shown. Their dotted lines indicate that essential requirements in these areas have to be adopted by the Commission. If such essential requirements are adopted, and as far and as long as they are applicable, they will justify individual standards whose scope is likely to be specified by function or interface type.

The bottom of the figure shows the relationship of the standards to radio equipment and telecommunications terminal equipment. A particular equipment may be radio equipment, telecommunications terminal equipment or both. The General Standard will always apply to it, and a radio spectrum standard will apply if it is radio equipment. An article 3.3 standard will apply as well only if the relevant essential requirement is adopted by the Commission and if the equipment in question lies within the scope of the corresponding standard. Thus, depending on the nature of the equipment, the essential requirements under the Directive may be covered in just the General Standard or in a set of standards that includes the General Standard.

The modularity principle has been taken because:

- it minimizes the number of standards needed. Because equipment may, in fact, have multiple interfaces and functions it is not practicable to produce a single standard for each possible combination of functions that may occur in an equipment;
- it provides scope for standards under articles 3.2 and 3.3 to be added when new frequency bands are agreed or when the Commission takes decisions under article 3 without requiring alteration of standards that are already published;
- it clarifies, simplifies and promotes the usage of Harmonized Standards as the relevant means of conformity assessment.

## 1 Scope

The present document applies to Short Range Devices (SRDs) transmitters and receivers:

- transmitters operating in range from 1 GHz to 40 GHz with power levels ranging up to 4W;
- receivers operating in the range from 1 GHz to 40 GHz.

The present document contains the technical characteristics for radio equipment and is referencing CEPT/ERC Recommendation for SRDs CEPT/ERC Recommendation 70-03 [4].

The present document does not necessarily include all the characteristics which may be required by a user, nor does it necessarily represent the optimum performance achievable. It is a product family standard which may be completely or partially superseded by specific standards covering specific applications.

The present document applies to generic SRDs:

- either with a Radio Frequency (RF) output connection and specified antenna, or with an integral antenna;
- for alarms, identification systems, radio-determination, telecommand, telemetry etc. applications;
- for all types of modulation;
- with or without speech.

The present document covers fixed stations, mobile stations and portable stations. If a system includes transponders, these are measured together with the transmitter.

All types of modulation for radio devices are covered by the present document, provided the requirements of subclauses 7.2 and 7.3 are met.

The radio equipment, covered by the classification SRD is divided into several power classes based on maximum output power (see table 1). The power class designation is based on CEPT/ERC Recommendation 70-03 [4].

Power Class Power level (conducted or radiated) 8 10 mW 9 25 mW 100 mW 11 500 mW 12 1 W 13 14 2 W 14a 4 W

Table 1: Maximum radiated peak power (e.i.r.p.)

The present document does not require measurements for radiated emissions below 25 MHz.

Additional standards or specifications may be required for equipment such as that intended for connection to the Public Switched Telephone Network (PSTN).

The present document is intended to cover the provisions of Article 3.2 of Directive 1999/5/EC [1] (R&TTE Directive), see Annex C of EN 300 440-1 [2].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of Article 3 of the R&TTE Directive [1] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site http://www.newapproach.org.

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- [1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [2] ETSI EN 300 440-1 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short range devices; Radio equipment to be used in the 1 GHz to 40 GHz frequency range; Part 1: Technical characteristics and test methods".
- [3] ETSI ETR 028 (1994): "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [4] CEPT/ERC Recommendation 70-03 (1997): "Relating to the use of Short Range Devices (SRD)".

## 3 Definitions, symbols and abbreviations

#### 3.1 Definitions

For the purposes of the present document, the terms and definitions in the R&TTE Directive [1], and EN 300 440-1 [2] apply.

## 3.2 Symbols

For the purposes of the present document, the symbols defined in EN 300 440-1 [2] apply.

#### 3.3 Abbreviations

For the purposes of the present document, the abbreviations defined in EN 300 440-1 [2] apply.

## 4 Technical requirements specifications

## 4.1 Transmitter requirements

### 4.1.1 Effective radiated power

The effective radiated power, as defined in EN 300 440-1 [2], subclause 7.1.1, shall not exceed the limits in EN 300 440-1 [2], subclause 7.1.3, table 2.

This requirement applies to transmitters with an integral or dedicated antenna.

## 4.1.2 Permitted range of operating frequencies

The permitted range of operation frequencies, as defined in EN 300 440-1 [2], subclause 7.2.1, shall not exceed the limits in EN 300 440-1 [2], subclause 7.2.4.

#### 4.1.3 Spurious emissions

The spurious emissions, as defined in EN 300 440-1 [2], subclause 7.3.1, shall not exceed the limits in EN 300 440-1 [2], subclause 7.3.7, table 4.

This requirement applies to all transmitters.

#### 4.1.4 Duty cycle

The duty cycle, as defined in EN 300 440-1 [2], subclause 7.4.1, shall not exceed the limits in EN 300 440-1 [2], subclause 7.4.3, table 5.

This requirement applies to all transmitters.

## 4.2 Receiver requirements

### 4.2.1 Adjacent channel selectivity-in-band

The adjacent channel selectivity-in-band, as defined in EN 300 440-1 [2], subclauses 8.1 and 8.1.1, shall not exceed the limits in EN 300 440-1 [2], subclause 8.1.3, table 6.

This requirement applies to Equipment Class 1 receivers, as defined in EN 300 440-1 [2], subclause 4.1.1.

## 4.2.2 Adjacent band selectivity

The adjacent band selectivity, as defined in EN 300 440-1 [2], subclause 8.2.1, shall not exceed the limits in EN 300 440-1 [2], table 7.

This requirement applies to Equipment Class 1 receivers, as defined in EN 300 440-1 [2], subclause 4.1.1.

## 4.2.3 Blocking or desensitization

The blocking or desensitization, as defined in EN 300 440-1 [2], subclause 8.3.1, shall not exceed the limits in EN 300 440-1 [2], subclause 8.3.3, table 8.

This requirement applies to Equipment Class 1 and Class 2 receivers, as defined in EN 300 440-1 [2], subclause 4.1.1.

## 4.2.4 Spurious radiations

The spurious radiations, as defined in EN 300 440-1 [2], subclause 8.4.1, shall not exceed the limits in EN 300 440-1 [2], subclause 8.4.5.

This requirement applies to all receivers.

## 5 Testing for compliance with technical requirements

### 5.1 Essential radio test suites

#### 5.1.1 Environmental conditions for testing

#### 5.1.1.1 Normal and extreme test-conditions

Type tests shall be made under normal test conditions, and also, where stated, under extreme test conditions.

The test conditions and procedures shall be as specified in EN 300 440-1 [2], subclauses 5.3 to 5.4.

#### 5.1.1.2 Test power source

The test power source shall meet the requirements of EN 300 440-1 [2], subclause 5.2.

### 5.1.2 Choice of samples for test suites

Measurement shall be performed, according to the present document, on samples of equipment defined in EN 300 440-1 [2], subclauses 4.2.1 to 4.2.3.2.

#### 5.1.3 Transmitter test suites

#### 5.1.3.1 Effective radiated power

Either:

• the test specified in EN 300 440-1 [2], subclauses 7.1.2 and 7.1.2.1 shall be carried out;

or

the test specified in EN 300 440-1 [2], subclauses 7.1.2 and 7.1.2.2 shall be carried out.

This test suite applies to transmitters with an integral or dedicated antenna.

#### 5.1.3.2 Permitted range of operation frequencies

Either:

• the test specified in EN 300 440-1 [2], subclause 7.2.2 shall be carried out;

or

• the test specified in EN 300 440-1 [2], subclause 7.2.3 as appropriate shall be carried out.

This test suite applies to all transmitters.

#### 5.1.3.3 Spurious emissions

Either:

• the tests specified in EN 300 440-1 [2], subclause 7.3.3 and EN 300 440-1 [2], subclause 7.3.4 shall be carried out;

or

• the test specified in EN 300 440-1 [2], subclause 7.3.5 shall be carried out.

This test suite applies to all transmitters.

#### 5.1.4 Receiver test suites

#### 5.1.4.1 Spurious radiations

Either:

• the tests specified in EN 300 440-1 [2], subclause 8.4.2 and EN 300 440-1 [2], subclause 8.4.3 shall be carried out;

or

• the test specified in EN 300 440-1 [2], subclause 8.4.4 shall be carried out.

This test suite applies to all receivers.

## 5.2 Other test specifications

The requirements in subclause 4.2 have been set on the assumption that the test specifications in table 2 will be used to verify the performance of equipment.

**Table 2: Receiver test specifications** 

Subclause	Performance requirement	Subclause on EN 300 440-1 [2] containing the test method
4.2.1	Adjacent channel selectivity-in-band	8.1.2
4.2.2	Adjacent band selectivity	8.2.2
4.2.3	Blocking or desensitization	8.3.2
4.2.4	Spurious radiations	8.4.2 and 8.4.3; or 8.4.4

## 6 Interpretation of measurement results

The interpretation of the results recorded in the test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit shall be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be separately included in the test report;
- the value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 3.

**Table 3: Measurement uncertainty** 

RF frequency	$\pm 1 \times 10^{-7}$
RF power, conducted	± 4 dB
Adjacent channel power	± 3 dB
Conducted emission of transmitter, valid up to 12,75 GHz	± 4 dB
Conducted emission of receivers	± 3 dB
Radiated emission of transmitter, valid up to 12,75 GHz	± 6 dB
Radiated emission of receiver, valid up to 12,75 GHz	± 6 dB

For the test methods, according to the present document the uncertainty figures shall be calculated according to the methods described in the ETR 028 [3] and shall correspond to an expansion factor (coverage factor) k = 1,96 or k = 2 (which provide confidence levels of respectively 95 % and 95,45 % in case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 3 is based on such expansion factors.

The particular expansion factor used for the evaluation of the measurement uncertainty shall be stated.

## Annex A (informative):

# Subclauses of the present document relevant for essential requirements of relevant EC Council Directives

# A.1 Compliance with 99/5/EC (R&TTE Directive) article 3.3e

The subclauses noted are necessary to ensure access to emergency services. At the time of publication, this has not been invoked as an essential requirement of the R&TTE Directive for equipment covered by the present document.

Table A.1: Subclauses of the present document relevant to ensure access to emergency services

Clause/s	ubclause number and title	Corresponding article of the R&TTE Directive	Qualifying remarks	
4.2.1	Adjacent channel selectivity-in-band	3.3 e	Applies to Class 1 receivers	
4.2.2	Adjacent band selectivity	3.3 e	Applies to Class 1 receivers	
4.2.3	Blocking or desensitization	3.3 e	Applies to Class 1 & 2 receivers	

# A.2 Compliance with 99/5/EC (R&TTE Directive) article 3.3f

The subclauses noted are necessary to facilitate the use of equipment by users with a disability. At the time of publication, this has not been invoked as an essential requirement of the R&TTE Directive for equipment covered by the present document.

Table A.2: Subclauses of the present document relevant in order to facilitate the use of equipment by users with a disability

Clause/su	oclause number and title Corresponding article of the R&TTE Directive		Qualifying remarks	
4.2.1	Adjacent channel selectivity-in-band	3.3 f	Applies to Class 1 receivers	
4.2.2	Adjacent band selectivity	3.3 f	Applies to Class 1 receivers	
4.2.3	Blocking or desensitization	3.3 f	Applies to Class 1 & 2 receivers	

## Bibliography

The following material, though not specifically referenced in the body of the present document (or not publicly available), gives supporting information.

- Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.

# History

		<b>Document history</b>		
V1.1.1	July 2000	Public Enquiry	PE 20001117:	2000-07-19 to 2000-11-17