

ETSI EN 300 443-4 V1.1.2 (2000-06)

European Standard (Telecommunications series)

**Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling System No. two (DSS2) protocol;
B-ISDN user-network interface layer 3 specification
for basic call/bearer control;
Part 4: Abstract Test Suite (ATS) and partial Protocol
Implementation eXtra Information for Testing (PIXIT)
proforma specification for the user**



Reference

DEN/SPS-05149-4

KeywordsATS, basic, B-ISDN, broadband, DSS2, ISDN,
layer 3, PIXIT, UNI, user**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).

In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights.....	5
Foreword	5
1 Scope.....	6
2 References.....	6
3 Definitions and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Abstract Test Method.....	8
5 Untestable test purposes.....	8
6 ATS to TP map.....	8
7 PCTR conformance	8
8 PIXIT conformance.....	9
9 ATS Conformance	9
Annex A (normative): Protocol Conformance Test Report (PCTR) proforma.....	10
A.1 Identification summary	10
A.1.1 Protocol conformance test report.....	10
A.1.2 IUT identification.....	10
A.1.3 Testing environment.....	10
A.1.4 Limits and reservations.....	11
A.1.5 Comments.....	11
A.2 IUT Conformance status	11
A.3 Static conformance summary	11
A.4 Dynamic conformance summary.....	12
A.5 Static conformance review report	12
A.6 Test campaign report.....	12
A.7 Observations.....	21
Annex B (normative): Partial PIXIT proforma.....	22
B.1 Identification summary	22
B.2 Abstract test suite summary	22
B.3 Test laboratory	22
B.4 Client (of the Test Laboratory)	23
B.5 SUT	23
B.6 Protocol information	24
B.6.1 Protocol identification	24
B.6.2 Configuration to be tested	24
B.6.3 Stimuli for the IUT	25
B.6.4 Test management timers	26
B.6.5 Parameter Values.....	26

Annex C (normative):	Abstract Test Suite (ATS)	28
C.1	The TTCN Graphical form (TTCN.GR).....	28
C.2	The TTCN Machine Processable form (TTCN.MP)	28
History	29

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocol for Advanced Networks (SPAN).

The present document is part 4 of a multi-part EN covering the Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol, as identified below:

- Part 1: "Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";**
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

National transposition dates	
Date of adoption of this EN:	19 May 2000
Date of latest announcement of this EN (doa):	31 August 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	28 February 2001
Date of withdrawal of any conflicting National Standard (dow):	28 February 2001

1 Scope

The present document specifies the network Abstract Test Suite (ATS) for the T_B reference point or coincident S_B and T_B reference point (as defined in ITU-T Recommendation I.413 [9]) of implementations conforming to the standards for the signalling user-network layer 3 specification for basic call/bearer control of the Digital Subscriber Signalling System No. two (DSS2) protocol for the pan-European Broadband Integrated Services Digital Network (B-ISDN), EN 300 443-1 [1].

A further part of the present document specifies the Test Suite Structure and Test Purposes (TSS&TP) related to this ATS and partial PIXIT proforma. Other parts specify the TSS&TP and the ATS and partial PIXIT proforma for the User side of the T_B reference point or coincident S_B and T_B reference point of implementations conforming to EN 300 443-1 [1].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ETSI EN 300 443-1 (V1.3): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".
- [2] ETSI EN 300 443-2 (V1.2): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] ETSI EN 300 443-3 (V1.1): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 3: Test Suite Structure and Test Purposes (TSS&TP) specification for the user".
- [4] ISO/IEC 9646-1 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 1: General concepts".
- [5] ISO/IEC 9646-2 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 2: Abstract Test Suite specification".
- [6] ISO/IEC 9646-3 (1998): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 3: The Tree and Tabular Combined Notation (TTCN)".
- [7] ISO/IEC 9646-4 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 4: Test realization".
- [8] ISO/IEC 9646-5 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 5: Requirements on test laboratories and clients for the conformance assessment process".
- [9] ITU-T Recommendation I.413 (1993): "B-ISDN user-network interface".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Implementation Under Test (IUT): see ISO/IEC 9646-1 [4]

System Under Test (SUT): see ISO/IEC 9646-1 [4]

Abstract Test Suite (ATS): see ISO/IEC 9646-1 [4]

Protocol Implementation Conformance Statement (PICS): see ISO/IEC 9646-1 [4]

PICS proforma: see ISO/IEC 9646-1 [4]

Protocol Implementation eXtra Information for Testing (PIXIT): see ISO/IEC 9646-1 [4]

PIXIT proforma: see ISO/IEC 9646-1 [4]

Lower Tester (LT): see ISO/IEC 9646-1 [4]

Upper Tester (UT): see ISO/IEC 9646-1 [4]

Point of Control and Observation (PCO): see ISO/IEC 9646-1 [4]

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
ExTS	Executable Test Suite
IUT	Implementation Under Test
LT	Lower Tester
MOT	Means Of Testing
PCO	Point of Control and Observation
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
PTC	Parallel Test Component
SUT	System Under Test
TCP	Test Co-ordination Procedures
TP	Test Purpose
TTCN	Tree and Tabular Combined Notation
UT	Upper Tester

4 Abstract Test Method

The remote test method is applied for the user ATS. The Point of Control and Observation (PCO) resides at the service access point between layers 2 and 3. This PCO is named "L0" (for Lower). The L0 PCO is used to control and observe the behaviour of the Implementation Under Test (IUT) and test case verdicts are assigned depending on the behaviour observed at this PCO.



Figure 1: Remote test method

ISO/IEC 9646-2 [5] allows the informal expression of Test Co-ordination Procedures (TCP) between the System Under Test (SUT) upper layer(s) and the Lower Tester (LT). In the ATS contained in annex C, TCP is achieved by use of a second "informal" PCO, called "O" (for Operator). This PCO is used to specify control but not observation above the IUT and consequently, events at this PCO are never used to generate test case verdicts. The use of this O PCO is regarded as a preferred alternative to the use of the implicit send event, in that it allows the ATS to specify in a clear and meaningful way what actions are required to be performed on the IUT.

5 Untestable test purposes

There are no untestable test purposes associated with this ATS.

6 ATS to TP map

The identifiers used for the TPs (see EN 300 443-3 [3]) are reused as test case names. Thus there is a straightforward one-to-one mapping.

7 PCTR conformance

A test laboratory, when requested by a client to produce a PCTR, is required, as specified in ISO/IEC 9646-5 [8], to produce a PCTR conformant with the PCTR template given in annex B of ISO/IEC 9646-5 [8].

Furthermore, a test laboratory, offering testing for the ATS specification contained in annex C, when requested by a client to produce a PCTR, is required to produce a PCTR conformant with the PCTR proforma contained in annex A of the present document.

A PCTR which conforms to this PCTR proforma specification shall preserve the content and ordering of the clauses contained in annex A. Clause A.6 of the PCTR may contain additional columns. If included, these shall be placed to the right of the existing columns. Text in italics may be retained by the test laboratory.

8 PIXIT conformance

A test realizer, producing an executable test suite for the Abstract Test Suite (ATS) specification contained in annex C, is required, as specified in ISO/IEC 9646-4 [7], to produce an augmented partial PIXIT proforma conformant with this partial PIXIT proforma specification.

An augmented partial PIXIT proforma which conforms to this partial PIXIT proforma specification shall, as a minimum, have contents which are technically equivalent to annex B. The augmented partial PIXIT proforma may contain additional questions that need to be answered in order to prepare the Means Of Testing (MOT) for a particular Implementation Under Test (IUT).

A test laboratory, offering testing for the ATS specification contained in annex C, is required, as specified in ISO/IEC 9646-5 [8], to further augment the augmented partial PIXIT proforma to produce a PIXIT proforma conformant with this partial PIXIT proforma specification.

A PIXIT proforma which conforms to this partial PIXIT proforma specification shall, as a minimum, have contents which are technically equivalent to annex B. The PIXIT proforma may contain additional questions that need to be answered in order to prepare the test laboratory for a particular IUT.

9 ATS Conformance

The test realizer, producing a Means Of Testing (MOT) and Executable Test Suite (ExTS) for this Abstract Test Suite (ATS) specification, shall comply with the requirements of ISO/IEC 9646-4 [7]. In particular, these concern the realization of an Executable Test Suite (ExTS) based on each ATS. The test realizer shall provide a statement of conformance of the MOT to this ATS specification.

An ExTS which conforms to this ATS specification shall contain test groups and test cases which are technically equivalent to those contained in the ATS in annex C. All sequences of test events comprising an abstract test case shall be capable of being realized in the executable test case. Any further checking which the test system might be capable of performing is outside the scope of this ATS specification and shall not contribute to the verdict assignment for each test case.

Test laboratories running conformance test services using this ATS shall comply with ISO/IEC 9646-5 [8].

A test laboratory which claims to conform to this ATS specification shall use an MOT which conforms to this ATS.

Annex A (normative): Protocol Conformance Test Report (PCTR) proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PCTR proforma in this annex so that it can be used for its intended purposes and may further publish the completed PCTR.

A.1 Identification summary

A.1.1 Protocol conformance test report

PCTR number:	
PCTR Date:	
Corresponding SCTR number:	
Corresponding SCTR date:	
Test Laboratory identification:	
Test Laboratory Manager:	
Signature:	

A.1.2 IUT identification

Name:	
Version:	
Protocol specification:	EN 300 443
PICS:	
Previous PCTRs (if any)	

A.1.3 Testing environment

PIXIT Reference number:	
ATS Specification:	EN 300 443-4
Abstract Test Method:	Remote test method (see ISO/IEC 9646-2)
Means of Testing identification:	
Dates of testing:	
Conformance Log reference(s):	
Retention Date for Log reference(s):	

A.1.4 Limits and reservations

Additional information relevant to the technical contents or further use of the test report, or to the rights and obligations of the test laboratory and the client, may be given here. Such information may include restriction on the publication of the report.

.....

.....

.....

.....

.....

A.1.5 Comments

Additional comments may be given by either the client or the test laboratory on any of the contents of the PCTR, for example, to note disagreement between the two parties.

.....

.....

.....

.....

A.2 IUT Conformance status

This IUT has or has not been shown by conformance assessment to be non-conforming to the specified protocol specification.

Strike the appropriate words in this sentence. If the PICS for this IUT is consistent with the static conformance requirements (as specified in clause A.3 of this report) and there are no "FAIL" verdicts to be recorded (in clause A.6) strike the words "has or", otherwise strike the words "or has not".

A.3 Static conformance summary

The PICS for this IUT is or is not consistent with the static conformance requirements in the specified protocol.

Strike the appropriate words in this sentence.

A.4 Dynamic conformance summary

The test campaign did or did not reveal errors in the IUT.

Strike the appropriate words in this sentence. If there are no "FAIL" verdicts to be recorded (in clause A.6 of this report) strike the words "did or", otherwise strike the words "or did not".

Summary of the results of groups of tests:

.....

.....

.....

.....

A.5 Static conformance review report

If clause A.3 indicates non-conformance, this subclause itemizes the mismatches between the PICS and the static conformance requirements of the specified protocol specification.

.....

.....

.....

.....

.....

.....

A.6 Test campaign report

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_01_01				
L3BU_01_02				
L3BU_01_03				
L3BU_01_04				
L3BU_02_01				
L3BU_03_01				
L3BU_03_02				
L3BU_03_03				
L3BU_04_01				
L3BU_04_02				
L3BU_05_01				
L3BU_06_01				
L3BU_06_02				
L3BU_07_01				
L3BU_07_02				
L3BU_07_03				
L3BU_07_04				
L3BU_08_01				
L3BU_08_02				
L3BU_08_03				
L3BU_08_04				
L3BU_09_01				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_09_02				
L3BU_09_03				
L3BU_09_04				
L3BU_10_01				
L3BU_10_02				
L3BU_10_03				
L3BU_10_04				
L3BU_10_05				
L3BU_10_06				
L3BU_10_07				
L3BU_10_08				
L3BU_11_01				
L3BU_11_02				
L3BU_11_03				
L3BU_12_01				
L3BU_12_02				
L3BU_12_03				
L3BU_13_01				
L3BU_13_02				
L3BU_14_01				
L3BU_15_01				
L3BU_15_02				
L3BU_15_03				
L3BU_15_04				
L3BU_15_05				
L3BU_15_06				
L3BU_15_07				
L3BU_15_08				
L3BU_15_09				
L3BU_15_10				
L3BU_15_11				
L3BU_16_01				
L3BU_16_02				
L3BU_16_03				
L3BU_16_04				
L3BU_16_05				
L3BU_16_06				
L3BU_16_07				
L3BU_16_08				
L3BU_17_01				
L3BU_17_02				
L3BU_18_01				
L3BU_18_02				
L3BU_18_03				
L3BU_18_04				
L3BU_19_01				
L3BU_19_02				
L3BU_19_03				
L3BU_19_04				
L3BU_19_05				
L3BU_19_06				
L3BU_19_07				
L3BU_19_08				
L3BU_19_09				
L3BU_19_10				
L3BU_19_11				
L3BU_19_12				
L3BU_19_13				
L3BU_19_14				
L3BU_19_15				
L3BU_19_16				
L3BU_19_17				
L3BU_19_18				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_19_19				
L3BU_19_20				
L3BU_20_01				
L3BU_20_02				
L3BU_20_03				
L3BU_20_04				
L3BU_20_05				
L3BU_20_06				
L3BU_20_07				
L3BU_20_08				
L3BU_20_09				
L3BU_20_10				
L3BU_20_11				
L3BU_20_12				
L3BU_20_13				
L3BU_20_14				
L3BU_20_15				
L3BU_20_16				
L3BU_20_17				
L3BU_20_18				
L3BU_20_19				
L3BU_20_20				
L3BU_20_21				
L3BU_20_22				
L3BU_20_23				
L3BU_20_24				
L3BU_20_25				
L3BU_20_26				
L3BU_20_27				
L3BU_20_28				
L3BU_20_29				
L3BU_20_30				
L3BU_20_31				
L3BU_20_32				
L3BU_20_33				
L3BU_20_34				
L3BU_20_35				
L3BU_20_36				
L3BU_20_37				
L3BU_20_38				
L3BU_20_39				
L3BU_20_40				
L3BU_20_41				
L3BU_20_42				
L3BU_20_43				
L3BU_20_44				
L3BU_20_45				
L3BU_21_01				
L3BU_21_02				
L3BU_21_03				
L3BU_21_04				
L3BU_21_05				
L3BU_21_06				
L3BU_21_07				
L3BU_21_08				
L3BU_21_09				
L3BU_21_10				
L3BU_21_11				
L3BU_21_12				
L3BU_21_13				
L3BU_21_14				
L3BU_21_15				
L3BU_21_16				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_21_17				
L3BU_21_18				
L3BU_21_19				
L3BU_21_20				
L3BU_21_21				
L3BU_21_22				
L3BU_21_23				
L3BU_21_24				
L3BU_21_25				
L3BU_21_26				
L3BU_21_27				
L3BU_21_28				
L3BU_21_29				
L3BU_21_30				
L3BU_21_31				
L3BU_21_32				
L3BU_21_33				
L3BU_21_34				
L3BU_21_35				
L3BU_21_36				
L3BU_21_37				
L3BU_22_01				
L3BU_22_02				
L3BU_22_03				
L3BU_22_04				
L3BU_22_05				
L3BU_22_06				
L3BU_22_07				
L3BU_22_08				
L3BU_22_09				
L3BU_22_10				
L3BU_22_11				
L3BU_22_12				
L3BU_22_13				
L3BU_22_14				
L3BU_22_15				
L3BU_22_16				
L3BU_22_17				
L3BU_22_18				
L3BU_22_19				
L3BU_22_20				
L3BU_22_21				
L3BU_22_22				
L3BU_22_23				
L3BU_22_24				
L3BU_22_25				
L3BU_22_26				
L3BU_22_27				
L3BU_22_28				
L3BU_22_29				
L3BU_22_30				
L3BU_22_31				
L3BU_22_32				
L3BU_23_01				
L3BU_23_02				
L3BU_23_03				
L3BU_23_04				
L3BU_23_05				
L3BU_23_06				
L3BU_23_07				
L3BU_23_08				
L3BU_23_09				
L3BU_23_10				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_23_11				
L3BU_23_12				
L3BU_23_13				
L3BU_23_14				
L3BU_23_15				
L3BU_23_16				
L3BU_23_17				
L3BU_23_18				
L3BU_23_19				
L3BU_23_20				
L3BU_23_21				
L3BU_23_22				
L3BU_23_23				
L3BU_23_24				
L3BU_23_25				
L3BU_23_26				
L3BU_23_27				
L3BU_23_28				
L3BU_23_29				
L3BU_23_30				
L3BU_23_31				
L3BU_23_32				
L3BU_24_01				
L3BU_24_02				
L3BU_24_03				
L3BU_24_04				
L3BU_24_05				
L3BU_24_06				
L3BU_24_07				
L3BU_24_08				
L3BU_24_09				
L3BU_24_10				
L3BU_24_11				
L3BU_24_12				
L3BU_24_13				
L3BU_24_14				
L3BU_24_15				
L3BU_24_16				
L3BU_24_17				
L3BU_24_18				
L3BU_24_19				
L3BU_24_20				
L3BU_24_21				
L3BU_24_22				
L3BU_24_23				
L3BU_25_01				
L3BU_25_02				
L3BU_25_03				
L3BU_25_04				
L3BU_25_05				
L3BU_25_06				
L3BU_25_07				
L3BU_25_08				
L3BU_25_09				
L3BU_25_10				
L3BU_25_11				
L3BU_25_12				
L3BU_25_13				
L3BU_25_14				
L3BU_25_15				
L3BU_25_16				
L3BU_25_17				
L3BU_25_18				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_25_19				
L3BU_25_20				
L3BU_25_21				
L3BU_25_22				
L3BU_25_23				
L3BU_25_24				
L3BU_25_25				
L3BU_25_26				
L3BU_25_27				
L3BU_25_28				
L3BU_25_29				
L3BU_25_30				
L3BU_25_31				
L3BU_25_32				
L3BU_25_33				
L3BU_25_34				
L3BU_25_35				
L3BU_25_36				
L3BU_25_37				
L3BU_26_01				
L3BU_26_02				
L3BU_26_03				
L3BU_26_04				
L3BU_26_05				
L3BU_26_06				
L3BU_26_07				
L3BU_26_08				
L3BU_26_09				
L3BU_26_10				
L3BU_26_11				
L3BU_26_12				
L3BU_26_13				
L3BU_26_14				
L3BU_26_15				
L3BU_26_16				
L3BU_26_17				
L3BU_26_18				
L3BU_26_19				
L3BU_26_20				
L3BU_26_21				
L3BU_26_22				
L3BU_26_23				
L3BU_27_01				
L3BU_27_02				
L3BU_27_03				
L3BU_27_04				
L3BU_27_05				
L3BU_27_06				
L3BU_27_07				
L3BU_27_08				
L3BU_27_09				
L3BU_27_10				
L3BU_27_11				
L3BU_27_12				
L3BU_27_13				
L3BU_27_14				
L3BU_27_15				
L3BU_27_16				
L3BU_27_17				
L3BU_27_18				
L3BU_27_19				
L3BU_27_20				
L3BU_27_21				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_27_22				
L3BU_27_23				
L3BU_27_24				
L3BU_27_25				
L3BU_27_26				
L3BU_27_27				
L3BU_27_28				
L3BU_27_29				
L3BU_27_30				
L3BU_27_31				
L3BU_27_32				
L3BU_27_33				
L3BU_27_34				
L3BU_27_35				
L3BU_27_36				
L3BU_27_37				
L3BU_27_38				
L3BU_27_39				
L3BU_28_01				
L3BU_28_02				
L3BU_28_03				
L3BU_28_04				
L3BU_28_05				
L3BU_28_06				
L3BU_28_07				
L3BU_28_08				
L3BU_28_09				
L3BU_28_10				
L3BU_28_11				
L3BU_28_12				
L3BU_28_13				
L3BU_28_14				
L3BU_28_15				
L3BU_28_16				
L3BU_28_17				
L3BU_28_18				
L3BU_28_19				
L3BU_28_20				
L3BU_28_21				
L3BU_28_22				
L3BU_28_23				
L3BU_28_24				
L3BU_28_25				
L3BU_28_26				
L3BU_28_27				
L3BU_28_28				
L3BU_28_29				
L3BU_28_30				
L3BU_28_31				
L3BU_28_32				
L3BU_28_33				
L3BU_28_34				
L3BU_28_35				
L3BU_28_36				
L3BU_28_37				
L3BU_28_38				
L3BU_29_01				
L3BU_29_02				
L3BU_29_03				
L3BU_29_04				
L3BU_29_05				
L3BU_29_06				
L3BU_29_07				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_29_08				
L3BU_29_09				
L3BU_29_10				
L3BU_29_11				
L3BU_29_12				
L3BU_29_13				
L3BU_29_14				
L3BU_29_15				
L3BU_29_16				
L3BU_29_17				
L3BU_29_18				
L3BU_29_19				
L3BU_29_20				
L3BU_29_21				
L3BU_29_22				
L3BU_29_23				
L3BU_29_24				
L3BU_29_25				
L3BU_29_26				
L3BU_29_27				
L3BU_29_28				
L3BU_29_29				
L3BU_29_30				
L3BU_29_31				
L3BU_29_32				
L3BU_30_01				
L3BU_30_02				
L3BU_30_03				
L3BU_30_04				
L3BU_30_05				
L3BU_30_06				
L3BU_30_07				
L3BU_30_08				
L3BU_30_09				
L3BU_30_10				
L3BU_30_11				
L3BU_30_12				
L3BU_30_13				
L3BU_30_14				
L3BU_30_15				
L3BU_30_16				
L3BU_30_17				
L3BU_30_18				
L3BU_30_19				
L3BU_30_20				
L3BU_30_21				
L3BU_30_22				
L3BU_30_23				
L3BU_30_24				
L3BU_30_25				
L3BU_30_26				
L3BU_30_27				
L3BU_30_28				
L3BU_30_29				
L3BU_30_30				
L3BU_30_31				
L3BU_31_01				
L3BU_31_02				
L3BU_31_03				
L3BU_31_04				
L3BU_31_05				
L3BU_31_06				
L3BU_31_07				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_31_08				
L3BU_31_09				
L3BU_31_10				
L3BU_31_11				
L3BU_31_12				
L3BU_31_13				
L3BU_31_14				
L3BU_31_15				
L3BU_31_16				
L3BU_31_17				
L3BU_31_18				
L3BU_31_19				
L3BU_31_20				
L3BU_31_21				
L3BU_31_22				
L3BU_31_23				
L3BU_31_24				
L3BU_31_25				
L3BU_31_26				
L3BU_31_27				
L3BU_32_01				
L3BU_32_02				
L3BU_32_03				
L3BU_32_04				
L3BU_32_05				
L3BU_32_06				
L3BU_32_07				
L3BU_32_08				
L3BU_32_09				
L3BU_32_10				
L3BU_32_11				
L3BU_32_12				
L3BU_32_13				
L3BU_32_14				
L3BU_32_15				
L3BU_32_16				
L3BU_32_17				
L3BU_32_18				
L3BU_32_19				
L3BU_32_20				
L3BU_32_21				
L3BU_32_22				
L3BU_32_23				
L3BU_32_24				
L3BU_32_25				
L3BU_32_26				
L3BU_33_01				
L3BU_33_02				
L3BU_33_03				
L3BU_33_04				
L3BU_33_05				
L3BU_33_06				
L3BU_33_07				
L3BU_33_08				
L3BU_33_09				
L3BU_34_01				
L3BU_34_02				
L3BU_34_03				
L3BU_35_01				
L3BU_35_02				
L3BU_35_03				
L3BU_35_04				
L3BU_35_05				

ATS Reference	Selected ? (Y/N)	Run ? (Y/N)	Verdict	Observations
L3BU_35_06				
L3BU_35_07				

A.7 Observations

Additional information relevant to the technical content of the PCTR are given here.

.....

.....

.....

.....

.....

.....

Annex B (normative): Partial PIXIT proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PIXIT proforma in this annex so that it can be used for its intended purposes and may further publish the completed PIXIT.

B.1 Identification summary

PIXIT Number:

.....

Test Laboratory Name:

.....

Date of Issue:

.....

Issued to:

.....

B.2 Abstract test suite summary

Protocol Specification: EN 300 443-1

ATS Specification: EN 300 443-4

Abstract Test Method: Remote test method (see ISO/IEC 9646-2)

B.3 Test laboratory

Test Laboratory Identification:

.....

Accreditation status of the test service:

.....

Accreditation reference:

.....

Test Laboratory Manager:

.....

Test Laboratory contact:

.....

Means of Testing:

.....

Test Laboratory instructions for Completion:

.....

B.4 Client (of the Test Laboratory)

Client Identification:

.....

Client Test manager:

.....

Client contact:

.....

Test Facilities required:

.....

B.5 SUT

Name:

.....

Version:

.....

SCS Reference:

.....

Machine configuration:

.....

Operating System Identification:

.....

IUT Identification:

.....

PICS (all layers):

.....

.....

Limitations of the SUT:

.....

Environmental Conditions:

.....

B.6 Protocol information

B.6.1 Protocol identification

Specification reference: EN 300 443-1

Protocol Version:

PICS Reference:

NOTE: The PICS Reference should reference a completed PICS which is conformant with the PICS proforma contained in EN 300 443-2.

B.6.2 Configuration to be tested

Table B.1: Configuration to be tested

Item	Configuration The access to be tested ...	Supported Y/N
1.1	releases the layer 2 connection after entering the Null call state N0?	
Call/connection states		
1.2	is stable in the Call Received call/connection state U7 (i.e. CONNECT messages are not sent automatically)?	
1.3	is stable in the Incoming Call Proceeding call/connection state U9 (i.e. ALERTING and CONNECT messages are not sent automatically)?	
Compatibility checking		
1.4	checks the compatibility of the contents of the AAL parameters information element in incoming SETUP messages?	
1.5	checks the compatibility of the contents of the high layer compatibility information element in incoming SETUP messages?	
1.6	checks the compatibility of the contents of the low layer compatibility information element in incoming SETUP messages?	
1.7	has a number assigned to it?	
1.8	has a sub-address assigned to it?	
Associated signalling at the originating side (only, if PICS MCu 1,1 is supported)		
1.97	can be configured so that a specific VCI (given in PIXIT 4,21) in the VPC carrying the signalling VC is not available for switched connections.	
1.10	Can be configured so that all VCIs in the VPC carrying the signalling VC are not available for switched connections.	
Non-associated signalling at the originating side		
1.11	Can be configured so that a specific VCI (given in PIXIT 4,22) in a specific VPC (given in PIXIT 4,17) is not available for switched connections.	
1.12	can be configured so that a specific VPC (given in PIXIT 4,23) is not available for switched connections.	
1.13	can be configured so that no VCI is available.	

Item	Configuration The access to be tested ...	Supported Y/N
Restart procedures		
1.14	sends a RESTART message on the second expiry of timer T308 (no answer to RELEASE message).	
1.15	sends a RESTART message with the coding "indicated virtual channel" in the class field of the Restart indicator information element on the second expiry of timer T308. (only, if PIXIT 1,14 is supported)	
1.16	can be stimulated to send RESTART messages in incoming (answer YES) or outgoing calls (answer NO). This PIXIT item affects the preamble to all tests in the test groups 18 and 32. (only, if PIXIT 1,14 is supported, note)	
NOTE: If RESTART messages can be stimulated for both incoming and outgoing calls, answer "both" to that question. The relevant test groups have to be run twice then, once with this PIXIT item set to "YES" (incoming call) and once set to "NO" (outgoing call).		

B.6.3 Stimuli for the IUT

Table B.2: Actions required to stimulate the IUT

Item	Action What actions, if possible, have to be taken to ...	Supported Y/N	Stimulus (action taken)
Non-associated signalling at the origination side			
2.1	cause the IUT to send SETUP messages with the coding "exclusive VPCI, any VCI" in the preferred/exclusive field of the Connection identifier information element?		
2.2	cause the IUT to send SETUP messages with the coding "exclusive VPCI, exclusive VCI" in the preferred/exclusive field of the Connection identifier information element?		
Call refusal/clearing			
2.3	cause the IUT to refuse a compatible SETUP message by sending a RELEASE COMPLETE message indicating the cause value 21 "call rejected"?		
2.4	cause the IUT to be busy and to refuse a compatible SETUP message by sending a RELEASE COMPLETE message indicating the cause value 17 "user busy"?		
2.5	cause the IUT to send a RELEASE message in call/connection state U3?		
2.6	cause the IUT to send a RELEASE message in call/connection state U4?		
2.7	cause the IUT to send a RELEASE message in call/connection state U7?		
2.8	cause the IUT to send a RELEASE message in call/connection state U8?		
2.9	cause the IUT to send a RELEASE message in call/connection state U9?		
2.10	cause the IUT to send a RELEASE message in call/connection state U10?		
Notification procedure			
2.11	cause the IUT to send a NOTIFY message in call/connection state U10?		

Item	Action What actions, if possible, have to be taken to ...	Supported Y/N	Stimulus (action taken)
Provision of 64 kbit/s circuit mode-services (only, if PICS MCu 9 is supported)			
2.12	initiate a call originating in the N-ISDN towards the tester?		
2.13	initiate a call originating in the N-ISDN that carries high layer compatibility information towards the tester?		
2.14	initiate a call originating in the N-ISDN that carries low layer compatibility information towards the tester?		

B.6.4 Test management timers

Table B.3: Timer values

Item	Timer Give a value for the timer that is used ...	Value (in seconds)
3.1	as network side value for T308 (default value 4 seconds).	
3.2	as network side value for T310 (default value 10 seconds).	
3.3	to wait for the IUT to respond to a stimulus sent by the tester (TAC).	
3.4	to control that the IUT does not respond to a stimulus sent by the tester (TNOAC).	
3.5	to wait for the test operator to perform an implicit send action or to wait for a PTC to react (TWAIT).	
NOTE:	The IUT provider may fill in a value range rather than a fixed value for the test management timers. During test execution the test laboratory will choose specific values for the timers dependant on the means of testing used. These specific values may even be beyond the range given by the IUT provider, if this is necessary for achieving satisfactory test results.	

B.6.5 Parameter Values

Table B.4: Parameter values

Item	Parameter values Give ...	Value
ATM adaption layer parameters		
4.1	a coding of an AAL parameters information element, which the IUT does not support, for the purpose of rejecting incoming calls.	
Broadband bearer capability		
4.2	a coding of a Broadband bearer capability information element, which the IUT is compatible with, for the purpose of accepting incoming calls.	
4.3	a coding of a Broadband bearer capability information element for the provision of 64 kbit/s circuit mode services (BCOB-A, susceptible to clipping), which the IUT is compatible with, for the purpose of accepting incoming calls.	
4.4	a coding of a Broadband bearer capability information element indicating a service that is not supported, for the purpose of rejecting incoming calls. (note)	
Narrowband bearer capability		
4.5	a coding of a Narrowband bearer capability information element, which the IUT is compatible with, for the purpose of accepting incoming calls. (only, if PICS MCu 9 is supported)	
Called party number		
4.6.1	a coding of the Type of number and the Addressing/Numbering plan identification fields of the Called party number information elements to be sent to the IUT.	

Item	Parameter values Give ...	Value
4.6.2	a coding of valid number digits.	
4.7	a coding of an incomplete set of number digits for the purpose of rejecting incoming calls.	
4.8	a coding of an invalid or mis-matching set of number digits for the purpose of rejecting incoming calls.	
Called party sub-address		
4.9	a coding of an invalid or mis-matching set of sub-address information for the purpose of rejecting incoming calls.	
ATM traffic descriptor		
4.10	a coding of an ATM traffic descriptor information element, which the IUT is compatible with, for the purpose of accepting incoming calls.	
4.11	a coding of an ATM traffic descriptor information element indicating a peak cell rate that can not be not provided, for the purpose of rejecting incoming calls. (note)	
Quality of service		
4.12	a coding of a Quality of service information element indicating a QOS class that can not be not provided, for the purpose of rejecting incoming calls. (note)	
En-to-end transit delay		
4.13	a coding of an End-to-end transit delay information element indicating a cumulative transit delay that can not be not accepted, for the purpose of rejecting incoming calls. (note)	
High layer compatibility		
4.14	a coding of an incompatible High layer compatibility information element for the purpose of rejecting incoming calls. (note)	
Low layer compatibility		
4.15	a coding of an incompatible Low layer compatibility information element for the purpose of rejecting incoming calls. (note)	
Notification indicator		
4.16	a coding of a Notification indicator information element to be sent to the IUT.	
4.17	an invalid coding of a Notification indicator information element to be sent to the IUT for the purpose of testing the IUT's reaction on the receipt of an information element with content error. (note)	
Connection identifier		
4.18	a value for the preferred VPCI.	
4.19	a value for the preferred VCI.	
4.20	the value for the VPCI carrying the signalling VCI	
4.21	the value for the signalling VCI	
4.22	a value for a VCI in the VPCI carrying the signalling VCI that has been made unavailable. (Associated signalling, only if PIXIT 1,9 is supported)	
4.23	a value for a VCI in the VPCI given by PIXIT item 4.17 that has been made unavailable. (Non-associated signalling, only if PIXIT 1,10 is supported)	
4.24	a value for a VPCI that has been made unavailable. (Associated signalling, only if PIXIT 1,12 is supported)	
4.25	a value for a VPCI that is not recognized by the IUT when received in a RESTART messages. (note)	
Error values		
4.26	a value for an unrecognized message type.	
4.27	a value for an unrecognized information element identifier.	
4.28	a value for an unrecognized protocol discriminator.	
NOTE: These fields need only be completed, if the specified coding exists.		

Annex C (normative): Abstract Test Suite (ATS)

This ATS has been produced using the Tree and Tabular Combined Notation (TTCN) according to ISO/IEC 9646-3 [6].

The ATS was developed on a separate TTCN software tool and therefore the TTCN tables are not completely referenced in the table of contents. The ATS itself contains a test suite overview part which provides additional information and references.

C.1 The TTCN Graphical form (TTCN.GR)

The TTCN.GR representation of this ATS is contained in an Adobe Portable Document Format™ file (443_4_2.PDF contained in archive en_30044304v010102p0.ZIP) which accompanies the present document.

C.2 The TTCN Machine Processable form (TTCN.MP)

The TTCN.MP representation corresponding to this ATS is contained in an ASCII file (443_4_2.MP contained in archive en_30044304v010102p0.ZIP) which accompanies the present document.

History

Document history		
V1.1.1	July 1999	Public Enquiry PE 9949: 1999-07-07 to 1999-11-05
V1.1.2	March 2000	Vote V 20000519: 2000-03-20 to 2000-05-19
V1.1.2	June 2000	Publication