

Draft **EN 301 002-5** V1.1.3 (1999-07)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);
Security tools (SET) procedures;
Digital Subscriber Signalling System No. one (DSS1) protocol;
Part 5: Test Suite Structure and Test Purposes (TSS&TP)
specification for the network**



Reference

DEN/SPS-05141-5 (9a190ie0.PDF)

Keywords

ISDN, DSS1, supplementary services, security,
TSS&TP, network

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
<http://www.etsi.org>
If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	4
1 Scope.....	5
2 References	5
3 Definitions and abbreviations	6
3.1 Definitions	6
3.1.1 Definitions related to conformance testing.....	6
3.1.2 Definitions related to EN 301 002-1	6
3.2 Abbreviations.....	7
4 Test Suite Structure (TSS).....	7
5 Test Purposes (TP)	7
5.1 Introduction	7
5.1.1 TP naming convention	7
5.1.2 Source of TP definition	8
5.1.3 TP structure.....	8
5.1.4 Test strategy	9
5.2 Network TPs for SET	9
5.2.1 Signalling procedures at the coincident S and T reference point and for interworking with private ISDN	9
5.2.1.1 Registration - PIN.....	9
5.2.1.2 Invocation and Operation	10
5.2.1.3 Notification of possible fraudulent use	11
5.2.1.3.1 PIN.....	11
5.2.1.3.2 TAN	11
6 Compliance	12
7 Requirements for a comprehensive testing service	12
Bibliography	13
History.....	14

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by by ETSI Technical Committee Services and Protocol for Advanced Networks (SPAN), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document is part 5 of a multi-part standard covering the Digital Subscriber Signalling System No. one (DSS1) protocol specification for the Integrated Services Digital Network (ISDN) Security tools (SET) procedures, as described below:

- Part 1: "Protocol specification";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";**
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

This fifth part of EN 301 002 specifies the Test Suite Structure and Test Purposes (TSS&TP) for the network side of the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [7]) of implementations conforming to the stage three standard for the Security tools (SET) procedures for the pan-European Integrated Services Digital Network (ISDN) by means of the Digital Subscriber Signalling System No. one (DSS1) protocol, EN 301 002-1 [1].

A further part of the present document specifies the Abstract Test Suite (ATS) and partial PIXIT proforma based on the present document. Other parts specify the TSS&TP and the ATS and partial PIXIT proforma for the User side of the T reference point or coincident S and T reference point of implementations conforming to EN 301 002-1 [1].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] EN 301 002-1: "Integrated Services Digital Network (ISDN); Security tools (SET) procedures; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [2] EN 301 002-2: "Integrated Services Digital Network (ISDN); Security tools (SET) procedures; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [4] ISO/IEC 9646-2: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract test suite specification".
- [5] EN 300 196-1: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [6] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces - Reference configurations".
- [7] EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".
- [8] ITU-T Recommendation I.112 (1993): "Vocabulary of terms for ISDNs".
- [9] CCITT Recommendation E.164 (1991): "Numbering plan for the ISDN era".
- [10] ITU-T Recommendation I.210 (1993): "Principles of the telecommunication services supported by an ISDN and the means to describe them".
- [11] ETS 300 406 (1995): "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [12] ETR 232: "Security Techniques Advisory Group (STAG); Glossary of security terminology".

- [13] EN 301 132: "Integrated Services Digital Network (ISDN); Security tools (SET) for use within telecommunication services".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply.

3.1.1 Definitions related to conformance testing

Abstract Test Suite (ATS): refer to ISO/IEC 9646-1 [3]

Implementation Under Test (IUT): refer to ISO/IEC 9646-1 [3]

Protocol Implementation Conformance Statement (PICS): refer to ISO/IEC 9646-1 [3]

PICS proforma: refer to ISO/IEC 9646-1 [3]

Protocol Implementation eXtra Information for Testing (PIXIT): refer to ISO/IEC 9646-1 [3]

PIXIT proforma: refer to ISO/IEC 9646-1 [3]

system under test: refer to ISO/IEC 9646-1 [3]

Test Purpose (TP): refer to ISO/IEC 9646-1 [3]

3.1.2 Definitions related to EN 301 002-1

component: see EN 300 196-1 [5], subclause 11.2.2.1

Dummy call reference: see EN 300 403-1 [7], subclause 4.3

Integrated Services Digital Network (ISDN): see ITU-T Recommendation I.112 [8], definition 308

invoke component: see EN 300 196-1 [5], subclause 11.2.2.1

ISDN number: number conforming to the numbering and structure specified in CCITT Recommendation E.164 [9]

Personal Identification Number (PIN): see ETR 232 [12]

return error component: see EN 300 196-1 [5], subclause 11.2.2.1

return result component: see EN 300 196-1 [5], subclause 11.2.2.1

S/T: DSS1 protocol entity at the User side of the user-network interface where a coincident S and T reference point applies

security tool: see DEN/NA-010036 [13], clause 3

served user: user to whom a security tool is provided in combination with a telecommunication service

service; telecommunication service: see ITU-T Recommendation I.112 [8], definition 201

supplementary service: see ITU-T Recommendation I.210 [10], subclause 2.4

T: DSS1 protocol entity at the User side of the user-network interface where a T reference point applies (User is a Private ISDN)

Transaction Number (TAN): see EN 301 132 [13], clause 3

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATS	Abstract Test Suite
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
SET	Security tools
TAN	Transaction Number
TP	Test Purpose
TSS	Test Suite Structure

4 Test Suite Structure (TSS)

Signalling procedures at the coincident S and T reference point and for interworking with private ISDN	Group
Registration - PIN	N01
Invocation and operation (exceptional procedures)	N02
Notification of possible fraudulent use	
PIN	N03
TAN	N04

Figure 1: Test suite structure

5 Test Purposes (TP)

5.1 Introduction

For each test requirement a TP is defined.

5.1.1 TP naming convention

Tps are numbered, starting at 001, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite and whether it applies to the network or the user (see table 1).

Table 1: TP identifier naming convention scheme

Identifier: <ss>_<iut><group>_<nnn>			
<ss>	=	supplementary service:	"SET"
<iut>	=	type of IUT:	U User N Network
<group>	=	group	2 digit field representing group reference according to TSS
<nnn>	=	sequential number	(001-999)

5.1.2 Source of TP definition

The TPs are based on EN 301 002-1 [1].

5.1.3 TP structure

Each TP has been written in a manner which is consistent with all other TPs. The intention of this is to make the TPs more readable and checkable. A particular structure has been used and this is illustrated in table 2. This table should be read in conjunction with any TP, i.e. use a TP as an example to fully understand the table.

Table 2: Structure of a single TP for SET

TP Part	Text	Example
Header	TP Identifier Reference to the subclause of the base specification containing the conformance requirement. Reference to selection criteria	see table 1 subclause 9.1.1 see note 1
Stimulus	Ensure that the IUT in the <basic call state> and <supplementary service state> <trigger> <i>see below for message structure</i> <i>or</i> <goal>	U00, U10 etc. SCNFR Wait Deactivation state receiving a XXXX message to request a ...
Reaction	<action> <conditions> <i>if the action is sending</i> <i>see below for message structure</i> <next action>, etc. and enters <supplementary service state> <i>and/or</i> and remains in the same call state(s) <i>or</i> and enters call state <state>	sends, saves, does, etc. using en-bloc sending, ...
Message structure	<message type> message containing a a) <info element> information element with b) a <field name> encoded as <i>or</i> including <coding of the field> and <i>back to a or b</i> ,	SETUP, FACILITY, CONNECT, ... Bearer capability, Facility, ... see note 2
Selection	Selection criteria reference	Call forwarding supported. PICS: R 1.3
NOTE 1:	In order to use the same structure as for test group selection, the selection criteria is indicated at the bottom of the test purpose.	
NOTE 2:	Unless specified the messages are valid and contain at least the mandatory information elements and possibly optional information elements, the information elements are valid and contain at least the mandatory parameters and possibly optional parameters.	

5.1.4 Test strategy

As the base standard EN 301 002-1 [1] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the PICS specification EN 301 002-2 [2].

The TPs are only based on conformance requirements related to the externally observable behaviour of the IUT, and are limited to conceivable situations to which a real implementation is likely to be faced (ETS 300 406 [11]).

All the test purposes are mandatory unless they have a selection criteria. Optional test purposes (with selection criteria), are applicable according to the configuration options of the IUT. The configuration option shall be covered by a PICS item.

5.2 Network TPs for SET

All PICS items referred to in this subclause are as specified in EN 301 002-2 [2] unless indicated otherwise by another numbered reference.

Unless specified:

- The messages indicated are valid and contain at least the mandatory information elements and possibly optional information elements.
- The information elements indicated are valid and contain at least the mandatory parameters and possibly optional parameters.
- The FACILITY messages are transmitted using the point to point connectionless bearer independent transport mechanism (dummy call reference, DL-DATA-REQUEST) as specified in subclause 8.3.2.2 of EN 300 196-1 [5]. Where the broadcast connectionless bearer independent transport mechanism applies (dummy call reference, DL-UNIT DATA-REQUEST), the indication of the corresponding subclause of EN 300 196-1 is given (i.e. subclause 8.3.2.4 of [5]).

5.2.1 Signalling procedures at the coincident S and T reference point and for interworking with private ISDN

NOTE: The signalling procedures use mainly the bearer-independent connectionless transport mechanism with the dummy call reference. To augment the readability of the test purposes, basic call states are only mentioned where significant.

5.2.1.1 Registration - PIN

Selection: IUT supports registration of PIN security. PICS: R 4.1.

SET_N01_001 subclause 9.3.1

Ensure that the IUT in the Idle state, on receipt of a FACILITY message containing a Facility information element with a ModifyPin invoke component including the oldPin, the newPin and the servedUserNr parameters,
sends a FACILITY message containing a Facility information element with a ModifyPin return result component and enters the Idle state.

SET_N01_002 subclause 9.3.2

Ensure that the IUT in the Idle state, on receipt of a FACILITY message containing a Facility information element with a ModifyPin invoke component including the oldPin, the newPin parameters and the servedUserNr parameter including an invalid number,
sends a FACILITY message containing a Facility information element with a ModifyPin return error component indicating "invalidServedUserNr" and enters the Idle state.

SET_N01_003 subclause 9.3.2

Ensure that the IUT in the Idle state, on receipt of a FACILITY message containing a Facility information element with a ModifyPin invoke component, and no telecommunication service using a PIN is subscribed to,
sends a FACILITY message containing a Facility information element with a ModifyPin return error component indicating "pinNotProvided" and enters the Idle state.

SET_N01_004 subclause 9.3.2

Ensure that the IUT in the Idle state, on receipt of a FACILITY message containing a Facility information element with a ModifyPin invoke component, and the served user has exceeded the number of times (blocking limit N) that an invalid PIN can be used,

sends a FACILITY message containing a Facility information element with a ModifyPin return error component indicating "userControlBlocked" and enters the Idle state.

SET_N01_005 subclause 9.3.2

Ensure that the IUT in the Idle state, on receipt of a FACILITY message containing a Facility information element with a ModifyPin invoke component containing an oldPin parameter that does not match the currently registered PIN,

sends a FACILITY message containing a Facility information element with a ModifyPin return error component indicating "invalidPin" and enters the Idle state.

SET_N01_006 subclause 9.3.2

Ensure that the IUT in the Idle state, on receipt of a FACILITY message containing a Facility information element with a ModifyPin invoke component containing a newPin parameter with a wrong format,

sends a FACILITY message containing a Facility information element with a ModifyPin return error component indicating "invalidNewPin" and enters the Idle state.

SET_N01_007 subclause 9.3.2

Ensure that the IUT in the Idle state, on receipt of a FACILITY message containing a Facility information element with a ModifyPin invoke component containing a newPin parameter with a primitive PIN,

sends a FACILITY message containing a Facility information element with a ModifyPin return error component indicating "primitivePin" and enters the Idle state.

SET_N01_008 subclause 9.3.2

Ensure that the IUT in the Idle state, on receipt of a FACILITY message containing a Facility information element with a ModifyPin invoke component containing a newPin parameter that is identical to the currently registered PIN,

sends a FACILITY message containing a Facility information element with a ModifyPin return error component indicating "newPinIsOldPin" and enters the Idle state.

5.2.1.2 Invocation and Operation

Invocation of the PIN security tool shall consist of using the registered PIN in association with certain telecommunication services, requiring this security tool. The procedures related to the use of a PIN or a TAN in association with telecommunication services are described in the appropriate telecommunication services. Consequently, the test purposes concerning these invocation and operation procedures are included in the TSS&TP documents of the relevant telecommunication services (e.g. Outgoing Call Barring, Remote Control, ...).

The following test purposes check the exceptional procedures in relation with any telecommunication service using PIN or TAN. The signalling procedures are depending on the telecommunication service. Therefore the test purposes are only defined in a generic way.

SET_N02_001 subclause 9.6.2

Ensure that the IUT in the Idle state, having used a telecommunication service with a valid PIN that has expired, sends an appropriate message containing the error value "newPinIsOldPin" and enters the Idle state.

SET_N02_002 subclause 9.6.2

Ensure that the IUT in the Idle state, having used a telecommunication service with a PIN that does not match the currently registered PIN,

sends an appropriate message containing the error value "invalidPin" and enters the Idle state.

SET_N02_003 subclause 9.6.2

Ensure that the IUT in the Idle state, having used a telecommunication service, and the served user has exceeded the number of times (blocking limit N) that an invalid PIN can be used,

sends an appropriate message containing the error value "userControlBlocked" and enters the Idle state.

SET_N02_004 subclause 9.6.2

Ensure that the IUT in the Idle state, having used a telecommunication service with a TAN that does not match the currently registered TAN,

sends an appropriate message containing the error value "invalidTan" and enters the Idle state.

SET_N02_005 subclause 9.6.2

Ensure that the IUT in the Idle state, having used a telecommunication service, and the served user has exceeded the number of times (blocking limit N) that an invalid TAN can be used,
sends an appropriate message containing the error value "userControlBlocked" and enters the Idle state.

5.2.1.3 Notification of possible fraudulent use**5.2.1.3.1 PIN****SET_N03_001 subclause 9.7**

Ensure that the IUT in the Idle state, to indicate that one or more attempts (but less than the blocking limit N whereby all procedures using a PIN are blocked) have been made to use an invalid PIN, and MSN is not provided to the served user,
sends a FACILITY message (subclause 8.3.2.4 of [5]) containing a Facility information element with a PossibleFraudulentPinUse invoke component, and no Called Party Number information element, and remains in the Idle state.

SET_N03_002 subclause 9.7

Ensure that the IUT in the Idle state, to indicate that the network option applies to automatically reinitialize the blocked PIN security tool after a predefined time period, with the served user having not yet received a notification of possible fraudulent use while use of the PIN was not blocked, and MSN is not provided to the served user,
sends a FACILITY message (subclause 8.3.2.4 of [5]) containing a Facility information element with a PossibleFraudulentPinUse invoke component, and no Called Party Number information element, and remains in the Idle state.

SET_N03_003 subclause 9.7

Ensure that the IUT in the Idle state, to indicate that one or more attempts (but less than the blocking limit N whereby all procedures using a PIN are blocked) have been made to use an invalid PIN, and MSN is provided to the served user,
sends a FACILITY message (subclause 8.3.2.4 of [5]) containing a Facility information element with a PossibleFraudulentPinUse invoke component, and a Called Party Number information element including the multiple subscriber number of the served user, and remains in the Idle state.

Selection: S/T reference point (no private ISDN). PICS: R 3.1.

SET_N03_004 subclause 9.7

Ensure that the IUT in the Idle state, to indicate that the network option applies to automatically reinitialize the blocked PIN security tool after a predefined time period, with the served user having not yet received a notification of possible fraudulent use while use of the PIN was not blocked, and MSN is provided to the served user,
sends a FACILITY message (subclause 8.3.2.4 of [5]) containing a Facility information element with a PossibleFraudulentPinUse invoke component, and no Called Party Number information element, and remains in the Idle state.

5.2.1.3.2 TAN**SET_N04_001 subclause 9.8**

Ensure that the IUT in the Idle state, to indicate that one or more attempts (but less than the blocking limit N whereby all procedures using a TAN are blocked) have been made to use an invalid TAN, and MSN is not provided to the served user,
sends a FACILITY message (subclause 8.3.2.4 of [5]) containing a Facility information element with a PossibleFraudulentTanUse invoke component, and no Called Party Number information element, and remains in the Idle state.

SET_N04_002 subclause 9.8

Ensure that the IUT in the Idle state, to indicate that the network option applies to automatically reinitialize the blocked TAN security tool after a predefined time period, with the served user having not yet received a notification of possible fraudulent use while use of the TAN was not blocked, and MSN is not provided to the served user,
sends a FACILITY message (subclause 8.3.2.4 of [5]) containing a Facility information element with a PossibleFraudulentTanUse invoke component, and no Called Party Number information element, and remains in the Idle state.

SET_N04_003 subclause 9.8

Ensure that the IUT in the Idle state, to indicate that one or more attempts (but less than the blocking limit N whereby all procedures using a TAN are blocked) have been made to use an invalid TAN, and MSN is provided to the served user, sends a FACILITY message (subclause 8.3.2.4 of [5]) containing a Facility information element with a PossibleFraudulentTanUse invoke component, and a Called Party Number information element including the multiple subscriber number of the served user, and remains in the Idle state.

Selection: S/T reference point (no private ISDN). PICS: R 3.1.

SET_N04_004 subclause 9.8

Ensure that the IUT in the Idle state, to indicate that the network option applies to automatically reinitialize the blocked TAN security tool after a predefined time period, with the served user having not yet received a notification of possible fraudulent use while use of the TAN was not blocked, and MSN is provided to the served user, sends a FACILITY message (subclause 8.3.2.4 of [5]) containing a Facility information element with a PossibleFraudulentTanUse invoke component, and no Called Party Number information element, and remains in the Idle state.

6 Compliance

An ATS which complies with this TSS&TP specification shall:

- a) consist of a set of test cases corresponding to the set or to a subset of the TPs specified in clause 6;
- b) use a TSS which is an appropriate subset of the whole of the TSS specified in clause 4;
- c) use the same naming conventions for the test groups and test cases;
- d) maintain the relationship specified in clause 5 between the test groups and TPs and the entries in the PICS proforma to be used for test case deselection;
- e) comply with ISO/IEC 9646-2 [4].

In the case of a) or b) above, a subset shall be used only where a particular Abstract Test Method (ATM) makes some TPs untestable. All testable TPs from clause 5 shall be included in a compliant ATS.

7 Requirements for a comprehensive testing service

As a minimum the Remote test method, as specified in ISO/IEC 9646-2 [4], shall be used by any organization claiming to provide a comprehensive testing service for network equipment claiming conformance to EN 301 002-1 [1].

Bibliography

The following material, though not specifically referenced in the body of the present document (or not publicly available), gives supporting information.

- ISO/IEC 9646-3: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 3: The Tree and Tabular Combined Notation (TTCN)".
- EN 300 403-3: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 3: Protocol Implementation Conformance Statement (PICS) proforma specification".

History

Document history		
V1.1.3	July 1999	Public Enquiry PE 9951: 1999-07-21 to 1999-11-19