

Draft **EN 301 029-1** V1.1.1 (1997-04)

---

*European Standard (Telecommunications series)*

**Broadband Integrated Services Digital Network (B-ISDN);  
Signalling System No.7;  
B-ISDN User Part (B-ISUP);  
Part 1: Overview of the B-ISDN network node interface  
signalling capability set 2, step 1**

[ITU-T Recommendation Q.2721.1 (1996)]

---



*European Telecommunications Standards Institute*

---

---

Reference

DEN/SPS-01043-1 (9j090ico.PDF)

---

Keywords

B-ISDN, SS7, B-ISUP, NNI

***ETSI Secretariat***

---

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

---

Office address

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16  
Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

X.400

c= fr; a=atlas; p=etsi; s=secretariat

---

Internet

secretariat@etsi.fr  
<http://www.etsi.fr>

---

***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

---

## Intellectual Property Rights

ETSI has not been informed of the existence of any Intellectual Property Right (IPR) which could be, or could become essential to the present document. However, pursuant to the ETSI Interim IPR Policy, no investigation, including IPR searches, has been carried out. No guarantee can be given as to the existence of any IPRs which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure (TAP).

The present document is part 1 of a multi-part standard covering the Broadband Integrated Services Digital Network (B-ISDN) User Part (B-ISUP) signalling capability set 2, step 1, as identified below:

- Part 1:** "Overview of the B-ISDN network node interface signalling capability set 2, step 1 [ITU-T Recommendation Q.2721.1 (1996)]";
- Part 2: "Network node interface specification for point-to-multipoint call/connection control [ITU-T Recommendation Q.2722.1 (1996)]";
- Part 3: "Support of additional traffic parameters for statistical bit rate and quality of service [ITU-T Recommendation Q.2723.1 (1996)]";
- Part 4: "Look-ahead without state change for the network node interface [ITU-T Recommendation Q.2724.1 (1996)]";
- Part 5: "Support of negotiation during connection setup [ITU-T Recommendation Q.2725.1 (1996)]";
- Part 6: "Modification procedures [ITU-T Recommendation Q.2725.2 (1996)]";
- Part 7: "ATM end system address for calling and called party [ITU-T Recommendation Q.2726.1 (1996)]";
- Part 8: "Call priority [ITU-T Recommendation Q.2726.2 (1996)]";
- Part 9: "Network generated session identifier [ITU-T Recommendation Q.2726.3 (1996)]";
- Part 10: "Support of frame relay [ITU-T Recommendation Q.2727 (1996)]".

<b>Proposed national transposition dates</b>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

---

## Endorsement notice

The text of ITU-T Recommendation Q.2721.1 (1996) was approved by ETSI as an EN without any modifications.

---

## History

<b>Document history</b>		
V1.1.1	April 1997	Public Enquiry PE 9733: 1997-04-18 to 1997-08-15