



**Meteorological Aids (Met Aids);
Radiosondes to be used in the 400,15 MHz to 406 MHz
frequency range with power levels ranging up to 200 mW;
Part 2: Harmonised Standard covering the essential
requirements of article 3.2 of the Directive 2014/53/EU**

Reference

REN/ERM-JTFEA-26

Keywords

radio, regulation, short range, testing, UHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
Executive summary	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definitions, symbols and abbreviations	6
3.1 Definitions	6
3.2 Symbols.....	6
3.3 Abbreviations	7
4 Technical requirements specifications	7
4.1 Environmental profile.....	7
4.2 Conformance requirements	7
4.2.1 Transmitter requirements	7
4.2.1.1 Frequency error	7
4.2.1.2 Carrier power (conducted)	7
4.2.1.3 Effective radiated power	7
4.2.1.4 Modulation bandwidth	7
4.2.1.5 Spurious emissions.....	7
4.2.1.6 Frequency stability under low-voltage conditions	7
5 Testing for compliance with technical requirements.....	8
5.1 Environmental conditions for testing	8
5.1.1 Normal and extreme test-conditions	8
5.1.2 Test power source	8
5.2 Interpretation of the measurement results	8
5.3 Radio test suites.....	8
5.3.1 Transmitter test specifications	8
5.3.1.1 Frequency error	8
5.3.1.2 Carrier power (conducted)	8
5.3.1.3 Effective radiated power	9
5.3.1.4 Modulation bandwidth	9
5.3.1.5 Spurious emissions.....	9
5.3.1.6 Frequency stability under low-voltage conditions	9
Annex A (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU	10
History	11

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared in reply to the Commission's standardisation request Commission Implementing Decision C(2015) 5376 final of 04.08.2015 to provide a means of conforming to the essential requirements of Directive 2014/53/EU on "the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment" - also known as the Radio Equipment Directive [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 2 of a multi-part deliverable covering digitally modulated Radiosonde transmitters in the Meteorological Aids frequency band from 400,15 MHz to 406 MHz, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonised Standard covering the essential requirements of article 3.2 of the Directive 2014/53/EU".

National transposition dates	
Date of adoption of this EN:	22 October 2015
Date of latest announcement of this EN (doa):	31 January 2016
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2016
Date of withdrawal of any conflicting National Standard (dow):	31 July 2017

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Executive summary

The present document contains Conformance requirements for Meteorological Aids (Radiosondes) to be used in the 400,15 to 406 MHz frequency range. These requirements are defined for frequency error, carrier power, effective radiated power, modulation bandwidth, spurious emissions and frequency stability under low voltage conditions.

1 Scope

The present document applies to Radiosondes in the Meteorological Aids service to be used in the 400,15 MHz to 406 MHz frequency range with power levels ranging up to 200 mW.

The present document contains requirements to demonstrate that "... *Radio equipment shall be so constructed that it both effectively uses and supports the efficient use of radio spectrum in order to avoid harmful interference*" [i.1].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 302 054-1 (V1.2.1) (10-2015): "Meteorological Aids (Met Aids); Radiosondes to be used in the 400,15 MHz to 406 MHz frequency range with power levels ranging up to 200 mW; Part 1: Technical characteristics and test methods".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.3] ETSI TR 100 028-2 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
-

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the RE Directive [i.1] and ETSI EN 302 054-1 [1] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI EN 302 054-1 [1] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 302 054-1 [1] apply.

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Conformance requirements

4.2.1 Transmitter requirements

4.2.1.1 Frequency error

The frequency error, as defined in ETSI EN 302 054-1 [1], clause 7.2.1, shall not exceed the limits given in ETSI EN 302 054-1 [1], clause 7.2.3.

In order to assess compliance the test procedure in clause 5.3.1.1 shall be done.

4.2.1.2 Carrier power (conducted)

The carrier power (conducted), as defined in ETSI EN 302 054-1 [1], clause 7.3.1, shall not exceed the limits in ETSI EN 302 054-1 [1], clause 7.3.3.

NOTE: This requirement applies to transmitters which may be used without an integral or dedicated antenna.

In order to assess compliance the test procedure in clause 5.3.1.2 shall be done.

4.2.1.3 Effective radiated power

The effective radiated power, as defined in ETSI EN 302 054-1 [1], clause 7.4.1, shall not exceed the limits given in ETSI EN 302 054-1 [1], clause 7.4.3.

NOTE: This requirement applies to transmitters with an integral or dedicated antenna.

In order to assess compliance the test procedure in clause 5.3.1.3 shall be done.

4.2.1.4 Modulation bandwidth

The modulation bandwidth, as defined in ETSI EN 302 054-1 [1], clause 7.5.1, shall not exceed the limits in ETSI EN 302 054-1 [1], clause 7.5.3.

In order to assess compliance the test procedure in clause 5.3.1.4 shall be done.

4.2.1.5 Spurious emissions

The spurious emissions, as defined in ETSI EN 302 054-1 [1], clause 7.6.1, shall not exceed the limits given in ETSI EN 302 054-1 [1], clause 7.6.3.

In order to assess compliance the test procedure in clause 5.3.1.4 shall be done.

4.2.1.6 Frequency stability under low-voltage conditions

The frequency stability under low-voltage conditions, as defined in ETSI EN 302 054-1 [1], clause 7.7.1, shall comply conditions given in ETSI EN 302 054-1 [1], clause 7.7.3.

In order to assess compliance the test procedure in clause 5.3.1.5 shall be done.

5 Testing for compliance with technical requirements

5.1 Environmental conditions for testing

5.1.1 Normal and extreme test-conditions

Type tests shall be made under normal test conditions, and also, where stated, under extreme test conditions.

The test procedures shall be as specified in ETSI EN 302 054-1 [1], clauses 5.3 to 5.4.

5.1.2 Test power source

The test power source shall meet the requirements of ETSI EN 302 054-1 [1], clause 5.2.

5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the recorded value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 1.

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)). Principles for the calculation of measurement uncertainty are contained in ETSI TR 100 028 [i.2], in particular in annex D of the ETSI TR 100 028-2 [i.3].

Table 1 is based on such expansion factors.

Table 1: Maximum measurement uncertainty

Parameter	Uncertainty
Frequency error	$\pm 1 \times 10^{-7}$
Carrier power, conducted	$\pm 1,5$ dB
Radiated emission of transmitter, valid up to 4 GHz	± 6 dB
Conducted emission of transmitter, valid up to 4 GHz	± 3 dB
Temperature	± 1 °C
Relative Humidity	± 10 %RH
Voltage (DC)	± 1 %

5.3 Radio test suites

5.3.1 Transmitter test specifications

5.3.1.1 Frequency error

The test is specified in ETSI EN 302 054-1 [1], clause 7.2.

5.3.1.2 Carrier power (conducted)

The test is specified in ETSI EN 302 054-1 [1], clause 7.3.

5.3.1.3 Effective radiated power

The test is specified in ETSI EN 302 054-1 [1], clause 7.4.

5.3.1.4 Modulation bandwidth

The test is specified in ETSI EN 302 054-1 [1], clause 7.5.

5.3.1.5 Spurious emissions

The test is specified in ETSI EN 302 054-1 [1], clause 7.6.

5.3.1.6 Frequency stability under low-voltage conditions

The test is specified in ETSI EN 302 054-1 [1], clause 7.7.

Annex A (normative): Relationship between the present document and the essential requirements of Directive 2014/53/EU

The present document has been prepared in reply to the Commission's standardisation request Commission Implementing Decision C(2015) 5376 final of 04.08.2015 to provide a means of conforming to the essential requirements of Directive 2014/53/EU on "the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment" - also known as the Radio Equipment Directive [i.1].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

Table A.1: Relationship between the present document and the essential requirements of Directive 2014/53/EU

Harmonised Standard ETSI EN 302 054-2				
The following requirements are relevant to the presumption of conformity under the article 3.2 of Directive 2014/53/EU [i.1]				
Requirement			Requirement Conditionality	
No	Description	Reference: Clause No	U/C	Condition
1	Frequency error	4.2.1.1	U	
2	Carrier power	4.2.1.2	U	
3	Effective radiated power	4.2.1.3	U	
4	Modulation bandwidth	4.2.1.4	U	
5	Spurious emission	4.2.1.5	U	
6	Frequency stability under low-voltage conditions	4.2.1.6	U	

Key to columns:

Requirement:

- No** A unique identifier for one row of the table which may be used to identify a requirement.
- Description** A textual reference to the requirement.
- Clause Number** Identification of clause(s) defining the requirement in the present document unless another document is referenced explicitly.

Requirement Conditionality:

- U/C** Indicates whether the requirement shall be unconditionally applicable (U) or is conditional upon the manufacturers claimed functionality of the equipment (C).
- Condition** Explains the conditions when the requirement shall or shall not be applicable for a requirement which is classified "conditional".

Presumption of conformity stays valid only as long as a reference to the present document is maintained in the list published in the Official Journal of the European Union. Users of the present document should consult frequently the latest list published in the Official Journal of the European Union.

Other Union legislation may be applicable to the product(s) falling within the scope of the present document.

History

Document history		
V1.1.1	March 2003	Publication
V1.2.0	June 2015	EN Approval Procedure AP 20151022: 2015-06-24 to 2015-10-22
V1.2.1	October 2015	Publication