



**E**UROPEAN  
**T**ELECOMMUNICATION  
**S**TANDARD

**ETS 300 564**

August 1996

Third Edition

---

Source: ETSI TC-SMG

Reference: RE/SMG-030480PR2

ICS: 33.060.50

**Key words:** Digital cellular telecommunications system, Global System for Mobile communications (GSM)

**GSM**

GLOBAL SYSTEM FOR  
MOBILE COMMUNICATIONS

**Digital cellular telecommunications system (Phase 2);  
Mobile radio interface layer 3  
Supplementary services specification  
Formats and coding  
(GSM 04.80)**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

---

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.



## Contents

Foreword .....	5
1 Scope .....	7
1.1 Normative references .....	7
1.2 Abbreviations .....	8
2 Message functional definitions and contents .....	9
2.1 General .....	9
2.2 Messages for supplementary services control.....	10
2.3 Facility .....	10
2.4 Register.....	11
2.4.1 Register (network to mobile station direction).....	11
2.4.2 Register (mobile station to network direction).....	11
2.4.2.1 SS version .....	12
2.5 Release complete .....	12
2.5.1 Cause .....	12
2.5.2 Facility .....	12
3 General message format and information elements coding .....	13
3.1 Overview .....	13
3.2 Protocol discriminator .....	13
3.3 Transaction identifier .....	13
3.4 Message type.....	13
3.5 Other information elements .....	14
3.6 Facility information element .....	14
3.6.1 Component (octet 3 etc.).....	15
3.6.2 Component type tag .....	17
3.6.3 Component ID tag .....	17
3.6.4 Operation Code .....	18
3.6.5 Sequence and Set tags .....	18
3.6.6 Error Code.....	18
3.6.7 Problem Code .....	18
3.7 Version handling for supplementary services .....	20
3.7.1 Supplementary service screening indicator.....	20
3.7.2 Supplementary service version indicator.....	20
4 Supplementary services operation specifications .....	21
4.1 General .....	21
4.2 Operation types.....	22
4.2.1 [spare] .....	24
4.2.2 Operation types description.....	24
4.2.2.1 RegisterSS (MS --> network).....	24
4.2.2.2 EraseSS (MS --> network).....	24
4.2.2.3 ActivateSS (MS --> network) .....	24
4.2.2.4 DeactivateSS (MS --> network) .....	25
4.2.2.5 InterrogateSS (MS --> network).....	25
4.2.2.6 NotifySS (network --> MS).....	25
4.2.2.7 RegisterPassword (MS --> network).....	25
4.2.2.8 GetPassword (network --> MS) .....	25
4.2.2.9 ProcessUnstructuredSS-Data (MS --> network) .....	25
4.2.2.10 ProcessUnstructuredSS-Request (MS --> network).....	25
4.2.2.11 UnstructuredSS-Request (network --> MS).....	25
4.2.2.12 UnstructuredSS-Notify (network --> MS).....	25
4.2.2.13 ForwardCheckSSIndication (network --> MS) .....	25
4.2.2.14 ForwardChargeAdvice (network --> MS) .....	26
4.2.2.15 BuildMPTY (MS --> network).....	26
4.2.2.16 HoldMPTY (MS --> network) .....	26

	4.2.2.17	RetrieveMPTY (MS --> network).....	26
	4.2.2.18	SplitMPTY (MS --> network) .....	26
	4.2.2.19	ForwardCUG-Info (MS --> network).....	26
4.3	Error types.....		27
4.3.1	Error types ASN.1 specification .....		27
4.3.2	Error types description .....		27
	4.3.2.1	UnknownSubscriber.....	27
	4.3.2.2	BearerServiceNotProvisioned.....	27
	4.3.2.3	TeleServiceNotProvisioned.....	28
	4.3.2.4	IllegalSS-Operation .....	28
	4.3.2.5	SS-ErrorStatus .....	28
	4.3.2.6	SS-NotAvailable .....	28
	4.3.2.7	SS-SubscriptionViolation.....	28
	4.3.2.8	SS-Incompatibility .....	28
	4.3.2.9	SystemFailure .....	28
	4.3.2.10	DataMissing .....	28
	4.3.2.11	UnexpectedDataValue .....	28
	4.3.2.12	PasswordRegistrationFailure .....	29
	4.3.2.13	NegativePasswordCheck.....	29
	4.3.2.14	FacilityNotSupported.....	29
	4.3.2.15	ResourcesNotAvailable.....	29
	4.3.2.16	MaxNumberOfMPTY-ParticipantsExceeded .....	29
	4.3.2.17	CallBarred .....	29
	4.3.2.18	NumberOfPW-AttemptsViolation .....	29
	4.3.2.19	AbsentSubscriber.....	29
	4.3.2.20	IllegalSubscriber.....	29
	4.3.2.21	IllegalEquipment.....	30
	4.3.2.22	USSD-Busy .....	30
	4.3.2.23	UnknownAlphabet.....	30
4.4	Data types and identifiers.....		31
4.4.1	General .....		31
4.4.2	ASN.1 data types .....		31
4.4.3	Identifiers definition.....		33
	4.4.3.1	chargingInformation .....	33
	4.4.3.2	e1 .....	33
	4.4.3.3	e2 .....	33
	4.4.3.4	e3 .....	33
	4.4.3.5	e4 .....	33
	4.4.3.6	e5 .....	33
	4.4.3.7	e6 .....	33
	4.4.3.8	e7 .....	33
	4.4.3.9	ss-Code.....	34
	4.4.3.10	ss-Notification .....	34
	4.4.3.11	ss-Status .....	34
	4.4.3.12	callsWaiting-Indicator.....	34
	4.4.3.13	callOnhold-Indicator .....	34
	4.4.3.14	mpty-Indicator .....	34
	4.4.3.15	forwardCUG-InfoArg .....	34
	4.4.3.16	cug-Index .....	34
	4.4.3.17	suppressPrefCUG.....	34
	4.4.3.18	suppressOA .....	34
	4.4.3.19	clirSuppressionRejected .....	34
4.5	Operations and errors implementation.....		35
Annex A (informative):	Expanded ASN.1 Module "SS-Protocol" .....		37
History .....			49

## Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI).

This ETS specifies the coding of information necessary for support of supplementary service operation on the mobile radio interface layer 3 within the Digital cellular telecommunications system (Phase 2).

This ETS correspond to GSM technical specification, GSM 04.80 version 4.11.1.

Reference is made within this ETS to GSM Technical Specifications (GSM-TS) (note).

Reference is also made within this ETS to GSM 04.8x series. The specifications in the series can be identified, with their full title, within the normative reference Clause of this ETS by the last two digits of their GSM reference number e.g. GSM 04.8x series, refers to GSM 04.81, GSM 04.82, etc.

**NOTE:** TC-SMG has produced documents which give the technical specifications for the implementation of the Digital cellular telecommunications system. Historically, these documents have been identified as GSM Technical Specifications (GSM-TS). These TSs may have subsequently become I-ETTs (Phase 1), or ETs (Phase 2), whilst others may become ETSI Technical Reports (ETRs). GSM-TSs are, for editorial reasons, still referred to in current GSM ETs.

<b>Transposition dates</b>	
Date of adoption of this ETS:	31 August 1996
Date of latest announcement of this ETS (doa):	30 November 1996
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 May 1997
Date of withdrawal of any conflicting National Standard (dow):	31 May 1997

Blank page

## 1 Scope

This ETS contains the coding of information necessary for support of supplementary service operation on the mobile radio interface layer 3.

Clause 2 gives the functional definitions and contents of messages for call independent supplementary service operations. Messages necessary for support of call related supplementary service operations are defined in TS GSM 04.08.

Clause 3 gives the general format and coding for messages used for call independent supplementary service and the format and coding of information elements used for both call related and call independent supplementary service operations.

Clause 4 gives the specification of the call related and call independent supplementary service operations.

### 1.1 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] GSM 01.04 (ETR 100): "Digital cellular telecommunications system (Phase 2); Abbreviations and acronyms".
- [2] GSM 02.24 (ETS 300 510): "Digital cellular telecommunications system (Phase 2); Description of Charge Advice Information (CAI)".
- [3] GSM 04.06 (ETS 300 555): "Digital cellular telecommunications system (Phase 2); Mobile Station - Base Station system (MS - BSS) interface Data Link (DL) layer specification".
- [4] GSM 04.07 (ETS 300 556): "Digital cellular telecommunications system (Phase 2); Mobile radio interface signalling layer 3 General aspects".
- [5] GSM 04.08 (ETS 300 557): "Digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 specification".
- [6] GSM 04.10 (ETS 300 558): "Digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 Supplementary services specification General aspects".
- [7] GSM 04.80 (ETS 300 564): "Digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 supplementary services specification Formats and coding".
- [8] GSM 04.81 (ETS 300 565): "Digital cellular telecommunications system (Phase 2); Line identification supplementary services - Stage 3".
- [9] GSM 04.82 (ETS 300 566): "Digital cellular telecommunications system (Phase 2); Call Forwarding (CF) supplementary services - Stage 3".

- [10] GSM 04.83 (ETS 300 567): "Digital cellular telecommunications system (Phase 2); Call Waiting (CW) and Call Hold (HOLD) supplementary services - Stage 3".
- [11] GSM 04.84 (ETS 300 568): "Digital cellular telecommunications system (Phase 2); Multi Party (MPTY) supplementary services - Stage 3".
- [12] GSM 04.85 (ETS 300 569): "Digital cellular telecommunications system (Phase 2); Closed User Group (CUG) supplementary services - Stage 3".
- [13] GSM 04.86 (ETS 300 570): "Digital cellular telecommunications system (Phase 2); Advice of Charge (AoC) supplementary services - Stage 3".
- [14] GSM 04.88 (ETS 300 571): "Digital cellular telecommunications system (Phase 2); Call Barring (CB) supplementary services - Stage 3".
- [15] GSM 04.90 (ETS 300 572): "Digital cellular telecommunications system (Phase 2); Unstructured supplementary services operation - Stage 3".
- [16] GSM 09.02 (ETS 300 599): "Digital cellular telecommunications system (Phase 2); Mobile Application Part (MAP) specification".
- [17] GSM 09.11 (ETS 300 606): "Digital cellular telecommunications system (Phase 2); Signalling interworking for supplementary services".
- [18] CCITT Recommendation X.208: "Specification of basic encoding rules for Abstract Syntax Notation One (ASN.1)".
- [19] CCITT Recommendation X.209: "Specification of Abstract Syntax Notation One (ASN.1)".
- [20] CCITT Recommendation Q.773: "Transaction capabilities formats and encoding".

## 1.2 Abbreviations

Abbreviations used in this ETS are listed in GSM 01.04.



## 2 Message functional definitions and contents

### 2.1 General

This clause defines the structure of the messages of the layer 3 protocol defined in TS GSM 04.80. These messages are standard L3 messages as defined in TS GSM 04.07.

Each definition includes:

- a) a brief description of the message;
- b) a table listing the information elements in the order of their appearance in the message. In a sequence of consecutive IEs with half octet length, the first IE occupies bits 1 to 4 of octet N, the second bits 5 to 8 of octet N, the third bits 1 to 4 of octet N+1 etc.;

For each IE the table indicates:

- 1) the information element identifier, in hexadecimal notation, if the IE has format T, TV or TLV. If the IEI has half octet length, it is specified by a notation representing the IEI as a hexadecimal digit followed by a "-" (example: B-);
  - 2) the name of the IE (which gives an idea of the semantics of the element), which is used in this and other specifications as a reference to the IE within the message;
  - 3) the name of the type of the IE (which indicates the coding of the value part of the IE), and a reference to a description of the value part of the IE;
  - 4) the presence requirement indication (M, C or O) for the IE, as defined in TS GSM 04.07;
  - 5) the format of the IE (T, V, TV, LV, TLV) as defined in TS GSM 04.07;
  - 6) the length of the IE (or permissible range of lengths), in octets, in the message, where "?" means that the maximum length of the IE is only constrained by the link layer protocol, and in the case of the facility IE by possible further considerations specified in TS GSM 04.10. This indication is non-normative.
- c) subclauses specifying conditions for IEs with presence requirement C or O in the relevant message. Together with other conditions specified in TS GSM 04.80, GSM 04.10 or GSM 04.8x and 04.9x-series this defines when the IE shall be included or not, what non-presence of such IEs means, and (for IEs with presence requirement C) the static conditions for presence and/or non-presence of the IEs (see TS GSM 04.07).

## 2.2 Messages for supplementary services control

Table 2.1 summarizes the messages for call independent supplementary services control. See TS GSM 04.10 for a detailed description of call independent supplementary service messages.

**Table 2.1: Messages for call independent supplementary service control**

Messages for supplementary service control	Reference
FACILITY	2.3
REGISTER	2.4
RELEASE COMPLETE	2.5

## 2.3 Facility

This message is sent by the mobile station or the network to request or acknowledge a supplementary service. It is used when information is to be conveyed and the transaction already exists, but is not to be released. The supplementary service to be invoked, and its associated parameters, are specified in the Facility information element. See table 2.2.

**Table 2.2: FACILITY message content**

IEI	Information element	Type / Reference	Presence	Format	Length
	Supplementary service protocol discriminator	Protocol discriminator 3.2	M	V	1/2
	Transaction identifier	Transaction identifier 3.3	M	V	1/2
	Facility message type	Message type 3.4	M	V	1
	Facility	Facility 3.5	M	LV	2-?

## 2.4 Register

### 2.4.1 Register (network to mobile station direction)

This message is sent by the network to the mobile station to assign a new transaction identifier for call independent supplementary service control and to request or acknowledge a supplementary service. See table 2.3.

**Table 2.3: REGISTER message content (network to mobile station direction)**

IEI	Information element	Type / Reference	Presence	Format	Length
	Supplementary service protocol discriminator	Protocol discriminator 3.2	M	V	1/2
	Transaction identifier	Transaction identifier 3.3	M	V	1/2
	Register message type	Message type 3.4	M	V	1
1C	Facility	Facility 3.5	M	TLV	2-?

### 2.4.2 Register (mobile station to network direction)

This message is sent by the mobile station to the network to assign a new transaction identifier for call independent supplementary service control and to request or acknowledge a supplementary service. See table 2.4.

**Table 2.4: REGISTER message content (mobile station to network direction)**

IEI	Information element	Type / Reference	Presence	Format	Length
	Supplementary service protocol discriminator	Protocol discriminator 3.2	M	V	1/2
	Transaction identifier	Transaction identifier 3.3	M	V	1/2
	Register message type	Message type 3.4	M	V	1
1C	Facility	Facility 3.5	M	TLV	2-?
7F	SS version	SS version indicator 3.8.2	O	TLV	3

**2.4.2.1 SS version**

This information element shall be included if the supplementary service operation being invoked is implemented according to the phase 2 GSM standards.

**2.5 Release complete**

This message is sent by the mobile station or the network to release a transaction used for call independent supplementary service control. It may also request or acknowledge a supplementary service. See table 2.5.

**Table 2.5: RELEASE COMPLETE message content**

<b>IEI</b>	<b>Information element</b>	<b>Type / Reference</b>	<b>Presence</b>	<b>Format</b>	<b>Length</b>
	Supplementary service protocol discriminator	Protocol discriminator 3.2	M	V	1/2
	Transaction identifier	Transaction identifier 3.3	M	V	1/2
	Release Complete message type	Message type 3.4	M	V	1
08	Cause	Cause TS GSM 04.08	O	TLV	4-32
1C	Facility	Facility 3.5	O	TLV	2-?

**2.5.1 Cause**

This information element shall be included when the functional handling of the Cause IE is specified in the service description or TS GSM 09.11. If the functional handling of the Cause IE is not specified, the receiving entity may ignore the IE.

**2.5.2 Facility**

This information element shall be included as required by the service description and the procedures defined in TS GSM 04.10.

### 3 General message format and information elements coding

The figures and text in this clause describe message contents. Within each octet, the bit designated "bit 1" is transmitted first, followed by bits 2, 3, 4, etc. Similarly, the octet shown at the top of each figure is sent first.

#### 3.1 Overview

Within the layer 3 protocol defined in TS GSM 04.80, every message is a standard L3 message as defined in TS GSM 04.07. This means that the message consists of the following parts:

- a) protocol discriminator;
- b) transaction identifier;
- c) message type;
- d) other information elements, as required.

Unless specified otherwise, a particular information element may be present only once in a given message.

When a field extends over more than one octet, the order of bit values progressively decreases as the octet number increases. The least significant bit of the field is represented by the lowest numbered bit of the highest numbered octet of the field.

#### 3.2 Protocol discriminator

The Protocol Discriminator (PD) and its use are defined in TS GSM 04.07. TS GSM 04.80 defines the protocols relating to the PD values:

1 0 1 1      supplementary services (call independent).

#### 3.3 Transaction identifier

For general rules, format and coding of transaction identifier values, see TS GSM 04.08.

#### 3.4 Message type

The message type IE and its use are defined in TS GSM 04.07. Table 3.1 defines the value part of the message type IE used in the supplementary service protocol.

**Table 2.5: RELEASE COMPLETE message content**

8 7 6 5 4 3 2 1	Message types
0 x 1 0 . . . . 1 0 1 0	Clearing messages: - RELEASE COMPLETE
0 x 1 1 . . . . 1 0 1 0 1 0 1 1	Miscellaneous message group: - FACILITY - REGISTER

NOTE 1: Bit 8 is reserved for possible future use as an extension bit, see TS GSM 04.07.

NOTE 2: Bit 7 is reserved for the send sequence number in messages sent from the mobile station. In messages sent from the network, bit 7 is coded with a "0", see TS GSM 04.07.

**3.5 Other information elements**

These information elements are coded according to the general coding rules as defined in TS GSM 04.08.

Table 3.2 contains the code-points allocated to the information elements used in messages defined in this ETS. All IEs are defined in TS GSM 04.08, but the content of the Facility and SS version indicator IEs are defined within this ETS.

**Table 3.2: Information elements specific to call independent supplementary service control**

8 7 6 5 4 3 2 1		Reference (IE content)
0 . . . . .	Type 3 and 4 information elements	
0 0 0 1 0 0 0	Cause	TS GSM 04.08
0 0 1 1 1 0 0	Facility	3.6
1 1 1 1 1 1 1	SS version indicator	3.8.2

**3.6 Facility information element**

The purpose of the Facility information element is to indicate the invocation and operation of supplementary services, identified by the corresponding operation code within the Facility information element.

The Facility information element is coded as shown in figure 3.1 and tables 3.3 to 3.17.

The Facility is a type 4 information element with no upper length limit except that given by the maximum number of octets in a L3 message, see TS GSM 04.06.

8	7	6	5	4	3	2	1	
0	0	0	1	1	1	0	0	octet 1
Facility IEI								
Length of Facility contents								octet 2
Component(s) (note)								octet 3 etc.

NOTE: One or more components may be included depending on specific service requirements.

**Figure 3.1: Facility information element**

**3.6.1 Component (octet 3 etc.)**

This subclause provides the formats and encoding of components in the Facility information element. Formats and encoding methods make use of and is a subset of CCITT Recommendation Q.773 (Transaction Capabilities formats and Encoding) and T/S 43/BB. The used part of CCITT Recommendation Q.773 respectively T/S 43/BB is almost the same as the Component Portion of TC messages. The only difference is that returnResultNotLast is not used.

This subclause is further based on:

- CCITT Recommendation X.208 (Specification of Abstract Syntax Notation One (ASN.1));
- CCITT Recommendation X.209 (Specification of basic encoding rules for Abstract Syntax Notation One);

and is consistent with these CCITT recommendations.

The CCITT Recommendations X.208 and X.209 formal description language is not used.

The parameters in tables 3.3 to 3.6 may be one of the following:

- a Sequence of Parameters;
- a Set of Parameters;
- a specific Parameter with its own tag (i.e. not part of a Sequence or Set);
- nothing at all (i.e. absent).

NOTE: Concerning the general rules for encoding (structure of encoding, identifier octets, length octets, etc.) see CCITT Recommendations X.208 and X.209. For these general rules the same exceptions apply as stated in TS GSM 09.02. This holds also for tables 3.3 to 3.6.

**Table 3.3: Invoke component**

<b>Invoke component</b>	<b>Reference</b>	<b>Mandatory indication</b>
Component type tag	3.6.2	M
Component length	X.209	
Invoke ID tag	3.6.3	
Invoke ID length	X.209	M
Invoke ID	3.6.3	
Linked ID tag	3.6.3	
Linked ID length	X.209	O
Linked ID	3.6.3	
Operation Code tag	3.6.4	
Operation Code length	X.209	M
Operation Code	3.6.4	
Parameters	4	O

**Table 3.4: Return Result component**

<b>Return Result component</b>	<b>Reference</b>	<b>Mandatory indication</b>
Component type tag	3.6.2	M
Component length	X.209	
Invoke ID tag	3.6.3	
Invoke ID length	X.209	M
Invoke ID	3.6.3	
Sequence tag	3.6.5	O (note)
Sequence length	X.209	
Operation Code tag	3.6.4	
Operation Code length	X.209	O (note)
Operation Code	3.6.4	
Parameters	4	O (note)

NOTE: Omitted if the Return Result component does not include any parameters.

**Table 3.5: Return Error component**

<b>Return Error component</b>	<b>Reference</b>	<b>Mandatory indication</b>
Component type tag	3.6.2	M
Component length	X.209	
Invoke ID tag	3.6.3	
Invoke ID length	X.209	M
Invoke ID	3.6.3	
Error Code tag	3.6.6	
Error Code length	X.209	M
Error Code	3.6.6	
Parameters	4	O

**Table 3.6: Reject component**

<b>Reject component</b>	<b>Reference</b>	<b>Mandatory indication</b>
Component type tag	3.6.2	M
Component length	X.209	
Invoke ID tag (note)	3.6.3	
Invoke ID length	X.209	M
Invoke ID	3.6.3	
Problem Code tag	3.6.7	
Problem Code length	X.209	M
Problem Code	3.6.7	

NOTE: If the Invoke ID is not available, Universal Null (table 3.9) with length = 0 shall be used.



### 3.6.2 Component type tag

The Component type tag is coded context-specific, constructor as indicated in table 3.7.

**Table 3.7: Coding of Component type tag**

Component type tag	8	7	6	5	4	3	2	1
Invoke	1	0	1	0	0	0	0	1
Return Result	1	0	1	0	0	0	1	0
Return Error	1	0	1	0	0	0	1	1
Reject	1	0	1	0	0	1	0	0

### 3.6.3 Component ID tag

The term Component ID refers to the Invoke ID or the Linked ID. The Component ID tag is coded as shown in table 3.8.

**Table 3.8: Coding of Component ID tag**

Component ID tag	8	7	6	5	4	3	2	1
Invoke ID	0	0	0	0	0	0	1	0
Linked ID (note)	1	0	0	0	0	0	0	0

NOTE: This tag differs from the Invoke ID tag, which is coded as a Universal INTEGER, in order to distinguish it from the following tag (Operation Code) which is also coded as a Universal INTEGER.

The length of a Component ID is 1 octet.

An Invoke Component has one or two Component IDs: an Invoke ID, and if it is desired to associate the Invoke with a previous Invoke, then the Linked ID is provided in addition to the Invoke ID.

Return Result and Return Error Components have one Component ID, called an Invoke ID which is the reflection of the Invoke ID of the Invoke Component to which they are responding.

The Reject Component uses as its Invoke ID, the Invoke ID in the Component being rejected. If this ID is unavailable (e.g. due to mutilation of the message not detected by lower layers), then the Invoke ID tag is replaced with a universal NULL tag as shown in table 3.9. Universal NULL has always length = 0

Any kind of component, except a reject component, may be rejected.

**Table 3.9: Coding of NULL tag**

NULL tag	8	7	6	5	4	3	2	1
NULL tag	0	0	0	0	0	1	0	1

If an Invoke containing both Invoke and Linked IDs is being rejected, only the Invoke ID is used in the Reject Component.

### 3.6.4 Operation Code

Each Operation is assigned an Operation Code to identify it. An Operation Code follows an Operation Code tag and Operation Code length. The Operation Code tag is coded as shown in table 3.10.

**Table 3.10: Coding of Operation Code tag**

	8 7 6 5 4 3 2 1
Operation Code tag	0 0 0 0 0 0 1 0

The Operation Codes for the different Operations are defined in subclause 4.5.

### 3.6.5 Sequence and Set tags

When there is more than one parameter in a Component (applicable to all Component types), they follow the Sequence or Set tag, which are coded universal, constructor as shown in table 3.11.

**Table 3.11: Coding of Sequence and set tags**

<b>Sequence and set tags</b>	8 7 6 5 4 3 2 1
Sequence tag	0 0 1 1 0 0 0 0
Set tag	0 0 1 1 0 0 0 1

### 3.6.6 Error Code

Each Error is assigned a value (Error Code) to identify it.

An Error Code follows an Error Code tag and Error Code length. The Error Code tag is coded as shown in table 3.12.

**Table 3.12: Coding of Error Code tag**

	8 7 6 5 4 3 2 1
Error Code tag	0 0 0 0 0 0 1 0

The Error Codes for the different Errors are defined in subclause 4.5.

### 3.6.7 Problem Code

The Problem Code consists of one of the four elements: General Problem, Invoke Problem, Return Result Problem or Return Error Problem. The tags for these elements are coded as shown in table 3.13.

**Table 3.13: Coding of Problem tags**

<b>Problem tags</b>	8 7 6 5 4 3 2 1
General Problem tag	1 0 0 0 0 0 0 0
Invoke Problem tag	1 0 0 0 0 0 0 1
Return Result Problem tag	1 0 0 0 0 0 1 0
Return Error Problem tag	1 0 0 0 0 0 1 1

The Problem Codes for the different Problems are shown in tables 3.14 to 3.17.

**Table 3.14: Coding of General Problem Codes**

<b>General Problem Codes</b>	8	7	6	5	4	3	2	1
Unrecognized Component	0	0	0	0	0	0	0	0
Mistyped Component	0	0	0	0	0	0	0	1
Badly Structured Component	0	0	0	0	0	0	0	1

**Table 3.15: Coding of Invoke Problem Codes**

<b>Invoke Problem Codes</b>	8	7	6	5	4	3	2	1
Duplicate Invoke ID	0	0	0	0	0	0	0	0
Unrecognized Operation	0	0	0	0	0	0	0	1
Mistyped Parameter	0	0	0	0	0	0	1	0
Resource Limitation	0	0	0	0	0	0	1	1
Initiating Release	0	0	0	0	0	1	0	0
Unrecognized Linked ID	0	0	0	0	0	1	0	1
Linked Response Unexpected	0	0	0	0	0	1	1	0
Unexpected Linked Operation	0	0	0	0	0	1	1	1

**Table 3.16: Coding of Return Result Problem Codes**

<b>Return Result Problem Codes</b>	8	7	6	5	4	3	2	1
Unrecognized Invoke ID	0	0	0	0	0	0	0	0
Return Result Unexpected	0	0	0	0	0	0	0	1
Mistyped Parameter	0	0	0	0	0	0	1	0

**Table 3.17: Coding of Return Error Problem Codes**

<b>Return Error Problem Codes</b>	8	7	6	5	4	3	2	1
Unrecognized Invoke ID	0	0	0	0	0	0	0	0
Return Error Unexpected	0	0	0	0	0	0	0	1
Unrecognized Error	0	0	0	0	0	0	1	0
Unexpected Error	0	0	0	0	0	0	1	1
Mistyped Parameter	0	0	0	0	0	1	0	0

### 3.7 Version handling for supplementary services

#### 3.7.1 Supplementary service screening indicator

The purpose of the supplementary service screening indicator is to allow the network to assess the capabilities of the MS in advance of a network initiated SS activity. The SS screening indicator is sent in the mobile station classmark 2 as defined in TS GSM 04.08. The handling of the SS screening indicator is described in TS GSM 04.10.

<b>8</b>	<b>7</b>	<b>6</b>	<b>5</b>	<b>4</b>	<b>3</b>	<b>2</b>	<b>1</b>
(note)	(note)	SS screening indicator			(note)		

NOTE: Values not relevant to supplementary services.

**Figure 3.2: Coding of SS screening indicator in mobile station classmark 2**

**Table 3.18: Coding of SS screening indicator in mobile station classmark 2**

<b>SS screening indicator in mobile station classmark 2</b>	<b>6</b>	<b>5</b>
default value of phase 1	0	0
capability of handling of ellipsis notation and phase 2 error handling (note 1) 0	1	
for future use (note 2)	1	0
for future use (note 2)	1	1

NOTE 1: Ellipsis notation is described in TS GSM 04.10 and GSM 09.02. SS Error handling is described in TS GSM 04.10.

NOTE 2: The network shall interpret these values the same as "01".

#### 3.7.2 Supplementary service version indicator

The purpose of the supplementary service version indicator is to allow the network to select the correct version of a protocol for a specific supplementary service. The SS version indicator is included in messages as defined in TS GSM 04.08 and GSM 04.80. The coding described in table 3.19 refers to the first octet received in the SS version indicator. Any other octets received shall be ignored. The handling of the SS version indicator is described in TS GSM 04.10.

**Table 3.19: Coding of SS version indicator**

<b>SS version indicator</b>	<b>8</b>	<b>7</b>	<b>6</b>	<b>5</b>	<b>4</b>	<b>3</b>	<b>2</b>	<b>1</b>
phase 2 service, ellipsis notation, and phase 2 error handling is supported (note 1)	0	0	0	0	0	0	0	0
all other values are for future use (note 2)								

NOTE 1: Ellipsis notation is described in TS GSM 04.10 and GSM 09.02. SS Error handling is described in TS GSM 04.10.

NOTE 2: The network shall interpret all possible values of the SS version indicator the same as "00000000".

## 4 Supplementary services operation specifications

### 4.1 General

This clause specifies the abstract syntax for the Supplementary Service protocol using the Abstract Syntax Notation One (ASN.1), defined in CCITT Recommendation X.208 (1998).

The mapping of OPERATION and ERROR to components is defined in clause 3 of this ETS.

The encoding rules which are applicable to the defined abstract syntax are the Basic Encoding Rules for Abstract Syntax Notation One, defined in CCITT Recommendation X.209 (1998) with the same exceptions as stated in TS GSM 09.02. For each Supplementary Service parameter which has to be transferred by a Supplementary Service message, there is a PDU field (an ASN.1 NamedType) whose ASN.1 identifier has the same name as the corresponding parameter, except for the differences required by the ASN.1 notation (blanks between words are removed, the first letter of the first word is lower-case and the first letter of the following words are capitalized (e.g. "bearer service" is mapped to "bearerService"). In addition some words may be abbreviated as follows:

- ms mobile subscriber;
- ss supplementary services;
- cug closed user group.

The ASN.1 data type which follows the keywords ARGUMENT "PARAMETER" or "RESULT" (for OPERATION and ERROR) is always optional from a syntactic point of view. However, except specific mention, it has to be considered as mandatory from a semantic point of view. When in an invoke component, a mandatory element is missing in any component or inner data structure, a reject component is returned with the problem code "Mistyped Parameter". When an optional element is missing in an invoke component or in an inner data structure while it is required by the context, an error component is returned; the associated type of error is "DataMissing".

In case an element is defined as mandatory in the protocol description (TS GSM 04.80 including imports from TS GSM 09.02), but is not present according to the service description (stage 1 to stage 3), the ASN.1 protocol description takes precedence over the diagrams in the GSM 04.8x and 04.9x-series of technical specifications.

When possible *operations* and errors are imported from TS GSM 09.02 thereby making the MSC transparent to most of the messages sent to or from the MS.

Timer values for operations which require timers are shown as ASN.1 comments.

Ellipsis Notation shall be used in the same way as described in TS GSM 09.02 and shall be supported on the radio interface by the MS and the network for all operations defined in this ETS including those imported from TS GSM 09.02.

## 4.2 Operation types

Table 4.1 summarises the operations defined for supplementary services in this ETS and shows which of these operations are call related and call independent. The terms "call related" and "call independent" are defined in TS GSM 04.10.

**Table 4.1: Relevance of supplementary service operations**

Operation name	Call related SS	Call independent SS
RegisterSS	-	+
EraseSS	-	+
ActivateSS	-	+
DeactivateSS	-	+
InterrogateSS	-	+
RegisterPassword	-	+
GetPassword	-	+
ProcessUnstructuredSS-Data	+	+
ForwardCheckSS-Indication	-	+
ProcessUnstructuredSS-Request	-	+
UnstructuredSS-Request	-	+
UnstructuredSS-Notify	-	+
ForwardChargeAdvice	+	-
NotifySS	+	-
ForwardCUG-Info	+	-
BuildMPTY	+	-
HoldMPTY	+	-
RetrieveMPTY	+	-
SplitMPTY	+	-

NOTE: The ProcessUnstructuredSS-Data operation may be used call related by a phase 1 MS.

```

SS-Operations {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Access (2) modules (3)
  ss-Operations (0) version2 (2)}

DEFINITIONS ::=

BEGIN

EXPORTS

-- exports operation types

-- operations defined in this ETS
NotifySS, ForwardChargeAdvice, ForwardCUG-Info, BuildMPTY, HoldMPTY, RetrieveMPTY, SplitMPTY;

IMPORTS

OPERATION FROM
TCAPMessages {
  ccitt recommendation q 773 modules (2) messages (1) version2 (2)}

```

```

-- The MAP operations
-- RegisterSS, EraseSS, ActivateSS, DeactivateSS, InterrogateSS,
-- RegisterPassword, GetPassword, ProcessUnstructuredSS-Data,
-- ProcessUnstructuredSS-Request, UnstructuredSS-Request, UnstructuredSS-Notify
-- ForwardCheckSS-Indication
-- are imported from MAP-Operations in SS-Protocol module.

-- imports SS-data types
NotifySS-Arg,
ForwardChargeAdviceArg,
ForwardCUG-InfoArg
FROM SS-DataTypes {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Access (2) modules (3)
  ss-Datatypes (2) version2 (2)}

-- imports MAP-errors
IllegalSS-Operation, SS-ErrorStatus, SS-NotAvailable,
SS-Incompatibility, SystemFailure, FacilityNotSupported
FROM MAP-Errors {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Network (1) modules (3)
  map-Errors (10) version2 (2)}

-- imports SS-Errors
ResourcesNotAvailable, MaxNumberOfMPTY-ParticipantsExceeded
FROM SS-Errors {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Access (2) modules (3)
  ss-Errors (1) version2 (2)}
;

-- operation types definition

NotifySS ::=
  ARGUMENT
  notifySS-Arg
  OPERATION
  NotifySS-Arg

ForwardChargeAdvice ::=
  ARGUMENT
  forwardChargeAdviceArg
  RESULT
  OPERATION -- Timer T(AoC)= 1s to 40s
  ForwardChargeAdviceArg

ForwardCUG-Info ::=
  ARGUMENT
  forwardCUG-InfoArg
  OPERATION
  ForwardCUG-InfoArg

BuildMPTY ::=
  RESULT
  ERRORS{
  IllegalSS-Operation,
  SS-ErrorStatus,
  SS-NotAvailable,
  SS-Incompatibility,
  SystemFailure,
  ResourcesNotAvailable,
  MaxNumberOfMPTY-ParticipantsExceeded}

```

```

HoldMPTY ::=
    RESULT
    ERRORS{
        IllegalSS-Operation,
        SS-ErrorStatus,
        SS-Incompatibility,
        FacilityNotSupported,
        SystemFailure}
    OPERATION -- Timer T(HoldMPTY)= 5s to 30s

RetrieveMPTY ::=
    RESULT
    ERRORS{
        IllegalSS-Operation,
        SS-ErrorStatus,
        SS-Incompatibility,
        FacilityNotSupported,
        SystemFailure}
    OPERATION -- Timer T(RetrieveMPTY)= 5s to 30s

SplitMPTY ::=
    RESULT
    ERRORS{
        IllegalSS-Operation,
        SS-ErrorStatus,
        SS-Incompatibility,
        FacilityNotSupported,
        SystemFailure}
    OPERATION -- Timer T(SplitMPTY)= 5s to 30s

END

```

#### 4.2.1 [spare]

#### 4.2.2 Operation types description

For each operation type this subclause provides a brief prose description.

##### 4.2.2.1 RegisterSS (MS --> network)

This operation type is invoked by an MS to register data related to a supplementary service in the network. When no BasicService parameter is provided, the registration applies to all provisioned and applicable basic services.

##### 4.2.2.2 EraseSS (MS --> network)

This operation type is invoked by an MS to erase data related to a supplementary service in the network. When no BasicService parameter is provided, the erasure applies to all provisioned and applicable basic services.

##### 4.2.2.3 ActivateSS (MS --> network)

This operation type is invoked by an MS to request the network for a supplementary service activation. When no BasicService parameter is provided, the activation applies to all provisioned and applicable basic services.



**4.2.2.4 DeactivateSS (MS --> network)**

This operation type is invoked by an MS to request the network for a supplementary service deactivation. When no BasicService parameter is provided, the deactivation applies to all provisioned and applicable basic services.

**4.2.2.5 InterrogateSS (MS --> network)**

This operation type is invoked by an MS to request the network for a supplementary service interrogation. When no BasicService parameter is provided, the interrogation applies to all provisioned and applicable basic services.

**4.2.2.6 NotifySS (network --> MS)**

This operation type is invoked by the network to forward a supplementary service notification towards a mobile subscriber.

**4.2.2.7 RegisterPassword (MS --> network)**

This operation type is invoked by an MS to register a new password related to the management by the subscriber himself of subscription data in the HLR. The operation "Register password" will be successful if the subscriber can provide the old password, the new password and the new password again as results of 3 subsequent operations "Get password".

**4.2.2.8 GetPassword (network --> MS)**

This operation type is invoked by the network to request a password from the mobile subscriber. It may be used to allow the registration of a new password or the management of subscription data by the subscriber himself (e.g. modification of call barring activation status).

**4.2.2.9 ProcessUnstructuredSS-Data (MS --> network)**

This operation type is invoked by an MS to relay unstructured information in order to allow end to end SS operation between the MS and the network following specific rules (e.g. embedding of keypad commands). The operation is used in order to provide backward compatibility (see TS GSM 04.90).

**4.2.2.10 ProcessUnstructuredSS-Request (MS --> network)**

This operation type is invoked by an MS to start an unstructured supplementary service data application in the network.

**4.2.2.11 UnstructuredSS-Request (network --> MS)**

This operation type is invoked by the network to request unstructured information from the MS in order to perform an unstructured supplementary service data application.

**4.2.2.12 UnstructuredSS-Notify (network --> MS)**

This operation type is invoked by the network to give an unstructured supplementary service notification to the mobile user.

**4.2.2.13 ForwardCheckSSIndication (network --> MS)**

This operation type is invoked by the network to indicate to the mobile subscriber that the status of supplementary services may not be correct in the network. The procedures for initiating ForwardCheckSSIndication are specified in TS GSM 09.02.

**4.2.2.14 ForwardChargeAdvice (network --> MS)**

This operation type is invoked by the network to forward Advice of Charge information to the mobile subscriber.

**4.2.2.15 BuildMPTY (MS --> network)**

This operation type is invoked by an MS to request the network to connect calls in a multi party call.

**4.2.2.16 HoldMPTY (MS --> network)**

This operation type is invoked by an MS to put the MS-connection to a multi party call (invoked by that MS) on hold.

**4.2.2.17 RetrieveMPTY (MS --> network)**

This operation type is invoked by an MS to request retrieval of a multi party call held by that MS.

**4.2.2.18 SplitMPTY (MS --> network)**

This operation type is invoked by an MS to request a private communication with one of the remote parties in a multi party call invoked by that MS.

**4.2.2.19 ForwardCUG-Info (MS --> network)**

This operation type is used by an MS to explicitly invoke a CUG call.

### 4.3 Error types

#### 4.3.1 Error types ASN.1 specification

The following ASN.1 module provides an ASN.1 specification of errors. Errors from MAP are imported in the SS-Protocol module in subclause 4.5.

```
SS-Errors {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Access (2) modules (3)
  ss-Errors (1) version2 (2)}

DEFINITIONS ::=

BEGIN

IMPORTS

ERROR FROM
TCAPMessages {
  ccitt recommendation q 773 modules (2) messages (1) version2 (2)};

-- The MAP errors
-- UnknownSubscriber, BearerServiceNotProvisioned, TeleserviceNotProvisioned,
-- IllegalSS-Operation, SS-ErrorStatus, SS-NotAvailable, SS-SubscriptionViolation,
-- SS-Incompatibility, SystemFailure, DataMissing, UnexpectedDataValue, FacilityNotSupported,
-- PW-RegistrationFailure, NegativePW-Check, CallBarred, NumberOfPW-AttemptsViolation,
-- AbsentSubscriber, IllegalSubscriber, IllegalEquipment, USSD-Busy, UnknownAlphabet
-- are imported from MAP-Errors in SS-Protocol module.

-- error types definition
ResourcesNotAvailable ::= ERROR
MaxNumberOfMPTY-ParticipantsExceeded ::= ERROR

END
```

#### 4.3.2 Error types description

For each error type this subclause provides a brief prose description.

##### 4.3.2.1 UnknownSubscriber

This error is returned by the network when it is requested to perform an operation concerning an unknown subscriber.

##### 4.3.2.2 BearerServiceNotProvisioned

This error is returned by the network when it is requested to perform an operation on a supplementary service and not even a subset of the requested bearer service group has been subscribed to.

#### **4.3.2.3 TeleServiceNotProvisioned**

This error is returned by the network when it is requested to perform an operation on a supplementary service and not even a subset of the requested teleservice group has been subscribed to.

#### **4.3.2.4 IllegalSS-Operation**

This error is returned by the network when it is requested to perform an illegal operation which is defined as not applicable for the relevant supplementary service(s) (e.g. registration request for a service which must be registered by the administration). For the definition of the allowed operations for the individual supplementary services, see GSM 04.8x and 04.9x-series of technical specifications.

#### **4.3.2.5 SS-ErrorStatus**

This error is returned by the network when it is requested to perform an operation which is not compatible with the current status of the relevant supplementary service. The current status may be given as additional information by use of the SS-parameter.

#### **4.3.2.6 SS-NotAvailable**

This error is returned by the network when it is requested to perform an operation on a supplementary service which is not available in the current location area.

#### **4.3.2.7 SS-SubscriptionViolation**

This error is returned by the network when it is requested to perform an operation on a supplementary service, transgressing the subscription restrictions. The nature of the restriction or the transgressed options may be sent as parameters.

#### **4.3.2.8 SS-Incompatibility**

This error is returned by the network when it is requested for a supplementary service operation incompatible with the status of an other supplementary service or with the teleservice or bearer service for which the operation is requested. This error shall only be used if the operation is not compatible for even a subset of the teleservice group or bearer service group specified in the request. The identity and status of the conflicting service may also be indicated. The additional information may contain the SS-code parameter, the Basic Service Group parameter and the SS-status parameter.

#### **4.3.2.9 SystemFailure**

This error is returned by the network, when it cannot perform an operation because of a failure in the network.

#### **4.3.2.10 DataMissing**

This error is returned by the network when an optional parameter is missing in an invoke component or an inner data structure, while it is required by the context of the request.

#### **4.3.2.11 UnexpectedDataValue**

This error is returned by the network when it receives a parameter with an unexpected value, without type violation.

#### **4.3.2.12 PasswordRegistrationFailure**

This error is returned when a password registration procedure fails because of abnormal subscriber inputs. A more specific diagnostic may be passed as error parameter and indicates situations such as:

- invalid password format;
- new passwords mismatch.

#### **4.3.2.13 NegativePasswordCheck**

This error is returned to indicate the negative result of a password check because the subscriber has not provided the required password or has provided a password which does not match the valid one.

#### **4.3.2.14 FacilityNotSupported**

This error is returned by the network receiving a request about a facility which is not supported in the PLMN.

#### **4.3.2.15 ResourcesNotAvailable**

This error is returned by the network to the MS if temporarily there are no resources to support e.g. a multi party call available in the network.

#### **4.3.2.16 MaxNumberOfMPTY-ParticipantsExceeded**

This error is returned by the network to the MS if the request must be rejected because the number of subscribers to join a multi party call would exceed the maximum value.

#### **4.3.2.17 CallBarred**

This error is returned by the network to the MS when call independent subscriber control procedures are barred by the operator. The parameter "operator barring" shall be included.

#### **4.3.2.18 NumberOfPW-AttemptsViolation**

This error is returned by the network to the MS when the maximum number of wrong password attempts is exceeded.

#### **4.3.2.19 AbsentSubscriber**

This error is returned when the subscriber has activated the detach service or the system detects the absence condition. This error is not used on the radio interface but only between network entities.

#### **4.3.2.20 IllegalSubscriber**

This error is returned when illegality of the access has been established by use of authentication procedure. This error is not used on the radio interface but only between network entities.

**4.3.2.21 IllegalEquipment**

This error is returned when the IMEI check procedure has shown that the IMEI is blacklisted or not white-listed. This error is not used on the radio interface but only between network entities.

**4.3.2.22 USSD-Busy**

This error is returned by the MS to the network when the MS is not able to process the unstructured supplementary service data operation due to an on-going MMI input of the user or an already existing call independent supplementary service transaction.

**4.3.2.23 UnknownAlphabet**

This error is returned by the MS or the network when the alphabet/language used for the unstructured supplementary service data operation is not known by the network or the MS.

## 4.4 Data types and identifiers

### 4.4.1 General

The data types used in the SS protocol specifications are described in the ASN.1 module provided in subclause 4.4.2, while subclause 4.4.3 provides an overview of the identifiers used in SS ASN.1 specifications.

Since size constraints are subject to modifications named values have been defined in the following module for the upper boundaries of the value ranges associated to several sub-type specifications.

### 4.4.2 ASN.1 data types

This subclause provides an ASN.1 module defining the abstract data types in operations and errors specification. Only data types which are specific for this ETS are defined. All other data types are imported from MAP together with the import of operations and errors.

```

SS-DataTypes {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Access (2) modules (3)
  ss-DataTypes (2) version2 (2)}

DEFINITIONS

IMPLICIT TAGS ::=

BEGIN

-- exports all data types defined in this module

IMPORTS

SS-Code
FROM MAP-SS-Code {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Network (1) modules (3)
  map-SS-Code (15) version2 (2)}

-- imports MAP-SS-DataTypes
SS-Status, CUG-Index
FROM MAP-SS-DataTypes {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Network (1) modules (3)
  map-SS-DataTypes (14) version2 (2)}
;

-- data types definition

NotifySS-Arg ::= SEQUENCE{
  ss-Code [1] SS-Code OPTIONAL,
  ss-Status [4] SS-Status OPTIONAL,
  ss-Notification [5] SS-Notification OPTIONAL,
  callsWaiting-Indicator [14] NULL OPTIONAL,
  callOnHold-Indicator [15] CallOnHold-Indicator OPTIONAL,
  mpty-Indicator [16] NULL OPTIONAL,
  cug-Index [17] CUG-Index OPTIONAL,
  clirSuppressionRejected [18] NULL OPTIONAL,
  ...}

```

```
ForwardChargeAdviceArg ::= SEQUENCE{
    ss-Code                [0]    SS-Code,
    chargingInformation    [1]    ChargingInformation,
    ...}

```

```
SS-Notification ::= OCTET STRING (SIZE (1))

```

```
-- Bit 8 7 6 5 4          00000 (Unused)

--      Bit 3              Call is forwarded indication to A-subscriber
--                          (calling subscriber)
--      0                   No information content
--      1                   Outgoing call has been forwarded to C

--      Bit 2              Call is forwarded indication to B-subscriber
--                          (forwarding subscriber)
--      0                   No information content
--      1                   Incoming call has been forwarded to C

--      Bit 1              Call is forwarded indication to C-subscriber
--                          (forwarded-to subscriber)
--      0                   No information content
--      1                   Incoming call is a forwarded call

```

```
ChargingInformation ::= SEQUENCE{
    e1                      [1] E1 OPTIONAL,
    e2                      [2] E2 OPTIONAL,
    e3                      [3] E3 OPTIONAL,
    e4                      [4] E4 OPTIONAL,
    e5                      [5] E5 OPTIONAL,
    e6                      [6] E6 OPTIONAL,
    e7                      [7] E7 OPTIONAL,
    ...}

```

```
E1 ::= INTEGER (0..max10TimesUnitsPerTime)
max10TimesUnitsPerTime INTEGER ::= 8191

```

```
E2 ::= INTEGER (0..max10TimesTimeInterval)
max10TimesTimeInterval INTEGER ::= 8191

```

```
E3 ::= INTEGER (0..max100TimesScalingFactor)
max100TimesScalingFactor INTEGER ::= 8191

```

```
E4 ::= INTEGER (0..max10TimesIncrement)
max10TimesIncrement INTEGER ::= 8191

```

```
E5 ::= INTEGER (0..max10TimesIncrementPerDataInterval)
max10TimesIncrementPerDataInterval INTEGER ::= 8191

```

```
E6 ::= INTEGER (0..maxNumberOfSegmentsPerDataInterval)
maxNumberOfSegmentsPerDataInterval INTEGER ::= 8191

```

```
E7 ::= INTEGER (0..max10TimesInitialTime)
max10TimesInitialTime INTEGER ::= 8191

```



```

CallOnHold-Indicator ::= ENUMERATED {
                                callRetrieved (0),
                                callOnHold (1)}

ForwardCUG-InfoArg ::= SEQUENCE {
    cug-Index                [0]    CUG-Index OPTIONAL,
    suppressPrefCUG          [1]    NULL OPTIONAL,
    suppressOA               [2]    NULL OPTIONAL,
    ...}

END

```

#### 4.4.3 Identifiers definition

The parameters which are described in the following subclauses correspond to the identifiers used in operation and error types description.

##### 4.4.3.1 chargingInformation

The chargingInformation identifier refers to the necessary information for the Advice of Charge supplementary service. See TS GSM 02.24.

##### 4.4.3.2 e1

The e1 identifier refers to 10 times the number of LPLMN units per time interval in connection with the Advice of Charge supplementary service, see TS GSM 02.24.

##### 4.4.3.3 e2

The e2 identifier refers to 10 times the length of the time interval in seconds in connection with the Advice of Charge supplementary service, see TS GSM 02.24.

##### 4.4.3.4 e3

The e3 identifier refers to 100 times the scaling factor to convert from LPLMN units to HPLMN units in connection with the Advice of Charge supplementary service, see TS GSM 02.24.

##### 4.4.3.5 e4

The e4 identifier refers to 10 times the LPLMN increment in connection with the Advice of Charge supplementary service, see TS GSM 02.24.

##### 4.4.3.6 e5

The e5 identifier refers to 10 times the number of LPLMN units incremented per data interval in connection with the Advice of Charge supplementary service, see TS GSM 02.24.

##### 4.4.3.7 e6

The e6 identifier refers to the number of segments per data interval in connection with the Advice of Charge supplementary service, see TS GSM 02.24.

##### 4.4.3.8 e7

The e7 identifier refers to 10 times the length of the initial time interval in seconds in connection with the Advice of Charge supplementary service, see TS GSM 02.24.

**4.4.3.9 ss-Code**

The ss-Code identifier refers to the code which identify a supplementary service or a group of supplementary services.

**4.4.3.10 ss-Notification**

The ss-Notification identifier refers to one or several supplementary service notifications which have to be forwarded to a mobile subscriber.

**4.4.3.11 ss-Status**

The ss-Status identifier refers to the status of a supplementary service.

**4.4.3.12 callsWaiting-Indicator**

The callsWaiting-Indicator identifier refers to the indication given to the mobile station that the call is waiting.

**4.4.3.13 callOnhold-Indicator**

The callOnHold-Indicator identifier refers to the indication given to the mobile station that the call has been put on hold or has been retrieved.

**4.4.3.14 mpty-Indicator**

The mpty-Indicator identifier refers to the indication given to the mobile station that the multi party call has been invoked.

**4.4.3.15 forwardCUG-InfoArg**

The forwardCUG-InfoArg identifier refers to the indication given from the mobile subscriber to the network in connection with explicit invocation of a CUG call.

**4.4.3.16 cug-Index**

The cug-Index identifier refers to the index of a CUG given in an explicit invocation of a CUG call.

**4.4.3.17 suppressPrefCUG**

The suppressPrefCUG identifier refers to the mobile subscribers request to the network to prohibit the use of the preferential CUG.

**4.4.3.18 suppressOA**

The suppressOA identifier refers to the mobile subscribers request to the network to prohibit the use of the subscriber option "OA allowed".

**4.4.3.19 clirSuppressionRejected**

The clirSuppressionRejected identifier refers to the indication given to the mobile station that the CLIR suppression request has been rejected.

#### 4.5 Operations and errors implementation

For the actual implementation of supplementary services, operations and errors have to be defined by value. The following ASN.1 module, imports operation types from the ASN.1 module described in subclause 4.2 and operation and error types from MAP. It defines operations by allocating operations and errors a local value. For the involved operations and errors the same local values as in MAP are allocated.

```

SS-Protocol {
  ccitt identified-organization (4) etsi (0) mobileDomain (0)
  gsm-Access (2) modules (3) ss-Protocol (3) version2 (2)}

DEFINITIONS ::=

BEGIN

IMPORTS

-- imports operation types

-- imports operation type from MAP-MobileServiceOperations
ForwardCheckSS-Indication
FROM MAP-MobileServiceOperations {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Network (1) modules (3)
  map-MobileServiceOperations (5) version2 (2)}

-- imports operation types from MAP-SupplementaryServiceOperations
RegisterSS, EraseSS, ActivateSS, DeactivateSS, InterrogateSS, RegisterPassword, GetPassword,
ProcessUnstructuredSS-Data, ProcessUnstructuredSS-Request, UnstructuredSS-Request,
UnstructuredSS-Notify
FROM MAP-SupplementaryServiceOperations {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Network (1) modules (3)
  map-SupplementaryServiceOperations (8) version2 (2)}

-- imports operation types from SS-Operations
NotifySS, ForwardChargeAdvice, BuildMPTY, HoldMPTY, RetrieveMPTY, SplitMPTY,
ForwardCUG-Info
FROM SS-Operations {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Access (2) modules (3)
  ss-Operations (0) version2 (2)}

-- imports error types

-- imports error types from MAP-Errors
UnknownSubscriber, BearerServiceNotProvisioned, TeleserviceNotProvisioned,
IllegalSS-Operation, SS-ErrorStatus, SS-NotAvailable, SS-SubscriptionViolation,
SS-Incompatibility, SystemFailure, DataMissing, UnexpectedDataValue, PW-RegistrationFailure,
NegativePW-Check, FacilityNotSupported, CallBarred, NumberOfPW-AttemptsViolation,
AbsentSubscriber, IllegalSubscriber, IllegalEquipment, USSD-Busy, UnknownAlphabet

FROM MAP-Errors {
  ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Network (1) modules (3)
  map-Errors (10) version2 (2)}

```

-- imports error types from SS-Errors

ResourcesNotAvailable, MaxNumberOfMPTY-ParticipantsExceeded

FROM SS-Errors {

ccitt identified-organization (4) etsi (0) mobileDomain (0) gsm-Access (2) modules (3)  
ss-Errors (1) version2 (2)}

;

-- allocation of local values to operations

registerSS	RegisterSS ::= localValue 10
eraseSS	EraseSS ::= localValue 11
activateSS	ActivateSS ::= localValue 12
deactivateSS	DeactivateSS ::= localValue 13
interrogateSS	InterrogateSS ::= localValue 14
notifySS	NotifySS ::= localValue 16
registerPassword	RegisterPassword ::= localValue 17
getPassword	GetPassword ::= localValue 18
processUnstructuredSS-Data	ProcessUnstructuredSS-Data ::= localValue 19
forwardCheckSS-Indication	ForwardCheckSS-Indication ::= localValue 38
processUnstructuredSS-Request	ProcessUnstructuredSS-Request ::= localValue 59
unstructuredSS-Request	UnstructuredSS-Request ::= localValue 60
unstructuredSS-Notify	UnstructuredSS-Notify ::= localValue 61
forwardCUG-Info	ForwardCUG-Info ::= localValue 120
splitMPTY	SplitMPTY ::= localValue 121
retrieveMPTY	RetrieveMPTY ::= localValue 122
holdMPTY	HoldMPTY ::= localValue 123
buildMPTY	BuildMPTY ::= localValue 124
forwardChargeAdvice	ForwardChargeAdvice ::= localValue 125

-- allocation of local values to errors

unknownSubscriber	UnknownSubscriber ::= localValue 1
illegalSubscriber	IllegalSubscriber ::= localValue 9
bearerServiceNotProvisioned	BearerServiceNotProvisioned ::= localValue 10
teleserviceNotProvisioned	TeleserviceNotProvisioned ::= localValue 11
illegalEquipment	IllegalEquipment ::= localValue 12
callBarred	CallBarred ::= localValue 13
illegalSS-Operation	IllegalSS-Operation ::= localValue 16
ss-ErrorStatus	SS-ErrorStatus ::= localValue 17
ss-NotAvailable	SS-NotAvailable ::= localValue 18
ss-SubscriptionViolation	SS-SubscriptionViolation ::= localValue 19
ss-Incompatibility	SS-Incompatibility ::= localValue 20
facilityNotSupported	FacilityNotSupported ::= localValue 21
absentSubscriber	AbsentSubscriber ::= localValue 27
systemFailure	SystemFailure ::= localValue 34
dataMissing	DataMissing ::= localValue 35
unexpectedDataValue	UnexpectedDataValue ::= localValue 36
pw-RegistrationFailure	PW-RegistrationFailure ::= localValue 37
negativePW-Check	NegativePW-Check ::= localValue 38
numberOfPW-AttemptsViolation	NumberOfPW-AttemptsViolation ::= localValue 43
unknownAlphabet	UnknownAlphabet ::= localValue 71
ussd-Busy	USSD-Busy ::= localValue 72
maxNumberOfMPTY-ParticipantsExceeded	MaxNumberOfMPTY-ParticipantsExceeded ::= localValue 126
resourcesNotAvailable	ResourcesNotAvailable ::= localValue 127

END

## Annex A (informative): Expanded ASN.1 Module "SS-Protocol"

```
-- Expanded ASN.1 Module 'SS-Protocol'  
--SIEMENS ASN.1 Compiler P2.10 (94-10-21 10:03:57)  
-- Date: 94-10-21 Time: 10:50:58
```

```
SS-Protocol { 0 identified-organization (4) etsi (0) mobileDomain (0) gsm-Access (2) modules (3) ss-  
Protocol (3) version2 (2) }
```

### DEFINITIONS

```
::=
```

```
BEGIN
```

```
registerSS OPERATION
```

```
ARGUMENT
```

```
registerSS-Arg SEQUENCE {  
  ss-Code OCTET STRING (SIZE (1)),  
  basicService CHOICE {  
    bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),  
    teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,  
  forwardedToNumber [4] IMPLICIT OCTET STRING (SIZE (1..20)) OPTIONAL,  
  forwardedToSubaddress [6] IMPLICIT OCTET STRING (SIZE (1..21)) OPTIONAL,  
  noReplyConditionTime [5] IMPLICIT INTEGER (5..30) OPTIONAL,  
  ... }
```

```
RESULT
```

```
ss-Info CHOICE {  
  forwardingInfo [0] IMPLICIT SEQUENCE {  
    ss-Code OCTET STRING (SIZE (1)) OPTIONAL,  
    forwardingFeatureList SEQUENCE SIZE (1..13) OF  
    SEQUENCE {  
      basicService CHOICE {  
        bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),  
        teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,  
      ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,  
      forwardedToNumber [5] IMPLICIT OCTET STRING (SIZE (1..9)) OPTIONAL,  
      forwardedToSubaddress [8] IMPLICIT OCTET STRING (SIZE (1..21)) OPTIONAL,  
      forwardingOptions [6] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,  
      noReplyConditionTime [7] IMPLICIT INTEGER (5..30) OPTIONAL,  
      ... },  
    ... },  
  callBarringInfo [1] IMPLICIT SEQUENCE {  
    ss-Code OCTET STRING (SIZE (1)) OPTIONAL,  
    callBarringFeatureList SEQUENCE SIZE (1..13) OF  
    SEQUENCE {  
      basicService CHOICE {  
        bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),  
        teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,  
      ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,  
      ... },  
    ... },  
  cug-Info [2] IMPLICIT SEQUENCE {  
    cug-SubscriptionList SEQUENCE SIZE (1..10) OF  
    SEQUENCE {  
      cug-Index INTEGER (0..32767),  
      cug-Interlock OCTET STRING (SIZE (4)),  
      intraCUG-Options ENUMERATED {  
        noCUG-Restrictions (0),  
        cugIC-CallBarred (1),  
        cugOG-CallBarred (2)},  
      basicServiceGroupList SEQUENCE SIZE (1..13) OF  
      CHOICE {
```

```

        bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
        teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
    ... },
    cug-FeatureList SEQUENCE SIZE (1..13) OF
    SEQUENCE {
        basicService CHOICE {
            bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
            teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
        preferentialCUG-Indicator INTEGER (0..32767) OPTIONAL,
        interCUG-Restrictions OCTET STRING (SIZE (1)),
        ... } OPTIONAL,
    ... },
    ss-Data [3] IMPLICIT SEQUENCE {
        ss-Code OCTET STRING (SIZE (1)) OPTIONAL,
        ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
        ss-SubscriptionOption CHOICE {
            cliRestrictionOption [2] IMPLICIT ENUMERATED {
                permanent (0),
                temporaryDefaultRestricted (1),
                temporaryDefaultAllowed (2)},
            overrideCategory [1] IMPLICIT ENUMERATED {
                overrideEnabled (0),
                overrideDisabled (1)} } OPTIONAL,
        basicServiceGroupList SEQUENCE SIZE (1..13) OF
        CHOICE {
            bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
            teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
        ... } }
    ERRORS {
        -- systemFailure -- localValue 34,
        -- dataMissing -- localValue 35,
        -- unexpectedDataValue -- localValue 36,
        -- unknownSubscriber -- localValue 1,
        -- bearerServiceNotProvisioned -- localValue 10,
        -- teleserviceNotProvisioned -- localValue 11,
        -- callBarred -- localValue 13,
        -- illegalSS-Operation -- localValue 16,
        -- ss-ErrorStatus -- localValue 17,
        -- ss-SubscriptionViolation -- localValue 19,
        -- ss-Incompatibility -- localValue 20}
    ::= localValue 10

eraseSS OPERATION
ARGUMENT
    ss-ForBS SEQUENCE {
        ss-Code OCTET STRING (SIZE (1)),
        basicService CHOICE {
            bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
            teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
        ... }
RESULT
    ss-Info CHOICE {
        forwardingInfo [0] IMPLICIT SEQUENCE {
            ss-Code OCTET STRING (SIZE (1)) OPTIONAL,
            forwardingFeatureList SEQUENCE SIZE (1..13) OF
            SEQUENCE {
                basicService CHOICE {
                    bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
                    teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
                ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
                forwardedToNumber [5] IMPLICIT OCTET STRING (SIZE (1..9)) OPTIONAL,
                forwardedToSubaddress [8] IMPLICIT OCTET STRING (SIZE (1..21)) OPTIONAL,
                forwardingOptions [6] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,

```

```

    noReplyConditionTime [7] IMPLICIT INTEGER (5..30) OPTIONAL,
    ... },
  ... },
  callBarringInfo [1] IMPLICIT SEQUENCE {
    ss-Code OCTET STRING (SIZE (1)) OPTIONAL,
    callBarringFeatureList SEQUENCE SIZE (1..13) OF
      SEQUENCE {
        basicService CHOICE {
          bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
          teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
          ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
          ... },
        ... },
  cug-Info [2] IMPLICIT SEQUENCE {
    cug-SubscriptionList SEQUENCE SIZE (1..10) OF
      SEQUENCE {
        cug-Index INTEGER (0..32767),
        cug-Interlock OCTET STRING (SIZE (4)),
        intraCUG-Options ENUMERATED {
          noCUG-Restrictions (0),
          cugIC-CallBarred (1),
          cugOG-CallBarred (2)},
        basicServiceGroupList SEQUENCE SIZE (1..13) OF
          CHOICE {
            bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
            teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
            ... },
        cug-FeatureList SEQUENCE SIZE (1..13) OF
          SEQUENCE {
            basicService CHOICE {
              bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
              teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
              preferentialCUG-Indicator INTEGER (0..32767) OPTIONAL,
              interCUG-Restrictions OCTET STRING (SIZE (1)),
              ... } OPTIONAL,
            ... },
        ss-Data [3] IMPLICIT SEQUENCE {
          ss-Code OCTET STRING (SIZE (1)) OPTIONAL,
          ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
          ss-SubscriptionOption CHOICE {
            cliRestrictionOption [2] IMPLICIT ENUMERATED {
              permanent (0),
              temporaryDefaultRestricted (1),
              temporaryDefaultAllowed (2)},
            overrideCategory [1] IMPLICIT ENUMERATED {
              overrideEnabled (0),
              overrideDisabled (1)} OPTIONAL,
            basicServiceGroupList SEQUENCE SIZE (1..13) OF
              CHOICE {
                bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
                teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
                ... }}
  ERRORS {
    -- systemFailure -- localValue 34,
    -- dataMissing -- localValue 35,
    -- unexpectedDataValue -- localValue 36,
    -- unknownSubscriber -- localValue 1,
    -- bearerServiceNotProvisioned -- localValue 10,
    -- teleserviceNotProvisioned -- localValue 11,
    -- callBarred -- localValue 13,
    -- illegalSS-Operation -- localValue 16,
    -- ss-ErrorStatus -- localValue 17,
    -- ss-SubscriptionViolation -- localValue 19}

```

::= localValue 11

activateSS OPERATION

ARGUMENT

ss-ForBS SEQUENCE {  
 ss-Code OCTET STRING (SIZE (1)),  
 basicService CHOICE {  
 bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),  
 teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,  
 ... }

RESULT

ss-Info CHOICE {  
 forwardingInfo [0] IMPLICIT SEQUENCE {  
 ss-Code OCTET STRING (SIZE (1)) OPTIONAL,  
 forwardingFeatureList SEQUENCE SIZE (1..13) OF  
 SEQUENCE {  
 basicService CHOICE {  
 bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),  
 teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,  
 ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,  
 forwardedToNumber [5] IMPLICIT OCTET STRING (SIZE (1..9)) OPTIONAL,  
 forwardedToSubaddress [8] IMPLICIT OCTET STRING (SIZE (1..21)) OPTIONAL,  
 forwardingOptions [6] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,  
 noReplyConditionTime [7] IMPLICIT INTEGER (5..30) OPTIONAL,  
 ... },  
 ... },  
 callBarringInfo [1] IMPLICIT SEQUENCE {  
 ss-Code OCTET STRING (SIZE (1)) OPTIONAL,  
 callBarringFeatureList SEQUENCE SIZE (1..13) OF  
 SEQUENCE {  
 basicService CHOICE {  
 bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),  
 teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,  
 ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,  
 ... },  
 ... },  
 cug-Info [2] IMPLICIT SEQUENCE {  
 cug-SubscriptionList SEQUENCE SIZE (1..10) OF  
 SEQUENCE {  
 cug-Index INTEGER (0..32767),  
 cug-Interlock OCTET STRING (SIZE (4)),  
 intraCUG-Options ENUMERATED {  
 noCUG-Restrictions (0),  
 cugIC-CallBarred (1),  
 cugOG-CallBarred (2)},  
 basicServiceGroupList SEQUENCE SIZE (1..13) OF  
 CHOICE {  
 bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),  
 teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,  
 ... },  
 cug-FeatureList SEQUENCE SIZE (1..13) OF  
 SEQUENCE {  
 basicService CHOICE {  
 bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),  
 teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,  
 preferentialCUG-Indicator INTEGER (0..32767) OPTIONAL,  
 interCUG-Restrictions OCTET STRING (SIZE (1)),  
 ... } OPTIONAL,  
 ... },  
 ss-Data [3] IMPLICIT SEQUENCE {  
 ss-Code OCTET STRING (SIZE (1)) OPTIONAL,  
 ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,  
 ss-SubscriptionOption CHOICE {



```

cliRestrictionOption [2] IMPLICIT ENUMERATED {
  permanent (0),
  temporaryDefaultRestricted (1),
  temporaryDefaultAllowed (2)},
overrideCategory [1] IMPLICIT ENUMERATED {
  overrideEnabled (0),
  overrideDisabled (1)} OPTIONAL,
basicServiceGroupList SEQUENCE SIZE (1..13) OF
CHOICE {
  bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
  teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
... }
ERRORS {
  -- systemFailure -- localValue 34,
  -- dataMissing -- localValue 35,
  -- unexpectedDataValue -- localValue 36,
  -- unknownSubscriber -- localValue 1,
  -- bearerServiceNotProvisioned -- localValue 10,
  -- teleserviceNotProvisioned -- localValue 11,
  -- callBarred -- localValue 13,
  -- illegalSS-Operation -- localValue 16,
  -- ss-ErrorStatus -- localValue 17,
  -- ss-SubscriptionViolation -- localValue 19,
  -- ss-Incompatibility -- localValue 20,
  -- negativePW-Check -- localValue 38,
  -- numberOfPW-AttemptsViolation -- localValue 43}
::= localValue 12

deactivateSS OPERATION
ARGUMENT
  ss-ForBS SEQUENCE {
    ss-Code OCTET STRING (SIZE (1)),
    basicService CHOICE {
      bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
      teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
    ... }
RESULT
  ss-Info CHOICE {
    forwardingInfo [0] IMPLICIT SEQUENCE {
      ss-Code OCTET STRING (SIZE (1)) OPTIONAL,
      forwardingFeatureList SEQUENCE SIZE (1..13) OF
SEQUENCE {
        basicService CHOICE {
          bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
          teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
          ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
          forwardedToNumber [5] IMPLICIT OCTET STRING (SIZE (1..9)) OPTIONAL,
          forwardedToSubaddress [8] IMPLICIT OCTET STRING (SIZE (1..21)) OPTIONAL,
          forwardingOptions [6] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
          noReplyConditionTime [7] IMPLICIT INTEGER (5..30) OPTIONAL,
          ... },
        ... },
    callBarringInfo [1] IMPLICIT SEQUENCE {
      ss-Code OCTET STRING (SIZE (1)) OPTIONAL,
      callBarringFeatureList SEQUENCE SIZE (1..13) OF
SEQUENCE {
        basicService CHOICE {
          bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
          teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
          ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
          ... },
        ... },
    cug-Info [2] IMPLICIT SEQUENCE {

```

```

cug-SubscriptionList SEQUENCE SIZE (1..10) OF
SEQUENCE {
  cug-Index INTEGER (0..32767),
  cug-Interlock OCTET STRING (SIZE (4)),
  intraCUG-Options ENUMERATED {
    noCUG-Restrictions (0),
    cugIC-CallBarred (1),
    cugOG-CallBarred (2)},
  basicServiceGroupList SEQUENCE SIZE (1..13) OF
  CHOICE {
    bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
    teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
  ... },
cug-FeatureList SEQUENCE SIZE (1..13) OF
SEQUENCE {
  basicService CHOICE {
    bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
    teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
  preferentialCUG-Indicator INTEGER (0..32767) OPTIONAL,
  interCUG-Restrictions OCTET STRING (SIZE (1)),
  ... } OPTIONAL,
... },
ss-Data [3] IMPLICIT SEQUENCE {
  ss-Code OCTET STRING (SIZE (1)) OPTIONAL,
  ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
  ss-SubscriptionOption CHOICE {
    cliRestrictionOption [2] IMPLICIT ENUMERATED {
      permanent (0),
      temporaryDefaultRestricted (1),
      temporaryDefaultAllowed (2)},
    overrideCategory [1] IMPLICIT ENUMERATED {
      overrideEnabled (0),
      overrideDisabled (1)} OPTIONAL,
  basicServiceGroupList SEQUENCE SIZE (1..13) OF
  CHOICE {
    bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
    teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
  ... }}
ERRORS {
  -- systemFailure -- localValue 34,
  -- dataMissing -- localValue 35,
  -- unexpectedDataValue -- localValue 36,
  -- unknownSubscriber -- localValue 1,
  -- bearerServiceNotProvisioned -- localValue 10,
  -- teleserviceNotProvisioned -- localValue 11,
  -- callBarred -- localValue 13,
  -- illegalSS-Operation -- localValue 16,
  -- ss-ErrorStatus -- localValue 17,
  -- ss-SubscriptionViolation -- localValue 19,
  -- negativePW-Check -- localValue 38,
  -- numberOfPW-AttemptsViolation -- localValue 43}
::= localValue 13

interrogateSS OPERATION
ARGUMENT
  ss-ForBS SEQUENCE {
    ss-Code OCTET STRING (SIZE (1)),
    basicService CHOICE {
      bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
      teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
    ... }
RESULT
  interrogateSS-Res CHOICE {

```

```

ss-Status [0] IMPLICIT OCTET STRING (SIZE (1)),
forwardedToNumber [1] IMPLICIT OCTET STRING (SIZE (1..9)),
basicServiceGroupList [2] IMPLICIT SEQUENCE SIZE (1..13) OF
CHOICE {
    bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
    teleservice [3] IMPLICIT OCTET STRING (SIZE (1))},
forwardingFeatureList [3] IMPLICIT SEQUENCE SIZE (1..13) OF
SEQUENCE {
    basicService CHOICE {
        bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
        teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
    ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
    forwardedToNumber [5] IMPLICIT OCTET STRING (SIZE (1..9)) OPTIONAL,
    forwardedToSubaddress [8] IMPLICIT OCTET STRING (SIZE (1..21)) OPTIONAL,
    forwardingOptions [6] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
    noReplyConditionTime [7] IMPLICIT INTEGER (5..30) OPTIONAL,
    ... },
cli-RestrictionInfo [4] IMPLICIT SEQUENCE {
    ss-Status OCTET STRING (SIZE (1)),
    cliRestrictionOption ENUMERATED {
        permanent (0),
        temporaryDefaultRestricted (1),
        temporaryDefaultAllowed (2)} OPTIONAL,
    ... }}
ERRORS {
    -- systemFailure -- localValue 34,
    -- dataMissing -- localValue 35,
    -- unexpectedDataValue -- localValue 36,
    -- unknownSubscriber -- localValue 1,
    -- bearerServiceNotProvisioned -- localValue 10,
    -- teleserviceNotProvisioned -- localValue 11,
    -- callBarred -- localValue 13,
    -- illegalSS-Operation -- localValue 16,
    -- ss-NotAvailable -- localValue 18}
::= localValue 14

```

#### notifySS OPERATION

##### ARGUMENT

```

notifySS-Arg SEQUENCE {
    ss-Code [1] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
    ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
    ss-Notification [5] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
    callsWaiting-Indicator [14] IMPLICIT NULL OPTIONAL,
    callOnHold-Indicator [15] IMPLICIT ENUMERATED {
        callRetrieved (0),
        callOnHold (1)} OPTIONAL,
    mpty-Indicator [16] IMPLICIT NULL OPTIONAL,
    cug-Index [17] IMPLICIT INTEGER (0..32767) OPTIONAL,
    clirSuppressionRejected [18] IMPLICIT NULL OPTIONAL,
    ... }
::= localValue 16

```

#### registerPassword OPERATION

##### ARGUMENT

```

ss-Code OCTET STRING (SIZE (1))

```

##### RESULT

```

newPassword NumericString (FROM ("0"|"1"|"2"|"3"|"4"|"5"|"6"|"7"|"8"|"9")|SIZE (4))

```

##### ERRORS {

```

    -- systemFailure -- localValue 34,
    -- dataMissing -- localValue 35,
    -- unexpectedDataValue -- localValue 36,
    -- callBarred -- localValue 13,
    -- ss-SubscriptionViolation -- localValue 19,

```

```

-- pw-RegistrationFailure -- localValue 37,
-- negativePW-Check -- localValue 38,
-- numberOfPW-AttemptsViolation -- localValue 43}
LINKED {
-- getPassword -- localValue 18}
::= localValue 17

getPassword OPERATION
ARGUMENT
  guidanceInfo ENUMERATED {
    enterPW (0),
    enterNewPW (1),
    enterNewPW-Again (2),
    badPW-TryAgain (3),
    badPW-FormatTryAgain (4)}
RESULT
  currentPassword NumericString (FROM ("0"|"1"|"2"|"3"|"4"|"5"|"6"|"7"|"8"|"9")|SIZE (4))
::= localValue 18

processUnstructuredSS-Data OPERATION
ARGUMENT
  ss-UserData IA5String (SIZE (1..200))
RESULT
  ss-UserData IA5String (SIZE (1..200))
ERRORS {
-- systemFailure -- localValue 34,
-- unexpectedDataValue -- localValue 36}
::= localValue 19

forwardCheckSS-Indication OPERATION
::= localValue 38

processUnstructuredSS-Request OPERATION
ARGUMENT
  ussd-Arg SEQUENCE {
    ussd-DataCodingScheme OCTET STRING (SIZE (1)),
    ussd-String OCTET STRING (SIZE (1..160)),
    ... }
RESULT
  ussd-Res SEQUENCE {
    ussd-DataCodingScheme OCTET STRING (SIZE (1)),
    ussd-String OCTET STRING (SIZE (1..160)),
    ... }
ERRORS {
-- systemFailure -- localValue 34,
-- dataMissing -- localValue 35,
-- unexpectedDataValue -- localValue 36,
-- unknownAlphabet -- localValue 71,
-- callBarred -- localValue 13}
::= localValue 59

unstructuredSS-Request OPERATION
ARGUMENT
  ussd-Arg SEQUENCE {
    ussd-DataCodingScheme OCTET STRING (SIZE (1)),
    ussd-String OCTET STRING (SIZE (1..160)),
    ... }
RESULT
  ussd-Res SEQUENCE {
    ussd-DataCodingScheme OCTET STRING (SIZE (1)),
    ussd-String OCTET STRING (SIZE (1..160)),
    ... }
ERRORS {

```

```

-- systemFailure -- localValue 34,
-- dataMissing -- localValue 35,
-- unexpectedDataValue -- localValue 36,
-- absentSubscriber -- localValue 27,
-- illegalSubscriber -- localValue 9,
-- illegalEquipment -- localValue 12,
-- unknownAlphabet -- localValue 71,
-- ussd-Busy -- localValue 72}
::= localValue 60

```

## unstructuredSS-Notify OPERATION

## ARGUMENT

```

ussd-Arg SEQUENCE {
  ussd-DataCodingScheme OCTET STRING (SIZE (1)),
  ussd-String OCTET STRING (SIZE (1..160)),
  ... }

```

## ERRORS {

```

-- systemFailure -- localValue 34,
-- dataMissing -- localValue 35,
-- unexpectedDataValue -- localValue 36,
-- absentSubscriber -- localValue 27,
-- illegalSubscriber -- localValue 9,
-- illegalEquipment -- localValue 12,
-- unknownAlphabet -- localValue 71,
-- ussd-Busy -- localValue 72}

```

```

::= localValue 61

```

## forwardCUG-Info OPERATION

## ARGUMENT

```

forwardCUG-InfoArg SEQUENCE {
  cug-Index [0] IMPLICIT INTEGER (0..32767) OPTIONAL,
  suppressPrefCUG [1] IMPLICIT NULL OPTIONAL,
  suppressOA [2] IMPLICIT NULL OPTIONAL,
  ... }

```

```

::= localValue 120

```

## splitMPTY OPERATION

## RESULT

```

zzzz-empty NULL

```

## ERRORS {

```

-- illegalSS-Operation -- localValue 16,
-- ss-ErrorStatus -- localValue 17,
-- ss-Incompatibility -- localValue 20,
-- facilityNotSupported -- localValue 21,
-- systemFailure -- localValue 34}

```

```

::= localValue 121

```

## retrieveMPTY OPERATION

## RESULT

```

zzzz-empty NULL

```

## ERRORS {

```

-- illegalSS-Operation -- localValue 16,
-- ss-ErrorStatus -- localValue 17,
-- ss-Incompatibility -- localValue 20,
-- facilityNotSupported -- localValue 21,
-- systemFailure -- localValue 34}

```

```

::= localValue 122

```

## holdMPTY OPERATION

## RESULT

```

zzzz-empty NULL

```

## ERRORS {

```

-- illegalSS-Operation -- localValue 16,

```

```
-- ss-ErrorStatus -- localValue 17,  
-- ss-Incompatibility -- localValue 20,  
-- facilityNotSupported -- localValue 21,  
-- systemFailure -- localValue 34}  
 ::= localValue 123
```

buildEMPTY OPERATION

RESULT

zzzz-empty NULL

ERRORS {

```
-- illegalSS-Operation -- localValue 16,  
-- ss-ErrorStatus -- localValue 17,  
-- ss-NotAvailable -- localValue 18,  
-- ss-Incompatibility -- localValue 20,  
-- systemFailure -- localValue 34,  
-- resourcesNotAvailable -- localValue 127,  
-- maxNumberOfEMPTY-ParticipantsExceeded -- localValue 126}
```

::= localValue 124

forwardChargeAdvice OPERATION

ARGUMENT

```
forwardChargeAdviceArg SEQUENCE {  
  ss-Code [0] IMPLICIT OCTET STRING (SIZE (1)),  
  chargingInformation [1] IMPLICIT SEQUENCE {  
    e1 [1] IMPLICIT INTEGER (0..8191) OPTIONAL,  
    e2 [2] IMPLICIT INTEGER (0..8191) OPTIONAL,  
    e3 [3] IMPLICIT INTEGER (0..8191) OPTIONAL,  
    e4 [4] IMPLICIT INTEGER (0..8191) OPTIONAL,  
    e5 [5] IMPLICIT INTEGER (0..8191) OPTIONAL,  
    e6 [6] IMPLICIT INTEGER (0..8191) OPTIONAL,  
    e7 [7] IMPLICIT INTEGER (0..8191) OPTIONAL,  
    ... },  
  ... }  
}
```

RESULT

zzzz-empty NULL

::= localValue 125

unknownSubscriber ERROR

::= localValue 1

illegalSubscriber ERROR

::= localValue 9

bearerServiceNotProvisioned ERROR

::= localValue 10

teleserviceNotProvisioned ERROR

::= localValue 11

illegalEquipment ERROR

::= localValue 12

callBarred ERROR

PARAMETER

```
callBarringCause ENUMERATED {  
  barringServiceActive (0),  
  operatorBarring (1)}
```

::= localValue 13

illegalSS-Operation ERROR

::= localValue 16

ss-ErrorStatus ERROR

```

PARAMETER
  ss-Status OCTET STRING (SIZE (1))
 ::= localValue 17

ss-NotAvailable ERROR
 ::= localValue 18

ss-SubscriptionViolation ERROR
PARAMETER
  ss-SubscriptionOption CHOICE {
    cliRestrictionOption [2] IMPLICIT ENUMERATED {
      permanent (0),
      temporaryDefaultRestricted (1),
      temporaryDefaultAllowed (2)},
    overrideCategory [1] IMPLICIT ENUMERATED {
      overrideEnabled (0),
      overrideDisabled (1)}}
 ::= localValue 19

ss-Incompatibility ERROR
PARAMETER
  ss-IncompatibilityCause SEQUENCE {
    ss-Code [1] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
    basicService CHOICE {
      bearerService [2] IMPLICIT OCTET STRING (SIZE (1)),
      teleservice [3] IMPLICIT OCTET STRING (SIZE (1))} OPTIONAL,
    ss-Status [4] IMPLICIT OCTET STRING (SIZE (1)) OPTIONAL,
    ... }
 ::= localValue 20

facilityNotSupported ERROR
 ::= localValue 21

absentSubscriber ERROR
PARAMETER
  mwd-Set BOOLEAN
 ::= localValue 27

systemFailure ERROR
PARAMETER
  networkResource ENUMERATED {
    plmn (0),
    hlr (1),
    vlr (2),
    pvlr (3),
    controllingMSC (4),
    vmsc (5),
    eir (6),
    rss (7)}
 ::= localValue 34

dataMissing ERROR
 ::= localValue 35

unexpectedDataValue ERROR
 ::= localValue 36

pw-RegistrationFailure ERROR
PARAMETER
  pw-RegistrationFailureCause ENUMERATED {
    undetermined (0),
    invalidFormat (1),
    newPasswordsMismatch (2)}

```

::= localValue 37

negativePW-Check ERROR

::= localValue 38

numberOfPW-AttemptsViolation ERROR

::= localValue 43

unknownAlphabet ERROR

::= localValue 71

ussd-Busy ERROR

::= localValue 72

maxNumberOfEMPTY-ParticipantsExceeded ERROR

::= localValue 126

resourcesNotAvailable ERROR

::= localValue 127

END



## History

Document history			
March 1994	Public Enquiry	PE 59:	1994-03-21 to 1994-08-12
November 1994	Vote	V 69:	1994-11-21 to 1995-01-13
February 1995	First Edition		
December 1995	Unified Approval Procedure (Second edition)	UAP 40:	1995-12-04 to 1996-03-29
March 1996	Unified Approval Procedure (Third edition)	UAP 44:	1996-03-04 to 1996-06-28
August 1996	Second Edition		
August 1996	Third Edition		