

Private Integrated Services Network (PISN); Mapping functions for the tunnelling of QSIG through IP networks



Reference

DTS/ECMA-00234

Keywords

PINX, PISN

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	5
Foreword.....	5
Brief history	5
1 Scope	6
2 Conformance	6
3 References	6
4 Definitions	7
4.1 External definitions	7
4.2 Other definitions.....	7
4.2.1 Calling PINX	7
4.2.2 Called PINX.....	7
4.2.3 Channel.....	7
4.2.3.1 D _Q -Channel	7
4.2.3.2 U _Q -Channel	7
4.2.4 Resource Control Information	7
4.2.5 Inter-PINX Connection (IPC).....	7
4.2.6 QPKT.....	7
5 List of acronyms	8
6 Introduction	8
6.1 Reference configuration	8
6.2 Specific scenarios	8
7 Capabilities at the Q reference point	9
8 Capabilities at the C reference point	10
8.1 TCP connection	10
8.2 UDP streams.....	10
9 Mapping functions.....	11
9.1 Mapping the D _Q -channel	11
9.2 Mapping a U _Q -channel	11
10 IPC control functions.....	11
10.1 Procedure for U _Q -channel establishment.....	11
10.2 Procedure for U _Q -channel clearing.....	12
Annex A (normative): Implementation Conformance Statement (ICS) Proforma	13
A.1 Introduction	13
A.2 Instructions for completing the ICS proforma.....	13
A.2.1 General structure of the ICS proforma	13
A.2.2 Additional information	14
A.2.3 Exception information.....	14
A.3 ICS proforma for ECMA-336	14
A.3.1 Implementation identification	14
A.3.2 Implementation summary.....	14
A.4 General requirements	15
A.5 U _Q -channel bearer capabilities at the Q reference point.....	15
A.6 D _Q -channel capability at the Q reference point	15
A.7 Capabilities at the C reference point	15

A.8	Mapping functions.....	15
A.9	IPC control functions.....	16
A.10	Support of resource control information	16
A.10.1	Support of bearer capabilities information	16
A.10.2	Support of IP address type.....	16
Annex B (normative): Message syntax for Resource Control Information.....		17
B.1	Introduction	17
B.2	Message syntax	17
B.2.1	Resource control header	17
B.2.2	Protocol indicator	17
B.2.3	Resource control information	17
B.2.3.1	Bearer capabilities information.....	18
B.2.3.2	UDP stream information	18
History	20

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ECMA on behalf of its members and those of the European Telecommunications Standards Institute (ETSI).

Brief history

The present document is one of a series of ECMA standards defining mapping functions in exchanges of Private Integrated Services Networks required for the utilization of intervening network scenarios. The series uses the ISDN concepts as developed by ITU-T (formerly CCITT) and is also within the framework of standards for open systems interconnection as defined by ISO/IEC. It has been produced under ETSI work item DTS/ECMA-00234.

The present document is based upon the practical experience of ECMA member companies and the results of their active and continuous participation in the work of ISO/IEC JTC1, ITU-T, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.

The present document has been adopted by the ECMA General Assembly of June 2002.

1 Scope

The present document specifies functions for using a packet network that uses the Internet Protocol (IP) as its network layer protocol and UDP and TCP as its transport layer protocols, to interconnect two Private Integrated services Network eXchanges (PINXs) forming part of a Private Integrated Services Network (PISN). Interconnection is achieved by carrying the inter-PINX signalling protocol directly over the Transmission Control Protocol (TCP) and inter-PINX user information (e.g. voice) over the Real-time Transport Protocol (RTP), RTP being carried over the User Datagram Protocol (UDP). The inter-PINX signalling protocol is assumed to be QSIG, as specified in EN 300 172, ETS 300 239 and other standards.

The present document provides for two types of interconnection:

- on-demand, where a separate TCP connection for QSIG is established at the start of each call and cleared down at the end of that call; and
- semi-permanent, where a single TCP connection with an indefinite lifetime carries QSIG on behalf of many single calls.

The present document is applicable to PINXs that can be interconnected to form a PISN using QSIG as the inter-PINX signalling protocol.

2 Conformance

In order to conform to the present document, a PINX shall satisfy the requirements identified in the Implementation Conformance Statement (ICS) proforma in annex A.

3 References

The following standards contain provisions which, through reference in this text, constitute provision of this Standard. All standards are subject to revision, and parties to agreements based on this Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

ETSI ETS 300 475-1: "Private Telecommunication Network (PTN); Reference configuration; Part 1: Reference configuration for PTN eXchanges (PTNXs) [ISO/IEC 11579-1 (1994), modified]".

ETSI EN 300 171: "Private Integrated Services Network (PISN); Specification, functional models and information flows; Control aspects of circuit-mode basic services [ISO/IEC 11574 (1994) modified]".

ETSI EN 300 172: "Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Circuit-mode basic services [ISO/IEC 11572 (1996) modified]".

ETSI ETS 300 239: "Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Generic functional protocol for the support of supplementary services [ISO/IEC 11582 (1995), modified]".

ITU-T Recommendation I.112 (1993): "Vocabulary of terms for ISDNs".

ITU-T Recommendation I.210 (1993): "Principles of telecommunication services supported by an ISDN and the means to describe them".

IETF RFC 760: "Internet Protocol".

IETF RFC 761: "Transmission Control Protocol".

IETF RFC 768: "User Datagram Protocol".

IETF RFC 1889: "RTP: a transport protocol for real-time applications".

IETF RFC 2126: "ISO Transport Service on top of the TCP (ITOT)".

4 Definitions

For the purposes of the present document, the following terms and definitions apply:

4.1 External definitions

The present document uses the following terms defined in other documents:

- IVN (ETS 300 475-1)
- PINX (ETS 300 475-1)
- PISN (ETS 300 475-1)
- Service (ITU-T Recommendation I.112)
- Signalling (ITU-T Recommendation I.112)

4.2 Other definitions

4.2.1 Calling PINX

In the context of a call or call-independent signalling connection across an IPL, the PINX that transmits the QSIG SETUP message.

4.2.2 Called PINX

In the context of a call or call-independent signalling connection across an IPL, the PINX that receives the QSIG SETUP message.

4.2.3 Channel

A means of bi-directional transmission of user or signalling information between two points.

4.2.3.1 D_Q-Channel

A channel used to convey call control information between the Q reference points of two peer PINXs.

4.2.3.2 U_Q-Channel

A channel used to convey user information between the Q reference points of two peer PINXs.

4.2.4 Resource Control Information

Information exchanged between peer PINXs for the purpose of establishing UDP streams

4.2.5 Inter-PINX Connection (IPC)

A connection provided by an IVN between two C reference points used to transport inter-PINX information from the PISN control plane and/or the PISN user plane.

4.2.6 QPKT

A packet format defined within the present document for conveying QSIG message and RCI (Resource Control Information).

5 List of acronyms

IP	Internet Protocol
IPC	Inter-PINX connection
IPL	Inter-PINX Link
IVN	InterVening Network
PINX	Private Integrated services Network eXchange
PISN	Private Integrated Services Network
QSIG	SIGnalling information flows at the Q reference point
RCI	Resource Control Information
RTCP	Realtime Transport Control Protocol
RTP	Realtime Transport Protocol
TCP	Transmission Control Protocol
UDP	User Datagram Protocol

6 Introduction

6.1 Reference configuration

ETS 300 475-1 defines a reference configuration for a PINX. Logically the switching and call control functions of a PINX communicate over an instance of the Q reference point with a peer PINX. This communication is known as an Inter-PINX Link (IPL) and comprises a signalling channel, known as a D_Q-channel, and one or more user information channels, each known as a U_Q-channel; see figure 1. One or more IPLs can be established between the same pair of PINXs.




Figure 1: IPL concept

There are many ways of implementing an IPL. In general, the IPL uses services of another network, known as an Intervening Network (IVN). A PINX interfaces to the IVN at the C reference point. The IVN provides connections, known as Inter-PINX Connections (IPCs) between the C reference points of the peer PINXs. Mapping functions within each PINX map the D_Q-channel and the U_Q-channels at the Q reference point onto one or more IPCs at the C reference point.

6.2 Specific scenarios

The present document specifies mapping functions for use when the IVN is an IP-based network that is used to provide the following types of IPC:

- a TCP connection for carrying signalling information and Resource Control Information; and
- a pair of UDP streams, one stream in each direction, for carrying user information over RTP.

A single IPL requires a single TCP connection, for support of the D_Q -channel, and one pair of UDP streams per U_Q -channel. In addition to carrying the QSIG protocol, the TCP connection is also required to carry resource control information for establishing the UDP streams.

The present document supports two types of interconnection between peer PINXs:

- On-demand, where a single TCP connection for QSIG and a pair of UDP streams for user information are established at the start of each call and cleared down at the end of that call;
- Semi-permanent, where a single TCP connection with an indefinite lifetime carries QSIG on behalf of many calls.

In the semi-permanent case, the TCP connection can support zero, one or more than one call at the same time. A pair of UDP streams for user information is established at the start of each call and cleared down at the end of that call.

Figure 2 illustrates these concepts.




Figure 2: IPC concept (Semi-permanent)

7 Capabilities at the Q reference point

For each instance of the Q reference point:

- one signalling channel (D_Q) for carrying the inter-PINX Layer 3 signalling protocol, and
- zero, one or more user channels (U_Q)

shall be provided.

NOTE: In the special case of an on-demand interconnection used only for a call independent signalling connection, no U_Q -channels are provided.

For a U_Q -channel the following bearer capability shall be provided:

- transfer mode: circuit mode;
- information transfer rate: 64 kbit/s;
- information transfer capability: speech or 3,1 kHz audio;
- user information layer 1 protocol: G.711 A or μ law.

Other bearer capabilities are outside the scope of the present document.

For a D_Q -channel the following bearer capability shall be provided:

- transfer mode: packet mode;

- information transfer rate: implementation-dependent;
- information transfer capability: unrestricted digital information.

The functions to map D_Q - and U_Q -channels to an inter-PINX connection (IPC) at the C reference point are described in clause 9.

8 Capabilities at the C reference point

The PINX mapping functions shall meet the following requirements.

8.1 TCP connection

A PINX shall support a packet network interface suitable for communication according to IETF RFC 761. The protocol stack used in the present document is described as figure 3.





Figure 3: Protocol stack for Mapping/IP-QSIG

The RCI provides information required to establish the media path(s).

A TPKT is a packet format as defined in IETF RFC 2126. It is used to delimit individual messages (PDUs) within the TCP stream, which itself provides a continuous stream of octets without explicit boundaries. A TPKT consists of a one octet version number field, followed by a one octet reserved field, followed by a two octet length field, followed by the actual data. The version number field shall contain the value "3", the reserved field shall contain the value "0". The length field shall contain the length of the entire packet including the version number, the reserved and the length fields as a 16-bit big-endian word.

A QPKT is a packet format as defined in figure 4. A QPKT consists of a two octet length field, followed by a single QSIG message, followed by RCI. The first octet of the QSIG message shall be the octet immediately following the QPKT length field, the last octet shall be the octet immediately preceding the RCI. The length field indicates the length of the QSIG message and therefore indicates the start of the RCI.



NOTE: In most circumstances, the RCI field is omitted.

Figure 4: QPKT structure of Mapping/IP-QSIG

The D_Q -channel shall be mapped to the well-known TCP port (4029) or to a dynamically assigned port. RCI shall be in accordance with annex B.

8.2 UDP streams

The U_Q -channel shall be mapped to a received UDP stream and a transmitted UDP stream, each carrying RTP packets. The received UDP stream shall be received at a local IP address and port as indicated in transmitted RCI and the transmitted UDP stream shall be transmitted to a remote IP address and port as indicated in received RCI.

NOTE: If required, PINXs can use RTCP as defined in IETF RFC 1889 to monitor the quality of RTP carried over UDP streams.

9 Mapping functions

9.1 Mapping the D_Q-channel

For transmission, a complete QSIG message and RCI shall be embedded in a QPKT packet within a TPKT packet as defined in clause 8.1. The segmentation and reassembly procedures of EN 300 172 shall not be used.

The RCI implicitly refers to the call to which the QSIG message relates. It shall be included in the first forward and first backward message of each call, and shall not be included in subsequent messages. In addition, RCI shall not be included with call-independent messages.

9.2 Mapping a U_Q-channel

Each U_Q-channel shall be mapped to a pair of unidirectional UDP streams with suitable transport capabilities defined by the RCI. The mapping function is responsible for proper packetization, de-packetization, transcoding etc. of media data.

10 IPC control functions

To establish the IPC for the D_Q-channel, the PINX initiating the TCP connection needs to know the IP address of the other PINX. The means for determining the IP address is outside the scope of the present document.

For the on-demand scenario, the calling PINX shall establish a TCP connection for the D_Q-channel following the procedure specified in IETF RFC 761 whenever a call or call-independent signalling connection is to be established and shall clear down the TCP connection when the call or call-independent signalling connection has been cleared.

For the semi-permanent scenario, when a call or call independent signalling connection is to be established, if a D_Q-channel (TCP connection) exists between the peer-PINXs, the calling PINX shall use that D_Q-channel. If no D_Q-channel exists between the peer PINXs, the calling PINX shall establish a TCP connection for the D_Q-channel following the procedure specified in IETF RFC 761. It is an implementation matter when to clear the TCP connection, except that it shall not to be cleared while still being used for a call or call independent signalling connection.

For either scenario, U_Q-channel establishment and clear down shall be in accordance with clauses 10.1 and 10.2 respectively.

10.1 Procedure for U_Q-channel establishment

U_Q-channel establishment shall occur whenever a call is established.

In order to establish the U_Q-channel, the calling PINX and the called PINX shall each transmit RCI in accordance with annex B. The calling PINX shall transmit RCI in the same QPKT packet as the QSIG SETUP message.

The called PINX shall check that the received RCI information is acceptable and if so transmit RCI in the same QPKT packet as the QSIG SETUP ACKNOWLEDGE message or the QSIG CALL PROCEEDING message, whichever is transmitted first.

NOTE 1: EN 300 172 requires the Channel identification information element to be present in the QSIG SETUP message and in the QSIG SETUP ACKNOWLEDGE message or CALL PROCEEDING message, whichever is transmitted first. The contents of the Channel identification information element can be ignored on receipt.

NOTE 2: If the first response to the SETUP message is neither SETUP ACKNOWLEDGE nor CALL PROCEEDING (e.g. RELEASE COMPLETE), no RCI is returned.

After transmitting RCI, the calling PINX shall be prepared to receive RTP packets on the IP address and port as specified in the transmitted RCI.

The called PINX shall include in the transmitted RCI the same codec type and payload period as specified in the received RCI. After transmitting the RCI, the called PINX shall begin transmitting RTP packets to the IP address and port as specified in the received RCI in accordance with the codec type and payload period as specified in the received RCI as soon as media becomes available. The called PINX shall also be prepared to receive RTP packets on the IP address and port as specified in the transmitted RCI.

After having received RCI in the first response message and after having received the CONNECT message, the calling PINX shall begin transmitting RTP packets to the IP address and port in the received RCI in accordance with the codec type and payload period in the received RCI.

During the establishment of the U_Q -channel, if either the calling PINX or the called PINX receives unacceptable content in the RCI, that PINX shall behave as specified in EN 300 172 for the case where the content of the Channel identification information element is unacceptable.

10.2 Procedure for U_Q -channel clearing

Before transmitting a QSIG call clearing message (DISCONNECT, RELEASE or RELEASE COMPLETE), a PINX shall stop transmitting RTP packets and shall ignore the contents of any further received RTP packets.

After transmitting or receiving a QSIG RELEASE COMPLETE message, the PINX should release the resources associated with the U_Q -channel.

Annex A (normative): Implementation Conformance Statement (ICS) Proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the ICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed ICS.

A.1 Introduction

The supplier of a implementation which is claimed to conform to the present document shall complete the following Implementation Conformance Statement (ICS) proforma.

A completed ICS proforma is the ICS for the implementation in question. The ICS is a statement of which capabilities and options of the have been implemented. The ICS can have a number of uses, including use:

- by the implementor, as a check-list to reduce the risk of failure to conform to the standard through oversight;
- by the supplier and acquirer, or potential acquirer, of the implementation, as a detailed indication of the capabilities of the implementation, stated relative to the common basis for understanding provided by the standard's ICS proforma;
- by the user or potential user of the implementation, as a basis for initially checking the possibility of interworking with another implementation - while interworking can never be guaranteed, failure to interwork can often be predicted from incompatible ICSs.

A.2 Instructions for completing the ICS proforma

A.2.1 General structure of the ICS proforma

The ICS proforma is a fixed-format questionnaire divided into clauses each containing a group of individual items. Each item is identified by an item number, the name of the item (question to be answered), and the reference(s) to the clause(s) that specifies (specify) the item in the main body of the present document.

The "Status" column indicates whether an item is applicable and if so whether support is mandatory or optional. The following terms are used:

m	mandatory (the capability is required for conformance to the standard);
o	optional (the capability is not required for conformance to the , but if the capability is implemented it is required to conform to the specifications);
o.<n>	optional, but support of at least one of the group of options labelled by the same numeral <n> is required;
x	prohibited;
<c.cond>	conditional requirement, depending on support for the item or items listed in condition <cond>;
<item>;m	simple conditional requirement, the capability being mandatory if item number <item> is supported, otherwise not applicable;
<item>;o	simple conditional requirement, the capability being optional if item number <item> is supported, otherwise not applicable.

Answers to the questionnaire items are to be provided either in the "Support" column, by simply marking an answer to indicate a restricted choice (Yes or No), or in the "Not Applicable" column (N/A).

A.2.2 Additional information

Items of additional information allow a supplier to provide further information intended to assist the interpretation of the ICS. It is not intended or expected that a large quantity will be supplied, and a ICS can be considered complete without any such information. Examples might be an outline of the ways in which a (single) implementation can be set up to operate in a variety of environments and configurations.

References to items of additional information may be entered next to any answer in the questionnaire, and may be included in items of exception information.

A.2.3 Exception information

It may occasionally happen that a supplier will wish to answer an item with mandatory or prohibited status (after any conditions have been applied) in a way that conflicts with the indicated requirement. No pre-printed answer will be found in the Support column for this. Instead, the supplier is required to write into the Support column an x.<i> reference to an item of exception information, and to provide the appropriate rationale in the exception item itself.

An implementation for which an exception item is required in this way does not conform to the present document. A possible reason for the situation described above is that a defect in the Standard has been reported, a correction for which is expected to change the requirement not met by the implementation.

A.3 ICS proforma for ECMA-336

A.3.1 Implementation identification

Supplier	
Contact point for queries about the ICS	
Implementation name(s) and version(s)	
Other information necessary for full identification, e.g. name(s) and version(s) for machines and/or operating systems; system name(s)	

Only the first three items are required for all implementations; other information may be completed as appropriate in meeting the requirement for full identification.

The terms name and version should be interpreted appropriately to correspond with a suppliers terminology (e.g. type, series, model).

A.3.2 Implementation summary

Implementation version	1.0
Addenda implemented (if applicable)	
Amendments implemented	
Have any exception items been required (see clause A.2.3)?	No <input type="checkbox"/> Yes <input type="checkbox"/> (The answer Yes means that the implementation does not conform to this standard)

Date of Statement	
-------------------	--

A.4 General requirements

Item	Question/feature	References	Status	N/A	Support
A1	Support of on-demand IPC		m		Yes []
A2	Support of semi-permanent IPC		o		Yes [] No []

A.5 U_Q-channel bearer capabilities at the Q reference point

Item	Question/feature	References	Status	N/A	Support
B1	Support transfer mode as "circuit mode"	7	m		Yes []
B2	Support 64 kbit/s information transfer rate	7	m		Yes []
B3	Support "speech" for information transfer capability	7	o.1		Yes [] No []
B4	Support "3,1 kHz audio" for information transfer capability	7	o.1		Yes [] No []
B5	Support "G.711A-law" for user information layer 1 protocol	7	o.2		Yes [] No []
B6	Support "G.711 μ -law" for user information layer 1 protocol	7	o.2		Yes [] No []
B7	Support other user information layer 1 protocol (specify:)	7	o		Yes [] No []

A.6 D_Q-channel capability at the Q reference point

Item	Question/feature	References	Status	N/A	Support
C1	Support of "packet mode" as transfer mode	7	m		Yes []
C2	Support of "unrestricted digital information" for information transfer capability	7	m		Yes []

A.7 Capabilities at the C reference point

Item	Question/feature	References	Status	N/A	Support
D1	Support of QPKT packet structure	8.1	m		Yes []
D2	Support of well-know TCP port (4029) for D _Q -channel	8.1	m		Yes []
D3	Support of dynamically assigned TCP port for D _Q -channel	8.1	o		Yes [] No []
D4	Support of dynamically assigned UDP port as signalled by RCI	8.2	m		Yes []

A.8 Mapping functions

Item	Question/feature	References	Status	N/A	Support
E1	Support mapping of the D _Q -channel	9.1	m		Yes []
E2	Support mapping of the U _Q -channel	9.2	m		Yes []

A.9 IPC control functions

Item	Question/feature	References	Status	N/A	Support
F1	Support establishing / clearing of the D _Q -channel for the on-demand scenario	10	m		Yes []
F2	Support establishing / clearing of the D _Q -channel for the semi-permanent scenario	10	A2:m	[]	Yes []
F3	Support establishing of the U _Q -channel	10.1	m		Yes []
F4	Support clearing of the U _Q -channel	10.2	m		Yes []

A.10 Support of resource control information

A.10.1 Support of bearer capabilities information

Item	Question/feature	References	Status	N/A	Support
G1	Support codec type "g711Alaw64k"	B.2.3.1	o.1		Yes [] No []
G2	Support codec type "g711Ulaw64k"	B.2.3.1	o.1		Yes [] No []
G3	Support codec type "g723.1"	B.2.3.1	o.1		Yes [] No []
G4	Support codec type "g729"	B.2.3.1	o.1		Yes [] No []
G5	Support codec type "g729AnnexA"	B.2.3.1	o.1		Yes [] No []
G6	Support codec type "g729wAnnexB"	B.2.3.1	o.1		Yes [] No []
G7	Support codec type "g729AnnexAwAnnexB"	B.2.3.1	o.1		Yes [] No []
G8	Support payload period (specify: msec)	B.2.3.1	m		Yes []

A.10.2 Support of IP address type

Item	Question/feature	References	Status	N/A	Support
H1	Support of IP address type "IPv4"	B.2.3.2	m		Yes []
H2	Support of IP address type "IPv6"	B.2.3.2	o		Yes [] No []

Annex B (normative): Message syntax for Resource Control Information

B.1 Introduction

This annex defines the syntax for RCI, which is exchanged between peer PINXs for the purpose of establishing a pair of IPCs for providing a U_Q-channel. A PINX shall be capable of transmitting and receiving RCI in accordance with this syntax.

B.2 Message syntax

Octet group	8	7	6	5	4	3	2	1	Reference
1	Resource control header								B.2.1
2	Protocol indicator								B.2.2
3	Resource control information								B.2.3

B.2.1 Resource control header

Octet	8	7	6	5	4	3	2	1	
1.1	0	1	1	1	1	1	1	0	Resource control discriminator
1.2	x	x	x	x	x	x	x	x	Length of entire RCI

B.2.2 Protocol indicator

Octet	8	7	6	5	4	3	2	1	
2.1	x	x	x	x	x	x	x	x	Protocol identifier
2.2	x	x	x	x	x	x	x	x	Version identifier

"Protocol identifier" is coded as follows:

Bit	8	7	6	5	4	3	2	1	
	0	0	0	0	0	0	0	0	ECMA-336
Others									Reserved

"Version identifier" is coded as follows:

Bit	8	7	6	5	4	3	2	1	
	0	0	0	0	0	0	0	1	Version information

B.2.3 Resource control information

Octet group	8	7	6	5	4	3	2	1	Description	Reference
3.1	x	x	x	x	x	x	x	x	Bearer capabilities information	B.2.3.1
3.2	x	x	x	x	x	x	x	x	UDP stream information	B.2.3.2

B.2.3.1 Bearer capabilities information

Octet	8	7	6	5	4	3	2	1
3.1.1	0	0	0	0	0	1	0	0
3.1.2	x	x	x	x	x	x	x	x
3.1.3	x	x	x	x	x	x	x	x

Bearer capabilities information discriminator
 Type of codec (any value from the list below)
 Payload period (unit: milliseconds.)

Type of codec is coded as follows:

Bit	8	7	6	5	4	3	2	1
	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	1	1
	0	0	0	0	0	1	0	0
	0	0	0	0	0	1	0	1
	0	0	0	0	1	0	1	0
	0	0	0	0	1	0	1	1
	0	0	0	0	1	1	1	0
	0	0	0	0	1	1	1	1
Others								

g711Alaw64k,
 g711Ulaw64k,
 g723.1 with silence compression,
 g723.1 without silence compression,
 g729,
 g729AnnexA,
 g729wAnnexB,
 g729AnnexAwAnnexB,
 Reserved

B.2.3.2 UDP stream information

UDP stream information is coded as follows:

Octet	8	7	6	5	4	3	2	1
3.2.1	0	0	0	1	0	0	0	0
3.2.2								
3.2.3								
to								
3.2.3+								
n-1								
3.2.3+								
n								
3.2.3+								
n+1								

UDP stream information discriminator
 Type of IP address
 IP address (n octets) (note 1)

UDP port number for RTP (note 2, note 3)

NOTE 1: Octet 3.2.3 contains the most significant octet of the IP address.

NOTE 2: The RTCP port number should be one greater than the RTP port number.

NOTE 3: Octet 3.2.3+n contains the most significant octet of the UDP port number.

"Type of IP address" is coded as follows:

Bit	8	7	6	5	4	3	2	1
	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	1	0
Others								

IPv4 address
 IPv6 address, optional
 Reserved

The length of field of "IP address" (n octets) depends on the type of IP address. For an IPv4 address this field occupies 4 octets. For an IPv6 address this field occupies 16 octets. For example, if an IPv4 address is used, octets 3.2.1 to 3.2.8 are coded as follows:

Octet	8	7	6	5	4	3	2	1
3.2.1	0	0	0	1	0	0	0	0
3.2.2	0	0	0	0	0	0	0	0
3.2.3	1	0	1	0	1	1	0	0
3.2.4	0	0	0	1	0	0	0	0
3.2.5	0	0	0	0	0	0	0	1
3.2.6	0	0	0	0	0	0	0	1
3.2.7	1	1	0	1	1	0	1	0
3.2.8	1	1	0	0	0	0	0	0

UDP stream information (RTP)

Type of IP address

IP address (172.16.1.1)

UDP port number for RTP (56 000)

History

Document history		
V1.1.1	July 2002	Publication