



**Railway Telecommunications (RT);  
GSM-R improved receiver parameters;  
Part 1: Requirements for radio reception**

---

Reference

RTS/RT-0032

---

Keywords

ER-GSM, radio, R-GSM

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
Modal verbs terminology.....	4
Introduction .....	4
1 Scope .....	5
2 References .....	5
2.1 Normative references .....	5
2.2 Informative references.....	6
3 Abbreviations .....	6
4 Frequency bands and channel arrangement.....	6
5 Transmitter characteristics for 8 Watt mobiles .....	7
5.0 General provisions.....	7
5.1 Output power.....	7
5.1.1 Mobile Station .....	7
6 Transmitter characteristics for 2 Watt mobiles .....	9
6.0 General provisions.....	9
6.1 Output power.....	9
6.1.1 Mobile Station .....	9
7 Receiver characteristics for 8 Watt mobiles.....	11
7.0 General provisions.....	11
7.1 Blocking characteristics .....	11
7.1.0 Blocking characteristics of the receiver.....	11
7.1.1 Blocking with CW interfering signals .....	11
7.1.2 Blocking with broadband interfering signals .....	12
8 Receiver characteristics for 2 Watt mobiles.....	12
8.0 General provisions.....	12
8.1 Blocking characteristics .....	13
8.1.0 Blocking characteristics of the receiver.....	13
8.1.1 Blocking with CW interfering signals .....	13
8.1.2 Blocking with broadband interfering signals .....	14
9 Other requirements.....	14
<b>Annex A (normative): Environmental conditions .....</b>	<b>15</b>
A.1 General .....	15
A.2 Environmental requirements for the MSs.....	15
A.2.0 General provisions.....	15
A.2.1 Temperature (R-GSM 900 and ER-GSM 900).....	15
A.2.2 Vibration (R-GSM 900 and ER-GSM 900).....	15
<b>Annex B (informative): Bibliography.....</b>	<b>16</b>
History .....	17

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Railway Telecommunications (RT).

The present document is part 1 of a multi-part deliverable covering the Railway Telecommunications (RT); GSM-R improved receiver parameters, as identified below:

**Part 1: "Requirements for radio reception";**

Part 2: "Radio conformance testing".

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The present document is adding the requirements for the 2 Watt professional small mobile stations (OPH and OPS) for the pan-European digital cellular telecommunication system R-GSM/ER-GSM. The requirements already defined in the previous version 1.3.1 for the receiver of professional mobile station 8 Watt (cab radio and EDOR) are kept unchanged.

---

# 1 Scope

The present document defines the Radio Frequency requirements specific for the professional Mobile Station. The measurement methods are specified in ETSI TS 102 933-2 [5] and ETSI TS 100 607-1 [2].

Requirements are defined for two categories of parameters:

- Those that are required to provide compatibility between the radio channels, connected either to separate or common antennas, that are used in the system. This category also includes parameters providing compatibility with existing systems in the same or adjacent frequency bands.
- Those that define the reception requirements for all types of professional MS.

MSs may operate on more than one of the frequency bands specified in clause 4. These MSs, defined in ETSI EN 300 919 [1], are referred to as "Multi band MSs" in the present document.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 919: "Digital cellular telecommunications system (Phase 2+) (GSM); Types of Mobile Stations (MS) (GSM 02.06)".
- [2] ETSI TS 100 607-1: "Digital cellular telecommunications system (Phase 2+); Mobile Station (MS) conformance specification; Part 1: Conformance specification (3GPP 11.10-1 Release 1999)".
- [3] CENELEC EN 50155:2007: "Railway applications - Electronic equipment used on rolling stock".
- [4] ETSI TS 100 910: "Digital cellular telecommunications system (Phase 2+); Radio transmission and reception (3GPP TS 05.05 Release 1999)".
- [5] ETSI TS 102 933-2: "Railway Telecommunications (RT); GSM-R improved receiver parameters; Part 2: Radio conformance testing".
- [6] UIC Project EIRENE (European Integrated Railway Radio Enhanced Network): "System Requirements Specification".
- [7] ETSI TS 100 911: "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control (3GPP TS 05.08)".
- [8] ETSI TS 101 349: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control/Medium Access Control (RLC/MAC) protocol (3GPP TS 04.60)".
- [9] Void.
- [10] ETSI TS 136 141: "LTE; Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing (3GPP TS 36.141)".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1] ETSI TR 101 748: "Digital cellular telecommunications system (Phase 2+) (GSM); Abbreviations and acronyms (GSM 01.04)".

## 3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI TR 101 748 [i.1] and the following apply:

EDOR	ETCS Data Only Radio
ETCS	European Train Control System
OPH	Operational Purpose Handheld
OPS	Operational Purpose Handheld for Shunting

## 4 Frequency bands and channel arrangement

- a) Railways GSM 900 Band, R-GSM (includes Standard and Extended GSM 900 Band):
- for Railways GSM 900 band, the system is required to operate in the following frequency band:
    - 876 MHz to 915 MHz: mobile transmit, base receive;
    - 921 MHz to 960 MHz: base transmit, mobile receive.
- b) Extended Railways GSM 900 Band, ER-GSM (includes Standard and Extended GSM 900 Band):
- for Railways GSM 900 band, the system is required to operate in the following frequency band:
    - 873 MHz to 915 MHz: mobile transmit, base receive;
    - 918 MHz to 960 MHz: base transmit, mobile receive.

NOTE 1: The term GSM 900 is used for any GSM system, which operates in any 900 MHz band.

NOTE 2: The BTS may cover a complete band, or the BTS capabilities may be restricted to a subset only, depending on the operators needs.

The carrier spacing is 200 kHz.

The carrier frequency is designated by the absolute radio frequency channel number (ARFCN). For each carrier ARFCN, the corresponding frequency value in the lower band ( $F_l(n)$ ) and in the upper band ( $F_u(n)$ ) are defined below.

**Table 0**

Band	Frequency value of the carrier ARFCN in the lower band	Frequency channel number (ARFCN)	Frequency value of the carrier ARFCN in the upper band
R-GSM 900	$F_l(n) = 890 + 0,2 \times n$ $F_l(n) = 890 + 0,2 \times (n - 1\ 024)$	$0 \leq n \leq 124$ $955 \leq n \leq 974$	$F_u(n) = F_l(n) + 45$
ER-GSM 900	$F_l(n) = 890 + 0,2 \times n$ $F_l(n) = 890 + 0,2 \times (n - 1\ 024)$	$0 \leq n \leq 124$ $940 \leq n \leq 974$	$F_u(n) = F_l(n) + 45$

NOTE: Frequencies are in MHz.

## 5 Transmitter characteristics for 8 Watt mobiles

### 5.0 General provisions

Throughout this clause, unless otherwise stated, requirements are given in terms of power levels at the antenna connector of the equipment. For equipment with integral antenna only, a reference antenna with 0 dBi gain shall be assumed.

For GMSK modulation, the term output power refers to the measure of the power when averaged over the useful part of the burst.

For 8-PSK modulation, the term output power refers to a measure that, with sufficient accuracy, is equivalent to the long term average of the power when taken over the useful part of the burst for random data.

The term peak hold refers to a measurement where the maximum is taken over a sufficient time that the level would not significantly increase if the holding time were longer.

Unless otherwise specified, the common rules of ETSI TS 100 607-1 [2] shall be applied.

### 5.1 Output power

#### 5.1.1 Mobile Station

The MS maximum output power and lowest power control level shall be, according to its class (as specified in ETSI EN 300 919 [1]), as defined in tables 1 and 2.

For GMSK modulation:

**Table 1**

Power class	ER-GSM/R-GSM Nominal Maximum output	Tolerance (dB) for conditions	
	Power	Normal	Extreme
2	8 W (39 dBm)	±2	±2,5

For 8-PSK modulation (optional):

**Table 2**

Power class	ER-GSM/R-GSM Nominal Maximum output	ER-GSM/R-GSM Tolerance (dB) for conditions	
	Power	Normal	Extreme
E1	33 dBm	±2	±2,5

Maximum output power for 8-PSK in any one band is always equal to or less than GMSK maximum output power for the same equipment in the same band.

The different power control levels as defined in ETSI TS 100 911 [7] needed for adaptive power control shall have the nominal output power as defined in table 3, starting from the power control level for the lowest nominal output power up to the power control level for the maximum nominal output power corresponding to the class of the particular MS as defined in tables 1 and 2. Whenever a power control level commands the MS to use a nominal output power equal to or greater than the maximum nominal output power for the power class of the MS, the nominal output power transmitted shall be the maximum nominal output power for the MS class, and the tolerance specified for that class (see tables 1 and 2) shall apply.

Table 3

ER-GSM/R-GSM			
Power control level	Nominal Output power (dBm)	Tolerance (dB) for conditions	
		Normal	Extreme
0 to 2	39	±2	±2,5
3	37	±3	±4
4	35	±3	±4
5	33	±3	±4
6	31	±3	±4
7	29	±3	±4
8	27	±3	±4
9	25	±3	±4
10	23	±3	±4
11	21	±3	±4
12	19	±3	±4
13	17	±3	±4
14	15	±3	±4
15	13	±3	±4
16	11	±5	±6
17	9	±5	±6
18	7	±5	±6
19 to 31	5	±5	±6

Furthermore, the difference in output power actually transmitted by the MS between two power control levels where the difference in nominal output power indicates an increase of 2 dB (taking into account the restrictions due to power class), shall be  $+2 \pm 1,5$  dB. Similarly, if the difference in output power actually transmitted by the MS between two power control levels where the difference in nominal output power indicates an decrease of 2 dB (taking into account the restrictions due to power class), shall be  $-2 \pm 1,5$  dB.

NOTE: A 2 dB nominal difference in output power can exist for non-adjacent power control levels e.g. power control levels 18 and 22.

A change from any power control level to any power control level may be required by the base transmitter. The maximum time to execute this change is specified in ETSI TS 100 911 [7].

In order to manage mobile terminal heat dissipation resulting from transmission on multiple uplink timeslots, the mobile station shall reduce its maximum output power by the following values on a per-assignment basis.

Table 4

Number of timeslots in uplink assignment	Permissible nominal reduction of maximum output power, (dB)
1	0
2	0 to 3,0
3	1,8 to 4,8
4	3,0 to 6,0

The supported maximum output power for each number of uplink timeslots shall form a monotonic sequence. The maximum reduction of maximum output power from an allocation of n uplink timeslots to an allocation of n+1 uplink timeslots shall be equal to the difference of maximum permissible nominal reduction of maximum output power for the corresponding number of timeslots, as defined in table 4.

As an exception, in case of a multislot uplink assignment, the first power control step down from the maximum output power is allowed to be in the range 0 dB to 2 dB.

In case the MS transmits on more uplink slots than assigned (e.g. due to a polling response) MS may reduce uplink power as above for a multislot uplink configuration but as a function of the number of active uplink slots on a TDMA frame basis as specified in ETSI TS 101 349 [8].

## 6 Transmitter characteristics for 2 Watt mobiles

### 6.0 General provisions

Throughout this clause, unless otherwise stated, requirements are given in terms of power levels at the antenna connector of the equipment. For equipment with integral antenna only, a reference antenna with 0 dBi gain shall be assumed.

For GMSK modulation, the term output power refers to the measure of the power when averaged over the useful part of the burst.

For 8-PSK modulation, the term output power refers to a measure that, with sufficient accuracy, is equivalent to the long term average of the power when taken over the useful part of the burst for random data.

The term peak hold refers to a measurement where the maximum is taken over a sufficient time that the level would not significantly increase if the holding time were longer.

Unless otherwise specified, the common rules of ETSI TS 100 607-1 [2] shall be applied.

### 6.1 Output power

#### 6.1.1 Mobile Station

The MS maximum output power and lowest power control level shall be, according to its class (as specified in ETSI EN 300 919 [1]), as defined in tables 5 and 6.

For GMSK modulation:

**Table 5**

Power class	ER-GSM/R-GSM Nominal Maximum output	Tolerance (dB) for conditions	
	Power	Normal	Extreme
4	2 W (33 dBm)	±2	±2,5

For 8-PSK modulation (optional):

**Table 6**

Power class	ER-GSM/R-GSM Nominal Maximum output	ER-GSM/R-GSM Tolerance (dB) for conditions	
	Power	Normal	Extreme
E2	27 dBm	±3	±4

Due to the 8-PSK modulation scheme and its resulting high peak-to-average ratio the maximum output power for the 8-PSK in any one band shall be always less than the GMSK maximum output power for the same equipment in the same band.

The different power control levels as defined in ETSI TS 100 911 [7] needed for adaptive power control shall have the nominal output power as defined in table 7, starting from the power control level for the lowest nominal output power up to the power control level for the maximum nominal output power corresponding to the class of the particular MS as defined in tables 5 and 6. Whenever a power control level commands the MS to use a nominal output power equal to or greater than the maximum nominal output power for the power class of the MS, the nominal output power transmitted shall be the maximum nominal output power for the MS class, and the tolerance specified for that class (see tables 5 and 6) shall apply.

Table 7

ER-GSM/R-GSM			
Power control level	Nominal Output power (dBm)	Tolerance (dB) for conditions	
		Normal	Extreme
0 to 5	33	±2	±2,5
6	31	±3	±4
7	29	±3	±4
8	27	±3	±4
9	25	±3	±4
10	23	±3	±4
11	21	±3	±4
12	19	±3	±4
13	17	±3	±4
14	15	±3	±4
15	13	±3	±4
16	11	±5	±6
17	9	±5	±6
18	7	±5	±6
19 to 31	5	±5	±6

Furthermore, the difference in output power actually transmitted by the MS between two power control levels where the difference in nominal output power indicates an increase of 2 dB (taking into account the restrictions due to power class), shall be  $+2 \pm 1,5$  dB. Similarly, if the difference in output power actually transmitted by the MS between two power control levels where the difference in nominal output power indicates an decrease of 2 dB (taking into account the restrictions due to power class), shall be  $-2 \pm 1,5$  dB.

NOTE: A 2 dB nominal difference in output power can exist for non-adjacent power control levels e.g. power control levels 18 and 22.

A change from any power control level to any power control level may be required by the base transmitter. The maximum time to execute this change is specified in ETSI TS 100 911 [7].

In order to manage mobile terminal heat dissipation resulting from transmission on multiple uplink timeslots, the mobile station shall reduce its maximum output power by the following values on a per-assignment basis.

Table 8

Number of timeslots in uplink assignment	Permissible nominal reduction of maximum output power, (dB)
1	0
2	0 to 3,0
3	1,8 to 4,8
4	3,0 to 6,0

The supported maximum output power for each number of uplink timeslots shall form a monotonic sequence. The maximum reduction of maximum output power from an allocation of n uplink timeslots to an allocation of n+1 uplink timeslots shall be equal to the difference of maximum permissible nominal reduction of maximum output power for the corresponding number of timeslots, as defined in table 8.

As an exception, in case of a multislot uplink assignment, the first power control step down from the maximum output power is allowed to be in the range 0 dB to 2 dB.

In case the MS transmits on more uplink slots than assigned (e.g. due to a polling response), the MS may reduce uplink power as above for a multislot uplink configuration but as a function of the number of active uplink slots on a TDMA frame basis as specified in ETSI TS 101 349 [8].

## 7 Receiver characteristics for 8 Watt mobiles

### 7.0 General provisions

In this clause, the requirements are given in terms of power levels at the antenna connector of the receiver assuming a 0 dBi gain antenna.

The following requirements are only applicable for ARFCN located within the R-GSM/ER-GSM band, i.e.: 955 to 973 for R-GSM MS and 940 to 973 for ER-GSM MS.

NOTE: Non static wanted signals and interfering signals in reality (e.g. non static, amplitude modulated, broadband signals) could be worse for the receiver performance than the required continuous wave signal. In order to be comparable to existing standards the continuous wave sine signal is used.

### 7.1 Blocking characteristics

#### 7.1.0 Blocking characteristics of the receiver

The blocking characteristics of the receiver are specified separately for in-band and out-of-band performance as identified in tables 9 and 10.

**Table 9**

Frequency band	Frequency range (MHz) ER-GSM/R-GSM professional MS
in-band	915 to 925,6
out-of-band (a)	0,1 to < 915
out-of-band (b)	925,6 to < 927
out-of-band (c)	927 to 960
out-of-band (d)	> 960 to 12 750

#### 7.1.1 Blocking with CW interfering signals

The reference sensitivity performance as specified in ETSI TS 100 910 [4], tables 1, 1a, 1b, 1c, 1d and 1e shall be met when the following signals are simultaneously input to the receiver:

- for all cases a useful signal, modulated with the relevant supported modulation (GMSK or 8-PSK), at frequency  $f_0$ , at a level of -101 dBm;
- a continuous, static sine wave signal at a level as in table 10 and at a frequency (f) which is an integer multiple of 200 kHz.

With the following exceptions, called spurious response frequencies:

- in-band, for a maximum of six occurrences (which if grouped shall not exceed three contiguous occurrences per group);
- out-of-band, for a maximum of 24 occurrences (which if below  $f_0$  and grouped shall not exceed three contiguous occurrences per group).

For spurious responses, the performance shall be met when the continuous sine wave signal (f) is set to a level of -40 dBm.

For the out of band emissions of the interfering signal, the maximum noise level shall not exceed -113 dBm/200 kHz on the wanted ARFCN and its (bi)adjacent channels.

Table 10

Frequency band	ER-GSM 900/R-GSM 900 professional MS (dBm)
in-band	
600 kHz $\leq  f-f_0  < 800$ kHz	-38
800 kHz $\leq  f-f_0  < 1,6$ MHz	-33
1,6 MHz $\leq  f-f_0  < 5$ MHz	-23
5 MHz $\leq  f-f_0 $	-23
out-of-band	
(a)	0
(b)	-13
(c)	-10
(d)	0

The following exceptions to the level of the sine wave signal (f) in table 10 shall apply:

For professional MS R-GSM 900 and ER-GSM 900: in the band 880 MHz to 912 MHz	-5 dBm
in the band 912 MHz to 915 MHz	-12 dBm

## 7.1.2 Blocking with broadband interfering signals

The receiver performance as specified in ETSI TS 100 910 [4], tables 1, 1a, 1b, 1c, 1d and 1e shall be maintained in presence of the following interferers at the receiver antenna port.

Table 11

Wanted GSMR Signal Level on ARFCN 970 (dBm)	Interferer(s) Characteristics			Comment
	ARFCN	Freq. (MHz)	Mobile Input Level (dBm/200 kHz)	
-101	3476	927,6	-13	LTE single interferer
	3476 & 3526	927,6 & 932,6	-13	LTE dual interferers

LTE interferer: as defined in clause 6.1.1.1: TM1.1 BW 5 MHz of ETSI TS 136 141 [10].

For the out of band emissions of the interfering signal, the maximum noise level shall not exceed -113 dBm/200 kHz on the wanted ARFCN and its (bi)adjacent channels.

# 8 Receiver characteristics for 2 Watt mobiles

## 8.0 General provisions

In this clause, the requirements are given in terms of power levels at the antenna connector of the receiver assuming a 0 dBi gain antenna.

The following requirements are only applicable for ARFCN located within the R-GSM/ER-GSM band, i.e.: 955 to 973 for R-GSM MS and 940 to 973 for ER-GSM MS.

NOTE: Non static wanted signals and interfering signals in reality (e.g. non static, amplitude modulated, broadband signals) could be worse for the receiver performance than the required continuous wave signal. In order to be comparable to existing standards the continuous wave sine signal is used.

## 8.1 Blocking characteristics

### 8.1.0 Blocking characteristics of the receiver

The blocking characteristics of the receiver are specified separately for in-band and out-of-band performance as identified in tables 12 and 13.

**Table 12**

Frequency band	Frequency range (MHz) ER-GSM/R-GSM professional MS
in-band	915 to 925,6
out-of-band (a)	0,1 to < 915
out-of-band (b)	925,6 to < 927
out-of-band (c)	927 to 960
out-of-band (d)	> 960 to 12 750

### 8.1.1 Blocking with CW interfering signals

The reference sensitivity performance as specified in ETSI TS 100 910 [4], tables 1, 1a, 1b, 1c, 1d and 1e shall be met when the following signals are simultaneously input to the receiver:

- for all cases a useful signal, modulated with the relevant supported modulation (GMSK or 8-PSK), at frequency  $f_0$ , at a level of -101 dBm;
- a continuous, static sine wave signal at a level as in table 13 and at a frequency (f) which is an integer multiple of 200 kHz.

With the following exceptions, called spurious response frequencies:

- in-band, for a maximum of six occurrences (which if grouped shall not exceed three contiguous occurrences per group);
- out-of-band, for a maximum of 24 occurrences (which if below  $f_0$  and grouped shall not exceed three contiguous occurrences per group).

For spurious responses, the performance shall be met when the continuous sine wave signal (f) is set to a level of -40 dBm.

For the out of band emissions of the interfering signal, the maximum noise level shall not exceed -113 dBm/200 kHz on the wanted ARFCN and its (bi)adjacent channels.

**Table 13**

Frequency band	ER-GSM 900/R-GSM 900 professional MS (dBm)
in-band	
600 kHz $\leq  f-f_0  < 800$ kHz	-38
800 kHz $\leq  f-f_0  < 1,6$ MHz	-33
1,6 MHz $\leq  f-f_0  < 5$ MHz	-23
5 MHz $\leq  f-f_0 $	-23
out-of-band	
(a)	0
(b)	-24
(c)	-18
(d)	0

The following exceptions to the level of the sine wave signal (f) in table 13 shall apply:

For professional MS R-GSM 900 and ER-GSM 900: in the band 880 MHz to 912 MHz	-5 dBm
in the band 912 MHz to 915 MHz	-12 dBm

## 8.1.2 Blocking with broadband interfering signals

The receiver performance as specified in ETSI TS 100 910 [4], tables 1, 1a, 1b, 1c, 1d and 1e shall be maintained in presence of the following interferers at the receiver antenna port.

**Table 14**

Wanted GSMR Signal Level on ARFCN 970 (dBm)	Interferer(s) Characteristics			Comment
	ARFCN	Freq. (MHz)	Mobile Input Level (dBm/5 MHz)	
Mobile Input Level (dBm/200 kHz)				
-101	3476	927,6	-26	LTE single interferer
	3476 & 3526	927,6 & 932,6	-26	LTE dual interferers

LTE interferer: as defined in clause 6.1.1.1: TM1.1 BW 5 MHz of ETSI TS 136 141 [10].

For the out of band emissions of the interfering signal, the maximum noise level shall not exceed -113 dBm/200 kHz on the wanted ARFCN and its (bi)adjacent channels.

---

## 9 Other requirements

RF characteristics which are not explicitly addressed in the present document shall be taken from ETSI TS 100 910 [4].

In addition, unless otherwise stated, the extended environmental requirements defined in the present document (see annex A) shall apply to specified equipment.

Multi band MSs shall meet all requirements for each of the bands supported.

---

## Annex A (normative): Environmental conditions

### A.1 General

This normative annex specifies the environmental requirements for the professional MS according to the values specified within CENELEC EN 50155 [3], within these limits the requirements of the GSM specifications shall be fulfilled.

---

## A.2 Environmental requirements for the MSs

### A.2.0 General provisions

The requirements in this clause apply to professional MSs.

#### A.2.1 Temperature (R-GSM 900 and ER-GSM 900)

The MS shall fulfil all the requirements in the full temperature range of:

- +15 °C to +35 °C for normal conditions (with relative humidity of 25 % to 75 %);

The extreme condition class T3 of CENELEC EN 50155 [3] shall be applied for 8-Watt. and class T1 column 2 of CENELEC EN 50155 [3] for 2-Watt.

Outside this temperature range the professional MS, if powered on, shall not make ineffective use of the radio frequency spectrum. In no case shall the professional MS exceed the transmitted levels as defined in ETSI TS 100 910 [4] for extreme operation.

#### A.2.2 Vibration (R-GSM 900 and ER-GSM 900)

The MS shall fulfil all the requirements according to EIRENE [6] System Requirement Specification.

Outside the specified frequency range the professional MS, if powered on, shall not make ineffective use of the radio frequency spectrum. In no case shall the MS exceed the transmitted levels as defined in ETSI TS 100 910 [4] for extreme operation.

---

## Annex B (informative): Bibliography

- CENELEC EN 50125-1: "Railway applications - Environmental conditions for equipment".
- Recommendation ITU-T O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".

---

## History

<b>Document history</b>		
V1.1.1	December 2010	Publication
V1.2.1	December 2011	Publication
V1.3.1	June 2014	Publication
V2.1.1	June 2015	Publication