

ETSI TS 122 282 V14.3.0 (2017-03)



**LTE;
Mission Critical Data over LTE
(3GPP TS 22.282 version 14.3.0 Release 14)**



ReferenceDTS/TSGS-0122282ve30

KeywordsLTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope	6
2 References	6
3 Definitions, symbols and abbreviations	6
3.1 Definitions	6
3.2 Abbreviations	7
4 Overview	7
5 MCDData generic capability requirements common for on-network and off-network	7
5.1 Introduction	7
5.2 SDS feature	7
5.2.1 General.....	7
5.2.2 Requirements	8
5.2.3 Remote Start Requirements Using SDS.....	8
5.3 File distribution capability.....	9
5.3.1 General.....	9
5.3.2 Requirements	9
5.4 Data streaming capability	9
5.4.1 General.....	9
5.4.2 Requirements	9
5.5 IP connectivity.....	10
5.5.1 Service description.....	10
5.5.2 Requirements	10
6 MCDData specific requirements	10
6.1 MCDData Services common for on network and off network.....	10
6.1.1 Conversation management including delivery notification	10
6.1.1.1 Service description	10
6.1.1.2 Service requirements.....	11
6.1.2 Robots.....	11
6.1.2.1 Robots remote control	11
6.1.2.1.1 Service description	11
6.1.2.1.2 Requirements	11
6.1.2.2 Robot identification.....	12
6.1.2.2.1 Service description	12
6.1.2.2.2 Requirements	12
6.1.3 MCDData enhanced status	12
6.1.3.1 Service description	12
6.1.3.2 Requirements	13
6.2 MCDData Services requirements specific to on-network use	13
6.2.1 Database enquiries and secured internet access	13
6.2.1.1 Service description	13
6.2.1.2 Requirements	13
6.2.2 Transmission control requirements.....	13
6.2.2.1 General	13
6.2.2.2 Receiving data.....	14
6.2.2.3 Accessing data.....	14
6.2.2.4 Data reconfiguration and termination.....	14
6.2.3 Communication termination	14
6.3 MCDData Services requirements specific to off-network use	15
6.3.1 Private Communication Off-Network.....	15

6.3.1.1	Overview	15
6.3.1.2	Requirements	15
6.3.2	MCDATA Transmission Control Off-Network	16
6.3.2.1	Overview	16
6.3.2.2	General Aspects	16
6.3.2.3	Requesting Permission to Transmit.....	16
6.3.2.4	Override	16
6.3.2.5	Terminating Permission to Transmit.....	17
6.3.2.6	Transmit Time Limit	17
7	Interworking	17
7.1	Interworking with non LTE data systems.....	17
Annex A (informative):	Change history	18
History		19

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document provides the service requirements for operation of the MCDATA service. MCDATA makes use of capabilities included in Group Communication System Enablers for LTE (GCSE_LTE), Proximity Services (ProSe), Isolated E-UTRAN operation for Public Safety (IOPS) and Mission Critical Services Common Requirements (MCCoRe) with additional requirements specific to the MCDATA Service. The MCDATA Service can be used for public safety applications and also for general commercial applications (e.g., utility companies and railways).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TR 41.001: "GSM Specification set".
- [3] 3GPP TS 22.280: "Mission Critical Services Common Requirements".
- [4] 3GPP TS 22.179: "Mission Critical Push to Talk (MCPTT) over LTE; Stage 1".
- [5] ETSI TS 100 392-2 v.3.7.1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [6] 3GPP TS 22.281: "Mission Critical Video services over LTE".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

Conversation: A series of messages that are linked to the same topic within a group or one-to-one data communication.

Conversation ID: An identifier that uniquely identifies a conversation within a group or one-to-one data communication.

MCDATA Conversation Hang Time: The time from the transmission of an MCDATA message after which a subsequent MCDATA message is no longer considered to be linked to the previous one.

MCDATA System: The collection of applications, services, and enabling capabilities required to provide Mission Critical Data for a Mission Critical Organization.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

IOPS	Isolated E-UTRAN Operation for Public Safety
SDS	Short Data Service

4 Overview

MCDData defines a service for Mission Critical Data services. As well as voice services, current mission critical users have been increasing their use of data services, including low throughput services on legacy networks and data services on commercial networks. This need will continue to grow with the creation of the new multimedia services. The MCDData service needs to provide a means to manage all data connections of mission critical users in the field and provide relevant resources to the ones who need it. For example mission critical users already use event manager software along with the voice system. The migration to LTE networks will allow mission critical users to operate current and new data services whilst relying on the fundamental capabilities of mission critical communication such as defined for MCPTT in [4] and included into MCCoRe [3].

The MCDData Service provides a set of communication services that will be directly used by the user or functions that will be called by external applications in control rooms.

The MCDData Service will reuse functions including end-to-end encryption, key management, authentication of the sender, etc. defined in [3] in order to provide group communications for data services. As for all mission critical services, users affiliate to groups in order to receive communications directed to the group.

In addition, the MCDData Service will provide a set of generic capabilities such as: messaging, file distribution, data streaming, IP proxy, etc. Also, the MCDData Service will provide specific services such as conversation management, data base enquiries, internet access, robots control.

The MCDData Service is expected to have open interfaces in the network. It needs also to provide an opportunity for a variety of multimedia applications using the MCDData Service.

5 MCDData generic capability requirements common for on-network and off-network

5.1 Introduction

MCDData makes frequent use of a set of capabilities and enablers that allows for many end user services to be built on a common foundation. Several generic capabilities are defined for use in the MCDData Service. These capabilities can be used on their own to transfer files, messages and other content to individuals and affiliated members of groups or combined with other services, through an application, to provide complete end users services as determined by the authorities implementing the service. The MCDData generic capabilities are common for on-network and off-network.

It is not intended to invent new protocols for the MCDData Service. Where existing protocols are efficient and sufficient, the service should make use of these protocols.

5.2 SDS feature

5.2.1 General

The SDS feature of the MCDData Service could be considered as a basic protocol carrying a limited size, but variable content, payload message. This message could be text or could be marked for extensible purposes including short binary

messages for application communication. Messaging could be one-to-one messaging or could be group messaging using groups as specified in MCCoRe.

5.2.2 Requirements

[R-5.2.2-001] The MCDData Service shall provide an SDS feature for conveyance of limited size, variable content, messages.

[R-5.2.2-002] The MCDData SDS shall provide a group service to affiliated members with policy assertion capabilities (e.g. certain types of message or content may only be relevant to certain members of a group due, for example, to location).

[R-5.2.2-003] The MCDData SDS shall provide a one to one service with policy assertion capabilities (e.g. policy to limit certain types of message or content to certain users due, for example, to location or user privilege).

[R-5.2.2-004] The MCDData SDS shall provide the option to include a content payload of at least [1000] characters of 8 bit text or [500] characters of 16 bit text or [250] characters of 32 bit text and the necessary character encoding information (for example to identify alphabet used).

[R-5.2.2-005] The MCDData SDS shall provide the option to include a content payload of at least [1000] characters of hyperlink or interleaved text and hyperlink(s) to allow subsequent access to linked content (which may be a large file).

[R-5.2.2-006] The MCDData SDS shall provide the option to include a content payload of at least [1000] bytes of binary data to be used by a local running application and the necessary addressing detail to identify the intended application.

[R-5.2.2-007] The MCDData SDS shall provide a message thread indication so that multiple message flows can be managed independently.

[R-5.2.2-008] When replying to a message on the MCDData SDS or sending any message which should be coupled with previously sent or received messages or message flows; the message thread indication shall use the same indication as was used for those previous messages.

[R-5.2.2-009] The MCDData SDS shall provide a selectable read receipt indication. When requested, the receiving entity shall provide receipt indication for delivered and read messages as appropriate.

NOTE 1: The read indication will implicitly indicate delivered as well.

[R-5.2.2-010] The MCDData SDS shall provide a configurable read receipt indication. When configured, the receiving entity shall provide receipt indication addressed to the application for delivered and read messages as appropriate.

NOTE 2: The read indication will implicitly indicate delivered as well.

[R-5.2.2-011] The MCDData SDS shall permit delivery history interrogation for suitably authorized users.

[R-5.2.2-012] The MCDData SDS shall provide the option to add a field indicating location of the sending user/UE.

[R-5.2.2-013] The MCDData SDS shall allow empty messages including only a field indicating location of the sending user/UE.

5.2.3 Remote Start Requirements Using SDS

[R-5.2.3-001] SDS content received in a UE, addressed to a known local application that is not yet running shall cause the UE to start the local application and pass the content to the application. This could be used to start an application and pass to it the initial data.

[R-5.2.3-002] The MCDData SDS shall provide the capability to remotely start a local application (e.g. situational awareness). This may be through specific use of binary payload on the SDS.

5.3 File distribution capability

5.3.1 General

File distribution is a fundamental capability of the MCDData Service. File distribution can be used to provide a standalone file transfer capability or can be invoked by a controlling application to support the purpose of the application.

5.3.2 Requirements

[R-5.3.2-001] The MCDData Service shall provide a file distribution capability.

[R-5.3.2-002] The MCDData file distribution capability shall provide a service to allow a user to send a file to any combination of individual users and/or affiliated groups.

[R-5.3.2-003] The MCDData file distribution capability shall provide an option for each recipient to choose to receive the file or not (e.g. by storing the file and sending a link (URL) to all relevant members).

NOTE 1: By using this capability a user can choose when to receive the file.

[R-5.3.2-004] The MCDData file distribution capability shall allow a user to reject to receive the file where appropriate.

[R-5.3.2-005] The MCDData file distribution capability shall provide a sending user selectable indication for mandatory download so that the UE, for all relevant receiving members, will automatically download the file.

NOTE 2: The mandatory indication provides a system level capability and could be invoked automatically by need of the application or might be provided for selection by the user.

[R-5.3.2-006] The MCDData file distribution capability shall provide download complete indications for each recipient successfully downloading the file.

[R-5.3.2-007] The MCDData file distribution capability shall allow the sender to select to send the file immediately to all chosen users.

[R-5.3.2-008] The MCDData file distribution capability shall make use of available system delivery efficiencies for distribution of common information to users within a specific geographic area and able to receive at the same time.

[R-5.3.2-009] The MCDData file distribution capability shall allow a user to cancel distribution of files they have sent, but have not been delivered.

[R-5.3.2-010] The MCDData file distribution capability shall allow an authorised user to cancel distribution of files being sent or waiting to be sent.

5.4 Data streaming capability

5.4.1 General

Data streaming is a fundamental capability of the MCDData Service. Data streaming can be used to provide a standalone data streaming capability or can be invoked by a controlling application to support the purpose of the application.

5.4.2 Requirements

[R-5.4.2-001] The MCDData Service shall provide a data streaming capability.

[R-5.4.2-002] The MCDData data streaming capability shall provide an option that allows each recipient to choose to receive the data stream or not (e.g. by sending a link (URL) to all relevant members).

[R-5.4.2-003] The MCDData data streaming capability shall allow a user to reject to receive the datastream.

[R-5.4.2-004] The MCDData data streaming capability shall provide a sending user selectable indication for automatic reception by the UE.

[R-5.4.2-005] The MCDData data streaming capability shall provide start and stop records to the sender for each recipient successfully receiving the data stream.

[R-5.4.2-006] The MCDData data streaming capability shall make use of available system delivery efficiencies for streaming of common information to users within the same relevant area and able to receive at the same time.

[R-5.4.2-007] The MCDData data streaming capability shall allow a user to cancel streaming of data they have initiated including data remaining buffered in the system waiting to be streamed.

[R-5.4.2-008] The MCDData data streaming capability shall allow an authorised user to terminate streaming of data being sent and cancel streaming of data remaining buffered in the system waiting to be streamed.

5.5 IP connectivity

5.5.1 Service description

IP connectivity can be used for MCDData applications that are based on the IP client-server paradigm. The UE can contain a client using a service in the network (e.g. a police officer accessing a server on the police Intranet from his mobile phone). The UE can also contain a server that is accessed by other UEs (e.g. a mobile information display that is controlled by a police officer from his mobile phone). As an UE for MCDData application can be an unmanned device, or device without user interface, authorization of IP data transport can be provided remotely by an authorized user for the UE.

5.5.2 Requirements

[R-5.5.2-001] The MCDData Service shall enable a UE to initiate transport of IP data towards a server in the network or another UE.

[R-5.5.2-002] The MCDData Service shall enable incoming transport of IP data towards a UE, initiated by another UE.

[R-5.5.2-003] The MCDData Service shall enable an authorized person for an UE to authorize initiation of transport of IP data from that UE to specific destinations. This authorization may be preconfigured or may be provided by the authorized person when IP data transport to a new destination is initiated. Authorization may be revoked on demand by the authorized person.

[R-5.5.2-004] The MCDData Service shall enable a UE or authorized person for this UE to authorize initiation of incoming transport of IP data from specific other UEs. This authorization may be preconfigured, or may be provided by the authorized person when IP data transport from a new destination is initiated. Authorization may be revoked on demand by the authorized person.

[R-5.5.2-005] The MCDData Service shall support incoming and outgoing IP data transport for a UE with a higher per packet priority (e.g. QCI=6).

[R-5.5.2-006] The MCDData Service shall enable an authorized person to remotely authorize the use of higher per packet priority for a particular UE.

6 MCDData specific requirements

6.1 MCDData Services common for on network and off network

6.1.1 Conversation management including delivery notification

6.1.1.1 Service description

A group of people can be involved in different activities in an operational situation. As a consequence, there is a need to manage different activities and to easily retrieve data exchanged around one activity. Conversation management can be seen as an aggregation of related MCDData transmissions for a given activity.

The system will not be able to manage an infinite number of conversations. Rather than simply limiting the number of conversations and asking users to send a notification when the conversation ends, it is proposed here to limit the time of a conversation.

6.1.1.2 Service requirements

[R-6.1.1.2-001] The MCDData Service shall provide a conversation management feature for each MCDData User.

[R-6.1.1.2-002] The MCDData conversation management service shall be available for group communication as well as for one-to-one communications.

[R-6.1.1.2-003] The MCDData Service conversation management feature shall use the SDS and file distribution generic capabilities.

NOTE: For instance, if SDS and file distribution capability are combined for a conversation, the two thread indications are assumed to appear in the conversation as unique.

[R-6.1.1.2-004] A conversation shall be identified through a unique conversation ID.

[R-6.1.1.2-005] The MCDData Service conversation management feature shall provide an MCDData Conversation Hang Time after which the last message/file shall no longer be correlated to the previous.

[R-6.1.1.2-006] The MCDData Conversation Hang Time shall be available to the user.

[R-6.1.1.2-007] The MCDData Conversation Hang Time shall be configurable for each MCDData User and each MCDData Group.

[R-6.1.1.2-008] The MCDData Service conversation management feature shall allow multiple parallel conversations for the same group or the same pair of users.

[R-6.1.1.2-009] The MCDData Service shall provide a mechanism to send a “message delivered” and/or “message read” notification to the message sender and to one or more authorized MCDData users for each message of a conversation.

[R-6.1.1.2-010] The MCDData Service shall make use of SDS and file distribution capability to provide relevant access to delivery history and delivery efficiencies.

6.1.2 Robots

6.1.2.1 Robots remote control

6.1.2.1.1 Service description

Robots as defined in 3GPP TS 22.281 [6] will be used more and more to provide unique services to mission critical organizations. Critical communications users need, as a consequence, a common communication framework for robots which can take advantage of different transport technologies such as LTE. The MCDData Service, working in conjunction with existing robot control capabilities, will provide mechanisms to do that.

The following sub-clause aims at defining requirements to ensure robot control communication can be provided through LTE.

We expect different manufacturers for robots. As a consequence a well-known transport framework is needed in order to ensure easy integration of new robots.

6.1.2.1.2 Requirements

[R-6.1.2.1.2-001] The MCDData Service shall enable the control of robots.

[R-6.1.2.1.2-002] The MCDData Service shall provide a common transmission framework to use and control robots.

[R-6.1.2.1.2-003] The MCDData Service shall provide a default control latency depending on the robots type under

- 50 ms for an aerial unmanned vehicle;

- 200 ms for an aquatic or submarine unmanned vehicle; and
- 400 ms for a terrestrial unmanned vehicle .

NOTE: At this stage of the work, the latency is an end to end latency. The split between network latency and robot latency is left for stage 2. The latency is measured between the action of the pilot and the movement of the robot (not only MCDData Service).

[R-6.1.2.1.2-004] The MCDData Service shall be able to simultaneously manage multiple robots and robot types.

[R-6.1.2.1.2-005] Void.

[R-6.1.2.1.2-006] The MCDData Service shall support management of an aerial unmanned vehicle at an altitude of up to 150 m above the floor.

[R-6.1.2.1.2-007] The MCDData Service shall have a default priority scheme for each kind of robot (aerial, aquatic, submarine or terrestrial unmanned vehicles).

[R-6.1.2.1.2-008] The MCDData Service shall be able to provide relevant priorities to different MCDData communications according to the default priority scheme without additional configuration.

[R-6.1.2.1.2-009] The MCDData Service default priority scheme shall ensure that data exchanged for controlling a robot has relevant high priority amongst user data and cannot be pre-empted.

[R-6.1.2.1.2-010] The MCDData Service default priority scheme shall ensure that essential robots telemetry data (such as position when out of sight) has also a high priority and cannot be pre-empted.

[R-6.1.2.1.2-011] The essential telemetry data shall be identified and minimized in order not to forbid critical operational data to be transmitted.

6.1.2.2 Robot identification

6.1.2.2.1 Service description

Robots as defined in [6] (e.g., aerial, aquatic, submarine and terrestrial unmanned vehicles) will need to be identified across the organization in order to share who is doing what.

There will also be a need to exchange information specific to different robots.

6.1.2.2.2 Requirements

[R-6.1.2.2.2-001] The MCDData Service shall provide a means to identify robots used by a Mission Critical Organization.

[R-6.1.2.2.2-002] The MCDData Service shall provide a mechanism for an authorized user to get identifying information for one or more robots associated with all MCDData UEs that are under the coverage of the MCDData System. Location information may be also sent with identifying data.

[R-6.1.2.2.2-003] The MCDData Service shall provide to an MCDData authorized User a means to get the location of each robot associated with any MCDData UE under the coverage of the MCDData System.

[R-6.1.2.2.2-004] The MCDData Service shall be able to provide characteristics (free formatted information transported by 3GPP) of an MCDData UE associated with a given robot to the authorized user.

6.1.3 MCDData enhanced status

6.1.3.1 Service description

Mission Critical Service users need to share status information specific to their activities. For instance status can be: available, in operation on site, going to the operation site, or just arrived. When working in a group, there is a need to constantly share this information.

6.1.3.2 Requirements

[R-6.1.3.2-001] The MCDData Service shall provide a means to share in real-time operational status information between members of a selected group.

[R-6.1.3.2-002] The possible operational status values shall be configurable.

[R-6.1.3.2-003] The minimum number of possible different operational status values shall be 32.

6.2 MCDData Services requirements specific to on-network use

6.2.1 Database enquiries and secured internet access

6.2.1.1 Service description

Mission critical users are already using data applications today for which a priority management will need to be implemented.

6.2.1.2 Requirements

[R-6.2.1.2-001] The MCDData Service shall provide controlled access to external services (e.g. data bases, web sites, event manager software).

[R-6.2.1.2-002] The MCDData Service shall be able to select priorities to data flows for external services (e.g. data bases access, web sites, event manager software).

6.2.2 Transmission control requirements

6.2.2.1 General

[R-6.2.2.1-001] The MCDData Service shall determine which Participant(s) are allowed to transmit data.

[R-6.2.2.1-002a] The MCDData Service shall provide a mechanism so that small data items can be automatically sent to the chosen receiving users (private communication) or to affiliated members of the Selected MCDData group.

[R-6.2.2.1-002b] The MCDData Service shall provide a mechanism so that when an MCDData request to transmit is granted, the data can be automatically sent on to the chosen receiving users (private communication) or to affiliated members of the Selected MCDData group (i.e. without prior acceptance from the receiving user).

[R-6.2.2.1-002c] The MCDData Service shall provide a mechanism so that when an MCDData request to transmit is granted the data can be temporarily stored in the system and an invitation to receive is sent to the chosen receiving users (private communication) or to affiliated members of the Selected MCDData group.

NOTE 1: This is for support of sending large data files, allowing the receiving user to choose when to receive.

[R-6.2.2.1-002d] The MCDData Service may provide a configurable default time to live value for data waiting to be delivered to a receiving user.

[R-6.2.2.1-002e] The MCDData Service may terminate all remaining invitations to receive after expiry of the time to live.

[R-6.2.2.1-003] The MCDData Service shall provide a mechanism for the MCDData Administrator to configure the maximum data size for automatic data transmission.

[R-6.2.2.1-004] When an MCDData UE has begun to transmit data or when the data transmission has completed the MCDData Service shall begin to send the data to all affiliated members of the selected group.

NOTE 2: Where the MCDData Service chooses to use eMBMS to broadcast the data to several users, the UE will need to be notified to select the relevant channel before the data is sent.

NOTE 3: The MCDData Service might choose to temporarily store the transmitted data and deliver it independently to receiving users as appropriate.

[R-6.2.2.1-005] The MCDData Service may withhold permission to transmit for service based pre-emptive capacity reasons.

[R-6.2.2.1-006] Following an MCDData Service request for permission to transmit on the Selected MCDData Group, an Affiliated MCDData Group Member that made but was not granted the request shall be given an indication that permission to transmit was not given at that time.

[R-6.2.2.1-007] When a user is not allowed to start a communication the request may be queued or rejected.

6.2.2.2 Receiving data

[R-6.2.2.2-001] An MCDData user shall be able to choose to download data for any recently invited group communications.

NOTE: A list of available data is stored and presented to the user on demand. The term, recent, might be time limited, size of list limited or any other limit.

6.2.2.3 Accessing data

[R-6.2.2.3-001] The MCDData Service shall provide, periodically and on demand, to the MCDData User the list of available recently invited data group communications for which he is affiliated.

[R-6.2.2.3-002] The MCDData user shall be able to affiliate to one or more MCDData Groups subject to MCDData settings and UE capabilities.

6.2.2.4 Data reconfiguration and termination

[R-6.2.2.4-001] The MCDData Service shall make efficient use of resources.

[R-6.2.2.4-002] The MCDData Service shall provide a notification to a transmitting MCDData Group Member if there are no other MCDData Group Members who have affiliated to the MCDData Group.

[R-6.2.2.4-003] Following a notification that there are no other MCDData Group Members affiliated to the MCDData Group and if the transmitting MCDData Group Member does not terminate their request to transmit, the MCDData Service may either (terminate the permission to transmit) or (allow the transmission to continue and store the transmitted data for a time to live time and deliver invitations to receive to subsequent affiliating members).

6.2.3 Communication termination

[R-6.2.3-001] The MCDData Service shall enable an authorized MCDData User to terminate the transmission of a transmitting participant at any time.

[R-6.2.3-002] A transmitting participant shall be able to indicate to the MCDData Service that the participant no longer wants to transmit.

[R-6.2.3-003] If a transmitting participant of an MCDData Service Group Communication is pre-empted, the MCDData Service shall terminate the communication.

[R-6.2.3-004] If MCDData User(s) are pre-empted from an on-going MCDData Service communication as there is insufficient capacity to support their on-going participation, the MCDData Service shall provide the MCDData User(s) with a notification that they have been removed from the communication for reasons of lack of capacity.

[R-6.2.3-005] The MCDData Service shall have a configurable limit for the maximum amount of data or time that a Participant transmits from a single request to transmit.

NOTE 1: Infinite is a valid setting for the transmit data limit.

[R-6.2.3-006] The MCDData Service shall enable an MCDData Administrator to configure the limits for a transmission that a Participant transmits from a single request to transmit.

[R-6.2.3-007] The MCDData Service may provide a notification of intent to terminate a communication e.g. to give the user time to request an extension.

[R-6.2.3-008] The MCDData Service may terminate a communication without previously sending a notification.

[R-6.2.3-009] The MCDData Service may include an indication of termination reason (e.g. data volume limit, administrator action, time limit expiry) with any notification of intent to terminate or actual termination.

[R-6.2.3-010] An MCDData UE shall provide, to the MCDData User, a notification of intent to terminate including any reason given.

[R-6.2.3-010a] An MCDData UE may provide, to the MCDData User, a notification of termination including any reason given.

[R-6.2.3-011] The MCDData Service may include a request for more information with any notification of intent to terminate communication.

NOTE 2: For example to allow the UE to indicate the remaining data volume to send if known.

[R-6.2.3-012] An MCDData UE shall respond to a request for more information.

[R-6.2.3-012a] The response to the request for more information may include an indication of the amount of data still to be transmitted.

[R-6.2.3-013] The MCDData Service shall terminate an MCDData Service Group Communication if any termination condition occurs.

6.3 MCDData Services requirements specific to off-network use

6.3.1 Private Communication Off-Network

6.3.1.1 Overview

Private Communications off-network allows two MCDData Users to communicate directly with each other without the use of the network. Private Communications off-network is generally applicable to all of the MCDData subservices (SDS, file distribution capability, data streaming capability, IP connectivity).

6.3.1.2 Requirements

[R-6.3.1.2-001] The MCDData service shall support Private Communications Off-Network.

[R-6.3.1.2-002] The MCDData service shall provide a mechanism for an MCDData User to cancel an MCDData Private Communication prior to the Communication setup.

[R-6.3.1.2-003] The MCDData service shall provide a means by which an authorized MCDData User initiates an MCDData Private Communication.

[R-6.3.1.2-004] The MCDData service shall provide a means by which an MCDData UE initiates an MCDData Private Communication to any MCDData User for which the MCDData UE's current MCDData User is authorized.

NOTE: For off-network use, only an MCDData UE within communication range (possibly via a ProSe UE-to-UE Relay) receives the transmission.

[R-6.3.1.2-005] The MCDData service shall provide a mechanism for an MCDData User to reject an MCDData Private Communication.

[R-6.3.1.2-006] The MCDData service shall provide a means by which an MCDData User ends a Private Communication in which the MCDData User is a Participant.

[R-6.3.1.2-007] The MCDData service shall provide a mechanism for an MCDData Administrator to configure for a particular authorized MCDData User, a set of MCDData Users under the same authority to which an MCDData Private Communication can be made.

[R-6.3.1.2-008] The MCDData service shall provide a mechanism for an MCDData Administrator to configure the maximum duration for MCDData Private Communications for MCDData Users within their authority.

6.3.2 MCDData Transmission Control Off-Network

6.3.2.1 Overview

MCDData Transmission Control Off-Network provides a necessary capability for an authorized user of the MCDData service to request to transmit, receive an indication of being allowed to transmit or not being allowed to transmit and terminate a request to transmit when the MCDData user no longer wants to transmit. A transmit time limit is provided which allows an MCDData Administrator to configure the limits for any transmission related to a single request to transmit. MCDData Transmission Control Off-Network also provides an override capability based on a priority hierarchy to override an active MCDData transmission of a transmitting Participant based on configuration. The MCDData Transmission Control Off-Network capability does not apply to all of the MCDData subservices (SDS, file distribution capability, data streaming capability, IP connectivity).

6.3.2.2 General Aspects

[R-6.3.2.2-001] The MCDData service when operating off-network shall determine at a point in time which off-network Participant(s) are allowed to transmit to other off-network Participants.

[R-6.3.2.2-002] An MCDData Group shall have the flexibility to be configured to allow simultaneous transmitting MCDData Group Members.

[R-6.3.2.2-003] The MCDData service shall provide a mechanism for the MCDData Service Administrator to configure the maximum number of simultaneous communications received by an off-network MCDData User in a single MCDData Group.

6.3.2.3 Requesting Permission to Transmit

[R-6.3.2.3-001] An authorized Participant shall be able to request to transmit to an MCDData Group or an individual MCDData User.

[R-6.3.2.3-002] The MCDData service shall determine which Participant(s) are permitted to transmit when there are simultaneous requests for permission to transmit within the same group.

[R-6.3.2.3-003] Following an MCDData request for permission to transmit on the Selected MCDData Group, any Affiliated MCDData User that made and was granted the request shall be given an indication of being allowed to transmit.

[R-6.3.2.3-004] Following an MCDData request for permission to transmit on the Selected MCDData Group, any Affiliated MCDData User that made and was not granted the request shall be given an indication that permission to transmit was not given at that time.

[R-6.3.2.3-005] Following an MCDData Private Communication request for permission to transmit, an MCDData User that is allowed to transmit shall be given an indication that the user is allowed to transmit to the targeted MCDData User(s).

[R-6.3.2.3-006] Following an MCDData Private Communication request for permission to transmit, an MCDData User that is not allowed to transmit shall be given an indication that the permission to transmit was queued or rejected.

[R-6.3.2.3-007] The MCDData service when operating off-network shall provide a mechanism for an MCDData Participant to cancel its MCDData request to transmit at any stage, including before the request has been granted.

[R-6.3.2.3-008] The MCDData service shall provide a mechanism for the MCDData Administrator to configure parameter(s) relating to the automatic termination of an off-network MCDData service request to transmit.

6.3.2.4 Override

[R-6.3.2.4-001] An MCDData UE shall be pre-provisioned by an MCDData Administrator and/or authorized user with the necessary information in order that override may operate during off-network MCDData communication.

[R-6.3.2.4-002] The MCDData service shall provide a mechanism for MCDData Administrators to create a priority hierarchy for determining what Participants, Participant types, and urgent transmission types, when operating off the network, be granted a request to override an active off-network MCDData transmission.

[R-6.3.2.4-003] The priority hierarchy used for granting a request to override an active MCDData transmission shall contain at least four (4) levels.

[R-6.3.2.4-004] The MCDData service shall provide a mechanism for Participants, to override an active MCDData transmission of a transmitting Participant based on configuration.

[R-6.3.2.4-005] If an MCDData transmission is overridden, the MCDData Service shall provide a means of notifying the overridden Participant(s) that the transmission has been overridden.

[R-6.3.2.4-006] The MCDData service shall provide a mechanism to enable an MCDData Administrator to configure which MCDData Group transmission(s) a Participant(s) receives, for cases where an MCDData transmission can be overridden.

[R-6.3.2.4-007] If the MCDData Group has been configured to only allow the overriding transmitting Participant to transmit, the MCDData service shall revoke the transmit permission of the overridden transmitting Participant.

6.3.2.5 Terminating Permission to Transmit

[R-6.3.2.5-001] A transmitting Participant shall be able to indicate to the off-network MCDData service that the Participant no longer wants to transmit.

[R-6.3.2.5-002] The off-network MCDData service shall provide an indication to receiving Participants that the transmitting Participant has finished transmitting.

6.3.2.6 Transmit Time Limit

[R-6.3.2.6-001] The Off-Network MCDData Service shall provide a mechanism for an MCDData UE to be pre-provisioned by an MCDData Administrator and/or authorized user with the necessary information in order that a transmit time limit function may operate during off-network MCDData communication.

[R-6.3.2.6-002] The Off-Network MCDData Service shall enable an MCDData Administrator to configure the limits (e.g. elapsed time, quantity of data) for any transmission related to a single request to transmit.

[R-6.3.2.6-003] The Off-Network MCDData Service shall have configurable limits (e.g. elapsed time, quantity of data), including indefinite, for any transmission related to a single request to transmit (e.g. elapsed time, quantity of data).

[R-6.3.2.6-004] The Off-Network MCDData Service shall provide an indication to the transmitting Participant a configurable amount before the transmit limit is reached.

[R-6.3.2.6-005] The Off-Network MCDData Service shall provide an indication to the transmitting Participant that the Participant's transmit limit has been reached.

[R-6.3.2.6-006] The Off-Network MCDData Service shall remove the permission to transmit from the transmitting Participant when the Participant's transmit limit has been reached.

7 Interworking

7.1 Interworking with non LTE data systems

[R-7.1-001] Interworking between the MCDData SDS and TETRA Short Data Service [5] shall be supported.

Editor's Note: interworking with other non-LTE systems is FFS.

Annex A (informative): Change history

Change history											
TSG SA #	SA Doc.	SA1 Doc	Spec	CR	Rev	Rel	Ca t	Subject/Comment	Old	New	WI
SP-73	SP-160545	S1-162015	22.282	0001		Rel-14	F	Remove requirement in MCDData TS 22.282 that has been added to MCCoRe TS 22.280.	14.0.0	14.1.0	MCImp-MCDData
SP-73	SP-160545	S1-162424	22.282	0002	1	Rel-14	D	Editorial changes to several clauses and sub-clauses in MCDData TS 22.282 for consistency and to improve understanding and readability.	14.0.0	14.1.0	MCImp-MCDData
SP-73	SP-160545	S1-162500	22.282	0003	2	Rel-14	B	In MCDData TS 22.282 Add requirements to empty sub-clause 6.3 MCDData Services requirements specific to off-network use.	14.0.0	14.1.0	MCImp-MCDData
SP-73	SP-160545	S1-162426	22.282	0004	1	Rel-14	F	In MCDData TS 22.282 Provide changes to sub-clause 6.1.2 Robots, to improve understanding and readability.	14.0.0	14.1.0	MCImp-MCDData
SP-73	SP-160545	S1-162026	22.282	0005		Rel-14	F	In MCDData TS 22.282 Modify the title of clause 5 MCDData generic capability requirements and add a sentence to the introduction sub-clause 5.1	14.0.0	14.1.0	MCImp-MCDData
SP-73	SP-160545	S1-162496	22.282	0006	2	Rel-14	F	Remove data streaming from MCDData TS 22.282 sub-clause 6.1.1.1 Service description 1st paragraph, 3rd sentence.	14.0.0	14.1.0	MCImp-MCDData
SP-73	SP-160545	S1-162030	22.282	0007		Rel-14	F	In MCDData TS 22.282 change group to users in sub-clause 5.2.2 requirement 3.	14.0.0	14.1.0	MCImp-MCDData
SP-73	SP-160545	S1-162428	22.282	0008	1	Rel-14	F	Change may to shall in MCDData TS 22.282 sub-clause 6.2.3 requirement 10.	14.0.0	14.1.0	MCImp-MCDData
SP-73	SP-160545	S1-162429	22.282	0009	1	Rel-14	F	Corrections to 22.282	14.0.0	14.1.0	MCImp-MCDData
SP-74	SP-160893	S1-163014	22.282	0010		Rel-14	F	Change the numbering for requirement 3 in sub-clause 6.1.2.1.2.	14.1.0	14.2.0	MCImp-MCDData
SP-75	SP-170150	S1-170167	22.282	0011		Rel-14	D	Replace Configuration with Conversation in R-6.1.1.2-006	14.2.0	14.3.0	MCImp-MCDData
SP-75	SP-170150	S1-171026	22.282	0012		Rel-14	F	Correct inconsistent use of the term 'one-to-many'	14.2.0	14.3.0	MCImp-MCDData

History

Document history		
V14.3.0	March 2017	Publication