

ETSI TS 129 345 V13.1.0 (2016-04)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Inter-Proximity-services (Prose) function signalling aspects;
Stage 3
(3GPP TS 29.345 version 13.1.0 Release 13)**



Reference

RTS/TSGC-0429345vd10

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope	8
2 References	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Abbreviations	9
4 General Description.....	10
4.1 Introduction	10
5 Procedures Description.....	10
5.1 introduction	10
5.2 ProSe Service Authorization	10
5.2.1 General.....	10
5.2.2 Detailed behaviour of the ProSe Function in the HPLMN	11
5.2.3 Detailed behaviour of the ProSe Function in the Local PLMN or VPLMN	12
5.3 ProSe Direct Discovery Authorization	12
5.3.1 General.....	12
5.3.2 Detailed behaviour of the HPLMN ProSe Function	13
5.3.3 Detailed behaviour of the ProSe Function in the local PLMN or VPLMN	15
5.4 ProSe Match Report	17
5.4.1 General.....	17
5.4.2 Detailed behaviour of the HPLMN ProSe Function	18
5.4.3 Detailed behaviour of the ProSe Function in the local PLMN	18
5.5 ProSe Match Report info	19
5.5.1 General.....	19
5.5.2 Detailed behaviour of the requesting ProSe Function.....	20
5.5.3 Detailed behaviour of the receiving ProSe Function	20
5.6 ProSe Proximity Request.....	21
5.6.1 General.....	21
5.6.2 Detailed behaviour of the ProSe Function of the requesting UE	22
5.6.3 Detailed behaviour of the ProSe Function of the targeted UE	22
5.7 ProSe Location Update.....	23
5.7.1 General.....	23
5.7.2 Detailed behaviour of the ProSe Function of the requesting UE	24
5.7.3 Detailed behaviour of the ProSe Function of the targeted UE	24
5.8 ProSe Cancellation	24
5.8.1 General.....	24
5.8.2 Detailed behaviour of the ProSe Function of the requesting UE	25
5.8.3 Detailed behaviour of the ProSe Function of the targeted UE	25
5.9 ProSe Proximity Alert	25
5.9.1 General.....	25
5.9.2 Detailed behaviour of the ProSe Function of the targeted UE	26
5.9.3 Detailed behaviour of the ProSe Function of the requesting UE	26
5.10 ProSe Direct Discovery Authorization Update.....	27
5.10.1 General.....	27
5.10.2 Detailed behaviour of the HPLMN ProSe Function	28
5.10.3 Detailed behaviour of the ProSe Function in the local PLMN or VPLMN	28
5.11 ProSe Direct Discovery Authorization Update Result	28
5.11.1 General.....	28
5.11.2 Detailed behaviour of the ProSe Function in the local PLMN	29

5.11.3	Detailed behaviour of the HPLMN ProSe Function	29
6	Protocol Specification and Implementation	30
6.1	Introduction	30
6.1.1	Use of Diameter base protocol.....	30
6.1.2	Securing Diameter Messages	30
6.1.3	Accounting functionality	30
6.1.4	Use of sessions.....	30
6.1.5	Transport protocol	30
6.1.6	Routing considerations	30
6.1.7	Advertising Application Support	31
6.1.8	Diameter Application Identifier.....	31
6.1.9	Use of the Supported-Features AVP	31
6.2	Commands.....	32
6.2.1	Introduction.....	32
6.2.2	Command-Code values	32
6.2.3	ProSe-Authorization-Request (PAR) Command	32
6.2.4	ProSe-Authorization-Answer (PAA) Command.....	33
6.2.5	ProSe-Discovery-Request (PDR) Command	33
6.2.6	ProSe-Discovery-Answer (PDA) Command	34
6.2.7	ProSe-Match-Request (PMR) Command.....	34
6.2.8	ProSe-Match-Answer (PMA) Command.....	35
6.2.9	ProSe-Match-Report-Info-Request (PIR) Command.....	35
6.2.10	ProSe-Match-Report-Info-Answer (PIA) Command	35
6.2.11	ProSe-Proximity-Request (PRR) Command.....	36
6.2.12	ProSe-Proximity-Answer (PRA) Command	36
6.2.13	ProSe-Location-Update-Request (PLR) Command	37
6.2.14	ProSe-Location-Update-Answer (PLA) Command	37
6.2.15	ProSe-Alert-Request (ALR) Command	38
6.2.16	ProSe-Alert-Answer (ALA) Command	38
6.2.17	ProSe-Cancellation-Request (PCR) Command.....	38
6.2.18	ProSe-Cancellation-Answer (PCA) Command.....	39
6.3	Information Elements	39
6.3.1	General.....	39
6.3.2	App-Layer-User-Id	42
6.3.3	Assistance-info	42
6.3.4	Assistance-Info-Validity-Timer	43
6.3.5	Discovery-Type	43
6.3.6	EAP-Master-Session-Key	43
6.3.7	Feature-List-ID AVP	44
6.3.8	Feature-List AVP	44
6.3.9	Filter-Id	44
6.3.10	Location-Estimate.....	44
6.3.11	MAC-Address	44
6.3.12	Match-Report.....	44
6.3.13	MSISDN	45
6.3.14	Operating-Channel	45
6.3.15	P2P-Features	45
6.3.16	ProSe-App-Code.....	45
6.3.17	ProSe-App-Id.....	45
6.3.18	ProSe-App-Mask	45
6.3.19	ProSe-Direct-Allowed	45
6.3.20	ProSe-Discovery-Filter	45
6.3.21	PRR-Flags.....	46
6.3.22	ProSe-Validity-Timer	46
6.3.23	Requesting-EPUIID	46
6.3.24	Supported-Features	46
6.3.25	SSID.....	46
6.3.26	Targeted-EPUIID	46
6.3.27	Time-Window	46
6.3.28	User-Identifier.....	46
6.3.29	Visited-PLMN-Id.....	47

6.3.30	WiFi-P2P-Assistance-Info	47
6.3.31	WLAN-Assistance-Info	47
6.3.32	WLAN-Link-Layer-Id	47
6.3.33	WLAN-Link-Layer-Id-List	47
6.3.34	OC-Supported-Features	48
6.3.35	OC-OLR	48
6.3.36	Validity-Time-Announce	48
6.3.37	Validity-Time-Monitor	48
6.3.38	Validity-Time-Communication	48
6.3.39	ProSe-App-Code-Info	48
6.3.40	MIC	48
6.3.41	UTC-based-Counter	48
6.3.42	Location-Update-Trigger	49
6.3.43	Location-Update-Event-Type	49
6.3.44	Change-Of-Area-Type	49
6.3.45	Location-Update-Event-Trigger	50
6.3.46	Report-Cardinality	50
6.3.47	Minimum-Interval-Time	50
6.3.48	Periodic-Location-Type	50
6.3.49	Location-Report-Interval-Time	50
6.3.50	Total-Number-Of-Reports	51
6.3.51	Authorized-Discovery-Range	51
6.3.52	ProSe-Match-Refresh-Timer	51
6.3.53	Discovery-Auth-Request	51
6.3.54	Discovery-Auth-Response	52
6.3.55	Match-Request	53
6.3.56	Match-Report-Info	53
6.3.57	PMR-Flags	54
6.3.58	ProSe-Application-Metadata	54
6.3.59	Discovery-Entry-ID	54
6.3.60	ProSe-Metadata-Index-Mask	54
6.3.61	App-Identifier	54
6.3.62	OS-ID	54
6.3.63	OS-App-ID	54
6.3.64	Requesting-RPAUID	54
6.3.65	Target-RPAUID	55
6.3.66	Target-PDUID	55
6.3.67	ProSe-Restricted-Code	55
6.3.68	ProSe-Restricted-Code-Suffix-Range	55
6.3.69	Beginning-Suffix	55
6.3.70	Ending-Suffix	55
6.3.71	Match-Timestamp	55
6.3.72	DRMP	55
6.3.73	Banned-RPAUID	56
6.3.74	Banned-PDUID	56
6.3.75	Code-Receiving-Security-Material	56
6.3.76	Code-Sending-Security-Material	56
6.3.77	DUSK	56
6.3.78	DUIK	57
6.3.79	DUCK	57
6.3.80	MIC-Check-Indicator	57
6.3.81	Encrypted-Bitmask	57
6.3.82	ProSe-App-Code-Suffix-Range	57
6.4	Result-Code and Experimental-Result Values	57
6.4.1	General	57
6.4.2	Success	57
6.4.3	Permanent Failures	58
6.4.3.1	DIAMETER_ERROR_USER_UNKNOWN (5001)	58
6.4.3.2	DIAMETER_ERROR_UNAUTHORIZED_SERVICE (5511)	58
6.4.3.3	DIAMETER_ERROR_NO_ASSOCIATED_DISCOVERY_FILTER (5630)	58
6.4.3.4	DIAMETER_ERROR_ANNOUNCING_UNAUTHORIZED_IN_PLMN (5631)	58
6.4.3.5	DIAMETER_ERROR_INVALID_APPLICATION_CODE (5632)	58

6.4.3.6	DIAMETER_ERROR_PROXIMITY_UNAUTHORIZED (5633).....	58
6.4.3.7	DIAMETER_ERROR_PROXIMITY_REJECTED (5634).....	58
6.4.3.8	DIAMETER_ERROR_NO_PROXIMITY_REQUEST (5635).....	58
6.4.3.9	DIAMETER_ERROR_UNAUTHORIZED_SERVICE_IN_THIS_PLMN (5636)	58
6.4.3.10	DIAMETER_ERROR_PROXIMITY_CANCELLED (5637).....	58
6.4.3.11	DIAMETER_ERROR_INVALID_DISCOVERY_TYPE (5641)	59
6.4.3.12	DIAMETER_ERROR_INVALID_TARGET_PDUID (5638)	59
6.4.3.13	DIAMETER_ERROR_INVALID_TARGET_RPAUID (5639)	59
6.4.3.14	DIAMETER_ERROR_NO_ASSOCIATED_RESTRICTED_CODE (5640).....	59
6.4.3.15	DIAMETER_ERROR_REVOCATION_FAILURE (56x1).....	59
6.4.3.16	DIAMETER_ERROR_ALREADY_BANNED (56x2).....	59
6.4.4	Transient Failures	59
Annex A (normative):	Diameter overload control mechanism	60
A.1	General	60
A.2	Responding ProSe Function behaviour	60
A.3	Requesting ProSe Function behaviour	60
Annex B (Informative):	Diameter overload node behaviour	61
B.1	Message prioritization	61
Annex C (normative):	Diameter message priority mechanism.....	62
C.1	General	62
C.2	PC6/PC7 interfaces.....	62
C.2.1	General.....	62
C.2.2	ProSe Function behaviour.....	62
Annex D (informative):	Change history	63
History		65

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document describes the Diameter-based interfaces between the Proximity Services (ProSe) Function in the HPLMN and the ProSe Function in a local PLMN (PC6 interface) or between the Proximity Services (ProSe) Function in the HPLMN and the ProSe Function in a visited PLMN (PC7 interface).

This specification defines the Diameter application for PC6/PC7 reference points between the ProSe Functions. The interactions between the ProSe Functions are specified.

The stage 2 description for Proximity Services (ProSe) features in EPS is specified in 3GPP TS 23.303 [2].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23 303: "Proximity-based services (ProSe); Stage 2".
- [3] 3GPP TS 29 228: "IP Multimedia (IM) Subsystem Cx and Dx Interfaces; Signalling flows and message contents".
- [4] 3GPP TS 23.003: "Numbering, addressing and identification".
- [5] 3GPP TS 29.329: "Sh interface based on the Diameter protocol; Protocol details".
- [6] 3GPP TS 23.032: "Universal Geographical Area Description (GAD)".
- [7] IETF RFC 3588: "Diameter Base Protocol".
- [8] 3GPP TS 33.210: "3G security; Network Domain Security (NDS); IP network layer security".
- [9] IETF RFC 4960: "Stream Control Transport Protocol".
- [10] 3GPP TS 29.229: "Cx and Dx interfaces based on the Diameter protocol; protocol details".
- [11] IETF RFC 5234: "Augmented BNF for Syntax Specifications: ABNF".
- [12] IETF RFC 4072: "Diameter Extensible Authentication Protocol (EAP) Application".
- [13] 3GPP TS 32.299: "Charging management; Diameter charging applications".
- [14] 3GPP TS 29.344: "Proximity-services (ProSe) Function to Home Subscriber Server (HSS) aspects (PC4); Stage 3".
- [15] 3GPP TS 29.273: "Evolved Packet System (EPS); 3GPP EPS AAA interfaces".
- [16] 3GPP TS 29.272: "Evolved Packet System (EPS); Mobility Management Entity (MME) and Serving GPRS Support Node (SGSN) related interfaces based on Diameter protocol".
- [17] Wi-Fi Alliance Technical Committee P2P Task Group, "Wi-Fi Peer-to-Peer (P2P) Technical Specification", Version 1.1.

- [18] 3GPP TS 29.336: "Home Subscriber Server (HSS) diameter interfaces for interworking with packet data networks and applications".
- [19] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".
- [20] IEEE Std 802.11-2012: "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".
- [21] IETF RFC 7683: "Diameter Overload Indication Conveyance".
- [22] 3GPP TS 24.334: "Proximity-services (ProSe) User Equipment (UE) to ProSe function protocol aspects; Stage 3".
- [23] 3GPP TS 33.303: "Proximity-based Services (ProSe); Security aspects".
- [24] 3GPP TS 23.271: "Functional stage 2 description of Location Services (LCS)".
- [25] Open Mobile Alliance, OMA AD SUPL: "Secure User Plane Location Architecture", (<http://www.openmobilealliance.org>).
- [26] 3GPP TS 24.333: "Proximity-services (ProSe) Management Objects (MO)".
- [27] IETF draft-ietf-dime-drmp-03: "Diameter Routing Message Priority".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

ALUID	Application Layer User ID
DRMP	Diameter Routing Message Priority
DUCK	Discovery User Confidentiality Key
DUIK	Discovery User Integrity Key
DUSK	Discovery User Scrambling Key
EPUID	EPC ProSe User ID
MIC	Message Integrity Check
PDUID	ProSe Discovery UE ID
ProSe	Proximity-based Services
RPAUID	Restricted ProSe Application User ID
UTC	Universal Time Coordinated
WLLID	WLAN Link Layer ID

4 General Description

4.1 Introduction

The PC6 reference point is defined between a ProSe Function in the HPLMN and a ProSe Function in a local PLMN.

The PC7 reference point is defined between ProSe Function in the HPLMN and a ProSe Function in a visited PLMN.

The definition of the PC6/PC7 reference points and related functionalities are given in 3GPP TS 23.303 [2].

As defined in 3GPP TS 23.303 [2], the PC6/PC7 reference points are used for:

- HPLMN control of service authorization for ProSe;
- Authorization of ProSe Direct Discovery requests;
- Retrieval of Discovery Filter(s) corresponding ProSe Application ID name(s);
- Translation of ProSe Application Code(s) to the associated ProSe Application Name.

5 Procedures Description

5.1 introduction

This clause describes the Diameter-based PC6 and PC7 interfaces related procedures and Information elements exchanged between functional entities.

In the tables that describe the Information Elements transported by each Diameter command, each Information Element is marked as (M) Mandatory, (C) Conditional or (O) Optional in the "Cat." column. For the correct handling of the Information Element according to the category type, see the description detailed in clause 6 of the 3GPP TS 29.228 [3].

5.2 ProSe Service Authorization

5.2.1 General

The ProSe Service Authorization Procedure shall be used between the ProSe Function in the HPLMN and the ProSe Function in Local PLMN or VPLMN to obtain service authorization information for ProSe Direct Discovery, ProSe Direct Communication or both. The procedure shall be invoked by the ProSe Function in the HPLMN by the UE and is used:

- to request service authorization information for ProSe related to the UE from the ProSe Function in the local PLMN or VPLMN;
- to provide the ProSe Function in the local PLMN or VPLMN with the UE identity (IMSI or MSISDN) in order to allow to perform charging;

This procedure is mapped to the commands ProSe-Authorization-Request/Answer (PAR/PAA) in the Diameter application specified in clause 6.

Table 5.2.1-1 specifies the involved information elements for the request.

Table 5.2.1-2 specifies the involved information elements for the answer.

Table 5.2.1-1: ProSe Service Authorization Request

Information element name	Mapping to Diameter AVP	Cat.	Description
UE Identity (See 6.3.28)	User-Identifier	M	This information element shall contain either the user IMSI, formatted according to 3GPP TS 23.003 [4], subclause 2.2, or the user MSISDN, formatted according to 3GPP TS 29.329 [5].
PLMN Id (See 6.3.29)	Visited-PLMN-Id	M	This IE shall contain the PLMN-Id (3GPP TS 23.003 [4]) of the network in which the ProSe Function is located.
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.

Table 5.2.1-2: ProSe Service Authorization Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - User Unknown - Unauthorized Service - Unauthorized Service in this PLMN
ProSe Direct Allowed (See 6.3.42)	ProSe-Direct-Allowed	C	This Information Element shall contain the ProSe authorization information of the user. It shall be present if success is reported.
Validity Time of Announcing (see.6.3.36)	Validity-Time-Announce	C	This Information Element shall contain the validity time for a UE authorization to perform ProSe direct discovery announcing in this PLMN. It shall be present if success is reported.
Validity Time of Monitoring (see.6.3.37)	Validity-Time-Monitor	C	This Information Element shall contain the validity time for a UE authorization to perform ProSe direct discovery monitoring in this PLMN. It shall be present if success is reported.
Validity Time of Communication (see.6.3.38)	Validity-Time-Communication	C	This Information Element shall contain the validity time for a UE authorization to perform ProSe direct communication in this PLMN. It shall be present if success is reported.
Authorized Discovery Range (See 3GPP TS 29.344 [14])	Authorized-Discovery-Range	C	This information element shall contain the authorised range (short/medium/long) at which the UE is allowed to announce in the given PLMN according to the defined announcing authorisation policy for this UE. It shall be present if the discovery authorization type is for announcing. Otherwise it shall be absent.

5.2.2 Detailed behaviour of the ProSe Function in the HPLMN

The ProSe Function in the HPLMN shall make use of this procedure to request service authorization information for ProSe related to the UE from the ProSe Function in local PLMN or VPLMN. The ProSe Function shall include in the request the UE identity (IMSI or MSISDN) and the PLMN-Id identifying the PLMN of the requesting ProSe Function.

When receiving a ProSe Service Authorization response from the ProSe Function in the local PLMN or VPLMN, the ProSe Function in the HPLMN shall check the result code. If it indicates SUCCESS, the ProSe Function shall merge with its own policy.

5.2.3 Detailed behaviour of the ProSe Function in the Local PLMN or VPLMN

When receiving a ProSe Service Authorization request, the ProSe Function in the local PLMN or VPLMN shall, in the following order:

1. Check whether the UE Identity (IMSI or MSISDN) exists. If not, a Result Code of `DIAMETER_ERROR_USER_UNKNOWN` shall be returned.
2. Check whether ProSe is authorized for this UE Identity. If not, a Result Code of `DIAMETER_ERROR_UNAUTHORIZED_SERVICE` shall be returned.

If there is an error in any of the above steps then the ProSe Function shall stop processing the request and shall return the error code specified in the respective step.

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall stop processing the request and set the Result Code to `"DIAMETER_UNABLE_TO_COMPLY"`.

Otherwise, when the UE is authorized to use ProSe Direct Discovery or ProSe Direct Communication in this PLMN, the ProSe Function shall return the authorization data in the response, according to the supported/unsupported features of the ProSe Function in the Local PLMN or VPLMN, and the authorised announcing range (short/medium/long) at which and if the UE is allowed to announce in the VPLMN according to the defined announcing authorisation policy for this UE (see 3GPP TS 24.333 [26] for the possible values of the range) and shall set the Result Code to `"DIAMETER_SUCCESS"`.

5.3 ProSe Direct Discovery Authorization

5.3.1 General

The ProSe Direct Discovery Authorization Procedure shall be used between the ProSe Function in the HPLMN and the ProSe Function in a local PLMN or VPLMN to obtain authorization for access to the discovery resources and perform ProSe Direct Discovery. The procedure shall be invoked by the ProSe Function in the HPLMN and is used:

- to request the ProSe Function in VPLMN or a PLMN other than the HPLMN/VPLMN for the authorization for ProSe Direct Discovery announcing when the announcing UE is roaming in the VPLMN or announcing in a PLMN different from the HPLMN/VPLMN;
- to perform the resolution ProSe Application ID Name to ProSe Application Code and/or ProSe Application Mask when the ProSe Application ID has PLMN-specific scope for open ProSe Direct discovery;
- to notify the ProSe Function in local PLMN that the previously allocated ProSe Discovery Filter for a ProSe Application ID which has PLMN-specific scope is no longer monitored by a monitoring UE of the HPLMN;
- to perform the resolution of a target RPAUID to a ProSe Restricted Code or ProSe Restricted Code Prefix for restricted ProSe Direct Discovery;
- to provide the ProSe Function in the local PLMN or VPLMN with the application identity in order to allow it to perform charging;
- to provide the ProSe Function in the local PLMN or VPLMN with the UE identity (i.e. IMSI or MSISDN) in order to allow to perform charging;
- to provide the ProSe Function in VPLMN with the allocated ProSe Application Code, ProSe Restricted Code or ProSe Restricted Code Prefix/Suffix Pool, and the corresponding validity timer, or a notification of the termination or change of the allocated ProSe-related codes, in order to allow to perform charging.
- to provide the ProSe Function in VPLMN with the allocated ProSe Query Code or ProSe Response Code and the corresponding validity timer when such a code is announced in restricted ProSe Direct Discovery model B procedure, in order to allow to perform charging.

- to provide the ProSe Function in VPLMN/Local PLMN with the allocated ProSe Query Code, ProSe Response Code and associated validity timer for a given RPAUID using restricted ProSe Direct Discovery model B.

This procedure is mapped to the commands ProSe-Discovery-Request/Answer (PDR/PDA) in the Diameter application specified in clause 6.

Table 5.3.1-1 specifies the involved information elements for the request.

Table 5.3.1-2 specifies the involved information elements for the answer.

Table 5.3.1-1: ProSe Direct Discovery Authorization Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Discovery Authorization Request (See 6.3.53)	Discovery-Auth-Request	M	This information element shall contain the information elements used in discovery authorization request.
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Discovery Entry ID (See 6.3.59)	Discovery-Entry-ID	C	This Information Element contains the discovery entry ID used by the sending ProSe Function to identify the discovery entry related to this request.

Table 5.3.1-2: ProSe Direct Discovery Authorization Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - Announcing Not Authorized - No Associated Discovery Filter
Discovery Authorization Response (See 6.3.53)	Discovery-Auth-Response	C	This information element shall contain the information elements used in discovery authorization response. This information element shall be present if the Result Code AVP is DIAMETER_SUCCESS.
Discovery Entry ID (See 6.3.59)	Discovery-Entry-ID	C	This Information Element contains the discovery entry ID used by the sending ProSe Function to identify the discovery entry related to this request.

5.3.2 Detailed behaviour of the HPLMN ProSe Function

The ProSe Function in the HPLMN shall make use of this procedure to request the ProSe Function in VPLMN or a PLMN other than the HPLMN/VPLMN for ProSe Direct Discovery announcing authorisation for an announcing UE roaming in the VPLMN or announcing in a PLMN different from the HPLMN/VPLMN.

- For open ProSe Direct Discovery, the HPLMN ProSe Function shall include in the request the Discovery Entry ID and shall include in the Discovery Authorization Request the Discovery Type set to "ANNOUNCING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the ProSe Application ID corresponding to the request from the announcing UE and the ProSe Application Code or ProSe Application Code Prefix/Suffix(es) assigned for this request. The Discovery Authorization Request shall include the UE identity (i.e., IMSI or MSISDN) and the ProSe Validity Timer corresponding to ProSe Application Code in order to allow the ProSe Function in VPLMN or the PLMN other than the HPLMN/VPLMN to perform charging. If the announcing UE's original announce request is for updating the metadata, the updated metadata shall also be

included. If the announcing UE's original announce request is for stopping the announcing operation, the ProSe Function shall not include any ProSe Application Code(s) or ProSe Validity Timer.

- For restricted ProSe Direct Discovery, the HPLMN ProSe Function shall include in the Discovery Authorization Request the Discovery Entry ID and the Discovery Type set to "ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the application identity, RPAUID corresponding to the announcing UE, the ProSe Restricted Code assigned for this request. The Discovery Authorization Request shall also include the UE identity (i.e., IMSI or MSISDN) and the ProSe Validity Timer corresponding to ProSe Restricted Code in order to allow the ProSe Function in VPLMN or the PLMN other than the HPLMN/VPLMN to perform charging. For restricted ProSe Direct Discovery using application-controlled extension, the ProSe Function shall include a ProSe Restricted Code Prefix and one or more ProSe Restricted Code Suffix Range in the Discovery Authorization Request. If the announcing UE's original announce request is for stopping the announcing operation, the ProSe Function shall not include any ProSe Restricted Code or ProSe Restricted Code Prefix or ProSe Restricted Code Suffix Range(s), or ProSe Validity Timer.
- For restricted ProSe Direct Discovery model B discoverer operation, the HPLMN ProSe Function shall include in the Discovery Authorization Request the Discovery Entry ID and the Discovery Type set to "DISCOVERER_ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the application identity, RPAUID corresponding to the discoverer UE as well as the ProSe Query Code assigned for this request. The Discovery Authorization Request shall also include the UE identity (i.e., IMSI or MSISDN) and the ProSe Validity Timer corresponding to ProSe Query Code in order to allow the ProSe Function in VPLMN or the PLMN other than the HPLMN/VPLMN to perform charging
- For restricted ProSe Direct Discovery model B discoveree operation, the HPLMN ProSe Function shall include in the Discovery Authorization Request the Discovery Entry ID and the Discovery Type set to "DISCOVEREE_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the application identity, RPAUID corresponding to the discoverer UE as well as the ProSe Response Code assigned for this request. The Discovery Authorization Request shall also include the UE identity (i.e., IMSI or MSISDN) and the ProSe Validity Timer corresponding to ProSe Query Code in order to allow the ProSe Function in VPLMN or the PLMN other than the HPLMN/VPLMN to perform charging.

The ProSe Function in the HPLMN shall make use of this procedure to retrieve from the ProSe Function in the local PLMN the Discovery Filter for monitoring in open ProSe Direct Discovery or to retrieve parameters needed to create a Restricted Discovery Filter, or ProSe Response Filter associated with the monitored/queried application-layer identity for restricted ProSe Direct Discovery.

- For open ProSe Direct Discovery, the HPLMN ProSe Function shall include in the request the Discovery Entry ID and shall include in the Discovery Authorization Request the Discovery Type set to "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the ProSe Application ID name corresponding to the request from the monitoring UE. The Discovery Authorization Request shall also include the UE identity (i.e., IMSI or MSISDN) in order to allow the ProSe Function in local PLMN to perform charging. If the monitoring UE's original announce request is for stopping the monitoring operation or the allocated Discovery Filter has been revoked by the ProSe Function, the ProSe Function shall not include the ProSe Application ID name.
- For restricted ProSe Direct Discovery, the HPLMN ProSe Function shall include in the Discovery Authorization Request the Discovery Entry ID and the Discovery Type set to "MONITORING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the application identity, the requesting RPAUID, target RPAUID and target PDUID of a monitoring target. The Discovery Authorization Request shall also include the UE identity (i.e., IMSI or MSISDN) in order to allow the ProSe Function in local PLMN to perform charging.
- For restricted ProSe Direct Discovery model B discoveree operation, the HPLMN ProSe Function shall include in the Discovery Authorization Request the Discovery Entry ID and the Discovery Type set to the indicate "DISCOVERER_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the application identity, the requesting RPAUID, target RPAUID and target PDUID of a monitoring target. The request shall include the UE identity (IMSI or MSISDN) and the Discovery Entry ID in order to allow the ProSe Function in local PLMN to perform charging.

When receiving the ProSe Direct Discovery Authorization response with the Result Code set to

"DIAMETER_SUCCESS" for a request with the Discovery Type set to

"MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the HPLMN ProSe Function shall

check whether a ProSe Discovery Filter is received for each ProSe Application ID Name sent in the request. If a ProSe Discovery Filter is missing for one ProSe Application ID Name, the ProSe Function shall consider that there is no valid ProSe Discovery Filter the ProSe associated with this ProSe Application ID Name in the ProSe Function in the local PLMN or VPLMN.

When receiving the ProSe Direct Discovery Authorization response with the Result Code set to "DIAMETER_SUCCESS" for a request with the Discovery Type set to "MONITORING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY" or "DISCOVERER_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the HPLMN ProSe Function shall enclose the information in Code Receiving Security Material parameter in the discovery filter created for the target RPAUID. If a DUIK parameter is included in the response message, the ProSe Function shall store the DUIK in order to verify the MIC field, as specified in 3GPP TS 24.334 [22].

5.3.3 Detailed behaviour of the ProSe Function in the local PLMN or VPLMN

When receiving a ProSe Direct Discovery Authorization request, the ProSe Function in the local PLMN or VPLMN shall check the value of the Discovery Type.

- If the value is "ANNOUNCING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the ProSe Function shall check if the UE is authorized to announce in the PLMN.
 - If the UE is not authorized, the experimental result code shall be set to "DIAMETER_ERROR_ANNOUNCING_UNAUTHORIZED_IN_PLMN" in the response sent by the ProSe Function.
 - If the UE is authorized, the result code shall be set to "DIAMETER_SUCCESS" in the response sent by the ProSe Function. The ProSe Function shall store the UE identity (i.e., IMSI or MSISDN) in order to perform charging. In addition, the ProSe Function in the VPLMN or the PLMN other than the HPLMN/VPLMN shall store the ProSe Validity Timer corresponding to ProSe Application Code or ProSe Application Code Prefix/Suffix(es) in order to perform charging. If no ProSe Application Code is included in the request, the ProSe Function shall remove the discovery entry associated with the Discovery Entry ID for the requesting UE.
- If the value is "ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the ProSe Function shall check whether the UE is authorized to announce in the PLMN for restricted discovery model A.
 - If the UE is not authorized, the experimental result code shall be set to "DIAMETER_ERROR_ANNOUNCING_NOT_AUTHORIZED" in the response sent by the ProSe Function.
 - If the UE is authorized, the result code shall be set to "DIAMETER_SUCCESS" in the response sent by the ProSe Function. The ProSe Function in the VPLMN or the PLMN other than the HPLMN/VPLMN shall store the UE identity (IMSI or MSISDN) in order to perform charging;
 - ProSe Function in the VPLMN or the PLMN other than the HPLMN/VPLMN shall store the Application Identity, and the ProSe Validity Timer corresponding to ProSe Restricted Code or ProSe Restricted Code Prefix and ProSe Restricted Code Suffix(es) in order to perform charging. If no ProSe Restricted Code or ProSe Restricted Code Prefix is included in the request, the ProSe Function shall remove the discovery entry associated with the Discovery Entry ID for the requesting UE.
- If the value is "DISCOVEREE_ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the ProSe Function shall check whether the UE is authorized to announce in the PLMN for restricted discovery model B discoveree operation.
 - If the UE is not authorized, the experimental result code shall be set to "DIAMETER_ERROR_ANNOUNCING_UNAUTHORIZED_IN_PLMN" in the response sent by the ProSe Function.

- If the UE is authorized, the result code shall be set to "DIAMETER_SUCCESS" in the response sent by the ProSe Function. The ProSe Function in the VPLMN or the PLMN other than the HPLMN/VPLMN shall store the UE identity (IMSI or MSISDN) in order to perform charging;
- ProSe Function in the VPLMN or the PLMN other than the HPLMN/VPLMN shall store the Application Identity, and the ProSe Validity Timer corresponding to ProSe Response Code in order to perform charging.
- If the value is "DISCOVERER_ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the ProSe Function shall check whether the UE is authorized to announce in the PLMN for restricted discovery model B discoverer operation.
 - If the UE is not authorized, the experimental result code shall be set to "DIAMETER_ERROR_ANNOUNCING_UNAUTHORIZED_IN_PLMN" in the response sent by the ProSe Function.
 - If the UE is authorized, the result code shall be set to "DIAMETER_SUCCESS" in the response sent by the ProSe Function. The ProSe Function in the VPLMN or the PLMN other than the HPLMN/VPLMN shall store the UE identity (IMSI or MSISDN), the Application Identity and the ProSe Validity Timer corresponding to ProSe Query Code in order to perform charging;
- If the value is "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the ProSe Function shall check whether one or more Discovery Filter(s) exist for each ProSe Application ID name received in the request.
 - If there is no valid Discovery Filter associated to the ProSe Application ID name in the request, the experimental result code shall be set to "DIAMETER_ERROR_NO_ASSOCIATED_DISCOVERY_FILTER" in the response sent by the ProSe Function.
- If no ProSe Application ID is included in the request, the ProSe Function shall remove the discovery entry associated with the Discovery Entry ID for the requesting UE. If there exists one or more valid Discovery Filters related to the ProSe Application ID name, the ProSe Function shall return the Discovery Authorization Response including the Discovery Filter(s) along with the Discovery Entry ID and set the result code to "DIAMETER_SUCCESS" in the response. If the announcing UE is roaming, the PLMN-Id of the VPLMN shall be included in the Discovery Authorization Response.
- If the value is "MONITORING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the ProSe Function shall process the request in the following order to check if the monitoring is authorized.
 - The ProSe function shall check whether the target PDUID is known and belongs to its own PLMN. If not, the experimental result code shall be set to "DIAMETER_ERROR_INVALID_TARGET_PDUID" in the response sent by the ProSe Function.
 - The ProSe function may check whether the requesting RPAUID is allowed to discover the target RPAUID. If not, the experimental result code shall be set to "DIAMETER_ERROR_INVALID_TARGET_RPAUID" in the response sent by the ProSe Function.
 - The ProSe function shall check whether a valid ProSe Restricted Code or ProSe Restricted Code Prefix exists for the target RPAUID included in the request.
 - If not, the experimental result code shall be set to "DIAMETER_ERROR_NO_ASSOCIATED_RESTRICTED_CODE" in the response sent by the ProSe Function.
 - Otherwise, the ProSe Function shall set the result code to "DIAMETER_SUCCESS" in the response. The ProSe Function shall return the Discovery Authorization Response including the ProSe Restricted Code or ProSe Restricted Code Prefix associated with the target RPAUID, and the corresponding Code Receiving Security Material and optionally a DUIK, and its corresponding Validity Timer. If the announcing UE is roaming, the PLMN-Id of the VPLMN shall be also included in the response.
- If the value is "DISCOVERER_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the ProSe Function shall process the request in the following order to check whether the monitoring is authorized.

- The ProSe function shall check if the target PDUID is known and belongs to its own PLMN. If not, the experimental result code shall be set to "DIAMETER_ERROR_INVALID_TARGET_PDUID" in the response sent by the ProSe Function.
- The ProSe function may check if the requesting RPAUID is allowed to discover the target RPAUID. If not, the experimental result code shall be set to "DIAMETER_ERROR_INVALID_TARGET_RPAUID" in the response sent by the ProSe Function.
- The ProSe function shall check if both ProSe Query Code and ProSe Response Code exist for the target RPAUID included in the request.
 - If not, the experimental result code shall be set to "DIAMETER_ERROR_NO_ASSOCIATED_RESTRICTED_CODE" in the response sent by the ProSe Function.
 - Otherwise, the ProSe Function shall set the result code to "DIAMETER_SUCCESS" in the response. The ProSe Function shall return the Discovery Authorization Response including the ProSe Query Code and the corresponding Code Sending Security Material and ProSe Response Code Code associated with the target RPAUID, and the corresponding Code Receiving Security Material and optionally a DUIK, and its corresponding Validity Timer. If the discoverer UE is roaming or announcing in a PLMN different from the HPLMN/VPLMN, the PLMN-Id of the VPLMN or PLMN other than the HPLMN/VPLMN shall be also included in the response.

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall set the Result Code to "DIAMETER_UNABLE_TO_COMPLY".

5.4 ProSe Match Report

5.4.1 General

The ProSe Match Report Procedure shall be used between the ProSe Function in the HPLMN and the ProSe Function in the local PLMN identified by the PLMN-Id contained in the ProSe Application Code(s) discovered by the monitoring UE.. The procedure shall be invoked by the ProSe Function in the HPLMN and is used:

- to confirm that the ProSe Application Code(s) is authorized to be transmitted on the monitored PLMN;
- to retrieve the ProSe Application ID(s), associated validity timer(s) and associated match report refresh timer(s) corresponding to the ProSe Application Code(s) as well metadata associated with the ProSe Application ID if available and requested by the UE; and
- to provide the ProSe Function in the local PLMN with the identity (IMSI or MSISDN) of the monitoring UE in order to allow to perform charging.

This procedure is mapped to the commands ProSe-Match-Request/Answer (PMR/PMA) in the Diameter application specified in clause 6.

Table 5.4.1-1 specifies the involved information elements for the request.

Table 5.4.1-2 specifies the involved information elements for the answer.

Table 5.4.1-1: ProSe Match Report Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Match Request	Match-Request	M	This information element shall contain the information elements used in discovery match request.
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
PMR Flags (See 6.3.57)	PMR-Flags	C	This Information Element contains a bit mask. See 6.3.57 for the meaning of the bits.

Table 5.4.1-2: ProSe Match Report Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - Announcing Not Authorized in PLMN - Invalid Application Code
Match Report (See 6.3.12)	Match-Report	C	This Information Element shall contain the information elements in response to the discovery match request. This Information Element shall be present only when the Result-Code AVP is DIAMETER_SUCCESS. Multiple instances of this Information Element may be present in the message.

5.4.2 Detailed behaviour of the HPLMN ProSe Function

The ProSe Function in the HPLMN shall make use of this procedure to retrieve from the ProSe Function in the local PLMN (identified by the PLMN-Id contained in the ProSe Application Code) the ProSe Application ID(s) that correspond to ProSe Application Code(s) discovered by the monitoring UE. The HPLMN ProSe Function shall include in the Match Request the Discovery Type set to "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the discovered ProSe Application Code(s) corresponding to the request from the monitoring UE as well as the MIC and UTC-based counter associated with the discovered ProSe Application Code. The request shall include the UE identity (i.e. IMSI or MSISDN) in order to allow the ProSe Function in the local PLMN to perform charging of the monitoring UE. If the metadata information associated with the ProSe Application ID is requested by the UE, the flag "Metadata Requested" shall be set in the PMR Flags.

When receiving the ProSe Match Report response from the ProSe Function in the local PLMN with the Result Code set to "DIAMETER_SUCCESS", the HPLMN ProSe Function shall check whether a Match Report is received for each ProSe Application Code sent in the request. If a Match Report is missing for one ProSe Application Code, this ProSe Application Code shall be considered as invalid by the ProSe Function.

5.4.3 Detailed behaviour of the ProSe Function in the local PLMN

When receiving a ProSe Match Report request, the ProSe Function in the local PLMN shall check the value of the Discovery Type contained in the Match Request.

- If the value indicated in the Discovery Type is not supported, the experimental result code shall be set to "DIAMETER_ERROR_INVALID_DISCOVERY_TYPE" in the response.
- If the value is "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the ProSe Function shall check whether that the ProSe Application Code received is authorized to be announced in the monitored PLMN.
 - If not, the experimental result code shall be set to "DIAMETER_ERROR_ANNOUNCING_UNAUTHORIZED_IN_PLMN" in the response.
 - If the ProSe Code is authorized to be announced, the ProSe Function shall check the validity of the ProSe Application Code(s) discovered by the monitoring UE, i.e. a ProSe Application ID name is associated and the validity timer has not expired, and the MIC value associated with the ProSe Application Code is valid when verified based on the associated UTC-based counter as defined in 3GPP TS 33.303 [23].
 - If none of the ProSe Application Code(s) is valid in the ProSe Function, i.e. either no ProSe Application Code exists, the validity timer(s) has expired, or MIC check(s) for the ProSe Application Code(s) has

failed, the experimental result code shall be set to

"DIAMETER_ERROR_INVALID_APPLICATION_CODE" in the response sent by the ProSe Function.

- Otherwise, when at least one ProSe Application Code is valid, the ProSe Function shall return the Match Report and set the result code to "DIAMETER_SUCCESS" in the response. For each valid ProSe Application code, the Match Report shall contain the matched ProSe Application Code, the ProSe Application ID Name, the validity timer and the match report refresh timer. The Match Report may include metadata associated with the ProSe Application ID if requested and available. The ProSe Function may store the monitoring UE identity (i.e. IMSI or MSISDN) in order to perform charging.

If there is an error in any of the above steps then the ProSe Function shall stop processing the request and shall return the error code specified in the respective step.

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall stop processing the request and set the Result Code to "DIAMETER_UNABLE_TO_COMPLY".

If the ProSe Application Code contains a metadata index, a ProSe-Metadata-Index-Mask AVP shall be provided for this ProSe Application Code.

5.5 ProSe Match Report info

5.5.1 General

For open discovery, the ProSe Match Report Info Procedure shall be used by the ProSe Function in the HPLMN of the monitoring UE to provide a match report information to the ProSe Function of the visited PLMN in which the announcing UE is roaming. For restricted discovery, the ProSe Match Report Info Procedure shall also be used by the ProSe Function in the HPLMN of the monitoring UE or discoverer UE to provide a match report information to the ProSe Function of the HPLMN of the announcing UE or discoveree UE.

This procedure is mapped to the commands ProSe-Match-Report-Info-Request/Answer (PIR/PIA) in the Diameter application specified in clause 6.

Table 5.5.1-1 specifies the involved information elements for the request.

Table 5.5.1-2 specifies the involved information elements for the answer.

Table 5.5.1-1: ProSe Match Report Info Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Match Report Information (See 6.3.56)	Match-Report-Info	C	This information element shall contain the information elements used in discovery match report info request. This information element shall be present if the Discovery Type is <u>MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY</u> .
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.

Table 5.5.1-2: ProSe Match Report Info Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - Unknown User

5.5.2 Detailed behaviour of the requesting ProSe Function

When the monitored PLMN-Id provided by the monitoring UE during the Match Report procedure (see subclause 5.4) is different from the PLMN-Id contained in the ProSe Application Code discovered by the monitoring UE, i.e. the announcing UE is roaming in a visited PLMN, the monitoring UE's ProSe Function in the HPLMN may make use of this procedure to send a match report information to the ProSe Function in the visited PLMN in which the announcing UE is roaming.. In such case, the HPLMN ProSe Function shall include in the Match Report Information the Discovery Type set to "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY" as well as the ProSe Application ID and the identity of the monitoring UE (i.e. IMSI or MSISDN).

When the HPLMN ProSe Function of the monitoring UE processes a match report for a discovered ProSe Restricted Code from the UE, and finds that the target PDUID for the corresponding discovery entry contains a PLMN-Id different from the PLMN of the ProSe Function, the monitoring UE's ProSe Function in the HPLMN may make use of this procedure to send a match report information to the ProSe Function to which the announcing UE belongs. In such case, the HPLMN ProSe Function shall include in the Match Report Information the Discovery Type set to "MONITORING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the ProSe Restricted Code, the RPAUID, the target RPAUID and the identity of the monitoring UE (i.e. IMSI or MSISDN). The ProSe Function may also include the timestamp of the match event in the Match Report Information.

When the HPLMN ProSe Function of the discoverer UE processes a match report for a discovered ProSe Response Code from the discoverer UE, and finds that the target PDUID for the corresponding discovery entry contains a PLMN-Id different from the PLMN of the ProSe Function, the discoverer UE's ProSe Function in the HPLMN may make use of this procedure to send a match report information to the ProSe Function to which the discoveree UE belongs. In such case, the HPLMN ProSe Function shall include in the Match Report Information the Discovery Type set to "DISCOVERER_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the ProSe Response Code, the RPAUID, the target RPAUID and the identity of the discoverer UE (i.e. IMSI or MSISDN). The ProSe Function may also include the timestamp of the match event in the Match Report Information.

5.5.3 Detailed behaviour of the receiving ProSe Function

When receiving a ProSe Match Report Info request, the ProSe Function shall check the value of the Discovery Type contained in the Match Report Information.

- If the value indicated in the Discovery Type is not supported, the experimental result code shall be set to "DIAMETER_ERROR_INVALID_DISCOVERY_TYPE" in the response.
- If the value is "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", "MONITORING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY" or "DISCOVERER_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the ProSe Function shall check whether the UE Identity (i.e. IMSI or MSISDN) exists.
- If not, a Result Code of DIAMETER_ERROR_USER_UNKNOWN shall be returned.

- Otherwise, it shall acknowledge the reception of the Match Report info and set the Result Code to "DIAMETER_SUCCESS" in the response.

If the ProSe Function in the VPLMN cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall stop processing the request and set the Result Code to "DIAMETER_UNABLE_TO_COMPLY" in the response.

5.6 ProSe Proximity Request

5.6.1 General

The ProSe Proximity Request Procedure shall be used by a ProSe Function in charge of the requesting UE to request the ProSe Function in charge of another UE to indicate when two UEs will enter into proximity within a requested time window.

This procedure is mapped to the commands ProSe-Proximity-Request/Answer (PRR/PRA) in the Diameter application specified in clause 6.

Table 5.6.1-1 specifies the involved information elements for the request.

Table 5.6.1-2 specifies the involved information elements for the answer.

Table 5.6.1-1: ProSe Proximity Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Requesting EPUID (See 6.3.23)	Requesting-EPUID	M	This Information Element shall contain the EPC ProSe User ID (EPUID) of the UE triggering the Proximity Request.
Targeted EPUID (See 6.3.26)	Targeted-EPUID	M	This Information Element shall contain the EPC ProSe User ID (EPUID) of the UE targeted by the Proximity Request.
Time Window (See 6.3.27)	Time-Window	M	This Information Element shall contain the time period during which the Proximity request is valid
Requesting UE Location (See 6.3.10)	Location-Estimate	M	This Information Element shall contain the current location of the requesting UE expressed in GAD shapes defined in TS 23.032 [6]
Location Update Trigger (See 6.3.a)	Location-Update-Trigger	O	If present, this Information Element shall contain the trigger that will cause the location updates performed by the ProSe Function.
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
PRR Flags (See 6.3.21)	PRR-Flags	M	This Information Element contains a bit mask. See 6.3.21 for the meaning of the bits.

Table 5.6.1/2: ProSe Proximity Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - EPUID unknown - Proximity request rejected - Proximity unauthorized
Targeted UE Location (See 6.3.10)	Location-estimate	C	This Information Element shall contain the current location of the targeted UE expressed in GAD shapes defined in TS 23.032 [6]. This information shall be present when the Result Code is "DIAMETER_SUCCESS" and the location of the targeted UE is known.
WLAN Link Layer ID (See 6.3.32)	WLAN-Link-Layer-Id	C	This Information shall contain the permanent link layer identity used by the targeted UE for WLAN direct discovery and/or WLAN direct communication. It shall be present if the requesting UE has requested EPC support for WLAN direct discovery and if the targeted UE has a permanent WLAN Link Layer ID for communication (e.g. permanent MAC address).

5.6.2 Detailed behaviour of the ProSe Function of the requesting UE

The ProSe Function of the UE triggering the Proximity request shall make use of this procedure to propagate the Proximity request to the ProSe Function of the targeted UE. The ProSe Function shall include in the request the EPC ProSe User Identities of the requesting and targeted UEs, the location of the requesting UE, the validity period of the Proximity request and, the location update trigger. If the requesting UE has requested EPC support for WLAN direct discovery and communication with the targeted UE, the PRR-Flag "WLAN Indication" shall be set.

NOTE: The location update trigger enable the ProSe Function of the targeted UE to configure SUPL reporting in targeted UE using the ""Inside" trigger with Repeated Reporting" mechanism as defined in OMA AD SUPL [25].

When receiving a ProSe Proximity response from the ProSe Function of the targeted UE, the ProSe Function of the requesting UE shall check the result code. If it indicates SUCCESS, the ProSe Function shall create and manage a context associated with the Proximity request, including the EPUIDs of the UEs, the validity period of this Proximity request and the WLAN indication received in the Proximity request until the execution of the Proximity Alert procedure, the Proximity Request Cancellation procedure or until the expiry of the time window during which the request is valid.

5.6.3 Detailed behaviour of the ProSe Function of the targeted UE

When receiving a ProSe Proximity request, the ProSe Function of the targeted UE, shall, in the following order:

1. Check whether the EPC ProSe User Identity of the targeted UE exists. If not, a Result Code of DIAMETER_ERROR_USER_UNKNOWN shall be returned.
2. Check whether the proximity request is authorized by the user. If not, the Proximity request is not authorized by the user, a Result Code of DIAMETER_ERROR_PROXIMITY_UNAUTHORIZED shall be returned.
3. Check the location of the requesting UE and the time window received in the request and determine whether UEs are likely to enter into proximity based the last known location of the targeted UE. If it is unlikely that UEs enter into proximity for the received time window, a Result Code of DIAMETER_ERROR_PROXIMITY_REJECTED shall be returned in the response.

If there is an error in any of the above steps then the ProSe Function shall stop processing the request and shall return the error code specified in the respective step.

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall stop processing the request and set the Result Code to "DIAMETER_UNABLE_TO_COMPLY".

Otherwise, the ProSe Function shall acknowledge the reception of the Proximity and set the Result Code to "DIAMETER_SUCCESS" in the response. The message may include the last known location of the targeted UE, if available. The message may also include the permanent WLAN Link Layer ID (e.g. MAC address) of the targeted UE if available and if the PRR-Flag "WLAN Indication" was set in the request. The ProSe Function shall create and manage a context associated with the Proximity request, including the identity of ProSe Function triggering the Proximity request, the EPUIDs of the UEs, the validity period of this Proximity request, the WLAN indication, the location update periodicity and/or location update trigger received in the Proximity request until the execution of the Proximity Alert procedure, the Proximity Request Cancellation procedure or until the expiry of the time window during which the request is valid.

5.7 ProSe Location Update

5.7.1 General

The ProSe Location Update Procedure shall be used by a ProSe Function to forward the location of UE to the ProSe Function triggering the Proximity Request and in charge of determining the proximity of two UEs.

This procedure is mapped to the commands ProSe-Location-Update-Request/Answer (PLR/PLA) in the Diameter application specified in clause 6.

Table 5.7.1-1 specifies the involved information elements for the request.

Table 5.7.1-2 specifies the involved information elements for the answer.

Table 5.7.1-1: ProSe Location Update Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Targeted EPUID (See 6.3.26)	Targeted-EPUID	M	This Information Element shall contain the EPC ProSe User ID (EPUID) of the UE targeted by the Proximity Request.
Targeted UE Location (See 6.3.10)	Location-Estimate	M	This Information Element shall contain the current location of the targeted UE expressed in GAD shapes defined in TS 23.032 [6].
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.

Table 5.7.1-2: ProSe Location Update Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	<p>This IE shall contain the result of the operation.</p> <p>The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol.</p> <p>The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP.</p> <p>The following errors are applicable:</p> <ul style="list-style-type: none"> - User Unknown - Proximity Cancelled

5.7.2 Detailed behaviour of the ProSe Function of the requesting UE

The ProSe Function of the UE targeted by the Proximity request shall make use of this procedure to periodically update the targeted UE's location in the ProSe Function in charge of Proximity request. The ProSe Function shall include in the request the EPC ProSe User Identity and the location of the targeted UE.

5.7.3 Detailed behaviour of the ProSe Function of the targeted UE

When receiving a ProSe Location Update request, the ProSe Function in charge of the Proximity request shall, in the following order:

1. Check whether a proximity request exists for the EPC ProSe User Identity received in the request. If there is no pending Proximity request for this EPUID, a Result Code of `DIAMETER_ERROR_USER_UNKNOWN` shall be returned.
2. Check the location of the requesting UE and the time window indicated by the requesting UE and determine whether UEs are likely to enter into proximity based the last known location of the targeted UE. If it is unlikely that UEs enter into proximity for the received time window, a Result Code of `DIAMETER_ERROR_PROXIMITY_CANCELLED` shall be returned in the response.

If there is an error in any of the above steps then the ProSe Function shall stop processing the request and shall return the error code specified in the respective step.

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall stop processing the request and set the Result Code to `"DIAMETER_UNABLE_TO_COMPLY"`.

Otherwise, the ProSe Function shall acknowledge the reception of the ProSe Location Update and set the Result Code to `"DIAMETER_SUCCESS"` in the response.

5.8 ProSe Cancellation

5.8.1 General

The ProSe Cancellation Procedure shall be used between the ProSe Function in the HPLMN and the ProSe Function in the local/visited PLMN. The procedure shall be invoked by the ProSe Function in HPLMN and is used:

- to indicate that the service authorization for ProSe Direct Discovery and ProSe Direct Communication is revoked for this UE.
- to indicate that the Proximity Request sent earlier is cancelled.

This procedure is mapped to the commands ProSe-Cancellation-Request/Answer (PCR/PCA) in the Diameter application specified in clause 6.

Table 5.8.1-1 specifies the involved information elements for the request.

Table 5.8.1-2 specifies the involved information elements for the answer.

Table 5.8.1-1: ProSe Cancellation Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Requesting EPUID (See 6.3.23)	Requesting-EPUID	M	This Information Element shall contain the EPC ProSe User ID (EPUID) of the UE triggering the Proximity Request.
Targeted EPUID (See 6.3.26)	Targeted-EPUID	M	This Information Element shall contain the EPC ProSe User ID (EPUID) of the UE targeted by the Proximity Request.
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.

Table 5.8.1-2: ProSe Cancellation Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - No proximity request

5.8.2 Detailed behaviour of the ProSe Function of the requesting UE

The ProSe Function of the requesting UE shall make use of this procedure to cancel a Proximity Request sent earlier to the ProSe Function in charge of the targeted UE (e.g. due to change in the location of one of the UEs, termination of corresponding application or due to completion of certain event). The ProSe Function shall include in the request the EPC ProSe User Identities of the requesting and targeted UEs.

5.8.3 Detailed behaviour of the ProSe Function of the targeted UE

When receiving a ProSe Cancellation request, the ProSe Function of the targeted UE shall check whether there is a context associated with EPC ProSe User Identities included in the request. If not, the Result Code of `DIAMETER_ERROR_NO_PROXIMITY_REQUEST` shall be returned. Otherwise, the ProSe Function shall cancel the Proximity request and set the Result Code to `"DIAMETER_SUCCESS"` in the response

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall set the Result Code to `"DIAMETER_UNABLE_TO_COMPLY"`.

5.9 ProSe Proximity Alert

5.9.1 General

The ProSe Proximity Alert Procedure shall be used by a ProSe Function in charge of Proximity request to indicate to the ProSe Function of the UE targeted by the Proximity request that UEs enter into proximity and that a Proximity Alert should be sent to the targeted UE.

This procedure is mapped to the commands ProSe-Alert-Request/Answer (ALR/ALA) in the Diameter application specified in clause 6.

Table 5.9.1-1 specifies the involved information elements for the request.

Table 5.9.1-2 specifies the involved information elements for the answer.

Table 5.9.1-1: ProSe Proximity Alert Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Application Layer User ID (See 6.3.2)	Application-Layer-User-Id	M	This Information Element shall contain the Application Layer User ID of the requesting UE entering into proximity.
Targeted EPUID (See 6.3.26)	Targeted-EPUID	M	This Information Element shall contain the EPC ProSe User ID (EPUID) of the targeted UE to which the Proximity Alert shall be sent.
Assistance Information (See 6.3.3)	Assistance-Info	O	If present, this Information Element shall contain the assistance information for WLAN direct discovery and communications if required.
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.

Table 5.9.1-2: ProSe Proximity Alert Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - Announcing Not Authorized - No Discovery Filter

5.9.2 Detailed behaviour of the ProSe Function of the targeted UE

The ProSe Function in charge of the Proximity request shall make use of this procedure to indicate to the ProSe Function in charge of the targeted UE that the UEs enter into proximity and a Proximity Aleter should be sent to the targeted UE. The ProSe Function shall include in the request the Application Layer User ID and the EPUID of the requesting UE entering into proximity. It may include assistance information for WLAN direct discovery and communications if required the WLAN indication was included in the Proximity request.

5.9.3 Detailed behaviour of the ProSe Function of the requesting UE

When receiving a ProSe Proximity Alert request, the ProSe Function of the targeted UE, shall, in the following order:

1. Check whether the EPC ProSe User Identity of the targeted UE exists. If not, a Result Code of DIAMETER_ERROR_USER_UNKNOWN shall be returned.
2. Check whether the proximity request is authorized by the user. If not, the Proximity request is not authorized by the user, a Result Code of DIAMETER_ERROR_PROXIMITY_UNAUTHORIZED shall be returned.

If there is an error in any of the above steps then the ProSe Function shall stop processing the request and shall return the error code specified in the respective step.

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall stop processing the request and set the Result Code to "DIAMETER_UNABLE_TO_COMPLY".

Otherwise, the ProSe Function shall acknowledge the reception of the ProSe Proximity Alert request and shall set the Result Code to "DIAMETER_SUCCESS" in the response. The ProSe Function shall forward the Proximity Alert to the requesting UE.

5.10 ProSe Direct Discovery Authorization Update

5.10.1 General

The ProSe Direct Discovery Authorization Update Procedure shall be used between the ProSe Function in the HPLMN and the ProSe Function in a local PLMN or VPLMN to update authorization for access to the discovery resources and perform ProSe Direct Discovery. The procedure shall be invoked by the ProSe Function in the HPLMN and is used:

- to provide the ProSe Function in Local PLMN with an update for banned users.

This procedure is mapped to the commands ProSe-Discovery-Request/Answer (PDR/PDA) in the Diameter application specified in clause 6.

Table 5.10.1-1 specifies the involved information elements for the request.

Table 5.10.1-2 specifies the involved information elements for the answer.

Table 5.10.1-1: ProSe Direct Discovery Authorization Update Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Discovery Authorization Request (See 6.3.53)	Discovery-Auth-Request	M	This information element shall contain the information elements used in discovery authorization request.
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Discovery Entry ID (See 6.3.59)	Discovery-Entry-ID	C	This Information Element contains the discovery entry ID used by the sending ProSe Function to identify the discovery entry related to this request.

Table 5.10.1-2: ProSe Direct Discovery Authorization Update Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - Announcing Not Authorized - No Associated Discovery Filter
Discovery Authorization Response (See 6.3.53)	Discovery-Auth-Response	C	This information element shall contain the information elements used in discovery authorization response. This information element shall be present if the Result Code AVP is DIAMETER_SUCCESS.
Discovery Entry ID (See 6.3.59)	Discovery-Entry-ID	C	This Information Element contains the discovery entry ID used by the sending ProSe Function to identify the discovery entry related to this request.

5.10.2 Detailed behaviour of the HPLMN ProSe Function

The ProSe Function in the HPLMN shall make use of this procedure to revoke permissions to discover a ProSe Restricted Code given to users served by the ProSe Function located in a Local PLMN. The HPLMN ProSe Function shall include in the request the Discovery Entry ID and shall include in the Discovery Authorization Request the Discovery Type set to "MONITORING_UPDATE_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the application identity, the ProSe-restricted-Code, Banned RPAUID and Banned PDUID of a monitoring target. When receiving the ProSe Direct Discovery Authorization Update response with the Result Code set to "DIAMETER_SUCCESS" for a request with the Discovery Type set to "MONITORING_UPDATE_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the HPLMN ProSe Function shall start a timer to wait for the ProSe Function in Local PLMN/VPLMN to report the result of the Direct Discovery Authorization Update procedure for the monitoring operation, i.e., whether the ProSe Discovery Filter(s) for monitoring this ProSe Restricted Code has been successfully revoked in the banned UE.

5.10.3 Detailed behaviour of the ProSe Function in the local PLMN or VPLMN

When receiving a ProSe Direct Discovery Authorization Update request, the ProSe Function in the local PLMN or VPLMN shall process the request in the following order to check whether the monitoring is authorized.

- The ProSe function shall check if the Banned PDUID belongs to its own PLMN.
- If not, the experimental result code shall be set to "DIAMETER_ERROR_INVALID_TARGET_PDUID" in the response sent by the ProSe Function.
- If the Banned PDUID belongs to its own PLMN, the ProSe function may check if the requesting RPAUID is allowed to discover the Banned RPAUID.
 - If not, the experimental result code shall be set to "DIAMETER_ERROR_INVALID_TARGET_RPAUID" in the response sent by the ProSe Function;
 - Otherwise, the ProSe Function shall set the result code to "DIAMETER_SUCCESS" in the response.

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall set the Result Code to "DIAMETER_UNABLE_TO_COMPLY".

5.11 ProSe Direct Discovery Authorization Update Result

5.11.1 General

The ProSe Direct Discovery Authorization Update Result Procedure shall be used between the ProSe Function in the local PLMN and the ProSe Function in the HPLMN to report the result of ProSe Direct Discovery Authorization Update in Local PLMN to the ProSe Function in the HPLMN. In this case the procedure shall be invoked by the ProSe Function in the local PLMN and is used:

- to report the result of Direct Discovery Authorization Update procedure initiated by the ProSe Function in the HPLMN.

This procedure is mapped to the commands ProSe-Discovery-Request/Answer (PDR/PDA) in the Diameter application specified in clause 6.

Table 5.11.1-1 specifies the involved information elements for the request.

Table 5.11.1-2 specifies the involved information elements for the answer.

Table 5.11.1-1: ProSe Direct Discovery Authorization Update Result Request

Information element name	Mapping to Diameter AVP	Cat.	Description
Discovery Authorization Request (See 6.3.53)	Discovery-Auth-Request	M	This information element shall contain the information elements used in discovery authorization request.
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Discovery Entry ID (See 6.3.59)	Discovery-Entry-ID	C	This Information Element contains the discovery entry ID used by the sending ProSe Function to identify the discovery entry related to this request.

Table 5.11.1-2: ProSe Direct Discovery Authorization Update Result Answer

Information element name	Mapping to Diameter AVP	Cat.	Description
Supported Features (See 6.3.24)	Supported-Features	O	If present, this information element shall contain the list of features supported by the origin host.
Result (See 6.4)	Result-Code / Experimental-Result	M	This IE shall contain the result of the operation. The Result-Code AVP shall be used to indicate success / errors as defined in the Diameter Base Protocol. The Experimental-Result AVP shall be used for PC6/PC7 errors. This is a grouped AVP which shall contain the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP. The following errors are applicable: - Announcing Not Authorized - No Associated Discovery Filter
Discovery Authorization Response (See 6.3.53)	Discovery-Auth-Response	C	This information element shall contain the information elements used in discovery authorization response. This information element shall be present if the Result Code AVP is DIAMETER_SUCCESS.
Discovery Entry ID (See 6.3.59)	Discovery-Entry-ID	C	This Information Element contains the discovery entry ID used by the sending ProSe Function to identify the discovery entry related to this request.

5.11.2 Detailed behaviour of the ProSe Function in the local PLMN

The ProSe Function in the local PLMN shall make use of this procedure to report to the ProSe Function in HPLMN the result of the ProSe Direct Discovery Authorization Update for restricted ProSe Direct Discovery. The local PLMN ProSe Function shall include in the Discovery Authorization Update Result Request the Discovery Entry ID and the Discovery Type set to "MONITORING_RESPONSE_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the application identity, the ProSe-Restricted-Code, Banned RPAUID and Banned PDUID of a monitoring target, result of the monitoring update operation.

5.11.3 Detailed behaviour of the HPLMN ProSe Function

When receiving a ProSe Direct Discovery Authorization Update Result request (Discovery Type set to "MONITORING_RESPONSE_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY" in the PDR command), the ProSe Function in the HPLMN shall check whether there exists a discovery entry matching the Discovery Entry ID included in the request. If yes, then the ProSe Function shall update the result for the given ProSe Restricted Code or ProSe Restricted Code Prefix in this entry regarding the revocation operation for banned RPAUID and banned PDUID indicated in the request message.

- If not, the experimental result code shall be set to "DIAMETER_ERROR_NO_ASSOCIATED_RESTRICTED_CODE" in the response sent by the ProSe Function.

- If it exists, the ProSe Function shall set the result code to "DIAMETER_SUCCESS" in the Discovery AuthorizationUpdate Result response and shall store the outcome of the operation provided to be able to forward this to the UE.

If the ProSe Function cannot fulfil the received request for reasons not stated in the above steps, e.g. due to a database error or any of the required actions cannot be performed, it shall set the Result Code to "DIAMETER_UNABLE_TO_COMPLY".

6 Protocol Specification and Implementation

6.1 Introduction

6.1.1 Use of Diameter base protocol

The Diameter Base Protocol as specified in IETF RFC 3588 [7] shall apply except as modified by the defined support of the methods and the defined support of the commands and AVPs, result and error codes as specified in this specification. Unless otherwise specified, the procedures (including error handling and unrecognised information handling) shall be used unmodified.

6.1.2 Securing Diameter Messages

For secure transport of Diameter messages, see 3GPP TS 33.210 [8].

6.1.3 Accounting functionality

Accounting functionality (Accounting Session State Machine, related command codes and AVPs) shall not be used on the PC6/PC7 interfaces.

6.1.4 Use of sessions

Between the ProSe Functions, Diameter sessions shall be implicitly terminated. An implicitly terminated session is one for which the server does not maintain state information. The client shall not send any re-authorization or session termination requests to the server.

The Diameter base protocol includes the Auth-Session-State AVP as the mechanism for the implementation of implicitly terminated sessions.

The client (server) shall include in its requests (responses) the Auth-Session-State AVP set to the value NO_STATE_MAINTAINED (1), as described in IETF RFC 3588 [7]. As a consequence, the server shall not maintain any state information about this session and the client shall not send any session termination request. Neither the Authorization-Lifetime AVP nor the Session-Timeout AVP shall be present in requests or responses.

6.1.5 Transport protocol

Diameter messages over the PC6/PC7 interfaces shall make use of SCTP IETF RFC 4960 [9].

6.1.6 Routing considerations

This subclause specifies the use of the Diameter routing AVPs Destination-Realm and Destination-Host.

The Destination-Realm AVP shall contain the network domain name of the targeted ProSe Function. The network domain name is either known by the sending ProSe Function or derived from the PLMN-Id of the targeted ProSe Function to construct the EPC Home Network Realm/Domain, as indicated in 3GPP TS 23.003 [4], subclause 19.2.

If a ProSe Function knows the address/name of the ProSe Function in charge of a given UE, and the associated network domain name, both the Destination-Realm and Destination-Host AVPs shall be present in the request.

If a ProSe Function knows only the network domain name, the Destination-Realm AVP shall be present and the command shall be routed to the next Diameter node.

Consequently, the Destination-Realm AVP is declared as mandatory and the Destination-Host AVP is declared as optional in the ABNF for all requests initiated by a ProSe Function.

If the Vendor-Specific-Application-ID AVP is received in any of the commands, it may be ignored by the receiving node, and it shall not be used for routing purposes.

NOTE: The Vendor-Specific-Application-ID can be included as an optional AVP in all commands in order to ensure interoperability with diameter agents following a strict implementation of IETF RFC 3588 [7], by which messages not including this AVP will be rejected. IETF RFC 3588 [7] indicates that the AVP is present in all proxiable commands, such as those defined in this specification, despite the fact that the contents of this AVP are redundant since the Application ID is already present in the command header. This AVP can be removed in subsequent revisions of this specification, once the new diameter base protocol specification will be adopted by 3GPP.

6.1.7 Advertising Application Support

The ProSe Functions shall advertise support of the Diameter Inter ProSe Functions Application by including the value of the application identifier in the Auth-Application-Id AVP within the Vendor-Specific-Application-Id grouped AVP of the Capabilities-Exchange-Request and Capabilities-Exchange-Answer commands.

The vendor identifier value of 3GPP (10415) shall be included in the Supported-Vendor-Id AVP of the Capabilities-Exchange-Request and Capabilities-Exchange-Answer commands, and in the Vendor-Id AVP within the Vendor-Specific-Application-Id grouped AVP of the Capabilities-Exchange-Request and Capabilities-Exchange-Answer commands.

The Vendor-Id AVP included in Capabilities-Exchange-Request and Capabilities-Exchange-Answer commands that is not included in the Vendor-Specific-Application-Id AVPs as described above shall indicate the manufacturer of the Diameter node as per IETF RFC 3588 [7].

6.1.8 Diameter Application Identifier

The Diameter Inter ProSe Functions Application protocol shall be defined as an IETF vendor specific Diameter application, where the vendor is 3GPP. The vendor identifier assigned by IANA to 3GPP (<http://www.iana.org/assignments/enterprise-numbers>) is 10415.

The Diameter application identifier assigned to the Diameter Inter ProSe Functions application is 16777340 (allocated by IANA). The same Diameter application identifier is used over the PC6 interface and the PC7 interface.

6.1.9 Use of the Supported-Features AVP

When new functionality is introduced on the PC6/PC7 interfaces, it should be defined as optional. If backwards incompatible changes cannot be avoided, the new functionality shall be introduced as a new feature and support advertised with the Supported-Features AVP. The usage of the Supported-Features AVP on the PC6/PC7 interfaces is consistent with the procedures for the dynamic discovery of supported features as defined in subclause 7.2 of 3GPP TS 29.229 [10].

When extending the application by adding new AVPs for a feature, the new AVPs shall have the M bit cleared and the AVP shall not be defined mandatory in the command ABNF.

As defined in 3GPP TS 29.229 [10], the Supported-Features AVP is of type grouped and contains the Vendor-Id, Feature-List-ID and Feature-List AVPs. On the all reference points as specified in this specification, the Supported-Features AVP is used to identify features that have been defined by 3GPP and hence, for features defined in this document, the Vendor-Id AVP shall contain the vendor ID of 3GPP (10415). If there are multiple feature lists defined for the reference point, the Feature-List-ID AVP shall differentiate those lists from one another.

6.2 Commands

6.2.1 Introduction

This subclause defines the Command code values and related ABNF for each command described in this specification.

6.2.2 Command-Code values

This subclause defines Command-Code values for the Diameter Inter ProSe Functions application used over the PC6/PC7 interfaces as allocated by IANA.

Every command is defined by means of the ABNF syntax IETF RFC 5234 [11], according to the rules in IETF RFC 3588 [7]. In the case, the definition and use of an AVP is not specified in this document, the guidelines in IETF RFC 3588 [7] shall apply.

NOTE: For this release, the Vendor-Specific-Application-ID is included as an optional AVP in all commands in order to ensure interoperability with diameter agents following a strict implementation of IETF RFC 3588 [7], by which messages not including this AVP will be rejected. IETF RFC 3588 [7] indicates that the AVP shall be present in all proxiable commands, such as those specified here, despite that the contents of this AVP are redundant since the Application ID is already present in the command header. This AVP may be removed in subsequent revisions of this specification, once the diameter base protocol is updated accordingly.

The following Command Codes are defined in this specification:

Table 6.2.2-1: Command-Code values for Diameter ProSe Inter Functions Application

Command-Name	Abbreviation	Code	Clause
ProSe-Authorization-Request	PAR	8388668	6.2.3
ProSe-Authorization-Answer	PAA	8388668	6.2.4
ProSe-Discovery-Request	PDR	8388669	6.2.5
ProSe-Discovery-Answer	PDA	8388669	6.2.6
ProSe-Match-Request	PMR	8388670	6.2.7
ProSe-Match-Answer	PMA	8388670	6.2.8
ProSe-Match-Report-Info-Request	PIR	8388671	6.2.9
ProSe-Match-Report-Info-Answer	PIA	8388671	6.2.10
ProSe-Proximity-Request	PRR	8388672	6.2.11
ProSe-Proximity-Answer	PRA	8388672	6.2.12
ProSe-Location-Update-Request	PLR	8388673	6.2.13
ProSe-Location-Update-Answer	PLA	8388673	6.2.14
ProSe-Alert-Request	ALR	8388674	6.2.15
ProSe-Alert-Answer	ALA	8388674	6.2.16
ProSe-Cancellation-Request	PCR	8388675	6.2.17
ProSe-Cancellation-Answer	PCA	8388675	6.2.18

For these commands, the Application-ID field shall be set to 16777340 (application identifier of the Diameter Inter ProSe Functions interface application, allocated by IANA).

6.2.3 ProSe-Authorization-Request (PAR) Command

The ProSe-Authorization-Request (PAR) Command, indicated by the Command-Code field set to 8388668 and the "R" bit set in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function in Local PLMN/VPLMN.

Message Format

```
< ProSe-Authorization-Request > ::= < Diameter Header: 8388668, REQ, PXY, 16777340 >
                                     < Session-Id >
                                     [ DRMP ]
```

```

[ Vendor-Specific-Application-Id ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
[ Destination-Host ]
{ Destination-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
{ User-Identity }
{ Visited-PLMN-Id }
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.4 ProSe-Authorization-Answer (PAA) Command

The ProSe-Authorization-Answer (PAA) Command, indicated by the Command-Code field set to 8388668 and the "R" bit cleared in the Command Flags field, is sent from the ProSe Function in Local PLMN/VPLMN to the ProSe Function in the HPLMN.

Message Format

```

< ProSe-Authorization-Answer > ::= < Diameter Header: 8388668, PXY, 16777340 >
< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
[ Result-Code ]
[ Experimental-Result ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
[ OC-OLR ]
[ ProSe-Direct-Allowed ]
[ Validity-Time-Announce ]
[ Validity-Time-Monitor ]
[ Validity-Time-Communication ]
[ Authorized-Discovery-Range ]
*[ AVP ]
*[ Failed-AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.5 ProSe-Discovery-Request (PDR) Command

The ProSe-Discovery-Request (PDR) Command, indicated by the Command-Code field set to 8388669 and the "R" bit set in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function in Local PLMN.

Message Format

```

< ProSe-Discovery-Request > ::= < Diameter Header: 8388669, REQ, PXY, 16777340 >
< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
[ Destination-Host ]
{ Destination-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]

```

```

{ Discovery-Auth-Request }
[ Discovery-Entry-ID ]
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.6 ProSe-Discovery-Answer (PDA) Command

The ProSe-Discovery-Answer (PDA) Command, indicated by the Command-Code field set to 8388669 and the "R" bit cleared in the Command Flags field, is sent from the ProSe Function in Local PLMN to the ProSe Function in the HPLMN.

Message Format

```

< ProSe-Discovery-Answer > ::= < Diameter Header: 8388669, PXY, 16777340 >
< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
[ Result-Code ]
[ Experimental-Result ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
[ OC-OLR ]
[ Discovery-Auth-Response ]
[ Discovery-Entry-ID ]
*[ AVP ]
*[ Failed-AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.7 ProSe-Match-Request (PMR) Command

The ProSe-Match-Request (PMR) Command, indicated by the Command-Code field set to 8388670 and the "R" bit set in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function in Local PLMN.

Message Format

```

< ProSe-Match-Request > ::= < Diameter Header: 8388670, REQ, PXY, 16777340 >
< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
[ Destination-Host ]
{ Destination-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
{ Match-Request }
[ PMR-Flags ]
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.8 ProSe-Match-Answer (PMA) Command

The ProSe-Match-Answer (PMA) Command, indicated by the Command-Code field set to 8388670 and the "R" bit cleared in the Command Flags field, is sent from the ProSe Function in Local PLMN to the ProSe Function in the HPLMN.

Message Format

```
< ProSe-Match-Answer > ::= < Diameter Header: 8388670, PXY, 16777340 >
    < Session-Id >
    [ DRMP ]
    [ Vendor-Specific-Application-Id ]
    [ Result-Code ]
    [ Experimental-Result ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    *[ Supported-Features ]
    [ OC-Supported-Features ]
    [ OC-OLR ]
    *[ Match-Report ]
    *[ AVP ]
    *[ Failed-AVP ]
    *[ Proxy-Info ]
    *[ Route-Record ]
```

6.2.9 ProSe-Match-Report-Info-Request (PIR) Command

The ProSe-Match-Report-Info-Request (PIR) Command, indicated by the Command-Code field set to 8388671 and the "R" bit set in the Command Flags field, is sent from the ProSe Function in the HPLMN of the monitoring UE to the ProSe Function of the PLMN in which the announcing UE is roaming.

Message Format

```
< ProSe-Match-Report-Info-Request > ::= < Diameter Header: 8388671, REQ, PXY, 16777340 >
    < Session-Id >
    [ DRMP ]
    [ Vendor-Specific-Application-Id ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ Destination-Host ]
    { Destination-Realm }
    *[ Supported-Features ]
    [ OC-Supported-Features ]
    { Match-Report-Info }
    *[ AVP ]
    *[ Proxy-Info ]
    *[ Route-Record ]
```

6.2.10 ProSe-Match-Report-Info-Answer (PIA) Command

The ProSe-Match-Report-Info-Answer (PIA) Command, indicated by the Command-Code field set to 8388671 and the "R" bit cleared in the Command Flags field, is sent from the ProSe Function of the PLMN in which the announcing UE is roaming to the ProSe Function in the HPLMN of the monitoring UE.

Message Format

```
< ProSe-Match-Report-Info-Answer > ::= < Diameter Header: 8388671, PXY, 16777340 >
```

```

< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
[ Result-Code ]
[ Experimental-Result ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
[ OC-OLR ]
*[ AVP ]
*[ Failed-AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.11 ProSe-Proximity-Request (PRR) Command

The ProSe-Proximity-Request (PRR) Command, indicated by the Command-Code field set to 8388672 and the "R" bit set in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function of another PLMN.

Message Format

```

< ProSe-Proximity-Request > ::= < Diameter Header: 8388672, REQ, PXY, 16777340 >
< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
[ Destination-Host ]
{ Destination-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
{ PRR-Flags }
{ Requesting-EPUID }
{ Targeted-EPUID }
{ Time-Window }
{ Location-Estimate }
[ Location-Update-Trigger ]
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.12 ProSe-Proximity-Answer (PRA) Command

The ProSe-Proximity-Answer (PRA) Command, indicated by the Command-Code field set to 8388672 and the "R" bit cleared in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function of another PLMN.

Message Format

```

< ProSe-Proximity-Answer > ::= < Diameter Header: 8388672, PXY, 16777340 >
< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
[ Result-Code ]
[ Experimental-Result ]

```

```

{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
[ OC-OLR ]
[ Location-Estimate ]
[WLAN-Link-Layer-Id ]
*[ AVP ]
*[ Failed-AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.13 ProSe-Location-Update-Request (PLR) Command

The ProSe-Location-Update-Request (PLR) Command, indicated by the Command-Code field set to 8388673 and the "R" bit set in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function of another PLMN.

Message Format

```

< ProSe-Location-Update-Request > ::= < Diameter Header: 8388673, REQ, PXY, 16777340 >
< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
[ Destination-Host ]
{ Destination-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
{ Targeted-EPUID }
{ Location-Estimate }
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.14 ProSe-Location-Update-Answer (PLA) Command

The ProSe-Location-Update-Answer (PLA) Command, indicated by the Command-Code field set to 8388673 and the "R" bit cleared in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function of another PLMN.

Message Format

```

< ProSe-Location-Update-Answer > ::= < Diameter Header: 8388673, PXY, 16777340 >
< Session-Id >
[ DRMP ]
[ Vendor-Specific-Application-Id ]
[ Result-Code ]
[ Experimental-Result ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
*[ Supported-Features ]
[ OC-Supported-Features ]
[ OC-OLR ]
*[ AVP ]
*[ Failed-AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2.15 ProSe-Aler-Request (ALR) Command

The ProSe-Aler-Request (ALR) Command, indicated by the Command-Code field set to 8388674 and the "R" bit set in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function of another PLMN.

Message Format

```
< ProSe-Aler-Request > ::= < Diameter Header: 8388674, REQ, PXY, 16777340 >
    < Session-Id >
    [ DRMP ]
    [ Vendor-Specific-Application-Id ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ Destination-Host ]
    { Destination-Realm }
    *[ Supported-Features ]
    [ OC-Supported-Features ]
    { App-Layer-User-Id }
    { Targeted-EPUID }
    [ Assistance-Info ]
    *[ AVP ]
    *[ Proxy-Info ]
    *[ Route-Record ]
```

6.2.16 ProSe-Aler-Answer (ALA) Command

The ProSe-Aler-Answer (ALA) Command, indicated by the Command-Code field set to 8388674 and the "R" bit cleared in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function of another PLMN.

Message Format

```
< ProSe-Aler-Answer > ::= < Diameter Header: 8388674, PXY, 16777340 >
    < Session-Id >
    [ DRMP ]
    [ Vendor-Specific-Application-Id ]
    [ Result-Code ]
    [ Experimental-Result ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    *[ Supported-Features ]
    [ OC-Supported-Features ]
    [ OC-OLR ]
    *[ AVP ]
    *[ Failed-AVP ]
    *[ Proxy-Info ]
    *[ Route-Record ]
```

6.2.17 ProSe-Cancellation-Request (PCR) Command

The ProSe-Cancellation-Request (PCR) Command, indicated by the Command-Code field set to 8388675 and the "R" bit set in the Command Flags field, is sent from the ProSe Function in the HPLMN to the ProSe Function in a local/visited PLMN.

Message Format

```

< ProSe-Cancellation-Request > ::=
  < Diameter Header: 8388675, REQ, PXY, 16777340 >
  < Session-Id >
  [ DRMP ]
  [ Vendor-Specific-Application-Id ]
  { Auth-Session-State }
  { Origin-Host }
  { Origin-Realm }
  [ Destination-Host ]
  { Destination-Realm }
  *[ Supported-Features ]
  [ OC-Supported-Features ]
  { Requesting-EPUIID }
  { Targeted-EPUIID }
  *[ AVP ]
  *[ Proxy-Info ]
  *[ Route-Record ]

```

6.2.18 ProSe-Cancellation-Answer (PCA) Command

The ProSe-Cancellation-Answer (PCA) Command, indicated by the Command-Code field set to 8388675 and the "R" bit cleared in the Command Flags field, is sent from the ProSe Function in a local/visited PLMN to the ProSe Function in the HPLMN.

Message Format

```

< ProSe-Cancellation-Answer > ::=
  < Diameter Header: 8388675, PXY, 16777340 >
  < Session-Id >
  [ DRMP ]
  [ Vendor-Specific-Application-Id ]
  [ Result-Code ]
  [ Experimental-Result ]
  { Auth-Session-State }
  { Origin-Host }
  { Origin-Realm }
  *[ Supported-Features ]
  [ OC-Supported-Features ]
  [ OC-OLR ]
  *[ AVP ]
  *[ Failed-AVP ]
  *[ Proxy-Info ]
  *[ Route-Record ]

```

6.3 Information Elements

6.3.1 General

The following table (table 6.3.1-1) specifies the Diameter AVPs defined for the PC6/PC7 interfaces, their AVP Code values, types, possible flag values and whether or not the AVP may be encrypted. The Vendor-ID header of all AVPs defined in this specification shall be set to 3GPP (10415).

For all AVPs which contain bit masks and are of the type Unsigned32 e.g., PRR-Flags, bit 0 shall be the least significant bit. For example, to get the value of bit 0, a bit mask of 0x0001 shall be used.

Table 6.3.1-1: PC6/PC7 specific Diameter AVPs

Attribute Name	AVP Code	Clause defined	Value Type	AVP Flag rules				May Encr.
				Must	May	Should not	Must not	
App-Layer-User-Id	3801	6.3.2	UTF8String	M, V				No
Assistance-info	3802	6.3.3	Grouped	M, V				No
Assistance-Info-Validity-Timer	3803	6.3.4	Unsigned32	M, V				No
Discovery-Type	3804	6.3.5	Unsigned32	M, V				No
Filter-Id	3805	6.3.9	OctetString	M, V				No
MAC-Address	3806	6.3.11	UTF8String	M, V				No
Match-Report	3807	6.3.12	Grouped	M, V				No
Operating-Channel	3808	6.3.14	Unsigned32	M, V				No
P2P-Features	3809	6.3.15	Unsigned32	M, V				No
ProSe-App-Code	3810	6.3.16	OctetString	M, V				No
ProSe-App-Id	3811	6.3.17	UTF8String	M, V				No
ProSe-App-Mask	3812	6.3.18	OctetString	M, V				No
ProSe-Discovery-Filter	3813	6.3.20	Grouped	M, V				No
PRR-Flags	3814	6.3.21	Unsigned32	M, V				No
ProSe-Validity-Timer	3815	6.3.22	Unsigned32	M, V				No
Requesting-EPUID	3816	6.3.23	UTF8String	M, V				No
Targeted-EPUID	3817	6.3.26	UTF8String	M, V				No
Time-Window	3818	6.3.27	Unsigned32	M, V				No
WiFi-P2P-Assistance-Info	3819	6.3.30	Grouped	M, V				No
WLAN-Assistance-Info	3820	6.3.31	Grouped	M, V				No
WLAN-Link-Layer-Id	3821	6.3.32	OctetString	M, V				No
WLAN-Link-Layer-Id-List	3822	6.3.33	Grouped	M, V				No
Location-Update-Trigger	3823	6.3.42	Grouped	M, V				No
Location-Update-Event-Type	3824	6.3.43	Unsigned32	M, V				No
Change-Of-Area-Type	3825	6.3.44	Grouped	M, V				No
Location-Update-Event-Trigger	3826	6.3.45	Unsigned32	M, V				No
Report-Cardinality	3827	6.3.46	Enumerated	M, V				No
Minimum-Interval-Time	3828	6.3.47	Unsigned32	M, V				No
Periodic-Location-Type	3829	6.3.48	Grouped	M, V				No
Location-Report-Interval-Time	3830	6.3.49	Unsigned32	M, V				No
Total-Number-Of-Reports	3831	6.3.50	Unsigned32	M, V				No
Validity-Time-Announce	3832	6.3.36	Unsigned32	M, V				No
Validity-Time-Monitor	3833	6.3.37	Unsigned32	M, V				No
Validity-Time-Communication	3834	6.3.38	Unsigned32	M, V				No
ProSe-App-Code-Info	3835	6.3.39	Grouped	M, V				No
MIC	3836	6.3.40	OctetString	M, V				No
UTC-based-Counter	3837	6.3.41	Unsigned32	M, V				No
ProSe-Match-Refresh-Timer	3838	6.3.52	Unsigned32	M, V				No
ProSe-Metadata-Index-Mask	3839	6.3.60	OctetString	V			M	No
App-Identifier	3840	6.3.61	Group	V			M	No
OS-ID	3841	6.3.62	OctetString	V			M	No
OS-App-ID	3842	6.3.63	UTF8String	V			M	No
Requesting-RPAUID	3843	6.3.64	UTF8String	V			M	No
Target-RPAUID	3844	6.3.65	UTF8String	V			M	No
Target-PDUID	3845	6.3.66	OctetString	V			M	No
ProSe-Restricted-Code	3846	6.3.67	OctetString	V			M	No
ProSe-Restricted-Code-Suffix-Range	3847	6.3.68	OctetString	V			M	No
Beginning-Suffix	3848	6.3.69	OctetString	V			M	No
Ending-Suffix	3849	6.3.70	OctetString	V			M	No
Discovery-Entry-ID	3850	6.3.59	Unsigned32	V			M	No
Match-Timestamp	3851	6.3.71	Time	V			M	No
PMR-Flags	3852	6.3.57	Unsigned32	M, V				No
ProSe-Application-Metadata	3853	6.3.58	UTF8String	M, V				No
Discovery-Auth-Request	3854	6.3.53	Grouped	M, V				No
Discovery-Auth-Response	3855	6.3.54	Grouped	M, V				No
Match-Request	3856	6.3.55	Grouped	M, V				No
Match-Report-Info	3857	6.3.56	Grouped	M, V				No
Banned-RPAUID	3858	6.3.73	UTF8String	V			M	No
Banned-PDUID	3859	6.3.74	OctetString	V			M	No

Attribute Name	AVP Code	Clause defined	Value Type	AVP Flag rules				
				Must	May	Should not	Must not	May Encr.
Code-Receiving-Security-Material	38xa	6.3.75	Grouped	V			M	No
Code-Sending-Security-Material	38xb	6.3.76	Grouped	V			M	No
DUSK	38xc	6.3.77	OctetString	V			M	No
DUIK	38xd	6.3.78	OctetString	V			M	No
DUCK	38xe	6.3.79	OctetString	V			M	No
MIC-Check-indicator	38xf	6.3.80	Unsigned32	V			M	No
Encrypted-Bitmask	38xg	6.3.81	OctetString	V			M	No
ProSe-App-Code-Suffix-Range	38xh	6.3.82	OctetString	V			M	No
NOTE 1: The AVP header bit denoted as "M", indicates whether support of the AVP is required. The AVP header bit denoted as "V" indicates whether the optional Vendor-ID field is present in the AVP header. For further details, see IETF RFC 3588 [7].								
NOTE 2: If the M-bit is set for an AVP and the receiver does not understand the AVP, it shall return a rejection. If the M-bit is not set for an AVP, the receiver shall not return a rejection, whether or not it understands the AVP. If the receiver understands the AVP but the M-bit value does not match with the definition in this table, the receiver shall ignore the M-bit.								

The following table (table 6.3.1-2) specifies the Diameter AVPs re-used by the PC6/PC7 interfaces from existing Diameter Applications, including a reference to their respective specifications and when needed, a short description of their use within PC6/PC7 interfaces.

Any other AVPs from existing Diameter Applications, except for the AVPs from Diameter Base Protocol, do not need to be supported. The AVPs from Diameter Base Protocol are not included in table 6.3.1-2.

Table 6.3.1-2: PC6/PC7 re-used Diameter AVPs

Attribute Name	Reference	Comments	M-bit
Supported-Features	3GPP TS 29.229 [10]		
EAP-Master-Session-Key	IETF RFC 4072 [12]		
Feature-List-ID	3GPP TS 29.229 [10]		
Feature-List	3GPP TS 29.229 [10]	See subclause 7.3.10	
MSISDN	3GPP TS 29.329 [5]		
User-Name	IETF RFC 3588 [7]		
Location-Estimate	3GPP TS 32.299 [13]		
ProSe-Direct-Allowed	3GPP TS 29.344 [14]		
Authorized-Discovery-Range	3GPP TS 29.344 [14]		
SSID	3GPP TS 29.273 [15]		
Visited-PLMN-Id	3GPP TS 29.272 [16]		
User-Identifier	3GPP TS 29.336 [18]		
OC-Supported-Features	IETF RFC 7683 [21]	See subclause 6.3.34	Must set
OC-OLR	IETF RFC 7683 [21]	See subclause 6.3.35	Must set
DRMP	IETF draft-ietf-dime-drmp-03 [27]	see section 6.3.72	Must not set
Service-Result	3GPP TS 29.336 [18]		
NOTE 1: The M-bit settings for re-used AVPs override those of the defining specifications that are referenced. Values include: "Must set", "Must not set". If the M-bit setting is blank, then the defining specification applies.			
NOTE 2: If the M-bit is set for an AVP and the receiver does not understand the AVP, it shall return a rejection. If the M-bit is not set for an AVP, the receiver shall not return a rejection, whether or not it understands the AVP. If the receiver understands the AVP but the M-bit value does not match with the definition in this table, the receiver shall ignore the M-bit.			

6.3.2 App-Layer-User-Id

The App-Layer-User-Id AVP is of type UTF8String. This AVP contains an identity identifying a user within the context of a specific application (e.g. alice@social.net).

6.3.3 Assistance-info

The Assistance-Info AVP is of type Grouped. It shall contain the information for direct discovery and communications between UEs.

The AVP format shall conform to:

```
Assistance-Info ::= <AVP header: 3802 10415>
                    [ WLAN-Assistance-Info ]
                    *[AVP]
```

6.3.4 Assistance-Info-Validity-Timer

The Assistance-Info-Validity-Timer AVP is of type Unsigned32 and it shall contain the maximum number of seconds of validity of the provided assistance information.

6.3.5 Discovery-Type

The Discovery-Type AVP is of type Unsigned32 and contains a 32-bit address space representing types of Direct Discovery Authorization Request. The following values are defined:

ANNOUNCING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY (0)

This value is used when the Direct Discovery Authorization Request message is sent for a UE requesting authorization for announcing in open Prose Direct Discovery (Model A).

MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY (1)

This value is used when the Direct Discovery Authorization Request message is sent for a UE requesting authorization for monitoring in open Prose Direct Discovery (Model A).

ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY (2)

This value is used when the Direct Discovery Authorization Request message is sent for a UE requesting authorization for announcing in restricted ProSe Direct Discovery (Model A).

MONITORING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY (3)

This value is used when the Direct Discovery Authorization Request message is sent for a UE requesting authorization for monitoring in restricted ProSe Direct Discovery (Model A).

DISCOVEREE_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY (4)

This value is used when the Direct Discovery Authorization Request message is sent for a discoveree UE requesting authorization for monitoring in restricted ProSe Direct Discovery (Model B).

DISCOVERER_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY (5)

This value is used when the Direct Discovery Authorization Request message is sent to the ProSe Function in local PLMN for a discoverer UE requesting authorization for announcing in restricted ProSe Direct Discovery (Model B).

DISCOVERER_ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY (6)

This value is used when the Direct Discovery Authorization Request message is sent to the ProSe Function in the visited PLMN for a discoverer UE requesting authorization for announcing in restricted ProSe Direct Discovery (Model B).

MONITORING_UPDATE_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY (7)

This value is used when the Direct Discovery Authorization Request message is sent for the ProSe Function requesting to ban a user of an authorization for monitoring in restricted ProSe Direct Discovery (Model A).

MONITORING_RESPONSE_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY (8)

This value is used when the Direct Discovery Authorization Request message is sent for the ProSe Function reporting the result of an authorization for monitoring in restricted ProSe Direct Discovery (Model A).

6.3.6 EAP-Master-Session-Key

The EAP-Master-Session-Key AVP is of type OctetString and it shall contains keying material for protecting the communications between UEs. This AVP is defined in the IETF RFC 4072 [12]

6.3.7 Feature-List-ID AVP

The syntax of this AVP is defined in 3GPP TS 29.229 [10]. For this release, the Feature-List-ID AVP value shall be set to 1.

6.3.8 Feature-List AVP

The syntax of this AVP is defined in 3GPP TS 29.229 [10]. A null value indicates that there is no feature used by the application.

NOTE: There is no feature defined for this release.

6.3.9 Filter-Id

The Filter-Id AVP is of type OctetString. This AVP shall contain the identifier of a Discovery Filter.

6.3.10 Location-Estimate

The Location-Estimate AVP is of type OctetString and it shall contain an estimate of the location of an MS in universal coordinates and the accuracy of the estimate. This AVP is defined in the 3GPP TS 32.299 [13].

6.3.11 MAC-Address

The MAC-Address AVP is of type UTF8String and it shall contain a 6-octet MAC address used as link layer identifier for discovery and communication. It shall be encoded in upper-case ASCII characters with the octet values separated by dash characters. It shall contain a string of 17 octets. Example: "00-10-A4-23-19-C0".

6.3.12 Match-Report

The Match-Report AVP is of type Grouped. It shall contain the information elements used in ProSe Match Report answer.

The AVP format shall conform to:

```
Match-Report ::= <AVP header: 3807 10415>
                { Discovery-Type }
                [ ProSe-App-Code ]
                [ ProSe-Metadata-Index-Mask ]
                [ ProSe-App-Id ]
                [ ProSe-Validity-Timer ]
                [ ProSe-Match-Refresh-Timer ]
                [ ProSe-Application-Metadata ]
                *[AVP]
```

The valid value for Discovery-Type for Match-Report AVP is:
"MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY",

When the Discovery-Type is set to "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the Match-Report shall contain a ProSe Application Code, the associated ProSe Application ID Name, the validity time for which the ProSe Application Code is valid, and the associated match report refresh timer.

If the ProSe Application Code contains a metadata index, a ProSe-Metadata-Index-Mask AVP shall be provided for this ProSe Application Code.

6.3.13 MSISDN

The MSISDN AVP is of type OctetString. This AVP contains an MSISDN, in international number format as described in ITU-T Rec E.164 [19]. This AVP is defined in the 3GPP TS 29.329 [5].

6.3.14 Operating-Channel

The Operating-Channel AVP is of type Unsigned32 and it shall contain the operating channel in MHz on which Wi-Fi P2P discovery and communication should take place.

6.3.15 P2P-Features

The P2P-Features AVP is of type Unsigned32 and it shall contain a bit mask. The meaning of the bits shall be as defined in table 6.3.15-1:

Table 6.3.15-1: P2P-Features

Bit	Name	Description
0	Group Owner Indication	This bit, when set, shall indicate that the UE should implement the Group Owner (GO) functionality specified in the Wi-Fi P2P specification [17]. When not set, this bit shall indicate the UE should behave as a Wi-Fi P2P client that attempts to discover and associate with a GO.
NOTE: Bits not defined in this table shall be cleared by the sending ProSe Function and discarded by the receiving ProSe Function.		

6.3.16 ProSe-App-Code

The ProSe-App-Code AVP is of type OctetString. This AVP contains a ProSe Application Code or ProSe Application Code Prefix (see 3GPP TS 23.003 [4]) is associated with a ProSe Application ID.

6.3.17 ProSe-App-Id

The ProSe-App-Id AVP is of type UTF8String. This AVP contains a ProSe Application ID (see 3GPP TS 23.003 [4]).

6.3.18 ProSe-App-Mask

The ProSe-App-Mask AVP is of type OctetString. This AVP contains a ProSe Application Mask (see 3GPP TS 24.334 [22]).

6.3.19 ProSe-Direct-Allowed

The ProSe-Direct-Allowed AVP is of type Unsigned32 and it shall contain a bit mask that indicates the permissions for ProSe direct services for the UE in the PLMN of the responding ProSe Function. This AVP is defined in the 3GPP TS 29.344 [14].

6.3.20 ProSe-Discovery-Filter

The ProSe-Discovery-Filter AVP is of type Grouped. It shall contain a Filter ID, a ProSe Application ID name, a validity timer, a ProSe Application Code and zero or more ProSe Application Masks.

The AVP format shall conform to:

```
ProSe-Discovery-Filter ::= <AVP header: 3813 10415>
                        { Filter-Id }
                        { ProSe-App-Id }
```

{ ProSe-Validity-Timer }

{ ProSe-App-Code }

*[ProSe-App-Mask]

*[AVP]

6.3.21 PRR-Flags

The PRR-Flags AVP is of type Unsigned32 and it shall contain a bit mask. The meaning of the bits shall be as defined in table 6.3.21-1:

Table 6.3.21-1: PRA-Flags

Bit	Name	Description
0	WLAN Indication	This bit, when set, shall indicate the UE is requested EPC support for WLAN direct discovery and communication
NOTE: Bits not defined in this table shall be cleared by the sending ProSe Function and discarded by the receiving ProSe Function.		

6.3.22 ProSe-Validity-Timer

The ProSe-Validity-Timer AVP is of type Unsigned32 and it shall contain the maximum number of seconds of validity of a ProSe Application Code or a ProSe Discovery Filter.

6.3.23 Requesting-EPUIID

The Requesting-EPUIID AVP is of type UTF8String. This AVP contains an identifier for EPC-level ProSe Discovery and EPC support for WLAN direct communication that uniquely identifies a UE registered for ProSe triggering a Proximity request.

6.3.24 Supported-Features

The Supported-Features AVP is of type Grouped and it informs the destination host about the features that the origin host supports for the application. This AVP is defined in the 3GPP TS 29.229 [10].

6.3.25 SSID

The SSID AVP is of type UTF8String and it shall contain the Service Set Identifier which identifies a specific 802.11 extended service set (see IEEE Std 802.11-2012 [20]). This AVP is defined in the 3GPP TS 29.273 [15].

6.3.26 Targeted-EPUIID

The Targeted-EPUIID AVP is of type UTF8String. This AVP contains an identifier for EPC-level ProSe Discovery and EPC support for WLAN direct communication that uniquely identifies a UE registered for ProSe targeted by a Proximity request.

6.3.27 Time-Window

The Time-Window AVP is of type Unsigned32 and it shall contain the maximum number of seconds of validity of the Proximity request.

6.3.28 User-Identifier

The User-Identifier AVP is of type Grouped. It shall contain the UE identity used as identifier of a Proximity-based service subscribed by the user (i.e. IMSI or MSISDN). This AVP is defined in the 3GPP TS 29.336 [18].

6.3.29 Visited-PLMN-Id

The Visited-PLMN-Id AVP is of type OctetString. This AVP shall contain the concatenation of MCC and MNC. This AVP is defined in the 3GPP TS 29.272 [16].

6.3.30 WiFi-P2P-Assistance-Info

The WiFi-P2P-Assistance-Info AVP is of type Grouped. It shall contain information to assist WLAN direct discovery and communication as required by the Wi-Fi P2P technology.

The AVP format shall conform to:

```
WiFi-P2P-Assistance-Info ::= <AVP header: 3819 10415>
    [ SSID ]
    [ EAP-Master-Session-Key ]
    [ P2P-Features ]
    [ WLAN-Link-Layer-Id-List ]
    [ WLAN-Link-Layer-Id-List ]
    [ Operating-Channel ]
    [ Assistance-Info-Validity-Timer ]
    *[AVP]
```

6.3.31 WLAN-Assistance-Info

The WLAN-Assistance-Info AVP is of type Grouped. It shall contain information to assist WLAN direct discovery and communication required for WLAN direct discovery and communication between UEs.

The AVP format shall conform to:

```
WLAN-Assistance-Info ::= <AVP header: 3820 10415>
    [ WiFi-P2P-Assistance-Info ]
    *[AVP]
```

6.3.32 WLAN-Link-Layer-Id

The WLAN-Link-Layer-Id AVP is of type Grouped. It shall contain a link layer identity used for WLAN direct discovery and/or WLAN direct communication.

The AVP format shall conform to:

```
WLAN-Link-Layer-Id ::= <AVP header: 3821 10415>
    [ MAC-Address ]
    *AVP
```

6.3.33 WLAN-Link-Layer-Id-List

The WLAN-Link-Layer-Id-List AVP is of type Grouped. It shall contain a list of WLAN Link Layer IDs provided to a UE implementing the Group Owner functionality in a Wi-Fi P2P group.

The AVP format shall conform to:

```
WLAN-Link-Layer-Id-List ::= <AVP header: 3822 10415>
```


*[WLAN-Link-Layer-Id]

*AVP

6.3.34 OC-Supported-Features

The OC-Supported-Features AVP is of type Grouped and it is defined in IETF RFC 7683 [21]. This AVP is used to support Diameter overload control mechanism, see Annex A for more information.

6.3.35 OC-OLR

The OC-OLR AVP is of type Grouped and it is defined in IETF RFC 7683 [21]. This AVP is used to support Diameter overload control mechanism, see Annex A for more information.

6.3.36 Validity-Time-Announce

The Validity-Time-Announce AVP is of type Unsigned32 and it shall contain the maximum number of seconds of validity of a ProSe announcing authorization policy.

6.3.37 Validity-Time-Monitor

The Validity-Time-Monitor AVP is of type Unsigned32 and it shall contain the maximum number of seconds of validity of a ProSe monitoring authorization policy.

6.3.38 Validity-Time-Communication

The Validity-Time-Communication AVP is of type Unsigned32 and it shall contain the maximum number of seconds of validity of a ProSe communication authorization policy.

6.3.39 ProSe-App-Code-Info

The ProSe-App-Code-Info AVP is of type Grouped. It shall contain a ProSe Application Code, the associated MIC and the associated UTC-based counter.

The AVP format shall conform to:

```
ProSe-App-Code-Info ::=      <AVP header: 3835 10415>
                               { ProSe-App-Code }
                               { MIC }
                               { UTC-based-Counter }
                               *[AVP]
```

6.3.40 MIC

The MIC AVP is of type OctetString and shall contain a MIC (Message Integrity Check) associated with a discovered ProSe Application Code, as defined in 3GPP TS 33.303 [23].

6.3.41 UTC-based-Counter

The UTC-based-Counter AVP is of type Unsigned32 and it shall contain the UTC-based counter (in seconds) associated with a discovered ProSe Application Code as defined in 3GPP TS 24.334 [22].

6.3.42 Location-Update-Trigger

The Location-Update-Trigger AVP is of type Grouped. It shall contain the type of event that will trigger a locate update procedure to forward the location of UE to the ProSe Function initiating the Proximity Request.

The AVP format shall conform to:

```
Location-Update-Trigger::=<AVP header: 3823 10415>
    { Location-Update-Event-Type }
    [ Change-Of-Area-Type ]
    [ Periodic-Location-Type ]
    *[AVP]
```

The Change-Of-Area-Type AVP shall be present if the Location-Update-Event-Type AVP value is set to CHANGE_OR_AREA (1). Otherwise, it shall be absent.

The Periodic-Location-Type AVP shall be present if the Location-Update-Event-Type AVP value is set to PERIODIC_LOCATION (2). Otherwise, it shall be absent.

6.3.43 Location-Update-Event-Type

The Location-Update-Event-Type AVP is of type Unsigned32 and contains an 32-bit address space representing types of events that will trigger a location update. The following values are defined:

UE_AVAILABLE (0)

This value shall be used to indicate that the location update trigger is any event in which the MSC/SGSN/MME has established a contact with the UE.

CHANGE_OF_AREA (1)

This value shall be used to indicate that the location update trigger is an event where the UE enters or leaves a pre-defined geographical area or if the UE is currently within the pre-defined geographical area.

PERIODIC_LOCATION (2)

This value shall be used to indicate that the location update trigger is an event where a defined periodic timer expires in the UE and activates a location report or a location request

The types of event listed above are defined in the subclause 4.4.2.1 of the 3GPP TS 23.271 [24]

6.3.44 Change-Of-Area-Type

The Change-Of-Area-Type AVP is of type Grouped. It shall contain the information related to the type of event that will trigger a locate update procedure to forward the location of UE to the ProSe Function initiating the Proximity Request.

The AVP format shall conform to:

```
Change-Of-Area-Type::=<AVP header: 3825 10415>
    { Location-Update-Event-Trigger }
    { Report-Cardinality }
    [ Minimum-Interval-Time ]
    *[AVP]
```

The Minimum-Interval-Time AVP may be present only if the Report-Cardinality AVP value is set to MULTIPLE (1).

6.3.45 Location-Update-Event-Trigger

The Location-Update-Event-Type AVP is of type Unsigned32 and contains a 32-bit address space representing the possible change of area events i.e. UE enters, leaves or is within requested target area. The following values are defined:

UE_ENTRY (0)

This value shall be used to indicate the event trigger is the UE entering a pre-defined geographical area.

UE_EXIT (1)

This value shall be used to indicate the event trigger is the UE leaving a pre-defined geographical area

UE_PRESENCE (2)

This value shall be used to indicate the event trigger is the current presence of the UE within a pre-defined geographical area.

The types of change of area event listed above are defined in the subclause 4.4.2.1 of the 3GPP TS 23.271 [24].

6.3.46 Report-Cardinality

The Report-Cardinality AVP is of type Enumerated. The following values are defined:

SINGLE (0)

This value shall be used to indicate the change of area event shall be reported one time only.

MULTIPLE (1)

This value shall be used to indicate the change of area event may be reported several times.

6.3.47 Minimum-Interval-Time

The Minimum-Interval-Time AVP is of type Unsigned32 and shall contain the minimum number of seconds between area event reports.

6.3.48 Periodic-Location-Type

The Periodic-Location-Type AVP is of type Grouped. It shall contain the time interval between successive location reports and the total number of reports.

The AVP format shall conform to:

Periodic-Location-Type ::= <AVP header: 3829 10415>

{ Location-Report-Interval-Time }

{ Total-Number-Of-Reports }

*[AVP]

6.3.49 Location-Report-Interval-Time

The Location-Report-Interval-Time AVP is of type Unsigned32 and shall contain the number of seconds between successive location reports.

6.3.50 Total-Number-Of-Reports

The Total-Number-Of-Reports AVP is of type Unsigned32 and shall indicate the maximum number of requested location reports.

6.3.51 Authorized-Discovery-Range

The Authorized-Discovery-Range AVP is of type Unsigned32 and it shall contain a value that indicates the authorised announcing range (short/medium/long) at which the UE is allowed to announce in the given PLMN according to the defined announcing authorisation policy for this UE. This AVP is defined in the 3GPP TS 29.344 [14].

6.3.52 ProSe-Match-Refresh-Timer

The ProSe-Match-Refresh-Timer AVP is of type Unsigned32 and it shall contain the number of seconds indicating how long the UE shall wait before sending a new Match Report for the associated ProSe Application Code.

6.3.53 Discovery-Auth-Request

The Discovery-Auth-Request is of type Grouped. It shall contain the information elements used in ProSe direct discovery authorization request.

The AVP format shall conform to:

```
Discovery-Auth-Request ::= <AVP header: 3854 10415>
    { Discovery-Type }
    [ User-Identity ]
    [ ProSe-App-ID ]
    [ ProSe-App-Code ]
    [ ProSe-App-Code-Suffix-Range ]
    [ ProSe-Validity-Timer ]
    [ App-Identifier ]
    [ Requesting-RPAUID ]
    [ Target-RPAUID ]
    [ Target-PDUID ]
    [ ProSe-Restricted-Code ]
    [ ProSe-Query-Code ]
    [ ProSe-Response-Code ]
    *[ ProSe-Restricted-Code-Suffix-Range ]
    [ Banned-RPAUID ]
    [ Banned-PDUID ]
    [ Service-Result ]
    *[AVP]
```

When the Discovery-Type is set to "ANNOUNCING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain a UE identity, a ProSe Application ID, a ProSe Application Code and optionally one or more ProSe Restricted Code Suffix-Range, and a ProSe Validity Timer.

When the Discovery-Type is set to "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain a UE identity and a ProSe Application ID.

When the Discovery-Type is set to "ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain a UE identity, an Application Identifier, the Requesting RPAUID, ProSe Restricted Code and optionally one or more ProSe Restricted Code SuffixRange, and a ProSe Validity Timer.

When the Discovery-Type is set to "MONITORING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain a UE identity, an Application Identifier, Requesting RPAUID, Target RPAUID, and Target PDUID.

When the Discovery-Type is set to "DISCOVEREE_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain a UE identity, an Application Identifier, Requesting RPAUID and a ProSe Response Code.

When the Discovery-Type is set to "DISCOVERER_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain a UE identity, an Application Identifier, Requesting RPAUID, Target RPAUID, and Target PDUID.

When the Discovery-Type is set to "DISCOVERER_ANNOUNCING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain a UE identity, an Application Identifier, Requesting RPAUID and a ProSe Query Code.

When the Discovery-Type is set to "MONITORING_UPDATE_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain an Application Identifier, a ProSe Restricted Code, a Banned RPAUID and a Banned PDUID.

When the Discovery-Type is set to "MONITORING_RESPONSE_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Request shall contain an Application Identifier, ProSe-Restricted-Code, Banned RPAUID, Banned PDUID and Result.

6.3.54 Discovery-Auth-Response

The Discovery-Auth-Response is of type Grouped. It shall contain the information elements used in ProSe direct discovery authorization answer.

The AVP format shall conform to:

```
Discovery-Auth-Response ::= <AVP header: 3855 10415>
    { Discovery-Type }
    *[ ProSe-Discovery-Filter ]
    [ Visited-PLMN-Id ]
    [ ProSe-Restricted-Code ]
    [ ProSe-Query-Code ]
    [ ProSe-Response-Code ]
    [ ProSe-Validity Timer ]
    [ Code-Sending-Security-Material ]
    [ Code-Receiving-Security-Material ]
    [ DUIK ]
    *[AVP]
```

When the Discovery-Type is set to "ANNOUNCING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Response shall contain no other parameters.

When the Discovery-Type is set to "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Response shall contain one or more ProSe Discovery Filters, and optionally a PLMN ID.

When the Discovery-Type is set to "MONITORING_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Response shall contain a ProSe Restricted Code, a Code Receiving Security Material, optionally a DUIK, and a ProSe Validity Timer. The DUIK parameter shall be included in Discovery-Auth-Response only if the Code-Receiving-Security-Material contains a MIC Check Indicator set to MIC_CHECK_BY_PROSE_FUNCTION.

When the Discovery-Type is set to "DISCOVERER_REQUEST_FOR_RESTRICTED_PROSE_DIRECT_DISCOVERY", the Discovery-Auth-Response shall contain a ProSe Query Code, a Code Sending Security Material, a ProSe Response Code, a Code Receiving Security Material, optionally a DUIK, and a ProSe Validity Timer. The DUIK parameter shall be included in Discovery-Auth-Response only if the Code-Receiving-Security-Material contains a MIC Check Indicator set to MIC_CHECK_BY_PROSE_FUNCTION.

6.3.55 Match-Request

The Match-Request is of type Grouped. It shall contain the information elements used in ProSe Match Report request.

The AVP format shall conform to:

```
Match-Request ::=      <AVP header: 3856 10415>
                        { Discovery-Type }
                        [ User Identity ]
                        [ Visited-PLMN-ID ]
                        *[ ProSe-App-Code-Info ]
                        *[AVP]
```

The valid value for Discovery-Type for Match-Report AVP is:
"MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY",

When the Discovery-Type is set to "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the Match-Request shall contain one UE Identity, one Visited PLMN ID, and one or more ProSe App Code Info.

6.3.56 Match-Report-Info

The Match-Report-Info is of type Grouped. It shall contain the information elements used in ProSe Match Report Info request.

The AVP format shall conform to:

```
Match-Report-Info ::=      <AVP header: 3857 10415>
                        { Discovery-Type }
                        [ User-Identity ]
                        *[ ProSe-App-ID ]
                        *[AVP]
```

The valid value for Discovery-Type for Match-Report-Info AVP is:
"MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY",

When the Discovery-Type is set to "MONITORING_REQUEST_FOR_OPEN_PROSE_DIRECT_DISCOVERY", the Match-Report-Info shall contain one User Identity and one or more ProSe Application IDs.

6.3.57 PMR-Flags

The PMR-Flags AVP is of type Unsigned32 and it shall contain a bit mask. The meaning of the bits shall be as defined in table 6.3.57/1:

Table 6.3.57/1: PMR-Flags

Bit	Name	Description
0	Metadata Requested	This bit, when set, indicates that metadata information associated with the ProSe Application ID are requested.
NOTE: Bits not defined in this table shall be cleared by the sending ProSe Function and discarded by the receiving receiving ProSe function.		

6.3.58 ProSe-Application-Metadata

The ProSe-Application-Metadata AVP is of type UTF8String. This AVP shall contain the metadata associated with the ProSe Application ID contained in the Match Report. As defined in 3GPP TS 24.334 [22], the length and contents of the metadata formatted as UTF8-encoded string are out of scope of 3GPP.

6.3.59 Discovery-Entry-ID

The Discovery-Entry-ID is of type Unsigned32. It shall contain the discovery Entry ID used to identify the discovery entry in the UE context related to the discovery authorization request in the requesting ProSe Function.

6.3.60 ProSe-Metadata-Index-Mask

The ProSe-Metadata-Index-Mask AVP is of type OctetString. This AVP contains a ProSe metadata index mask (see 3GPP TS 24.334 [22]).

6.3.61 App-Identifier

The App-Identifier AVP is of type Grouped. It shall contain an OS ID and OS Application ID name.

The AVP format shall conform to:

```
App-Identifier ::=
    <AVP header: 3840 10415>
    { OS-ID }
    { OS-App-ID }
    *[AVP]
```

6.3.62 OS-ID

The OS-ID AVP is of type OctetString. It shall contain an identifier of the operating system as defined in subclause 12.2.2.5 in 3GPP TS 24.334 [22].

6.3.63 OS-App-ID

The OS-App-ID AVP is of type UTF8String. It shall contain an OS specific application as defined in subclause 12.2.2.5 in 3GPP TS 24.334 [22].

6.3.64 Requesting-RPAUID

The Requesting-RPAUID AVP is of type UTF8String. This AVP contains an identifier for restricted ProSe direct discovery that uniquely identifies an application user originating a restricted ProSe direct discovery request.

6.3.65 Target-RPAUID

The Target-RPAUID AVP is of type UTF8String. This AVP contains an identifier for restricted ProSe direct discovery that uniquely identifies an application user targeted by a restricted ProSe direct discovery request.

6.3.66 Target-PDUID

The Target-PDUID AVP is of type OctetString. It shall contain the ProSe Discovery UE ID which uniquely identifies the UE targeted by a restricted ProSe direct discovery request.

6.3.67 ProSe-Restricted-Code

The ProSe-Restricted-Code AVP is of type OctetString. This AVP contains a ProSe Restricted Code (see 3GPP TS 23.003 [4]) which is associated with a RPAUID.

6.3.68 ProSe-Restricted-Code-Suffix-Range

The ProSe-Restricted-Code-Suffix-Range AVP is of type Grouped. It contains a range of consecutive ProSe Restricted Code Suffixes that can be appended to a ProSe Restricted Code Prefix. It shall contain a Beginning Suffix and may contain an Ending Suffix. If the Ending Suffix is not present, the only ProSe Restricted Code Suffix included in the ProSe Restricted Code Suffix Range is equal to the Beginning Suffix.

The AVP format shall conform to:

```
ProSe-Restricted-Code-Suffix-Range ::=      <AVP header: 3847 10415>
                                           { Beginning-Suffix }
                                           [ Ending-Suffix ]
                                           *[AVP]
```

Beginning Suffix and Ending Suffix shall have the same length.

6.3.69 Beginning-Suffix

The Beginning-Suffix AVP is of type OctetString. This AVP shall contain the lowest ProSe Restricted Code Suffix in a consecutive sequence of ProSe Restricted Code suffixes, or the lowest ProSe Application Code Suffix in a consecutive sequence of ProSe Application Code Suffixes. The format of ProSe Restricted Code Suffix or ProSe Application Code Suffix is defined in 3GPP TS 23.003 [4]. The size of this suffix shall align with octet boundary.

6.3.70 Ending-Suffix

The Ending-Suffix AVP is of type OctetString. This AVP shall contain the highest ProSe Restricted Code Suffix in a consecutive sequence of ProSe Restricted Code suffixes or the highest ProSe Application Code Suffix in a consecutive sequence of ProSe Application Code Suffixes. The format of ProSe Restricted Code Suffix or ProSe Application Code Suffix is defined in 3GPP TS 23.003 [4]. The size of this suffix shall align with octet boundary.

6.3.71 Match-Timestamp

The Match-Timestamp AVP is of type Time and it shall contain the UTC time identifying when the discovery match event occurred.

6.3.72 DRMP

The DRMP AVP is of type Enumerated and it is defined in IETF draft-ietf-dime-drmp-03 [27]. This AVP allows the Prose Function to indicate the relative priority of Diameter messages.

6.3.73 Banned-RPAUID

The Banned-RPAUID AVP is of type UTF8String. This AVP contains an identifier for restricted ProSe direct discovery that uniquely identifies an application user banned by a restricted ProSe direct discovery request.

6.3.74 Banned-PDUID

The Banned-PDUID AVP is of type OctetString. It shall contain the ProSe Discovery UE ID which uniquely identifies the UE Banned by a restricted ProSe direct discovery request.

6.3.75 Code-Receiving-Security-Material

The Code-Receiving-Security-Material AVP is of type Grouped. It shall contain security parameters used to indicate to a UE how a received restricted ProSe direct discovery message is protected. The Code Receiving Security Material may contain a DUSK and may contain either a DUIK or an indication whether to use Match Reports for MIC checking. It may also contain both a DUCK and a corresponding Encrypted Bitmask.

The AVP format shall conform to:

```
Code-Receiving-Security-Material ::=    <AVP header: 3847 10415>
                                         [ DUSK ]
                                         [ DUIK ]
                                         [ MIC-Check-Indicator ]
                                         [ DUCK ]
                                         [ Encrypted-Bitmask ]
                                         *[AVP]
```

6.3.76 Code-Sending-Security-Material

The Code-Sending-Security-Material AVP is of type Grouped. It shall contain security parameters used to indicate to a UE how to protect the transmission of restricted ProSe direct discovery message. The Code Sending Security Material may contain a DUSK and may contain a DUIK. It may also contain both a DUCK and a corresponding Encrypted Bitmask.

The AVP format shall conform to:

```
Code-Sending-Security-Material ::=    <AVP header: 3847 10415>
                                         [ DUSK ]
                                         [ DUIK ]
                                         [ DUCK ]
                                         [ Encrypted-Bitmask ]
                                         *[AVP]
```

6.3.77 DUSK

The DUSK AVP is of type OctetString. It shall contain the Discovery User Scrambling Key used to scramble or unscramble the restricted ProSe direct discovery message containing the ProSe Restricted Code, ProSe Query Code or ProSe Response Code. The format of the DUSK is defined in 3GPP TS 33.303 [23].

6.3.78 DUIK

The DUIK AVP is of type OctetString. It shall contain the Discovery User Integrity Key used to compute the MIC of the restricted ProSe direct discovery message containing the ProSe Restricted Code, ProSe Query Code or ProSe Response Code. The format of the DUIK is defined in 3GPP TS 33.303 [23].

6.3.79 DUCK

The DUCK AVP is of type OctetString. It shall contain the Discovery User Confidentiality Key used to encrypt and decrypt a portion in restricted ProSe direct discovery message. The format of the DUCK is defined in 3GPP TS 33.303 [23].

6.3.80 MIC-Check-Indicator

The MIC-Check-Indicator AVP is of type Unsigned32. It shall contain the indication of whether the UE shall use the ProSe Function to verify the MIC field of the received discovery message. The following values are defined:

MIC_CHECK_BY_PROSE_FUNCTION (1)

This value is used when the MIC check is required to be done by the ProSe Function.

6.3.81 Encrypted-Bitmask

The Encrypted-Bitmask AVP is of type OctetString. It shall contain a 184-bit bitmask which uses bit "1" to mark the positions of the bits of a ProSe Restricted Code, ProSe Query Code or ProSe Response Code, for which the DUCK encryption is applied.

6.3.82 ProSe-App-Code-Suffix-Range

The ProSe-App-Code-Suffix-Range AVP is of type Grouped. It contains a range of consecutive ProSe Application Code Suffixes that can be appended to a ProSe Application Code Prefix. It shall contain a Beginning Suffix and may contain an Ending Suffix. If the Ending Suffix is not present, the only ProSe Application Code Suffix included in the ProSe Application Code Suffix Range is equal to the Beginning Suffix.

The AVP format shall conform to:

```
ProSe-App-Code-Suffix-Range ::=  <AVP header: 3847 10415>
                                { Beginning-Suffix }
                                [ Ending-Suffix ]
                                *[AVP]
```

Beginning Suffix and Ending Suffix shall have the same length.

6.4 Result-Code and Experimental-Result Values

6.4.1 General

This subclause defines result code values that shall be supported by all Diameter implementations that conform to this specification.

6.4.2 Success

Result codes that fall within the Success category shall be used to inform a peer that a request has been successfully completed. The Result-Code AVP values defined in Diameter Base Protocol IETF RFC 3588 [7] shall be applied.

6.4.3 Permanent Failures

Errors that fall within the Permanent Failures category shall be used to inform the peer that the request has failed, and should not be attempted again. The Result-Code AVP values defined in Diameter Base Protocol IETF RFC 3588 [7] shall be applied. When one of the result codes defined here is included in a response, it shall be inside an Experimental-Result AVP and the Result-Code AVP shall be absent.

6.4.3.1 DIAMETER_ERROR_USER_UNKNOWN (5001)

This result code shall be sent by the ProSe Function in the HPLMN to indicate that the user identified by the UE identity is unknown

6.4.3.2 DIAMETER_ERROR_UNAUTHORIZED_SERVICE (5511)

This result code shall be sent by the ProSe Function in the HPLMN to indicate that no ProSe subscription is associated with the UE.

6.4.3.3 DIAMETER_ERROR_NO_ASSOCIATED_DISCOVERY_FILTER (5630)

This result code shall be sent by the ProSe Function in the local/visited PLMN to indicate that there is no valid Discovery Filter associated to the ProSe Application ID name received in the request.

6.4.3.4 DIAMETER_ERROR_ANNOUNCING_UNAUTHORIZED_IN_PLMN (5631)

This result code shall be sent by the ProSe Function in the local/visited PLMN to indicate that the UE is not authorized to announce in this PLMN.

6.4.3.5 DIAMETER_ERROR_INVALID_APPLICATION_CODE (5632)

This result code shall be sent by the ProSe Function in the local PLMN to indicate that none of the ProSe Application Code(s) received in the request is valid.

6.4.3.6 DIAMETER_ERROR_PROXIMITY_UNAUTHORIZED (5633)

This result code shall be sent by the ProSe Function in the serving PLMN to indicate that the Proximity request is not authorized by the user.

6.4.3.7 DIAMETER_ERROR_PROXIMITY_REJECTED (5634)

This result code shall be sent by the ProSe Function in the serving PLMN to indicate that it is unlikely that UEs enter into proximity for the received time window.

6.4.3.8 DIAMETER_ERROR_NO_PROXIMITY_REQUEST (5635)

This result code shall be sent by the ProSe Function in the serving PLMN to indicate that there is no context associated with EPC ProSe User Identities included in the request.

6.4.3.9 DIAMETER_ERROR_UNAUTHORIZED_SERVICE_IN_THIS_PLMN (5636)

This result code shall be sent by the ProSe Function HPLMN to indicate that ProSe is not authorized to announce in this PLMN.

6.4.3.10 DIAMETER_ERROR_PROXIMITY_CANCELLED (5637)

This result code shall be sent by the ProSe Function triggering the Proximity Request to indicate that the cancellation of the Proximity Request procedure as it determines that the UEs are unlikely to enter proximity within the requested time window.

6.4.3.11 DIAMETER_ERROR_INVALID_DISCOVERY_TYPE (5641)

This result code shall be sent by the ProSe Function to indicate that the Discovery Tpe in the request message is not supported.

6.4.3.12 DIAMETER_ERROR_INVALID_TARGET_PDUID (5638)

This result code shall be sent by the ProSe Function to indicate that the PDUID is not belonging to this ProSe Function.

6.4.3.13 DIAMETER_ERROR_INVALID_TARGET_RPAUID (5639)

This result code shall be sent by the ProSe Function to indicate that the target RPAUID is not allowed to be discovered.

6.4.3.14 DIAMETER_ERROR_NO_ASSOCIATED_RESTRICTED_CODE (5640)

This result code shall be sent by the ProSe Function to indicate that the there is no allocated ProSe Restricted Code for the requested target.

6.4.3.15 DIAMETER_ERROR_REVOCATION_FAILURE (56x1)

This value is used to indicate that the ProSe Function was unable to successfully complete the revocation procedure (in an operator-configured time period).

6.4.3.16 DIAMETER_ERROR_ALREADY_BANNED (56x2)

This value is used to indicate that the ProSe Function has determined that the revocation is not necessary because the target RPAUID has already been banned for discovery.

6.4.4 Transient Failures

Result codes that fall within the transient failures category shall be used to inform a peer that the request could not be satisfied at the time it was received, but may be able to satisfy the request in the future. The Result-Code AVP values defined in Diameter Base Protocol IETF RFC 3588 [7] shall be applied. When one of the result codes defined here is included in a response, it shall be inside an Experimental-Result AVP and the Result-Code AVP shall be absent.

Annex A (normative): Diameter overload control mechanism

A.1 General

Diameter overload control mechanism is an optional feature.

IETF RFC 7683 [21] specifies a Diameter overload control mechanism which includes the definition and the transfer of related AVPs between Diameter nodes.

It is recommended to make use of IETF RFC 7683 [21] on the PC6/PC7 interface where, when applied, the requesting ProSe Function shall behave as a reacting node and the responding ProSe Function as a reporting node.

A.2 Responding ProSe Function behaviour

The responding ProSe Function requests traffic reduction from requesting ProSe Function when it is in an overload situation, including OC-OLR AVP in answer commands as described in IETF RFC 7683 [21].

The ProSe Function identifies that it is in an overload situation by implementation specific means. For example, the ProSe Function may take into account the traffic over the PC6/PC7 interfaces or other interfaces, the level of usage of internal resources (CPU, memory), the access to external resources, etc.

The ProSe Function determines the specific contents of OC-OLR AVP in overload reports and the ProSe Function decides when to send OC-OLR AVPs by implementation specific means.

A.3 Requesting ProSe Function behaviour

The requesting ProSe Function applies required traffic reduction received in answer commands to subsequent applicable requests, as per IETF RFC 7683 [21].

Requested traffic reduction is achieved by the requesting ProSe Function by implementation specific means. For example, it may implement message throttling with prioritization or a message retaining mechanism for operations that can be postponed.

As a result of the need to throttle traffic, the requesting ProSe Function may reject Registration Request, Discovery Request, Match Report Requests initiated by UEs. The possible related error messages used over PC3 are described in the 3GPP TS 24.334 [22].

Annex B (Informative): Diameter overload node behaviour

B.1 Message prioritization

This clause describes possible behaviours of the requesting ProSe Function receiving an overload indication from the responding ProSe Function, regarding message prioritisation in an informative purpose.

The requesting ProSe Function may take the following into account when making throttling decisions:

- Identification of the procedures that can be deferred (e.g. Proximity Requests), so to avoid to drop non deferrable procedures;
- Prioritisation of certain types of request (e.g. between ProSe-Proximity-Request (PRR) and ProSe-Location-Update-Request (PLR)) according to the context of their use, in particular:
- Higher prioritisation for commands that are related to a registered user for a service, so to avoid the interruption of the registered service for the user.

Annex C (normative): Diameter message priority mechanism

C.1 General

IETF draft-ietf-dime-drmp-03 [27] specifies a Diameter routing message priority mechanism that allows Diameter nodes to indicate the relative priority of Diameter messages. With this information, other Diameter nodes may leverage the relative priority of Diameter messages into routing, resource allocation and also abatement decisions when overload control is applied.

C.2 PC6/PC7 interfaces

C.2.1 General

The Diameter message priority mechanism is an optional feature.

It is recommended to make use of IETF draft-ietf-dime-drmp-03 [27] over the PC6/PC7 interfaces of an operator network when the overload control defined in Annex A is applied on these PC6/7 interfaces.

C.2.2 ProSe Function behaviour

When the ProSe Function supports the Diameter message priority mechanism over the PC6 or the PC7 interface, the ProSe Function shall comply with IETF draft-ietf-dime-drmp-03 [27]. In particular, when priority is required, the ProSe Function shall include the DRMP AVP indicating a priority level in the requests it sends, and prioritise received requests according to the priority level received within the DRMP AVP. It shall prioritise received answers according to the priority level received within the DRMP AVP if present, otherwise according to the priority level of the corresponding request. It shall include the DRMP AVP in the answer to a received request if the required priority of the answer is different from the one of the request. The ProSe Function decisions for a required priority and for the priority level value are implementation specific.

Diameter requests related to high priority traffic should contain a DRMP AVP with a high priority of which the level value is operator dependent.

Annex D (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2014-04	CT4#64bis	C4-140705			TR Skeleton	0.0.0	0.1.0
2014-05	CT4#65	C4-141079			Proposed text for section "Scope"	0.1.0	0.2.0
2014-05	CT4#65	C4-141080			General Description of TS 29.345	0.1.0	0.2.0
2014-05	CT4#65	C4-141081			Description of the ProSe Service Authorization Procedure	0.1.0	0.2.0
2014-05	CT4#65	C4-141082			Description of the Direct Discovery Authorization procedure	0.1.0	0.2.0
2014-05	CT4#65	C4-141084			Description of the Match Report Procedure	0.1.0	0.2.0
2014-05	CT4#65	C4-141086			Description of the Proximity request Procedure	0.1.0	0.2.0
2014-05	CT4#65	C4-141087			Description of the Location Update procedure	0.1.0	0.2.0
2014-05	CT4#65	C4-141088			Description of the Cancellation procedure	0.1.0	0.2.0
2014-05	CT4#65	C4-141089			Description of Protocol Specification and Implementation	0.1.0	0.2.0
2014-05	CT4#65	C4-141090			Description of the Proximity Alert Procedure	0.1.0	0.2.0
2014-05	CT4#65	C4-141091			Description of Information Elements	0.1.0	0.2.0
2014-05	CT4#65	C4-141092			Description of Commands	0.1.0	0.2.0
2014-05	CT4#65	C4-141175			Description of Result Codes	0.1.0	0.2.0
2014-07	CT4#66	C4-141266			Editorial corrections	0.2.0	0.3.0
2014-07	CT4#66	C4-141422			Removal of the Cancellation-Type AVP	0.2.0	0.3.0
2014-07	CT4#66	C4-141423			Domain Name used for ProSe related Diameter Applications	0.2.0	0.3.0
2014-07	CT4#66	C4-141511			Description of the Match Report Info procedure	0.2.0	0.3.0
2014-07	CT4#66	C4-141512			Correction of the User-Identifier AVP	0.2.0	0.3.0
2014-07	CT4#66	C4-141641			Correction of the Discovery-Filter AVP	0.2.0	0.3.0
2014-09	CT#65	CP-140498			Presented for information and approval	0.3.0	1.0.0
2014-09	CT#65				Approved at CT#65	1.0.0	12.0.0
2014-12	CT#66	CP-140778	0006	1	ProSe Validity Timer to VPLMN	12.0.0	12.1.0
2014-12	CT#66	CP-140778	0003	1	Overload Control management	12.0.0	12.1.0
2014-12	CT#66	CP-140778	0007	1	Wrong P-CR implementations	12.0.0	12.1.0
2014-12	CT#66	CP-140778	0005		Clarification in the ProSe Direct Discovery Authorization Procedure	12.0.0	12.1.0
2014-12	CT#66	CP-140778	0001	4	Clarification on ProSe Application Code and Discovery Filter IE Formats	12.0.0	12.1.0
2014-12	CT#66	CP-140778	0009	1	Deletion of the unused AVP	12.0.0	12.1.0
2014-12	CT#66	CP-140778	0010	1	Updates of the values for Application ID, Command codes, AVP codes and Experimental-Result codes	12.0.0	12.1.0
2015-03	CT#67	CP-150028	0012	2	Correction on ProSe Service Authorization Procedures in PC6/PC7 interface	12.1.0	12.2.0
2015-03	CT#67	CP-150028	0014	2	Addition of Integrity Check aspects to ProSe Match Report procedure	12.1.0	12.2.0
2015-03	CT#67	CP-150028	0016	1	Correction in the Discovery Type description	12.1.0	12.2.0

2015-03	CT#67	CP-150028	0020	2	Location Update Trigger	12.1.0	12.2.0
2015-03	CT#67	CP-150149	0015	4	Introduction of Authorized Discovery Range Indication for announcing UE	12.1.0	12.2.0
2015-03	CT#67	CP-150031	0021	1	Update of the reference for IETF draft-ietf-dime-ovli	12.1.0	12.2.0
2015-06	CT#68	CP-150257	0022	1	Addition of Match Report Refresh Timer in PMA command	12.2.0	12.3.0
2015-06	CT#68	CP-150257	0024	1	Corrections of errors and inconsistencies in TS 29.345	12.2.0	12.3.0
2015-06	CT#68	CP-150257	0025	2	Ambiguity in the definition of ProSe-Discovery-Filter AVP	12.2.0	12.3.0
2015-06	CT#68	CP-150257	0027	2	Clarification on ProSe Validity Timer	12.2.0	12.3.0
2015-06	CT#68	CP-150257	0028	2	Alignment on using ProSe service and ProSe	12.2.0	12.3.0
2015-12	CT#70	CP-150755	0032	4	Correction of AVP and message definitions to allow Diameter command reuse	12.3.0	12.4.0
2015-12	CT#70	CP-150755	0033	1	Metadata in Match-Report	12.3.0	12.4.0
2015-12	CT#70	CP-150759	0035	1	Reference to DOIC updated with IETF RFC 7683	12.3.0	12.4.0
2015-12	CT#70	CP-150772	0029	5	Addition of ProSe discovery service authorization for restricted discovery	12.4.0	13.0.0
2015-12	CT#70	CP-150772	0030	2	ProSe Open Discovery for Dynamic Metadata	12.4.0	13.0.0
2015-12	CT#70	CP-150772	0031	2	AVP and Message format changes for new ProSe procedures	12.4.0	13.0.0
2015-12	CT#70	CP-150772	0034	2	Addition of ProSe match report info for restricted discovery	12.4.0	13.0.0
2016-03	CT#71	CP-160023	0041		Diameter message priority over PC6/PC7	13.0.0	13.1.0
2016-03	CT#71	CP-160036	0036	3	Monitoring update and Reporting of update result	13.0.0	13.1.0
2016-03	CT#71	CP-160036	0037	1	Inter-PLMN discovery transmission support	13.0.0	13.1.0
2016-03	CT#71	CP-160036	0038	1	Adding security related parameters for restricted ProSe direct discovery authorization	13.0.0	13.1.0
2016-03	CT#71	CP-160036	0039	1	Support open discovery with application-controlled extension	13.0.0	13.1.0
2016-03	CT#71	CP-160036	0040	-	Discovery update for open and restricted ProSe direct discovery	13.0.0	13.1.0

History

Document history		
V13.0.0	March 2016	Publication
V13.1.0	April 2016	Publication