ETSI TS 145 015 V4.0.0 (2004-11)

Technical Specification

Digital cellular telecommunications system (Phase 2+);
Release independent Downlink Advanced
Receiver Performance (DARP);
Implementation guidelines
(3GPP TS 45.015 version 4.0.0 Release 4)



Reference
DTS/TSGG-0145015v400

Keywords
GSM

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

If you find errors in the present document, please send your comment to one of the following services: http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**TM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**TM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Contents

Intelle	ectual Property Rights	2
	vord	
	vord	
	Scope	
	References	
3 3.1	Definitions and abbreviations	5
4.1	DARP MS Independent of Release RF Requirements Signalling Requirements	5
4.2	Signalling Requirements	6
Anne	x A (informative): Change history	7
	ry	

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies requirements on MSs supporting Downlink Advanced Receiver Performance (DARP) that are independent of release. TSG GERAN has agreed that the standardisation of DARP be independent of a release. However, in order to implement an MS that conforms to a particular release but supports DARP, which is specified in a later release, it is necessary to specify some extra requirements.

DARP is contained in the Release 6 specifications. In order to implement an MS conforming to Release 4 but supporting DARP, it is necessary for the MS to additionally conform to some parts of the Release 6 specifications, such as the radio frequency requirements for DARP and some signalling extensions relating to the MS Classmark and radio access capabilities.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TS 45.005: "Radio transmission and reception (Release 6)".
- [2] 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core Network protocols; Stage 3 (Release 6)".

3 Definitions and abbreviations

Unless listed below, all definitions and abbreviations used in the present document are listed in documents referenced in clause 2.

3.1 Abbreviations

For the purposes of the present document, the following abbreviations apply:

DARP Downlink Advanced Receiver Performance

4 DARP MS Independent of Release

MSs that conform to Release 4 and support DARP shall support the following requirements in Release 6.

4.1 RF Requirements

The MS shall comply with the RF requirements for DARP specified in [1]. These requirements are:

Section 6.3: Reference interference level.

4.2 Signalling Requirements

The MS shall support the following information elements specified in [2]:

Section 10.5.1.7 Mobile Station Classmark 3, with the following exceptions:

- Fields *High Multislot Capability*, *GERAN Iu mode Capabilities*, *T-GSM 400 Bands Supported / T-GSM 400 Associated Radio Capability* and *T-GSM 900 Associated Radio Capability* shall be indicated as not present since they are not defined in Release 4. This is done by setting the indication bit to '0'.
- Parameter *GERAN Feature Package 2* shall be indicated as not supported since it is not defined in Release 4. This is done by setting the bit value '0' for this parameter.
- In addition, for *GMSK Multislot Power Profile* and 8-PSK Multislot Power Profile, the value '00' shall be used as it indicates the same power reduction as defined in Release 4 except that the Release 4 MS might be transmitting at 1dB higher than indicated by this parameter.

Section 10.5.5.12a MS Radio Access Capability, with the following exceptions:

- Fields *High Multislot Capability* and *GERAN Iu Mode Capabilities* shall be indicated as not present since they are not defined in Release 4. This is done by setting the indication bit to '0'.
- Parameter *Multiple TBF Capability* shall be indicated as not supported since it is not defined in Release 4. This is done by setting the bit value '0' for this parameter.
- In addition, for *Access Technology Type*, the values '1001' through to '1011' shall not be used since GSM T 380, GSM T 410 and GSM T 900 are not supported in Release 4; and for *GMSK Multislot Power Profile* and 8-*PSK Multislot Power Profile*, the value '00' shall be used as it indicates the same power reduction as defined in Release 4 except that the Release 4 MS might be transmitting at 1dB higher than indicated by this parameter.

Annex A (informative): Change history

Change history									
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New		
2004-11	22	GP-042853			Version for Release 4		4.0.0		

History

Document history								
V4.0.0	November 2004	Publication						