

ETSI EN 301 025-3 V1.3.1 (2007-02)

Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
VHF radiotelephone equipment for general communications
and associated equipment for Class "D"
Digital Selective Calling (DSC);
Part 3: Harmonized EN under article 3.3 (e)
of the R&TTE Directive**



ReferenceREN/ERM-TG26-074-3

Keywordsmaritime, radio, regulation, traffic, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2007.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

| | |
|----------------------------------------------------------------|----|
| Intellectual Property Rights | 6 |
| Foreword..... | 6 |
| 1 Scope | 7 |
| 2 References | 7 |
| 3 Definitions and abbreviations..... | 8 |
| 3.1 Definitions | 8 |
| 3.2 Abbreviations | 8 |
| 4 Technical requirements specifications | 8 |
| 4.1 Environmental profile..... | 8 |
| 4.2 General, operational and technical requirements..... | 9 |
| 4.2.1 General and operational requirements | 9 |
| 4.2.1.1 Requirements | 9 |
| 4.2.1.2 Conformance..... | 9 |
| 4.2.2 Technical requirements..... | 9 |
| 4.2.2.1 Requirements | 9 |
| 4.2.2.2 Conformance..... | 9 |
| 4.3 Environmental requirements | 9 |
| 4.3.1 Vibration test | 9 |
| 4.3.1.1 Definition | 9 |
| 4.3.1.2 Requirement | 9 |
| 4.3.1.3 Conformance..... | 9 |
| 4.3.2 Temperature tests..... | 9 |
| 4.3.2.1 Definition | 9 |
| 4.3.2.2 Dry heat..... | 9 |
| 4.3.2.2.1 Definition..... | 9 |
| 4.3.2.2.2 Requirement | 10 |
| 4.3.2.2.3 Conformance | 10 |
| 4.3.2.3 Damp heat | 10 |
| 4.3.2.3.1 Definition..... | 10 |
| 4.3.2.3.2 Requirement | 10 |
| 4.3.2.3.3 Conformance | 10 |
| 4.3.2.4 Low temperature | 10 |
| 4.3.2.4.1 Definition..... | 10 |
| 4.3.2.4.2 Requirement | 10 |
| 4.3.2.4.3 Conformance | 10 |
| 4.4 Conformance requirements | 10 |
| 4.4.1 Sensitivity of the modulator, including microphone..... | 10 |
| 4.4.1.1 Definition | 10 |
| 4.4.1.2 Limit..... | 10 |
| 4.4.1.3 Conformance..... | 10 |
| 4.4.2 Audio frequency response | 11 |
| 4.4.2.1 Definition | 11 |
| 4.4.2.2 Limit..... | 11 |
| 4.4.2.3 Conformance..... | 11 |
| 4.4.3 Audio frequency harmonic distortion of the emission..... | 11 |
| 4.4.3.1 Definition | 11 |
| 4.4.3.2 Limit..... | 11 |
| 4.4.3.3 Conformance..... | 11 |
| 4.4.4 Residual modulation of the transmitter | 11 |
| 4.4.4.1 Definition | 11 |
| 4.4.4.2 Limit..... | 11 |
| 4.4.4.3 Conformance..... | 11 |
| 4.4.5 Frequency error (demodulated DSC signal) | 11 |
| 4.4.5.1 Definition | 11 |

| | | |
|-------------|----------------------------------------------------------------------|----|
| 4.4.5.2 | Limit..... | 11 |
| 4.4.5.3 | Conformance..... | 11 |
| 4.4.6 | Modulation index for DSC | 12 |
| 4.4.6.1 | Definition | 12 |
| 4.4.6.2 | Limit..... | 12 |
| 4.4.6.3 | Conformance..... | 12 |
| 4.4.7 | Modulation rate for DSC | 12 |
| 4.4.7.1 | Definition | 12 |
| 4.4.7.2 | Limit..... | 12 |
| 4.4.7.3 | Conformance..... | 12 |
| 4.4.8 | Testing of generated call sequences..... | 12 |
| 4.4.8.1 | Definition | 12 |
| 4.4.8.2 | Limit..... | 12 |
| 4.4.8.3 | Conformance..... | 12 |
| 4.4.9 | Harmonic distortion and rated audio-frequency output power | 12 |
| 4.4.9.1 | Definition | 12 |
| 4.4.9.2 | Limit..... | 12 |
| 4.4.9.3 | Conformance..... | 12 |
| 4.4.10 | Receiver audio frequency response | 13 |
| 4.4.10.1 | Definition | 13 |
| 4.4.10.2 | Limit..... | 13 |
| 4.4.10.3 | Conformance..... | 13 |
| 4.4.11 | Receiver residual noise level | 13 |
| 4.4.11.1 | Definition | 13 |
| 4.4.11.2 | Limit..... | 13 |
| 4.4.11.3 | Conformance..... | 13 |
| 4.4.12 | Squelch operation | 13 |
| 4.4.12.1 | Definition | 13 |
| 4.4.12.2 | Limit..... | 13 |
| 4.4.12.3 | Conformance..... | 13 |
| 4.4.13 | Squelch hysteresis..... | 13 |
| 4.4.13.1 | Definition | 13 |
| 4.4.13.2 | Limit..... | 13 |
| 4.4.13.3 | Conformance..... | 13 |
| 4.4.14 | Dynamic range..... | 14 |
| 4.4.14.1 | Definition | 14 |
| 4.4.14.2 | Limit..... | 14 |
| 4.4.14.3 | Conformance..... | 14 |
| 4.4.15 | Verification of correct decoding of various types of DSC calls | 14 |
| 4.4.15.1 | Definition | 14 |
| 4.4.15.2 | Limit..... | 14 |
| 4.4.15.3 | Conformance..... | 14 |
| 5 | Testing for compliance with technical requirements..... | 14 |
| 5.1 | Test conditions, power supply and ambient temperatures | 14 |
| 5.2 | Interpretation of the measurement results | 14 |
| 5.3 | Essential radio test suites..... | 15 |
| 5.3.1 | Environmental tests..... | 15 |
| 5.3.1.1 | Introduction..... | 15 |
| 5.3.1.2 | Procedure | 15 |
| 5.3.1.3 | Performance check..... | 15 |
| 5.3.1.4 | Vibration test..... | 15 |
| 5.3.1.4.1 | Definition..... | 15 |
| 5.3.1.4.2 | Limit | 15 |
| 5.3.1.4.3 | Conformance | 15 |
| 5.3.1.5 | Temperature tests | 15 |
| 5.3.1.5.1 | Dry heat | 15 |
| 5.3.1.5.1.1 | Definition | 15 |
| 5.3.1.5.1.2 | Limit | 15 |
| 5.3.1.5.1.3 | Conformance..... | 16 |
| 5.3.1.5.2 | Damp heat..... | 16 |
| 5.3.1.5.2.1 | Definition | 16 |

| | | |
|-------------------------------|-------------------------------------------------------------------------------|-----------|
| 5.3.1.5.2.2 | Limit | 16 |
| 5.3.1.5.2.3 | Conformance..... | 16 |
| 5.3.1.5.3 | Low temperature..... | 16 |
| 5.3.1.5.3.1 | Definition | 16 |
| 5.3.1.5.3.2 | Limit | 16 |
| 5.3.1.5.3.3 | Conformance..... | 16 |
| 5.3.2 | Conformance tests | 16 |
| 5.3.2.1 | Sensitivity of the modulator, including microphone | 16 |
| 5.3.2.2 | Audio frequency response | 16 |
| 5.3.2.3 | Audio frequency harmonic distortion of the emission | 16 |
| 5.3.2.4 | Residual modulation of the transmitter | 16 |
| 5.3.2.5 | Frequency error (demodulated DSC signal)..... | 16 |
| 5.3.2.6 | Modulation index for DSC..... | 17 |
| 5.3.2.7 | Modulation rate for DSC..... | 17 |
| 5.3.2.8 | Testing of generated call sequences | 17 |
| 5.4 | Other test suites | 17 |
| 5.4.1 | General..... | 17 |
| 5.4.2 | Harmonic distortion and rated audio-frequency output power | 17 |
| 5.4.3 | Receiver audio frequency response | 17 |
| 5.4.4 | Receiver residual noise level | 17 |
| 5.4.5 | Squelch operation | 17 |
| 5.4.6 | Squelch hysteresis..... | 17 |
| 5.4.7 | Dynamic range..... | 17 |
| 5.4.8 | Verification of correct decoding of various types of DSC calls | 17 |
| Annex A (normative): | HS Requirement and conformance Test specifications Table (HS-RTT)..... | 18 |
| Annex B (informative): | The EN title in the official languages | 21 |
| Annex C (informative): | Bibliography..... | 23 |
| History | | 24 |

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations and following the Commission Decision 2000/638/EC of 22 September 2000.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The present document is part 3 of a multi-part deliverable covering the Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF radiotelephone equipment for general communications and associated equipment for Class "D" Digital Selective Calling (DSC), as identified below:

- Part 1: "Technical characteristics and methods of measurement";
- Part 2: "Harmonized EN under article 3.2 of the R&TTE Directive";
- Part 3: "Harmonized EN under article 3.3 (e) of the R&TTE Directive".**

| National transposition dates | |
|----------------------------------------------------------------------------------------|-----------------|
| Date of adoption of this EN: | 19 January 2007 |
| Date of latest announcement of this EN (doa): | 30 April 2007 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 October 2007 |
| Date of withdrawal of any conflicting National Standard (dow): | 31 October 2008 |

1 Scope

The present document covers the minimum requirements for general communication for shipborne fixed installations using a VHF radiotelephone operating in certain frequency bands allocated to the maritime mobile service using both 25 kHz and 12,5 kHz channels with associated equipment for DSC - class D.

The present document is intended to cover the provisions of Directive 1999/5/EC [1] (R&TTE Directive) article 3.3 (e), which states that radio equipment within the scope of the present document shall be so constructed that: "it supports certain features ensuring access to emergency services".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [1] will apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org/>.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

- [1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [2] ITU-R Recommendation M.493-11 (2004): "Digital selective-calling system for use in the maritime mobile service".
- [3] ETSI EN 301 025-1 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF radiotelephone equipment for general communications and associated equipment for Class "D" Digital Selective Calling (DSC); Part 1: Technical characteristics and methods of measurement".
- [4] EC decision 2004/71/EC of 4 September 2003 on essential requirements relating to marine radio communication equipment which is intended to be used on non-SOLAS vessels and to participate in the Global Maritime Distress and Safety System (GMDSS).
- [5] ETSI TR 100 028-1 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [1] and the following apply:

class D: class D equipment is intended to provide minimum facilities for VHF DSC distress, urgency and safety as well as routine calling and reception, not necessarily in full accordance with IMO GMDSS carriage requirements for VHF installations

NOTE: See ITU-R Recommendation M.493-11 [2].

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

G2B: phase-modulation with digital information, with a sub-carrier for DSC operation

G3E: phase-modulation (Frequency modulation with a pre-emphasis of 6 dB/octave) for speech

modulation index: ratio between the frequency deviation and the frequency of the modulation signal

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-------|-------------------------------------------------|
| DSC | Digital Selective Calling |
| GMDSS | Global Maritime Distress and Safety System |
| IMO | International Maritime Organization |
| MMSI | Maritime Mobile Service Identity |
| R&TTE | Radio and Telecommunications Terminal Equipment |
| RF | Radio Frequency |
| SINAD | Signal, Noise And Distortion |
| SOLAS | Safety of Life and Sea |
| VHF | Very High Frequency |

4 Technical requirements specifications

4.1 Environmental profile

Tests defined in the present document shall be carried out at representative points within the boundary limits of the declared operational environmental profile which, as a minimum, shall be that specified in the test conditions contained in the present document.

As technical performance varies subject to environmental conditions, tests shall be carried out under a sufficient variety of environmental conditions as specified in the present document to give confidence of compliance for the affected technical requirements. These environmental conditions represent those required by Article 2 of EC decision 2004/71/EC [4] (which shall also be within the boundary limits of the declared operational environmental profile).

4.2 General, operational and technical requirements

4.2.1 General and operational requirements

4.2.1.1 Requirements

The general and operational requirements are defined in EN 301 025-1 [3], clause 4.

4.2.1.2 Conformance

The manufacturer shall declare that compliance to these requirements is achieved and shall provide relevant documentation.

4.2.2 Technical requirements

4.2.2.1 Requirements

The technical requirements are defined in EN 301 025-1 [3], clause 5.

4.2.2.2 Conformance

The manufacturer shall declare that compliance to these requirements is achieved and shall provide relevant documentation.

4.3 Environmental requirements

4.3.1 Vibration test

4.3.1.1 Definition

This test is defined in EN 301 025-1 [3], clause 7.4.1.

4.3.1.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 301 025-1 [3], clause 7.3.

There shall be no harmful deterioration of the equipment visible.

4.3.1.3 Conformance

Relevant environment tests as defined in clause 5.3.1.4 shall be carried out.

4.3.2 Temperature tests

4.3.2.1 Definition

This series of tests is defined in EN 301 025-1 [3], clause 7.5.1.

4.3.2.2 Dry heat

4.3.2.2.1 Definition

This test is defined in EN 301 025-1 [3], clause 7.5.2.1.

4.3.2.2.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 301 025-1 [3], clause 7.3.

4.3.2.2.3 Conformance

Relevant environment tests as defined in clause 5.3.1.5.1 shall be carried out.

4.3.2.3 Damp heat

4.3.2.3.1 Definition

This test is defined in EN 301 025-1 [3], clause 7.5.3.1.

4.3.2.3.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 301 025-1 [3], clause 7.3.

4.3.2.3.3 Conformance

Relevant environment tests as defined in clause 5.3.1.5.2 shall be carried out.

4.3.2.4 Low temperature

4.3.2.4.1 Definition

This test is defined in EN 301 025-1 [3], clause 7.5.4.1.

4.3.2.4.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 301 025-1 [3], clause 7.3.

4.3.2.4.3 Conformance

Relevant environment tests as defined in clause 5.3.1.3 shall be carried out.

4.4 Conformance requirements

4.4.1 Sensitivity of the modulator, including microphone

4.4.1.1 Definition

This test is defined in EN 301 025-1 [3], clause 8.4.1.

4.4.1.2 Limit

The frequency deviation shall be as stated in EN 301 025-1 [3], clause 8.4.3.

4.4.1.3 Conformance

Conformance tests as defined in clause 5.3.2.1 shall be carried out.

4.4.2 Audio frequency response

4.4.2.1 Definition

This test is defined in EN 301 025-1 [3], clause 8.5.1.

4.4.2.2 Limit

The audio frequency response shall lie within the limits shown in EN 301 025-1 [3], clause 8.5.3, figure 2.

4.4.2.3 Conformance

Conformance tests as defined in clause 5.3.2.2 shall be carried out.

4.4.3 Audio frequency harmonic distortion of the emission

4.4.3.1 Definition

This test is defined in EN 301 025-1 [3], clause 8.6.1.

4.4.3.2 Limit

The harmonic distortion limit shall be as stated in EN 301 025-1 [3], clause 8.6.3.

4.4.3.3 Conformance

Conformance tests as defined in clause 5.3.2.3 shall be carried out.

4.4.4 Residual modulation of the transmitter

4.4.4.1 Definition

This test is defined in EN 301 025-1 [3], clause 8.11.1.

4.4.4.2 Limit

The residual modulation shall not exceed the limit stated in EN 301 025-1 [3], clause 8.11.3.

4.4.4.3 Conformance

Conformance tests as defined in clause 5.3.2.4 shall be carried out.

4.4.5 Frequency error (demodulated DSC signal)

4.4.5.1 Definition

This test is defined in EN 301 025-1 [3], clause 8.12.1.

4.4.5.2 Limit

The frequency error shall not exceed the limit stated in EN 301 025-1 [3], clause 8.12.3.

4.4.5.3 Conformance

Conformance tests as defined in clause 5.3.2.5 shall be carried out.

4.4.6 Modulation index for DSC

4.4.6.1 Definition

This test is defined in EN 301 025-1 [3], clause 8.13.1.

4.4.6.2 Limit

The modulation index shall not exceed the limit stated in EN 301 025-1 [3], clause 8.13.3.

4.4.6.3 Conformance

Conformance tests as defined in clause 5.3.2.6 shall be carried out.

4.4.7 Modulation rate for DSC

4.4.7.1 Definition

This test is defined in EN 301 025-1 [3], clause 8.14.1.

4.4.7.2 Limit

The frequency shall not exceed the limit stated in EN 301 025-1 [3], clause 8.13.3.

4.4.7.3 Conformance

Conformance tests as defined in clause 5.3.2.7 shall be carried out.

4.4.8 Testing of generated call sequences

4.4.8.1 Definition

This test is defined in EN 301 025-1 [3], clause 8.15.1.

4.4.8.2 Limit

The requirements stated in EN 301 025-1 [3], clause 8.15.3 shall be met.

4.4.8.3 Conformance

Conformance tests as defined in clause 5.3.2.8 shall be carried out.

4.4.9 Harmonic distortion and rated audio-frequency output power

4.4.9.1 Definition

This test is defined in EN 301 025-1 [3], clause 9.1.1.

4.4.9.2 Limit

The rated audio-frequency output power shall comply with the limits stated in EN 301 025-1 [3], clause 9.1.3.

4.4.9.3 Conformance

Conformance tests as defined in clause 5.4.2 may be carried out.

4.4.10 Receiver audio frequency response

4.4.10.1 Definition

This test is defined in EN 301 025-1 [3], clause 9.2.1.

4.4.10.2 Limit

The audio frequency response shall lie within the limits shown in EN 301 025-1 [3], clause 9.2.3, figure 5.

4.4.10.3 Conformance

Conformance tests as defined in clause 5.4.3 may be carried out.

4.4.11 Receiver residual noise level

4.4.11.1 Definition

This test is defined in EN 301 025-1 [3], clause 9.11.1.

4.4.11.2 Limit

The receiver residual noise level shall not exceed the limit stated in EN 301 025-1 [3], clause 9.11.3.

4.4.11.3 Conformance

Conformance tests as defined in clause 5.4.4 may be carried out.

4.4.12 Squelch operation

4.4.12.1 Definition

This test is defined in EN 301 025-1 [3], clause 9.12.1.

4.4.12.2 Limit

The squelch operation shall comply with the limits stated in EN 301 025-1 [3], clause 9.12.3.

4.4.12.3 Conformance

Conformance tests as defined in clause 5.4.5 may be carried out.

4.4.13 Squelch hysteresis

4.4.13.1 Definition

This test is defined in EN 301 025-1 [3], clause 9.13.1.

4.4.13.2 Limit

The squelch hysteresis shall comply with the limits stated in EN 301 025-1 [3], clause 9.13.3.

4.4.13.3 Conformance

Conformance tests as defined in clause 5.4.6 may be carried out.

4.4.14 Dynamic range

4.4.14.1 Definition

This test is defined in EN 301 025-1 [3], clause 10.6.1.

4.4.14.2 Limit

The bit error ratio shall not exceed the limit stated in EN 301 025-1 [3], clause 10.6.3.

4.4.14.3 Conformance

Conformance tests as defined in clause 5.4.7 may be carried out.

4.4.15 Verification of correct decoding of various types of DSC calls

4.4.15.1 Definition

This test is defined in EN 301 025-1 [3], clause 10.8.1.

4.4.15.2 Limit

The requirements stated in EN 301 025-1 [3], clause 10.8.3 shall be met.

4.4.15.3 Conformance

Conformance tests as defined in clause 5.4.8 may be carried out.

5 Testing for compliance with technical requirements

5.1 Test conditions, power supply and ambient temperatures

The general conditions for measurement as stated in EN 301 025-1 [3], clause 6 shall apply.

5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the recorded value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 1.

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028-1 [5] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 1 is based on such expansion factors.

Table 1: Maximum measurement uncertainty

| Parameter | Maximum uncertainty |
|-----------------------------------------------|------------------------|
| Radio Frequency (RF) | $\pm 1 \times 10^{-7}$ |
| RF power/level | $\pm 0,75$ dB |
| Audio output power | $\pm 0,5$ dB |
| Amplitude characteristics of receiver limiter | $\pm 1,5$ dB |
| Sensitivity at 20 dB SINAD | ± 3 dB |
| Two-signal measurement | ± 4 dB |
| Three-signal measurement | ± 3 dB |

5.3 Essential radio test suites

5.3.1 Environmental tests

5.3.1.1 Introduction

Environmental tests shall be carried out before tests are performed on the same equipment with respect to the other requirements of the present document.

5.3.1.2 Procedure

This test procedure is defined in EN 301 025-1 [3], clause 7.2.

5.3.1.3 Performance check

The "performance check" series of tests are defined in EN 301 025-1 [3], clause 7.3.

5.3.1.4 Vibration test

5.3.1.4.1 Definition

This test is defined in EN 301 025-1 [3], clause 7.4.1.

5.3.1.4.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 301 025-1 [3], clause 7.3.

There shall be no harmful deterioration of the equipment visible.

5.3.1.4.3 Conformance

Relevant environment tests as defined in clause 5.3.1 shall be carried out.

5.3.1.5 Temperature tests

5.3.1.5.1 Dry heat

5.3.1.5.1.1 Definition

This test is defined in EN 301 025-1 [3], clause 7.5.2.1.

5.3.1.5.1.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 301 025-1 [3], clause 7.3.

5.3.1.5.1.3 Conformance

Relevant environment tests as defined in clause 5.3.1 shall be carried out.

5.3.1.5.2 Damp heat

5.3.1.5.2.1 Definition

This test is defined in EN 301 025-1 [3], clause 7.5.3.1.

5.3.1.5.2.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 301 025-1 [3], clause 7.3.

5.3.1.5.2.3 Conformance

Relevant environment tests as defined in clause 5.3.1 shall be carried out.

5.3.1.5.3 Low temperature

5.3.1.5.3.1 Definition

This test is defined in EN 301 025-1 [3], clause 7.5.4.1.

5.3.1.5.3.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 301 025-1 [3], clause 7.3.

5.3.1.5.3.3 Conformance

Relevant environment tests as defined in clause 5.3.1 shall be carried out.

5.3.2 Conformance tests

5.3.2.1 Sensitivity of the modulator, including microphone

The test specified in EN 301 025-1 [3], clause 8.4.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.1.2 in order to prove compliance with the requirement.

5.3.2.2 Audio frequency response

The test specified in EN 301 025-1 [3], clause 8.5.2 shall be carried out .

The results obtained shall be compared to the limits in clause 4.4.2.2 in order to prove compliance with the requirement.

5.3.2.3 Audio frequency harmonic distortion of the emission

The test specified in EN 301 025-1 [3], clause 8.6.2 shall be carried out The results obtained under each of the stated test conditions shall be compared to the limits in clause 4.4.3.2 in order to prove compliance with the requirement.

5.3.2.4 Residual modulation of the transmitter

The test specified in EN 301 025-1 [3], clause 8.11.2 shall be carried out The results obtained shall be compared to the limits in clause 4.4.4.2 in order to prove compliance with the requirement.

5.3.2.5 Frequency error (demodulated DSC signal)

The test specified in EN 301 025-1 [3], clause 8.12.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.5.2 in order to prove compliance with the requirement.

5.3.2.6 Modulation index for DSC

The test specified in EN 301 025-1 [3], clause 8.13.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.6.2 in order to prove compliance with the requirement.

5.3.2.7 Modulation rate for DSC

The test specified in EN 301 025-1 [3], clause 8.14.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.7.2 in order to prove compliance with the requirement.

5.3.2.8 Testing of generated call sequences

The test specified in EN 301 025-1 [3], clause 8.15.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.8.2 in order to prove compliance with the requirement.

5.4 Other test suites

5.4.1 General

The requirements in clauses 4.4.9 to 4.4.15 inclusive have been set on the assumption that the test specifications in clauses 5.4.2 to 5.4.8 will be used to verify the performance of the equipment.

5.4.2 Harmonic distortion and rated audio-frequency output power

The test specified in EN 301 025-1 [3], clause 9.1.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.9.2 in order to prove compliance with the requirement.

5.4.3 Receiver audio frequency response

The test specified in EN 301 025-1 [3], clause 9.2.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.10.2 in order to prove compliance with the requirement.

5.4.4 Receiver residual noise level

The test specified in EN 301 025-1 [3], clause 9.11.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.11.2 in order to prove compliance with the requirement.

5.4.5 Squelch operation

The test specified in EN 301 025-1 [3], clause 9.12.2 shall be carried out. The results obtained in each of the tests shall be compared to the appropriate limits in clause 4.4.12.2 in order to prove compliance with the requirement.

5.4.6 Squelch hysteresis

The test specified in EN 301 025-1 [3], clause 9.13.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.13.2 in order to prove compliance with the requirement.

5.4.7 Dynamic range

The test specified in EN 301 025-1 [3], clause 10.6.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.14.2 in order to prove compliance with the requirement.

5.4.8 Verification of correct decoding of various types of DSC calls

The test specified in EN 301 025-1 [3], clause 10.8.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.15.2 in order to prove compliance with the requirement.

Annex A (normative): HS Requirement and conformance Test specifications Table (HS-RTT)

The HS Requirements and conformance Test specifications Table (HS-RTT) in table A1 serves a number of purposes, as follows:

- it provides a statement of all the essential requirements in words and by cross reference to a specific clause in the present document or to a specific clause in a specific referenced document;
- it provides a statement of all the test procedure corresponding to those essential requirements by cross reference to specific clause(s) in the present document or to a specific clause(s) in specific referenced document(s);
- it qualifies each requirement to be either:
 - Unconditional: meaning that the requirement applies in all circumstances; or
 - Conditional: meaning that the requirement is dependent on the supplier having chosen to support optional functionality defined within the schedule;
- in the case of Conditional requirements, it associates the requirement with the particular optional service or functionality;
- it qualifies each test procedure to be either:
 - Essential: meaning that it is included with the Essential Radio Test Suite and therefore the requirement shall be demonstrated to be met in accordance with the referenced procedures;
 - Other: meaning that the test procedure is illustrative but other means of demonstrating compliance with the requirement are permitted;
- when the schedule is completed in respect of a particular equipment, including the testing outcomes, and including a completed version of Table A1 it provides a means to assert the "presumption of conformity" with the HS.

Table A.1: HS Requirements and conformance Test specifications Table (HS-RTT)

| Harmonized Standard EN 301 025-3 | | | | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|----------------------|--------------------------------------|-----------|--------------------|----------------------|
| The following technical requirements and test specifications are relevant to the presumption of conformity under Article 3.3 (e) of the R&TTE Directive | | | | | | |
| Technical Requirement reference | | | Technical Requirement Conditionality | | Test Specification | |
| No | Description | Reference: Clause No | U/C | Condition | E/O | Reference: Clause No |
| 1 | General and operational requirements | 4.2.1 | U | | X | |
| 2 | Construction | 4.2.1.2 | U | | X | |
| 3 | Controls and indicators | 4.2.1.3 | U | | X | |
| 4 | Facilities for coding and decoding of DSC | 4.2.1.4 | U | | X | |
| 5 | DSC display | 4.2.1.5 | U | | X | |
| 6 | Handset and loudspeaker | 4.2.1.6 | U | | X | |

| Harmonized Standard EN 301 025-3 | | | | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|---------|---------------------------------------------|--|---------------------------|---------|
| The following technical requirements and test specifications are relevant to the presumption of conformity under Article 3.3 (e) of the R&TTE Directive | | | | | | |
| Technical Requirement reference | | | Technical Requirement Conditionality | | Test Specification | |
| 7 | Safety precautions | 4.2.1.7 | U | | X | |
| 8 | Labelling | 4.2.1.8 | U | | X | |
| 9 | Warm up | 4.2.1.9 | U | | X | |
| 10 | Technical requirements | 4.2.2 | U | | X | |
| 11 | Class of emission and modulation characteristics | 4.2.2.2 | U | | X | |
| 12 | Facilities for DSC transmission and reception | 4.2.2.3 | U | | X | |
| 13 | Ships identity – MMSI and Group MMSI | 4.2.2.4 | U | | X | |
| 14 | Entry of position information | 4.2.2.5 | U | | X | |
| 15 | Alarm circuits | 4.2.2.6 | U | | X | |
| 16 | Facilities for automatic identification | 4.2.2.7 | U | | X | |
| 17 | Multiple watch facilities | 4.2.2.8 | U | | X | |
| 18 | Sensitivity of the modulator, including microphone | 4.4.1 | U | | E | 5.3.2.1 |
| 19 | Audio frequency response | 4.4.2 | U | | E | 5.3.2.2 |
| 20 | Audio frequency harmonic distortion of the emission | 4.4.3 | U | | E | 5.3.2.3 |
| 21 | Residual modulation of the transmitter | 4.4.4 | U | | E | 5.3.2.4 |
| 22 | Frequency error (demodulated DSC signal) | 4.4.5 | U | | E | 5.3.2.5 |
| 23 | Modulation index for DSC | 4.4.6 | U | | E | 5.3.2.6 |
| 24 | Modulation rate for DSC | 4.4.7 | U | | E | 5.3.2.7 |
| 25 | Testing of call generated sequences | 4.4.8 | U | | E | 5.3.2.8 |
| 26 | Harmonic distortion and rated audio-frequency output power | 4.4.9 | U | | O | 5.4.2 |
| 27 | Receiver audio frequency response | 4.4.10 | U | | O | 5.4.3 |

| Harmonized Standard EN 301 025-3 | | | | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|--------|--------------------------------------|--|--------------------|-------|
| The following technical requirements and test specifications are relevant to the presumption of conformity under Article 3.3 (e) of the R&TTE Directive | | | | | | |
| Technical Requirement reference | | | Technical Requirement Conditionality | | Test Specification | |
| 28 | Receiver residual noise level | 4.4.11 | U | | O | 5.4.4 |
| 29 | Squelch operation | 4.4.12 | U | | O | 5.4.5 |
| 30 | Squelch hysteresis | 4.4.13 | U | | O | 5.4.6 |
| 31 | Dynamic range | 4.4.14 | U | | O | 5.4.7 |
| 32 | Verification of correct decoding of various types of DSC calls | 4.4.15 | U | | O | 5.4.8 |

Key to columns:

Essential Requirement:

No A unique identifier for one row of the table which may be used to identify an essential requirement or its test specification.

Description A textual reference to the requirement.

Clause Number Identification of clause(s) defining the essential requirement in the present document unless another document is referenced explicitly.

Conditionality:

U/C Indicates whether the requirement is to be *unconditionally* applicable (U) or is *conditional* upon the suppliers claimed functionality of the equipment (C).

Condition Explains the conditions when the requirement shall or shall not be applicable for a requirement which is classified "conditional".

Test Specification:

E/O Indicates whether the test specification forms part of the Essential Radio Test Suite (E) or whether it is one of the Other Test Suite (O).

NOTE: All tests whether "E" or "O" are relevant to the requirements. Rows designated "E" collectively make up the Essential Radio Test Suite; those designated "O" make up the Other Test Suite; for those designated "X" there is no test specified corresponding to the requirement. All tests classified "E" shall be performed as specified with satisfactory outcomes is a necessary condition for a presumption of conformity. Requirements associated with tests classified "O" or "X" must be complied with as a necessary condition for presumption of conformity, although conformance with the requirement may be claimed by an equivalent test or by manufacturer's assertion supported by appropriate entries in the technical construction file.

Clause Number Identification of clause(s) defining the test specification in the present, document unless another document is referenced explicitly. Where no test is specified (that is, where the previous field is "X") this field remains blank.

Annex B (informative): The EN title in the official languages

| Language | EN title |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Bulgaria | Електромагнитна съвместимост и въпроси на радиоспектъра (ERM). VHF радиотелефони за далекосъобщения с общо предназначение и съответни съоръжения за клас "D" цифрово селективно избиране (DSC). Част 3: Хармонизиран европейски стандарт (EN) според член 3.3(e) от Директивата за радиосъоръжения и крайни далекосъобщителни устройства (R&TTED) |
| Czech | Elektromagnetická kompatibilita a rádiové spektrum (ERM) - Radiotelefonní zařízení VHF pro všeobecnou komunikaci a přidružená zařízení třídy D s digitálním selektivním voláním (DSC) - Část 3: Harmonizovaná EN podle článku 3.3 (e) Směrnice R&TTE |
| Danish | Elektromagnetisk kompatibilitet og Radiospektrum Anliggender (ERM); VHF radiotelefoni udstyr til generel kommunikation og tilknyttet udstyr til "Klasse D" Digitale, selektive opkald (DSC); Del 3: Harmoniseret EN, som dækker de væsentlige krav i R&TTE direktivets artikel 3.3e |
| Dutch | Elektromagnetische compatibiliteit en radiospectrum zaken (ERM); VHF radiotelefonie apparatuur tbv algemene communicatie en bijbehorende apparatuur voor klasse "D" Digital Selective Calling (DSC); Deel 3: Geharmoniseerde EN welke invulling geeft aan de wezenlijke vereisten, neergelegd in artikel 3.3e van de R&TTE Directive |
| English | Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF radiotelephone equipment for general communications and associated equipment for Class "D" Digital Selective Calling (DSC); Part 3: Harmonized EN under article 3.3e of the R&TTE Directive |
| Estonian | Elektromagnetilise ühilduvuse ja raadiospektri küsimused (ERM); Üldise sidepidamise VHF raadiotelefoniseadmed ja klassi D digitaalselektiivväljakutse (DSC) lisaseadmed; Osa 3: Harmoneeritud EN R&TTE direktiivi artikli 3.3e alusel |
| Finnish | Sähkömagneettinen yhteensopivuus ja radiospektriasiat (ERM); Yleisen liikenteen meri-VHF -radiopuhelimet ja D-luokan digitaalisen selektiivikutsum (DSC) lisälaitteet; Osa 3: Harmonisoitu EN R&TTE - direktiivin artiklan 3.3e olennaisten vaatimusten mukaisesti |
| French | CEM et spectre radioélectrique (ERM) - Appareils de radiotéléphone en VHF pour la téléphonie générale et appareils associés pour Appel numérique sélectif (DSC) de classe "D" - Partie 3: EN harmonisée de l'article 3.3e de la Directive R&TTE |
| German | Elektromagnetische Verträglichkeit und Funkspektrumangelegenheiten (ERM); UKW-Sprechfunkanlagen des mobilen Seefunkdienstes für "allgemeine Kommunikation" mit Zusatzeinrichtung für den digitalen Selektivruf (DSC) Klasse D; Teil 3: Harmonisierte Europäische Norm (EN) mit wesentlichen Anforderungen nach R&TTE-Richtlinie Artikel 3.3e |
| Greek | Ηλεκτρομαγνητική Συμβατότητα και Θέματα Ραδιοφάσματος (ERM) - Συσκευή ραδιοτηλεφώνου VHF για γενικές επικοινωνίες και συσχετισμένος εξοπλισμός για ψηφιακή επιλεκτική κλήση (DSC) κατηγορίας D - Μέρος 3: Εναρμονισμένο EN για την κάλυψη του άρθρου 3.3 (e) της Οδηγίας R&TTE |
| Hungarian | Elektromágneses összeférhetőségi és rádióspektrumügyek (ERM). Általános kommunikációs célú VHF rádiótelefon-berendezések, és az ezekhez tartozó, D osztályú, digitális, szelektív hívóberendezések (DSC). 3. rész: Az R&TTE-irányelv 3.3e. cikkelye alá tartozó, harmonizált európai szabvány |
| Icelandic | Þættir sem varða rafsegulsviðssamhæfi og fjarskiptatiðni (ERM); VHF talstöðvarbúnaður til almennra fjarskipta og tengdur búnaður fyrir stafrænt valkall (DSC) í flokki 'D'. 3. hluti: Samræmdur Evrópustaðall skv. e-lið 3. mgr. 3. gr. í tilskipun 1999/5/EC um fjarskiptabúnað og endabúnað til fjarskipta |
| Italian | Compatibilità elettromagnetica e Questioni relative allo spettro delle radiofrequenze (ERM); apparecchiature radiotelefoniche VHF per comunicazioni generiche ed apparecchiature associate per Chiamate Digitali Selettive (DSC) di Classe "D"; Part 3: Norma Europea armonizzata per l'articolo 3.3e della direttiva R&TTE |
| Latvian | Elektromagnētiskā saderība un radiofrekvenču spektra jautājumi (ERM) - Ultrašviļņu (VHF) radiotelefona iekārta vispārējiem sakariem un saistītā iekārta "D" klases ciparu selektīvajam izsaukumam (DSC) - 3.daļa: Harmonizēts EN, kas atbilst R&TTE Direktīvas 3.3 (e) pantam |
| Lithuanian | Elektromagnetinio suderinamumo ir radijo dažnių spektro dalykai. Bendrųjų ryšių LAD radiotelefono įrenginiai ir su jais susiję D klasės skaitmeninio atrankiojo kvietimo (SAK) įrenginiai. 3 dalis. Darnusis Europos standartas pagal 1999/5/EC direktyvos 3.3 (e) straipsnį |
| Maltese | Kompatibilità elettromanjetika u materji relatati ma' spettru radjofoniku (ERM); Tagħmir tar-radjutelefonija fuq il-VHF għal komunikazzjonijiet generali u tagħmir assocjati għal Sejhat Selettivi Digitali ta' Klassi "D" (DSC) Parti 3: EN armonizzata taħt l-artiklu 3.3 (e) tad-Direttiva R&TTE |
| Norwegian | Elektromagnetisk kompatibilitet og Radiospektrums spørsmål (ERM); VHF radiotelefonutstyr for generell kommunikasjon og assosiert utstyr for klasse "D" Digital selektiv oppringing (DSC); Del 3: Harmonisert EN i R&TTE-direktivets artikkel 3.3e |

| Language | EN title |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Polish | Kompatybilność Elektromagnetyczna i Zagadnienia Widma Radiowego (ERM) - Urządzenia radiotelefoniczne VHF dla łączności ogólnej i związane wyposażenie do wywoływania selektywnego cyfrowego (DSC) "klasy D" - Część 3: Zharmonizowana EN zgodna z artykułem 3.3(e) dyrektywy R&TTE |
| Portuguese | Assuntos de Espectro Radioelétrico e Compatibilidade Electromagnética (ERM); Equipamento radiotelefónico VHF destinado a comunicações genéricas e equipamento associado para Chamada Selectiva Digital (DSC) de Classe "D"; Parte 3: EN harmonizada cobrindo os requisitos essenciais no âmbito do Artigo 3.3e da Directiva R&TTE |
| Romania | |
| Slovak | Elektromagnetická kompatibilita a závislosti rádiového spektra (ERM). Rádiotelefonne zariadenia VHF na všeobecné komunikácie a pridružené zariadenia triedy D digitálneho selektívneho volania (DSC). Časť 3: Harmonizovaná EN podľa článku 3.3 (e) smernice R&TTE |
| Slovenian | Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) – Radiotelefonska oprema VHF za splošne komunikacije in pripadajoča oprema za digitalni selektivni klic (DSC) razreda "D" – 3. del: Harmonizirani EN v skladu s členom 3.3(e) direktive R&TTE |
| Spanish | Compatibilidad electromagnética y cuestiones de espectro de radiofrecuencia (ERM); Equipos radioteléfono VHF para comunicaciones generales y equipos asociados para clase "D" Llamada selectiva digital (DSC); Parte 3: EN armonizada cubriendo los requisitos esenciales según el artículo 3.3e de la directiva de R&TTE |
| Swedish | Elektromagnetisk kompatibilitet och radio-spektrumfrågor (ERM); Radiotelefonutrustning på VHF avsedd för allmänna kommunikationer och associerad utrustning för Klass "D" digitalt selektivt anrop (DSC); Del 3: Harmoniserad EN enligt artikel 3.3e i R&TTE-direktivet |

Annex C (informative): Bibliography

- Council Directive 98/34/EC of the European Parliament and of the Council laying down a procedure for the provision of information in the field of Technical Standards and Regulations and of rules on Information Society Services.
- Commission Decision of 22 September 2000 on the application of Article 3(3)(e) of Directive 1999/5/EC to marine radiocommunication equipment intended to be fitted to seagoing non-SOLAS vessel and which is intended to participate in the global maritime distress and safety system (GMDSS) and not covered by Council Directive 96/98/EC on marine equipment.

History

| Document history | | |
|-------------------------|----------------|---------------------------|
| V1.1.1 | August 1998 | Publication as EN 301 025 |
| V1.1.1 | May 2001 | Publication |
| V1.2.1 | September 2004 | Publication |
| V1.3.1 | February 2007 | Publication |
| | | |