



**Methods for Testing and Specification (MTS);
The Testing and Test Control Notation version 3;
TTCN-3 Language Extensions: Extended TRI**

Reference

RES/MTS-202789xTRI ed131

Keywords

testing, TTCN-3

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references	6
3 Definitions and abbreviations	6
3.1 Definitions	6
3.2 Abbreviations	6
4 Package conformance and compatibility	6
5 Package concepts for the core language	7
6 Package semantics	7
7 TRI extensions for the package	7
7.1 Changes to clause 5.2 of ES 201 873-5, Error handling	8
7.2 Changes to clause 5.5.2 Connection handling operations	8
7.3 Changes to clause 5.5.3 Message based communication operations	9
7.4 Addition to clause 5.5.3 Message based communication operations	11
7.5 Changes to clause 5.5.4 Procedure based communication operations	12
7.6 Changes to clause 5.6.3 Miscellaneous operations	20
7.7 Changes to clause 6 Java language mapping	21
7.8 Changes to clause 7 C language mapping	23
7.9 Changes to clause 8 C++ language mapping	25
7.10 Changes to clause 9 C# language mapping	28
8 TCI extensions for the package	30
History	31

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This final draft ETSI Standard (ES) has been produced by ETSI Technical Committee Methods for Testing and Specification (MTS), and is now submitted for the ETSI standards Membership Approval Procedure.

The use of underline (additional text) and strike through (deleted text) highlights the differences between base document and extended documents.

The present document relates to the multi-part standard covering the Testing and Test Control Notation version 3, as identified below:

- ES 201 873-1 [1]: "TTCN-3 Core Language";
- ES 201 873-3 [i.2]: "TTCN-3 Graphical presentation Format (GFT)";
- ES 201 873-4 [2]: "TTCN-3 Operational Semantics";
- ES 201 873-5 [3]: "TTCN-3 Runtime Interface (TRI)";
- ES 201 873-6 [4]: "TTCN-3 Control Interface (TCI)";
- ES 201 873-7 [i.3]: "Using ASN.1 with TTCN-3";
- ES 201 873-8 [i.4]: "The IDL to TTCN-3 Mapping";
- ES 201 873-9 [i.5]: "Using XML schema with TTCN-3";
- ES 201 873-10 [i.6]: "TTCN-3 Documentation Comment Specification";
- ES 202 784 [i.8]: "TTCN-3 Language Extensions: Advanced Parameterization";
- ES 202 781 [i.7]: "TTCN-3 Language Extensions: Configuration and Deployment Support";
- ES 202 782 [i.10]: "TTCN-3 Language Extensions: Performance and Real-Time Testing";
- ES 202 785 [i.9]: "TTCN-3 Language Extensions: Behaviour Types".

1 Scope

The present document defines the Extended TRI package of TTCN-3. TTCN-3 can be used for the specification of all types of reactive system tests over a variety of communication ports. Typical areas of application are protocol testing (including mobile and Internet protocols), service testing (including supplementary services), module testing, testing of CORBA based platforms, APIs, etc. TTCN-3 is not restricted to conformance testing and can be used for many other kinds of testing including interoperability, robustness, regression, system and integration testing. The specification of test suites for physical layer protocols is outside the scope of the present document.

TTCN-3 packages are intended to define additional TTCN-3 concepts, which are not mandatory as concepts in the TTCN-3 core language or in its interfaces TRI and TCI, but which are optional as part of a package which is suited for dedicated applications and/or usages of TTCN-3.

This package defines a more efficient handling of software values by a version of TRI, that does not use binary encoded messages for the communication with the SUT, but uses the values as they are; meaning e.g. that software objects or serialized data can be passed directly between the SUT and the TE.

While the design of TTCN-3 package has taken into account the consistency of a combined usage of the core language with a number of packages, the concrete usages of and guidelines for this package in combination with other packages is outside the scope of the present document.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI ES 201 873-1: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 1: TTCN-3 Core Language".
- [2] ETSI ES 201 873-4: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 4: TTCN-3 Operational Semantics".
- [3] ETSI ES 201 873-5: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 5: TTCN-3 Runtime Interface (TRI)".
- [4] ETSI ES 201 873-6: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 6: TTCN-3 Control Interface (TCI)".
- [5] Recommendation ITU-T X.290: "OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - General concepts".

NOTE: The corresponding ISO/IEC standard is ISO/IEC 9646-1: "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 1: General concepts".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Void.
- [i.2] ETSI ES 201 873-3: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 3: TTCN-3 Graphical presentation Format (GFT)".
- [i.3] ETSI ES 201 873-7: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 7: Using ASN.1 with TTCN-3".
- [i.4] ETSI ES 201 873-8: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 8: The IDL to TTCN-3 Mapping".
- [i.5] ETSI ES 201 873-9: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 9: Using XML schema with TTCN-3".
- [i.6] ETSI ES 201 873-10: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 10: TTCN-3 Documentation Comment Specification".
- [i.7] ETSI ES 202 781: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; TTCN-3 Language Extensions: Configuration and Deployment Support".
- [i.8] ETSI ES 202 784: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; TTCN-3 Language Extensions: Advanced Parameterization".
- [i.9] ETSI ES 202 785: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; TTCN-3 Language Extensions: Behaviour Types".
- [i.10] ETSI ES 202 782: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; TTCN-3 Language Extensions: TTCN-3 Performance and Real Time Testing".
- [i.11] ETSI ES 202 786: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; TTCN-3 Language Extensions: Support of interfaces with continuous signals".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ES 201 873-1 [1], ES 201 873-4 [2], ES 201 873-5 [3], ES 201 873-6 [4] and Recommendation ITU-T X.290 [5] apply.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in ES 201 873-1 [1], ES 201 873-4 [2], ES 201 873-5 [3], ES 201 873-6 [4], Recommendation ITU-T X.290 [5] and the following apply:

XTRI	Extended TRI
------	--------------

4 Package conformance and compatibility

The package has no package tag as the choice to use TRI and/or XTRI affects the test adaptor only, but not the test specifications in TTCN-3.

For an implementation claiming to conform to this package version, all features specified in the present document shall be implemented consistently with the requirements given in the present document, ES 201 873-1 [1] and ES 201 873-4 [2].

The package presented in the present document is compatible to:

- ES 201 873-1 [1] (V4.5.1)
- ES 201 873-4 [2] (V4.4.1)
- ES 201 873-6 [4] (V4.5.1)
- ES 201 873-7 [i.3] (V4.5.1)
- ES 201 873-8 [i.4] (V4.5.1)
- ES 201 873-9 [i.5] (V4.5.1)
- ES 201 873-10 [i.6] (V4.5.1)

If later versions of those parts are available and should be used instead, the compatibility of the package defined in the present document has to be checked individually.

The package defined in the present document is also compatible to:

- ES 202 784 [i.8] (V1.3.1)
- ES 202 781 [i.7] (V1.2.1)
- ES 202 782 [i.10] (V1.2.1)
- ES 202 785 [i.9] (V1.3.1)
- ES 202 786 [i.11] (V1.2.1)

and can be used together with those packages.

If later versions of those packages are available and should be used instead, the compatibility to the package defined in the present document has to be checked individually.

5 Package concepts for the core language

Not applicable.

6 Package semantics

Not applicable.

7 TRI extensions for the package

Historically, TTCN has been used to test communication protocols which typically use encoded messages. This has been reflected in the TRI SA and TCI CD design of TTCN-3 by encoding and decoding messages to and from bitstrings. However, TTCN-3 also supports signature-based communication for which the transformation of objects into bitstrings and vice versa is cumbersome. Furthermore, some protocols use also structured messages for which the bitstring encoding is not helpful.

Therefore, an alternative API is being defined in this extension package of TTCN-3 along which TTCN-3 values can be directly passed to/from the SUT. It is defined by redefining the operations in TRI SA and PA as follows.

7.1 Changes to clause 5.2 of ES 201 873-5, Error handling

The SA or PA can in addition provide notifications about unrecoverable error situations by use of the operations xtriSAErrorReq and xtriPAErrorReq, respectively.

5.2.1 triSAErrorReq → xtriSAErrorReq

Signature	void <u>xtriSAErrorReq</u> (in string message, in any cause)
In Parameters	message A string value, i.e. the error phrase describing the problem. cause (Optional) cause of the problem.
Return Value	void
Constraint	Shall be called whenever an error situation has occurred in the SA with the exception of errors occurring when processing SA calls initiated by the TE. These errors are reported in the operation return. <u>The optional cause parameter can be used to provide information in addition to the error phrase in message.</u>
Effect	The TE will be notified about an unrecoverable error situation within the SA and may forward the error indication to the test management.

5.2.2 triPAErrorReq → xtriPAErrorReq

Signature	void <u>xtriPAErrorReq</u> (in string message, in any cause)
In Parameters	message A string value, i.e. the error phrase describing the problem. cause (Optional) cause of the problem.
Return Value	Void
Constraint	Shall be called whenever an error situation has occurred in the PA with the exception of errors occurring when processing PA calls initiated by the TE. These errors are reported in the operation return. <u>The optional cause parameter can be used to provide information in addition to the error phrase in message.</u>
Effect	The TE will be notified about an unrecoverable error situation within the PA and may forward the error indication to the test management.

7.2 Changes to clause 5.5.2 Connection handling operations

5.5.2.3 triMapParam → xtriMapParam

Signature	TriStatusType <u>xtriMap</u> (in TriPortIdType compPortId, in TriPortIdType tsiPortId, in TciParameterListType paramList)
In Parameters	compPortId identifier of the test component port to be mapped tsiPortId identifier of the test system interface port to be mapped paramList parameters of the parameterized map
Out Parameters	n.a.
Return Value	The return status of the <u>triMap</u> operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.
Constraints	This operation is called by the TE when it executes a TTCN-3 map operation.
Effect	The SA can establish a dynamic connection to the SUT for the referenced TSI port. The <u>triMap</u> operation returns TRI_Error in case a connection could not be established successfully, TRI_OK otherwise. The operation should return TRI_OK in case no dynamic connection needs to be established by the test system.

5.5.2.5

triUnmapParam → xtriUnmapParam

Signature	TriStatusType <u>xtriUnmap</u> (in TriPortIdType compPortId, in TriPortIdType tsiPortId, in TciParameterListType paramList)
In Parameters	compPortId identifier of the test component port to be unmapped tsiPortId identifier of the test system interface port to be unmapped paramList parameters of the parameterized map
Out Parameters	n.a.
Return Value	The return status of the triUnmap operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.
Constraints	This operation is called by the TE when it executes any TTCN-3 unmap operation.
Effect	The SA shall close a dynamic connection to the SUT for the referenced TSI port. The triUnmap operation returns TRI_Error in case a connection could not be closed successfully or no such connection has been established previously, TRI_OK otherwise. The operation should return TRI_OK in case no dynamic connections have to be closed by the test system.

7.3 Changes to clause 5.5.3 Message based communication operations

5.5.3.1

triSend → xtriSend

Signature	TriStatusType <u>xtriSend</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in Value SUTaddress, in Value sendMessage)
In Parameters	componentId identifier of the sending test component tsiPortId identifier of the test system interface port via which the message is sent to the SUT Adaptor SUTaddress (optional) destination <u>address value</u> within the SUT sendMessage the <u>value</u> to be sent
Out Parameters	n.a.
Return Value	The return status of the triSend operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.
Constraints	This operation is called by the TE when it executes a TTCN-3 unicast send operation on a component port, which has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 send operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case. <u>The encoding of sendMessage has to be done in the TE prior to this TRI operation call.</u>
Effect	The SA can send the message to the SUT. The triSend operation returns TRI_OK in case it has been completed successfully. Otherwise TRI_Error shall be returned. Notice that the return value TRI_OK does not imply that the SUT has received sendMessage.

5.5.3.2

triSendBC → xtriSendBC

Signature	TriStatusType <u>xtriSendBC</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in Value sendMessage)
In Parameters	componentId identifier of the sending test component tsiPortId identifier of the test system interface port via which the message is sent to the SUT Adaptor sendMessage the <u>value</u> to be sent
Out Parameters	n.a.
Return Value	The return status of the triSendBC operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.
Constraints	This operation is called by the TE when it executes a TTCN-3 broadcast send operation on a component port, which has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 send operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case. The encoding of sendMessage has to be done in the TE prior to this TRI operation call.
Effect	The SA can broadcast the message to the SUT. The triSendBC operation returns TRI_OK in case it has been completed successfully. Otherwise TRI_Error shall be returned. Notice that the return value TRI_OK does not imply that the SUT has received sendMessage.

5.5.3.3

triSendMC → xtriSendMC

Signature	TriStatusType <u>xtriSendMC</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in TciValueList SUTaddresses, in Value sendMessage)
In Parameters	componentId identifier of the sending test component tsiPortId identifier of the test system interface port via which the message is sent to the SUT Adaptor SUTaddresses <u>destination address values</u> within the SUT sendMessage the <u>values</u> to be sent
Out Parameters	n.a.
Return Value	The return status of the triSendMC operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.
Constraints	This operation is called by the TE when it executes a TTCN-3 multicast send operation on a component port, which has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 send operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case. The encoding of sendMessage has to be done in the TE prior to this TRI operation call.
Effect	The SA can multicast the message to the SUT. The triSendMC operation returns TRI_OK in case it has been completed successfully. Otherwise TRI_Error shall be returned. Notice that the return value TRI_OK does not imply that the SUT has received sendMessage.

5.5.3.4

triEnqueueMsg → xtriEnqueueMsg

Signature	<code>void xtriEnqueueMsg(in TriPortIdType tsiPortId, in any SUTaddress, in TriComponentIdType componentId, in any receivedMessage)</code>	
In Parameters	tsiPortId SUTaddress componentId receivedMessage	identifier of the test system interface port via which the message is enqueued by the SUT Adaptor (optional) <u>source address value</u> within the SUT identifier of the receiving test component the received <u>value</u>
Out Parameters	n.a.	
Return Value	<code>void</code>	
Constraints	<p>This operation is called by the SA after it has received a message from the SUT. It can only be used when tsiPortId has been either previously mapped to a port of componentId or has been referenced in the previous triExecuteTestCase statement.</p> <p>In the invocation of a triEnqueueMsg operation receivedMessage shall contain an encoded value.</p>	
Effect	<p>This operation shall pass the message to the TE indicating the component componentId to which the TSI port tsiPortId is mapped.</p> <p>The decoding of receivedMessage has to be done in the TE.</p>	

7.4 Addition to clause 5.5.3 Message based communication operations

In order to interpret unknown values along a type hypothesis, an additional xtriConvert operation is defined. It can be used in all cases where the type of the incoming value is not known. Please note that typically the value type is known in procedure-based communication and sometimes in message-based communication.

5.5.3.5

xtriConvert

Signature	<code>Value xtriConvert(in any value, in Type typeHypothesis)</code>	
In Parameters	<code>value</code>	the <u>value to be converted</u>
	<code>typeHypothesis</code>	the <u>type hypothesis</u>
Out Parameters	n.a.	
Return Value	Returns the converted value, if the value is of a compatible type as the <u>typeHypothesis</u> , else the distinct value <u>null</u> .	
Constraints	This operation shall be called whenever the TE has to convert a value. The TE might convert immediately after reception of the value, or might for performance considerations postpone the conversion until the actual access to the value.	
Effect	<p>This operation converts a <u>value</u> and returns a <u>value according to the type hypothesis if it matches</u>. The <u>typeHypothesis</u> determines whether the value can be converted. If not, the distinct <u>null</u> value shall be returned.</p>	

7.5 Changes to clause 5.5.4 Procedure based communication operations

5.5.4.1 triCall → xtriCall

Signature	TriStatusType <u>xtriCall</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in Value SUTaddress, in TriSignatureIdType signatureId, in TciParameterListType parameterList)	
In Parameters	componentId tsiPortId SUTaddress signatureId parameterList	identifier of the test component issuing the procedure call identifier of the test system interface port via which the procedure call is sent to the SUT Adaptor (optional) destination address within the SUT identifier of the signature of the procedure call a list of <u>encoded</u> parameters which are part of the indicated signature. The parameters in parameterList are ordered as they appear in the TTCN-3 signature declaration
Out Parameters	n.a.	
Return Value	The return status of the <u>triCall</u> operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.	
Constraints	<p>This operation is called by the TE when it executes a TTCN-3 unicast call operation on a component port, which has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 call operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case.</p> <p>All <i>in</i> and <i>inout</i> procedure parameters contain encoded values.</p> <p>The procedure parameters are the parameters specified in the TTCN-3 signature template. Their encoding has to be done in the TE prior to this TRI operation call.</p>	
Effect	<p>On invocation of this operation the SA can initiate the procedure call corresponding to the signature identifier <code>signatureId</code> and the TSI port <code>tsiPortId</code>.</p> <p>The <code>triCall</code> operation shall return without waiting for the return of the issued procedure call (see note). This TRI operation returns TRI_OK on successful initiation of the procedure call, TRI_Error otherwise. No error shall be indicated by the SA in case the value of any <i>out</i> parameter is non-null. Notice that the return value of this TRI operation does not make any statement about the success or failure of the procedure call.</p> <p>Note that an optional timeout value, which can be specified in the TTCN-3 ATS for a call operation, is <i>not</i> included in the <code>triCall</code> operation signature. The TE is responsible to address this issue by starting a timer for the TTCN-3 call operation in the PA with a separate TRI operation call, i.e. <code>triStartTimer</code>.</p>	
NOTE:	This might be achieved for example by spawning a new thread or process. This handling of this procedure call is, however, dependent on implementation of the TE.	

5.5.4.2

triCallBC → xtriCallBC

Signature	TriStatusType <u>xtriCallBC</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in TriSignatureIdType signatureId, in TciParameterListType parameterList)
In Parameters	<p>componentId tsiPortId signatureId parameterList</p> <p>identifier of the test component issuing the procedure call identifier of the test system interface port via which the procedure call is sent to the SUT Adaptor identifier of the signature of the procedure call a list of encoded parameters which are part of the indicated signature. The parameters in parameterList are ordered as they appear in the TTCN-3 signature declaration.</p>
Out Parameters	n.a.
Return Value	The return status of the <code>triCallBC</code> operation. The return status indicates the local success (<i>TRI_OK</i>) or failure (<i>TRI_Error</i>) of the operation.
Constraints	<p>This operation is called by the TE when it executes a TTCN-3 broadcast call operation on a component port, which has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 call operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case.</p> <p>All <i>in</i> and <i>inout</i> procedure parameters contain encoded values.</p> <p>The procedure parameters are the parameters specified in the TTCN-3 signature template. Their encoding has to be done in the TE prior to this TRI operation call.</p>
Effect	<p>On invocation of this operation the SA can initiate and broadcast the procedure call corresponding to the signature identifier <code>signatureId</code> and the TSI port <code>tsiPortId</code>.</p> <p>The <code>triCallBC</code> operation shall return without waiting for the return of the issued procedure call (see note). This TRI operation returns <i>TRI_OK</i> on successful initiation of the procedure call, <i>TRI_Error</i> otherwise. No error shall be indicated by the SA in case the value of any <i>out</i> parameter is non-null.</p> <p>Notice that the return value of this TRI operation does not make any statement about the success or failure of the procedure call.</p> <p>Note that an optional timeout value, which can be specified in the TTCN-3 ATS for a call operation, is <i>not</i> included in the <code>triCallBC</code> operation signature. The TE is responsible to address this issue by starting a timer for the TTCN-3 call operation in the PA with a separate TRI operation call, i.e. <code>triStartTimer</code>.</p>
NOTE: This might be achieved for example by spawning a new thread or process. This handling of this procedure call is, however, dependent on implementation of the TE.	

5.5.4.3

triCallMC → xtriCallMC

Signature	TriStatusType <u>xtriCallMC</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in TciValueList SUTaddresses, in TriSignatureIdType signatureId, in TciParameterListType parameterList)	
In Parameters	componentId tsiPortId SUTaddresses signatureId parameterList	identifier of the test component issuing the procedure call identifier of the test system interface port via which the procedure call is sent to the SUT Adaptor destination addresses within the SUT identifier of the signature of the procedure call a list of <u>encoded</u> parameters which are part of the indicated signature. The parameters in parameterList are ordered as they appear in the TTCN-3 signature declaration.
Out Parameters	n.a.	
Return Value	The return status of the <u>triCallMC</u> operation. The return status indicates the local success (<u>TRI_OK</u>) or failure (<u>TRI_Error</u>) of the operation.	
Constraints	<p>This operation is called by the TE when it executes a TTCN-3 multicast call operation on a component port, which has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 call operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case.</p> <p>All <u>in</u> and <u>inout</u> procedure parameters contain encoded values.</p> <p>The procedure parameters are the parameters specified in the TTCN-3 signature template. Their encoding has to be done in the TE prior to this TRI operation call.</p>	
Effect	<p>On invocation of this operation the SA can initiate and multicast the procedure call corresponding to the signature identifier <u>signatureId</u> and the TSI port <u>tsiPortId</u>.</p> <p>The <u>triCallMC</u> operation shall return without waiting for the return of the issued procedure call (see note). This TRI operation returns <u>TRI_OK</u> on successful initiation of the procedure call, <u>TRI_Error</u> otherwise. No error shall be indicated by the SA in case the value of any <u>out</u> parameter is non-null.</p> <p>Notice that the return value of this TRI operation does not make any statement about the success or failure of the procedure call.</p> <p>Note that an optional timeout value, which can be specified in the TTCN-3 ATS for a call operation, is <u>not</u> included in the <u>triCallMC</u> operation signature. The TE is responsible to address this issue by starting a timer for the TTCN-3 call operation in the PA with a separate TRI operation call, i.e. <u>triStartTimer</u>.</p>	
NOTE: This might be achieved for example by spawning a new thread or process. This handling of this procedure call is, however, dependent on implementation of the TE.		

5.5.4.4

triReply → xtriReply

Signature	TriStatusType <u>xtriReply</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in Value SUTaddress, in TriSignatureIdType signatureId, in TciParameterListType parameterList, in Value returnValue)	
In Parameters	componentId tsiPortId SUTaddress signatureId parameterList returnValue	identifier of the replying test component identifier of the test system interface port via which the reply is sent to the SUT Adaptor (optional) destination address within the SUT identifier of the signature of the procedure call a list of encoded parameters which are part of the indicated signature. The parameters in parameterList are ordered as they appear in the TTCN-3 signature declaration (optional) encoded return value of the procedure call
Out Parameters	n.a.	
Return Value	The return status of the triReply operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.	
Constraints	<p>This operation is called by the TE when it executes a TTCN-3 unicast reply operation on a component port that has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 reply operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case.</p> <p>All out and inout procedure parameters and the return value contain encoded values.</p> <p>The parameterList contains procedure call parameters. These parameters are the parameters specified in the TTCN-3 signature template. Their encoding has to be done in the TE prior to this TRI operation call.</p> <p>If no return type has been defined for the procedure signature in the TTCN-3 ATS, the distinct value null shall be passed for the return value.</p>	
Effect	<p>On invocation of this operation the SA can issue the reply to a procedure call corresponding to the signature identifier signatureId and the TSI port tsiPortId.</p> <p>The triReply operation will return TRI_OK on successful execution of this operation, TRI_Error otherwise. The SA shall indicate no error in case the value of any <i>in</i> parameter or an undefined return value is different from null.</p>	

5.5.4.5

triReplyBC → xtriReplyBC

Signature	TriStatusType <u>xtriReplyBC</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in TriSignatureIdType signatureId, in TciParameterListType parameterList, in Value returnValue)	
In Parameters	componentId tsiPortId signatureId parameterList returnValue	identifier of the replying test component identifier of the test system interface port via which the reply is sent to the SUT Adaptor identifier of the signature of the procedure call a list of en coded parameters which are part of the indicated signature. The parameters in parameterList are ordered as they appear in the TTCN-3 signature declaration (optional) en coded return value of the procedure call
Out Parameters	n.a.	
Return Value	The return status of the triReplyBC operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.	
Constraints	<p>This operation is called by the TE when it executes a TTCN-3 broadcast reply operation on a component port that has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 reply operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case.</p> <p>All out and inout procedure parameters and the return value contain encoded values.</p> <p>The parameterList contains procedure call parameters. These parameters are the parameters specified in the TTCN-3 signature template. Their encoding has to be done in the TE prior to this TRI operation call.</p> <p>If no return type has been defined for the procedure signature in the TTCN-3 ATS, the distinct value null shall be passed for the return value.</p>	
Effect	<p>On invocation of this operation the SA can broadcast the reply to procedure calls corresponding to the signature identifier signatureId and the TSI port tsiPortId.</p> <p>The triReplyBC operation will return TRI_OK on successful execution of this operation, TRI_Error otherwise. The SA shall indicate no error in case the value of any <i>in</i> parameter or an undefined return value is different from null.</p>	

5.5.4.6

triReplyMC → xtriReplyMC

Signature	TriStatusType <u>xtriReplyMC</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in TciValueList SUTaddresses, in TriSignatureIdType signatureId, in TciParameterListType parameterList, in Value returnValue)	
In Parameters	componentId tsiPortId SUTaddresses signatureId parameterList returnValue	identifier of the replying test component identifier of the test system interface port via which the reply is sent to the SUT Adaptor destination addresses within the SUT identifier of the signature of the procedure call a list of encoded parameters which are part of the indicated signature. The parameters in parameterList are ordered as they appear in the TTCN-3 signature declaration (optional) encoded return value of the procedure call
Out Parameters	n.a.	
Return Value	The return status of the triReplyMC operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.	
Constraints	<p>This operation is called by the TE when it executes a TTCN-3 multicast reply operation on a component port that has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 reply operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case.</p> <p>All out and inout procedure parameters and the return value contain encoded values.</p> <p>The parameterList contains procedure call parameters. These parameters are the parameters specified in the TTCN-3 signature template. Their encoding has to be done in the TE prior to this TRI operation call.</p> <p>If no return type has been defined for the procedure signature in the TTCN-3 ATS, the distinct value null shall be passed for the return value.</p>	
Effect	<p>On invocation of this operation the SA can multicast the reply to procedure calls corresponding to the signature identifier signatureId and the TSI port tsiPortId.</p> <p>The triReplyMC operation will return TRI_OK on successful execution of this operation, TRI_Error otherwise. The SA shall indicate no error in case the value of any <i>in</i> parameter or an undefined return value is different from null.</p>	

5.5.4.7

triRaise → xtriRaise

Signature	TriStatusType <u>xtriRaise</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in Value SUTaddress, in TriSignatureIdType signatureId, in Value exc)	
In Parameters	componentId tsiPortId SUTaddress signatureId exc	identifier of the test component raising the exception identifier of the test system interface port via which the exception is sent to the SUT Adaptor (optional) destination address within the SUT identifier of the signature of the procedure call which the exception is associated with the encoded exception
Out Parameters	n.a.	
Return Value	The return status of the triRaise operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.	
Constraints	<p>This operation is called by the TE when it executes a TTCN-3 unicast raise operation on a component port that has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 raise operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case.</p> <p>The encoding of the exception has to be done in the TE prior to this TRI operation call.</p>	
Effect	<p>On invocation of this operation the SA can raise an exception to a procedure call corresponding to the signature identifier signatureId and the TSI port tsiPortId.</p> <p>The triRaise operation returns TRI_OK on successful execution of the operation, TRI_Error otherwise.</p>	

5.5.4.8

triRaiseBC → xtriRaiseBC

Signature	TriStatusType <u>xtriRaiseBC</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in TriSignatureIdType signatureId, in Value exc)
In Parameters	componentId identifier of the test component raising the exception tsiPortId identifier of the test system interface port via which the exception is sent to the SUT Adaptor signatureId identifier of the signature of the procedure call which the exception is associated with exc the encoded exception
Out Parameters	n.a.
Return Value	The return status of the <u>triRaiseBC</u> operation. The return status indicates the local success (<u>TRI_OK</u>) or failure (<u>TRI_Error</u>) of the operation.
Constraints	This operation is called by the TE when it executes a TTCN-3 broadcast raise operation on a component port that has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 raise operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case. The encoding of the exception has to be done in the TE prior to this TRI operation call.
Effect	On invocation of this operation the SA can raise and broadcast an exception to procedure calls corresponding to the signature identifier <u>signatureId</u> and the TSI port <u>tsiPortId</u> . The <u>triRaiseBC</u> operation returns <u>TRI_OK</u> on successful execution of the operation, <u>TRI_Error</u> otherwise.

5.5.4.9

triRaiseMC → xtriRaiseMC

Signature	TriStatusType <u>xtriRaiseMC</u> (in TriComponentIdType componentId, in TriPortIdType tsiPortId, in TciValueList SUTaddresses, in TriSignatureIdType signatureId, in Value exc)
In Parameters	componentId identifier of the test component raising the exception tsiPortId identifier of the test system interface port via which the exception is sent to the SUT Adaptor SUTaddresses destination addresses within the SUT signatureId identifier of the signature of the procedure call which the exception is associated with exc the encoded exception
Out Parameters	n.a.
Return Value	The return status of the <u>triRaiseMC</u> operation. The return status indicates the local success (<u>TRI_OK</u>) or failure (<u>TRI_Error</u>) of the operation.
Constraints	This operation is called by the TE when it executes a TTCN-3 multicast raise operation on a component port that has been mapped to a TSI port. This operation is called by the TE for all TTCN-3 raise operations if no system component has been specified for a test case, i.e. only a MTC test component is created for a test case. The encoding of the exception has to be done in the TE prior to this TRI operation call.
Effect	On invocation of this operation the SA can raise and multicast an exception to a procedure calls corresponding to the signature identifier <u>signatureId</u> and the TSI port <u>tsiPortId</u> . The <u>triRaiseMC</u> operation returns <u>TRI_OK</u> on successful execution of the operation, <u>TRI_Error</u> otherwise.

5.5.4.10 triEnqueueCall → xtriEnqueueCall

Signature	<code>void xtriEnqueueCall(in TriPortIdType tsiPortId, in any SUTaddress, in TriComponentIdType componentId, in TriSignatureIdType signatureId, in TciParameterListType parameterList)</code>	
In Parameters	tsiPortId SUTaddress componentId signatureId parameterList	identifier of the test system interface port via which the procedure call is enqueued by the SUT Adaptor (optional) source address within the SUT identifier of the receiving test component identifier of the signature of the procedure call a list of <u>encoded</u> parameters which are part of the indicated signature. The parameters in parameterList are ordered as they appear in the TTCN-3 signature declaration. Description of data passed as parameters to the operation from the calling entity to the called entity
Out Parameters	n.a.	
Return Value	void	
Constraints	<p>This operation can be called by the SA after it has received a procedure call from the SUT. It can only be used when tsiPortId has been either previously mapped to a port of componentId or referenced in the previous triExecuteTestCase statement.</p> <p>In the invocation of a triEnqueueCall operation all in and inout procedure parameters contain encoded values.</p>	
Effect	<p>The TE can enqueue this procedure call with the signature identifier signatureId at the port of the component componentId to which the TSI port tsiPortId is mapped. The decoding of procedure parameters has to be done in the TE.</p> <p>The TE shall indicate no error in case the value of any <i>out</i> parameter is different from null.</p>	

5.5.4.11 triEnqueueReply → xtriEnqueueReply

Signature	<code>void xtriEnqueueReply(in TriPortIdType tsiPortId, in any SUTaddress, in TriComponentIdType componentId, in TriSignatureIdType signatureId, in TciParameterListType parameterList, in Value returnValue)</code>	
In Parameters	tsiPortId SUTaddress componentId signatureId parameterList returnValue	identifier of the test system interface port via which the reply is enqueued by the SUT Adaptor (optional) source address within the SUT identifier of the receiving test component identifier of the signature of the procedure call a list of <u>encoded</u> parameters which are part of the indicated signature. The parameters in parameterList are ordered as they appear in the TTCN-3 signature declaration (optional) <u>encoded</u> return value of the procedure call
Out Parameters	n.a.	
Return Value	void	
Constraints	<p>This operation can be called by the SA after it has received a reply from the SUT. It can only be used when tsiPortId has been either previously mapped to a port of componentId or referenced in the previous triExecuteTestCase statement.</p> <p>In the invocation of a triEnqueueReply operation all out and inout procedure parameters and the return value contain encoded values.</p> <p>If no return type has been defined for the procedure signature in the TTCN-3 ATS, the distinct value null shall be used for the return value.</p>	
Effect	<p>The TE can enqueue this reply to the procedure call with the signature identifier signatureId at the port of the component componentId to which the TSI port tsiPortId is mapped. The decoding of the procedure parameters has to be done within the TE.</p> <p>The TE shall indicate no error in case the value of any <i>in</i> parameter or an undefined return value is different from null.</p>	

5.5.4.12

triEnqueueException → xtriEnqueueException

Signature	void <u>xtriEnqueueException</u> (in TriPortIdType tsiPortId, in any SUTaddress, in TriComponentIdType componentId, in TriSignatureIdType signatureId, in any exc)		
In Parameters	tsiPortId SUTaddress componentId signatureId exc	identifier for the test system interface port via which the exception is enqueued by the SUT Adaptor (optional) source address within the SUT identifier of the receiving test component identifier of the signature of the procedure call which the exception is associated with the encoded exception	
Out Parameters	n.a.		
Return Value	void		
Constraints	This operation can be called by the SA after it has received a reply from the SUT. It can only be used when <code>tsiPortId</code> has been either previously mapped to a port of <code>componentId</code> or referenced in the previous <code>triExecuteTestCase</code> statement. In the invocation of a triEnqueueException operation exception shall contain an encoded value.		
Effect	The TE can enqueue this exception for the procedure call with the signature identifier <code>signatureId</code> at the port of the component <code>componentId</code> to which the TSI port <code>tsiPortId</code> is mapped. The decoding of the exception has to be done within the TE.		

7.6 Changes to clause 5.6.3 Miscellaneous operations

5.6.3.1

triExternalFunction → xtriExternalFunction

Signature	TriStatusType <u>xtriExternalFunction</u> (in TriFunctionIdType functionId, inout TciParameterListType parameterList, out Value returnValue)		
In Parameters	functionId	identifier of the external function	
Out Parameters	returnValue	(optional) encoded return value	
InOutParameters	parameterList	a list of encoded parameters for the indicated function. The parameters in <code>parameterList</code> are ordered as they appear in the TTCN-3 function declaration.	
Return Value	The return status of the <code>triExternalFunction</code> operation. The return status indicates the local success (TRI_OK) or failure (TRI_Error) of the operation.		
Constraints	This operation is called by the TE when it executes a function which is defined to be TTCN-3 external (i.e. all non-external functions are implemented within the TE). In the invocation of a triExternalFunction operation by the TE all in and inout function parameters contain encoded values. No error shall be indicated by the PA in case the value of any <code>out</code> parameter is non-null.		
Effect	For each external function specified in the TTCN-3 ATS the PA shall implement the behaviour. On invocation of this operation the PA shall invoke the function indicated by the identifier <code>functionId</code> . It shall access the specified <code>in</code> and <code>inout</code> function parameters in <code>parameterList</code> , evaluate the external function using the values of these parameters, and compute values for <code>inout</code> and <code>out</code> parameters in <code>parameterList</code> . The operation shall then return encoded values for all <code>inout</code> and <code>out</code> function parameters and the encoded return value of the external function. If no return type has been defined for this external function in the TTCN-3 ATS, the distinct value <code>null</code> shall be used for the latter. The <code>triExternalFunction</code> operation returns TRI_OK if the PA completes the evaluation of the external function successfully, TRI_Error otherwise. Note that whereas all other TRI operations are considered to be non-blocking, the <code>triExternalFunction</code> operation is considered to be <i>blocking</i> . That means that the operation shall not return before the indicated external function has been fully evaluated. External functions have to be implemented carefully as they could cause deadlock of test component execution or even the entire test system implementation.		

5.6.3.3

triRnd → xtriRnd

Signature	FloatValue xtriRnd(in TriComponentIdType componentId, in FloatValue seed)
In Parameters	componentId identifier of the component for which to generate the random number
	seed <u>the seed</u> to be used for generation of the random number or null
Out Parameters	n.a.
Return Value	The generated float random number
Constraints	This operation is called by the PA to generate a random number in the context of an external function.
Effect	A random number is generated in the scope of the component identified by the given component Id using the given seed (if any) according to the specification of the predefined rnd function defined in ES 201 873-1 [2].

7.7 Changes to clause 6 Java language mapping

Addition of the following subclause in clause 6.3 Type mapping.

6.3.3 Any type mapping

The IDL any type is represented by Java `java.lang.Object`.

6.5.2.1 Changes to triCommunicationSA

The extension to the `triCommunicationSA` interface is mapped to the following interface:

```
// TriCommunication
// TE -> SA
package org.etsi.ttcn.xtri;
public interface xTriCommunicationSA {
    public TriStatus xtriMapParam(TriPortId compPortId, TriPortId tsiPortId,
                                  TciParameterList paramList);
    // Ref: TRI-Definition 5.5.2.3
    public TriStatus xtriUnmapParam(TriPortId compPortId, TriPortId tsiPortId,
                                    TciParameterList paramList);
    // Ref: TRI-Definition 5.5.2.4

    // Message based communication operations
    // Ref: TRI-Definition 5.5.3.1
    public TriStatus xtriSend(TriComponentId componentId, TriPortId tsiPortId,
                             Value sutAddress, Value sendMessage);
    // Ref: TRI-Definition 5.5.3.2
    public TriStatus xtriSendBC(TriComponentId componentId, TriPortId tsiPortId,
                               Value sendMessage);
    // Ref: TRI-Definition 5.5.3.3
    public TriStatus xtriSendMC(TriComponentId componentId, TriPortId tsiPortId,
                               TciValueList sutAddresses, Value sendMessage);

    // Procedure based communication operations
    // Ref: TRI-Definition 5.5.4.1
    public TriStatus xtriCall(TriComponentId componentId,
                             TriPortId tsiPortId, Value sutAddress,
                             TriSignatureId signatureId, TciParameterList parameterList);
    // Ref: TRI-Definition 5.5.4.2
    public TriStatus xtriCallBC(TriComponentId componentId,
                               TriPortId tsiPortId,
                               TriSignatureId signatureId, TciParameterList parameterList);
    // Ref: TRI-Definition 5.5.4.3
    public TriStatus xtriCallMC(TriComponentId componentId,
                               TriPortId tsiPortId, TciValueList sutAddresses,
                               TriSignatureId signatureId, TciParameterList parameterList);

    // Ref: TRI-Definition 5.5.4.4
    public TriStatus xtriReply(TriComponentId componentId,
                             TriPortId tsiPortId, Value sutAddress,
                             TriSignatureId signatureId, TciParameterList parameterList,
                             Value returnValue);
    // Ref: TRI-Definition 5.5.4.5
    public TriStatus xtriReplyBC(TriComponentId componentId,
                               TriPortId tsiPortId,
                               TriSignatureId signatureId, TciParameterList parameterList,
```

```

    Value returnValue);
    // Ref: TRI-Definition 5.5.4.6
    public TriStatus xtriReplyMC(TriComponentId componentId,
                                TriPortId tsiPortId, TciValueList sutAddresses,
                                TriSignatureId signatureId, TciParameterList parameterList,
                                Value returnValue);

    // Ref: TRI-Definition 5.5.4.7
    public TriStatus xtriRaise(TriComponentId componentId, TriPortId tsiPortId,
                             Value sutAddress,
                             TriSignatureId signatureId,
                             Value exc);
    // Ref: TRI-Definition 5.5.4.8
    public TriStatus xtriRaiseBC(TriComponentId componentId,
                               TriPortId tsiPortId,
                               TriSignatureId signatureId,
                               Value exc);
    // Ref: TRI-Definition 5.5.4.9
    public TriStatus xtriRaiseMC(TriComponentId componentId, TriPortId tsiPortId,
                               TciValueList sutAddresses,
                               TriSignatureId signatureId,
                               Value exc);

    // Miscellaneous operations
    // Ref: TRI-Definition 5.5.3.5
    public Value xtriConvert(Object value, Type typeHypothesis);
}

}

```

6.5.2.2 Changes to triCommunicationTE

The extension to the `triCommunicationTE` interface is mapped to the following interface:

```

// TriCommunication
// SA -> TE
package org.etsi.ttcn.xtri;
public interface xTriCommunicationTE {
    // Message based communication operations
    // Ref: TRI-Definition 5.5.3.4
    public void xtriEnqueueMsg(TriPortId tsiPortId,
                               Object sutAddress, TriComponentId componentId,
                               Object receivedMessage);

    // Procedure based communication operations
    // Ref: TRI-Definition 5.5.4.10
    public void xtriEnqueueCall(TriPortId tsiPortId,
                               Object sutAddress, TriComponentId componentId,
                               TriSignatureId signatureId, TciParameterList parameterList );

    // Ref: TRI-Definition 5.5.4.11
    public void xtriEnqueueReply(TriPortId tsiPortId, Object sutAddress,
                               TriComponentId componentId, TriSignatureId signatureId,
                               TciParameterList parameterList, Value returnValue);

    // Ref: TRI-Definition 5.5.4.12
    public void xtriEnqueueException(TriPortId tsiPortId,
                                   Object sutAddress, TriComponentId componentId,
                                   TriSignatureId signatureId, Object exc);

    // Error handling
    // Ref: TRI-Definition 5.2.1
    public void xtriSAErrorReq (String message, Object cause);
}

```

6.5.3.1 Changes to TriPlatformPA

The extension to the `triPlatformPA` interface is mapped to the following interface:

```

// TriPlatform
// TE -> PA
package org.etsi.ttcn.xtri;
public interface xTriPlatformPA {
    // Ref: TRI-Definition 5.6.3.1
    public TriStatus xtriExternalFunction(TriFunctionId functionId,
                                         TciParameterList parameterList, Value returnValue);
}

```

6.5.3.2 Changes to TriPlatformTE

The extension to the triPlatformTE interface is mapped to the following interface:

```
// TriPlatform
// PA -> TE
package org.etsi.ttcn.xtri;
public interface xTriPlatformTE {
    // Error handling
    // Ref: TRI-Definition 5.2.2
    public void xtriPAErrorReq (String message, Object cause);
    // Ref: TRI-Definition 5.6.3.3
    public FloatValue xtriRnd(TriComponentId componentId, FloatValue seed);}

```

7.8 Changes to clause 7 C language mapping

7.2.1 Changes to Abstract type mapping

TRI ADT	ANSI C Representation	Notes and comments
any	<pre>typedef enum { e_char = 1, // character e_unsigned_char = 2, // unsigned char e_signed_char = 3, // signed char e_short = 4, // short signed integer e_short_int = 5, // short signed integer e_signed_short = 6, // short signed integer e_signed_short_int = 7, // short signed integer e_unsigned_short = 8, // unsigned short e_unsigned_short_int = 9, // unsigned short integer e_int = 10, // integer e_signed_int = 11, // signed integer e_unsigned = 12, // unsigned e_unsigned_int = 13, // unsigned integer e_long = 14, // long integer e_long_int = 15, // long integer e_signed_long = 16, // signed long integer e_signed_long_int = 17, // signed long integer e_unsigned_long = 18, // unsigned long integer e_unsigned_long_int = 19, // unsigned long integer e_long_long = 20, // long long integer e_long_long_int = 21, // long long integer e_signed_long_long = 22, // signed long long integer e_signed_long_long_int = 23, // signed long long integer e_unsigned_long_long = 24, // unsigned long long integer e_unsigned_long_long_int = 25, // unsigned long long integer e_float = 26, // float e_double = 27, // double e_long_double = 28, // long double e_ptr = 29, // void * e_char_string = 30, // char * e_wchar_string = 31, // wchar_t * } type_kind; typedef void *value; typedef struct { type_kind tag; value val; } Object;</pre>	

7.2.4 Changes to TRI operation mapping

```

TriStatus xtriMapParam
(const TriPortId* compPortId,
 const TriPortId* tsiPortId,
 const TciParameterListType* parameterList)
TriStatus xtriUnmapParam
(const TriPortId* compPortId,
 const TriPortId* tsiPortId,
 const TciParameterListType* parameterList)
TriStatus xtriSend
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const Value* sutAddress,
 const Value* sendMessage)
TriStatus xtriSendBC
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const Value* sendMessage)
TriStatus xtriSendMC
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const TciValueList* sutAddresses,
 const Value* sendMessage)
void xtriEnqueueMsg
(const TriPortId* tsiPortId,
 const Object* sutAddress,
 const TriComponentId* componentId,
 const Object* receivedMessage)
TriStatus xtriCall
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const Value* sutAddress,
 const TriSignatureId* signatureId,
 const TciParameterListType* parameterList)
TriStatus xtriCallBC
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const TriSignatureId* signatureId,
 const TciParameterListType* parameterList)
TriStatus xtriCallMC
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const TciValueList* sutAddresses,
 const TriSignatureId* signatureId,
 const TciParameterListType* parameterList)
TriStatus xtriReply
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const Value* sutAddress,
 const TriSignatureId* signatureId,
 const TciParameterListType* parameterList,
 const Value* returnValue)
TriStatus xtriReplyBC
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const TriSignatureId* signatureId,
 const TciParameterListType* parameterList,
 const Value* returnValue)
TriStatus xtriReplyMC
(const TriComponentId* componentId,
 const TriPortId* tsiPortId,
 const TciValueList* sutAddresses,
 const TriSignatureId* signatureId,
 const TciParameterListType* parameterList,
 const Value* returnValue)

```

```

TriStatus xtriRaise
(const TriComponentId* componentId,
const TriPortId* tsiPortId,
const Value* sutAddress,
const TriSignatureId* signatureId,
const Value* exception)
TriStatus xtriRaiseBC
(const TriComponentId* componentId,
const TriPortId* tsiPortId,
const TriSignatureId* signatureId,
const Value* exception)
TriStatus xtriRaiseMC
(const TriComponentId* componentId,
const TriPortId* tsiPortId,
const TciValueList* sutAddresses,
const TriSignatureId* signatureId,
const Value* exception)
void xtriEnqueueCall
(const TriPortId* tsiPortId,
const Object* sutAddress,
const TriComponentId* componentId,
const TriSignatureId* signatureId,
const TciParameterListType* parameterList)
void xtriEnqueueReply
(const TriPortId* tsiPortId,
const Object* sutAddress,
const TriComponentId* componentId,
const TriSignatureId* signatureId,
const TciParameterListType* parameterList,
const Value* returnValue)
void xtriEnqueueException
(const TriPortId* tsiPortId,
const Object* sutAddress,
const TriComponentId* componentId,
const TriSignatureId* signatureId,
const Object* exception)
TriStatus xtriExternalFunction
(const TriFunctionId* functionId,
TciParameterListType* parameterList,
Value* returnValue)
Value xtriConvert
(Object* value,
Type* typeHypothesis)
TFloat xtriRnd(TriComponentId *componentId, TFloat* seed)
void xtriPAErrorReq
(const char* message,
const Object* cause)
void xtriSAErrorReq
(const char* message,
const Object* cause)

```

7.9 Changes to clause 8 C++ language mapping

Addition of the following subclause in clause 8.5 Type mapping.

8.5.3 Any type mapping

The IDL any type is represented by struct type of type tag and value:

```

typedef enum {
    e_char = 1,                      // character
    e_unsigned_char = 2,              // unsigned char
    e_signed_char = 3,                // signed char

    e_short = 4,                     // short signed integer
    e_short_int = 5,                 // short signed integer
    e_signed_short = 6,               // short signed integer
    e_signed_short_int = 7,           // short signed integer
    e_unsigned_short = 8,              // unsigned short
    e_unsigned_short_int = 9,          // unsigned short integer

    e_int = 10,                      // integer
    e_signed_int = 11,                // signed integer
}

```

```

e_unsigned = 12,           // unsigned
e_unsigned_int = 13,       // unsigned integer

e_long = 14,              // long integer
e_long_int = 15,           // long integer
e_signed_long = 16,         // signed long integer
e_signed_long_int = 17,      // signed long integer
e_unsigned_long = 18,        // unsigned long integer
e_unsigned_long_int = 19,      // unsigned long integer

e_long_long = 20,           // long long integer
e_long_long_int = 21,         // long long integer
e_signed_long_long = 22,        // signed long long integer
e_signed_long_long_int = 23,      // signed long long integer
e_unsigned_long_long = 24,        // unsigned long long integer
e_unsigned_long_long_int = 25,      // unsigned long long integer

e_float = 26,               // float
e_double = 27,              // double
e_long_double = 28,           // long double

e_ptr = 29,                 // void *

e_char_string = 30,           // char *
e_wchar_string = 31,          // wchar_t *
} type_kind;

typedef void *value;

typedef struct {
    type_kind tag;
    value val;
} Object;

```

8.6.1 Changes to TriCommunicationSA

The extension to the `triCommunicationSa` class is mapped to the following class:

```

class xTriCommunicationSa {
public:

    //Destructor.
    virtual ~xTriCommunicationSA ()=0;

    //To establish a dynamic connection between two ports.
    virtual TriStatus xtriMapParam (const TriPortId *comPortId, const TriPortId *tsiPortId,
    TciParameterList *parameterList)=0;

    //To close a dynamic connection to the SUT for the referenced TSI port.
    virtual TriStatus xtriUnmapParam (const TriPortId *comPortId, const TriPortId *tsiPortId,
    TciParameterList *parameterList)=0;

    //Send operation on a component which has been mapped to a TSI port.
    virtual TriStatus xtriSend (const TriComponentId *componentId, const TriPortId *tsiPortId, const
    TciValue *SUTaddress, const TciValue *sendMessage)=0;

    //Send (broadcast) operation on a component which has been mapped to a TSI port.
    virtual TriStatus xtriSendBC (const TriComponentId *componentId, const TriPortId *tsiPortId,
    const TciValue *sendMessage)=0;

    //Send (multicast) operation on a component which has been mapped to a TSI port.
    virtual TriStatus xtriSendMC (const TriComponentId *componentId, const TriPortId *tsiPortId,
    const TciValueList *SUTaddresses, const TciValue *sendMessage)=0;

    //Initiate the procedure call.
    virtual TriStatus xtriCall (const TriComponentId *componentId, const TriPortId *tsiPortId, const
    TciValue *sutAddress, const TriSignatureId *signatureId, const TciParameterList
    *parameterList)=0;

    //Initiate and broadcast the procedure call.
    virtual TriStatus xtriCallBC (const TriComponentId *componentId, const TriPortId *tsiPortId,
    const TriSignatureId *signatureId, const TciParameterList *parameterList)=0;

    //Initiate and multicast the procedure call.
    virtual TriStatus xtriCallMC (const TriComponentId *componentId, const TriPortId *tsiPortId,
    const TciValueList *sutAddresses, const TriSignatureId *signatureId, const TciParameterList
    *parameterList)=0;

```

```

//Issue the reply to a procedure call.
virtual TriStatus xtriReply (const TriComponentId *componentId, const TriPortId *tsiPortId,
const TciValue *sutAddress, const TriSignatureId *signatureId, const TciParameterList *
parameterList, const TciValue *returnValue)=0;

//Broadcast the reply to a procedure call.
virtual TriStatus xtriReplyBC (const TriComponentId *componentId, const TriPortId *tsiPortId,
const TriSignatureId *signatureId, const TciParameterList *parameterList, const TciValue
*returnValue)=0;

//Multicast the reply to a procedure call.
virtual TriStatus xtriReplyMC (const TriComponentId *componentId, const TriPortId *tsiPortId,
const TciValueList *sutAddresses, const TriSignatureId *signatureId, const TciParameterList
*parameterList, const TciValue *returnValue)=0;

//Raise an exception to a procedure call.
virtual TriStatus xtriRaise (const TriComponentId *componentId, const TriPortId *tsiPortId,
const TciValue *sutAddress, const TriSignatureId *signatureId, const TciValue *exc)=0;

//Raise a broadcast an exception to a procedure call.
virtual TriStatus xtriRaiseBC (const TriComponentId *componentId, const TriPortId *tsiPortId,
const TriSignatureId *signatureId, const TciValue *exc)=0;

//Raise a multicast an exception to a procedure call.
virtual TriStatus xtriRaiseMC (const TriComponentId *componentId, const TriPortId *tsiPortId,
const TciValueList *sutAddresses, const TriSignatureId *signatureId, const TciValue *exc)=0;

// Miscellaneous operations
virtual TciValue *xtriConvert(const Object *value, const TciType *typeHypothesis)=0;
}

```

8.6.2 Changes to TriCommunicationTE

The extension to the `triCommunicationTe` class is mapped to the following class:

```

class xTriCommunicationTe {
public:

//Destructor.
virtual ~xTriCommunicationTE ();

//Called by SA after it has received a message from the SUT.
virtual void xtriEnqueueMsg (const TriPortId *tsiPortId, const Object *SUTaddress, const
TriComponentId *componentId, const Object *receivedMessage)=0;

//Called by SA after it has received a procedure call from the SUT.
virtual void xtriEnqueueCall (const TriPortId *tsiPortId, const Object *SUTaddress, const
TriComponentId *componentId, const TriSignatureId *signatureId, const TciParameterList
*parameterList)=0;

//Called by SA after it has received a reply from the SUT.
virtual void xtriEnqueueReply (const TriPortId *tsiPortId, const Object *SUTaddress, const
TriComponentId *componentId, const TriSignatureId *signatureId, const TciParameterList
*parameterList, const TciValue *returnValue)=0;

//Called by SA after it has received an exception from the SUT.
virtual void xtriEnqueueException (const TriPortId *tsiPortId, const Object *SUTaddress,
const TriComponentId *componentId, const TriSignatureId *signatureId, const Object *exc)=0;

// Error handling
virtual void xtriSAErrorReq (const String message, const Object *cause);
}

```

8.6.3 Changes to TriPlatformPA

The extension to the `TriPlatformPA` class is mapped to the following class:

```

class xTriPlatformPa {
public:

//Destructor.
virtual ~xTriPlatformPA ();

//For each external function specified in the TTCN-3 ATS implement the behaviour.

```

```

virtual TriStatus xtriExternalFunction (const TriFunctionId *functionId, TciParameterList
*parameterList, TciValue *returnValue)=0;
}

```

8.6.4 Changes to TriPlatformTE

The extension to the triPlatformTe class is mapped to the following interface:

```

class TriPlatformTe {
public:

    //Destructor.
    virtual ~xTriPlatformTE () ;

    //Called by PA in unrecoverable error situations.
    virtual void xtriPAError (const TString &message, const Object *cause)=0;

    //Generate random number.
    virtual FloatValue* xtriRnd (const TriComponentId *componentId, const FloatValue *seed)=0;
}

```

7.10 Changes to clause 9 C# language mapping

Addition of the following subclause in clause 9.4 Type mapping.

9.4.3 Any type mapping

The IDL any type is represented by C# object.

9.5.2.1 Changes to ITriCommunicationSA

The extension to the ITriCommunicationSA interface is defined as follows:

```

public interface IXTriCommunicationSA {
    // Reset operation
    // Ref: TRI-Definition 5.5.1
    TriStatus XTriMapParam(ITriPortId compPortId, ITriPortId tsiPortId,
    ITciParameterList parameterList);
    // Ref: TRI-Definition 5.5.2.3
    TriStatus XTriUnmapParam(ITriPortId compPortId, ITriPortId tsiPortId,
    ITciParameterList parameterList);
    // Ref: TRI-Definition 5.5.2.4

    // Message based communication operations
    // Ref: TRI-Definition 5.5.3.1
    TriStatus XTriSend(ITriComponentId componentId, ITriPortId tsiPortId,
    ITciValue address, ITciValue sentMessage);
    // Ref: TRI-Definition 5.5.3.2
    TriStatus XTriSendBC(ITriComponentId componentId, ITriPortId tsiPortId,
    ITciValue sentMessage);
    // Ref: TRI-Definition 5.5.3.3
    TriStatus XTriSendMC(ITriComponentId componentId, ITriPortId tsiPortId,
    ITciValueList addresses, ITciValue sentMessage);

    // Procedure based communication operations
    // Ref: TRI-Definition 5.5.4.1
    TriStatus XTriCall(ITriComponentId componentId, ITriPortId tsiPortId,
    ITciValue sutAddress, ITriSignatureId signatureId,
    ITciParameterList parameterList);
    // Ref: TRI-Definition 5.5.4.2
    TriStatus XTriCallBC(ITriComponentId componentId, ITriPortId tsiPortId,
    ITriSignatureId signatureId, ITciParameterList parameterList);
    // Ref: TRI-Definition 5.5.4.3
    TriStatus XTriCallMC(ITriComponentId componentId, ITriPortId tsiPortId,
    ITciValueList sutAddresses, ITriSignatureId signatureId,
    ITciParameterList parameterList);
    // Ref: TRI-Definition 5.5.4.4
    TriStatus XTriReply(ITriComponentId componentId, ITriPortId tsiPortId,
    ITciValue sutAddress, ITriSignatureId signatureId,
    ITciParameterList parameterList, ITciValue returnValue);
    // Ref: TRI-Definition 5.5.4.5
    TriStatus XTriReplyBC(ITriComponentId componentId, ITriPortId tsiPortId,
    ITciValueList sutAddresses, ITriSignatureId signatureId,
    ITciParameterList parameterList, ITciValue returnValue);
}

```

```

ITriSignatureId signatureId, ITciParameterList parameterList,
ITciValue returnValue);
// Ref: TRI-Definition 5.5.4.6
TriStatus XTriReplyMC(ITriComponentId componentId, ITriPortId tsiPortId,
ITciValueList sutAddresses, ITriSignatureId signatureId,
ITciParameterList parameterList, ITciValue returnValue);
// Ref: TRI-Definition 5.5.4.7
TriStatus XTriRaise(ITriComponentId componentId, ITriPortId tsiPortId,
ITciValue sutAddress, ITriSignatureId signatureId,
ITciValue exc);
// Ref: TRI-Definition 5.5.4.8
TriStatus XTriRaiseBC(ITriComponentId componentId, ITriPortId tsiPortId,
ITriSignatureId signatureId, ITciValue exc);
// Ref: TRI-Definition 5.5.4.9
TriStatus XTriRaiseMC(ITriComponentId componentId, ITriPortId tsiPortId,
ITciValueList sutAddresses, ITriSignatureId signatureId,
ITciValue exc);
// Ref: TRI-Definition 5.5.3.5
ITciValue XTriConvert(object value, ITciType typeHypothesis);
}

```

9.5.2.2 Changes to ITriCommunicationTE

The extension to the **ITriCommunicationTE** interface is defined as follows:

```

public interface IXTriCommunicationTE {
    // Message based communication operations
    // Ref: TRI-Definition 5.5.3.4
    void XTriEnqueueMessage(ITriPortId tsiPortId, object sutAddress,
                           ITriComponentId componentId, object msg);

    // Procedure based communication operations
    // Ref: TRI-Definition 5.5.4.10
    void XTriEnqueueCall(ITriPortId tsiPortId, object sutAddress,
                         ITriComponentId componentId, ITriSignatureId signatureId,
                         ITciParameterList parameterList);
    // Ref: TRI-Definition 5.5.4.10
    void XTriEnqueueReply(ITriPortId tsiPortId, object sutAddress,
                          ITriComponentId componentId, ITriSignatureId signatureId,
                          ITciParameterList parameterList, ITciValue returnValue);
    // Ref: TRI-Definition 5.5.4.11
    void XTriEnqueueException(ITriPortId tsiPortId, object sutAddress,
                             ITriComponentId componentId, ITriSignatureId signatureId,
                             object exc);
    // Ref: TRI Definition 5.2.1
    void XTriSErrorReq (string message, object cause);
}

```

9.5.2.3 Changes to ITriPlatformPA

The extension to the **ITriPlatformPA** interface is defined as follows:

```

public interface IXTriPlatformPA {
    // Ref: TRI-Definition 5.6.1      // Miscellaneous operations
    // Ref: TRI-Definition 5.6.3.1
    TriStatus XTriExternalFunction(ITriFunctionId functionId,
                                   ITciParameterList parameterList, ITciValue returnValue);
}

```

9.5.2.4 Changes to ITriPlatformTE

The extension to the **ITriPlatformTE** interface is defined as follows:

```

public interface ITriPlatformTE {
    // Ref: TRI Definition 5.2.2
    void XTriPAErrorReq (string message, object cause);
    // Ref: TRI Definition clause 5.6.3.3
    FloatValue XTriRnd(ITriComponentId componentId, FloatValue seed);
}

```

8 TCI extensions for the package

Not applicable.

History

Document history		
V1.1.1	April 2012	Publication
V1.2.1	April 2013	Publication
V1.3.1	April 2014	Membership Approval Procedure MV 20140607: 2014-04-08 to 2014-06-09