

**Telecommunications and Internet converged Services and
Protocols for Advanced Networking (TISPAN);
IP Multimedia: H.248 Profile for controlling
Multimedia Resource Function Processors (MRFP)
in the IP Multimedia System (IMS);
Protocol specification**



Reference

RES/TISPAN-03091-NGN-R1

Keywords

control, H.248, profile, stage 3

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2007.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	6
3 Definitions and abbreviations.....	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Applicability.....	8
4.1 Architecture	8
4.2 Functional requirements	9
5 Profile description	9
5.1 Profile identification.....	9
5.2 Summary	9
5.3 Gateway control protocol version.....	9
5.4 Connection model.....	10
5.5 Context attributes	10
5.6 Terminations.....	10
5.6.1 Termination names	10
5.6.2 Multiplexed terminations	11
5.7 Descriptors	11
5.7.1 Stream Descriptor	11
5.7.1.1 LocalControl Descriptor.....	11
5.7.2 Events Descriptor.....	12
5.7.3 EventBuffer Descriptor.....	13
5.7.4 Signals Descriptor.....	13
5.7.5 DigitMap Descriptor	14
5.7.6 Statistics Descriptor	14
5.7.7 ObservedEvents Descriptor	14
5.7.8 Topology Descriptor	14
5.7.9 Error Descriptor	15
5.8 Command API.....	15
5.8.1 Add	15
5.8.2 Modify	15
5.8.3 Subtract.....	15
5.8.4 Move	16
5.8.5 AuditValue.....	16
5.8.6 AuditCapabilities	16
5.8.7 Notify	16
5.8.8 ServiceChange	16
5.8.9 Manipulating and auditing context attributes.....	17
5.9 Generic command syntax and encoding.....	17
5.10 Transactions	18
5.11 Messages	18
5.12 Transport	18
5.13 Security	19
5.14 Packages	19
5.14.1 Generic package.....	21
5.14.2 Base root package	22
5.14.3 Network package	22
5.14.4 RTP package	23
5.14.5 Extended DTMF detection package.....	23
5.14.6 Call progress tones generator package.....	24
5.14.7 Basic services tones generator package	25

5.14.8	Expanded call progress tones generator package	25
5.14.9	Basic announcement syntax package	26
5.14.10	Voice variable syntax package.....	26
5.14.11	Announcement set syntax package	27
5.14.12	General text variable type package	27
5.14.13	Advanced audio server base package.....	28
5.14.14	AAS digit collection package	29
5.14.15	AAS recording package	30
5.14.16	AAS segment management package.....	31
5.14.17	Generic announcement package	32
5.14.18	Intrusion tones generator package	33
5.14.19	Business tones generation package	33
5.14.20	Conferencing tones generation package	34
5.14.21	Floor control package	34
5.14.22	View package.....	35
5.14.23	Volume control package	35
5.14.24	Volume detection package.....	36
5.14.25	Volume level mixing package	36
5.14.26	Mixing volume level control package.....	37
5.14.27	Inactivity timer package.....	37
5.14.28	MGC information package	38
5.15	Mandatory support of SDP and annex C information elements	38
5.16	Procedures	40
6	Procedures	40
6.1	General procedures.....	40
6.2	Use of voice codecs	40
6.2.1	Comfort noise insertion and silence suppression for voice codecs	40
6.2.2	DTMF transmission	41
6.2.3	Support of G.711 variants	41
6.2.3.1	G.711 Encoding law.....	41
6.2.3.2	G.711 silence suppression mode	41
6.2.3.3	G.711 packet loss concealment	42
6.3	Procedures for basic user interaction.....	42
6.4	Procedures for advanced user interaction	42
6.5	Procedures for conferencing	42
6.6	Procedures for transcoding	42
	History	44

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN), and is now submitted for the ETSI standards Membership Approval Procedure.

1 Scope

The present document defines a profile of the Gateway Control Protocol (H.248.1), for controlling Multimedia Resource Function Processors (MRFP) supporting in-band user interaction, conferencing and transcoding for voice-based services.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

- [1] ETSI ES 282 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture Release 1".
- [2] ETSI ES 282 002: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); PSTN/ISDN Emulation Sub-system (PES); Functional architecture".
- [3] ETSI ES 201 970: "Access and Terminals (AT); Public Switched Telephone Network (PSTN); Harmonized specification of physical and electrical characteristics at a 2-wire analogue presented Network Termination Point (NTP)".
- [4] ITU-T Recommendation H.248.45: "Gateway control protocol: MGC information package".
- [5] ITU-T Recommendation H.248.1 Corrigendum 1: "Gateway control protocol: Version 2".
- [6] ITU-T Recommendation H.248.4 Corrigendum 1: "Gateway control protocol: Transport over Stream Control Transmission Protocol (SCTP)".
- [7] ITU-T Recommendation H.248.7: "Gateway control protocol: Generic Announcement package".
- [8] ITU-T Recommendation H.248.9: "Gateway control protocol: Advanced media server packages".
- [9] ITU-T Recommendation H.248.14: "Gateway control protocol: Inactivity timer package".
- [10] ITU-T Recommendation H.248.16 Corrigendum 1: "Gateway control protocol: Enhanced digit collection packages and procedures".
- [11] ITU-T Recommendation H.248.19: "Gateway control protocol: Decomposed multipoint control unit, audio, video and data conferencing packages".
- [12] ITU-T Recommendation H.248.27: "Gateway control protocol: Supplemental tones packages".
- [13] ITU-T Recommendation Q.1950: "Bearer independent call bearer control protocol".
- [14] ITU-T Recommendation G.711: "Pulse code modulation (PCM) of voice frequencies".
- [15] ITU-T Recommendation G.711 Appendix I: "A high quality low-complexity algorithm for packet loss concealment with G.711".

- [16] ITU-T Recommendation G.711 Appendix II: "A comfort noise payload definition for ITU-T G.711 use in packet-based multimedia communication systems".
- [17] ITU-T Recommendation T.38: "Procedures for real-time Group 3 facsimile communication over IP networks".
- [18] ITU-T Recommendation E.180: "Technical characteristics of tones for the telephone service".
- [19] IETF RFC 2327: "SDP: Session Description Protocol".
- [20] IETF RFC 3551: "RTP Profile for Audio and Video Conferences with Minimal Control".
- [21] IETF RFC 2833: "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals".
- [22] IETF RFC 3389: "Real-time Transport Protocol (RTP) Payload for Comfort Noise (CN)".
- [23] IETF RFC 3555: "MIME Type Registration of RTP Payload Formats".
- [24] IETF RFC 4234: "Augmented BNF for Syntax Specifications: ABNF".
- [25] ETSI ES 201 235-3: "Access and Terminals (AT); Specification of Dual-Tone Multi-Frequency (DTMF) Transmitters and Receivers; Part 3: Receivers".
- [26] IETF RFC 3066: "Tags for the Identification of Languages".
- [27] ISO 8601: "Data elements and interchange formats - Information interchange - Representation of dates and times".
- [28] ITU-T Recommendation H.248.1: "Implementors Guide for the H.248 Sub-series of Recommendations ("Media Gateway Control Protocol")".
- [29] ITU-T Recommendation H.248.8: "Gateway control protocol: Error code and service change reason description".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Media Gateway (MG): See ITU-T Recommendation H.248.1 [5].

Media Gateway Controller (MGC): See ITU-T Recommendation H.248.1 [5].

Multimedia Resource Function Controller (MRFC): See ES 282 001 [1].

Multimedia Resource Function Processor (MRFP): See ES 282 001 [1].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAS	Advanced Audio Server
AS	Application Server
ASR	Automatic Speech Recognition
AVP	Audio/Video Profile
CN	Comfort Noise
CRC	Cyclic Redundancy Check
DNS	Domain Name System
DTMF	Dual Tone Multi Frequency
ID	Identity
IMS	IP Multimedia Subsystem

IP	Internet Protocol
MG	Media Gateway
MGC	Media Gateway Controller
MRFC	Multimedia Resource Function Controller
MRFP	Multimedia Resource Function Processor
PLC	Packet Loss Concealment
PT	Payload Type
RTCP	Real-Time Transport Control Protocol
RTP	Real-Time Transport Protocol
S-CSCF	Serving Call Session Control Function
SCTP	Stream Control Transmission Protocol
SDP	Session Description Protocol
SSRC	Synchronization SouRCe
TTL	Time To Live
TTS	Text To Speech
UDP	User Datagram Protocol
UI	User Interaction

4 Applicability

4.1 Architecture

Within the IMS architecture (ES 282 002 [2]), the Mp reference point allows an MRFC to control media stream resources provided by an MRFP. The MRFC controls the MRFP, based on the information received from Application Servers, via the S-CSCF, at the Mr reference point. The MRFP sources and sinks media streams at the Mb reference point, which represents the interface to core network transport resources. Figure 1 shows the functional entities and reference points involved in the control of multimedia resources. The present document focuses on the Mp reference point. The protocol used over the Mp reference point is the gateway control protocol defined in ITU-T Recommendation H.248.1 [5]. With regards to the architecture assumed by this Recommendation, the MRFC plays the role of an MGC and the MRFP plays the role of an MG.




Figure 1: MRF entities and interfaces in the IMS architecture

Three categories of MRFP functionalities are identified by the present document:

- Support of User Interaction (UI). This category is subdivided into two subcategories:
 - Basic User Interaction (BASIC_UI): This includes basic support for sending tones and fixed announcements, and support of DTMF collection.
 - Advanced User Interaction (ADVANCED_UI): This includes support for BASIC_UI, variable announcements, ASR and voice mailbox capabilities.

- Support for transcoding (TRANSCODING). This includes support for transcoding between voice codecs.

NOTE: Support of advanced transcoding (e.g. transcoding between voice codecs and text-based codecs or ITU-T Recommendation T.38 [17]) is outside the scope of the present document.

- Support for conferencing (CONFERENCING). This category is subdivided into two subcategories:
 - Basic Conferencing (BASIC_CONFERENCING): This includes support for 3-party calls.
 - Advanced conferencing (ADVANCED_CONFERENCING): This includes support for BASIC_CONFERENCING, support of large voice conferences and support for floor control procedures.

4.2 Functional requirements

Support of the packages identified in the profile definition implies support of the underlying functionalities. This clause identifies additional functional requirements that media gateways conforming to the present document shall comply with:

- Media Resource Function Processors (MRFP) shall support IPv4 and may support IPv6.
- Media Resource Function Processors (MRFP) shall support G.711 A-law voice codec and may support other codecs. Media Resource Function Processors supporting TRANSCODING are expected to support a wide range of well-known codecs. The list of codecs is outside the scope of the present document.
- Media Resource Function Processors (MRFP) shall support the procedures defined in RFC 2833 [21] to generate, detect and forward DTMF digits. DTMF shall be identified by name (see mode "Named Telephone Events" in clause 3 of RFC 2833 [21]), as opposed to their waveform properties.
- All properties of tones requested by the MRFC shall be provisioned in the MRFP. The MRFC is not required to send the physical characteristics of tones to Media Resource Function Processors (MRFP).

5 Profile description

5.1 Profile identification

The name and version of the profile that is sent in the service change command are:

Table 5.1.1: Profile Identification

Profile name	ETSIprof_MediaServer (to be registered at IANA)
Version	1

5.2 Summary

The profile defined in the present document enables the control of Multimedia Resource Function Processors (MRFP) supporting in-band user interaction, conferencing and transcoding for voice services.

NOTE: It is expected that future versions of this profile will support similar features in the context of multimedia communications.

5.3 Gateway control protocol version

Version 2 shall be the minimum version supported. Support of this version implies conformance to ITU-T Recommendation H.248.1 version 2 [5] and Corrigendum 1, and implementation of the corrections available in the latest version of the H.248 Implementors' Guide [28].

5.4 Connection model

Multimedia Resource Function Processors (MRFP) shall support ephemeral terminations that sink and source RTP traffic. This type of H.248 Termination is denoted "RTP" in the following clauses.

Only one stream type "audio" is supported by the present document. This stream type represents RTP/RTCP traffic with media type "audio" as defined in RFC 2327 [19].

Table 5.4.1: Connection Model

Maximum number of contexts	Provisioned (see note 1)
Maximum number of terminations per context	1 (see note 2), 2 (see note 3) 32 (see note 4)
Allowed terminations type combinations in a context:	Not Applicable
NOTE 1: The actual number of supported contexts can be audited by the MRFC using the MaxNrOfContexts property defined in the Base Root Package.	
NOTE 2: Support of 1 termination in a context is sufficient in case the MRFP supports USER_INTERACTION only.	
NOTE 3: Support of 2 terminations is required if TRANSCODING is supported.	
NOTE 4: Support of up to 32 terminations may be required if CONFERENCING is supported. The actual number of supported terminations can be audited by the MRFC using the maxTerminationsPerContext property defined in the Base Root Package.	

5.5 Context attributes

Table 5.5.1: Context Attributes

Context Attribute	Supported	Values supported
Topology	No (see note)	Not applicable
Priority Indicator	Yes	0 to 15
Emergency Indicator	No	Not applicable
ContextAttribute Descriptor	No	Not applicable
ContextIDList Parameter	No	Not applicable
AND/OR Context Attribute supported?	No	Not applicable (H.248 version 3 only)
NOTE: Use of the topology descriptor for supporting lawful interception may be required in future versions of this profile if the MRFP is used as a point of content interception.		

5.6 Terminations

5.6.1 Termination names

The Termination ID structure is provisioned in the MRFC and MRFP and is known by the MRFP and the MRFC at or before start up.

The following naming convention is recommended:

ephemeral/<string of alphanumeric characters or "/">, e.g. ephemeral/1/0/40000

The following ABNF [24] specification further describes the syntax for this naming convention.

```

pathName = EphToken SLASH EPHsystem
EphToken = "ephemeral" ; so called prefix
                    ; The maximum length of 'pathname' is defined in Annex B.2/H.248.1.
EPHsystem = 0*(HierarchyLevelHIGHToken SLASH) HierarchyLevelLOWToken
HierarchyLevelHIGHToken = 1*alphanum
HierarchyLevelLOWToken = Individual / Wildcard
alphanum   = ALPHA / DIGIT
Individual = 1*DIGIN
Wildcard   = "$" / "*"

```

5.6.2 Multiplexed terminations

Table 5.6.2.1: Multiplexed Terminations

Multiplex terminations supported?	NO
-----------------------------------	----

5.7 Descriptors

5.7.1 Stream Descriptor

Table 5.7.1.1: Maximum number of streams per termination type

Maximum number of streams per termination type	RTP	1
--	-----	---

5.7.1.1 LocalControl Descriptor

The following tables specify the level of support required with regard to the properties in the local control descriptor.

Table 5.7.1.1.1: LocalControl descriptor

		Termination type	Stream type
Reserve group used	NO	RTP	Not Applicable
Reserve value used	YES	RTP	Audio

- ReserveValue

The MRFC shall set the "ReserveValue" property to "true" when multiple codecs are specified within a single "m=" line of a session descriptor block and resources are required to be reserved in the MRFP for the multiple codecs. This situation occurs for example in case of user interaction procedures where the user is expected to either speak or enter digits. The "ReserveValue" property shall be set to "true" in cases where a low bit rate codec is used for transporting voice and the special payload type defined in RFC 2833 [21] is used for transporting DTMF.

Alternatively, if the MRFC when it specifies multiple codecs requires the MRFP to select one of the codecs, then it shall set the "ReserveValue" property to "false".

In the situation where the MRFC specifies a single codec within a "m=" line, then the ReserveValue property shall be omitted or set to "false".

- Stream Mode

Table 5.7.1.1.2: Stream mode

Termination Type	Stream type	Allowed StreamMode Values
ALL except ROOT	Any	Send, Receive, Send and Receive, Inactive

Table 5.7.1.1.3: Local control properties

Properties associated with Local Control Descriptor supported		Yes	
If yes	Property IDs Reported	Termination type	Stream type
	MGCinfo/db	RTP	Any
	nt/jit	RTP	Any
	aassm/*	RTP	Audio
	aasrec/*	RTP	Audio
	vcp/level	RTP	Audio
	vlmp/mixlevel	RTP	Audio
	vlmp/nspeakmix	RTP	Audio
	mvlcp/mixpartnum	RTP	Audio
	mvlcp/vollevip	RTP	Audio

5.7.2 Events Descriptor

Table 5.7.2.1: Events setting

Events settable on termination types and stream types	Yes		
If yes	Event ID	Termination Type	Stream Type
	g/*	RTP	Any
	nt/*	RTP	Any
	rtp/*	RTP	Any
	xdd/*	RTP	Audio
	aasrec/*	RTP	Audio
	aasdc/*	RTP	Audio
	aasb/*	RTP	Audio
	it/*	ROOT	Not Applicable
	vdp/*	RTP	Audio

Table 5.7.2.2: Event Buffer Control

Event Buffer Control used	No
---------------------------	----

Table 5.7.2.3: Keepactive Flag

Keepactive used on events	Yes
---------------------------	-----

Table 5.7.2.4: Embedded Events

Embedded events in an event descriptor	Yes
Embedded signals in an event descriptor	Yes

Table 5.7.2.5: Regulated Embedded Events

Regulated Embedded events are triggered on	None
--	------

Table 5.7.2.6: Reset Events Descriptor

ResetEventsDescriptor used with events	None
--	------

Table 5.7.2.7: Notification Behaviour

Supported Notification Behaviour	
NotifyImmediate	ALL events
NotifyRegulated	None
NeverNotify	None

5.7.3 EventBuffer Descriptor

Table 5.7.3.1: Event Buffer Descriptor

Event Buffer descriptor used	No	
<i>If yes</i>	Event IDs	Not applicable

5.7.4 Signals Descriptor

Table 5.7.4.1: Signals Descriptor

Signals settable dependant on termination or streams types	Yes		
<i>If yes</i>	Signal ID	Termination Type	Stream Type/ID
	cg/*	RTP	Audio
	srvtn/*	RTP	Audio
	xcg/*	RTP	Audio
	an/*	RTP	Audio
	int/*	RTP	Audio
	biztn/*	RTP	Audio
	aasrec/*	RTP	Audio
	aasdcc/*	RTP	Audio
	aasb/*	RTP	Audio
	conftr/*	RTP	Any
	aassm/*	RTP	Audio
	indview/*	RTP	Any

Table 5.7.4.2: Signals Lists

Signals Lists supported	Yes		
<i>If yes</i>	Termination Type Supporting Lists	RTP	
	Stream Type Supporting lists	Audio	
	Maximum number of signals per signal list	Provisioned	
	Intersignal delay parameter supported	No	

Table 5.7.4.3: Overriding of signal type and duration

Overriding of Signal type and duration supported?	Yes		
<i>If yes</i>	Signal ID	Type or duration override	

Table 5.7.4.4: Signal Direction

Signal Direction supported	No
-----------------------------------	----

Table 5.7.4.5: Notify Completion

Notify completion supported	Yes	
<i>If yes</i>	Signal ID cg/*, svrtn/*, xcg/*, an/*, int/*, biztn/*, conftn/*, indview/*	Type of completion supported ALL
RequestID Parameter Supported	Yes	

Table 5.7.4.6: Simultaneous signals

Signals played simultaneously	Yes	
<i>If yes</i>	Signal Ids that can be played simultaneously	ALL

Table 5.7.4.7: Keepactive on signals

Keepactive used on signals	Yes
-----------------------------------	-----

5.7.5 DigitMap Descriptor

Table 5.7.5.1: DigitMap Descriptor

DigitMaps supported	if (ADVANCED_UI) then YES else NO		
<i>If yes</i>	DigitMap Name	Structure	Timers

5.7.6 Statistics Descriptor

Table 5.7.6.1: Statistics Descriptor

Statistics supported on	Not Supported
--------------------------------	---------------

Table 5.7.6.2: Statistics reported on Subtract

Statistics reported on Subtract	No
--	----

5.7.7 ObservedEvents Descriptor

When the event is provisioned in the media gateway, the Request Id is set to FFFFFFFFH.

Table 5.7.7.1: Observed Events Descriptor

Event detection time supported	Yes
---------------------------------------	-----

5.7.8 Topology Descriptor

Table 5.7.8.1: Topology Descriptor

Allowed triples	Not supported
------------------------	---------------

5.7.9 Error Descriptor

Error codes sent by the MRFC.

Table 5.7.9.1: MRFC Error Descriptor

Supported H.248.8 [29] Error Codes	ALL
Supported Error Codes defined in packages	400-411,421,422, 430, 431,440,442—458, 505, 533

Error codes sent by the MRFP.

Table 5.7.9.2: MRFP Error Descriptor

Supported H.248.8 [29] Error Codes	ALL
Supported Error Codes defined in packages	400-411, 412, 421,422,430, 431, 432-435,440,441,442-458, 471, 500-540, 600-612

5.8 Command API

NOTE: It is assumed that an Error Descriptor may be returned in any command reply.

5.8.1 Add

Table 5.8.1.1: Add request

Descriptors used by Add request	ALL except Mux
--	----------------

Table 5.8.1.2: Add reply

Descriptors used by Add reply	ALL except Mux
--------------------------------------	----------------

5.8.2 Modify

Table 5.8.2.1: Modify request

Descriptors used by Modify request	ALL except Mux
---	----------------

Table 5.8.2.2: Modify reply

Descriptors used by Modify reply	ALL except Mux
---	----------------

5.8.3 Subtract

Table 5.8.3.1: Subtract request

Descriptors used by Subtract request	Audit
---	-------

Table 5.8.3.2: Subtract reply

Descriptors used by Subtract reply	None
---	------

5.8.4 Move

Table 5.8.4.1: Move request

Move command used	Yes
-------------------	-----

Table 5.8.4.2: Move reply

Descriptors used by Move Request	ALL except Mux
Descriptors used by Move Reply	ALL except Mux

5.8.5 AuditValue

Table 5.8.5.1: AuditValue

Audited Properties	ALL properties	in ALL descriptors
Audited Statistics	None	
Audited Signals	ALL	
Audited Events	ALL	
Packages Audit possible?	YES	

5.8.6 AuditCapabilities

This command is optional.

Table 5.8.6.1: AuditCapabilities

Audited Properties	ALL properties	in ALL descriptors
Audited Statistics	None	
Audited Signals	ALL	
Audited Events	ALL	

Table 5.8.6.2: Scoped audit

Audited Properties/ContextAttributes used for a scoped audit	None
--	------

5.8.7 Notify

Table 5.8.7.1: Notify descriptors

Descriptors used by Notify Request or Reply	ObservedEvents
---	----------------

5.8.8 ServiceChange

Table 5.8.8.1: Service change MRFC

ServiceChangeMethods and ServiceChangeReasons sent by MRFC.

Service Change Methods Supported	ServiceChange Reasons supported
Forced, Graceful, Restart, Handoff	900 – 917 except 908 and 909

Table 5.8.8.2: Service change MRFP

ServiceChangeMethods and **ServiceChangeReasons** sent by MRFP.

Service Change Methods Supported	ServiceChange Reasons supported
Forced, Graceful, Restart, Handoff, Failover, Disconnected	900-917

Table 5.8.8.3: Service change address

ServiceChangeAddress used	No
---------------------------	----

Table 5.8.8.4: Service change delay

ServiceChangeDelay used	Yes	
If yes	Valid time period	Provisioned

Table 5.8.8.5: Service change incomplete flag

ServiceChange Incomplete Flag used	No
------------------------------------	----

Table 5.8.8.6: Service change version

Version used in ServiceChangeVersion	Version 2 [5] shall be the minimum version used in ServiceChangeVersion.
--------------------------------------	--

Table 5.8.8.7: Profile negotiation

Profile negotiation as per H.248.18	No
-------------------------------------	----

5.8.9 Manipulating and auditing context attributes

Table 5.8.9.1: Manipulating and auditing context attributes

Context attributes manipulated	ALL supported attributes (See table 5.5.1)
Context attributes audited	ALL supported attributes (See table 5.5.1)

5.9 Generic command syntax and encoding

Table 5.9.1: Syntax and ENcoding

Supported encodings	Text encoding shall be supported by both the MRFP and the MRFC. Both the long and short form of text encoding shall be supported at the receiving side.
---------------------	---

5.10 Transactions

Table 5.10.1: Transactions

Maximum number of Transaction Requests/Replies/TransResponseAcks/Segment Replies per message	2 (see note)
NOTE: When two elements are conveyed in one message, it is recommended that this message comprises a Transaction Request/Transaction Reply/Transaction Pending plus a Transaction Response Ack.	

Table 5.10.2: Maximum number of commands per transaction request

Maximum number of commands per Transaction request	32 IF ADVANCED_CONFERENCING ELSE 3
NOTE: Only one action per transaction is supported.	

Table 5.10.3: Maximum number of commands per transaction reply

Maximum number of commands per Transaction reply	32 IF ADVANCED_CONFERENCING ELSE 3
---	------------------------------------

Table 5.10.4: Optional commands

Commands able to be marked "Optional"	AUDITVALUE, AUDITCAPABILITY
--	-----------------------------

Table 5.10.5: Transaction timers

Transaction Timer	Value
NormalMGExecutionTime	Provisioned in the MRFP
NormalMGCExecutionTime	Provisioned in the MRFP
MGOriginatedPendingLimit	Provisioned in the MRFP
MGCOriginatedPendingLimit	Provisioned in the MRFP
MGProvisionalResponseTimerValue	Provisioned in the MRFP
MGCProvisionalResponseTimerValue	Provisioned in the MRFP

Transaction timers (as defined in the properties of the Base Root package) shall be in a range between 100 ms and 5 s. The MRFC may overwrite the provisioned values.

5.11 Messages

It is recommended that MRFP and MRFC names are in the form of fully qualified domain name. For example the domain name of the MRFC may be of the form mrfc1.whatever.net and the name of the MRFP may be of the form mg1.whatever.net.

The fully qualified domain name will be used by the MRFP and MRFC as part of the "Message Identifier" in the H.248 messages which identifies the originator of the message.

5.12 Transport

Table 5.12.1: Transport

Supported transports	Transport over UDP shall be supported. Support of SCTP is optional and shall conform to ITU-Recommendation H.248.4 [6]. Choosing one option or the other is a network operator's decision, based on the network configuration.
-----------------------------	--

For UDP transport the destination IP addresses to be used for delivering the H.248 messages are retrieved through the following means:

- The MRFC stores the source IP address retrieved from the message carrying first ServiceChange command. All subsequent messages delivered to the MRFP will use this IP address.
- The MRFP stores the source IP address retrieved from the message carrying the reply to the ServiceChange command. All subsequent messages delivered to the MRFC uses this IP address.

NOTE: The MRFP uses the DNS lookup in order to retrieve the initial IP address to send the first ServiceChange command. This IP address may be different than the IP address returned in the reply to ServiceChange command.

Table 5.12.2: Segmentation supported

Segmentation supported	UDP: No SCTP: Inherent in transport (see note)
NOTE: The H.248 Segmentation Package according annex E.14 of H.248.1 [5]Version 3 is intended for H.248 transport technologies without the capability of automatic message segmentation. This method is not required for UDP- or SCTP-based H.248 signalling transport in this Profile.	

Table 5.12.3: Control association monitoring

Control association monitoring supported	UDP: AuditValue on Root and ITU-T Recommendation H.248.14 [9] SCTP: Inherent in Transport.
---	--

5.13 Security

Table 5.13.1: Security

Supported security	For the purpose of the present document the control protocols are considered to be inside the secured zone of a single operator. The specified H.248 security options should not be used, as these interfaces are considered to be within a secured zone.
---------------------------	---

5.14 Packages

Table 5.14.1: Mandatory packages

Mandatory packages		
Package Name/Reference	Package ID	Version
Generic (ITU-T Recommendation H.248.1 [5])	g	1
Base Root (ITU-T Recommendation H.248.1 [5])	root	2
Network (ITU-T Recommendation H.248.1 [5])	nt	1
RTP Package (ITU-T Recommendation H.248.1 [5])	rtp	1

Table 5.14.2: Optional packages

Optional Packages			
Package Name/Reference	Package ID	Version	Support dependent on
Extended DTMF Detection (H.248.16 [10])	xdd	1	Support is mandatory if BASIC_UI is supported and the AAS Digit Collection package is not supported, optional otherwise.
Call Progress Tones Generator (H.248.1 [5])	cg	1	Support is mandatory if BASIC_UI and the Advanced Audio Server Base and the Voice Variable Syntax packages are not supported, optional otherwise.

Optional Packages			
Package Name/Reference	Package ID	Version	Support dependent on
Basic Services Tones Generator (Q.1950 [13])	srvtn	1	Support is mandatory if BASIC_UI and the Advanced Audio Server Base and the Voice Variable Syntax packages are not supported, optional otherwise.
Expanded Call Progress Tones Generator (Q.1950 [13])	xcg	1	Support is mandatory if BASIC_UI and the Advanced Audio Server Base and the Voice Variable Syntax packages are not supported, optional otherwise.
Basic Announcement Syntax (H.248.9 [8])	bannsyx	1	Support is mandatory if ADVANCED_UI is supported, Support is mandatory if BASIC_UI is supported and the Generic Announcement package is not supported, optional otherwise.
Voice Variable Syntax (H.248.9 [8])	vvsyx	1	Support is mandatory if ADVANCED_UI is supported, optional otherwise.
Announcement Set Syntax (H.248.9 [8])	setsyx	2	Support is mandatory if ADVANCED_UI, optional otherwise.
General text Variable type (H.248.9 [8])	phrsyx	2	Support is mandatory if ADVANCED_UI, optional otherwise (required for TTS).
Advanced Audio Server Base (H.248.9 [8])	aasb	1	Support is mandatory if ADVANCED_UI, Support is mandatory if BASIC_UI and the Generic Announcement package is not supported, optional otherwise.
AAS Digit collection (H.248.9 [8])	aasdcc	2	Support is mandatory if ADVANCED_UI, optional otherwise.
AAS Recording package (H.248.9 [8])	aasrec	1	Support is mandatory if ADVANCED_UI, optional otherwise.
AAS segment management (H.248.9 [8])	aassm	1	Optional.
Generic Announcement (H.248.7 [7])	an	2	Support is mandatory if BASIC_UI and the Advanced Audio Server Base package is not supported, optional otherwise.
Intrusion Tones Generation (Q.1950 [13])	int	1	Support is mandatory if BASIC_UI and the Advanced Audio Server Base and the Voice Variable Syntax packages are not supported, optional otherwise.
Business Tones Generation (Q.1950 [13])	biztn	1	Support is mandatory if BASIC_UI and the Advanced Audio Server Base and the Voice Variable Syntax packages are not supported, optional otherwise.
Conferencing Tones Generation (H.248.27 [12])	conftn	1	Support is mandatory if BASIC_CONFERENCING is supported, not required otherwise.
Floor Control (H.248.19 [11])	fcp	1	Support is mandatory if ADVANCED_CONFERENCING is supported, not required otherwise.
View (H.248.19 [11])	indview	1	Support is mandatory if ADVANCED_CONFERENCING is supported, not required otherwise.
Volume Control (H.248.19 [11])	vcp	1	Support is mandatory if ADVANCED_CONFERENCING is supported, optional otherwise.
Volume Detection (H.248.19 [11])	vdt	1	Support is mandatory if ADVANCED_CONFERENCING is supported, optional otherwise.
Volume Level Mixing (H.248.19 [11])	vlm	1	Support is mandatory if ADVANCED_CONFERENCING is supported, not required otherwise.
Mixing Volume Level Control (H.248.19 [11])	mvlc	1	Support is mandatory if ADVANCED_CONFERENCING is supported, not required otherwise.
Inactivity Timer (H.248.14 [9])	it	1	Support is mandatory if UDP transport is enabled for H.248 messages.
MGC Information (H.248.45 [4])	MGCIinfo	1	This package may be supported as an operator option. For this profile the information string shall be limited to 32 octets in length.

5.14.1 Generic package

Table 5.14.1.1: Package usage information for generic package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		
None	Not applicable	Not applicable		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
Cause	O	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	None	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	General Cause	M	ALL	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
Signal Completion	Failure cause	Not used	Not applicable	Not applicable
	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	None	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Signal identity	M	ALL	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Termination method	M	ALL except PI	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Signal List ID	O	ALL	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Request ID	O	ALL	Not applicable
Statistics	Mandatory/ Optional	Used in command		Supported Values
None	Not applicable	Not applicable		Not applicable
Error Codes		Mandatory/Optional		
None		Not applicable		

5.14.2 Base root package

Table 5.14.2.1: Package usage information for base root package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
maxNrOfContexts, maxTerminationsPerContext	M	AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable
normalMGExecutionTime normalMGCExecutionTime MGProvisionalResponseTimerValue MGCProvisionalResponseTimerValue MGCOriginatedPendingLimit MGOigitatedPendingLimit	M	AUDITVALUE, AUDITCAPABILITY, MODIFY	ALL	Not applicable
ALL	M	AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable
Signals	Mandatory/ Optional	Used in command	Duration Provisioned Value	
None	Not applicable	Not applicable		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
None	Not applicable	Not applicable		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
Not applicable	Not applicable	Not applicable	Not applicable	
Statistics	Mandatory/ Optional	Used in command	Supported Values	
None	Not applicable	Not applicable		Not applicable
Error Codes		Mandatory/Optional		
None		Not applicable		

5.14.3 Network package

Table 5.14.3.1: Package usage information for network package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
Maximum Jitter Buffer	Should not be used by the MRFC and shall be ignored by the MRFP	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command	Duration Provisioned Value	
None	Not applicable	Not applicable	Not applicable	
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable

Events	Mandatory/ Optional	Used in command		
Network Failure	O	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Cause	M	ALL	Not applicable
Statistics	Mandatory/ Optional	Used in command		Supported Values
None				
Error Codes	Mandatory/Optional			
None	Not applicable			

5.14.4 RTP package

Table 5.14.4.1: Package usage information for RTP package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
None	Not applicable	Not applicable		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
Payload transition	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	RTP Payload Type	M	ALL	Not applicable
Statistics	Mandatory/ Optional	Used in command		Supported Values
None				
Error Codes	Mandatory/Optional			
None	Not applicable			

5.14.5 Extended DTMF detection package

Table 5.14.5.1: Package usage information for extended DTMF detection package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
None	Not applicable	Not applicable		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable

Events	Mandatory/ Optional	Used in command				
DTMF Digits (see note)	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	None	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	None	Not applicable	Not applicable	Not applicable		
Extended Digit Map Completion	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Buffer Control	M	ALL	0		
	Extra Digit Disposition	M	ALL	OFF		
	Match Procedure	M	ALL	base		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	digit string	M	ALL	Not applicable		
	termination method	M	ALL	Not applicable		
	Unmatched Event	M	ALL	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

NOTE: DTMF detection shall conform to ES 201 235-3 [25].

5.14.6 Call progress tones generator package

Table 5.14.6.1: Package usage information for call progress tones generator package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
All	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY		(see note)
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	None	Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
None	Not applicable	Not applicable		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
Statistics	Mandatory/ Optional	Used in command		Supported Values
None	Not applicable	Not applicable		Not applicable
Error Codes	Mandatory/Optional			
None	Not applicable			
<p>NOTE: Levels, cadences and frequencies of signals shall conform to national specifications. In the absence of such specification, the following rules shall be used:</p> <p>Levels, cadences and frequencies of the following signals shall conform to ES 201 970 [3]:</p> <ul style="list-style-type: none"> - Dial Tone. - Ringing Tone (also known as ringback tone). - Busy Tone. - Call Waiting Tone. <p>The characteristics of other signals shall conform to ITU-T Recommendation E.180 [18].</p>				

5.14.7 Basic services tones generator package

Table 5.14.7.1: Package usage information for basic services tones generator package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
None	Not applicable	Not applicable	Not applicable	Not applicable		
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value		
ALL	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY		(see note)		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Tone Direction	O	ALL	ext		
Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					
<p>NOTE: Unless specified otherwise in national specifications, the characteristics of the Message Waiting Tone signal shall be those defined in ES 201 970 [3] for the Special Dial Tone.</p>						

5.14.8 Expanded call progress tones generator package

Table 5.14.8.1: Package usage information for expanded call progress tones generator package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
ALL	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY		(see note)
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Tone Direction	O	ALL	ext

Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					
NOTE: Unless specified otherwise in national specifications, the characteristics of the Special Condition Dial Tone (spec) shall be those of the Special Dial Tone defined in ES 201 970 [3].						

5.14.9 Basic announcement syntax package

Table 5.14.9.1: Package usage information for basic announcement syntax package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
None	Not applicable	Not applicable	Not applicable	Not applicable		
Signals	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
Signal Parameters	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.10 Voice variable syntax package

Table 5.14.10.1: Package usage information for voice variable syntax package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		
None	Not applicable	Not applicable		
Signal Parameters	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable

Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.11 Announcement set syntax package

Table 5.14.11.1: Package usage information for announcement set syntax package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
None	Not applicable	Not applicable	Not applicable	Not applicable		
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value		
None	Not applicable	Not applicable		Not applicable		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.12 General text variable type package

Table 5.14.12.1: Package usage information for general text variable type package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
None	Not applicable	Not applicable		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
None	Not applicable	Not applicable		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable

	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
Statistics	Mandatory/ Optional	Used in command		Supported Values
None	Not applicable	Not applicable		Not applicable
Error Codes		Mandatory/Optional		
None		Not applicable		

5.14.13 Advanced audio server base package

Table 5.14.13.1: Package usage information for advanced audio server base package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
Play	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY>		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Announcement	M	ALL	Not applicable
	Interactions	M	ALL	1
	Interval	M	ALL	None
	Speed	O	ALL	0
	Volume	O	ALL	0
Events	Mandatory/ Optional	Used in command		
Audio Operation Failure	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Return Code	M	ALL	Not applicable
Statistics	Mandatory/ Optional	Used in command		Supported Values
None	Not applicable	Not applicable		Not applicable
Error Codes		Mandatory/Optional		
None		Not applicable		

5.14.14 AAS digit collection package

Table 5.14.14.1: Package usage information for AAS digit collection package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
Play Collect	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Initial Prompt	M	ALL	Not applicable
	Reprompt	M	ALL	Not applicable
	Number of Digits Prompt	M	ALL	Not applicable
	Successful announcement	M	ALL	Not applicable
	Announcement Failure	M	ALL	Not applicable
	Non Interruptible Play	M	ALL	FALSE
	Keep digits	M	ALL	FALSE
	Clear Digits Buffer	M	ALL	FALSE
	Maximum Number of Attempts	M	ALL	1
	Digit Map	M	ALL	Not applicable
	Speed	O	ALL	0
	Volume	M	ALL	0
	Offset	M	ALL	0
	Restart Key	M	ALL	0
	Re-input key	M	ALL	None
	Return Key	M	ALL	None
	Iterations	M	ALL	1
	Interval	M	ALL	None
	End Input Key	M	ALL	None
	Include End Input Key	M	ALL	FALSE
	Voice Information	M	ALL	dtmfonly
	Voice back	M	ALL	novoiceback
	INPA Prompt timer	M	ALL	None
Events	Mandatory/ Optional	Used in command		
Audio Operation Failure	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	None	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Return Code	M	ALL	Not applicable
Play Collect Success	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	None	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Digits Collected	M	ALL	Not applicable (see note)
	Number of attempts	M	ALL	Not applicable
	Amount Played	O	ALL	Not applicable

Statistics	Mandatory/ Optional	Used in command	Supported Values
None	Not applicable	Not applicable	Not applicable
Error Codes	Mandatory/Optional		
None	Not applicable		

NOTE: DTMF detection shall conform to ES 201 235-3 [25].

5.14.15 AAS recording package

Table 5.14.15.1: Package usage information for AAS recording package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
Maximum temporary record file	O	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	None
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
PlayRecord	M	ADD, MODIFY, AUDITVALUE AUDITCAPABILITY>		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Initial Prompt	M	ALL	Not applicable
	No Speech prompt	M	ALL	Not applicable
	Success announcement	M	ALL	Not applicable
	Failure Announcement	M	ALL	Not applicable
	Pre-speech timer	M	ALL	None
	Post Speech Timer	M	ALL	None
	Record Length Timer	M	ALL	None
	Recording Identifier	M	ALL	None
	Speed	O	ALL	0
	Volume	M	ALL	0
	Offset	M	ALL	0
	Restart Key	M	ALL	0
	Re-input key	M	ALL	None
	Return Key	M	ALL	None
Make Persistent	M	ADD, MODIFY, AUDITVALUE AUDITCAPABILITY>	Not applicable	
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Recording Identifier	M	ALL	None
Events	Mandatory/ Optional	Used in command		
Audio Operation Failure	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Return Code	M	ALL	Not applicable
Play Record Success	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	None	Not applicable	Not applicable	Not applicable

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Amount Played	M	ALL	1
	Number of attempts	M	ALL	1
	Recording result	M	ALL	None
	Recording Identity	M	ALL	None
	Recording Duration	M	ALL	None
Statistics	Mandatory/ Optional	Used in command		Supported Values
None	Not applicable	Not applicable		Not applicable
Error Codes		Mandatory/Optional		
None		Not applicable		

5.14.16 AAS segment management package

Table 5.14.16.1: Package usage information for AAS segment management package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
AAS segment control termination name	M	MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
Delete Persistent	M	MODIFY, AUDITCAPABILITY		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Segment Identifier	M	ALL	Not applicable
Override Audio	M	MODIFY, AUDITCAPABILITY		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Target Segment	M	ALL	Not applicable
	Overriding Segment	M	ALL	Not applicable
Restore Audio	M	MODIFY, AUDITCAPABILITY		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Target Segment	M	ALL	Not applicable
Events	Mandatory/ Optional	Used in command		
None	Not applicable		Not applicable	
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
Statistics	Mandatory/ Optional	Used in command	Supported Values	
None	Not applicable	Not applicable		Not applicable
Error Codes		Mandatory/Optional		
None		Not applicable		

5.14.17 Generic announcement package

Table 5.14.17.1: Package usage information for generic announcement package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
None	Not applicable	Not applicable	Not applicable	Not applicable		
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value		
Fixed Announcement Play		M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	Not applicable		
		Signal Parameters	Mandatory/ Optional	Supported Values		
		Announcement Name	M	ALL		
		Announcement Number of Cycles	M	ALL		
		Announcement Variant	M	Any language tag as defined in RFC 3066 [26]		
		Announcement Direction	M	ALL		
Variable Announcement Play	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY		Not applicable		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Announcement Name	M	ALL	Not applicable		
	Announcement Number of Cycles	M	ALL	Not applicable		
Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
	Announcement Variant	M	Any language tag as defined in RFC 3066 [26]	Not applicable		
	Announcement Direction	M	ALL	Not applicable		
	Specific Parameters Interpretation	M	time (ISO 8601 [27]), date (ISO 8601 [27]), digits, integer	Not applicable		
	Specific Parameters	M	ALL	Not applicable		
Events	Mandatory/ Optional	Used in command				
None						
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
Statistics	Mandatory/ Optional	Used in command	Supported Values			
None	Not applicable	Not applicable	Not applicable			
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.18 Intrusion tones generator package

Table 5.14.18.1: Package usage information for intrusion tones generator package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
None	Not applicable	Not applicable	Not applicable	Not applicable		
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value		
ALL	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY		Not applicable		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Tone Direction	O	External	Not applicable		
Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.19 Business tones generation package

Table 5.14.19.1: Package usage information for business tones generation package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
None	Not applicable	Not applicable	Not applicable	Not applicable		
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value		
ALL	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY		Not applicable		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Tone Direction	O	External	Not applicable		
Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.20 Conferencing tones generation package

Table 5.14.20.1: Package usage information for conferencing tones generation package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
None	Not Applicable	Not Applicable	Not Applicable	Not Applicable		
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value		
ALL	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY		Not applicable		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Tone Direction	O	External	Not applicable		
Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.21 Floor control package

Table 5.14.21.1: Package usage information for floor control package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
Activate Floor Controller	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable		
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value		
None	Not applicable	Not applicable		Not applicable		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.22 View package

Table 5.14.22.1: Package usage information for view package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
Being Viewed		M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	Not applicable
		Signal Parameters	Mandatory/ Optional	Supported Values
		Viewed by whom	M	ALL
		Viewer Identity	M	ALL
No Viewer		M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	Not applicable
		Signal Parameters	Mandatory/ Optional	Supported Values
		None		
Events	Mandatory/ Optional	Used in command		
None		Not applicable	Not applicable	
		Event Parameters	Mandatory/ Optional	Supported Values
		Not applicable	Not applicable	Not applicable
		ObservedEvent Parameters	Mandatory/ Optional	Supported Values
		Not applicable	Not applicable	Not applicable
Statistics	Mandatory/ Optional	Used in command		Supported Values
None	Not applicable	Not applicable		Not applicable
Error Codes		Mandatory/Optional		
None		Not applicable		

5.14.23 Volume control package

Table 5.14.23.1: Package usage information for volume control package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
Volume Level	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
None		Not applicable	Not applicable	
		Signal Parameters	Mandatory/ Optional	Duration Provisioned Value
		Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
None		Not applicable	Not applicable	
		Event Parameters	Mandatory/ Optional	Supported Values
		Not applicable	Not applicable	Not applicable
		ObservedEvent Parameters	Mandatory/ Optional	Supported Values
		Not applicable	Not applicable	Not applicable

Statistics	Mandatory/ Optional	Used in command	Supported Values
None	Not applicable	Not applicable	Not applicable
Error Codes	Mandatory/Optional		
None	Not applicable		

5.14.24 Volume detection package

Table 5.14.24.1: Package usage information for volume detection package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
None	Not applicable	Not applicable	Not applicable	Not applicable		
Signals	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable		Not applicable		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Events	Mandatory/ Optional	Used in command				
Volume Activity Detection	M	ADD, MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Volume Threshold	M	ALL	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	None	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command		Supported Values		
None	Not applicable	Not applicable		Not applicable		
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.25 Volume level mixing package

Table 5.14.25.1: Package usage information for volume level mixing package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
Volume Mixing Level	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable
N Speakers Mixing	O	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable
Signals	Mandatory/ Optional	Used in command		
None	Not applicable	Not applicable		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
None	Not applicable	Not applicable		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable

Statistics	Mandatory/ Optional	Used in command	Supported Values
None	Not applicable	Not applicable	Not applicable
Error Codes	Mandatory/Optional		
None	Not applicable		

5.14.26 Mixing volume level control package

Table 5.14.26.1: Package usage information for mixing volume level control package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value		
Mix Participant Number	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable		
Volume Level Input to Mix	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable		
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value		
None	Not applicable	Not applicable		Not applicable		
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Events	Mandatory/ Optional	Used in command				
None	Not applicable	Not applicable				
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value		
	Not applicable	Not applicable	Not applicable	Not applicable		
Statistics	Mandatory/ Optional	Used in command	Supported Values			
None	Not applicable	Not applicable	Not applicable			
Error Codes	Mandatory/Optional					
None	Not applicable					

5.14.27 Inactivity timer package

Table 5.14.27.1: Package usage information for inactivity timer package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
None	Not applicable	Not applicable	Not applicable	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
None	Not applicable	Not applicable		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
Inactivity Timeout	M	MODIFY, NOTIFY, AUDITVALUE, AUDITCAPABILITY		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Maximum Inactivity Time	M	ALL	None
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	None	Not applicable	Not applicable	Not applicable

Statistics	Mandatory/ Optional	Used in command	Supported Values
None	Not applicable	Not applicable	Not applicable
Error Codes	Mandatory/Optional		
None	Not applicable		

5.14.28 MGC information package

Table 5.14.28.1: Package usage information for MGC information package

Properties	Mandatory/ Optional	Used in command	Supported Values	Provisioned Value
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	M	ADD, MODIFY, AUDITVALUE, AUDITCAPABILITY	ALL	Not applicable
Signals	Mandatory/ Optional	Used in command		Duration Provisioned Value
None	Not applicable	Not applicable		Not applicable
	Signal Parameters	Mandatory/ Optional	Supported Values	Duration Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
Events	Mandatory/ Optional	Used in command		
None	Not applicable	Not applicable		
	Event Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	Not applicable	Not applicable	Not applicable	Not applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values	Provisioned Value
	None	Not applicable	Not applicable	Not applicable
Statistics	Mandatory/ Optional	Used in command		Supported Values
None	Not applicable	Not applicable		Not applicable
Error Codes	Mandatory/Optional			
None	Not applicable			

5.15 Mandatory support of SDP and annex C information elements

The v=, o=, s=, m=, c=, t=, a= and b= lines of the SDP (RFC 2327 [19]) syntax shall be supported. All other lines should be ignored if received.

Table 5.15.1: Supported annex C and SDP information elements

Information element	Annex C support	SDP support
Protocol version (v=)	Not Supported	The protocol version (v=) line contains a single field: v= <version> and shall be used in accordance with RFC 2327 [19] (i.e. v=0).
Origin (o=)	Not Supported	The origin line consists of 6 fields: o= <user name> <session ID> <version> <network type> <address type> <address>. The MRFC is not required to supply this line but shall accept it. The MRFP should populate this line as follows or use the value received from the MRFC: <ul style="list-style-type: none"> - <user name> should contain an hyphen. - <session ID> and <version> should contain one or more digits as described in RFC 2327 [19]. - <network type> shall be set to IN. - <address type> shall be set to IP4 or IP6 The Address Type shall be set to "IP4" or "IP6" depending on the addressing scheme used by the network to which the MRFP is connected. - <address> should contain the fully qualified domain name of the MRFP.
Session Name (s=)	Not Supported	The session name (s=) line contains a single field: s= <session-name>. The MRFC is not required to supply a session name but shall accept one. This line may be used to convey correlation information for use in CDRs. The MRFP shall use an hyphen "-" as a session name or the value received from the MRFC.
Connection data (c=)	Not Supported	The connection data line consists of 3 fields: c= <network-type> <address-type> <connection-address> <ul style="list-style-type: none"> - The <network-type> shall be set to "IN". - The <address-type> shall be set to "IP4" or "IP6" depending on the addressing scheme used by the network to which the MRFP is connected. - The <connection-address> sent by the MRFC in the remote descriptor is the address to which the MRFP shall send the media flows. - The <connection-address> sent by the MRFC in local descriptors may be a unicast IPv4 or IPv6 address or it may be wildcarded to allow the MRFP to choose an address.) In the second case, MRFPs shall fill this field with a unicast IP address at which they will receive the media stream. Thus a TTL value shall not be present and a "number of addresses" value shall not be present. The field shall not be filled with a fully-qualified domain name instead of an IP address. <p>When the <connection address> is wildcarded (i.e. choose wildcard) by the MRFC, the MRFP allocates an IP address based on the address type. The addressing space for which this address is taken may depend on the termination ID supplied by the MRFC.</p>
Media announcements (m=)	Not Supported	Media Announcements (m=) lines consist of 3 fields: m= <media> <port> <transport> <format> The <port> field in local descriptors may be provided by the MRFC or wildcarded (i.e. choose wildcard) to allow the MRFP to choose a value for the port on which it wishes to receive the media stream: <ul style="list-style-type: none"> - The <transport> field shall be set to "RTP/AVP". Dynamic payloads shall not be used when a static RTP/AVP payload value is defined in RFC 3551 [20].

Information element	Annex C support	SDP support
Bandwidth (b=)	Not Supported	<p>The Bandwidth (b=) line consists of 2 fields: $b= <\text{modifier}>: <\text{bandwidth-value}>$</p> <p>Bandwidth information shall be supplied by the MRFC if the required bandwidth cannot be immediately derived from the information contained in the m= line. If absent,) the MRFP shall assume a reasonable default bandwidth value for well-known codecs and shall provide this value in the response sent to the MRFC. The Modifier field shall be set to "AS".</p> <p>The Bandwidth Value field shall be set to the maximum bandwidth requirement of the media stream in kbit/s. The bandwidth value shall take into account all headers down to the IP layer, including a 5 % bandwidth for RTCP packets.</p>
Time (t=)	Not Supported	<p>The time (t=) line consists of two fields: $t= <\text{start-time}> <\text{stop-time}>$.</p> <p>This line is ignored by both the MRFC and the MRFP if received in local and remote descriptors.</p> <p>The MRFC is not required to supply a time description but shall accept one.</p> <p>When supplied, this line shall be set to 0 0.</p>
Attributes (a=)	Not Supported	<p>Attributes (a=) lines consist of two fields: $a= <\text{attribute}>: <\text{value}>$</p> <p>One or more of the "a" attribute lines specified below may be included, depending on the payload type. An attribute line not specified below should not be used. Only the following attributes are understood by the MRFP. Other attributes are ignored.</p> <p>$a= rtpmap: <\text{payload type}> <\text{encoding name}>/<\text{clock rate}> [<\text{encoding parameters}>]$ $a= fmtp:<\text{format}> <\text{format specific parameters}>$ $a= ptme: <\text{time}>$</p>

NOTE: How to specify different ptme values for different codecs when the m= line specifies multiple payload formats is outside the scope of TISPAN NGN R1.

5.16 Procedures

Procedures for ephemeral H.248 Terminations (here IP only) are described in clause 6.

6 Procedures

6.1 General procedures

Media Resource Function Processors shall discard packets with RTP payload types (PT) that do not match the Local Descriptor contents.

NOTE: Besides an incorrect RTP PT field might be also other reasons for discarding packets (invalid SSRC field, invalid CRC, etc.).

When sending packets from a termination, Media Resource Function Processors shall use the address and port in the Local Descriptor as a source address and port.

6.2 Use of voice codecs

6.2.1 Comfort noise insertion and silence suppression for voice codecs

If a codec has built-in support for silence suppression and comfort noise insertion, the activation or deactivation of these features shall be indicated using the a= line according to RFC 3551 [20] and RFC 3555 [23].

If the selected codec does not have built in support for silence suppression and comfort noise (CN) insertion, the CN payload code [22] may be included in the media description.

E.g. for ITU-T Recommendation G.711 [14], A-Law:

```
v= 0
c= IN <address type> <connection address>
m = audio <port number> RTP/AVP 8 13
a= ptime: 10
```

If the CN payload is included in the Local Descriptor, the MRFP shall be prepared to receive CN packets during silence periods. This action also corresponds to an implicit enabling of the silence suppression mode in receiving direction.

If the CN payload is included in the Remote Descriptor, the MRFP shall send CN packets during silence periods. This action corresponds to an implicit enabling of the silence suppression mode in sending direction.

Comfort noise generation, voice activity detection and discontinuous transmission algorithms are outside the scope of the present document.

6.2.2 DTMF transmission

When a G.711 codec is used, Media Resource Function Processors shall be able to generate, detect and forward DTMF tones inband.

When other codecs are used, the MRFC should request the use of the procedures defined in RFC 2833 [21] to send and receive DTMF tones.

- If the Local Descriptor sent by the MRFC includes the support for RFC 2833 [21], Media Resource Function Processors (MRFP) shall be prepared to receive and detect DTMF tones in the form of named events.
- If the Remote Descriptor indicates that RFC 2833 [21] is supported, Media Resource Function Processors (MRFP) shall be prepared to relay in the form of named events, any DTMF tone that may be received from other ephemeral terminations.
- Media Gateways supporting CONFERENCING or TRANSCODING shall support transcoding between in-band DTMF and named events defined RFC 2833 [21], based on the contents of the Local and Remote descriptors of the involved terminations.

A Dynamic Payload type shall be used to indicate support of RFC 2833 [21] for DTMF relay.

EXAMPLE:

```
v= 0
c= IN <address type> <connection address>
m= audio <port number> RTP/AVP 18 110
a= ptime: 10
a= rtpmap: 110 telephone-event/8000
a= fmtp: 110 0-15
```

6.2.3 Support of G.711 variants

6.2.3.1 G.711 Encoding law

Media Resource Function Processors conforming to the present document are required to support G.711 A-Law and may also support µ-Law in order to avoid call failure or transcoding in case the remote entity supports µ-Law only. How and where to perform transcoding in IP networks in case both terminals/gateways do not support the same variant is outside the scope of this profile.

6.2.3.2 G.711 silence suppression mode

G.711-over-IP may be operated with or without silence suppression. In case of silence suppression, comfort noise generation shall be based on ITU-T Recommendation G.711 Appendix II [16]. These features may be enabled/disabled on a per session basis, using the procedure described in clause 6.4.

6.2.3.3 G.711 packet loss concealment

G.711-over-IP may be operated with or without error loss concealment. Typically is that decision dependent on the IP packet loss rate conditions. G.711 error loss concealment is based on RTP packet granularity, therefore called as Packet Loss Concealment (PLC). ITU-T Recommendation G.711 Appendix I [15] provides a framework for G.711 PLC mode.

6.3 Procedures for basic user interaction

User Interaction procedures are applied to the ephemeral termination representing the media flow to/from the user involved in the interaction procedure. The ephemeral termination may already be in a context or may have to be created in a new context.

Signals representing tones and announcements are applied to this termination and played towards the exterior of the context. Events representing DTMF digits are detected on this termination.

6.4 Procedures for advanced user interaction

User Interaction procedures are applied to the ephemeral termination representing the media flow to/from the user involved in the interaction procedure. The ephemeral termination may already be in a context or may have to be created in a new context.

Signals representing tones and announcements are applied to this termination and played towards the exterior of the context.

Events representing DTMF digits or recognized speech segments are detected on this termination.

Voice-messaging services are implemented by applying the playrec signal from the AAS Recording package and detecting related event on this termination.

6.5 Procedures for conferencing

Conference services are implemented by creating H.248 contexts with the appropriate number of terminations using native H.248 mixing and transcoding capabilities. Each conference participant is represented by an ephemeral termination.

Floor control procedures are implemented according to the procedures described in H.248.19 [11].

6.6 Procedures for transcoding

The MRFP may be required to perform transcoding in the context of a conference setup or in the context of basic two party calls. This clause describes the procedures for controlling transcoding in case of a two party call. Procedures for controlling transcoding in conferences are described in clause 6.5.

NOTE: Media Transcoding is performed by the MRFP under the control an MRFC. The criteria that trigger the insertion of an MRFC in the SIP signalling path is outside the scope of the present document.

On receipt of a transcoding request for a two-party session between A and B, the MRCF shall request the MRFP to create a context with one ephemeral termination representing the A party (Ta) and one ephemeral termination representing the B party (Tb).

Remote and Local Descriptors shall be populated as follows:

- The Remote Descriptor for termination Ta shall be set according to the SDP Offer initially received from the A party.
- The Remote Descriptor for termination Tb shall be set according to the SDP Answer received from the B party.
- The media format in the Local Descriptor for termination Ta shall be set according to the SDP Offer initially received from the A party. The IP address and port shall be wildcarded.

- The media format in the Local Descriptor for termination Tb shall be set according to the SDP Answer received from the B party. The IP address and port shall be wildcarded.

The value of the Local Descriptor returned by the MRFP for the termination Ta shall be sent as an SDP Answer to the A party (via the S-CSCF/AS).

The value of the Local Descriptor returned by the MRFP for the termination Tb shall be sent as a new SDP Offer to the B party (via the S-CSCF/AS).

The MRFC is responsible for sending the SDP information in SIP messages that are compatible with the state of the SIP dialogue.

History

Document history		
V1.1.1	June 2006	Publication
V1.1.2	March 2007	Membership Approval Procedure MV 20070525: 2007-03-27 to 2007-05-25