

# ETSI TS 101 376-3-12 V1.1.1 (2001-03)

---

*Technical Specification*

**GEO-Mobile Radio Interface Specifications;  
Part 3: Network specifications;  
Sub-part 12: Technical realization of the  
Short Message Service Cell Broadcast (SMSCB);  
GMR-1 03.041**

---



---

**Reference**

DTS/SES-001-03041

---

**Keywords**CB, GMR, GSM, GSO, interface, MES, mobile,  
MSS, radio, satellite, SMS, S-PCN**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:  
editor@etsi.fr

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.  
All rights reserved.

---

# Contents

Intellectual Property Rights .....	4
Foreword .....	6
Introduction .....	7
1 Scope .....	8
2 References .....	8
3 Abbreviations .....	8
4 General description .....	9
5 Network architecture .....	9
6 CBE functionality .....	9
7 CBC functionality .....	9
8 GSC functionality .....	9
9 GTS functionality .....	9
10 MES functionality .....	9
11 Protocols and protocol architecture .....	9
<b>Annex A (informative): Protocols for interconnecting CBC and GSC.....</b>	<b>10</b>
History .....	11

## Intellectual Property Rights

The information pertaining to essential IPRs is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

The attention of ETSI has been drawn to the Intellectual Property Rights (IPRs) listed below which are, or may be, or may become, Essential to the present document. The IPR owner has undertaken to grant irrevocable licences, on fair, reasonable and non-discriminatory terms and conditions under these IPRs pursuant to the ETSI IPR Policy. Further details pertaining to these IPRs can be obtained directly from the IPR owner.

The present IPR information has been submitted to ETSI and pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### IPRs:

Project	Company	Title	Country of Origin	Patent n°	Countries Applicable
TS 101 376 V1.1.1	Digital Voice Systems Inc		US	US 5,226,084	US
TS 101 376 V1.1.1	Digital Voice Systems Inc		US	US 5,715,365	US
TS 101 376 V1.1.1	Digital Voice Systems Inc		US	US 5,826,222	US
TS 101 376 V1.1.1	Digital Voice Systems Inc		US	US 5,754,974	US
TS 101 376 V1.1.1	Digital Voice Systems Inc		US	US 5,701,390	US

IPR Owner: Digital Voice Systems Inc  
One Van de Graaff Drive Burlington,  
MA 01803  
USA

Contact: John C. Hardwick  
Tel.: +1 781 270 1030  
Fax: +1 781 270 0166

Project	Company	Title	Country of Origin	Patent n°	Countries Applicable
TS 101 376 V1.1.1	Ericsson Mobile Communication	Improvements in, or in relation to, equalisers	GB	GB 2 215 567	GB
TS 101 376 V1.1.1	Ericsson Mobile Communication	Power Booster	GB	GB 2 251 768	GB
TS 101 376 V1.1.1	Ericsson Mobile Communication	Receiver Gain	GB	GB 2 233 846	GB
TS 101 376 V1.1.1	Ericsson Mobile Communication	Transmitter Power Control for Radio Telephone System	GB	GB 2 233 517	GB

IPR Owner: Ericsson Mobile Communications (UK) Limited  
The Keytech Centre, Ashwood Way  
Basingstoke  
Hampshire RG23 8BG  
United Kingdom

Contact: John Watson  
Tel.: +44 1256 864 821

Project	Company	Title	Country of Origin	Patent n°	Countries Applicable
TS 101 376 V1.1.1	Hughes Network Systems		US	Pending	US

IPR Owner: Hughes Network Systems  
11717 Exploration Lane  
Germantown, Maryland 20876  
USA

Contact: John T. Whelan  
Tel: +1 301 428 7172  
Fax: +1 301 428 2802

Project	Company	Title	Country of Origin	Patent n°	Countries Applicable
TS 101 376 V1.1.1	Lockheed Martin Global Telecommunic. Inc	2.4-to-3 KBPS Rate Adaptation Apparatus for Use in Narrowband Data and Facsimile Communication Systems	US	US 6,108,348	US
TS 101 376 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Cellular Spacecraft TDMA Communications System with Call Interrupt Coding System for Maximizing Traffic Throughput Cellular Spacecraft TDMA Communications System with Call Interrupt Coding System for Maximizing Traffic Throughput	US	US 5,717,686	US
TS 101 376 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Enhanced Access Burst for Random Access Channels in TDMA Mobile Satellite System	US	US 5,875,182	
TS 101 376 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Spacecraft Cellular Communication System	US	US 5,974,314	US
TS 101 376 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Spacecraft Cellular Communication System	US	US 5,974,315	US
TS 101 376 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Spacecraft Cellular Communication System with Mutual Offset High-argin Forward Control Signals	US	US 6,072,985	US
TS 101 376 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Spacecraft Cellular Communication System with Spot Beam Pairing for Reduced Updates	US	US 6,118,998	US

IPR Owner: Lockheed Martin Global Telecommunications, Inc.  
900 Forge Road  
Norrstown, PA. 19403  
USA

Contact: R.F. Franciose  
Tel.: +1 610 354 2535  
Fax: +1 610 354 7244

---

# Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The contents of the present document are subject to continuing work within TC-SES and may change following formal TC-SES approval. Should TC-SES modify the contents of the present document it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version 1.m.n

where:

- the third digit (n) is incremented when editorial only changes have been incorporated in the specification;
- the second digit (m) is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.

The present document is part 3, sub-part 12 of a multi-part deliverable covering the GEO-Mobile Radio Interface Specifications, as identified below:

Part 1: "General specifications";

Part 2: "Service specifications";

**Part 3: "Network specifications";**

Sub-part 1: "Network Functions; GMR-1 03.001";

Sub-part 2: "Network Architecture; GMR-1 03.002";

Sub-part 3: "Numbering, Addressing and identification; GMR-1 03.003";

Sub-part 4: "Organization of Subscriber Data; GMR-1 03.008";

Sub-part 5: "Technical realization of Supplementary Services; GMR-1 03.011";

Sub-part 6: "Location Registration and Position Identification Procedures; GMR-1 03.012";

Sub-part 7: "Discontinuous Reception (DRX); GMR-1 03.013";

Sub-part 8: "Support of Dual-Tone Multifrequency Signalling (DTMF); GMR-1 03.014";

Sub-part 9: "Security related Network Functions; GMR-1 03.020";

Sub-part 10: "Functions related to Mobile Earth station (MES) in idle mode; GMR-1 03.022";

Sub-part 11: "Technical realization of the Short Message Service (SMS) Point-to-Point (PP); GMR-1 03.040";

**Sub-part 12: "Technical realization of the Short Message Service Cell Broadcast (SMSCB); GMR-1 03.041";**

Sub-part 13: "Technical realization of group 3 facsimile using transparent mode of transmission; GMR-1 03.045";

Sub-part 14: Transmission Planning Aspects of the Speech Service in the GMR-1 system; GMR-1 03.050";

Sub-part 15: "Line Identification supplementary service - Stage 2; GMR-1 03.081";

Sub-part 16: "Call Barring (CB) supplementary services - Stage 2; GMR-1 03.088";

Sub-part 17: "Unstructured Supplementary Service Data (USSD) - Stage 2; GMR-1 03.290";

Sub-part 18: "Terminal-to-Terminal Call (TtT); GMR-1 03.296";

Sub-part 19: "Optimal Routing technical realization; GMR-1 03.297";

Sub-part 20: "Technical realization of High-Penetration Alerting; GMR-1 03.298";

Sub-part 21: "Position Reporting services; Stage 2 Service description; GMR-1 03.299";

Part 4: "Radio interface protocol specifications";

Part 5: "Radio interface physical layer specifications";

Part 6: "Speech coding specifications";

Part 7: "Terminal adaptor specifications".

---

## Introduction

GMR stands for GEO (Geostationary Earth Orbit) Mobile Radio interface, which is used for mobile satellite services (MSS) utilizing geostationary satellite(s). GMR is derived from the terrestrial digital cellular standard GSM and supports access to GSM core networks.

Due to the differences between terrestrial and satellite channels, some modifications to the GSM standard are necessary. Some GSM specifications are directly applicable, whereas others are applicable with modifications. Similarly, some GSM specifications do not apply, while some GMR specifications have no corresponding GSM specification.

Since GMR is derived from GSM, the organization of the GMR specifications closely follows that of GSM. The GMR numbers have been designed to correspond to the GSM numbering system. All GMR specifications are allocated a unique GMR number as follows:

GMR-n xx.zyy

where:

- numbers xx and yy correspond to the GSM numbering scheme.
- xx.2yy (z= 2) is used for GMR specifications that do not correspond to a GSM specification. In this case, only the number xx corresponds to the GSM numbering scheme and the number yy is allocated by GMR.
- N denotes the first (n = 1) or second (n = 2) family of GMR specifications.

A GMR system is defined by the combination of a family of GMR specifications and GSM specifications as follows:

- If a GMR specification exists it takes precedence over the corresponding GSM specification (if any). This precedence rule applies to any references in the corresponding GSM specifications.

NOTE: Any references to GSM specifications within the GMR specifications are not subject to this precedence rule. For example, a GMR specification may contain specific references to the corresponding GSM specification.

- If a GMR specification does not exist, the corresponding GSM specification may or may not apply. The applicability of the GSM specifications is defined in GMR-1 01.201 [2].

---

# 1 Scope

The present document describes the Short Message Service Cell Broadcast (SMSCB) of the GMR-1 Mobile Satellite System. It defines the message formats over the Gateway Station System - Mobile Earth Station (GSS-MES) interface for the Teleservice 23 as specified in GSM 02.03 [5].

The present document is applicable to networks that conform to the GMR-1 specifications, and to mobile earth stations.

The Short Message Service Cell Broadcast (SMSCB) of the GMR-1 system differs from the descriptions in GSM 03.41 [6] in terminology only.

The present document is based on GSM 03.41 [6].

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] GMR-1 01.004 (ETSI TS 101 376-1-1): "GEO-Mobile Radio Interface Specifications; Part 1: General specifications; Sub-part 1: Abbreviations and acronyms; GMR-1 01.004".
- [2] GMR-1 01.201 (ETSI TS 101 376-1-2): "GEO-Mobile Radio Interface Specifications; Part 1: General specifications; Sub-part 2: Introduction to the GMR-1 Family; GMR-1 01.201".
- [3] GMR-1 03.022 (ETSI TS 101 376-3-10): "GEO-Mobile Radio Interface Specifications; Part 3: Network specifications; Sub-part 10: Functions related to Mobile Earth Station (MES) in idle mode; GMR-1 03.022".
- [4] GMR-1 05.002 (ETSI TS 101 376-5-2): "GEO-Mobile Radio Interface Specifications; Part 5: Radio interface physical layer specifications; Sub-part 2: Multiplexing and Multiple Access; Stage 2 Service Description; GMR-1 05.002".
- [5] GSM 02.03 (ETSI ETS 300 502): "European digital cellular telecommunications system (Phase 2); Teleservices supported by a GSM Public Land Mobile Network (PLMN) (GSM 02.03 V4.3.1)".
- [6] GSM 03.41 (ETSI ETS 300 537): "Digital cellular telecommunications system (Phase 2); Technical realization of Short Message Service Cell Broadcast (SMSCB) (GSM 03.41 V4.11.0)".
- [7] GSM 04.12 (ETSI ETS 300 560): "Digital cellular telecommunications system (Phase 2); Short Message Service Cell Broadcast (SMSCB) support on the mobile radio interface (GSM 04.12 V4.6.0)".

---

# 3 Abbreviations

For the purposes of the present document, the abbreviations given in GMR-1 01.004 [1] and the following apply.

MES	Mobile earth station
GMR	GEO-Mobile Radio
GSS	Gateway station system
GSC	Gateway station controller
GTS	Gateway transceiver station

---

## 4 General description

Refer to clause 2 of GSM 03.41 [6].

Handling of Short Message Service Cell Broadcast (SMSCB) should be supported when the MES is in idle mode - normal service state as described in GMR-1 03.022 [3]. The MES shall not support SMSCB reception in any other state or mode.

---

## 5 Network architecture

Refer to clause 3 of GSM 03.41 [6] with the following differences:

The message transfers are defined by GMR-1 specifications as follows:

- message transfer on link 1 is outside the scope of GMR-1 specifications;
- message transfer on link 2 is described in clause 11;
- message transfer on link 3 is outside the scope of GMR-1 Specifications;
- message transfer on link 4 is described in GSM 04.12 [7] and the timing of messages transferred on link 4 is described in GMR-1 05.002 [4].

---

## 6 CBE functionality

Refer to clause 4 of GSM 03.41 [6].

---

## 7 CBC functionality

Refer to clause 5 of GSM 03.41 [6].

---

## 8 GSC functionality

Refer to clause 6 of GSM 03.41 [6] with the following differences:

- references to GSM 08.52 shall be ignored.

---

## 9 GTS functionality

Refer to clause 7 of GSM 03.41 [6].

---

## 10 MES functionality

Refer to clause 8 of GSM 03.41 [6].

---

## 11 Protocols and protocol architecture

Refer to clause 9 of GSM 03.41 [6].

---

## Annex A (informative): Protocols for interconnecting CBC and GSC

Refer to annex B of GSM 03.41 [6].

---

## History

<b>Document history</b>		
V1.1.1	March 2001	Publication