

ETSI TS 101 377-4-12 V1.1.1 (2001-03)

Technical Specification

**GEO-Mobile Radio Interface Specifications;
Part 4: Radio interface protocol specifications;
Sub-part 12: Multiparty Supplementary Services (MPTY);
GMR-2 04.084**



Reference

DTS/SES-002-04084

Keywords

GMR, MSS, MES, satellite, GSO, S-PCN, GSM,
interface, mobile, MPTY, radio, supplementary
service

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	6
Introduction.....	7
1 Scope.....	8
2 References	8
3 Abbreviations	8
4 General.....	9
4.1 Beginning multi party service	9
History	10

Intellectual Property Rights

The information pertaining to essential IPRs is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

The attention of ETSI has been drawn to the Intellectual Property Rights (IPRs) listed below which are, or may be, or may become, Essential to the present document. The IPR owner has undertaken to grant irrevocable licences, on fair, reasonable and non-discriminatory terms and conditions under these IPRs pursuant to the ETSI IPR Policy. Further details pertaining to these IPRs can be obtained directly from the IPR owner.

The present IPR information has been submitted to ETSI and pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

IPRs:

Project	Company	Title	Country of Origin	Patent n°	Countries Applicable
TS 101 377 V1.1.1	Digital Voice Systems Inc		US	US 5,715,365	US
TS 101 377 V1.1.1	Digital Voice Systems Inc		US	US 5,754,974	US
TS 101 377 V1.1.1	Digital Voice Systems Inc		US	US 5,226,084	US
TS 101 377 V1.1.1	Digital Voice Systems Inc		US	US 5,701,390	US
TS 101 377 V1.1.1	Digital Voice Systems Inc		US	US 5,826,222	US

IPR Owner: Digital Voice Systems Inc
One Van de Graaff Drive Burlington,
MA 01803
USA

Contact: John C. Hardwick
Tel.: +1 781 270 1030
Fax: +1 781 270 0166

Project	Company	Title	Country of Origin	Patent n°	Countries Applicable
TS 101 377 V1.1.1	Ericsson Mobile Communication	Improvements in, or in relation to, equalisers	GB	GB 2 215 567	GB
TS 101 377 V1.1.1	Ericsson Mobile Communication	Power Booster	GB	GB 2 251 768	GB
TS 101 377 V1.1.1	Ericsson Mobile Communication	Receiver Gain	GB	GB 2 233 846	GB
TS 101 377 V1.1.1	Ericsson Mobile Communication	Transmitter Power Control for Radio Telephone System	GB	GB 2 233 517	GB

IPR Owner: Ericsson Mobile Communications (UK) Limited
The Keytech Centre, Ashwood Way
Basingstoke
Hampshire RG23 8BG
United Kingdom

Contact: John Watson
Tel.: +44 1256 864 821

Project	Company	Title	Country of Origin	Patent n°	Countries Applicable
TS 101 377 V1.1.1	Hughes Network Systems		US	Pending	US

IPR Owner: Hughes Network Systems
11717 Exploration Lane
Germantown, Maryland 20876
USA

Contact: John T. Whelan
Tel: +1 301 428 7172
Fax: +1 301 428 2802

Project	Company	Title	Country of Origin	Patent n°	Countries Applicable
TS 101 377 V1.1.1	Lockheed Martin Global Telecommunic. Inc	2.4-to-3 KBPS Rate Adaptation Apparatus for Use in Narrowband Data and Facsimile Communication Systems	US	US 6,108,348	US
TS 101 377 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Cellular Spacecraft TDMA Communications System with Call Interrupt Coding System for Maximizing Traffic Throughput Cellular Spacecraft TDMA Communications System with Call Interrupt Coding System for Maximizing Traffic Throughput	US	US 5,717,686	US
TS 101 377 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Enhanced Access Burst for Random Access Channels in TDMA Mobile Satellite System	US	US 5,875,182	
TS 101 377 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Spacecraft Cellular Communication System	US	US 5,974,314	US
TS 101 377 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Spacecraft Cellular Communication System	US	US 5,974,315	US
TS 101 377 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Spacecraft Cellular Communication System with Mutual Offset High-argin Forward Control Signals	US	US 6,072,985	US
TS 101 377 V1.1.1	Lockheed Martin Global Telecommunic. Inc	Spacecraft Cellular Communication System with Spot Beam Pairing for Reduced Updates	US	US 6,118,998	US

IPR Owner: Lockheed Martin Global Telecommunications, Inc.
900 Forge Road
Norrstown, PA. 19403
USA

Contact: R.F. Franciose
Tel.: +1 610 354 2535
Fax: +1 610 354 7244

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The contents of the present document are subject to continuing work within TC-SES and may change following formal TC-SES approval. Should TC-SES modify the contents of the present document it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version 1.m.n

where:

- the third digit (n) is incremented when editorial only changes have been incorporated in the specification;
- the second digit (m) is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.

The present document is part 4, sub-part 12 of a multi-part deliverable covering the GEO-Mobile Radio Interface Specifications, as identified below:

Part 1: "General specifications";

Part 2: "Service specifications";

Part 3: "Network specifications";

Part 4: "Radio interface protocol specifications";

Sub-part 1: "GMR-2 Mobile Earth Station-Network Interface; General Aspects and Principles; GMR-2 04.001";

Sub-part 2: "GMR-2 Mobile Earth Station-Network Interface; Channel Structures and Access capabilities; GMR-2 04.003";

Sub-part 3: "Layer 1 General requirements; GMR-2 04.004";

Sub-part 4: "Data Link Layer General Aspects; GMR-2 04.005";

Sub-part 5: "GMR-2 Mobile Earth Station - Network Interface; Data Link (DL) layer Specifications; GMR-2 04.006";

Sub-part 6: "Mobile Radio Interface Signalling Layer 3; General Aspects; GMR-2 04.007";

Sub-part 7: "Mobile radio interface Layer 3 Specifications; GMR-2 04.008";

Sub-part 8: "Point-to-Point Short Message Services; GMR-2 04.011";

Sub-part 9: "Performance requirements on the mobile radio interface; GMR-2 04.013";

Sub-part 10: "Rate Adaptation on the Mobile Earth Station (MES) - Gateway System Interface; GMR-2 04.021";

Sub-part 11: "Call Waiting (CW) and Call Holding (HOLD) Supplementary Services; GMR-2 04.083";

Sub-part 12: "Multiparty Supplementary Services (MPTY); GMR-2 04.084";

Sub-part 13: "Technical Realisation of the Early Flag Technique; GMR-2 04.201";

Sub-part 14: "Call Barring Supplementary Services; GMR-2 02.088";

Part 5: "Radio interface physical layer specifications";

Part 6: "Speech coding specifications".

Introduction

GMR stands for GEO (Geostationary Earth Orbit) Mobile Radio interface, which is used for mobile satellite services (MSS) utilizing geostationary satellite(s). GMR is derived from the terrestrial digital cellular standard GSM and supports access to GSM core networks.

Due to the differences between terrestrial and satellite channels, some modifications to the GSM standard are necessary. Some GSM specifications are directly applicable, whereas others are applicable with modifications. Similarly, some GSM specifications do not apply, while some GMR specifications have no corresponding GSM specification.

Since GMR is derived from GSM, the organization of the GMR specifications closely follows that of GSM. The GMR numbers have been designed to correspond to the GSM numbering system. All GMR specifications are allocated a unique GMR number as follows:

GMR-n xx.zyy

where :

xx.0yy (z=0) is used for GMR specifications that have a corresponding GSM specification. In this case, the numbers xx and yy correspond to the GSM numbering scheme;

xx.2yy (z=2) is used for GMR specifications that do not correspond to a GSM specification. In this case, only the number xx corresponds to the GSM numbering scheme and the number yy is allocated by GMR;

n denotes the first (n=1) or second (n=2) family of GMR specifications.

A GMR system is defined by the combination of a family of GMR specifications and GSM specifications as follows:

- If a GMR specification exists it takes precedence over the corresponding GSM specification (if any). This precedence rule applies to any references in the corresponding GSM specifications.

NOTE: Any references to GSM specifications within the GMR specifications are not subject to this precedence rule. For example, a GMR specification may contain specific references to the corresponding GSM specification.

- If a GMR specification does not exist the corresponding GSM specification may or may not apply. The applicability of the GSM specifications are defined in GMR-n 01.201.

1 Scope

The present document should be read in conjunction with GSM 04.84 [2] which specifies the stage 3 description of the Multi Party (MPTY) supplementary services.

The original text in GSM 04.84 [2] is fully applicable to the GMR-2 system except for the modified text shown in clause 4 of the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, subsequent revisions do apply.

[1] GMR-2 01.004 (ETSI TS 101 377-1-1): "GEO-Mobile Radio Interface Specifications; Part 1: General specifications; Sub-part 1: Abbreviations and Acronyms; GMR-2 01.004".

[2] GSM 04.84 (ETSI ETS 300 568): "European digital cellular telecommunications system (Phase 2); Multi Party (MPTY) supplementary services; Stage 3 (GSM 04.84 version 4.3.2)".

3 Abbreviations

For the purposes of the present document, all abbreviations are listed in GMR-2 01.004 [1].

4 General

The GMR-2 system shall provide limited support of Multi Party (MPTY) supplementary services when more than one MES is involved in this process. When an MES has established a single-hop MES-to-MES connection with another MES, the network will not support MPTY supplementary services. Hence, GSM 04.84 [2] is fully applicable with the following modification to the text in GSM 04.84 [2] clause 1.1.

4.1 Beginning multi party service

The first line of text in GSM 04.84 [2] clause 1.1 which reads:

"The served mobile subscriber A may initiate an active multi party call from an active call C and a held call B."

is replaced by:

"The served mobile subscriber A may initiate an active multi party call from an active call C and a held call B, *unless however, A and C are both GMR-2 mobile subscribers.*"

History

Document history		
V1.1.1	March 2001	Publication