

ETSI TS 132 414 V6.0.0 (2004-12)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Universal Mobile Telecommunications System (UMTS);
Telecommunication management;
Performance Management (PM)
Integration Reference Point (IRP);
Common Management Information Protocol (CMIP)
Solution Set (SS)
(3GPP TS 32.414 version 6.0.0 Release 6)**



Reference

DTS/TSGS-0532414v600

Keywords

GSM, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2004.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions.....	6
3.2 Abbreviations	6
4 Basic aspects	6
4.1 Architectural aspects	6
4.2 Mapping	6
4.2.1 Mapping of Information Object Classes	7
4.2.2 Mapping of Operations	7
4.2.3 Mapping of Operation Parameters	8
4.2.4 Mapping of Notifications.....	10
4.2.5 Mapping of Notification Parameters.....	10
-- 5 GDMO definitions	12
-- 5.1 Managed Object Classes.....	12
-- 5.1.1 pmIRP.....	12
-- 5.2 Packages	12
-- 5.2.1 pmIRPBasicPackage.....	12
-- 5.2.2 pmIRPOperationsPackage1	13
-- 5.2.3 pmIRPOperationsPackage2	13
-- 5.2.4 pmIRPOperationsPackage3	14
-- 5.2.5 pmIRPNNotificationPackage	14
-- 5.3 Actions.....	15
-- 5.3.1 createMeasurementJob.....	15
-- 5.3.2 stopMeasurementJob	16
-- 5.3.3 listMeasurementJobs.....	16
-- 5.3.4 suspendMeasurementJob	17
-- 5.3.5 resumeMeasurementJob	18
-- 5.3.6 createThresholdMonitor	18
-- 5.3.7 deleteThresholdMonitor	19
-- 5.3.8 listThresholdMonitors.....	20
-- 5.3.9 suspendThresholdMonitor	20
-- 5.3.10 resumeThresholdMonitor.....	21
-- 5.4 Notifications	21
-- 5.4.1 notifyMeasurementJobStatusChanged.....	21
-- 5.4.2 notifyThresholdMonitorStatusChanged.....	22
-- 6 ASN.1 definitions for the PM IRP	23
Annex A (informative): List of assigned Object Identifiers.....	30
Annex B (informative): Change history	32
History	33

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project: Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- TS 32.411: "Performance Management (PM) Integration Reference Point (IRP): Requirements";
- TS 32.412: "Performance Management (PM) Integration Reference Point (IRP): Information Service (IS)";
- TS 32.413: "Performance Management (PM) Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)";
- TS 32.414: "Performance Management (PM) Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".**

This TS-family describes the requirements and information model necessary for the Telecommunication Management (TM); Performance Management (PM) Integration Reference Point (IRP) of 3G systems. The TM principles and TM architecture are specified in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2].

As for the scope and definitions of Performance Management cf. 3GPP TS32.401 [3], 3GPP TS32.411[4].

1 Scope

The present document defines the performance management integration reference point for the CMIP solution set. It provides all the GDMO and ASN.1 definitions necessary to implement the PM IRP Information Service (TS 32.412 [7]) for the CMIP interface. In detail:

- clause 4 contains an introduction to some basic concepts of the CMIP interfaces;
- clause 5 contains the GDMO definitions for the Performance Management over the CMIP interfaces;
- clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is based on 3GPP TS32.412 (v6.1.X).

2 References

The following documents contain provisions, which through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.401: "Telecommunication management; Performance Management (PM); Concept and requirements".
- [4] 3GPP TS 32.411: "Telecommunication management; Performance Management (PM) Integration Reference Point (IRP): Requirements".
- [5] 3GPP TS 32.311: "Telecommunication management; Generic Integration Reference Point (IRP): Requirements".
- [6] 3GPP TS 32.304: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS) ".
- [7] 3GPP TS 32.412: "Telecommunication management; Performance Management (PM) Integration Reference Point (IRP): Information Service (IS)".
- [8] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management: Information Service (IS)".
- [9] 3GPP TS32.314: "Telecommunication management; Generic Integration Reference Point (IRP) management: Common Management Information Protocol (CMIP) SS".
- [10] ITU-T Recommendation [X.710 \(10/97\)](#): "Information technology - Open Systems Interconnection - Common Management Information service".
- [11] ITU-T Recommendations [X.711 \(10/97\)](#): "Information technology - Open Systems Interconnection - Common management information protocol: Specification".

3 Definitions and abbreviations

3.1 Definitions

For the purpose of the present document the terms and definitions given in 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.401 [3], 3GPP TS 32.411 [4] and the following apply:

IRP document version number string (or "IRPVersion"): See 3GPP TS 32.311 [5].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASN.1	Abstract Syntax Notation number 1
CMIP	Common Management Information Protocol
CMIS	Common Management Information Service
CMISE	Common Management Information Service Element
DN	Distinguished Name
EM	Element Manager
GDMO	Guidelines for the Definition of Managed Objects
IOC	Information Object Class
IRP	Integration Reference Point
Itf-N	Interface N (interface between NM and EM/NE)
ITU-T	International Telecommunication Union - Telecommunications
M	Mandatory
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NM	Network Manager
O	Optional
PM	Performance Management

4 Basic aspects

4.1 Architectural aspects

The PM IRP Information Service description is based on Information Object Classes (IOC), relationships among IOC and interfaces (used or implemented by IOC) which include operations and notifications.

In the present document for the CMIP interfaces the IOC are modelled as GDMO "Managed Object Classes" (MOC), defined specifically for performance management, the operations are modelled as GDMO "Actions" of a MOC while the notifications are modelled as GDMO "Notifications" included in the MOC that need to report events to a Manager.

The handling of notifications described in the present document is based on the Notification IRP CMIP Solution Set (3GPP TS 32.304 [6]).

4.2 Mapping

The semantics of the PM IRP is defined in 3GPP TS 32.412 [7]. The definitions of the management information given there are independent of any implementation technology and protocol. This clause maps these protocol-independent definitions onto their equivalences of the CMIP solution set of the PM IRP.

4.2.1 Mapping of Information Object Classes

For the PM IRP CMIP Solution Set the Information Object Classes (IOC) and the Interfaces defined in TS 32.412 [7] are mapped onto Managed Object Classes (MOC) as given in the following table. These MOC include all the Attributes, Actions and Notifications necessary to model performance management as described in TS 32.412 [7].

Table 4.2.1: Mapping of Information Object Classes

IS IOC	CMIP SS MOC
PMIRP	pMIRP

4.2.2 Mapping of Operations

The following table maps the Interface/Operations defined in the IS of the PM IRP onto their equivalents in the CMIP SS. These are qualified as Mandatory (M) or Optional (O).

Table 4.2.2: Mapping of Operations

IS Interface	Qualifier	IS Operation	CMIP SS Equivalent	Qualifier
PMIRPOperations_1	M	createMeasurementJob	CMISE M-ACTION service, action type: createMeasurementJob	M
		stopMeasurementJob	CMISE M-ACTION service, action type: stopMeasurementJob	M
		suspendMeasurementJob	CMISE M-ACTION service, action type: suspendMeasurementJob	O
		resumeMeasurementJob	CMISE M-ACTION service, action type: resumeMeasurementJob	O
		listMeasurementJobs	CMISE M-ACTION service, action type: listMeasurementJob	M
PMIRPOperations_2	O	createThresholdMonitor	CMISE M-ACTION service, action type: createThresholdMonitor	M
		deleteThresholdMonitor	CMISE M-ACTION service, action type: deleteThresholdMonitor	M
		listThresholdMonitors	CMISE M-ACTION service, action type: listThresholdMonitors	M
PMIRPOperations_3	O	suspendThresholdMonitor	CMISE M-ACTION service, action type: suspendThresholdMonitor	M
		resumeThresholdMonitor	CMISE M-ACTION service, action type: resumeThresholdMonitor	M
GenericIRPVersionOperation	M	getIRPVersion	CMISE M-ACTION service, action type: getIRPVersion, see Note	M
GenericIRPProfileOperation	O	getNotificationProfile	CMISE M-ACTION service, action type: getPNotificationProfile, see Note	M
		getOperationProfile	CMISE M-ACTION service, action type: getOperationProfile, see Note	M

NOTE: The Interfaces GenericIRPVersionOperation and GenericIRPProfileOperation are defined in 3GPP TS 32.312 [8] and inherited from TS32.314 [9].

4.2.3 Mapping of Operation Parameters

The following tables in this subclause show the parameters of each operations defined in the IS 3GPP TS 32.412 [8] and their equivalents in this CMIP SS.

The input parameters of the operations are mapped onto "Action information" (cf. GDMO and ASN.1 definitions for more details).

The output parameters of the operations are mapped onto "Action response" (cf. GDMO and ASN.1 definitions for more details).

Table 4.2.3.1: Parameter mapping of the operation *createMeasurementJob*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
iOCName	IN	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): mOCName	M
iOCIInstanceList	IN	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): mOCIInstanceList	M
measurementCategoryList	IN	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): measurementCategoryList	M
granularityPeriod	IN	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): granularityPeriod	M
reportingPeriod	IN	M	M-ACTION parameter 'Action reply' (CreateMeasurementJobInfo): reportingPeriod	M
startTime	IN	O	M-ACTION parameter 'Action reply' (CreateMeasurementJobInfo): startTime	M
stopTime	IN	O	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): stopTime	O
schedule	IN	O	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): schedule	O
jobId	OUT	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): jobId	M
unsupportedList	OUT	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): unsupportedList	M
status	OUT	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): status	M

Table 4.2.3.2: Parameter mapping of the operation *stopMeasurementJob*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
jobId	IN	M	M-ACTION parameter 'Action information' (StopMeasurementJobInfo): jobId	M
status	OUT	M	M-ACTION parameter 'Action information' (StopMeasurementJobInfo): status	M

Table 4.2.3.3: Parameter mapping of the operation *suspendMeasurementJob*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
jobId	IN	M	M-ACTION parameter 'Action information' (SuspendMeasurementJobInfo): jobId	M
status	OUT	M	M-ACTION parameter 'Action information' (SuspendMeasurementJobInfo): status	M

Table 4.2.3.4: Parameter mapping of the operation *resumeMeasurementJob*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
jobId	IN	M	M-ACTION parameter 'Action information' (ResumeMeasurementJobInfo): jobId	M
status	OUT	M	M-ACTION parameter 'Action information' (ResumeMeasurementJobInfo): status	M

Table 4.2.3.5: Parameter mapping of the operation *listMeasurementJobs*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
jobIdList	IN	M	M-ACTION parameter 'Action information' (ListMeasurementJobsInfo): jobIdList	M
jobInfoList	OUT	M	M-ACTION parameter 'Action information' (ListMeasurementJobsInfo): jobInfoList	M
status	OUT	M	M-ACTION parameter 'Action information' (ListMeasurementJobsInfo): status	M

Table 4.2.3.6: Parameter mapping of the operation *createThresholdMonitor*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
iOCName	IN	M	M-ACTION parameter 'Action information' (createThresholdMonitorInfo): mOCName	M
iOCHandleList	IN	M	M-ACTION parameter 'Action information' (createThresholdMonitorInfo): mOCHandleList	M
thresholdInfoList	IN	M	M-ACTION parameter 'Action information' (createThresholdMonitorInfo): thresholdInfoList	O
monitorGranularityPeriod	IN	M	M-ACTION parameter 'Action information' (createThresholdMonitorInfo): monitorGranularityPeriod	M
monitorId	OUT	M	M-ACTION parameter 'Action reply' (createThresholdMonitor): monitorId	M
unsupportedList	OUT	M	M-ACTION parameter 'Action reply' (createThresholdMonitor): unsupportedList	M
status	OUT	M	M-ACTION parameter 'Action reply' (createThresholdMonitor): status	M

Table 4.2.3.7: Parameter mapping of the operation *deleteThresholdMonitor*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
monitorId	IN	M	M-ACTION parameter 'Action information' (deleteThresholdMonitor): monitorId	M
status	OUT	M	M-ACTION parameter 'Action information' (deleteThresholdMonitor): status	M

Table 4.2.3.8: Parameter mapping of the operation *listThresholdMonitors*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
monitorIdList	IN	M	M-ACTION parameter 'Action information' (listThresholdMonitorsInfo): mOCName	M
monitorInfoList	OUT	M	M-ACTION parameter 'Action information' (listThresholdMonitorsInfo): monitorInfoList	M
status	OUT	M	M-ACTION parameter 'Action information' (listThresholdMonitorsInfo): status	M

Table 4.2.3.9: Parameter mapping of the operation *suspendThresholdMonitor*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
monitorId	IN	M	M-ACTION parameter 'Action information' (suspendThresholdMonitorInfo): monitorId	M
status	OUT	M	M-ACTION parameter 'Action information' (suspendThresholdMonitorsInfo): status	M

Table 4.2.3.10: Parameter mapping of the operation *resumeThresholdMonitor*

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
monitorId	IN	M	M-ACTION parameter 'Action information' (resumeThresholdMonitorInfo): monitorId	M
status	OUT	M	M-ACTION parameter 'Action information' (resumeThresholdMonitorsInfo): status	M

4.2.4 Mapping of Notifications

The following table maps the Notifications defined in the Information Service of the PM IRP [7] onto the equivalent Notifications of the CMIP solution set for the PM IRP. The CMIP Notifications are qualified as Mandatory (M) or Optional (O).

Table 4.2.4: Mapping of Notifications

IS Notification	CMIP SS Equivalent	Qualifier
notifyMeasurementJobStatusChanged	notifyMeasurementJobStatusChanged	M
notifyThresholdMonitorStatusChanged	notifyThresholdMonitorStatusChanged	O

4.2.5 Mapping of Notification Parameters

In the CMIP Solution Set notifications emitted by an Agent are reported to the Managers by means of the CMISE "M-EVENT-REPORT" service primitive, which again is implemented by means of the "m-EventReport OPERATION" (see ITU-T Recommendations X.710 [10] and X.711 [11]). The argument of the m-EventReport OPERATION is defined in ITU-T Recommendation X.711 [11] as follows:

```
EventReportArgument ::= SEQUENCE {
    managedObjectClass      ObjectClass,
    managedObjectInstance    ObjectInstance,
    eventTime               [5] IMPLICIT GeneralizedTime OPTIONAL,
    eventType                EventType,
    eventInfo               [8] ANY DEFINED BY eventType OPTIONAL
}
```

where **eventInfo** has to be further specified for each notification by means of specific GDMO/ASN.1 definitions.

For the notifications defined in 3GPP TS 32.412 [8] all parameters are mapped onto their CMIP SS equivalents as shown in the following tables.

Most parameters are mapped to the M-EVENT report parameter 'Event information'. The 'Event information' parameter is described by the ASN.1 definitions given in the present document.

Table 4.2.5.1: Parameter mapping of the notification *notifyMeasurementJobStatusChanged*

IS Parameter	Qualifier	CMIP SS Equivalent
objectClass	M	M-EVENT-REPORT parameter "Managed object class"
objectInstance	M	M-EVENT-REPORT parameter "Managed object instance"
notificationId	M	M-EVENT-REPORT parameter "Event information": notificationIdentifier
eventTime	M	M-EVENT-REPORT parameter "Event time"
notificationType	M	M-EVENT-REPORT parameter "Event type"
systemDN	C	The IS parameter is conditional and not used in the CMIP SS
jobId	M	M-EVENT-REPORT parameter "Event information": (NotifyMeasurementJobStatusChangedInfo): jobId
jobStatus	M	M-EVENT-REPORT parameter "Event information": (NotifyMeasurementJobStatusChangedInfo): jobStatus
reason	O	M-EVENT-REPORT parameter "Event information": (NotifyMeasurementJobStatusChangedInfo): reason

Table 4.2.5.2: Parameter mapping of the notification *notifyThresholdMonitorStatusChanged*

IS Parameter	Qualifier	CMIP SS Equivalent
objectClass	M	M-EVENT-REPORT parameter "Managed object class"
objectInstance	M	M-EVENT-REPORT parameter "Managed object instance"
notificationId	M	M-EVENT-REPORT parameter "Event information": notificationIdentifier
eventTime	M	M-EVENT-REPORT parameter "Event time"
notificationType	M	M-EVENT-REPORT parameter "Event type"
systemDN	C	The IS parameter is conditional and not used in the CMIP SS
monitorId	M	M-EVENT-REPORT parameter "Event information": (NotifyThresholdMonitorStatusChangedInfo): monitorId
monitorStatus	M	M-EVENT-REPORT parameter "Event information": (NotifyThresholdMonitorStatusChangedInfo): monitorStatus
reason	O	M-EVENT-REPORT parameter "Event information": (NotifyThresholdMonitorStatusChangedInfo): reason

-- 5 GDMO definitions

--Please do not remove the '—' in front of the headline numbering, as it is the CMIP code
--for a comment. This way the whole chapter can be put directly into a compiler.

-- 5.1 Managed Object Classes

-- 5.1.1 pmIRP

pmIRP MANAGED OBJECT CLASS

DERIVED FROM

"3GPP TS32.314" : managedGenericIRP;

CHARACTERIZED BY

pmIRPBasicPackage;

CONDITIONAL PACKAGES

pmIRPOperationsPackage1	PRESENT IF "an instance supports it",
pmIRPOperationsPackage2	PRESENT IF "an instance supports it",
pmIRPOperationsPackage3	PRESENT IF "an instance supports it",
pmIRPNotificationPackage	PRESENT IF "pmIRPOperationsPackage2 is supported";

REGISTERED AS {ts32-414ObjectClass 10600};

-- 5.2 Packages

-- 5.2.1 pmIRPBasicPackage

pmIRPBasicPackage PACKAGE

BEHAVIOUR

pmIRPBasicPackageBehaviour;

ACTIONS

createMeasurementJob,
stopMeasurementJob,
listMeasurementJobs;

NOTIFICATIONS

notifyMeasurementJobStatusChanged;

REGISTERED AS {ts32-414Package 10600};

pmIRPBasicPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The MOC pmIRP has been defined to provide information about the status of currently running or suspended or scheduled PM jobs controlled by the Agent to the Manager.

An instance of the 'pmIRP' MOC is identified by the value of the attribute 'pmIRPId'.

The actions 'createMeasurementJob' and 'stopMeasurementJob' is the means for the Manager to trigger the creation/ deletion of measurement jobs in the network elements.

The action 'listMeasurementJobs' returns a list of measurement jobs specified by the input parameters running in network elements managed by the same manager.

The notification 'notifyMeasurementJobStatusChanged' is sent by the Agent to the Manager to inform that an measurement job identified by the 'measurementJobId' has been stopped.";

-- 5.2.2 pmIRPOperationsPackage1**pmIRPOperationsPackage1 PACKAGE****BEHAVIOUR**

pmIRPOperationsPackage1Behaviour;

ACTIONS

suspendMeasurementJob,
resumeMeasurementJob;

NOTIFICATIONS

notifyMeasurementJobStatusChanged;

REGISTERED AS {ts32-414Package 20600};**pmIRPOperationsPackage1Behaviour BEHAVIOUR****DEFINED AS**

"The action 'suspendMeasurementJob' stops the collection of measurement result data done by the measurement job in the network element whilst the MOI of measurementJob still exists. The notification 'notifyFileReady' or 'notifyFilePreparationError' is emitted after the next reporting period is reached.

The action 'resumeMeasurementJob' resumes one or more suspended measurement jobs. The parameter values will be the same as at creation time of the measurement job.";

-- 5.2.3 pmIRPOperationsPackage2**pmIRPOperationsPackage2 PACKAGE****BEHAVIOUR**

pmIRPOperationsPackage2Behaviour;

ACTIONS

createThresholdMonitor,

deleteThresholdMonitor,

listThresholdMonitors;

REGISTERED AS {ts32-414Package 30600};

pmIRPOperationsPackage2Behaviour **BEHAVIOUR**

DEFINED AS

"The action 'createThresholdMonitor' supports IRPManager's request to create a ThresholdMonitor that defines the thresholds for some specific measurementTypes. If the threshold defined is crossed or reached, the related performance alarms will be emitted to subscribed IRPManager(s). The action 'deleteThresholdMonitor' deletes a specific threshold monitor.

The action 'listThresholdMonitors' returns a list of specified or all threshold monitors.";

-- 5.2.4 pmIRPOperationsPackage3

pmIRPOperationsPackage3 **PACKAGE**

BEHAVIOUR

pmIRPOperationsPackage3Behaviour;

ACTIONS

suspendThresholdMonitor,

resumeThresholdMonitor;

REGISTERED AS {ts32-414Package 40600};

pmIRPOperationsPackage3Behaviour **BEHAVIOUR**

DEFINED AS

"If successful the action 'suspendThresholdMonitor' blocks the PMIRP from emitting PM related alarms. The threshold monitor shall still exist. The notification notifyThresholdMonitorStatusChanged is emitted.

The action 'resumeThresholdMonitor' resumes a suspended threshold monitor. Again, the notification notifyThresholdMonitorStatusChanged is emitted.";

-- 5.2.5 pmIRPNotificationPackage

pmIRPNotificationPackage **PACKAGE**

BEHAVIOUR

pmIRPNotificationPackageBehaviour;

NOTIFICATIONS

notifyThresholdMonitorStatusChanged;

REGISTERED AS {ts32-414Package 50600};

pmIRPNotificationPackageBehaviour **BEHAVIOUR**

DEFINED AS

"The PMIRP Agent notifies all subscribed IRPManagers about the status changes of a ThresholdMonitor. The status changes in that case include Suspended=>Active, Active=>Suspended.

NOTE: The notifyThresholdMonitorStatusChanged notification is mandatory if pmIRPOperationsPackage2 is supported.";

-- 5.3 Actions**-- 5.3.1 createMeasurementJob**

createMeasurementJob **ACTION**

BEHAVIOUR

createMeasurementJobBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-414TypeModule.CreateMeasurementJobInfo;

WITH REPLY SYNTAX

TS32-414TypeModule.CreateMeasurementJobReply;

REGISTERED AS {ts32-414Action 10600};

createMeasurementJobBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to create a MeasurementJob through Itf-N.

Once created, the attributes of MeasurementJob (except MeasurementJob.jobStatus) and the related JobMeasurementSchedule and MeasuredAttribute will not be modified during the life-time of the MeasurementJob.

One MeasurementJob can collect the value of one or multiple measurementTypes. When a measurementType is collected by one MeasurementJob for a given instance, another MeasurementJob which wants to collect the same measurementType for the same instance with different or the same jobGranularityPeriod may be rejected. This behaviour shall be consistent for a given implementation by a specific vendor.";

-- 5.3.2 stopMeasurementJob

stopMeasurementJob ACTION

BEHAVIOUR

stopMeasurementJobBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-414TypeModule.StopMeasurementJobInfo;

WITH REPLY SYNTAX

TS32-414TypeModule.StopMeasurementJobReply;

REGISTERED AS {ts32-414Action 20600};

stopMeasurementJobBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to stop a MeasurementJob through Itf-N, after which the MeasurementJob may still be visible over Itf-N. Whether the MeasurementJob is removed from the managed system is vendor specific and out of scope of the present document. The behaviour of the IRPAGent when the job is stopped is vendor specific, i.e. the job can be stopped at the end of the GranularityPeriod or immediately.

After the job has been stopped, the notifyFileReady or notifyFilePreparationError notification shall be emitted immediately or when the next reporting period is reached";

-- 5.3.3 listMeasurementJobs

listMeasurementJobs ACTION

BEHAVIOUR

listMeasurementJobsBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

```
TS32-414TypeModule.ListMeasurementJobsInfo;
```

WITH REPLY SYNTAX

```
TS32-414TypeModule.ListMeasurementJobsReply;
```

REGISTERED AS {ts32-414Action 30600};

listMeasurementJobsBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to list the information of all or a set of specified current MeasurementJobs";

-- 5.3.4 suspendMeasurementJob

suspendMeasurementJob **ACTION**

BEHAVIOUR

```
suspendMeasurementJobBehaviour;
```

MODE

```
CONFIRMED;
```

WITH INFORMATION SYNTAX

```
TS32-414TypeModule.SuspendMeasurementJobInfo;
```

WITH REPLY SYNTAX

```
TS32-414TypeModule.SuspendMeasurementJobReply;
```

REGISTERED AS {ts32-414Action 40600};

suspendMeasurementJobBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to suspend a MeasurementJob through Itf-N. When the MeasurementJob is suspended, the collection of measurement result data by the MeasurementJob stops regardless of its schedule, but the MeasurementJob continues to exists.

The suspend operation is necessary in following situation:

- High work load experienced by managed system.
- The specified measurement data is not needed for a specific period of time.
- Other specific requirement.

After the job has been suspended, the notifyFileReady or notifyFilePreparationError notification shall be emitted immediately or when the next reporting period is reached";

-- 5.3.5 resumeMeasurementJob

resumeMeasurementJob **ACTION**

BEHAVIOUR

resumeMeasurementJobBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-414TypeModule.ResumeMeasurementJobInfo;

WITH REPLY SYNTAX

TS32-414TypeModule.ResumeMeasurementJobReply;

REGISTERED AS {ts32-414Action 50600};

resumeMeasurementJobBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to resume a suspended MeasurementJob. When the MeasurementJob is resumed, it will work according to criteria (e.g. granularity period, startTime, stopTime, schedule) set up by the corresponding createMeasurementJob operation";

-- 5.3.6 createThresholdMonitor

createThresholdMonitor **ACTION**

BEHAVIOUR

createThresholdMonitorBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-414TypeModule.CreateThresholdMonitorInfo;

WITH REPLY SYNTAX

TS32-414TypeModule.CreateThresholdMonitorReply;

REGISTERED AS {ts32-414Action 60600};

createThresholdMonitorBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to create a ThresholdMonitor that defines the thresholds for some specific measurementTypes. If the threshold defined is (a) crossed or (b) reached, the related performance alarms will be emitted to subscribed IRPManager(s).

Two cases are allowed:

- a) Threshold monitoring is accepted only for measurementType(s) that are already under monitoring by an existing MeasurementJob. The IRPManager, when interacting with this kind of PMIRP, must first start a MeasurementJob to monitor the measurementTypes and then invoke this operation for the same measurementTypes.
- b) Threshold monitoring of measurementType(s) is accepted regardless whether they are already under monitoring by existing MeasurementJob(s).";

-- 5.3.7 deleteThresholdMonitor

deleteThresholdMonitor **ACTION**

BEHAVIOUR

deleteThresholdMonitorBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-414TypeModule.DeleteThresholdMonitorInfo;

WITH REPLY SYNTAX

TS32-414TypeModule.DeleteThresholdMonitorReply;

REGISTERED AS {ts32-414Action 70600};

deleteThresholdMonitorBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to delete a specified ThresholdMonitor.

At the time of the removal, all outstanding (a) threshold-crossing or (b) threshold reaching alarms will stay (i.e. the FMIRP Agent's AlarmList will contain an AlarmInformation indicating (a) threshold-crossing or (b) threshold reaching). The IRPManager needs to use other means to remove the AlarmInformation in the FMIRP AlarmList.";

-- 5.3.8 listThresholdMonitors

listThresholdMonitors **ACTION**

BEHAVIOUR

listThresholdMonitorsBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-414TypeModule.ListThresholdMonitorsInfo;

WITH REPLY SYNTAX

TS32-414TypeModule.ListThresholdMonitorsReply;

REGISTERED AS {ts32-414Action 80600};

listThresholdMonitorsBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to list detailed information about all or specified ThresholdMonitors ";

-- 5.3.9 suspendThresholdMonitor

suspendThresholdMonitor **ACTION**

BEHAVIOUR

suspendThresholdMonitorBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-414TypeModule.SuspendThresholdMonitorInfo;

WITH REPLY SYNTAX

TS32-414TypeModule.SuspendThresholdMonitorReply;

REGISTERED AS {ts32-414Action 90600};

suspendThresholdMonitorBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to suspend the ThresholdMonitor. If the operation succeeds, the thresholdMonitorStatus shall be set to *Suspended*. The PMIRP shall not emit performance alarms related to this ThresholdMonitor. The ThresholdMonitor shall continue to exist";

-- 5.3.10 resumeThresholdMonitor

resumeThresholdMonitor **ACTION**

BEHAVIOUR

resumeThresholdMonitorBehaviour;

MODE

CONFIRMED;

WITH INFORMATION SYNTAX

TS32-414TypeModule.ResumeThresholdMonitorInfo;

WITH REPLY SYNTAX

TS32-414TypeModule.ResumeThresholdMonitorReply;

REGISTERED AS {ts32-414Action 100600};

resumeThresholdMonitorBehaviour **BEHAVIOUR**

DEFINED AS

"The behaviour of this action is described in 32.412.

This operation supports an IRPManager's request to resume a suspended ThresholdMonitor.";

-- 5.4 Notifications

-- 5.4.1 notifyMeasurementJobStatusChanged

notifyMeasurementJobStatusChanged **NOTIFICATION**

BEHAVIOUR

notifyMeasurementJobStatusChangedBehaviour;

WITH INFORMATION SYNTAX

TS32-414TypeModule.NotifyMeasurementJobStatusChangedInfo;

REGISTERED AS {ts32-414Notification 10600};

notifyMeasurementJobStatusChangedBehaviour **BEHAVIOUR**

DEFINED AS

"The PMIRP Agent notifies all subscribed IRPManagers about the status changes of a MeasurementJob. The status changes include Suspended=>Scheduled, Active=>Suspended, Scheduled=>Suspended, Suspended=>Active, Scheduled=>Active, Active=>Stopped, Suspended=>Stopped, Scheduled=>Stopped.

The 'Event Information' field contains the following data:

- notificationIdentifier

This ITU-T X.721 standardised parameter, together with MOI (Managed Object Instance), unambiguously identifies this notification.

- reason

This parameter indicates the reason for stopping/suspending/resuming the measurement job (if available).";

-- 5.4.2 notifyThresholdMonitorStatusChanged

notifyThresholdMonitorStatusChanged **NOTIFICATION**

BEHAVIOUR

notifyThresholdMonitorStatusChangedBehaviour;

WITH INFORMATION SYNTAX

TS32-414TypeModule.NotifyThresholdMonitorStatusChangedInfo;

REGISTERED AS {ts32-414Notification 20600};

notifyThresholdMonitorStatusChangedBehaviour **BEHAVIOUR**

DEFINED AS

" The PMIRP Agent notifies all subscribed IRPManagers about the status changes of a ThresholdMonitor. The status changes in that case include Suspended=>Active, Active=>Suspended.

NOTE: The notifyThresholdMonitorStatusChanged notification is mandatory if PMIRPOperations_2 is supported.

The 'Event information' field contains the following data:

- notificationIdentifier

This ITU-T X.721 standardised parameter, together with MOI (Managed Object Instance), unambiguously identifies this notification.

- reason

This parameter specifies the reason why the status of a measurementJob changed.";

-- 6 ASN.1 definitions for the PM IRP

TS32-414TypeModule {itu-t(0) identified-organization(4) etsi(0) mobileDomain(0) umts-Operation-Maintenance(3) ts-32-414(414) informationModel(0) asn1Module(2) version10600(10600)}

DEFINITIONS IMPLICIT TAGS ::=

BEGIN

--EXPORTS everything

IMPORTS

NotificationIdentifier, EventType, EventTime

FROM Attribute-ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 1}

CMISFilter, ObjectInstance, ObjectClass, EventTypeId

FROM CMIP-1 {joint-iso-ccitt ms(9) cmip(1) modules(0) protocol(3)};

baseNodeUMTS OBJECT IDENTIFIER ::= {itu-t (0) identified-organization (4)
 etsi (0) mobileDomain (0)
 umts-Operation-Maintenance (3)}

ts32-414Prefix OBJECT IDENTIFIER ::= {baseNodeUMTS ts-32-414(414)}

ts32-414 OBJECT IDENTIFIER ::= {ts32-414}

ts32-414InfoModel OBJECT IDENTIFIER ::= {ts32-414 informationModel(0)}

ts32-414PmIRPOBJECTCLASS OBJECT IDENTIFIER ::= {ts32-414 managedObjectClass(3)}

ts32-414PmIRPPackage OBJECT IDENTIFIER ::= {ts32-414InfoModel package(4)}

ts32-414PmIRPParameter OBJECT IDENTIFIER ::= {ts32-414InfoModel parameter(5)}

ts32-414PmIRPAttribute OBJECT IDENTIFIER ::= {ts32-414InfoModel attribute(7)}

ts32-414PmIRPAction OBJECT IDENTIFIER ::= {ts32-414InfoModel action(9)}

ts32-414PmIRPNotification OBJECT IDENTIFIER ::= {ts32-414InfoModel notification(10)}

-- Start of 3GPP SA5 own definitions

Counter ::= INTEGER

CreateMeasurementJobInfo ::= SEQUENCE OF JobInfo

CreateMeasurementJobReply ::= SEQUENCE

```
{
    jobId          JobId,
    unsupportedList UnsupportedList,
    status          ErrorCauses
}
```

CreateThresholdMonitorInfo ::= SEQUENCE OF ThresholdMonitorInfo

CreateThresholdMonitorReply ::= SEQUENCE

```
{
    monitorId      MonitorId,
    unsupportedList UnsupportedList,
    status          ErrorCauses
}
```

DeleteThresholdMonitorInfo ::= MonitorId

DeleteThresholdMonitorReply ::= ErrorCauses

ErrorCauses ::= ENUMERATED

```
{
    success          (0), -- operation / notification successfully performed
    partialSuccess    (1),
    unknownJob       (2),
    maxJobReached    (3),
    jobCannotBeStopped (4),
    jobAlreadySuspended (5),
```

```

jobIsNotSuspended          (6),
unknownThresholdMonitor    (9),
thresholdMonitorAlreadySuspended (10),
thresholdMonitorIsNotSuspended (11),
failure                   ( 255) -- operation failed, specific error unknown
}

```

Gauge ::= FLOAT

JobId ::= ObjectInstance

JobInfo ::= SEQUENCE

```

{
mOCName           GraphicString,
mOCInstanceList   SEQUENCE OF ObjectInstance, --MOI to be monitored
measurementCategoryList SEQUENCE OF ObjectClass,
granularityPeriod TimeInterval, -- {5, 15, 30, 45, 60, 720, 1440} minutes
reportingPeriod    TimeInterval, -- must be integer multiple of GranularityPeriod
startTime         GeneralizedTime,
stopTime          GeneralizedTime,
schedule          JobMeasurementSchedule
}
```

JobList ::= SEQUENCE OF JobId

JobListId ::= INTEGER

JobStatus ::= ENUMERATED

```

{
active      (0),
scheduled   (1),
suspended   (2),
stopped     (3)
}
```

ListMeasurementJobsInfo ::= JobList

ListMeasurementJobsReply ::= SEQUENCE

```
{
  jobInfoList    SEQUENCE OF JobInfo,
  status         ErrorCauses
}
```

ListThresholdMonitorInfo ::= SEQUENCE OF MonitorId

ListThresholdMonitorReply ::= SEQUENCE

```
{
  monitorInfoList SEQUENCE OF MonitorInfo,
  status         ErrorCauses
}
```

MonitorId ::= ObjectInstance

MonitorInfo ::= SEQUENCE

```
{
  mOCName          GraphicString,
  mOCIInstanceList SEQUENCE OF ObjectInstance,
  thresholdInfoList ThresholdInfoList,
  monitorGranularityPeriod TimeInterval
}
```

MonitorListId ::= INTEGER

ResumeMeasurementJobInfo ::= JobId

ResumeMeasurementJobReply ::= ErrorCauses

ResumeThresholdMonitorInfo ::= SEQUENCE OF MonitorId

ResumeThresholdMonitorReply ::= ErrorCauses

StartTime ::= GeneralizedTime

StopMeasurementJobInfo ::= SEQUENCE OF JobId

StopMeasurementJobReply ::= ErrorCauses

StopTime ::= GeneralizedTime

SuspendMeasurementJobInfo ::= SEQUENCE OF JobId

SuspendMeasurementJobReply ::= ErrorCauses

SuspendThresholdMonitorInfo ::= SEQUENCE OF MonitorId

SuspendThresholdMonitorReply ::= ErrorCauses

ThresholdInfo ::= SEQUENCE

```
{
measurementTypeName      GraphicString,
probableCause          GraphicString,
specificProblem        GraphicString,
direction              INTEGER,
thresholdPack          ThresholdPack
}
```

ThresholdMonitorInfo ::= SEQUENCE

```
{
mOCName                GraphicString,
mOCIInstanceList        SEQUENCE OF ObjectInstance,
thresholdInfoList       SEQUENCE OF ThresholdInfo,
monitorGranularityPeriod TimeInterval
}
```

ThresholdMonitorStatus ::= ENUMERATED

```
{
active      (0),
suspended   (1)
}
```

ThresholdPack ::= SEQUENCE

```
{
thresholdValue    ThresholdValue,
thresholdSeverity ThresholdSeverity,
hysteresis       INTEGER
}
```

ThresholdSeverity ::= ENUMERATED

```
{
warning      (0),
minor        (1),
major        (2),
critical     (3)
}
```

ThresholdValue ::= ENUMERATED

```
{
gauge      (0),
counter    (1)
}
```

TimeInterval ::= INTEGER**UnsupportedList ::= SEQUENCE**

```
{
mOCName      GraphicString,
mOCInstanceList SEQUENCE OF ObjectInstance,
measurementTypeName GraphicString,
reason        GraphicString
}
```

END -- of module TS32-414TypeModule

Annex A (informative): List of assigned Object Identifiers

This annex provides a list with all object identifiers that have been assigned in TS 32.344. These object identifiers shall not be assigned to new objects (also not in new versions of this document).

Basic Object Name	Name and OID of the current TS Version	Name and OIDs of previous TS Versions
Managed Object Classes		
ftIRP	Name: PMIRP OID : ts32-414ObjectClass 10600	--
Packages		
pmIRPBasicPackage	Name: pMIRPBasicPackage OID : ts32-4144Package 10600	--
pMIRPOperationsPackage1	Name: pMIRPOperationsPackage1 OID : ts32-4144Package 20600	--
pMIRPOperationsPackage2	Name: pMIRPOperationsPackage2 OID : ts32-4144Package 30600	--
pMIRPOperationsPackage3	Name:pMIRPOperationsPackage3 OID: ts32-4144Package 40600	--
pMIRPNotificationPackage	Name: pMIRPNotificationPackage OID : ts32-414Package 50600	--
Actions		
createMeasurementJob	Name:createMeasurementJob OID : ts32-4144Action 10600	--
stopMeasurementJob	Name: stopMeasurementJob OID : ts32-354Action 20600	--
listMeasurementJobs	Name: listMeasurementJob OID : ts32-414Action 30600	--
suspendMeasurementJob	Name: suspendMeasurementJob OID : ts32-414Action 40600	--
resumeMeasurementJob	Name: resumeMeasurementJob OID : ts32-414Action 50600	--
createThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 60600	--
deleteThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 70600	--
listThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 80600	--
suspendThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 90600	--
resumeThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 100600	--
Notifications		
notifyMeasurementJobStatusChanged	Name: notifyMeasurementJobStatusChanged OID : ts32-414Notification 10600	--
notifyThresholdMonitorStatusChanged	Name: notifyThresholdMonitorStatusChanged OID : ts32-4144Notification 20600	--
Attributes		
--	--	--
Parameters		
--	--	--
Name Bindings		

Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Dec 2004	S_26	SP-040785	--	--	Submitted to SA#26 for Approval	1.0.0	6.0.0

History

Document history		
V6.0.0	December 2004	Publication