

# ETSI TS 132 414 V6.1.0 (2005-09)

*Technical Specification*

**Digital cellular telecommunications system (Phase 2+);  
Universal Mobile Telecommunications System (UMTS);  
Telecommunication management;  
Performance Management (PM)  
Integration Reference Point (IRP);  
Common Management Information Protocol (CMIP)  
Solution Set (SS)  
(3GPP TS 32.414 version 6.1.0 Release 6)**



---

Reference

RTS/TSGS-0532414v610

---

Keywords

GSM, UMTS

***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

Individual copies of the present document can be downloaded from:  
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
[http://portal.etsi.org/chaircor/ETSI\\_support.asp](http://portal.etsi.org/chaircor/ETSI_support.asp)

---

***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.  
All rights reserved.

**DECT™, PLUGTESTS™ and UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON™** and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under  
<http://webapp.etsi.org/key/queryform.asp>.

---

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Foreword.....	4
Introduction .....	4
1    Scope .....	5
2    References .....	5
3    Definitions and abbreviations.....	6
3.1    Definitions.....	6
3.2    Abbreviations .....	6
4    Basic aspects .....	6
4.1    Architectural aspects .....	6
4.2    Mapping .....	6
4.2.1    Mapping of Information Object Classes .....	7
4.2.2    Mapping of Operations .....	7
4.2.3    Mapping of Operation Parameters .....	8
4.2.4    Mapping of Notifications.....	10
4.2.5    Mapping of Notification Parameters.....	10
-- 5  GDMO definitions .....	12
-- 5.1  Managed Object Classes.....	12
-- 5.1.1  pmIRP.....	12
-- 5.2  Packages .....	12
-- 5.2.1  pmIRPBasicPackage.....	12
-- 5.2.2  pmIRPOperationsPackage1 .....	12
-- 5.2.3  pmIRPOperationsPackage2 .....	13
-- 5.2.4  pmIRPOperationsPackage3 .....	13
-- 5.2.5  pmIRPNNotificationPackage .....	13
-- 5.2.6  pmIRPObjectCreationDeletionNotificationPackage.....	13
-- 5.3  Actions.....	14
-- 5.3.1  createMeasurementJob.....	14
-- 5.3.2  stopMeasurementJob .....	14
-- 5.3.3  listMeasurementJobs.....	14
-- 5.3.4  suspendMeasurementJob .....	15
-- 5.3.5  resumeMeasurementJob .....	15
-- 5.3.6  createThresholdMonitor .....	15
-- 5.3.7  deleteThresholdMonitor .....	16
-- 5.3.8  listThresholdMonitors.....	16
-- 5.3.9  suspendThresholdMonitor .....	16
-- 5.3.10  resumeThresholdMonitor.....	16
-- 5.4  Notifications .....	17
-- 5.4.1  notifyMeasurementJobStatusChanged.....	17
-- 5.4.2  notifyThresholdMonitorStatusChanged.....	17
-- 5.4.3  notifyThresholdMonitorObjectCreation .....	17
-- 5.4.4  notifyThresholdMonitorObjectDeletion .....	18
-- 6  ASN.1 definitions for the PM IRP .....	19
<b>Annex A (informative):     List of assigned Object Identifiers.....</b>	<b>24</b>
<b>Annex B (informative):     Change history .....</b>	<b>26</b>
History .....	27

---

## Foreword

This Technical Specification (TS) has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project: Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- TS 32.411: "Performance Management (PM) Integration Reference Point (IRP): Requirements";
- TS 32.412: "Performance Management (PM) Integration Reference Point (IRP): Information Service (IS)";
- TS 32.413: "Performance Management (PM) Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)";
- TS 32.414: "Performance Management (PM) Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".**

This TS-family describes the requirements and information model necessary for the Telecommunication Management (TM); Performance Management (PM) Integration Reference Point (IRP) of 3G systems. The TM principles and TM architecture are specified in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2].

As for the scope and definitions of Performance Management cf. 3GPP TS32.401 [3], 3GPP TS32.411[4].

---

## 1 Scope

The present document defines the performance management integration reference point for the CMIP solution set. It provides all the GDMO and ASN.1 definitions necessary to implement the PM IRP Information Service (TS 32.412 [7]) for the CMIP interface. In detail:

- clause 4 contains an introduction to some basic concepts of the CMIP interfaces;
- clause 5 contains the GDMO definitions for the Performance Management over the CMIP interfaces;
- clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is based on 3GPP TS32.412 (v6.4.0).

---

## 2 References

The following documents contain provisions, which through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.401: "Telecommunication management; Performance Management (PM); Concept and requirements".
- [4] 3GPP TS 32.411: "Telecommunication management; Performance Management (PM) Integration Reference Point (IRP): Requirements".
- [5] 3GPP TS 32.311: "Telecommunication management; Generic Integration Reference Point (IRP): Requirements".
- [6] 3GPP TS 32.304: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS) ".
- [7] 3GPP TS 32.412: "Telecommunication management; Performance Management (PM) Integration Reference Point (IRP): Information Service (IS)".
- [8] 3GPP TS 32.312: "Telecommunication management; Generic Integration Reference Point (IRP) management: Information Service (IS)".
- [9] 3GPP TS32.314: "Telecommunication management; Generic Integration Reference Point (IRP) management: Common Management Information Protocol (CMIP) SS".
- [10] ITU-T Recommendation [X.710 \(10/97\)](#): "Information technology - Open Systems Interconnection - Common Management Information service".
- [11] ITU-T Recommendations [X.711 \(10/97\)](#): "Information technology - Open Systems Interconnection - Common management information protocol: Specification".

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purpose of the present document the terms and definitions given in 3GPP TS 32.101 [1], 3GPP TS 32.102 [2], 3GPP TS 32.401 [3], 3GPP TS 32.411 [4] and the following apply:

**IRP document version number string (or "IRPVersion"):** See 3GPP TS 32.311 [5].

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ASN.1	Abstract Syntax Notation number 1
CMIP	Common Management Information Protocol
CMIS	Common Management Information Service
CMISE	Common Management Information Service Element
DN	Distinguished Name
EM	Element Manager
GDMO	Guidelines for the Definition of Managed Objects
IOC	Information Object Class
IRP	Integration Reference Point
Itf-N	Interface N (interface between NM and EM/NE)
ITU-T	International Telecommunication Union - Telecommunications
M	Mandatory
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NM	Network Manager
O	Optional
PM	Performance Management

---

## 4 Basic aspects

### 4.1 Architectural aspects

The PM IRP Information Service description is based on Information Object Classes (IOC), relationships among IOC and interfaces (used or implemented by IOC) which include operations and notifications.

In the present document for the CMIP interfaces the IOC are modelled as GDMO "Managed Object Classes" (MOC), defined specifically for performance management, the operations are modelled as GDMO "Actions" of a MOC while the notifications are modelled as GDMO "Notifications" included in the MOC that need to report events to a Manager.

The handling of notifications described in the present document is based on the Notification IRP CMIP Solution Set (3GPP TS 32.304 [6]).

### 4.2 Mapping

The semantics of the PM IRP is defined in 3GPP TS 32.412 [7]. The definitions of the management information given there are independent of any implementation technology and protocol. This clause maps these protocol-independent definitions onto their equivalences of the CMIP solution set of the PM IRP.

## 4.2.1 Mapping of Information Object Classes

For the PM IRP CMIP Solution Set the Information Object Classes (IOC) and the Interfaces defined in TS 32.412 [7] are mapped onto Managed Object Classes (MOC) as given in the following table. These MOC include all the Attributes, Actions and Notifications necessary to model performance management as described in TS 32.412 [7].

**Table 4.2.1: Mapping of Information Object Classes**

IS IOC	CMIP SS MOC
PMIRP	pMIRP

## 4.2.2 Mapping of Operations

The following table maps the Interface/Operations defined in the IS of the PM IRP onto their equivalents in the CMIP SS. These are qualified as Mandatory (M) or Optional (O).

**Table 4.2.2: Mapping of Operations**

IS Interface	Qualifier	IS Operation	CMIP SS Equivalent	Qualifier
PMIRPOperations_1	M	createMeasurementJob	CMISE M-ACTION service, action type: createMeasurementJob	M
		stopMeasurementJob	CMISE M-ACTION service, action type: stopMeasurementJob	M
		suspendMeasurementJob	CMISE M-ACTION service, action type: suspendMeasurementJob	O
		resumeMeasurementJob	CMISE M-ACTION service, action type: resumeMeasurementJob	O
		listMeasurementJobs	CMISE M-ACTION service, action type: listMeasurementJob	M
PMIRPOperations_2	O	createThresholdMonitor	CMISE M-ACTION service, action type: createThresholdMonitor	M
		deleteThresholdMonitor	CMISE M-ACTION service, action type: deleteThresholdMonitor	M
		listThresholdMonitors	CMISE M-ACTION service, action type: listThresholdMonitors	M
PMIRPOperations_3	O	suspendThresholdMonitor	CMISE M-ACTION service, action type: suspendThresholdMonitor	M
		resumeThresholdMonitor	CMISE M-ACTION service, action type: resumeThresholdMonitor	M
GenericIRPVersionOperation	M	getIRPVersion	CMISE M-ACTION service, action type: getIRPVersion, see Note	M
GenericIRPProfileOperation	O	getNotificationProfile	CMISE M-ACTION service, action type: getPNotificationProfile, see Note	M
		getOperationProfile	CMISE M-ACTION service, action type: getOperationProfile, see Note	M

NOTE: The Interfaces GenericIRPVersionOperation and GenericIRPProfileOperation are defined in 3GPP TS 32.312 [8] and inherited from TS32.314 [9].

### 4.2.3 Mapping of Operation Parameters

The following tables in this subclause show the parameters of each operations defined in the IS 3GPP TS 32.412 [8] and their equivalents in this CMIP SS.

The input parameters of the operations are mapped onto "Action information" (cf. GDMO and ASN.1 definitions for more details).

The output parameters of the operations are mapped onto "Action response" (cf. GDMO and ASN.1 definitions for more details).

**Table 4.2.3.1: Parameter mapping of the operation *createMeasurementJob***

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
iOCName	IN	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): mOCName	M
iOCIInstanceList	IN	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): mOCIInstanceList	M
measurementCategoryList	IN	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): measurementCategoryList	M
granularityPeriod	IN	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): granularityPeriod	M
reportingPeriod	IN	M	M-ACTION parameter 'Action reply' (CreateMeasurementJobInfo): reportingPeriod	M
startTime	IN	O	M-ACTION parameter 'Action reply' (CreateMeasurementJobInfo): startTime	M
stopTime	IN	O	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): stopTime	O
schedule	IN	O	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): schedule	O
jobId	OUT	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): jobId	M
unsupportedList	OUT	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): unsupportedList	M
status	OUT	M	M-ACTION parameter 'Action information' (CreateMeasurementJobInfo): status	M

**Table 4.2.3.2: Parameter mapping of the operation *stopMeasurementJob***

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
jobId	IN	M	M-ACTION parameter 'Action information' (StopMeasurementJobInfo): jobId	M
status	OUT	M	M-ACTION parameter 'Action information' (StopMeasurementJobInfo): status	M

**Table 4.2.3.3: Parameter mapping of the operation *suspendMeasurementJob***

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
jobId	IN	M	M-ACTION parameter 'Action information' (SuspendMeasurementJobInfo): jobId	M
status	OUT	M	M-ACTION parameter 'Action information' (SuspendMeasurementJobInfo): status	M

**Table 4.2.3.4: Parameter mapping of the operation *resumeMeasurementJob***

IS Parameter	IN/OUT	Qualifier	CMIP SS Equivalent	Qualifier
jobId	IN	M	M-ACTION parameter 'Action information' (ResumeMeasurementJobInfo): jobId	M
status	OUT	M	M-ACTION parameter 'Action information' (ResumeMeasurementJobInfo): status	M

**Table 4.2.3.5: Parameter mapping of the operation *listMeasurementJobs***

<b>IS Parameter</b>	<b>IN/OUT</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>	<b>Qualifier</b>
jobIdList	IN	M	M-ACTION parameter 'Action information' (ListMeasurementJobsInfo): jobIdList	M
jobInfoList	OUT	M	M-ACTION parameter 'Action information' (ListMeasurementJobsInfo): jobInfoList	M
status	OUT	M	M-ACTION parameter 'Action information' (ListMeasurementJobsInfo): status	M

**Table 4.2.3.6: Parameter mapping of the operation *createThresholdMonitor***

<b>IS Parameter</b>	<b>IN/OUT</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>	<b>Qualifier</b>
iOCName	IN	M	M-ACTION parameter 'Action information' (createThresholdMonitorInfo): mOCName	M
iOCInstanceList	IN	M	M-ACTION parameter 'Action information' (createThresholdMonitorInfo): mOCInstanceList	M
thresholdInfoList	IN	M	M-ACTION parameter 'Action information' (createThresholdMonitorInfo): thresholdInfoList	O
monitorGranularityPeriod	IN	M	M-ACTION parameter 'Action information' (createThresholdMonitorInfo): monitorGranularityPeriod	M
monitorId	OUT	M	M-ACTION parameter 'Action reply' (createThresholdMonitor): monitorId	M
unsupportedList	OUT	M	M-ACTION parameter 'Action reply' (createThresholdMonitor): unsupportedList	M
status	OUT	M	M-ACTION parameter 'Action reply' (createThresholdMonitor): status	M

**Table 4.2.3.7: Parameter mapping of the operation *deleteThresholdMonitor***

<b>IS Parameter</b>	<b>IN/OUT</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>	<b>Qualifier</b>
monitorId	IN	M	M-ACTION parameter 'Action information' (deleteThresholdMonitor): monitorId	M
status	OUT	M	M-ACTION parameter 'Action information' (deleteThresholdMonitor): status	M

**Table 4.2.3.8: Parameter mapping of the operation *listThresholdMonitors***

<b>IS Parameter</b>	<b>IN/OUT</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>	<b>Qualifier</b>
monitorIdList	IN	M	M-ACTION parameter 'Action information' (listThresholdMonitorsInfo): mOCName	M
monitorInfoList	OUT	M	M-ACTION parameter 'Action information' (listThresholdMonitorsInfo): monitorInfoList	M
status	OUT	M	M-ACTION parameter 'Action information' (listThresholdMonitorsInfo): status	M

**Table 4.2.3.9: Parameter mapping of the operation *suspendThresholdMonitor***

<b>IS Parameter</b>	<b>IN/OUT</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>	<b>Qualifier</b>
monitorId	IN	M	M-ACTION parameter 'Action information' (suspendThresholdMonitorInfo): monitorId	M
status	OUT	M	M-ACTION parameter 'Action information' (suspendThresholdMonitorsInfo): status	M

**Table 4.2.3.10: Parameter mapping of the operation *resumeThresholdMonitor***

<b>IS Parameter</b>	<b>IN/OUT</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>	<b>Qualifier</b>
monitorId	IN	M	M-ACTION parameter 'Action information' (resumeThresholdMonitorInfo): monitorId	M
status	OUT	M	M-ACTION parameter 'Action information' (resumeThresholdMonitorsInfo): status	M

## 4.2.4 Mapping of Notifications

The following table maps the Notifications defined in the Information Service of the PM IRP [7] onto the equivalent Notifications of the CMIP solution set for the PM IRP. The CMIP Notifications are qualified as Mandatory (M) or Optional (O).

**Table 4.2.4: Mapping of Notifications**

<b>IS Notification</b>	<b>CMIP SS Equivalent</b>	<b>Qualifier</b>
notifyMeasurementJobStatusChanged	notifyMeasurementJobStatusChanged	M
notifyThresholdMonitorStatusChanged	notifyThresholdMonitorStatusChanged	O
notifyThresholdMonitorObjectCreation	notifyThresholdMonitorObjectCreation	O
notifyThresholdMonitorObjectDeletion	notifyThresholdMonitorObjectDeletion	O

## 4.2.5 Mapping of Notification Parameters

In the CMIP Solution Set notifications emitted by an Agent are reported to the Managers by means of the CMISE "M-EVENT-REPORT" service primitive, which again is implemented by means of the "m-EventReport OPERATION" (see ITU-T Recommendations X.710 [10] and X.711 [11]). The argument of the m-EventReport OPERATION is defined in ITU-T Recommendation X.711 [11] as follows:

```
EventReportArgument ::= SEQUENCE {
    managedObjectClass          ObjectClass,
    managedObjectInstance        ObjectInstance,
    eventTime                   [5] IMPLICIT GeneralizedTime OPTIONAL,
    eventType                  EventTypeId,
    eventInfo                   [8] ANY DEFINED BY eventType OPTIONAL
}
```

where eventInfo has to be further specified for each notification by means of specific GDMO/ASN.1 definitions.

For the notifications defined in 3GPP TS 32.412 [8] all parameters are mapped onto their CMIP SS equivalents as shown in the following tables.

Most parameters are mapped to the M-EVENT report parameter 'Event information'. The 'Event information' parameter is described by the ASN.1 definitions given in the present document.

**Table 4.2.5.1: Parameter mapping of the notification *notifyMeasurementJobStatusChanged***

<b>IS Parameter</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>
objectClass	M	M-EVENT-REPORT parameter 'Managed object class'
objectInstance	M	M-EVENT-REPORT parameter 'Managed object instance'
notificationId	M	M-EVENT-REPORT parameter 'Event information': NotifyMeasurementJobStatusChangedInfo): notificationIdentifier
eventTime	M	M-EVENT-REPORT parameter 'Event time'
notificationType	M	M-EVENT-REPORT parameter 'Event type'
systemDN	C	The IS parameter is conditional and not used in the CMIP SS
jobId	M	M-EVENT-REPORT parameter 'Event information': (NotifyMeasurementJobStatusChangedInfo): jobId
jobStatus	M	M-EVENT-REPORT parameter 'Event information': (NotifyMeasurementJobStatusChangedInfo): jobStatus
reason	O	M-EVENT-REPORT parameter 'Event information': (NotifyMeasurementJobStatusChangedInfo): reason

**Table 4.2.5.2: Parameter mapping of the notification *notifyThresholdMonitorStatusChanged***

<b>IS Parameter</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>
objectClass	M	M-EVENT-REPORT parameter 'Managed object class'
objectInstance	M	M-EVENT-REPORT parameter 'Managed object instance'
notificationId	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorStatusChangedInfo): notificationIdentifier
eventTime	M	M-EVENT-REPORT parameter 'Event time'
notificationType	M	M-EVENT-REPORT parameter 'Event type'
systemDN	C	The IS parameter is conditional and not used in the CMIP SS
monitorId	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorStatusChangedInfo): monitorId
monitorStatus	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorStatusChangedInfo): monitorStatus
reason	O	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorStatusChangedInfo): reason

**Table 4.2.5.3: Parameter mapping of the notification *notifyThresholdMonitorObjectCreation***

<b>IS Parameter</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>
objectClass	M	M-EVENT-REPORT parameter 'Managed object class'
objectInstance	M	M-EVENT-REPORT parameter 'Managed object instance'
notificationId	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectCreateInfo): notificationIdentifier
eventTime	M	M-EVENT-REPORT parameter 'Event time'
notificationType	M	M-EVENT-REPORT parameter 'Event type'
systemDN	C	The IS parameter is conditional and not used in the CMIP SS
monitorId	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectCreateInfo): monitorId
monitorStatus	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectCreateInfo): monitorStatus
monitorGranularityPeriod	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectCreateInfo): monitorGranularityPeriod
eventType	M	M-EVENT-REPORT parameter 'Event type'
probableCause	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectCreateInfo): probableCause
specificProblem	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectCreateInfo): specificProblem
direction	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectCreateInfo): direction

**Table 4.2.5.4: Parameter mapping of the notification *notifyThresholdMonitorObjectDeletion***

<b>IS Parameter</b>	<b>Qualifier</b>	<b>CMIP SS Equivalent</b>
objectClass	M	M-EVENT-REPORT parameter 'Managed object class'
objectInstance	M	M-EVENT-REPORT parameter 'Managed object instance'
notificationId	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectDeletionInfo): notificationIdentifier
eventTime	M	M-EVENT-REPORT parameter 'Event time'
notificationType	M	M-EVENT-REPORT parameter 'Event type'
systemDN	C	The IS parameter is conditional and not used in the CMIP SS
monitorId	M	M-EVENT-REPORT parameter 'Event information': (NotifyThresholdMonitorObjectDeletionInfo): monitorId

---

## -- 5 GDMO definitions

--Please do not remove the "--" in front of the headline numbering, as it is the CMIP code --for a comment. This way the whole chapter can be put directly into a compiler.

### -- 5.1 Managed Object Classes

#### -- 5.1.1 pmIRP

```
pmIRP MANAGED OBJECT CLASS
  DERIVED FROM
    "3GPP TS32.314" : managedGenericIRP;
  CHARACTERIZED BY
    pmIRPBasicPackage;
  CONDITIONAL PACKAGES
    pmIRPOperationsPackage1      PRESENT IF "an instance supports it",
    pmIRPOperationsPackage2      PRESENT IF "an instance supports it",
    pmIRPOperationsPackage3      PRESENT IF "an instance supports it",
    pmIRPNotificationPackage    PRESENT IF "pmIRPOperationsPackage2 is supported",
    pmIRPObjectCreationDeletionNotificationPackage  PRESENT IF "pmIRPOperationsPackage2 is supported";
REGISTERED AS {ts32-414ObjectClass 10610};
```

### -- 5.2 Packages

#### -- 5.2.1 pmIRPBasicPackage

```
pmIRPBasicPackage PACKAGE
  BEHAVIOUR
    pmIRPBasicPackageBehaviour;
  ACTIONS
    createMeasurementJob,
    stopMeasurementJob,
    listMeasurementJobs;
  NOTIFICATIONS
    notifyMeasurementJobStatusChanged;
REGISTERED AS {ts32-414Package 10600};

pmIRPBasicPackageBehaviour BEHAVIOUR
DEFINED AS
"The MOC pmIRP has been defined to provide information about the status of currently running or suspended or scheduled PM jobs controlled by the Agent to the Manager.
An instance of the 'pmIRP' MOC is identified by the value of the attribute 'pmIRPId'.
The actions 'createMeasurementJob' and 'stopMeasurementJob' is the means for the Manager to trigger the creation/ deletion of measurement jobs in the network elements.
The action 'listMeasurementJobs' returns a list of measurement jobs specified by the input parameters running in network elements managed by the same manager.
The notification 'notifyMeasurementJobStatusChanged' is sent by the Agent to the Manager to inform that an measurement job identified by the 'measurementJobId' has been stopped.";
```

#### -- 5.2.2 pmIRPOperationsPackage1

```
pmIRPOperationsPackage1 PACKAGE
  BEHAVIOUR
    pmIRPOperationsPackage1Behaviour;
  ACTIONS
    suspendMeasurementJob,
    resumeMeasurementJob;
  NOTIFICATIONS
    notifyMeasurementJobStatusChanged;
REGISTERED AS {ts32-414Package 20600};

pmIRPOperationsPackage1Behaviour BEHAVIOUR
DEFINED AS
"The action 'suspendMeasurementJob' stops the collection of measurement result data done by the measurement job in the network element whilst the MOI of measurementJob still exists. The notification 'notifyFileReady' or 'notifyFilePreparationError' is emitted after the next reporting period is reached.
The action 'resumeMeasurementJob' resumes one or more suspended measurement jobs. The parameter
```

values will be the same as at creation time of the measurement job.";

### -- 5.2.3 pmIRPOperationsPackage2

```
pmIRPOperationsPackage2 PACKAGE
  BEHAVIOUR
    pmIRPOperationsPackage2Behaviour;
  ACTIONS
    createThresholdMonitor,
    deleteThresholdMonitor,
    listThresholdMonitors;
REGISTERED AS {ts32-414Package 30600};

pmIRPOperationsPackage2Behaviour BEHAVIOUR
DEFINED AS
  "The action 'createThresholdMonitor' supports IRPManager's request to create a ThresholdMonitor that defines the thresholds for some specific measurementTypes. If the threshold defined is crossed or reached, the related performance alarms will be emitted to subscribed IRPManager(s). The action 'deleteThresholdMonitor' deletes a specific threshold monitor. The action 'listThresholdMonitors' returns a list of specified or all threshold monitors.";
```

### -- 5.2.4 pmIRPOperationsPackage3

```
pmIRPOperationsPackage3 PACKAGE
  BEHAVIOUR
    pmIRPOperationsPackage3Behaviour;
  ACTIONS
    suspendThresholdMonitor,
    resumeThresholdMonitor;
REGISTERED AS {ts32-414Package 40600};

pmIRPOperationsPackage3Behaviour BEHAVIOUR
DEFINED AS
  "If successful the action 'suspendThresholdMonitor' blocks the PMIRP from emitting PM related alarms. The threshold monitor shall still exist. The notification notifyThresholdMonitorStatusChanged is emitted.
  The action 'resumeThresholdMonitor' resumes a suspended threshold monitor. Again, the notification notifyThresholdMonitorStatusChanged is emitted.";
```

### -- 5.2.5 pmIRPNotificationPackage

```
pmIRPNotificationPackage PACKAGE
  BEHAVIOUR
    pmIRPNotificationPackageBehaviour;
  NOTIFICATIONS
    notifyThresholdMonitorStatusChanged;
REGISTERED AS {ts32-414Package 50600};

pmIRPNotificationPackageBehaviour BEHAVIOUR
DEFINED AS
  "The PMIRP Agent notifies all subscribed IRPManagers about the status changes of a ThresholdMonitor. The status changes in that case include Suspended=>Active, Active=>Suspended.
  NOTE: The notifyThresholdMonitorStatusChanged notification is mandatory if pmIRPOperationsPackage2 is supported.";
```

### --5.2.6 pmIRPObjectCreationDeletionNotificationPackage

```
pmIRPObjectCreationDeletionNotificationPackage PACKAGE
  BEHAVIOUR
    pmIRPObjectCreationDeletionNotificationPackageBehaviour;
  NOTIFICATIONS
    notifyThresholdMonitorObjectCreation,
    notifyThresholdMonitorObjectDeletion;
REGISTERED AS {ts32-414Package 60610};

pmIRPObjectCreationDeletionNotificationPackageBehaviour BEHAVIOUR
DEFINED AS
  "The PMIRP Agent notifies all subscribed IRPManagers about the creation/ deletion of a ThresholdMonitor.";
```

## -- 5.3 Actions

### -- 5.3.1 createMeasurementJob

```
createMeasurementJob ACTION
  BEHAVIOUR
    createMeasurementJobBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.CreateMeasurementJobInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.CreateMeasurementJobReply;
REGISTERED AS {ts32-414Action 10600};

createMeasurementJobBehaviour BEHAVIOUR
DEFINED AS
"The behaviour of this action is described in 32.412.
This operation supports an IRPManager's request to create a MeasurementJob through Itf-N.
Once created, the attributes of MeasurementJob (except MeasurementJob.jobStatus) and the related JobMeasurementSchedule and MeasuredAttribute will not be modified during the life-time of the MeasurementJob.
One MeasurementJob can collect the value of one or multiple measurementTypes. When a measurementType is collected by one MeasurementJob for a given instance, another MeasurementJob which wants to collect the same measurementType for the same instance with different or the same jobGranularityPeriod may be rejected. This behaviour shall be consistent for a given implementation by a specific vendor.";
```

### -- 5.3.2 stopMeasurementJob

```
stopMeasurementJob ACTION
  BEHAVIOUR
    stopMeasurementJobBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.StopMeasurementJobInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.StopMeasurementJobReply;
REGISTERED AS {ts32-414Action 20600};

stopMeasurementJobBehaviour BEHAVIOUR
DEFINED AS
"The behaviour of this action is described in 32.412.
This operation supports an IRPManager's request to stop a MeasurementJob through Itf-N, after which the MeasurementJob may still be visible over Itf-N. Whether the MeasurementJob is removed from the managed system is vendor specific and out of scope of the present document.
The behaviour of the IRPAgent when the job is stopped is vendor specific, i.e. the job can be stopped at the end of the GranularityPeriod or immediately.
After the job has been stopped, the notifyFileReady or notifyFilePreparationError notification shall be emitted immediately or when the next reporting period is reached";
```

### -- 5.3.3 listMeasurementJobs

```
listMeasurementJobs ACTION
  BEHAVIOUR
    listMeasurementJobsBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.ListMeasurementJobsInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.ListMeasurementJobsReply;
REGISTERED AS {ts32-414Action 30600};

listMeasurementJobsBehaviour BEHAVIOUR
DEFINED AS
"The behaviour of this action is described in 32.412.
This operation supports an IRPManager's request to list the information of all or a set of specified current MeasurementJobs";
```

### -- 5.3.4 suspendMeasurementJob

```

suspendMeasurementJob ACTION
  BEHAVIOUR
    suspendMeasurementJobBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.SuspendMeasurementJobInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.SuspendMeasurementJobReply;
REGISTERED AS {ts32-414Action 40600};

suspendMeasurementJobBehaviour BEHAVIOUR
DEFINED AS
  "The behaviour of this action is described in 32.412.
  This operation supports an IRPManager's request to suspend a MeasurementJob through Itf-N. When
  the MeasurementJob is suspended, the collection of measurement result data by the
  MeasurementJob stops regardless of its schedule, but the MeasurementJob continues to exists.
  The suspend operation is necessary in following situation:
  - High work load experienced by managed system.
  - The specified measurement data is not needed for a specific period of time.
  - Other specific requirement.
  After the job has been suspended, the notifyFileReady or notifyFilePreparationError
  notification shall be emitted immediately or when the next reporting period is reached";

```

### -- 5.3.5 resumeMeasurementJob

```

resumeMeasurementJob ACTION
  BEHAVIOUR
    resumeMeasurementJobBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.ResumeMeasurementJobInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.ResumeMeasurementJobReply;
REGISTERED AS {ts32-414Action 50600};

resumeMeasurementJobBehaviour BEHAVIOUR
DEFINED AS
  "The behaviour of this action is described in 32.412.
  This operation supports an IRPManager's request to resume a suspended MeasurementJob. When the
  MeasurementJob is resumed, it will work according to criteria (e.g. granularity period,
  startTime, stopTime, schedule) set up by the corresponding createMeasurementJob operation";

```

### -- 5.3.6 createThresholdMonitor

```

createThresholdMonitor ACTION
  BEHAVIOUR
    createThresholdMonitorBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.CreateThresholdMonitorInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.CreateThresholdMonitorReply;
REGISTERED AS {ts32-414Action 60600};

createThresholdMonitorBehaviour BEHAVIOUR
DEFINED AS
  "The behaviour of this action is described in 32.412.
  This operation supports an IRPManager's request to create a ThresholdMonitor that defines the
  thresholds for some specific measurementTypes. If the threshold defined is (a) crossed or (b)
  reached, the related performance alarms will be emitted to subscribed IRPManager(s).
  Two cases are allowed:
  a) Threshold monitoring is accepted only for measurementType(s) that are already under
  monitoring by an existing MeasurementJob. The IRPManager, when interacting with this
  kind of PMIRP, must first start a MeasurementJob to monitor the measurementTypes and
  then invoke this operation for the same measurementTypes.
  b) Threshold monitoring of measurementType(s) is accepted regardless whether they are
  already under monitoring by existing MeasurementJob(s).";

```

### -- 5.3.7 deleteThresholdMonitor

```

deleteThresholdMonitor ACTION
  BEHAVIOUR
    deleteThresholdMonitorBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.DeleteThresholdMonitorInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.DeleteThresholdMonitorReply;
REGISTERED AS {ts32-414Action 70600};

deleteThresholdMonitorBehaviour BEHAVIOUR
DEFINED AS
  "The behaviour of this action is described in 32.412.
  This operation supports an IRPManager's request to delete a specified ThresholdMonitor.
  At the time of the removal, all outstanding (a) threshold-crossing or (b) threshold reaching
  alarms will stay (i.e. the FMIRP Agent's AlarmList will contain an AlarmInformation indicating
  (a) threshold-crossing or (b) threshold reaching). The IRPManager needs to use other means to
  remove the AlarmInformation in the FMIRP AlarmList.";
```

### -- 5.3.8 listThresholdMonitors

```

listThresholdMonitors ACTION
  BEHAVIOUR
    listThresholdMonitorsBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.ListThresholdMonitorsInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.ListThresholdMonitorsReply;
REGISTERED AS {ts32-414Action 80600};

listThresholdMonitorsBehaviour BEHAVIOUR
DEFINED AS
  "The behaviour of this action is described in 32.412.
  This operation supports an IRPManager's request to list detailed information about all or
  specified ThresholdMonitors ";
```

### -- 5.3.9 suspendThresholdMonitor

```

suspendThresholdMonitor ACTION
  BEHAVIOUR
    suspendThresholdMonitorBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.SuspendThresholdMonitorInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.SuspendThresholdMonitorReply;
REGISTERED AS {ts32-414Action 90600};

suspendThresholdMonitorBehaviour BEHAVIOUR
DEFINED AS
  "The behaviour of this action is described in 32.412.
  This operation supports an IRPManager's request to suspend the ThresholdMonitor. If the
  operation succeeds, the thresholdMonitorStatus shall be set to Suspended. The PMIRP shall not
  emit performance alarms related to this ThresholdMonitor. The ThresholdMonitor shall continue
  to exist";
```

### -- 5.3.10 resumeThresholdMonitor

```

resumeThresholdMonitor ACTION
  BEHAVIOUR
    resumeThresholdMonitorBehaviour;
  MODE
    CONFIRMED;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.ResumeThresholdMonitorInfo;
  WITH REPLY SYNTAX
    TS32-414TypeModule.ResumeThresholdMonitorReply;
```

```

REGISTERED AS {ts32-414Action 100600};

resumeThresholdMonitorBehaviour BEHAVIOUR
DEFINED AS
"The behaviour of this action is described in 32.412.
This operation supports an IRPManager's request to resume a suspended ThresholdMonitor.";
```

## -- 5.4 Notifications

### -- 5.4.1 notifyMeasurementJobStatusChanged

```

notifyMeasurementJobStatusChanged NOTIFICATION
BEHAVIOUR
    notifyMeasurementJobStatusChangedBehaviour;
WITH INFORMATION SYNTAX
    TS32-414TypeModule.NotifyMeasurementJobStatusChangedInfo;
REGISTERED AS {ts32-414Notification 10600};

notifyMeasurementJobStatusChangedBehaviour BEHAVIOUR
DEFINED AS
"The PMIRP Agent notifies all subscribed IRPManagers about the status changes of a
MeasurementJob. The status changes include Suspended=>Scheduled, Active=>Suspended,
Scheduled=>Suspended, Suspended=>Active, Scheduled=>Active, Active=>Stopped,
Suspended=>Stopped, Scheduled=>Stopped.

The 'Event Information' field contains the following data:
- notificationIdentifier
    This ITU-T X.721 standardised parameter, together with MOI (Managed Object Instance),
    unambiguously identifies this notification.
- reason
    This parameter indicates the reason for stopping/suspending/resuming the
    measurement job (if available).";
```

### -- 5.4.2 notifyThresholdMonitorStatusChanged

```

notifyThresholdMonitorStatusChanged NOTIFICATION
BEHAVIOUR
    notifyThresholdMonitorStatusChangedBehaviour;
WITH INFORMATION SYNTAX
    TS32-414TypeModule.NotifyThresholdMonitorStatusChangedInfo;
REGISTERED AS {ts32-414Notification 20600};

notifyThresholdMonitorStatusChangedBehaviour BEHAVIOUR
DEFINED AS
"The PMIRP Agent notifies all subscribed IRPManagers about the status changes of a
ThresholdMonitor. The status changes in that case include Suspended=>Active,
Active=>Suspended.

NOTE: The notifyThresholdMonitorStatusChanged notification is mandatory if
PMIRPOperations_2 is supported.

The 'Event information' field contains the following data:
- notificationIdentifier
    This ITU-T X.721 standardised parameter, together with MOI (Managed Object Instance),
    unambiguously identifies this notification.
- reason
    This parameter specifies the reason why the status of a measurementJob changed.";
```

### -- 5.4.3 notifyThresholdMonitorObjectCreation

```

notifyThresholdMonitorObjectCreation NOTIFICATION
BEHAVIOUR
    notifyThresholdMonitorObjectCreationBehaviour;
WITH INFORMATION SYNTAX
    TS32-414TypeModule.NotifyThresholdMonitorObjectCreationInfo;
REGISTERED AS {ts32-414Notification 30610};

notifyThresholdMonitorObjectCreationBehaviour BEHAVIOUR
DEFINED AS
"The PMIRP Agent notifies all subscribed IRPManagers about the creation of a
ThresholdMonitor instance.";
```

#### -- 5.4.4 notifyThresholdMonitorObjectDeletion

```
notifyThresholdMonitorObjectDeletion NOTIFICATION
  BEHAVIOUR
    notifyThresholdMonitorObjectDeletionBehaviour;
  WITH INFORMATION SYNTAX
    TS32-414TypeModule.NotifyThresholdMonitorObjectDeletionInfo;
REGISTERED AS {ts32-414Notification 40610};

notifyThresholdMonitorObjectDeletionBehaviour BEHAVIOUR
DEFINED AS
  " The PMIRP Agent notifies all subscribed IRPManagers about the deletion of a
  ThresholdMonitor instance. ";
```

---

## -- 6 ASN.1 definitions for the PM IRP

```

TS32-414TypeModule {itu-t(0) identified-organization(4) etsi(0) mobileDomain(0) umts-Operation-
Maintenance(3) ts-32-414(414) informationModel(0) asn1Module(2) version10600(10600)}

DEFINITIONS IMPLICIT TAGS ::=

BEGIN

--EXPORTS everything

IMPORTS

NotificationIdentifier, EventType, EventTime
    FROM Attribute-ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 1}

CMISFilter, ObjectInstance, ObjectClass, EventTypeID
    FROM CMIP-1 {joint-iso-ccitt ms(9) cmip(1) modules(0) protocol(3)};

baseNodeUMTS          OBJECT IDENTIFIER ::= {itu-t (0) identified-organization (4)
                                              etsi (0) mobileDomain (0)
                                              umts-Operation-Maintenance (3)}

ts32-414Prefix        OBJECT IDENTIFIER ::= {baseNodeUMTS ts-32-414(414)}
ts32-414               OBJECT IDENTIFIER ::= {ts32-414}
ts32-414InfoModel      OBJECT IDENTIFIER ::= {ts32-414 informationModel(0)}

ts32-414ObjectClass   OBJECT IDENTIFIER ::= {ts32-414 managedObjectClass(3)}
ts32-414Package        OBJECT IDENTIFIER ::= {ts32-414InfoModel package(4)}
ts32-414Parameter      OBJECT IDENTIFIER ::= {ts32-414InfoModel parameter(5)}
ts32-414Attribute       OBJECT IDENTIFIER ::= {ts32-414InfoModel attribute(7)}
ts32-414Action          OBJECT IDENTIFIER ::= {ts32-414InfoModel action(9)}
ts32-414Notification    OBJECT IDENTIFIER ::= {ts32-414InfoModel notification(10)}

-- Start of 3GPP SA5 own definitions

Counter ::= INTEGER

CreateMeasurementJobInfo ::= SEQUENCE OF JobInfo

CreateMeasurementJobReply ::= SEQUENCE
{
    jobId           JobId,
    unsupportedList UnsupportedList,
    status          ErrorCauses
}

CreateThresholdMonitorInfo ::= SEQUENCE OF ThresholdMonitorInfo

CreateThresholdMonitorReply ::= SEQUENCE
{
    monitorId       MonitorId,
    unsupportedList UnsupportedList,
    status          ErrorCauses
}

DailyOrWeekly ::= ENUMERATED
{
    daily          (0),
    weekly         (1),
    notScheduled  (2)
}

DaysOfTheWeek ::= BITSTRING
{
    sunday        (0),
    monday        (1),
    tuesday       (2),
    wednesday     (3),
    thursday      (4),
    friday        (5),
    saturday      (6)
} (SIZE (0..7)

```

```

DeleteThresholdMonitorInfo ::= MonitorId

DeleteThresholdMonitorReply ::= ErrorCauses

ErrorCauses ::= ENUMERATED
{
  success                               (0), -- operation / notification successfully performed
  partialSuccess                         (1),

  -- from createMeasurementJob (3GPP TS32.412 [7])
  invalidStartTime                      (2),
  invalidStopTime                       (3),
  invalidSchedule                        (4),
  invalidGranularityPeriod              (5),
  invalidReportingPeriod                (6),
  highWorkLoad                           (7),
  invalidPriority                        (8),

  --from stopMeasurementJob (3GPP TS32.412 [7])
  jobCannotBeStopped                   (9),
  unknownJob                            (10),

  --from suspendMeasurementJob (3GPP TS32.412 [7])
  jobAlreadySuspended                  (11),

  --from resumeMeasurementJob (3GPP TS32.412 [7])
  jobIsNotSuspended                    (12),
  hysteresisIsOverlapped               (13),
  invalidClassOrInstances              (14),
  invalidGranularityPeriod             (15),
  noValidMeasurementType               (16),
  invalidNumberOfThresholdPackElements (17),
  invalidOrderOfThresholdPackElements (18),
  invalidDirection                      (19),

  --from suspendThresholdMonitor (3GPP TS32.412 [7])
  unknownThresholdMonitor              (20),
  thresholdMonitorAlreadySuspended    (21),

  --from resumeThresholdMonitor (3GPP TS32.412 [7])
  thresholdMonitorIsNotSuspended       (22),

  --from notifyMeasurementJobStatusChanged (3GPP TS32.412 [7])
  failToReadMeasurementTypesForExtendedProlongPeriod (23),
  internalProblem                      (24),
  stopMeasurementJob                  (25),
  stopTimeReached                     (26),
  resumeMeasurementJob                (27),
  suspendMeasurementJob               (28),
  startTimeReached                   (29),
  suspendMeasurementJobBySystem      (30),

  --from notifyThresholdMonitorStatusChanged (3GPP TS32.412 [7])
  resumeThresholdMonitor              (31),
  suspendThresholdMonitor             (32),

  failure                             (255) -- operation failed, specific error unknown
}

Gauge ::= REAL

GranularityPeriod ::= INTEGER(15|30|45|60|720|1440) --minutes

JobId ::= ObjectInstance

JobInfo ::= SEQUENCE
{
  mOCName           GraphicString,
  mOCInstanceList   SEQUENCE OF ObjectInstance, --MOI to be monitored
  measurementCategoryList SEQUENCE OF ObjectClass,
  granularityPeriod GranularityPeriod,
  reportingPeriod   INTEGER, -- must be an integer multiple of GranularityPeriod
  startTime          GeneralizedTime,
  stopTime           GeneralizedTime,
  schedule           JobMeasurementSchedule
}

JobList ::= SEQUENCE OF JobId

JobListId ::= INTEGER

```

```

JobMeasurementschedule ::= SEQUENCE
{
  startTime      GeneralizedTime,
  stopTime       GeneralizedTime,
  scheduled      Timetable
}

JobStatus ::= ENUMERATED
{
  active        (0),
  scheduled     (1),
  suspended     (2),
  stopped       (3)
}

ListMeasurementJobsInfo ::= JobList

ListMeasurementJobsReply ::= SEQUENCE
{
  jobInfoList    SEQUENCE OF JobInfo,
  status         ErrorCauses
}

ListThresholdMonitorsInfo ::= SEQUENCE OF MonitorId

ListThresholdMonitorsReply ::= SEQUENCE
{
  monitorInfoList SEQUENCE OF MonitorInfo,
  status          ErrorCauses
}

MonitorId ::= ObjectInstance

MonitorInfo ::= SEQUENCE
{
  mOCName           GraphicString,
  mOCInstanceList   SEQUENCE OF ObjectInstance,
  thresholdInfoList ThresholdInfoList,
  monitorGranularityPeriod TimeInterval
}

MonitorListId ::= INTEGER

NotifyMeasurementJobStatusChangedInfo ::= SEQUENCE
{
  notificationId   NotificationIdentifier, --ITU-T X.721
  jobId            JobId,
  jobStatus         JobStatus,
  reason           ErrorCauses
}

NotifyThresholdMonitorStatusChangedInfo ::= SEQUENCE
{
  notificationId   NotificationIdentifier, --ITU-T X.721
  monitorId         MonitorId,
  monitorStatus     ThresholdMonitorStatus,
  reason           ErrorCauses
}

NotifyThresholdMonitorObjectCreationInfo ::= SEQUENCE
{
  notificationId   NotificationIdentifier, --ITU-T X.721
  monitorId         MonitorId,
  monitorStatus     ThresholdMonitorStatus,
  monitorGranularityPeriod TimeInteval,
  probableCause     GraphicString,
  specificProblem   GraphicString,
  direction          INTEGER
}

NotifyThresholdMonitorObjectDeletionInfo ::= SEQUENCE
{
  notificationId   NotificationIdentifier, --ITU-T X.721
  monitorId         MonitorId
}

ResumeMeasurementJobInfo ::= JobId

```

```

ResumeMeasurementJobReply ::= ErrorCauses
ResumeThresholdMonitorInfo ::= SEQUENCE OF MonitorId
ResumeThresholdMonitorReply ::= ErrorCauses

StopMeasurementJobInfo ::= SEQUENCE OF JobId
StopMeasurementJobReply ::= ErrorCauses

SuspendMeasurementJobInfo ::= SEQUENCE OF JobId
SuspendMeasurementJobReply ::= ErrorCauses
SuspendThresholdMonitorInfo ::= SEQUENCE OF MonitorId
SuspendThresholdMonitorReply ::= ErrorCauses

ThresholdInfo ::= SEQUENCE
{
  measurementTypeName      GraphicString,
  probableCause            GraphicString,
  specificProblem          GraphicString,
  direction                INTEGER,
  thresholdPack             ThresholdPack
}

ThresholdInfoList ::= SEQUENCE OF ThresholdInfo

ThresholdMonitorInfo ::= SEQUENCE
{
  mOCName                  GraphicString,
  mOCIInstanceList          SEQUENCE OF ObjectInstance,
  thresholdInfoList         SEQUENCE OF ThresholdInfo,
  monitorGranularityPeriod TimeInterval
}

ThresholdMonitorStatus ::= ENUMERATED
{
  active       (0),
  suspended    (1)
}

ThresholdPack ::= SEQUENCE
{
  thresholdValue           ThresholdValue,
  thresholdSeverity        ThresholdSeverity,
  hysteresis               INTEGER
}

ThresholdSeverity ::= ENUMERATED
{
  warning     (0),
  minor       (1),
  major       (2),
  critical    (3)
}

ThresholdValue ::= ENUMERATED
{
  gauge       (0),
  counter     (1)
}

TimeInterval ::= INTEGER

Timetable ::= SEQUENCE
{
  dailyOrWeekly           DailyOrWeekly,
  scheduledDaysOfTheWeek  DaysOfTheWeek   --may be any combination of the bits of DaysOfTheWeek
}

UnsupportedList ::= SEQUENCE
{
  mOCName                  GraphicString,
}

```

```

mOInstancelist      SEQUENCE OF ObjectInstance,
measurementTypeName GraphicString,
reason              UnsupportedListReason
}

UnsupportedListReason ::= ENUMERATED
{
  -- from createMeasurementJob (3GPP TS32.412 [7])
  measurementTypeNameIsUnknownToThePMIRP          (0),
  measurementTypeNameIsInvalid                   (1),
  measurementTypeNameIsNotSupportedInTheSpecificImplementation (2),
  theRelatedIOCInstanceIsUnknownToThePMIRP       (3),
  --for the ErrorCause highWorkload any of the following reasons may occur in UnsupportedList:
  insufficientCapacityToMonitorTheRelatedIOCInstances (4),
  emCpuBusy                                         (5),
  emHDSshortage                                     (6),
  emLowMemory                                       (7),
  neCpuBusyNeObjectInstList                      (8), -- neObjectInstList=list of affected network elements
  neHDSshortageNeObjectInstList                  (9),
  neLowMemoryNeObjectInstList                    (10),
  maxJobReached                                    (11),
  measurementTypeNameIsAlreadyMonitoredForTheIOCInstanceWithTheSameOrAnotherGranularityPeriod (12),
  -- from createThresholdMonitor (3GPP TS32.412 [7])
  thePMIRPHasTroubleStartingMonitoringTheThresholdOfThisMeasurementType (13),
  theMeasurementTypeIsIllegal                   (14),
  theMeasurementTypeExistsButItIsNotCurrentlyUnderMonitoringByAnyMeasurementJob (15),

  otherReason                                      (255)
}

END -- of module TS32-414TypeModule

```

## Annex A (informative): List of assigned Object Identifiers

This annex provides a list with all object identifiers that have been assigned in TS 32.344. These object identifiers shall not be assigned to new objects (also not in new versions of this document).

<b>Basic Object Name</b>	<b>Name and OID of the current TS Version</b>	<b>Name and OIDs of previous TS Versions</b>
<b>Managed Object Classes</b>		
pMIRP	Name: PMIRP OID : ts32-414ObjectClass 10600	--
<b>Packages</b>		
pMIRPBasicPackage	Name: pMIRPBasicPackage OID : ts32-4144Package 10600	--
pMIRPOperationsPackage1	Name: pMIRPOperationsPackage1 OID : ts32-4144Package 20600	--
pMIRPOperationsPackage2	Name: pMIRPOperationsPackage2 OID : ts32-4144Package 30600	--
pMIRPOperationsPackage3	Name:pMIRPOperationsPackage3 OID: ts32-4144Package 40600	--
pMIRPNotificationPackage	Name: pMIRPNotificationPackage OID : ts32-414Package 50600	--
pMIRPObjectCreationDeletionNotificationPackage	Name: pMIRPObjectCreationDeletionNotificationPackage OID : ts32-414Package 60610	--
<b>Actions</b>		
createMeasurementJob	Name:createMeasurementJob OID : ts32-4144Action 10600	--
stopMeasurementJob	Name: stopMeasurementJob OID : ts32-354Action 20600	--
listMeasurementJobs	Name: listMeasurementJob OID : ts32-414Action 30600	--
suspendMeasurementJob	Name: suspendMeasurementJob OID : ts32-414Action 40600	--
resumeMeasurementJob	Name: resumeMeasurementJob OID : ts32-414Action 50600	--
createThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 60600	--
deleteThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 70600	--
listThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 80600	--
suspendThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 90600	--
resumeThresholdMonitor	Name: createThresholdMonitor OID : ts32-414Action 100600	--
<b>Notifications</b>		
notifyMeasurementJobStatusChanged	Name: notifyMeasurementJobStatusChanged OID : ts32-414Notification 10600	--
notifyThresholdMonitorStatusChanged	Name: notifyThresholdMonitorStatusChanged OID : ts32-414Notification 20600	--
notifyThresholdMonitorObjectCreation	Name: notifyThresholdMonitorObjectCreation OID : ts32-414Notification 30610	--
notifyThresholdMonitorObjectDeletion	Name: notifyThresholdMonitorObjectDeletion OID : ts32-414Notification 40610	--
<b>Attributes</b>		
--	--	--

Parameters		
--	--	--
Name Bindings		
--	--	--

---

## Annex B (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
Dec 2004	SA_26	SP-040785	--	--	Submitted to SA#26 for Approval	--	1.0.0	6.0.0
Sep 2005	SA_29	SP-050460	0001	--	Add Create/Delete Notifications - Align CMIP SS with the IS 32.412	F	6.0.0	6.1.0

---

## History

<b>Document history</b>		
V6.0.0	December 2004	Publication
V6.1.0	September 2005	Publication