

ETSI EN 300 019-2-1 V2.2.1 (2014-10)



**Environmental Engineering (EE);
Environmental conditions and environmental tests
for telecommunications equipment;
Part 2-1: Specification of environmental tests;
Storage**

Reference

REN/EE-0157

Keywords

environment, equipment practice, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Environmental test specifications.....	7
3.1 Specification T 1.1: Weatherprotected, partly temperature-controlled storage locations.....	8
3.2 Specification T 1.2: Weatherprotected, not temperature-controlled storage locations.....	11
3.3 Specification T 1.3: Non-weatherprotected storage locations and T 1.3 E: Non-weatherprotected storage locations - extended.....	14
4 Notes to tables	19
4.1 General note	19
4.2 Notes to tables 1 to 7	19
Annex A (informative): Bibliography.....	21
History	22

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Environmental Engineering (EE).

The present document is part 2, sub-part 1 of a multi-part deliverable covering the environmental conditions and environmental tests for telecommunications equipment, as identified below:

Part 1: "Classification of environmental conditions";

Part 2: "Specification of environmental tests":

Sub-part 0: "Introduction";

Sub-part 1: "Storage";

Sub-part 2: "Transportation";

Sub-part 3: "Stationary use at weatherprotected locations";

Sub-part 4: "Stationary use at non-weatherprotected locations";

Sub-part 5: "Ground vehicle installations";

Sub-part 6: "Ship environments";

Sub-part 7: "Portable and non-stationary use";

Sub-part 8: "Stationary use at underground locations".

Part 1 specifies different standardized environmental classes covering climatic and biological conditions, chemically and mechanically active substances and mechanical conditions during storage, transportation and in use.

Part 2 specifies the recommended test severities and test methods for the different environmental classes.

National transposition dates	
Date of adoption of this EN:	1 October 2014
Date of latest announcement of this EN (doa):	31 January 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2015
Date of withdrawal of any conflicting National Standard (dow):	31 July 2015

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**may not**", "**need**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies test severities and methods for verification of the required resistibility of equipment according to the relevant environmental class.

The tests defined in the present document apply to storage of equipment covering the environmental conditions stated in EN 300 019-1-1 [1].

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 019-1-1 (2014): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-1: Classification of environmental conditions; Storage".
- [2] Void.
- [3] Void.
- [4] IEC 60068-2-1:2007: "Environmental testing - Part 2-1: Tests - Test A: Cold".
- [5] IEC 60068-2-2:2007: "Environmental testing - Part 2-2: Tests - Test B: Dry heat".
- [6] IEC 60068-2-6:2007: "Environmental testing - Part 2-6: Tests - Test Fc: Vibration (sinusoidal)".
- [7] IEC 60068-2-14:2009: "Environmental testing - Part 2-14: Tests - Test N: Change of temperature".
- [8] IEC 60068-2-18:2000: "Environmental testing - Part 2-18: Tests - Test R and guidance: Water".
- [9] IEC 60068-2-27:2008: "Environmental testing. Part 2-27: Tests - Test Ea and guidance: Shock".
- [10] IEC 60068-2-30:2005: "Environmental testing - Part 2-30: Tests - Test Db: Damp heat, cyclic (12 + 12 hour cycle)".
- [11] IEC 60068-2-78:2012: "Environmental testing - Part 2-78: Tests - Test Cab: Damp heat, steady state".
- [12] IEC 60068-2-64:2008: "Environmental testing - Part 2-64: Tests - Test Fh: Vibration, broadband random and guidance".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 019-2-0 (2003): "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-0: Specification of environmental tests; Introduction".
- [i.2] IEC 60068-2-68:1994: "Environmental testing - Part 2: Tests - Test L: Dust and sand".
- [i.3] IEC 60068-2: "Environmental testing - Part 2: Tests".

3 Environmental test specifications

The detailed descriptions of the environmental conditions are given in clauses 4 and 5 of EN 300 019-1-1 [1].

EN 300 019-2-0 [i.1] forms a general overview of part 2 of the present document.

If the equipment is normally stored in a packed state then it shall be tested in its packaging.

3.1 Specification T 1.1: Weatherprotected, partly temperature-controlled storage locations

This specification shall apply to weatherprotected or partially weather-controlled storage locations having partially temperature or humidity control. See tables 1 and 2.

Table 1: Test specification T 1.1: Weatherprotected, partly temperature-controlled storage locations - climatic tests

Environmental parameter			Environmental Class 1.1	Environmental test specification T1.1: Weatherprotected, partly temperature-controlled storage locations					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes	
Air temperature	low	(°C)	-5	-5	72 h	IEC 60068-2-1 [4]	Ab: Cold		
	high	(°C)	+45	+45 or +55	72 h	IEC 60068-2-2 [5]	Bb: Dry heat	2	
	change	(°C/min)	0,5	none				3	
Humidity	relative	low	(%)	5	none			10	
		high	(%)	95	93	96 h	IEC 60068-2-78 [11]	Cab: Damp heat steady state	5
	absolute	condensation		yes	none				6
		low	(g/m ³)	1	none				10
		high	(g/m ³)	29					8
Air	pressure	low	(kPa)	70	none			9	
		high	(kPa)	106	none			9	
	speed	(m/s)	1	none				10	
Water	rain	intensity		no					
		low temperature		no					
	other sources		no						
	icing & frosting		yes					10	
Radiation	solar	(W/m ²)	700					13	
	heat	(W/m ²)	600					13	

Environmental parameter			Environmental Class 1.1	Environmental test specification T1.1: Weatherprotected, partly temperature-controlled storage locations				
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes
Chemically active substances	sulphur	SO ₂ (mg/m ³)	0,3/1,0	none				14
		H ₂ S (mg/m ³)	0,1/0,5	none				14
	chlorine	salts	sea and road salt mist	none				14
		Cl ₂ (mg/m ³)	0,1/0,3	none				14
		HCl (mg/m ³)	0,1/0,5	none				14
	nitrogen	NO _x (mg/m ³)	0,5/1,0	none				14
		NH ₃ (mg/m ³)	1,0/3,0	none				14
	hydrogen fluoride	HF (mg/m ³)	0,01/0,03	none				14
ozone	O ₃ (mg/m ³)	0,05/0,1	none				14	
Mechanically active substances	dust	Sedimentation (mg/(m ² h))	1,5	none				15
		suspension (mg/m ³)	0,2	none				15
	sand	(mg/m ³)	30	none				15
Flora and Fauna	micro organisms		negligible					
	rodents, insects		negligible					
no = this condition does not occur in this class. NOTE: (n = number of note), see clause 4.2.								

Table 2: Test specification T 1.1: Weatherprotected, partly temperature-controlled storage locations - mechanical tests

Environmental parameter			Environmental Class 1.1	Environmental test specification T 1.1: Weatherprotected, partly temperature-controlled storage locations				
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes
Vibration	sinusoidal	velocity (mm/s)	1,5	5	2	IEC 60068-2-6 [6]	Fc: Vibration (sinusoidal)	17
		displacement (mm)						
		acceleration (m/s ²)	5					
		frequency range (Hz)	2-9 9-200	5-62 62-200	3 x 5 sweep cycles			
		axes of vibration		3				
	random	ASD (m ² /s ³)		0,02	3 x 30 minutes	IEC 60068-2-64 [12]	Fh: Vibration, broad-band random (digital control)	18
		(dB/oct)						
		frequency range (Hz)		+12 -12				
		axes of vibration		5-10 10-50 50-100				
				3				
Shocks	shocks	shock spectrum	Type L	none				19a
		duration (ms)	22					
		acceleration (m/s ²)	40					
		number of shocks						
		directions of shocks						
Load	static load	(kPa)	5	none				20

no = this condition does not occur in this class.
NOTE: (n = number of note), see clause 4.2.

3.2 Specification T 1.2: Weatherprotected, not temperature-controlled storage locations

This specification shall apply to weatherprotected or partially weatherprotected storage locations having neither temperature nor humidity control. See tables 3 and 4.

Table 3: Test specification T 1.2: Weatherprotected, not temperature-controlled storage locations - climatic tests

Environmental parameter			Environmental Class 1.2	Environmental test specification T1.2: Weatherprotected, not temperature-controlled storage locations					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes	
Air temperature	low	(°C)	-25	-25	72 h	IEC 60068-2-1 [4]	Ab: Cold		
	high	(°C)	+55	+55 or +70	72 h	IEC 60068-2-2 [5]	Bb: Dry heat	2	
	change	(°C/min)	0,5	none				3	
Humidity	relative	low	(%)	10	none			10	
		high	(%)	100	93	96 h	IEC 60068-2-78 [11]	Cab: Damp heat steady state	5
		condensation	(°C)	yes	+30				7
	absolute	low	(g/m ³)	0,5	90-100	2 cycles	IEC 60068-2-30 [10]	Db: Damp heat cyclic Variant 1	
		high	(g/m ³)	29	+30				10
Air	pressure	low	(kPa)	70	none			9	
		high	(kPa)	106	none			9	
	speed	(m/s)	30	none				10	
Water	rain	intensity		no					
		low temperature		no					
	other sources		dripping water					8	
	icing & frosting		yes	none				10	
Radiation	solar	(W/m ²)	1 120					13	
	heat	(W/m ²)	600					13	

Environmental parameter			Environmental Class 1.2	Environmental test specification T1.2: Weatherprotected, not temperature-controlled storage locations				
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes
Chemically Active substances	sulphur	SO ₃ (mg/m ³)	0,3/1,0	none				14
		H ₂ S (mg/m ³)	0,1/0,5	none				14
	chlorine	salts	sea and road salt mist	none				14
		Cl ₂ (mg/m ³)	0,1/0,3	none				14
		HCl (mg/m ³)	0,1/0,5	none				14
	nitrogen	NO _x (mg/m ³)	0,5/1,0	none				14
		NH ₃ (mg/m ³)	1,0/3,0	none				14
	hydrogen fluoride	HF (mg/m ³)	0,01/0,03	none				14
ozone	O ₃ (mg/m ³)	0,05/0,1	none				14	
Mechanically Active substances	dust	sedimentation (mg/(m ² h))	20	none				15
		suspension (mg/m ³)	5,0	none				15
	sand	(mg/m ³)	300	none				15
Flora and Fauna	micro organisms		mould, fungus, etc.	none				16
	rodents, insects		rodents, etc.	none				16
no = this condition does not occur in this class. NOTE: (n = number of note), see clause 4.2.								

Table 4: Test specification T 1.2: Weatherprotected, not temperature-controlled storage locations - mechanical tests

Environmental parameter			Environmental Class 1.2	Environmental test specification T1.2: Weatherprotected not temperature-controlled storage locations					
Type	Parameter	Detail parameter	Characteristic severity	Test severity		Duration	Reference	Method	Notes
Vibration	sinusoidal	velocity (mm/s)	1,5	5	2	3 x 5 sweep cycles	IEC 60068-2-6 [6]	Fc: Vibration (sinusoidal)	17
		displacement (mm)							
		acceleration (m/s ²)	2-9	9-200					
		frequency range (Hz)							
		axes of vibration							
	random	ASD (m ² /s ³)			0,02		IEC 60068-2-64 [12]	Fh: Vibration, broad-band random (digital control)	18
		(dB/oct)			+12	-12			
		frequency range (Hz)			5-10	10-50 50-100			
		axes of vibration			3				
Shocks	shocks	shock spectrum	Type L						19a
		duration (ms)	22						
		acceleration (m/s ²)	40	none					
		number of shocks							
		directions of shocks							
Load	static load	(kPa)	5	none					20

no = this condition does not occur in this class.
NOTE: (n = number of note), see clause 4.2.

3.3 Specification T 1.3: Non-weatherprotected storage locations and T 1.3 E: Non-weatherprotected storage locations - extended

This specification shall apply to storage locations which are not protected from direct weather influences. See tables 5 to 7.

Table 5: Test specification T 1.3: Non-weatherprotected storage locations - climatic tests

Environmental parameter			Environmental Class 1.3	Environmental test specification T1.3: Non-weatherprotected, storage locations					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes	
Air temperature	low	(°C)	-33	-33 or -45	72 h	IEC 60068-2-1 [4]	Ab: Cold	1	
	high	(°C)	+40	+55 or +40	72 h	IEC 60068-2-2 [5]	Bb: Dry heat	2	
	change	(°C) (°C/min)	0,5	-10/+40 0,5	2 cycles t1 = 3 h	IEC 60068-2-14 [7]	Nb: Change of temperature	4	
Humidity	relative	low	(%)	15	none			10	
		high	(%)	100	93	21 d	IEC 60068-2-78 [11]	Cab: Damp heat steady state	5
		condensation	(%) (°C)	yes	90-100 +30	6 cycles	IEC 60068-2-30 [10]	Db: Damp heat cyclic Variant 1	7
	absolute	low	(g/m ³)	0,26	none				10
		high	(g/m ³)	25					8
Air	pressure	low	(kPa)	70	none			9	
		high	(kPa)	106	none			9	
	speed	(m/s)	50	none				10	
Water	rain	intensity	(mm/min) (m ³ /min) (kPa)	6	0,01 90	3 min/m ² or 15 min	IEC 60068-2-18 [8]	Rb: Impacting water, Method 2.2	11
		low temperature	(°C)	+5					11
	other sources		splashing water					12	
	icing & frosting		yes	none				10	

Environmental parameter			Environmental Class 1.3	Environmental test specification T1.3: Non-weatherprotected, storage locations				
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes
Radiation	solar	(W/m ²)	1 120					13
	heat	(W/m ²)	negligible					13
Chemically active substances	sulphur	SO ₂ (mg/m ³)	0,3/1,0	none				14
		H ₂ S (mg/m ³)	0,1/0,5	none				14
	chlorine	salts	sea and road salt mist	none				14
		Cl ₂ (mg/m ³)	0,1/0,3	none				14
		HCl (mg/m ³)	0,1/0,5	none				14
	nitrogen	NO _x (mg/m ³)	0,5/1,0	none				14
		NH ₃ (mg/m ³)	1,0/3,0	none				14
	hydrogen fluoride	HF (mg/m ³)	0,01/0,03	none				14
ozone	O ₃ (mg/m ³)	0,05/0,1	none				14	
Mechanically active substances	dust	sedimentation(mg/(m ² h))	20	none				15
		suspension (mg/m ³)	5,0	none				15
	sand	(mg/m ³)	300	none				15
Flora and Fauna	micro organisms		mould, fungus, etc.	none				16
	rodents, insects		rodents, etc.	none				16
no = this condition does not occur in this class. NOTE: (n = number of note), see clause 4.2.								

Table 6: Test specification T 1.3 E: Non-weatherprotected storage locations - extended - climatic tests

Environmental parameter			Environmental Class 1.3E	Environmental test specification T1.3E: Non-weatherprotected, storage locations - extended					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes	
Air temperature	low	(°C)	-45	-45	72 h	IEC 60068-2-1 [4]	Ab: Cold		
	high	(°C)	+45	+45 or +60	72 h	IEC 60068-2-2 [5]	Bb: Dry heat	2	
	change	(°C) (°C/min)	0,5	-10/+40 0,5	2 cycles t ₁ = 3h	IEC 60068-2-14 [7]	Nb: Change of temperature	4	
Humidity	relative	low	(%)	8	none			10	
		high	(%)	100	93	21 d	IEC 60068-2-78 [11]	Cab: Damp heat steady state	5
		condensation	(%) (°C)	yes	90-100 +40	6 cycles	IEC 60068-2-30 [10]	Db: Damp heat cyclic Variant 1	7
	absolute	low	(g/m ³)	0,03	none				10
		high	(g/m ³)	30					8
Air	pressure	low	(kPa)	70	none			9	
		high	(kPa)	106	none			9	
	speed	(m/s)	50	none				10	
Water	rain	intensity	(mm/min) (m ³ /min) (kPa)	15	0,01 90	6 min/m ² or 30 min	IEC 60068-2-18 [8]	Rb: Impacting water, Method 2.2	11
		low temperature	(°C)	+5					11
	other sources		splashing water					12	
	icing & frosting		yes	none				10	
Radiation	solar	(W/m ²)	1 120					13	
	heat	(W/m ²)	negligible						

Environmental parameter			Environmental Class 1.3E	Environmental test specification T1.3E: Non-weatherprotected, storage locations - extended					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes	
Chemically active substances	sulphur	SO ₂ (mg/m ³)	0,3/1,0	none				14	
		H ₂ S (mg/m ³)	0,1/0,5	none				14	
	chlorine	salts	sea and road salt mist	none					14
		Cl ₂ (mg/m ³)	0,1/0,3	none					14
		HCl (mg/m ³)	0,1/0,5	none					14
	nitrogen	NO _x (mg/m ³)	0,5/1,0	none					14
		NH ₃ (mg/m ³)	1,0/3,0	none					14
	hydrogen fluoride	HF (mg/m ³)	0,01/0,03	none					14
ozone	O ₃ (mg/m ³)	0,05/0,1	none					14	
Mechanically active substances	dust	sedimentation (mg/(m ² h))	20	none					15
		suspension (mg/m ³)	5,0	none					15
	sand	(mg/m ³)	300	none					15
Flora and Fauna	micro organisms		mould, fungus, etc.	none					16
	rodents, insects		rodents, etc.	none					16

no = this condition does not occur in this class.
NOTE: (n = number of note), see clause 4.2.

**Table 7: Test specification T 1.3: Non-weatherprotected storage locations and
test specification T 1.3 E: Non-weatherprotected storage locations - extended - mechanical tests**

Environmental parameter			Environmental Class 1.3 & 1.3E	Environmental test specification T 1.3 and T 1.3E: Non-weatherprotected storage locations				
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes
Vibration	sinusoidal	displacement (mm)	3,0	1,2	3 x 5 sweep cycles	IEC 60068-2-6 [6]	Fc: Vibration (sinusoidal)	17
		acceleration (m/s ²)	10	4				
		frequency range (Hz)	2-9 9-200	5-9 9-200				
		axes of vibration		3				
Vibration	random	ASD (m ² /s ³)		0,04	3 x 30 minutes	IEC 60068-2-64 [12]	Fh: Vibration, broad-band random (digital control)	18
		(dB/oct)		+12 -12				
		frequency range (Hz)		5-10 10-50 50-100				
		axes of vibration		3				
Shocks	shocks	shock spectrum	Type I	half sine	3 in each direction	IEC 60068-2-27 [9]	Ea: Shock	19b
		duration (ms)	11	11				
		acceleration (m/s ²)	100	50				
		number of shocks						
		directions of shocks		6				
Load	static load	(kPa)	5	none				20

no = this condition does not occur in this class.
NOTE: (n = number of note), see clause 4.2.

4 Notes to tables

4.1 General note

The present document applies to storage of equipment covering environmental conditions stated in EN 300 019-1-1 [1]. The notes have been added to explain the main reasons for recommended tests or to explain why no test has been recommended even if there is a characteristic severity given.

The equipment should be tested in the state in which it is normally stored if possible. For example, if the equipment is in a packed state, then it should be tested in its packaging. If the equipment is stored both with and without its packaging it may be necessary to perform tests for both configurations. For some tests and equipment, the test may be more severe for the packaged rather than the unpacked equipment. For example, for an equipment in a sealed package, the change of temperature test may produce condensation.

4.2 Notes to tables 1 to 7

NOTE 1 (Air temperature, low)

The lower test temperature has been chosen to describe the conditions where the unpacked equipment has been exposed to extreme low temperatures and heat irradiation. If the equipment is tested without any package or if the equipment is small the duration may be decreased.

NOTE 2 (Air temperature, high)

Two test temperatures are given. The lower temperature applies if the equipment is protected against solar radiation. If the equipment is tested without any package or if the equipment is small the duration may be decreased.

NOTE 3

The characteristic severity value is considered to have insignificant effect on the equipment and therefore no test is recommended.

NOTE 4 (Air temperature, change)

In cold temperatures rapid change of temperature are not likely to occur during storage. Test Nb is intended for specimen with large thermal time constant.

NOTE 5 (Humidity, relative high)

These severities are the nearest IEC test temperature values, which according to the climatogram can be achieved in the relative humidity given in the table. This test is recommended for unpacked equipment only.

NOTE 6

This characteristic severity corresponds to the high value of relative humidity and small temperature variation within the equipment and is considered to be covered by test IEC 60068-2-78 [11] Test Cab.

NOTE 7 (Humidity, relative, condensation)

IEC 60068-2-30 [10] Test Db is recommended with test severities not higher than climatogram limits for this class.

NOTE 8

This effect is considered to be partly included in test IEC 60068-2-78 [11] Test Cab and/or test IEC 60068-2-30 [10] Test Db.

NOTE 9 (Air pressure, low and high)

No test is recommended for normal applications, because the effect of air pressure is evaluated at the component level.

NOTE 10

There is no IEC 60068-2 [i.3] test method for this parameter.

NOTE 11 (Water, rain)

IEC 60068-2-18 [8] Test Rb method 2.2 has been chosen even if it does not imitate normal rain. It is a simple hand held shower test, easy to perform and can demonstrate that the specimen design is adequately tolerated to survive this condition. The cooling effect of the low temperature of the rain is included in IEC 60068-2 [i.3] Test Nb. Two durations are given, whichever is greater should be chosen.

NOTE 12 (Water, other sources)

No test is recommended because the effect is already included in IEC 60068-2 [i.3] Test Rb.

NOTE 13 (Radiation, solar, heat)

The heating effect of solar radiation is included in the higher test temperature in IEC 60068-2-2 [5] Test Bb as described in note 2. Photochemical tests can be made separately for components and materials. No test is recommended in the present document.

NOTE 14 (Chemically active substances)

Characteristic severities are mean/maximum values. The characteristic severities should be considered when choosing components and materials. No test is recommended in the present document.

NOTE 15 (Mechanically active substances)

For mechanically active substances the packaging is supposed to protect the equipment against dust and sand where needed, therefore no test is recommended. The levels of dust both sedimentation and suspension are far lower than the lowest severity recommended in IEC 60068-2-68 [i.2] Test Lb.

NOTE 16 (Flora and fauna)

The characteristic severities should be considered when choosing components and materials. Therefore not test is recommended at the equipment level.

NOTE 17 (Vibration, sinusoidal)

The severities are given as peak values. The characteristic severity given is considered to be too severe for this class. Test severity values not specified in IEC 60068-2 [i.3].

NOTE 18 (Vibration, random)

ASD (Acceleration Spectral Density). Random vibration testing method may be used instead of the sinusoidal vibration test. The test severity values are not specified in IEC 60068-2 [i.3]. The maximum test frequency has been reduced because between 100 Hz and 200 Hz the contribution is insignificant.

	classes: 1.1 and 1.2	class: 1.3
Acceleration RMS (for information only)	1,06 m/s ²	1,5 m/s ²

NOTE 19 (Shocks)

- a** No test is required because this condition is covered by transportation test for packaged equipment and by in-use test for unpackaged equipment.
- b** The test can be omitted for packaged equipment if this condition is covered by transportation tests. The values for test severity are not specified in IEC 60068-2 [i.3]. The severities are given as peak values. The energy content and the Shock Response Spectrum (SRS) of the shock given as test severity have been considered more appropriate than that given by the characteristic severity.

NOTE 20 (Load)

Packaging and/or equipment should be designed with this requirement in mind.

Annex A (informative): Bibliography

ETSI ETR 100 035: "Equipment Engineering (EE); Environmental engineering; Guidance and terminology".

IEC 60068-1: "Environmental testing. Part 1: General and guidance".

IEC 60721-3-3:2002: "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 3: Stationary use at weatherprotected locations".

History

Document history		
Edition 1	May 1994	Publication as ETS 300 019-2-1
V2.1.2	September 2000	Publication
V2.1.6	June 2014	EN Approval Procedure AP 20141001: 2014-06-03 to 2014-10-01
V2.2.1	October 2014	Publication