

# ETSI EN 300 019-2-5 V2.1.2 (2001-09)

---

*European Standard (Telecommunications series)*

**Environmental Engineering (EE);  
Environmental conditions and environmental tests for  
telecommunications equipment;  
Part 2-5: Specification of environmental tests;  
Ground vehicle installations**

---



---

**Reference**REN/EE-01027-2-5

---

---

**Keywords**environment, mobile, terrestrial, testing

---

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

[editor@etsi.fr](mailto:editor@etsi.fr)

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.  
All rights reserved.

---

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
1 Scope .....	5
2 References .....	5
3 Environmental test specifications.....	5
3.1 Specification T 5.1: Protected installation.....	6
3.2 Specification T 5.2: Partly protected installation .....	10
4 Notes to tables .....	12
4.1 General note .....	12
4.2 Notes to tables 1 to 3 .....	12
<b>Annex A (informative): Bibliography .....</b>	<b>15</b>
History .....	16

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/legal/home.htm>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Environmental Engineering (EE).

The present document is part 2, sub-part 5 of a multi-part deliverable covering environmental conditions and environmental tests for telecommunications equipment, as identified below:

Part 1: "Classification of environmental conditions";

**Part 2: "Specification of environmental tests"**

Sub-part 0: "Introduction";

Sub-part 1: "Storage";

Sub-part 2: "Transportation";

Sub-part 3: "Stationary use at weatherprotected locations";

Sub-part 4: "Stationary use at non-weatherprotected locations";

**Sub-part 5: "Ground vehicle installations";**

Sub-part 6: "Ship environments";

Sub-part 7: "Portable and non-stationary use";

Sub-part 8: "Stationary use at underground locations".

Part 1 specifies different standardized environmental classes covering climatic and biological conditions, chemically and mechanically active substances and mechanical conditions during storage, transportation and in use.

Part 2 specifies the recommended test severities and test methods for the different environmental classes.

Part 2-0 forms a general overview of part 2. The present document deals with ground vehicle installations.

<b>National transposition dates</b>	
Date of adoption of this EN:	14 September 2001
Date of latest announcement of this EN (doa):	31 December 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2002
Date of withdrawal of any conflicting National Standard (dow):	30 June 2002

---

## 1 Scope

The present document specifies test methods and severities for the verification of the required resistibility of telecommunication equipment according to the relevant environmental class.

The tests in the present document apply to the use of equipment installed permanently or temporarily in ground vehicles and cover the vehicles and the environmental conditions stated in ETS 300 019-1-5 [1].

The tests cover installations in vehicles powered by electric motors and combustion engines. Applications in combustion engine compartments are excluded.

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] ETSI ETS 300 019-1-5: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-5: Classification of environmental conditions; Ground vehicle installations".
- [2] IEC 60068-2: "Environmental testing - Part 2: Tests".
- [3] ETSI ETS 300 019-2-0: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-0: Specification of environmental tests; Introduction".

---

## 3 Environmental test specifications

The detailed descriptions of the environmental conditions are given in clauses 4 and 5 of ETS 300 019-1-5 [1].

ETS 300 019-2-0 [3] forms a general overview of part 2 of the present multipart standard.

The equipment under test is assumed to be in its operational state throughout the test conditions described in this part unless otherwise stated. The required performance before, during and after the test needs to be specified in the product specification. Input and load conditions of the equipment shall be chosen to obtain full utilization of the equipment under test. The heat dissipation shall be maximized, except for the steady state, low temperature test, where it shall be minimized.

### 3.1 Specification T 5.1: Protected installation

This specification applies to use in weatherprotected heated locations in vehicles which are used in areas with or without well developed road systems depending on the selected IEC mechanical class. See tables 1, 2 and 2a.

**Table 1: Test specification T 5.1: Protected installation - climatic tests**

Environmental parameter			Environmental Class 5.1	Environmental test specification T5.1: Vehicle, protected installation					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes	
Air temperature	low	(°C)	-25	-25	16 h	IEC 60068-2-1 [2]	Ab/Ad: Cold	1	
	high	(°C)	+40 a), e)	+40 or +55	16 h	IEC 60068-2-2 [2]	Bb/Bd: Dry heat	2	
		(°C)	+70 b), c)	+70 or +85	16 h	IEC 60068-2-2 [2]	Bb/Bd: Dry heat	2	
	change	rapid	(°C)	-25/+30	none				3a
		gradual	(°C/min)	-25/+30 not c)	-25/+30	5 cycles t <sub>1</sub> = 3 h	IEC 60068-2-14 [2]	Na: Change of temperature	3b
Temperature	change	air/water	(°C)	no not c)					
		air/water	(°C)	+60/+5 c)	none			4	
		air/snow	(°C)	+60/-5 c)					
Humidity	relative	slow temperature change	(%) (°C)	95 +40	93 +40	96 h	IEC 60068-2-56 [2]	Cb: Damp heat, steady state	5
		rapid temperature change	(%) (°C)	95 -25/+30 not d)	90-100 +40	2 cycles	IEC 60068-2-30 [2]	Db: Damp heat, cyclic, Variant 2	6
		low	(%) (°C)	95 +10/+70 d)	90-100 +55	2 cycles	IEC 60068-2-30 [2]	Db: Damp heat, cyclic, Variant 2	6
	absolute	low	(%) (°C)	10 +30	none				8
		rapid temperature change	(g/m <sup>3</sup> ) (°C)	60 +70/+15	none				7
Air	pressure	low	(kPa)	70	none			9	
	speed		(m/s)	20	none			8	
Water	rain	Intensity	(mm/min)	no					
	other sources	velocity	(m/s)	0,3	none			8	
	wetness			wet surfaces	none			8,12	
Radiation	solar		(W/m <sup>2</sup> )	700				13	
	heat		(W/m <sup>2</sup> )	600				13	

Environmental parameter			Environmental Class 5.1	Environmental test specification T5.1: Vehicle, protected installation					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes	
Chemically active substance	sulphur	SO <sub>2</sub> (mg/m <sup>3</sup> )	0,3 / 1,0	none				14	
		H <sub>2</sub> S (mg/m <sup>3</sup> )	0,1 / 0,5	none				14	
	chlorine	sea salts	salt mist	none					14
		road salts	solid salt, salt water	none					14
		HCl (mg/m <sup>3</sup> )	0,1 / 0,5	none					14
	nitrogen	NO <sub>x</sub> (mg/m <sup>3</sup> )	0,5 / 1,0	none					14
		NH <sub>3</sub> (mg/m <sup>3</sup> )	1,0 / 3,0	none					14
	hydrogen fluoride	HF (mg/m <sup>3</sup> )	0,01 / 0,03	none				14	
	ozone	O <sub>3</sub> (mg/m <sup>3</sup> )	0,05/ 0,1	none				14	
Mechanically active substances	dust (Sedimentation)	other than cabin (mg/(m <sup>2</sup> h))	3,0	none				15	
		cabin only (mg/(m <sup>2</sup> h))	1,0					15	
	sand	(mg/m <sup>3</sup> )	0,1	none				15	
Flora and Fauna	micro organism		mould, fungus, etc.	none				16	
	rodents, insects		rodents, etc.	none				16	
Contaminating fluids	oil	motor	no						
		gearbox	no						
		hydraulic transformer		none				17	
	fluid	brake		Electrical engine compartment only	none				17
		cooling			none				17
	grease			none				17	
	battery electrolyte			none				17	
	fuel		no						
no:	This condition does not occur in this class.								
none:	Verification is required only in special cases.								
NOTES:	Number of note, see clause 4.2.								
Key:	a) Ventilated compartment; b) Unventilated compartment; c) Engine compartment; d) Near refrigerated air conditioning; e) Outdoor air.								

**Table 2: Test specification T5.1: Protected installation - mechanical tests (IEC Class 5M2)**  
**Test specification T5.2: Partly protected installation - mechanical tests (IEC Class 5M2)**

Environmental parameter			Environmental Class 5.1			Environmental test specification T5.1 and 5.2: Vehicle, protected and partly protected installations				
Type	Parameter	Detail parameter	Characteristic severity			Test severity	Duration	Reference	Method	Notes
Vibration	sinusoidal	displacement (mm)	3,3			none				18
		acceleration (m/s <sup>2</sup> )		3	15					
		frequency range (Hz)	2-9	9-200	200-500					
Vibration	random	ASD (m <sup>2</sup> /s <sup>3</sup> )	3		0,3	1		IEC 60068-2-64 [2]	Fh: Vibration, broad-band random (digital control)	19
		frequency range (Hz)	10-200		200-500					
		axes of vibration				5-20 20-500	3 x 30 min			
Shocks	shocks	shock spectrum duration (ms)	Type I		Type II	half sine		IEC 60068-2-27 [2]	Ea: Shock	20
		acceleration (m/s <sup>2</sup> )	11		6					
		number of shocks	100		300	300	3 in each direction			
		directions shocks				6				
Shocks	bump	acceleration (m/s <sup>2</sup> )	no			100		IEC 60068-2-29 [2]	Eb: Bump	21
		duration (ms)				11				
		number of bumps				6	100 in each direction			
		directions of bumps								

no: This condition does not occur in this class.  
none: Verification is required only in special cases.  
NOTES: Number of note, see clause 4.2.



**Table 2a: Test specification T5.1: Protected installation - mechanical tests (IEC Class 5M3)**  
**Test specification T5.2: Partly protected installation - mechanical tests (IEC Class 5M3)**

Environmental parameter			Environmental Class 5.1 & 5.2		Environmental test specification T5.1 and 5.2: Vehicle, protected and partly protected installations					
Type	Parameter	Detail parameter	Characteristic severity		Test severity	Duration	Reference	Method	Notes	
Vibration	sinusoidal	displacement (mm) acceleration (m/s <sup>2</sup> ) frequency range (Hz)	7,5 20 2-8	50 8-200 200-500	none				18	
	random	ASD (m <sup>2</sup> /s <sup>3</sup> ) (dB/oct) frequency range (Hz) axes of vibration	3 10-200	1 200-500	2 5-20 3	-3 20-500	3 x 30 min	IEC 60068-2-64 [2]	Fh: Vibration, broad-band random (digital control)	19
Shocks	shocks	shock spectrum duration (ms) acceleration (m/s <sup>2</sup> ) number of shocks directions of shocks	Type I 11 300	Type II 6 1 000	half sine 6 1 000 6		3 in each direction	IEC 60068-2-27 [2]	Ea: Shock	20
	bump	acceleration (m/s <sup>2</sup> ) duration (ms) number of bumps directions of bumps	no		100 11 6		100 in each direction	IEC 60068-2-29 [2]	Eb: Bump	21
no: This condition does not occur in this class. none: Verification is required only in special cases. NOTES: Number of note, see clause 4.2.										

### 3.2 Specification T 5.2: Partly protected installation

This specification applies to use in vehicles in areas with or without developed road systems depending on the selected IEC mechanical class excluding only non-weatherprotected use in unheated vehicles at extremely low temperature conditions, see tables 2 and 3.

**Table 3: Test specification T 5.2: Partly protected installation - climatic tests**

Environmental parameter			Environmental Class 5.2	Environmental test specification T 5.2: Vehicle, partly protected installations					
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes	
Air temperature	low	(°C)	-40	-40	16 h	IEC 60068-2-1 [2]	Ab/Ad: Cold	1	
	high	(°C)	+40 a), e)	+40 or +55	16 h	IEC 60068-2-2 [2]	Bb/Bd: Dry heat	2	
		(°C)	+70 b), c)	+70 or +85	16 h	IEC 60068-2-2 [2]	Bb/Bd: Dry heat	2	
	change	rapid	(°C)	-40/+30					3a
		gradual	(°C/min)	-40/+30 5 not c)	-40/+30	5 cycles t <sub>1</sub> = 3 h	IEC 60068-2-14 [2]	Na: Change of temperature	3b
Temperature	change	air / water	(°C)	-40/+5 not c)				4	
		air / water	(°C)	+70/+5 c)					
		air/ snow	(°C)	+70/-5 c)					
Humidity	relative	slow temperature change	(%) (°C)	95 +45	93 +40	96 h	IEC 60068-2-56 [2]	Cb: Damp heat, steady state	5
		rapid temperature change	(%) (°C)	95 -45/+30	90 - 100 +40	2 cycles	IEC 60068-2-30 [2]	Db: Damp heat, cyclic, variant 2	6
			(%) (°C)	95 +10/+70	90 - 100 +55	2 cycles	IEC 60068-2-30 [2]	Db: Damp heat, cyclic, variant 2	6
		low	(%) (°C)	10 +30					8
	absolute	rapid temperature change	(g/m <sup>3</sup> ) (°C)	60 +70/+15					7
Air	pressure	low	(kPa)	70	none			9	
	speed		(m/s)	20	none			8	
Water	rain	intensity	mm/min)	6	0,01 m <sup>3</sup> /min; 90 kPa	3 min/m <sup>2</sup> or 15 min	IEC 60068-2-18 [2]	Rb: Impacting water Method 1.2	10
	other sources	velocity	(m/s)	1				11	
	wetness			wet surfaces				8,12	
Radiation	solar		(W/m <sup>2</sup> )	1 120				13	
	heat		(W/m <sup>2</sup> ) (W/m <sup>2</sup> )	600 not c) 1 120 c)				13	
Chemically active	sulphur	SO <sub>2</sub>	(mg/m <sup>3</sup> )	0,3/1,0	none			14	
		H <sub>2</sub> S	(mg/m <sup>3</sup> )	0,1/0,5	none			14	
	chlorine	sea salts			salt mist	none			14
		road salts			solid salt salt water	none			14
		HCl	(mg/m <sup>3</sup> )		0,1/0,5	none			14

Environmental parameter			Environmental Class 5.2	Environmental test specification T 5.2: Vehicle, partly protected installations				
Type	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Notes
substances	nitrogen	NO <sub>x</sub> (mg/m <sup>3</sup> )	0,5/1,0	none				14
		NH <sub>3</sub> (mg/m <sup>3</sup> )	1,0/3,0	none				14
	hydrogen fluoride	HF (mg/m <sup>3</sup> )	0,01/0,03	none				14
	ozone	O <sub>3</sub> (mg/m <sup>3</sup> )	0,05/0,1	none				14
Mechanically active substances	dust (Sedimentation)	other than cabin (mg/(m <sup>2</sup> h))	3,0					15
		cabin only (mg/(m <sup>2</sup> h))	1,0					15
active substances	sand	other than cabin (mg/m <sup>3</sup> )	0,1					15
		cabin only	no					15
Flora and Fauna	micro organisms		mould, fungus, etc	none				16
	rodents, insects		rodents, etc.	none				16
Contaminating fluids	oil	motor	no					
		gearbox	no					
		hydraulic						17
		transformer						17
	fluid	brake	Electrical engine compartment only					17
		cooling						17
	grease							17
	battery electrolyte							17
fuel		no						
no:	This condition does not occur in this class.							
none:	Verification is required only in special cases.							
NOTES:	Number of note, see clause 4.2.							
Key:	a) Ventilated compartment; b) Unventilated compartment; c) Engine compartment; d) Near refrigerated air conditioning; e) Outdoor air.							

---

## 4 Notes to tables

### 4.1 General note

The present document applies to use of equipment installed permanently or temporally in ground vehicles and cover the vehicles and the environmental conditions stated in ETS 300 019-1-5 [1]. The notes have been added to explain the main reasons for recommended tests or to explain why no test has been recommended even if there is a characteristic severity given.

The relevant specification should specify when, during the environmental test programme, the equipment is in its operational state, and which performance requirements should be measured before, during and after the test, together with the appropriate pass/fail criteria.

### 4.2 Notes to tables 1 to 3

NOTE 1: (Air temperature, low).

The characteristic severity can be used as a cold start up temperature, but it may be modified by the product specification. The equipment under test shall remain operational throughout this test, except for the cold start up test which shall commence once low temperature stability is achieved.

NOTE 2: (Air temperature, high).

In a) and e) condition ( ventilated compartment and outdoor air ) the lower test temperature is equal to the characteristic severity and refers to equipment to be protected against solar and heat radiation. The higher test temperature includes solar radiation.

In b) and c) (unventilated and engine compartment) the higher test temperature is equal to the characteristic severity and refers to equipment to be protected against solar and heat radiation. The higher test temperature includes heat trap effect of direct solar radiation.

The equipment under test shall remain operational throughout this test, except for the start up test at high temperature which shall commence once high temperature stability is achieved.

NOTE 3: (Air temperature, change).

3a) (rapid)

The rapid change of temperature test is normally used to check design tolerancing. This effect is included in IEC 60068-2-14 [2] Test Na.

3b) (gradual)

The IEC 60068-2-14 [2] Test Na has been chosen since the rapid temperature change is considered to be more severe than gradual temperature change. For engine compartment the test temperature change near upper limit is considered to be less severe and this effect is covered by test Bb.

NOTE 4: (Temperature, change; air/water; air/snow).

Temperature change is partly included in IEC60068-2-14 [2] Test Na. The characteristic severity should be considered when designing the equipment and when choosing components and materials.

NOTE 5: (Humidity, relative, slow temperature change).

These severities are the nearest preferred values in IEC 60068-2-56 [2] Test Cb and the minor differences in humidity condition is considered to be insignificant and within normal measurement tolerances.

NOTE 6: (Humidity, relative, rapid temperature change).

Variant 2 has been chosen rather than variant 1 due to the high temperature/absolute humidity involved and the difficulty in maintaining tolerances in most chambers with heat producing specimen.

NOTE 7: (Humidity, absolute, rapid temperature change).

This effect is partly included in IEC 60068-2-30 [2] Test Db.

NOTE 8: There is no IEC 60068-2 [2] test method for this parameter.

NOTE 9: (Air pressure, low).

No test is recommended for normal applications, because the effect of air pressure is evaluated at the component level.

NOTE 10:(Water, rain).

IEC 60068-2-18 [2] Test Rb method 1.2 has been chosen even though it does not imitate normal rain. It is a simple hand held shower test, which is easy to perform and can demonstrate that the specimen design is adequately toleranced to survive this condition. The greater of the two given durations should be chosen.

NOTE 11:(Water, other sources).

No test is recommended because the effect is already included in IEC 60068-2-18 [2] Test Rb.

NOTE 12:(Water, wetness).

If the equipment is in contact with wet surface the corrosion effect and degeneration effect has to be considered.

NOTE 13:(Radiation, solar, heat).

Heating effect of all sources is included in high temperature test. Photochemical tests can be made separately for components and materials.

NOTE 14:(Chemically active substances).

For chemically active substances the characteristic severity should be considered when choosing components and materials. No test is recommended in the present document. Characteristic severities of chemically active substances are mean/maximum values.

NOTE 15:(Mechanically active substances).

The characteristic severities are much lower than lowest test severity in IEC 60068-2-68 [2] Test Lb and therefore no test is recommended. This condition should be considered when designing the equipment and when choosing components and materials.

NOTE 16:(Flora, fauna).

The characteristic severity should be considered when designing the equipment and when choosing components and materials.

NOTE 17:(Contaminating fluids).

Appropriate for electrical engine compartment only. The characteristic severity should be considered when designing the equipment and when choosing components and materials.

NOTE 18:(Vibration, sinusoidal).

Random vibration is considered to be a more realistic test for this condition, therefore no sinusoidal test is recommended. The severities are given as peak values.

NOTE 19:(Vibration, random).

ASD (Acceleration Spectral Density).

	<b>IEC class 5M2</b>	<b>IEC class 5M3</b>
Acceleration RMS (m/s <sup>2</sup> ) (for information only)	8,76	12,63

NOTE 20:(Shock).

The severities are given as peak values.

NOTE 21:(Bump).

The severities are given as peak values. Bump test is recommended in addition to shocks as the number of expected shocks is high. Bumps are of greatest significance in the vertical direction. If only one operational position is specified, 100 bumps have to be applied along that direction only.

---

## Annex A (informative): Bibliography

- ETSI ETR 035: "Equipment Engineering (EE); Environmental engineering; Guidance and terminology".
- IEC 60068-1: "Environmental testing. Part 1: General and guidance".
- IEC 60721-3-3: "Classification of environmental conditions - Part 3: Classification of groups of environmental parameters and their severities - Section 3: Stationary use at weatherprotected locations".

---

## History

<b>Document history</b>		
Edition 1	May 1994	Publication as ETS 300 019-2-5
V2.1.0	May 2001	One-step Approval Procedure OAP 20010914: 2001-05-16 to 2001-09-14
V2.1.2	September 2001	Publication