

Final draft **ETSI EN 300 220-3** V1.1.1 (2000-07)

Candidate Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility and
Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Radio equipment to be used in the 25 MHz to 1 000 MHz
frequency range with power levels ranging up to 500 mW;
Part 3: Harmonized EN covering essential requirements
of article 3.2 of the R&TTE Directive**



Reference

REN/ERM-RP08-0403-3

Keywords

radio, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	6
1 Scope	8
2 References	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols.....	9
3.3 Abbreviations	9
4 Technical requirements specifications	9
4.1 Transmitter requirements	9
4.1.1 Frequency error or frequency drift.....	9
4.1.2 Carrier power (conducted)	9
4.1.3 Effective radiated power	9
4.1.4 Frequency deviation.....	9
4.1.5 Modulation depth.....	10
4.1.6 Adjacent channel power.....	10
4.1.7 Range of modulation bandwidth for wide band equipment (> 25 kHz).....	10
4.1.8 Spurious emissions	10
4.1.9 Frequency stability under low-voltage conditions	10
4.1.10 Duty cycle.....	10
4.2 Receiver requirements	10
4.2.1 Spurious radiations	10
4.2.2 Adjacent channel selectivity - in band	10
4.2.3 Adjacent band selectivity.....	11
4.2.4 Blocking or desensitization.....	11
5 Testing for compliance with technical requirements.....	11
5.1 Essential radio test suites.....	11
5.1.1 Environmental conditions for testing	11
5.1.1.1 Normal and extreme test-conditions.....	11
5.1.1.2 Test power source	11
5.1.2 Choice of samples for test suites.....	11
5.1.3 Transmitter test suites	11
5.1.3.1 Frequency error or drift.....	11
5.1.3.2 Carrier power (conducted)	11
5.1.3.3 Effective radiated power	12
5.1.3.4 Frequency deviation	12
5.1.3.5 Modulation depth	12
5.1.3.6 Adjacent channel power	12
5.1.3.7 Range of modulation bandwidth for wide band equipment (> 25 kHz)	12
5.1.3.8 Spurious emissions.....	12
5.1.3.9 Frequency stability under low-voltage conditions	12
5.1.4 Receiver test suites.....	12
5.1.4.1 Spurious radiations.....	12
5.2 Other test specifications	13

6	Interpretation of measurement results	13
Annex A (informative):	Subclauses of the present document relevant for additional essential requirements of relevant EC Council Directives	14
A.1	Compliance with 99/5/EC (R&TTE Directive) article 3.3e	14
A.2	Compliance with 99/5/EC (R&TTE Directive) article 3.3f	14
History	15

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Candidate Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Voting phase of the ETSI standards Two-step Approval Procedure.

The present document is part 2 of a multi-part deliverable, covering the Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW, as identified below:

- Part 1: "Technical characteristics and test methods";
- Part 2: "Supplementary parameters not intended for conformity purposes";
- Part 3: "Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".**

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [3] laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive") [1].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Introduction

The present document is part of a set of standards designed to fit in a modular structure to cover all radio and telecommunications terminal equipment under the R&TTE Directive [1]. Each standard is a module in the structure. The modular structure is shown in figure 1.




Figure 1: Modular structure for the various standards used under the R&TTE Directive

The left hand edge of the figure shows the different subclauses of Article 3 of the Directive.

The vertical boxes show the standards under article 3.2 for the use of the radio spectrum. The scopes of these standards are specified either by frequency (normally in the case where frequency bands are harmonized) or by radio equipment type.

For article 3.3 various horizontal boxes are shown. Their dotted lines indicate that essential requirements in these areas have to be adopted by the Commission. If such essential requirements are adopted, and as far and as long as they are applicable, they will justify individual standards whose scope is likely to be specified by function or interface type.

The bottom of the figure shows the relationship of the standards to radio equipment and telecommunications terminal equipment. A particular equipment may be radio equipment, telecommunications terminal equipment or both. The General Standard will always apply to it, and a radio spectrum standard will apply if it is radio equipment. An article 3.3 standard will apply as well only if the relevant essential requirement is adopted by the Commission and if the equipment in question lies within the scope of the corresponding standard. Thus, depending on the nature of the equipment, the essential requirements under the Directive may be covered in just the General Standard or in a set of standards that includes the General Standard.

The modularity principle has been taken because:

- it minimizes the number of standards needed. Because equipment may, in fact, have multiple interfaces and functions it is not practicable to produce a single standard for each possible combination of functions that may occur in an equipment;
- it provides scope for standards under articles 3.2 and 3.3 to be added when new frequency bands are agreed or when the Commission takes decisions under article 3 without requiring alteration of standards that are already published;
- it clarifies, simplifies and promotes the usage of Harmonized Standards as the relevant means of conformity assessment.

1 Scope

The present document applies to short range device radio transmitters and receivers as described in the scope of EN 300 220-1 [2]

The present document is intended to cover the provisions of Article 3.2 of Directive 1999/5/EC [1] (R&TTE Directive) [1], which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] "Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications equipment and the mutual recognition of their conformity".
- [2] ETSI EN 300 220-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical characteristics and test methods".
- [3] "Council Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations
- [4] ETSI ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [5] CEPT/ERC Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions in the R&TTE Directive [1], and EN 300 220-1 [2] apply.

3.2 Symbols

For the purposes of the present document, the symbols defined in EN 300 220-1 [2] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations defined in EN 300 220-1 [2] apply.

4 Technical requirements specifications

4.1 Transmitter requirements

4.1.1 Frequency error or frequency drift

One of the following shall be met:

- the frequency error or frequency drift, as defined in EN 300 220-1 [2] subclause 8.1.1, shall not exceed the limits in EN 300 220-1 [2] table 7; or
- for narrow band equipment not capable of producing an unmodulated carrier, the adjacent channel power, as defined in EN 300 220-1 [2] subclause 8.5.2, shall not exceed the limits in EN 300 220-1 [2], subclause 8.5.3 under extreme conditions.

This requirement applies to all transmitters.

4.1.2 Carrier power (conducted)

The carrier power (conducted), as defined in EN 300 220-1 [2] subclause 8.2.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.2.3.

This requirement applies to transmitters which may be used without an integral or dedicated antenna.

4.1.3 Effective radiated power

The effective radiated power, as defined in EN 300 220-1 [2] subclause 8.3.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.3.3.

This requirement applies to transmitters with an integral or dedicated antenna.

4.1.4 Frequency deviation

The frequency deviation, as defined in EN 300 220-1 [2] subclause 8.4.1.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.4.1.2.2 for analogue signals within the audio bandwidth, and shall not exceed the limits in EN 300 220-1 [2] subclause 8.4.1.3.2 for analogue signals above the audio bandwidth.

This requirement applies to all transmitters employing narrow band frequency or phase modulation for voice applications.

4.1.5 Modulation depth

The modulation depth, as defined in EN 300 220-1 [2] subclause 8.4.2.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.4.2.2.2 for analogue signals within the audio bandwidth, and shall not exceed the limits in EN 300 220-1 [2] subclause 8.4.2.3.2 for analogue signals above the audio bandwidth

This requirement applies to all transmitters employing narrow band amplitude modulation for voice applications.

4.1.6 Adjacent channel power

The adjacent channel power, as defined in EN 300 220-1 [2] subclause 8.5.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.5.3.

This requirement applies to transmitters where a channel plan is used with a channel spacing of 25 kHz or less.

4.1.7 Range of modulation bandwidth for wide band equipment (> 25 kHz)

The range of modulation bandwidth, as defined in EN 300 220-1 [2] subclause 8.6.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.6.3.

This requirement applies to transmitters using wide band as defined in EN 300 220-1 [2], subclause 3.1.

4.1.8 Spurious emissions

The spurious emissions, as defined in EN 300 220-1 [2] subclause 8.7.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.7.5.

This requirement applies to all transmitters.

4.1.9 Frequency stability under low-voltage conditions

The frequency stability under low-voltage conditions, as defined in EN 300 220-1 [2] subclause 8.8.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.8.3.

This requirement applies to all battery-operated transmitters.

4.1.10 Duty cycle

The duty cycle, as defined in EN 300 220-1 [2] subclause 8.9.1, shall not exceed the limits in EN 300 220-1 [2] subclause 8.9.3.

This requirement applies to all transmitters.

4.2 Receiver requirements

4.2.1 Spurious radiations

The spurious radiations, as defined in EN 300 220-1 [2] subclause 9.4.1, shall not exceed the limits in EN 300 220-1 [2] subclause 9.4.5.

This requirement applies to all receivers.

4.2.2 Adjacent channel selectivity - in band

The adjacent channel selectivity in-band, as defined in EN 300 220-1 [2] subclause 9.1.1, shall be equal to or greater than the limits in EN 300 220-1 [2] subclause 9.1.3.

This requirement applies to class 1 receivers, as defined in EN 300 220-1 [2], subclause 4.1.1.

4.2.3 Adjacent band selectivity

The adjacent band selectivity, as defined in EN 300 220-1 [2] subclause 9.2.1, shall be equal to or greater than the limits in EN 300 220-1 [2], table 16.

This requirement applies to class 1 receivers, as defined in EN 300 220-1 [2], subclause 4.1.1.

4.2.4 Blocking or desensitization

The blocking or desensitization, as defined in EN 300 220-1 [2] subclause 9.3.1, shall be equal to or greater than the limits in EN 300 220-1 [2], subclause 9.3.3.

This requirement applies to class 1 and class 2 receivers, as defined in EN 300 220-1 [2], subclause 4.1.1.

5 Testing for compliance with technical requirements

5.1 Essential radio test suites

5.1.1 Environmental conditions for testing

5.1.1.1 Normal and extreme test-conditions

Type tests shall be made under normal test conditions, and also, where stated, under extreme test conditions.

The test procedures shall be as specified in EN 300 220-1 [2] subclauses 5.3 to 5.4.

5.1.1.2 Test power source

The test power source shall meet the requirements of EN 300 220-1 [2] subclause 5.2.

5.1.2 Choice of samples for test suites

Measurement shall be performed, according to the present document, on samples of equipment defined in EN 300 220-1 [2], subclauses 4.2.1 to 4.2.12.2.

5.1.3 Transmitter test suites

5.1.3.1 Frequency error or drift

For narrow band equipment, either:

- the test specified in EN 300 220-1 [2], subclause 8.1.2.1 shall be carried out; or
- the test specified in EN 300 220-1 [2], subclause 8.5.2 shall be carried out under extreme test conditions.

The test specified in EN 300 220-1 [2], subclause 8.1.3.1 shall be carried out on wide band equipment.

This test suite applies to all transmitters.

5.1.3.2 Carrier power (conducted)

The test specified in EN 300 220-1 [2], subclause 8.2.2 shall be carried out.

This test suite applies to transmitters which may be used without an integral or dedicated antenna.

5.1.3.3 Effective radiated power

The test specified in EN 300 220-1 [2], subclause 8.3.2 shall be carried out.

This test suite applies to transmitters with an integral or dedicated antenna.

5.1.3.4 Frequency deviation

The tests specified in EN 300 220-1 [2], subclause 8.4.1.2.1 and EN 300 220-1 [2], subclause 8.4.1.3.1 shall be carried out.

This test suite applies to all transmitters employing narrow band frequency or phase modulation for voice applications.

5.1.3.5 Modulation depth

The tests specified in EN 300 220-1 [2], subclause 8.4.2.2.1 and EN 300 220-1 [2], subclause 8.4.2.3.1 shall be carried out.

This test suite applies to all transmitters employing narrow band amplitude modulation for voice applications.

5.1.3.6 Adjacent channel power

The test specified in EN 300 220-1 [2], subclause 8.5.2 shall be carried out.

This test suite applies to transmitters where a channel plan is used with a channel spacing of 25 kHz or less.

5.1.3.7 Range of modulation bandwidth for wide band equipment (> 25 kHz)

The test specified in EN 300 220-1 [2], subclause 8.6.2 shall be carried out.

This test suite applies to transmitters using wide band as defined in EN 300 220-1 [2], subclause 3.1.

5.1.3.8 Spurious emissions

Either:

- the tests specified in EN 300 220-1 [2], subclause 8.7.2 and EN 300 220-1 [2], subclause 8.7.3 shall be carried out; or
- the test specified in EN 300 220-1 [2], subclause 8.7.4 shall be carried out.

This test suite applies to all transmitters.

5.1.3.9 Frequency stability under low-voltage conditions

The test specified in EN 300 220-1 [2], subclause 8.8.2 shall be carried out.

This test suite applies to all battery-operated transmitters.

5.1.4 Receiver test suites

5.1.4.1 Spurious radiations

Either:

- the tests specified in EN 300 220-1 [2], subclause 9.4.2 and EN 300 220-1 [2], subclause 9.4.3 shall be carried out; or
- the test specified in EN 300 220-1 [2], subclause 9.4.4 shall be carried out.

This test suite applies to all receivers.

5.2 Other test specifications

The requirements in subclause 4.2 have been set on the assumption that the test specifications in table 1a will be used to verify the performance of equipment.

Table 1a: Receiver test specifications

Subclause	Performance requirement	Subclause on EN 300 220-1 [2] containing the test method
4.2.1	Spurious radiations	9.4.2 and 9.4.3; or 9.4.4
4.2.2	Adjacent channel selectivity - in band	9.1.2
4.2.3	Adjacent band selectivity	9.2.2
4.2.4	Blocking or desensitization	9.3.2

6 Interpretation of measurement results

The interpretation of the results recorded in the test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit shall be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be separately included in the test report;
- the value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 2.

Table 2: Measurement uncertainty

RF frequency	$\pm 1 \times 10^{-7}$
RF power, conducted	$\pm 0,75$ dB
Maximum frequency deviation:	
- within 300 Hz and 6 kHz of audio frequency	± 5 %
- within 6 kHz and 25 kHz of audio frequency	± 3 dB
Adjacent channel power	± 3 dB
Conducted emission of transmitter, valid up to 12,75 GHz	± 4 dB
Conducted emission of receivers	± 3 dB
Radiated emission of transmitter, valid up to 12,75 GHz	± 6 dB
Radiated emission of receiver, valid up to 12,75 GHz	± 6 dB

For the test methods, according to the present document the uncertainty figures shall be calculated according to the methods described in the ETR 028 [4] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in case where the distributions characterising the actual measurement uncertainties are normal (Gaussian)).

Table 2 is based on such expansion factors.

The particular expansion factor used for the evaluation of the measurement uncertainty shall be stated.

Annex A (informative): Subclauses of the present document relevant for additional essential requirements of relevant EC Council Directives

A.1 Compliance with 99/5/EC (R&TTE Directive) article 3.3e

The subclauses noted are necessary to ensure access to emergency services. At the time of publication, this has not been invoked as an essential requirement of the R&TTE Directive for equipment covered by the present document.

Table A.1: Sub-clauses of the present document relevant to ensure access to emergency services

Clause/sub-clause number and title		Corresponding article of the R&TTE Directive	Qualifying remarks
4.2.2	Adjacent channel selectivity - in band	3.3 e	Applies to Class 1 receivers
4.2.3	Adjacent band selectivity	3.3 e	Applies to Class 1 receivers
4.2.4	Blocking or desensitization	3.3 e	Applies to Class 1 & 2 receivers

A.2 Compliance with 99/5/EC (R&TTE Directive) article 3.3f

The subclauses noted are necessary to facilitate the use of equipment by users with a disability. At the time of publication, this has not been invoked as an essential requirement of the R&TTE Directive for equipment covered by the present document.

Table A.2: Subclauses of the present document relevant in order to facilitate the use of equipment by users with a disability

Clause/subclause number and title		Corresponding article of the R&TTE Directive	Qualifying remarks
4.2.2	Adjacent channel selectivity - in band	3.3 f	Applies to Class 1 receivers
4.2.3	Adjacent band selectivity	3.3 f	Applies to Class 1 receivers
4.2.4	Blocking or desensitization	3.3 f	Applies to Class 1 & 2 receivers

NOTE: Receiver classes are defined in EN 300 220-1 [2] subclause 4.1.1.

History

Document history			
V1.1.1	January 2000	Public Enquiry	PE 200020: 2000-01-19 to 2000-05-19
V1.1.1	July 2000	Vote	V 20000901: 2000-07-03 to 2000-09-01