

ETSI EN 300 396-8-2 V1.1.1 (2001-01)

European Standard (Telecommunications series)

**Terrestrial Trunked Radio (TETRA);
Technical requirements for Direct Mode Operation (DMO);
Part 8: Protocol Implementation Conformance
Statement (PICS) proforma specification;
Sub-part 2: Type 1 repeater Air Interface (AI)**



Reference

DEN/TETRA-02007-8-2

Keywords

ICS, PICS, TETRA, DMO, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction.....	6
1 Scope.....	7
2 References.....	7
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations.....	8
4 Conformance to this PICS proforma specification	8
Annex A (normative): Protocol ICS proforma (PICS) for EN 300 396-4	9
A.1 Guidance for completing the PICS proforma.....	9
A.1.1 Purposes and structure.....	9
A.1.2 Abbreviations and conventions	9
A.1.3 Instructions for completing the PICS proforma	11
A.2 Identification of the implementation.....	11
A.2.1 Date of the statement.....	11
A.2.2 Implementation Under Test (IUT) identification	11
A.2.3 System Under Test (SUT) identification	11
A.2.4 Product supplier	12
A.2.5 Client (if different from product supplier)	12
A.2.6 PICS contact person	12
A.3 Identification of the Protocol.....	13
A.4 Global statement of conformance.....	13
A.5 Roles	13
A.6 Protocols for DM-MS supporting operation with a type 1 DM-REP (MS-REP1).....	13
A.6.1 MS-REP1 Direct Mode Call Control (DMCC) at Layer 3.....	13
A.6.1.1 DMCC major capabilities.....	14
A.6.1.2 Circuit mode call.....	14
A.6.1.3 Circuit mode call set-up	15
A.6.1.4 Circuit mode services offered	15
A.6.1.5 Short data services	16
A.6.1.6 Type of short data service.....	16
A.6.1.7 Data transmission.....	17
A.6.1.8 SDS user defined data	18
A.6.1.9 DMCC PDUs.....	18
A.6.1.10 DMCC constants.....	20
A.6.1.11 DMCC timers	20
A.6.2 MS-REP1 Data link layer (DLL) at Layer 2	21
A.6.2.1 MS-REP1 MAC features.....	21
A.6.2.2 MS-REP1-MAC procedures	22
A.6.2.3 MS-REP1 MAC PDUs.....	26
A.6.2.4 MS-REP1 MAC generated messages.....	27
A.6.2.5 MS-REP1 MAC constants.....	27
A.6.2.6 MS-REP1 MAC timers	29
A.7 Type 1 DM-REP Protocol.....	30
A.7.1 DM-REP1 Data link layer (DLL) at Layer 2	30
A.7.1.1 Major services.....	30
A.7.1.2 DM-REP1 MAC features	30

A.7.1.3	DM-REP1 MAC procedures.....	31
A.7.1.4	DM-REP1 MAC PDUs	33
A.7.1.5	DM-REP1 MAC generated messages	33
A.7.1.6	DM-REP1 MAC constants	33
A.7.1.7	DM-REP1 MAC timers.....	34
A.8.	PDU parameters for MS-REP1 and DM-REP1 used in DMCC at layer 3 and DLL at layer 2	35
A.8.1	MS-REP1 PDU parameters for DMCC at layer 3	35
A.8.1.1	DM-SETUP	35
A.8.1.2	DM-SETUP PRES	36
A.8.1.3	DM-CONNECT.....	36
A.8.1.4	DM-DISCONNECT.....	36
A.8.1.5	DM-CONNECT ACK.....	37
A.8.1.6	DM-OCCUPIED.....	37
A.8.1.7	DM-RELEASE	37
A.8.1.8	DM-TX CEASED.....	38
A.8.1.9	DM-TX REQUEST.....	38
A.8.1.10	DM-TX ACCEPT	38
A.8.1.11	DM-PREEMPT	38
A.8.1.12	DM-PRE ACCEPT	39
A.8.1.13	DM-REJECT	39
A.8.1.14	DM-INFO.....	39
A.8.1.15	DM-SDS UDATA	40
A.8.1.16	DM-SDS DATA	40
A.8.1.17	DM-SDS ACK.....	41
A.8.2	MS-REP1 and DM-REP1 PDU parameters for DLL at layer 2	41
A.8.2.1	DMAC-SYNC in SCH/S.....	41
A.8.2.2	DPRES-SYNC PDU	42
A.8.2.3	DMAC-DATA.....	43
A.8.2.4	DMAC-FRAG	43
A.8.2.5	DMAC-END.....	43
A.8.2.6	DMAC-U SIGNAL.....	44
A.8.3	DM-MAC generated message parameters	44
A.8.3.1	DM-RESERVED	44
A.8.3.2	DM-SDS OCCUPIED.....	44
A.8.3.3	DM-TIMING REQUEST.....	44
A.8.3.4	DM-TIMING ACK.....	44
History		45

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Terrestrial Trunked Radio (TETRA).

The present document had been submitted to Public Enquiry as ETS 300 396-8-2. During the processing for Vote it was converted into an EN.

The present document is part 8 of a multi-part deliverable covering the Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); as identified below:

Part 1: "General network design";

Part 2: "Radio aspects";

Part 3: "Mobile Station to Mobile Station (MS-MS) Air Interface (AI) protocol";

Part 4: "Type 1 repeater air interface";

Part 5: "Gateway air interface";

Part 6: "Security";

Part 7: "Type 2 repeater air interface";

Part 8: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 9: "Service and Description Language (SDL) model";

Part 10: "Managed Direct Mode Operation (DMO)".

National transposition dates	
Date of adoption of this EN:	22 December 2000
Date of latest announcement of this EN (doa):	31 March 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2001
Date of withdrawal of any conflicting National Standard (dow):	30 September 2001

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called an Implementation Conformance Statement (ICS).

1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for TETRA Direct Mode Operation (DMO) Mobile Stations (MS) connected to type 1 repeater (MS-REP1) and for TETRA Direct Mode Operation type 1 repeaters (DM-REP1) Air Interface (AI) protocol, defined in EN 300 396-4 [1] in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [5] and ETS 300 406 [3].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] ETSI EN 300 396-4: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 4: Type 1 repeater air interface".
- [2] ETSI ETS 300 396-8-1: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 8: Protocol Implementation Conformance Statement (PICS) proforma specification; Sub-part 1: Mobile Station to Mobile Station (MS-MS) Air Interface (AI)".
- [3] ETSI ETS 300 406: "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications Standardization Methodology".
- [4] ISO/IEC 9646-1 (1994): "Information technology - Open systems interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [5] ISO/IEC 9646-7 (1995): "Information technology - Open systems interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".
- [6] ETSI ETS 300 396-3 (1998): "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 3: Mobile Station to Mobile Station (MS-MS) Air Interface (AI) protocol".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 300 396-4 [1], ISO/IEC 9646-1 [4], ISO/IEC 9646-7 [5] and the following apply.

Implementation Conformance Statement (ICS): statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented. The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

ICS proforma: document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS

Protocol ICS (PICS): ICS for an implementation or system claimed to conform to a given protocol specification

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ICS	Implementation Conformance Statement
IUT	Implementation Under Test
PICS	Protocol Implementation Conformance Statement
SCS	System Conformance Statement
SUT	System Under Test

4 Conformance to this PICS proforma specification

If it claims to conform to the present document, the actual PICS proforma to be filled in by a supplier shall be technically equivalent to the text of the PICS proforma given in annex A, and shall preserve the numbering/naming and ordering of the proforma items.

A PICS which conforms to the present document shall be a conforming PICS proforma completed in accordance with the guidance for completion given in clause A.1.

Annex A (normative): Protocol ICS proforma (PICS) for EN 300 396-4

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.

A.1 Guidance for completing the PICS proforma

A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in EN 300 396-4 [1] may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into clauses for the following categories of information:

- guidance for completing the PICS proforma;
- identification of the implementation;
- global statement of conformance;
- identification of the roles, MS-REP1 or DM-REP1;
- MS-REP1 layer 3 protocol part;
- MS-REP1 layer 2 protocol part;
- DM-REP1 part (layer 2);
- PDU parameters at layer 3 and layer 2.

A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [5].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Status column

The following notations, defined in ISO/IEC 9646-7 [5], are used for the status column:

- | | |
|-----|---|
| m | mandatory - the capability is required to be supported; |
| o | optional - the capability may be supported or not; |
| n/a | not applicable - in the given context, it is impossible to use the capability; |
| x | prohibited (excluded) - there is a requirement not to use this capability in the given context; |

- | | |
|-----|--|
| o.i | qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies a unique group of related optional items and the logic of their selection which is defined immediately following the table; |
| ci | conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table. |

Reference column

The reference column makes reference to EN 300 396-4 [1], except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [5], are used for the support column:

- | | |
|---------------|---|
| Y or y | supported by the implementation; |
| N or n | not supported by the implementation; |
| N/A, n/a or - | no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status). |

If this PICS proforma is completed in order to describe a multiple-profile support in a system, it is necessary to be able to answer that a capability is supported for one profile and not supported for another. In that case, the supplier shall enter the unique reference to a conditional expression, preceded by "?" (e.g. ?3). This expression shall be given in the space for comments provided at the bottom of the table. It uses predicates defined in the SCS, each of which refers to a single profile and which takes the value TRUE if and only if that profile is to be used.

EXAMPLE: ?3: IF prof1 THEN Y ELSE N.

It is also possible to provide a comment to an answer in the space provided at the bottom of the table.

NOTE: As stated in ISO/IEC 9646-7 [5], support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the type, the list, the range, or the length of values allowed. The following notations are used:

- range of values: <min value> .. <max value>
example: 5 .. 20
- list of values: <value1>, <value2>,, <valueN>
example: 2, 4, 6, 8, 9
example: '1101'B, '1011'B, '1111'B
example: '0A'H, '34'H, '2F'H
- list of named values: <name1>(<val1>), <name2>(<val2>),, <nameN>(<valN>)
example: reject(1), accept(2)
- length: size (<min size> .. <max size>)
example: size (1 .. 8)

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

References to items

For each possible item answer (answer in the support column) within the PICS proforma a unique reference exists, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are discriminated by letters (a, b, etc.), respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table 5 of annex A.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table 6 of annex A.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in clause A.1.2.

If necessary, the supplier may provide additional comments in space at the bottom of the tables, or separately on sheets of paper.

More detailed instructions are given at the beginning of the different clauses of the PICS proforma.

A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

A.2.1 Date of the statement

A.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

IUT version:

A.2.3 System Under Test (SUT) identification

SUT name:

.....

Hardware configuration:

.....

.....
Operating system:
.....

A.2.4 Product supplier

Name:

Address:
.....
.....

Telephone number:.....

Facsimile number:

E-mail address:.....

Additional information:
.....
.....

A.2.5 Client (if different from product supplier)

Name:

Address:
.....
.....

Telephone number:.....

Facsimile number:

E-mail address:.....

Additional information:
.....
.....

A.2.6 PICS contact person

(A person to contact if there are any queries concerning the content of the PICS)

Name:

Telephone number:.....

Facsimile number:

E-mail address:.....

Additional information:

A.3 Identification of the Protocol

This PICS proforma applies to the following standard:

EN 300 396-4 [1]: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 4: Type 1 repeater air interface".

In addition to the physical layer, which is not involved in the PICS description, this standard contains two layers of the protocol stack for the DM-MS operating with a type 1 repeater (MS-REP1), which are Direct Mode Call Control (DMCC) at layer 3 and Data Link Layer (DLL) at layer 2, and one layer only (layer 2) for the type 1 DM-REP protocol.

Each of these three parts is addressed in a different section of the present PICS.

When submitting an implementation for test, the implementer is required to answer the questions of the section(s) of the proforma pertaining to the part(s) of the protocol submitted to the test, i.e. the MS-REP1 and/or the DM-REP1 section.

A.4 Global statement of conformance

Are all mandatory capabilities of the DM-MS for operation with a type 1 DM-REP implemented? (Yes/No/(n/a))

Are all mandatory capabilities of the type 1 Repeater Layer 2 Protocol implemented? (Yes/No/(n/a))

NOTE: Answering "No" to any of these questions indicates non-conformance to the Protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS proforma. Answering "n/a" to any of these questions indicates that the questions related to that part do not apply.

A.5 Roles

The supplier of the implementation shall state the role of the implementation, in table A.1.

Table A.1: Roles

Item	Role	Reference	Status	Support
1	DM-MS supporting operation with a type 1 DM-REP (MS-REP1)	4.1	o.1	
2	Type 1 repeater (Layer 2 protocol of a DM-REP1)	4.1	o.1	

o.1: It is mandatory to support at least one of these items.

A.6 Protocols for DM-MS supporting operation with a type 1 DM-REP (MS-REP1)

A.6.1 MS-REP1 Direct Mode Call Control (DMCC) at Layer 3

This clause is derived from clause A.5 of ETS 300 396-8-1 [2] which contains the PICS for DMCC layer 3 of a regular DM-MS. Complements are added for type 1 repeater, e.g. on table A.17 DMCC constants where two new constants DN304, DN317 are introduced in DMCC layer 3. Note that the whole table numbering is changed, and the PDU descriptions are moved to clause A.8.

A.6.1.1 DMCC major capabilities

The supplier of the MS-REP1 implementation shall state the support of the implementation for each of the following protocol services, in table A.2.

Table A.2: DMCC services

Prerequisite: A.1/1 - MS-REP1				
Item	Service	Reference	Status	Support
1	Circuit mode call	6.2	o.2	
2	Short Data Service (SDS)	6.3	o.2	

o.2: It is mandatory to support at least one of these items.

A.6.1.2 Circuit mode call

The supplier of the implementation shall state the support of the implementation for each of the following circuit mode call protocol features, in table A.3.

Table A.3: Circuit mode protocol features

Prerequisite: A.2/1 - circuit mode call				
Item	Protocol features	Reference	Status	Support
1	Group address call capability	5.2	o.3	
2	Individual address call capability	5.2	o.3	
3	Initiate call set-up without presence check	6.2.1.1	o	
4	Initiate call set-up with presence check	6.2.2.1	o	
5	Accept call set-up without presence check	6.2.1.2	m	
6	Accept call set-up with presence check	6.2.2.2	o	
7	Master end of call transmission	6.2.4.1	c301	
8	Receive end of call transmission	6.2.4.2	m	
9	Master call termination	6.2.4.1, 6.2.5.1	c301	
10	Receive call termination	6.2.4.2, 6.2.5.2	m	
11	Accept call pre-emption	6.2.4.1, 6.2.5.1	c301	
12	Initiate pre-emption in ongoing call	6.2.4.2	o	
13	Initiate a new call by pre-emption	6.2.6	o	
14	Initiate call change-over	6.2.5.2	o	
15	Accept call change-over	6.2.5.1	c301	
16	Late entry by called party	6.2.3.2	o	
17	Receive TPNI in call setup	6.2.4.3	m	
18	Suppress TPNI in call setup	6.2.4.3	o	
19	Receive inter-MNI call	6.2.4.3	m	
20	Initiate inter-MNI call	6.2.4.3	o	

o.3: It is mandatory to support at least one of these items.

c301: IF A.3/3 OR A.3/4 -- If initiation of call set-up with or without presence check supported
 THEN m -- then mandatory
 ELSE n/a

A.6.1.3 Circuit mode call set-up

The supplier of the implementation shall state the support of the implementation for each of the following circuit mode call set-up procedures, in tables A.4 to A.5.

Table A.4: Circuit mode call set-up procedures - Group call

Prerequisite: A.3/1 AND A.3/3 - Initiate group call set-up				
Item	Set-up procedure	Reference	Status	Support
1	Group call address	6.2.1.1	m	
2	Call on temporary group address	6.2.1.3	o	

Table A.5: Circuit mode call set-up procedures - Individual call

Prerequisite: A.3/2 - Individual address call capability				
Item	set-up procedure	Reference	Status	Support
1	Individual call without presence check	6.2.1.1	c501	
2	Individual call with presence check	6.2.2.1	c502	

c501: IF A.3/3 THEN o ELSE n/a -- If initiate call set-up without presence check then optional

c502: IF A.3/4 THEN m ELSE n/a -- If initiate call set-up with presence check then mandatory

A.6.1.4 Circuit mode services offered

The supplier of the implementation shall state the support of the implementation for each of the following circuit mode services, in table A.6

Table A.6: Circuit mode services offered

Prerequisite: A.2/1 - circuit mode call				
Item	Circuit mode service	Reference	Status	Support
1	Circuit mode speech:	5.4	o.4	
2	Circuit mode data unprotected: 7.2	5.4	o.4	
3	Circuit mode data low protection: 4.8, N=1	5.4	o.4	
4	Circuit mode data low protection: 4.8, N=4	5.4	o.4	
5	Circuit mode data low protection: 4.8, N=8	5.4	o.4	
6	Circuit mode data high protection: 2.4, N=1	5.4	o.4	
7	Circuit mode data high protection: 2.4, N=4	5.4	o.4	
8	Circuit mode data high protection: 2.4, N=8	5.4	o.4	
9	Clear mode transmission	5.2	o.5	
10	End to end encrypted transmission	5.2	o.5	
11	Normal priority call	5.4	m	
12	High priority call	5.4	o	
13	Pre-emptive priority call	5.4	o	
14	Emergency pre-emptive priority call	5.4	o	
15	Recent user priority service	5.4	o	

o.4: It is mandatory to support at least one of these items.

o.5: It is mandatory to support at least one of these items.

A.6.1.5 Short data services

The supplier of the implementation shall state the support of the implementation for each of the following short data services, in table A.7.

Table A.7: Short Data Services

Prerequisite: A.2/2 - Short Data Services				
Item	Short data service	Reference	Status	Support
1	Send data (note 1)	6.3.1	o.6	
2	Receive data (note 2)	6.3.2	o.6	
3	Extended error protection (FCS)	6.3.4	m	
NOTE 1: Capability to originate short data transaction as master				
NOTE 2: Capability to receive short data transaction as slave				

o.6: It is mandatory to support at least one of these items.

A.6.1.6 Type of short data service

The supplier of the implementation shall state the support of the implementation for each of the following types of SDSs, in tables A.8 to A.12.

Table A.8: Type of short data service

Prerequisite: A.2/2 - Short Data Services				
Item	Type of short data service	Reference	Status	Support
1	Group address SDS capability	6.3	o.7	
2	Individual address SDS capability	6.3	o.7	
3	Pre-defined short data messages	6.3	o.8	
4	User-defined short data messages	6.3	o.8	
5	OTAR (note)	6.3	o.8	
6	Enable/disable (note)	6.3	o.8	
7	Additional addressing (receive)	6.3.3	c801	
8	Additional addressing (send)	6.3.3	c802	
NOTE: The detailed PICS proforma for DMO security is defined in a separate PICS proforma covering security aspects.				

o.7: It is mandatory to support at least one of these items.

o.8: It is mandatory to support at least one of these items.

c801: IF A.7/2 THEN m ELSE n/a -- If receive SDS supported then mandatory

c802: IF A.7/1 THEN o ELSE n/a -- If send SDS supported then optional

Table A.9: Send short data service on group address

Prerequisite: A.7/1 AND A.8/1 - Group address SDS capability				
Item	SDS on group address	Reference	Status	Support
1	Unacknowledged data service	6.3	m	

Table A.10: Send short data service on individual address

Prerequisite: A.7/1 AND A.8/2 - Individual address SDS capability				
Item	SDS on individual address	Reference	Status	Support
1	Unacknowledged data service	6.3	o.9	
2	Acknowledged data service	6.3	o.9	
3	Extraction of data if included in ACK	6.3	c1001	

o.9: It is mandatory to support at least one of these items.

c1001: IF A.10/2 -- If the sending of acknowledged short data service supported
 THEN m -- then mandatory
 ELSE n/a

Table A.11: Receive short data service on group address

Prerequisite: A.7/2 AND A.8/1 - Group address SDS capability				
Item	SDS on group address	Reference	Status	Support
1	Unacknowledged data service	6.3	m	

Table A.12: Receive short data service on individual address

Prerequisite: A.7/2 AND A.8/2 - Individual address SDS capability				
Item	SDS on individual address	Reference	Status	Support
1	Unacknowledged data service	6.3	o.10	
2	Acknowledged data service	6.3	o.10	
3	Including data in ACK	6.3	o	

o.10: It is mandatory to support at least one of these items.

A.6.1.7 Data transmission

The supplier of the implementation shall state the support of the implementation for each of the following services for sending data, in table A.13.

Table A.13: Sending data services

Prerequisite: A.7/1 - Send data using SDS				
Item	Send data	Reference	Status	Support
1	Send short data on a free channel	6.3.1.1	m	
2	Send short data after pre-emption of a circuit mode call (new call)	6.3.1.2	o	
3	Send short data stealing from circuit mode transmission	6.3.1.3	c1301	
4	Send short data after pre-emption of a circuit mode call (ongoing call)	6.3.1.4.1	c1302	
5	Send short data after changeover of a circuit mode call	6.3.1.4.2	c1302	
6	Send short data as master of a circuit mode call	6.3.1.4.3	c1302	

c1301: IF A.3/3 OR A.3/4 -- If initiate CM call set-up supported
 THEN o -- then optional
 ELSE n/a

c1302: IF A.2/1 -- If CM call supported then optional
 THEN o
 ELSE n/a

A.6.1.8 SDS user defined data

The supplier of the implementation shall state the support of the implementation for each of the following types of SDSs, in table A.14.

Table A.14: SDS user defined data

Prerequisite: A.8/4 - User defined short data				
Item	Circuit mode service	Reference	Status	Support
1	User defined data 1 (16 bits)	5.4	o.11	
2	User defined data 2 (32 bits)	5.4	o.11	
3	User defined data 3 (64 bits)	5.4	o.11	
4	User defined data 4 (up to 2047 bits)	5.4	o.11	

o.11: It is mandatory to support at least one of these items.

A.6.1.9 DMCC PDUs

The supplier of the implementation shall state the support of the implementation for each of the following circuit mode and SDS PDUs, in tables A.15 to A.16.

Table A.15: Circuit Mode call and pre-emption PDUs

Item	PDU	Reference from ETS 300 396-3 [6]	Sending		Receiving	
			Status	Support	Status	Support
1	DM-SETUP	9.5.1	c1501		c1502	
2	DM-SETUP PRES	9.5.2	c1503		c1504	
3	DM-CONNECT	9.5.3	c1504		c1503	
4	DM-DISCONNECT	9.5.4	c1504		c1503	
5	DM-CONNECT ACK	9.5.5	c1503		c1504	
6	DM-OCCUPIED	9.5.6	c1505		c1502	
7	DM-RELEASE	9.5.7	c1505		c1502	
8	DM-TX CEASED	9.5.8	c1505		c1502	
9	DM-TX REQUEST	9.5.9	c1506		c1505	
10	DM-TX ACCEPT	9.5.10	c1505		c1512	
11	DM-PREEMPT	9.5.11	c1507		c1511	
12	DM-PRE ACCEPT	9.5.12	c1511		c1513	
13	DM-REJECT	9.5.13	c1509		c1510	
14	DM-INFO	9.5.14	c1508		c1502	

c1501:	IF A.3/1 OR A.5/1 THEN m ELSE n/a	-- If group call or individual call setup without presence check -- supported then mandatory
c1502:	IF A.2/1 THEN m ELSE n/a	-- If circuit mode call supported -- then mandatory
c1503:	IF A.5/2 THEN m ELSE n/a	-- If individual call setup with presence check supported -- then mandatory
c1504:	IF A.3/6 THEN m ELSE n/a	-- If accept of call set-up with presence check supported -- then mandatory
c1505:	IF A.3/3 OR A.3/4 THEN m ELSE n/a	-- If initiate call set-up with or without presence check supported -- then mandatory
c1506:	IF A.3/14 OR A.13/5 THEN m ELSE n/a	-- If CM or SDS call changeover supported -- then mandatory

c1507:	IF A.3/10 OR A.3/13 OR A.13/2 OR A.13/4 THEN m ELSE n/a	-- If initiation of CM or SDS pre-emption is supported -- then mandatory
c1508:	IF A.3/18 THEN m ELSE o	-- If sending of TPNI can be suppressed then -- mandatory else -- optional
c1509:	IF A.3/3 OR A.3/4 THEN m ELSE IF A.12/2 OR A.12/3. THEN o ELSE n/a	-- If initiate CM call supported -- then mandatory -- If receive acknowledged SDS supported -- then optional
c1510:	IF A.2/1 OR A.10/2 OR A.10/3 THEN m ELSE n/a	-- If circuit mode call or send acknowledged short data -- supported -- then mandatory
c1511:	IF A.3/3 OR A.3/4 OR A.7/1 THEN m ELSE n/a	-- If initiation of CM or SDS call -- supported -- then mandatory
c1512:	IF A.2/1 OR A.13/5 THEN m ELSE n/a	-- If circuit mode call or send SDS after changeover supported -- then mandatory
c1513:	IF A.2/1 OR A.13/2 OR A.13/4 THEN m ELSE n/a	-- If circuit mode call or send SDS after pre-emption supported -- then mandatory

Table A.16: Specific SDS PDUs

Prerequisite: A.2/2 - Short Data Services						
Item	PDU	Reference from document ETS 300 396-3 [6]	Sending		Receiving	
			Status	Support	Status	Support
1	DM-SDS UDATA	9.5.15	c1601		c1603	
2	DM-SDS DATA	9.5.16	c1602		c1604	
3	DM-SDS ACK	9.5.17	c1604		c1602	

c1601:	IF A.9/1 OR A.10/1 THEN m ELSE n/a	-- If sending of unacknowledged SDS with group or individual address -- supported then mandatory
c1602:	IF A.10/2 OR A.10/3 THEN m ELSE n/a	-- If sending of acknowledged data service with or without data in ACK -- supported then mandatory
c1603:	IF A.11/1 OR A.12/1 THEN m ELSE n/a	-- If receiving of unacknowledged supported -- then mandatory
c1604:	IF A.12/2 OR A.12/3 THEN m ELSE n/a	-- If receiving of acknowledged data service supported -- then mandatory

A.6.1.10 DMCC constants

The supplier of the implementation shall state the support of the implementation for each of the following DMCC constants, in table A.17.

Table A.17: DMCC constants

Item	Constants	Reference	Status	Support	Value ranges	
					Allowed	Supported
1	DN303 -- DM-SETUP PRES -- retries	A.2	c.1701		1..3	
2	DN314 -- DM-SDS UDATA -- retries	A.2	c.1702		1..6	
3	DN315 -- DM-SDS DATA -- retries on -- negative response	A.2	c.1703		2..6	
4	DN316 -- DM-SDS DATA -- retries on no -- response	A.2	c.1703		1..4	
5	DN304 -- DM-SETUP or DM-SETUP PRES -- retries on DM- -- REP1 link failure	A.2	c.1704		1..3	
6	DN317 -- DM-SDS DATA or -- DM-SDS UDATA -- retries on DM- -- REP1 link failure	A.2	c.1705		1..3	

- c.1701: IF A.5/2 THEN m ELSE n/a -- If call set-up with presence check supported then
-- mandatory
- c.1702: IF A.9/1 OR A.10/1 -- If unacknowledged SDS supported for
THEN m ELSE n/a -- group or individual address then mandatory
- c.1703: IF A.10/2 OR A.10/3 -- If acknowledged SDS supported with or without
THEN m ELSE n/a -- data in ACK then mandatory
- c.1704: IF A.2/3 OR A.2/4 -- If initiate call set-up without presence OR with presence check
THEN m ELSE n/a -- then mandatory
- c.1705: IF A.6/1 THEN m -- If Send Data then mandatory
ELSE n/a

A.6.1.11 DMCC timers

The supplier of the implementation shall state the support of the implementation for each of the following DMCC timers, in table A.18.

Table A.18: DMCC timers

Item	Timer	Reference	Status	Support	Values	
					Default	Supported
1	DT303 -- Wait DM- -- SETUP -- PRES -- response	A.1	c1801		250 -- mSec	
2	DT307 -- Wait DM- -- CONNECT -- ACK	A.1	c1802		350 -- mSec	
3	DT311 -- Call -- transaction -- time	A.1	c1803		300 -- Sec	
4	DT314 -- SDS failure -- timer	A.1	c1804		500 -- mSec	
5	DT316 -- Wait DM- -- SDS DATA -- response	A.1	c1805		400 -- mSec	

c1801: IF A.3/4 -- If initiation of call set-up with presence check supported
 THEN m -- then mandatory
 ELSE n/a

c1802: IF A.3/6 -- If accept call set-up with presence check supported
 THEN m -- then mandatory
 ELSE n/a

c1803: IF A.3/3 OR A.3/4 -- If initiate CM call set-up supported
 THEN m -- then mandatory
 ELSE n/a

c1804: IF A.7/1 -- If SDS send data supported
 THEN m -- then mandatory
 ELSE n/a

c1805: IF A.10/2 OR A.10/3 -- If acknowledged SDS supported with or without
 THEN m -- data in ACK. then mandatory
 ELSE n/a

A.6.2 MS-REP1 Data link layer (DLL) at Layer 2

A.6.2.1 MS-REP1 MAC features

The supplier of the implementation shall state the support of the implementation for each of the following MS-REP1 MAC features, in table A.19.

Table A.19: MS-REP1 MAC features

Prerequisite: A.1/1 – MS-REP1				
Item	Feature	Reference	Status	Support
1	Scrambling mechanism	8.2.4	m	
2	PDU error detection	8.2.5	m	
3	Stealing mechanism	8.2.6.2.2	c1901	
4	MS-REP1 channel usage procedures	8.4	m	
5	Signalling messages procedures	8.5	m	
6	Traffic mode procedures	8.6	c1902	

c1901: IF A.3/3 OR A.3/4 -- If initiation of call set-up with or without presence check
 THEN m -- supported then mandatory
 ELSE o -- else optional

c1902: IF A.2/1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a

A.6.2.2 MS-REP1-MAC procedures

The supplier of the implementation shall state the support of the implementation for each of the following MAC procedures, in tables A.20 to A.26.

Table A.20: MS-REP1 channel usage procedures

Item	MS-REP1 channel procedure	Reference	Status	Support
1	MS-REP type 1A channel arrangement	8.4.1.1	o.12	
2	MS-REP type 1B channel arrangement	8.4.1.1	o.12	
3	MS-REP1 channel operation	8.4.1.2	m	
4	Determination of MS-REP1 channel state	8.4.2	m	
5	Slave MS-REP1 channel surveillance procedure	8.4.2.4	m	
6	Master MS-REP1 channel surveillance during a call	8.4.2.3	c2001	
7	MS-REP1 channel monitoring procedures	8.4.4	m	
8	Transmission of layer 3 messages procedures	8.4.5	c2003	
9	Transmission of layer 2 messages procedures	8.4.6	c2003	
10	MS-REP1 dual watch	8.4.7.10, 8.3.1	o	
11	Air interface encryption	8.4.7.11	o	
12	MS-REP1 channel A operation only	8.4.7.12	m	
13	Short data within circuit mode	8.4.7.13	c2007	
14	SDS time remaining	8.4.7.14	c2004	
15	Timing change procedure	8.4.7.15	c2005	
16	Timing change at changeover or pre-emption for requesting MS-REP1	8.4.7.16	c2006	

o.12: It is mandatory to support at least one of these items.

c2001: IF A.3/3 OR A.3/4 OR A.7/1 -- If CM call initiate or SDS send supported
 THEN m -- then mandatory
 ELSE n/a

c2003: IF (A.3/3 OR A.3/4 OR A.3/6) -- If CM call initiate or accept call with presence check
 OR A.7/1 OR A.12/2 -- or SDS send or receive acknowledged short data
 OR A.12/3 -- supported
 THEN m -- then mandatory
 ELSE n/a

c2004: IF A.7/1 -- If send SDS supported
 THEN m -- then mandatory
 ELSE n/a

c2005: IF A.3/3 OR A.3/4 -- If CM call set-up with or without presence check supported
 THEN o -- then optional
 ELSE n/a

c2006: IF A.3/12 OR A.3/13 OR A.3/14 -- If changeover or pre-emption for CM call or SDS data
 OR A.13/2 OR A.13/4 -- supported then optional
 OR A.13/5
 THEN o
 ELSE n/a

c2007: IF A.7/1 -- If send SDS supported
 THEN o -- then optional
 ELSE n/a

Table A.21: MS-REP1 channel monitoring procedures

Item	MS-REP1 monitoring procedures	Reference	Status	Support
1	MS-REP1 channel monitoring during call set-up	8.4.4.1	c2103	
2	MS-REP1 channel monitoring during new call transaction	8.4.4.1	c2103	
3	MS-REP1 channel monitoring during call set-up with presence check	8.4.4.2	c2101	
4	MS-REP1 channel monitoring in occupation during circuit mode call as slave	8.4.4.3	c2104	
5	MS-REP1 channel monitoring in occupation during circuit mode call as master	8.4.4.3	c2103	
6	MS-REP1 channel monitoring in reservation during circuit mode call as slave	8.4.4.4	c2104	
7	MS-REP1 channel monitoring in reservation during circuit mode call as master	8.4.4.4	c2103	
8	MS-REP1 channel monitoring in occupation during SDS call	8.4.4.5	c2105	
9	MS-REP1 channel usage monitoring during pre-emption signalling	8.4.4.6	c2106	
10	Monitoring MS-REP1 channel usage during timing change request signalling	8.4.4.7	c2107	

c2101:	IF A.5/2 THEN m ELSE n/a	-- If call set-up with presence check supported then -- mandatory
c2102:	IF A.3/6 THEN m ELSE n/a	-- If accept call set-up with presence check supported -- then mandatory
c2103:	IF A.3/3 OR A.3/4 THEN m ELSE n/a	-- If initiate circuit mode call set-up supported -- then mandatory
c2104:	IF A.2/1 THEN m ELSE n/a	-- if CM call supported -- then mandatory
c2105:	IF A.7/1 THEN m ELSE n/a	-- If send data using SDS supported -- then mandatory
c2106:	IF A.3/10 OR A.3/13 THEN m ELSE n/a	-- If Initiate pre-emption in ongoing call or new call -- supported then mandatory
c2107:	IF A.28/3 THEN m ELSE n/a	-- If PDU MS-REP1-TIMING REQUEST supported -- then mandatory

Table A.22: MS-REP1 MAC signalling messages

Item	Signalling messages procedure	Reference	Status	Support
1	Addressing in synchronization burst	8.5.2.1.1	c2201	
2	Addressing in normal burst	8.5.2.1.2	c2201	
3	Air Interface encryption	8.5.3	c2202	
4	Reception of message	8.5.2.2	m	
5	Fragmentation started by DMAC-SYNC PDU	8.5.4.1	c2203	
6	Reconstruction started by DMAC-SYNC PDU	8.5.4.2	c2204	
7	Fill bit addition	8.5.5.1	c2201	
8	Fill bit deletion	8.5.5.2	m	
9	Null PDU flag use	8.5.5.3	o	
10	Null PDU flag recognition	8.5.5.3	m	
11	Transmission of message by layer 2 unacknowledged service	8.5.6.1	c2201	

- c2201: IF A.3/3 OR A.3/4 OR A.3/6 -- If CM call initiate or accept call with presence check
OR A.7/1 OR A.12/2 -- or SDS send or receive acknowledged short data
OR A.12/3 -- supported
THEN m -- then mandatory
ELSE n/a
- c2202: IF A.8/5 THEN m ELSE n/a -- If OTAR supported then mandatory
- c2203: IF A.7/1 OR A.12/3 -- If sending short data service or including short data in ACK
THEN o -- supported then optional
ELSE n/a
- c2204: IF A.7/2 OR A.10/3 -- If receiving short data or extraction of data in ACK
THEN m -- supported then mandatory
ELSE n/a

Table A.23: MS-REP1 MAC reception of messages by layer 2 unacknowledged service

Item	Use of frame countdown element in received message	Reference	Status	Support
1	Suppression of duplicate messages	8.5.6.2	m	
2	Delaying switch into traffic mode	8.5.6.2	c2301	
3	Timing of set-up signalling for pre-emption or changeover	8.5.6.2	c2302	
4	Timing of immediate SDS retransmission	8.5.6.2	c2303	
5	Timing of response to message from master	8.5.6.2	c2304	
6	Timing of response to fragmented message from master	8.5.6.2	c2305	
7	Timing of DM-CONNECT ACK	8.5.6.2	c2306	

- c2301: IF A.2/1 THEN m ELSE n/a -- If circuit mode call supported then mandatory
- c2302: IF A.3/10 OR A.3/11 OR A.3/13 OR -- If CM or SDS pre-emption in ongoing or new
A.13/2 OR A.13/4 OR A.13/5 -- call or changeover supported
THEN m -- then mandatory
ELSE n/a
- c2303: IF A.10/2 OR A.10/3 -- If sending acknowledged SDS data service with or
THEN m -- without data in ACK supported then mandatory
ELSE n/a
- c2304: IF A.3/6 OR A.12/2 OR A.12/3 -- If accept call set-up with presence check and
THEN m -- receive acknowledge SDS then mandatory
ELSE n/a
- c2305: IF A.22/5 AND (A.12/2 OR A.12/3) -- If reconstruction and SDS acknowledged
THEN m -- data service with or without data in ACK
ELSE n/a -- supported then mandatory

c2306: IF A.5/2 THEN m ELSE n/a -- If call set-up with presence check supported
-- then mandatory

Table A.24: MS-REP1 MAC random access master MS procedures

Item	Procedure	Reference	Status	Support
1	Indication of frames available for request	8.5.7.2.1	c2401	
2	Monitoring frames available for requests	8.5.7.2.2	c2402	
3	Response to pre-emption or changeover request	8.5.7.2.3	c2402	
4	Response to timing change request	8.5.7.2.4	c2401	

c2401: IF A.3/3 OR A.3/4 -- If CM initiate call set-up supported
THEN m -- then mandatory
ELSE n/a

c2402: IF (A.3/3 OR A.3/4) OR A.7/1 -- If CM initiate call set-up or SDS data send supported
THEN m -- then mandatory
ELSE n/a

Table A.25: MS-REP1 MAC random access requesting MS procedures

Item	Procedure	Reference	Status	Support
1	Preparation for random access	8.5.7.3.1	c2501	
2	First transmission of request	8.5.7.3.2	c2501	
3	Valid access slots	8.5.7.3.3	c2501	
4	Wait for response	8.5.7.3.4	c2501	
5	Subsequent transmission of request	8.5.7.3.5	c2501	
6	Abandon random access attempt	8.5.7.3.6	c2501	

c2501: IF A.3/3 OR A.3/4 OR -- If CM initiate call set-up or SDS pre-emption or SDS changeover
A.13/2 OR A.13/4 OR -- or MS-REP1-TIMING REQUEST PDU supported
A.13/5 OR A.28/3
THEN m -- then mandatory
ELSE n/a

Table A.26: MS-REP1 MAC traffic mode procedures

Prerequisite: A.1/1 - Circuit mode call				
Item	Feature	Reference	Status	Support
1	Enter U-plane mode for call set-up without presence check - outgoing call	8.6.3.1.1	c2601	
2	Enter U-plane mode for call set-up without presence check - incoming call	8.6.3.1.2	c2602	
3	Enter U-plane mode for call set-up with presence check - outgoing call	8.6.3.2.1	c2603	
4	Enter U-plane mode for call set-up with presence check - incoming call	8.6.3.2.2	c2604	
5	Leaving U-plane mode - Master MS	8.6.3.4.1	c2605	
6	Leaving U-plane mode - Slave MS	8.6.3.4.2	c2607	
7	Stealing from circuit mode capacity - transmission on STCH	8.6.5.1	c2605	
8	Stealing from circuit mode capacity - reception on STCH	8.6.5.3	c2607	
9	Fragmentation on STCH	8.5.4.1	c2606	
10	Reconstruction on STCH	8.5.4.2	c2607	

c2601:	IF A.3/3 THEN m ELSE n/a	-- If call set-up without presence check supported -- then mandatory
c2602:	IF A.3/5 THEN m ELSE n/a	-- If accept call set-up without presence check supported -- then mandatory
c2603:	IF A.5/2 THEN m ELSE n/a	-- If initiate call set-up with presence check supported -- then mandatory
c2604:	IF A.3/6 a THEN m ELSE n/	-- If accept call set-up with presence check supported -- then mandatory
c2605:	IF A.3/3 OR A.3/4 THEN m ELSE n/a	-- If initiate CM call set-up supported -- then mandatory
c2606:	IF A.3/3 OR A.3/4 THEN o ELSE n/a	-- If initiate CM call set-up supported -- then optional
c2607:	IF A.3/5 OR A.3/6 THEN m ELSE n/a	-- If accept call set-up with or without presence check supported -- then mandatory

A.6.2.3 MS-REP1 MAC PDUs

The supplier of the implementation shall state the support of the implementation for each of the following MAC PDUs, in table A.27.

Table A.27: MS-REP1 MAC PDUs

Item	PDU	Reference	Sending		Receiving	
			Status	Support	Status	Support
1	DMAC-SYNC	10.1.1	m		m	
2	DPRES-SYNC	10.1.2	n/a		o	
3	DMAC-DATA	10.2	c2701		m	
4	DMAC-FRAG	10.2	c2702		c2703	
5	DMAC-END	10.2	c2702		c2703	
6	DMAC-U SIGNAL	10.2	c2704		c2705	
7	DMAC-TRAFFIC	10.2	c2704		c2705	

c2701:	IF A.3/3 OR A.3/4 OR A.3/6 OR A.7/1 OR A.12/2 OR A.12/3 THEN m ELSE n/a	-- If CM call initiate or accept call with presence check -- or SDS send or receive acknowledged short data -- supported -- then mandatory
c2702:	IF A.22/5 OR A.26/9 THEN m ELSE n/a	-- If fragmentation supported -- then mandatory
c2703:	IF A.22/6 OR A.26/10 THEN m ELSE n/a	-- If reconstruction supported -- then mandatory
c2704:	IF A.3/3 OR A.3/4 THEN m ELSE n/a	-- If initiate CM call set-up supported -- then mandatory
c2705:	IF A.2/1 THEN m ELSE n/a	-- If circuit mode call supported then mandatory

A.6.2.4 MS-REP1 MAC generated messages

The supplier of the implementation shall state the support of the implementation for each of the following MS-REP1-MAC generated messages, in table A.28.

Table A.28: MS-REP1 MAC generated messages

Item	MAC generated message	Reference	Sending		Receiving	
			Status	Support	Status	Support
1	DM-RESERVED	10.4	c2801		m	
2	DM-SDS OCCUPIED	10.4	c2803		m	
3	DM-TIMING REQUEST	10.4	c2804		m	
4	DM-TIMING ACK	10.4	c2802		c2804	

- c2801: IF A.3/3 OR A.3/4 -- If initiate CM call set-up supported
 THEN m -- then mandatory
 ELSE n/a
- c2802: IF A.2/1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a
- c2803: IF A.7/1 -- If send short data service supported
 THEN m -- then mandatory
 ELSE n/a
- c2804: IF A.20/15 -- If timing change procedure supported
 THEN m -- then mandatory
 ELSE n/a

A.6.2.5 MS-REP1 MAC constants

The supplier of the implementation shall state the support of the implementation for each of the following MS-REP1-MAC constants, in tables A.29 and A.30.

Table A.29: MS-REP1 MAC constants

Item	Constant	Reference	Status	Support	Values	
					Default /Range	Supported
1	DN204 (min)	A.4	c2901		1	
2	DN205 (max)	A.4	c2901		8	
3	DN206 (min)	A.4	c2902		8	
4	DN207 (max)	A.4	c2902		12	
5	DN208	A.4	c2903		2 .. 8	
6	DN209	A.4	c2904		2 .. 8	
7	DN210	A.4	c2905		3	
8	DN212	A.4	c2906		2	
9	DN213	A.4	c2907		8	
10	DN232	A.4	c2903		2/2 .. 4	
11	DN233	A.4	c2906		2/2 .. 4	

- c2901: IF A.3/3 OR A.3/4 OR A.7/1 -- If initiate CM call set-up or SDS send data supported
 THEN m -- then mandatory
 ELSE n/a
- c2902: IF A.3/4 OR A.10/2 OR A.10/3 -- If initiate CM call set-up with presence check or send SDS
 THEN m -- acknowledged data with or without data in ACK then
 ELSE n/a -- mandatory
- c2903: IF A.3/3 OR A.3/4 -- If initiate CM call set-up with or without presence check
 THEN m -- supported then mandatory
 ELSE n/a

- c2904: IF A.2/1 OR A.7/2
THEN m -- If CM call supported or SDS receive data supported
ELSE n/a -- then mandatory
- c2905: IF A.3/6 OR A.12/2 OR A.12/3
THEN m -- If CM call receive with presence check supported or
ELSE n/a -- receive acknowledged SDS with or without data
-- in ACK supported then mandatory
- c2906: IF A.10/2 OR A.10/3
THEN m -- If send SDS data with or without data in ACK supported
ELSE n/a -- then mandatory
- c2907: IF A.25/6
THEN m -- If MAC abandon random access procedure supported
ELSE n/a -- then mandatory

Table A.30: MS-REP1 MAC number of frame transmissions

Item	Message type	Reference	Status	Support	Values	
					Allowed	Supported
1	DM-SETUP (new call setup)	A.5	c3001		2 .. 4	
2	DM-SETUP (continuation of ongoing call)	A.5	c3001		1 .. 4	
3	DM-SETUP PRES (new call setup)	A.5	c3002		2 .. 4	
4	DM-SETUP PRES (continuation of ongoing call)	A.5	c3002		1 .. 4	
5	DM-CONNECT	A.5	c3003		1 .. DN210	
6	DM-DISCONNECT	A.5	c3003		1 .. DN210	
7	DM-CONNECT ACK	A.5	c3002		1 .. 4	
8	DM-TX CEASED	A.5	c3004		2 .. 4	
9	DM-RELEASE	A.5	c3004		2 .. 4	
10	DM-TX ACCEPT	A.5	c3004		2 .. 4	
11	DM-PRE ACCEPT	A.5	c3005		2 .. 4	
12	DM-REJECT	A.5	c3006		1 .. 4	
13	DM-TIMING ACK (during occupation)	A.5	c3007		1 .. 4	
14	DM-TIMING ACK (during reservation for rejection)	A.5	c3007		1 .. 4	
15	DM-TIMING ACK (during reservation for acceptance)	A.5	c3007		2 .. 4	
16	DM-SDS DATA (DSB) (new call set-up)	A.5	c3008		2 .. 4	
17	DM-SDS DATA (DSB) (continuation of ongoing call)	A.5	c3008		1 .. 4	
18	DM-SDS UDATA (DSB) (new call set-up)	A.5	c3009		2 .. 4	
19	DM-SDS UDATA (DSB) (continuation of ongoing call)	A.5	c3009		1 .. 4	
20	DM-SDS ACK (fragmentation)	A.5	c3010		1 .. DN210	

- c4301: IF A.3/3
THEN m -- If initiate CM call without presence check supported
ELSE n/a -- then mandatory
- c4302: IF A.3/4
THEN m -- If initiate CM call with presence check supported
ELSE n/a -- then mandatory
- c4303: IF A.3/6
THEN m -- If accept call set-up with presence check supported
ELSE n/a -- then mandatory
- c4304: IF A.3/3 OR A.3/4
THEN m -- If initiate CM call with or without presence check supported
ELSE n/a -- then mandatory
- c4305: IF A.3/3 OR A.3/4 OR A.7/1
THEN m -- If initiate CM call or send SDS data supported
ELSE n/a -- then mandatory

c4306:	IF A.3/3 OR A.3/4 THEN m ELSE IF A.12/2 OR A.12/3 THEN o ELSE n/a	-- If initiate CM call supported -- then mandatory -- If receive acknowledged SDS supported -- then optional
c4307:	IF A.20/9 THEN m ELSE n/a	-- If timing change procedure supported -- then mandatory
c4308:	IF A.10/2 OR A.10/3 THEN m ELSE n/a	-- If acknowledged data service with or without data in ACK -- supported then mandatory
c4309:	IF A.9/1 OR A.10/1 THEN m ELSE n/a	-- If unacknowledged SDS with group or individual -- address supported then mandatory
c4310:	IF A.12/2 OR A.12/3 THEN m ELSE n/a	-- If receive acknowledged SDS supported -- then mandatory

A.6.2.6 MS-REP1 MAC timers

The supplier of the implementation shall state the support of the implementation for each of the following MS-REP1-MAC timers, in table A.31.

Table A.31: MS-REP1 MAC timers

Item	Timer	Reference	Status	Support	Values	
					Default	Supported
1	DT205	A.3	c3101		18 -- frames	
2	DT207	A.3	m		90 -- frames	
3	DT210	A.3	c3102		4 -- frames	
4	DT211	A.3	c3103		3 -- frames	
5	DT212	A.3	o		7 -- frames	
6	DT213	A.3	c3104		5 .. 60 -- multiframes	
7	DT214	A.3	c3105		36 -- frames	
8	DT221	A.3	c3106		90 --frames	
9	DT225	A.3	c3106		90 --frames	

c3101:	IF A.3/3 OR A.3/4 OR A.7/1 THEN m ELSE n/a	-- If initiate CM call set-up or SDS send data supported -- then mandatory
c3102:	IF A.10/2 OR A.10/3 THEN m ELSE n/a	-- If acknowledged SDS with or without data in ACK -- supported then mandatory
c3103:	IF A.25/4 THEN m ELSE n/a	-- If random access wait for response supported -- then mandatory
c3104:	IF A.25/6 THEN m ELSE n/a	-- If abandon random access attempt supported -- then mandatory
c3105:	IF A.25/3 THEN m ELSE n/a	-- If valid access slot supported -- then mandatory
c3106:	IF A.112/1 THEN m ELSE n/a	-- If circuit mode call supported -- then mandatory

A.7 Type 1 DM-REP Protocol

A.7.1 DM-REP1 Data link layer (DLL) at Layer 2

A.7.1.1 Major services

The supplier of the DM-REP1 implementation shall state the support of the implementation for each of the following protocol services, in table A.32.

Table A.32: Type 1 DM-REP services

Prerequisite: A.1/2 - Type1 DM-REP				
Item	Service	Reference	Status	Support
1	Circuit mode call		o.13	
2	Short Data Service (SDS)		o.13	

o.13: It is mandatory to support at least one of these items.

NOTE: A DM-REP1 has no layer 3 protocol, where these options are defined. The consequence is that there is no explicit reference in the specification for the table above.

When one of these options is declared supported, the whole functionality is supposed to be supported. For instance, there are no further options for the support of presence check, or acknowledged data, or data fragmentation.

A.7.1.2 DM-REP1 MAC features

The supplier of the implementation shall state the support of the implementation for each of the following DM-REP1 MAC features, in table A.33

Table A.33: DM-REP1 MAC features

Item	Feature	Reference	Status	Support
1	Scrambling mechanism	9.2	m	
2	PDU error detection via CRC	9.2	m	
3	Reception/regeneration/retransmission of messages	9.1	m	
4	Reception/retransmission of traffic	9.1	m	
5	Stealing mechanism	9.2	m	
6	DM channel usage procedures	9.4	m	
7	Procedures for retransmission of signalling messages	9.5	m	
8	Traffic mode procedures	9.6	c3301	
9	DM-REP physical layer of Type 1A	9.3	o.14	
10	DM-REP physical layer of Type 1B	9.3	o.14	

o.14: It is mandatory to support at least one of these items.

c3301: IF A.32 /1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a

A.7.1.3 DM-REP1 MAC procedures

The supplier of the implementation shall state the support of each of the following MAC procedures, in tables A.34 to A.39.

Table A.34: DM-REP1 channel usage procedures

Item	DM-REP1 channel procedure	Reference	Status	Support
1	DM-REP type 1A channel structure	9.4.1.1	c3401	
2	DM-REP type 1B channel structure	9.4.1.1	c3402	
3	DM-REP1 channel synchronization	9.4.1.2	m	
4	Determination of DM-REP1 channel state	9.4.2	m	
5	DM-REP1 channel surveillance procedure when idle on a free channel	9.4.2.2.1	m	
6	DM-REP1 channel surveillance procedure when idle at MS-REP1call set-up	9.4.2.2.2	m	
7	DM-REP1 channel surveillance procedure when idle on a free channel	9.4.2.2.3	m	
8	DM-REP1 channel surveillance procedure when call active	9.4.2.3	m	
9	Criteria for changing DM-REP1 channel state	9.4.3	m	
10	DM-REP1 channel monitoring procedures	9.4.4	m	
11	DM-REP1 presence signal on free channel	9.4.5.1	m	
12	DM-REP1 presence signal on channel in occupation	9.4.5.2	m	
13	DM-REP1 presence signal on channel in reservation	9.4.5.3	m	
14	DM-REP1 linearization	9.4.6	m	

c3401: IF A.33/9 -- If Type 1A DM-REP supported
 THEN m -- then mandatory
 ELSE n/a

c3402: IF A.33/10 -- If Type 1B DM-REP supported
 THEN m -- then mandatory
 ELSE n/a

Table A.35: DM-REP1 channel monitoring procedures

Item	MS-REP1 monitoring procedures	Reference	Status	Support
1	DM channel monitoring during call set-up with presence check	9.4.4.1	c3501	
2	DM channel in occupation during circuit mode call	9.4.4.2	c3501	
3	DM channel in reservation during circuit mode call	9.4.4.3	c3501	
4	DM channel in occupation during SDS call	9.4.4.4	c3502	
5	DM channel following pre-emption or changeover acceptance	9.4.4.5	c3501	
6	DM channel following timing change announcement	9.4.4.6	m	

c3501: IF A.32 /1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a

c3502: IF A.32 /2 -- If SDS supported
 THEN m -- then mandatory
 ELSE n/a

Table A.36: DM-REP1 procedures for retransmission of signalling messages from master MS

Item	Retransmission procedure	Reference	Status	Support
1	Signalling messages received from the master MS-REP1 in a DSB	9.5.1.1	m	
2	Signalling messages received from the master MS-REP1 in a DNB	9.5.1.2	m	
3	Regeneration of additional repetitions on slave link	9.5.1.3	0	

Table A.37: DM-REP1 procedures for retransmission of signalling messages from slave MS

Item	Retransmission procedure	Reference	Status	Support
1	Re-transmission of DMAC-SYNC	9.5.2.1	m	
2	Re-transmission of response msg	9.5.2.2	m	
3	Re-transmission of random access request	9.5.2.3	m	

Table A.38: DM-REP1 signalling mechanisms

Item	Signalling mechanisms	Reference	Status	Support
1	Frame countdown procedure	9.5.3.1	m	
2	Fill bit addition	9.5.3.2	m	
3	Fill bit deletion	9.5.3.2	m	
4	Null PDU flag use	9.5.3.3	o	
5	Null PDU flag recognition	9.5.3.3	m	
6	Air Interface encryption	9.5.3.4	c3801	
7	Timing change procedure	9.5.3.5	m	
8	Random access procedure	9.5.3.6	m	

c3801: IF security THEN m ELSE n/a -- If security (OTAR) supported then mandatory

Table A.39: DM-REP1 traffic mode procedures

Item	Feature	Reference	Status	Support
1	Change of U-plane mode for call set-up without presence check	9.6.2.1	c3901	
2	Change of U-plane mode for call set-up with presence check	9.6.2.2	c3901	
3	Change of U-plane mode - end of traffic transmission	9.6.2.3	c3901	
4	Traffic mode: Reception of TCH and STCH on the master link	9.6.3.1	m	
5	Traffic mode: Re-transmission of TCH and STCH on the slave link	9.6.3.2	m	

c3901: IF A.32 /1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a

A.7.1.4 DM-REP1 MAC PDUs

The supplier of the implementation shall state the support of the implementation for each of the following MAC PDUs, in table A.40.

Table A.40: DM-REP1 MAC PDUs

Item	PDU	Reference	Sending		Receiving	
			Status	Support	Status	Support
1	DMAC-SYNC	10.1.1	m		m	
2	DPRES-SYNC	10.1.2	o		n/a	
3	DMAC-DATA	10.2	m		m	
4	DMAC-FRAG	10.2	m		m	
5	DMAC-END	10.2	m		m	
6	DMAC-U SIGNAL	10.2	m		m	
7	DMAC-TRAFFIC	10.2	m		m	

A.7.1.5 DM-REP1 MAC generated messages

The supplier of the implementation shall state the support of the implementation for each of the following DM-REP1 MAC generated messages, in table A.41.

Table A.41: DM-REP1 MAC generated messages

Item	MAC generated message	Reference	Sending		Receiving	
			Status	Support	Status	Support
1	DM-RESERVED	10.4	c4101		m	
2	DM-SDS OCCUPIED	10.4	c4102		m	
3	DM-TIMING REQUEST	10.4	m		m	
4	DM-TIMING ACK	10.4	m		m	

c4101: IF A.32 /1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a

c4102: IF A.32 /2 -- If short data service supported
 THEN m -- then mandatory
 ELSE n/a

A.7.1.6 DM-REP1 MAC constants

The supplier of the implementation shall state the support of the implementation for each of the following DM-REP1 MAC constants, in tables A.42 and A.43.

Table A.42: DM-REP1 MAC constants

Item	Constant	Reference	Status	Support	Values	
					Default /Range	Supported
1	DN232	A.7	c4201		2/2-4	
2	DN233	A.7	c4202		2/2-4	
3	DN253	A.7	m		2	
4	DN259	A.7	m		any	

Supported values for DN232 and DN233 must be equal to the ones chosen in the DM MS-REP1. See table A.29 for their definition.

c4201: IF A.32 /1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a

c4202: IF A.32 /2 -- If short data service supported
 THEN m -- then mandatory
 ELSE n/a

Table A.43: DM-REP1 MAC number of frame transmissions

Item	Message type	Reference	Status	Support	Values	
					Allowed	Supported
1	DM-SETUP (new call setup)	A.5	c4301		2 .. 4	
2	DM-SETUP (continuation of ongoing call)	A.5	c4301		1 .. 4	
3	DM-SETUP PRES (new call setup)	A.5	c4301		2 .. 4	
4	DM-SETUP PRES (continuation of ongoing call)	A.5	c4301		1 .. 4	
5	DM-CONNECT	A.5	c4301		1 .. DN210	
6	DM-DISCONNECT	A.5	c4301		1 .. DN210	
7	DM-CONNECT ACK	A.5	c4301		1 .. 4	
8	DM-TX CEASED	A.5	c4301		2 .. 4	
9	DM-RELEASE	A.5	c4301		2 .. 4	
10	DM-TX ACCEPT	A.5	c4301		2 .. 4	
11	DM-PRE ACCEPT	A.5	c4301		2 .. 4	
12	DM-REJECT	A.5	c4301		1 .. 4	
13	DM-TIMING ACK (during occupation)	A.5	c4301		1 .. 4	
14	DM-TIMING ACK (during reservation for rejection)	A.5	c4301		1 .. 4	
15	DM-TIMING ACK (during reservation for acceptance)	A.5	c4301		2 .. 4	
16	DM-SDS DATA (DSB) (new call set-up)	A.5	c4302		2 .. 4	
17	DM-SDS DATA (DSB) (continuation of ongoing call)	A.5	c4302		1 .. 4	
18	DM-SDS UDATA (DSB) (new call set-up)	A.5	c4302		2 .. 4	
19	DM-SDS UDATA (DSB) (continuation of ongoing call)	A.5	c4302		1 .. 4	
20	DM-SDS ACK (fragmentation)	A.5	c4302		1 .. DN210	

c4301: IF A.32 /1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a

c4302: IF A.32 /2 -- If short data service supported
 THEN m -- then mandatory
 ELSE n/a

A.7.1.7 DM-REP1 MAC timers

The supplier of the implementation shall state the support of the implementation for each of the following DM-REP1 MAC timers, in table A.44.

Table A.44: DM-REP1 MAC timers

Item	Timer	Reference	Status	Support	Values	
					Default	Supported
1	DT250	A.6	c4401		xx -- frames	
2	DT251	A.6	c4402		4 -- frames	
3	DT252	A.6	c4401		9 -- frames	
4	DT253	A.6	m		xx -- frames	
5	DT254	A.6	m		xx -- frames	
6	DT256	A.6	c4401		180 -- frames	
7	DT257	A.6	c4401		xx -- frames	
8	DT258	A.6	c4401		180 --frames	

c4401: IF A.32 /1 -- If circuit mode call supported
 THEN m -- then mandatory
 ELSE n/a
 c4402: IF A.32 /2 -- If short data service supported
 THEN m -- then mandatory
 ELSE n/a

A.8. PDU parameters for MS-REP1 and DM-REP1 used in DMCC at layer 3 and DLL at layer 2

A.8.1 MS-REP1 PDU parameters for DMCC at layer 3

The supplier of the implementation shall state the support of the implementation for each of the following DMCC PDU elements, in tables A.45 to A.61.

A.8.1.1 DM-SETUP

Table A.45: DM-SETUP PDU contents

Prerequisite: A.2/1 - Circuit mode call				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Timing flag	10.6	m	
2	LCH in frame 3 flag	10.6	m	
3	Pre-emption flag	10.6	m	
4	Power class	10.6	m	
5	Power control flag	10.6	m	
6	Reserved	10.5	m	
7	Circuit mode type	10.6	m	
8	Reserved	10.5	m	
9	Priority level	10.6	m	
DM-SDU elements				
10	End-to-end encryption flag	10.7	m	
11	Call type flag	10.7	m	
12	External source flag	10.7	m	
13	Reserved	10.5	m	

A.8.1.2 DM-SETUP PRES

Table A.46: DM-SETUP PRES PDU contents

Prerequisite: A.15/2a OR A.15/2b - DM-SETUP PRES PDU				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Reserved	10.5	m	
2	Power class	10.6	m	
3	Power control flag	10.6	m	
4	Reserved	10.5	m	
5	Circuit mode type	10.6	m	
6	Reserved	10.5	m	
7	Priority level	10.6	m	
DM-SDU elements				
8	End-to-end encryption flag	10.7	m	
9	Call type flag	10.7	m	
10	External source flag	10.7	m	
11	Reserved	10.5	m	

A.8.1.3 DM-CONNECT

Table A.47: DM-CONNECT PDU contents

Prerequisite: A.15/3a OR A.15/3b - DM-CONNECT PDU				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Circuit mode type	10.6	m	
2	Reserved	10.5	m	
DM-SDU elements				
3	Reserved	10.5	m	

A.8.1.4 DM-DISCONNECT

Table A.48: DM-DISCONNECT PDU contents

Prerequisite: A.15/4a OR A.15/4b - DM-DISCONNECT PDU				
Item	Elements	Reference	Status	Support
DM-SDU elements				
1	Disconnect cause	10.7	m	

A.8.1.5 DM-CONNECT ACK

Table A.49: DM-CONNECT ACK PDU contents

Prerequisite: A.15/5a OR A.15/5b - DM-CONNECT ACK PDU				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Timing flag	10.6	m	
2	LCH in frame 3 flag	10.6	m	
3	Pre-emption flag	10.6	m	
4	Power class	10.6	m	
5	Power control flag	10.6	m	
6	Reserved	10.5	m	
7	Circuit mode type	10.6	m	
8	Reserved	10.5	m	
9	Priority level	10.6	m	
DM-SDU elements				
10	End-to-end encryption flag	10.7	m	
11	Call type flag	10.7	m	
12	External source flag	10.7	m	
13	Reserved	10.5	m	

A.8.1.6 DM-OCCUPIED

Table A.50: DM-OCCUPIED PDU contents

Prerequisite: A.2/1 - Circuit mode call				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Timing flag	10.6	m	
2	LCH in frame 3 flag	10.6	m	
3	Pre-emption flag	10.6	m	
4	Power class	10.6	m	
5	Power control flag	9.6.9	m	
6	Reserved	10.5	m	
7	Circuit mode type	10.6	m	
8	Reserved	10.5	m	
9	Priority level	10.6	m	
DM-SDU elements				
10	End-to-end encryption flag	10.7	m	
11	Call type flag	10.7	m	
12	External source flag	10.7	m	
13	Reserved	10.5	m	

A.8.1.7 DM-RELEASE

Table A.51: DM-RELEASE PDU contents

Prerequisite: A.2/1 - Circuit mode call				
Item	Elements	Reference	Status	Support
DM-SDU elements				
1	Release cause	10.7	m	

A.8.1.8 DM-TX CEASED

Table A.52: DM-TX CEASED contents

Prerequisite: A.2/1 - Circuit mode call				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Reservation time remaining	10.6	m	
2	Timing flag	10.6	m	
3	Requests flag	10.6	m	
4	Changeover requests flag	10.6	m	
5	Requests bitmap	10.6	m	
6	Recent user priority flag	10.6	m	
7	Timing change announced	10.6	m	
8	Timing adjustment	10.6	m	
9	Priority level	10.6	m	
DM-SDU elements				
10	Cease cause	10.7	m	

A.8.1.9 DM-TX REQUEST

Table A.53: DM-TX REQUEST PDU contents

Prerequisite: A.15/9a OR A.15/9b - DM-TX REQUEST PDU				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Timing change required	10.6	m	
2	Timing adjustment	10.6	m	
3	Priority level	10.6	m	

A.8.1.10 DM-TX ACCEPT

Table A.54: DM-TX ACCEPT PDU contents

Prerequisite: A.2/1 - Circuit mode call				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Timing change announced	10.6	m	
2	Timing adjustment	10.6	m	

A.8.1.11 DM-PREEMPT

Table A.55: DM-PREEMPT PDU contents

Prerequisite: A.15/11a OR A.15/11b - DM-PREEMPT PDU				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Perceived channel state	10.6	m	
2	Timing change required	10.6	m	
3	Timing adjustment	10.6	m	
4	New call pre-emption	10.6	m	
5	Type of pre-emption	10.6	m	
6	Priority level	10.6	m	

A.8.1.12 DM-PRE ACCEPT

Table A.56: DM-PRE ACCEPT PDU contents

Prerequisite: A.2/1 - Circuit mode call				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	Timing change announced	10.6	m	
2	Timing adjustment	10.6	m	
3	New call pre-emption	10.6	m	
4	Type of pre-emption	10.6	m	

A.8.1.13 DM-REJECT

Table A.57: DM-REJECT PDU contents

Prerequisite: A.15/13a OR A.15/13b - DM-REJECT PDU				
Item	Elements	Reference	Status	Support
DM-SDU elements				
1	Reject cause	10.7	m	

A.8.1.14 DM-INFO

Table A.58: DM-INFO PDU contents

Prerequisite: A.2/1 - Circuit mode call				
Item	Elements	Reference	Status	Support
DM-SDU elements				
1	Information type	10.7	m	
2	Calling party TSI	10.7	m	

A.8.1.15 DM-SDS UDATA

Table A.59: DM-SDS UDATA PDU contents

Prerequisite: A.16/1a OR A.16/1b - DM-SDS UDATA PDU				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	SDS time remaining	10.6	m	
2	SDS transaction type	10.6	m	
3	Priority level	10.6	m	
4	FCS flag	10.6	m	
DM-SDU elements				
5	Additional addressing flag	10.7	m	
6	Additional address type(s)	10.7	o	
7	Calling party TSI	10.7	o	
8	Short Data Type Identifier	10.7	m	
9	User defined data 1	10.7	o	
10	User defined data 2	10.7	o	
11	User defined data 3	10.7	o	
12	Length indicator	10.7	o	
13	User defined data 4	10.7	o	
14	Precoded status	10.7	o	
15	OTAR information	10.5	o	
16	Enable/disable information	10.5	o	
17	FCS	10.7	m	

NOTE: Options depend upon Data Security or Short Data Type Identifier, imposed by MS-REP1. See the definitions of these options for MS_REP in tables A.14 and A.8.

A.8.1.16 DM-SDS DATA

Table A.60: DM-SDS DATA PDU contents

Prerequisite: A.16/2a OR A.16/2b - DM-SDS DATA PDU				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	SDS time remaining	10.6	m	
2	SDS transaction type	10.6	m	
3	Priority level	10.6	m	
4	FCS flag	10.6	m	
DM-SDU elements				
5	Additional addressing flag	10.7	m	
6	Additional address type(s)	10.7	o	
7	Calling party TSI	10.7	o	
8	Short Data Type Identifier	10.7	m	
9	User defined data 1	10.7	o	
10	User defined data 2	10.7	o	
11	User defined data 3	10.7	o	
12	Length indicator	10.7	o	
13	User defined data 4	10.7	o	
14	Precoded status	10.7	o	
15	OTAR information	10.5	o	
16	Enable/disable information	10.5	o	
17	FCS	10.7	m	

NOTE: Options depend upon Data Security or Short Data Type Identifier, imposed by MS-REP1. See the definitions of these options for MS_REP in tables A.14 and A.8.

A.8.1.17 DM-SDS ACK

Table A.61: DM-SDS ACK PDU contents

Prerequisite: A.16/3a OR A. 16/3b - DM-SDS ACK PDU				
Item	Elements	Reference	Status	Support
Message dependent elements				
1	FCS flag	10.6	m	
DM-SDU elements				
2	Acknowledgement type	10.7	m	
3	Short Data Type Identifier	10.7	m	
4	User defined data 1	10.7	o	
5	User defined data 2	10.7	o	
6	User defined data 3	10.7	o	
7	Length indicator	10.7	o	
8	User defined data 4	10.7	o	
9	Precoded status	10.7	o	
10	OTAR information	10.5	o	
11	Enable/disable information	10.5	o	
12	FCS	10.7	m	

NOTE: Options depend upon Data Security or Short Data Type Identifier, imposed by MS-REP1. See the definitions of these options for MS_REP in tables A.14 and A.8.

A.8.2 MS-REP1 and DM-REP1 PDU parameters for DLL at layer 2

The supplier of the implementation shall state the support of the implementation for each of the following MAC PDU parameters, in tables A.62 to A.69.

A.8.2.1 DMAC-SYNC in SCH/S

Table A.62: Information elements for DMAC-SYNC PDU in SCH/S

Item	Information element	Reference	Status	Support
1	System code	10.3	m	
2	SYNC PDU type = 00	10.3	m	
3	Communication type = 01	10.3 - 10.1.1	m	
4	Master/slave link flag	10.3 - 10.1.1	m	
5	Reserved	10.1.1	m	
6	Gateway master flag	10.3	n/a	
7	Reserved	10.1.1	m	
8	A/B channel usage = 00	10.3 - 10.1.1	m	
9	Slot number	10.3	m	
10	Frame number	10.3	m	
11	AI encryption state	10.3	m	
12	Time Variant Parameter	10.3	o	
13	Timestamp flag	10.3	o	
14	KSG number	10.3	o	
15	Encryption key number	10.3	o	
16	Reserved	10.1.1	m	
NOTE 1: The n/a status is used for elements which do not apply to DMO REP applications.				
NOTE 2: Options depend upon Encryption, imposed by MS-REP.				

Table A.63: Information elements for DMAC-SYNC PDU in SCH/H

Item	Information element	Reference	Status	Support
1	Repeater address	10.3 - 10.1.1	m	
2	Gateway address	10.3	n/a	
3	Reserved	10.1.1	m	
4	Fill bit indication	10.3	m	
5	Fragmentation flag	10.3	m	
6	Number of SCH/F slots	10.3	m	
7	Frame countdown	10.3	m	
8	Destination address type	10.3	m	
9	Destination address	10.3	m	
10	Source address type	10.3	m	
11	Source address	10.3	m	
12	Mobile Network Identity	10.3	m	
13	Message type	10.3	m	
14	Message dependent elements	10.3	m	
15	DM SDU	10.3	m	
NOTE 1: Items 1 and 2 are present only for communication with a repeater or gateway.				
NOTE 2: The n/a status is used for elements which do not apply to repeater applications.				

A.8.2.2 DPRES-SYNC PDU

Table A.64: Information elements for DPRES-SYNC PDU in SCH/S

Item	Information element	Reference	Status	Support
1	System code	10.1.2	m	
2	SYNC PDU type = 01	10.1.2	m	
3	Communication type = 01	10.1.2	m	
4	Reserved	10.1.2	m	
5	Two-frequency repeater flag	10.1.2, 10.3.10	m	
6	Repeater operating modes = 00	10.1.2, 10.3.8	m	
7	Spacing of uplink	10.1.2, 10.3.9	m	
8	Reserved	10.1.2	m	
9	Master/slave link flag	10.1.2	m	
10	Channel usage = 00	10.1.2, 10.3.7	m	
11	Slot number	10.1.2	m	
12	Frame number	10.1.2	m	
13	Repeater address	10.1.2	m	
14	Power class	10.1.2	m	
15	Power control flag	10.1.2	m	
16	Channel state	10.1.2, 10.3.6	m	
17	Frame countdown	10.1.2	m	
18	Reserved	10.1.2	m	
19	Priority level	10.1.2	m	
20	Reserved	10.1.2	m	
21	Values of DN232 and DN233	10.1.2, 10.3.14	m	
22	Value of DT254	10.1.2, 10.3.13	m	
23	Reserved	10.1.2	m	

Table A.65: Information elements for DPRES-SYNC PDU in SCH/H

Item	Information element	Reference	Status	Support
1	Mobile Netw Id (MNI) of DM-REP1	10.1.2, 10.3.11	m	
2	Usage Restriction Type	10.1.2, 10.3.12	m	
3	Addressing for URT = 0010	10.1.2, 10.3.1	m	
4	Addressing for URT = 0011	10.1.2, 10.3.2	m	
5	Addressing for URT = 0100	10.1.2, 10.3.3	m	
6	Addressing for URT = 0101 or 0110 or 0111	10.1.2, 10.3.4	m	
7	Addressing for URT = 1000	10.1.2, 10.3.5	m	
8	Proprietary	10.1.2	m	
9	Reserved	10.1.2	m	
10	Reserved	10.1.2	m	
11	Reserved	10.1.2	m	

A.8.2.3 DMAC-DATA

Table A.66: Information elements for DMAC-DATA PDU

Item	Information element	Reference	Sending		Receiving	
			Status	Support	Status	Support
1	MAC PDU type	10.3	m		m	
2	Fill bit indication	10.3	m		m	
3	Second half slot stolen flag	10.3	m		m	
4	Fragmentation flag	10.3	m		m	
5	Null PDU flag	10.3	m		m	
6	Frame countdown	10.3	m		m	
7	AI encryption state	10.3	m		m	
8	Destination address type	10.3	m		m	
9	Destination address	10.3	m		m	
10	Source address type	10.3	m		m	
11	Source address	10.3	o		m	
12	Mobile Network Identity	10.3	m		m	
13	Message type	10.3	m		m	
14	Message dependent elements	10.3	m		m	
15	DM-SDU	10.3	m		m	

A.8.2.4 DMAC-FRAG

Table A.67: Information elements for DMAC-FRAG PDU

Item	Information element	Reference	Status	Support
1	MAC PDU type	10.3	m	
2	MAC PDU subtype	10.3	m	
3	Fill bit indication	10.3	m	
4	DM-SDU	10.3	m	

A.8.2.5 DMAC-END

Table A.68: Information elements for DMAC-END PDU

Item	Information element	Reference	Status	Support
1	MAC PDU type	10.3	m	
2	MAC PDU subtype	10.3	m	
3	Fill bit indication	10.3	m	
4	DM-SDU	10.3	m	

A.8.2.6 DMAC-U SIGNAL

Table A.69: Information elements for DMAC-U SIGNAL PDU

Item	Information element	Reference	Status	Support
1	MAC PDU type	10.3	m	
2	Second half slot stolen flag	10.3	m	
3	U-plane DM-SDU	10.3	m	

A.8.3 DM-MAC generated message parameters

The supplier of the implementation shall state the support of the implementation for each of the following DM-MAC generated message parameters, in tables A.70 to A.73.

A.8.3.1 DM-RESERVED

Table A.70: Information elements for DM-RESERVED

Item	Information element	Reference	Status	Support
1	All elements	10.4	m	

A.8.3.2 DM-SDS OCCUPIED

Table A.71: Information elements for DM-SDS OCCUPIED

Item	Information element	Reference	Status	Support
1	All elements	10.4	m	

A.8.3.3 DM-TIMING REQUEST

Table A.72: Information elements for DM-TIMING REQUEST

Item	Information element	Reference	Status	Support
1	All elements	10.4	m	

A.8.3.4 DM-TIMING ACK

Table A.73: Information elements for DM-TIMING ACK

Item	Information element	Reference	Status	Support
1	All elements	10.4	m	

History

Document history		
Edition 1	October 1999	Public Enquiry PE 200007: 1999-10-20 to 2000-02-18-
	October 2000	Converted from ETS to EN between Public Enquiry and Vote
V1.1.1	October 2000	Vote V 20001222: 2000-10-23 to 2000-12-22
V1.1.1	January 2001	Publication