
# Draft ETSI EN 300 908 V8.4.0 (2000-05)

European Standard (Telecommunications series)

Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path (GSM 05.02 version 8.4.0 Release 1999)



Reference REN/SMG-020502Q8R2

Keywords

Digital cellular telecommunications system, Global System for Mobile communications (GSM)

#### ETSI

#### 650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <a href="http://www.etsi.org/tb/status/">http://www.etsi.org/tb/status/</a>

> If you find errors in the present document, send your comment to: editor@etsi.fr

#### **Copyright Notification**

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 2000. All rights reserved.

# Contents

Intelle	ectual Property Rights	6
Forew	vord	6
1	Scope	7
1.1	References	
1.2	Abbreviations	8
2	General	8
3	Logical channels	8
3.1	General	
3.2	Traffic channels	
3.2.1	General	8
3.2.2	Speech traffic channels	
3.2.3	Circuit switched data traffic channels	9
3.2.4	Packet data traffic channels (PDTCH)	9
3.3	Control channels	
3.3.1	General	
3.3.2	Broadcast channels	
3.3.2.1		
3.3.2.2		
3.3.2.2		
3.3.2.2		
3.3.2.3		
3.3.2.4		
3.3.2.4		
3.3.2.4		
3.3.3	Common control type channels	
3.3.3.1		
3.3.3.2		
3.3.3.2		
3.3.3.2 3.3.4	2.2 COMPACT Common Control Channels (CPCCCH) Dedicated control channels	
3.3.4.1		
3.3.4.2		
3.3.5	Cell Broadcast Channel (CBCH)	
3.3.6	CTS control channels	
3.3.6.1		
3.3.6.2		
3.3.6.3		
3.3.6.4		
3.4	Combination of channels	
4	The physical resource	
-		
4.1 4.2	General Radio frequency channels	
4.2	Cell allocation and mobile allocation	
4.2.1	Downlink and uplink	
4.3	Timeslots, TDMA frames, and time groups	
4.3.1	General	
4.3.2	Timeslot number	
4.3.3	TDMA frame number	
4.3.4	Time group	
5	Physical channels	
5.1	General	
5.2	Bursts	
5.2.1	General	16

5.2.2	Types of burst and burst timing	
5.2.3	Normal burst (NB)	17
5.2.4	Frequency correction burst (FB)	19
5.2.5	Synchronization Burst (SB)	19
5.2.6	Dummy burst	20
5.2.7	Access burst (AB)	20
5.2.8	Guard period	
5.3	Physical channels and bursts	
5.4	Radio frequency channel sequence	
5.5	Timeslot and TDMA frame sequence	
5.6	Parameters for channel definition and assignment.	
5.6.1	General.	
5.6.2	General parameters	
5.6.3	Specific parameters	
6 Ma	apping of logical channels onto physical channels	
6.1	General	22
6.2	Mapping in frequency of logical channels onto physical channels	23
6.2.1	General	23
6.2.2	Parameters	23
6.2.3	Hopping sequence generation	24
6.2.4	Specific cases	25
6.2.5	Change in the frequency allocation of a base transceiver station	
6.2.6	Frequency assignment in CTS	
6.3	Mapping in time of logical channels onto physical channels	
6.3.1	Mapping in time of circuit switched logical channels onto physical channels	
6.3.1.1	General	
6.3.1.2	Key to the mapping table of clause 7	
6.3.1.3	Mapping of BCCH data	
6.3.1.4	Mapping of SID Frames	
6.3.2	Mapping in time of packet logical channels onto physical channels	
6.3.2.1	General	
6.3.2.2	Mapping of the uplink channels	
6.3.2.2.1	Mapping of uplink packet traffic channel (PDTCH/U) and PACCH/U	
6.3.2.2.2	Mapping of the Packet Timing Advance Control Channel (PTCCH/U)	
6.3.2.2.3	Mapping of the uplink PCCCH i.e. PRACH	
6.3.2.2.3a		
6.3.2.3	Mapping of the downlink channels	
6.3.2.3.1	Mapping of the (PDTCH/D) and PACCH/D	
6.3.2.3.2	Mapping of the PTCCH/D and TACCH/D	
6.3.2.3.3	Mapping of the PBCCH	
6.3.2.3.3a	11 0	
6.3.2.3.4	Mapping of the PCCCH	
6.3.2.3.4		
6.3.2.4 6.3.2.4	Mapping of PBCCH data	
6.3.2.4	Mapping of COMPACT CPBCCH data	
6.3.3		
6.3.3.1	Mapping in time of CTS control channels onto physical channels CTSBCH timeslot assignment	
	CTSPCH, CTSARCH and CTSAGCH timeslot assignment	
6.3.3.2	<b>0</b>	
6.4 6.4.1	Permitted channel combinations onto a basic physical channel	
6.4.1	Permitted channel combinations onto a basic physical channel	
6.4.2	Multislot configurations	
6.4.2.1	Multislot configurations for circuit switched connections	
6.4.2.2	Multislot configurations for packet switched connections	
6.5	Operation of channels and channel combinations	
6.5.1	General.	
6.5.2	Determination of CCCH_GROUP and PAGING_GROUP for MS in idle mode	
6.5.3	Determination of specific paging multiframe and paging block index	
6.5.4	Short Message Service Cell Broadcast (SMSCB)	
6.5.5	Voice group and voice broadcast call notifications	
6.5.6	Determination of PCCCH_GROUP and PAGING_GROUP for MS in GPRS attached mode	40

6.5.7	Determination of	CTS_PAGING_GROUP and specific paging 52-multiframe for MS in CT	S mode41
Anne	x A (normative):	Phase 2 mobiles in a Phase 1 infrastructure	61
A.1	Scope		61
A.2	Implementation option	s for TCH channels	61
A.2.1		Ι	
A.2.1.	1 A dummy burst w	ith (BN61, BN62, BN86) = training sequence bits of normal bursts	61
A.2.1.	2 A dummy burst w	ith the "C0 filling training sequence	61
A.2.1.		ith (BN61, BN62, BN86) mapped from the TSC bits of normal bursts acc	
	the table		61
A.2.1.	4 Partial SID inform	nation	61
A.2.2	Half burst filling		61
A.2.2.		nation from any associated SID frame; or	
A.2.2.		the dummy bursts (encrypted or not encrypted)	
A.2.3	•	g flag	
A.2.4		aling flag	
A.2.5	Allowed combination	18	
A.3	Idle Channels		62
Anne	x B (normative):	Multislot capability	63
B.1	MS classes for multisl	ot capability	63
B.2	Constraints imposed b	y the service selected	65
B.3	Network requirements	for supporting MS multislot classes	65
Anne	x C (informative):	CTSBCH Timeslot shifting example	68
Anne	x D (informative):	COMPACT multiframe structure examples	69
Anne	x E (informative):	Change control history	77
Histor			79

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

# Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Special Mobile Group (SMG), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document defines the physical channels of the radio sub-system required to support the logical channels of the digital mobile cellular and personal communication systems operating in the 900 MHz and 1 800 MHz band (GSM 900 and DCS 1 800).

The contents of the present document are subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version 8.x.y

where:

- 8 indicates release 1999 of GSM Phase 2+.
- x the second digit is incremented for changes of substance, i.e. technical enhancements, corrections, updates, etc.
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

Proposed national transposition dates		
Date of latest announcement of this EN (doa):	3 months after ETSI publication	
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa	
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa	

# 1 Scope

The present document defines the physical channels of the radio sub-system required to support the logical channels. It includes a description of the logical channels and the definition of frequency hopping, TDMA frames, timeslots and bursts.

# 1.1 References

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1999 document, references to GSM documents are for Release 1999 versions (version 8.x.y).
- [1] GSM 01.04: "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 03.03: "Digital cellular telecommunications system (Phase 2+); Numbering, addressing and identification".
- [3] GSM 04.03: "Digital cellular telecommunications system (Phase 2+); Mobile Station Base Station System (MS BSS) interface Channel structures and access capabilities".
- [4] GSM 04.06: "Digital cellular telecommunications system (Phase 2+); Mobile Station Base Station System (MS BSS) interface Data Link (DL) layer specification".
- [5] GSM 04.08: "Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification".
- [6] GSM 05.03: "Digital cellular telecommunications system (Phase 2+); Channel coding".
- [7] GSM 05.04: "Digital cellular telecommunications system; Modulation".
- [8] GSM 05.05: "Digital cellular telecommunications system (Phase 2+); Radio transmission and reception".
- [9] GSM 05.08: "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control".
- [10] GSM 05.10: "Digital cellular telecommunications system (Phase 2+); Radio subsystem synchronization".
- [11] GSM 03.64: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Overall description of the GPRS Radio Interface; Stage 2".
- [12] GSM 04.60: "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS interface; Radio Link Control (RLC) and Medium Access Control (MAC) Layer Specification".
- [13] GSM 03.52: "Digital cellular telecommunications system (Phase 2+); GSM Cordless Telephony System (CTS), Phase 1; Lower layers of the CTS Radio Interface; Stage 2".
- [14] GSM 04.56: "Digital cellular telecommunications system (Phase 2+); GSM Cordless Telephony System (CTS), Phase 1; CTS radio interface layer 3 specification".
- [15] GSM 05.56: "Digital cellular telecommunications system (Phase 2+); GSM Cordless Telephony System (CTS), Phase 1; CTS-FP radio subsystem".

# 1.2 Abbreviations

Abbreviations used in the present document are listed in GSM 01.04 [1].

# 2 General

The radio subsystem is required to support a certain number of logical channels that can be separated into two categories as defined in GSM 04.03:

- i) the traffic channels (TCH's);
- ii) the control channels.

More information is given about these logical channels in clause 3 which also defines a number of special channels used by the radio sub-system.

Clause 4 of this document describes the physical resource available to the radio sub-system, clause 5 defines physical channels based on that resource and clause 6 specifies how the logical channels shall be mapped onto physical channels. Figure 1 depicts this process.

# 3 Logical channels

# 3.1 General

This subclause describes the logical channels that are supported by the radio subsystem.

# 3.2 Traffic channels

## 3.2.1 General

Traffic channels (TCH's) are intended to carry either encoded speech or user data in circuit switched mode. Two general forms of traffic channel are defined:

- i) Full rate traffic channel (TCH/F). This channel carries information at a gross rate of 22,8 kbit/s.
- ii) Half rate traffic channel (TCH/H). This channel carries information at a gross rate of 11,4 kbit/s.
- iii) Enhanced circuit switched full rate traffic channel (E-TCH/F). This channel carries information at a gross rate of 69,6 kbit/s including the stealing symbols.

Packet data traffic channels (PDTCH's) are intended to carry user data in packet switched mode. For the purpose of this EN, any reference to traffic channel does not apply to PDTCH unless explicitly stated.

All traffic channels are bi-directional unless otherwise stated. Unidirectional downlink full rate channels, TCH/FD, are defined as the downlink part of the corresponding TCH/F.

Multiple full rate channels can be allocated to the same MS. This is referred to as multislot configurations, which is defined in subclause 6.4.2.1.

Multiple packet data traffic channels can be allocated to the same MS. This is referred to as multislot packet configurations, as defined in subclause 6.4.2.2.

The specific traffic channels available in the categories of speech and user data are defined in the subclauses following.

## 3.2.2 Speech traffic channels

The following traffic channels are defined to carry encoded speech:

- i) full rate traffic channel for speech (TCH/FS);
- ii) half rate traffic channel for speech (TCH/HS);
- iii) enhanced full rate traffic channel for speech (TCH/EFS);
- iv) adaptive full rate traffic channel for speech (TCH/AFS);
- v) adaptive half rate traffic channel for speech (TCH/AHS).

# 3.2.3 Circuit switched data traffic channels

The following traffic channels are defined to carry user data:

- i) full rate traffic channel for 9,6 kbit/s user data (TCH/F9.6);
- ii) full rate traffic channel for 4,8 kbit/s user data (TCH/F4.8);
- iii) half rate traffic channel for 4,8 kbit/s user data (TCH/H4.8);
- iv) half rate traffic channel for  $\leq 2,4$  kbit/s user data (TCH/H2.4);
- v) full rate traffic channel for  $\leq 2,4$  kbit/s user data (TCH/F2.4);
- vi) full rate traffic channel for 14,4 kbit/s user data (TCH/F14.4);
- vii) enhanced circuit switched full rate traffic channel for 28,8 kbit/s user data (E-TCH/F28.8);
- viii) enhanced circuit switched full rate traffic channel for 32,0 kbit/s user data (E-TCH/F32.0);
- ix) enhanced circuit switched full rate traffic channel for 43.2 kbit/s user data (E-TCH/F43.2).

## 3.2.4 Packet data traffic channels (PDTCH)

A PDTCH corresponds to the resource allocated to a single MS on one physical channel for user data transmission. Due to the dynamic multiplexing onto the same physical channel of different logical channels (see subclause 6.3.2), a PDTCH using GMSK modulation carries information at an instantaneous bit rate ranging from 0 to 22,8 kbit/s. A PDTCH using 8PSK modulation carries information (including stealing symbols) at an instantaneous bit rate ranging from 0 to 69,6 kbit/s.

All packet data traffic channels are uni-directional, either uplink (PDTCH/U), for a mobile originated packet transfer or downlink (PDTCH/D) for a mobile terminated packet transfer.

# 3.3 Control channels

# 3.3.1 General

Control channels are intended to carry signalling or synchronization data. Four categories of control channel are defined: broadcast, common, dedicated and CTS control channels. Specific channels within these categories are defined in the subclauses following.

## 3.3.2 Broadcast channels

#### 3.3.2.1 Frequency correction channels (FCCH and CFCCH)

The frequency correction channel carries information for frequency correction of the mobile station. It is required only for the operation of the radio sub-system. Different mapping is used for FCCH and COMPACT CFCCH (see clause 7).

#### 3.3.2.2 Synchronization channels

The synchronization channel carries information for frame synchronization of the mobile station and identification of a base transceiver station. It is required only for the operation of the radio sub-system. Different channels are used for SCH and COMPACT CSCH.

#### 3.3.2.2.1 Synchronization channel (SCH)

Specifically the synchronization channel (SCH) shall contain two encoded parameters:

- a) Base transceiver station identity code (BSIC): 6 bits (before channel coding) consists of 3 bits of PLMN colour code with range 0 to 7 and 3 bits of BS colour code with range 0 to 7 as defined in GSM 03.03.
- b) Reduced TDMA frame number (RFN): 19 bits (before channel coding) =

T1 (11 bits) range 0 to  $2047 = FN \text{ div} (26 \times 51)$ T2 (5 bits) range 0 to 25 = FN mod 26 T3 ' = (T3 - 1) div 10(3 bits) range 0 to 4 where Т3 (6 bits) range 0 to 50 = FN mod 51 and FN = TDMA frame number as defined in subclause 4.3.3.

GSM 04.06 and GSM 04.08 specify the precise bit ordering, GSM 05.03 the channel coding of the above parameters and GSM 05.10 defines how the TDMA frame number can be calculated from T1, T2, and T3'.

#### 3.3.2.2.2 COMPACT synchronization channel (CSCH)

The COMPACT packet synchronization channel CSCH shall contain two encoded parameters:

- a) Base transceiver station identity code (BSIC): 6 bits (before channel coding) consists of 3 bits of PLMN colour code with range 0 to 7 and 3 bits BS colour code with range 0 to 7 as defined in GSM 03.03.
- b) Reduced TDMA frame number (RFN): 19 bits (before channel coding) =

 R1
 (10 bits)
 range 0 to 1023
 = FN div (51 x 52)

 R2
 (6 bits)
 range 0 to 50
 = (FN div 52) mod 51

 TG
 (2 bits)
 range 0 to 3

Reserved (1 bit)

where

FN = TDMA frame number as defined in subclause 4.3.3

and

TG = time group as defined in subclause 4.3.4.

GSM 04.06 and GSM 04.08 specify the precise bit ordering, GSM 05.03 the channel coding of the above parameters and GSM 05.10 defines how the TDMA frame number can be calculated from R1 and R2.

#### 3.3.2.3 Broadcast control channel (BCCH)

The broadcast control channel broadcasts general information on a base transceiver station per base transceiver station basis. Of the many parameters contained in the BCCH, the use of the following parameters, as defined in GSM 04.08 are referred to in subclause 6.5:

a) CCCH\_CONF which indicates the organization of the common control channels:

From this parameter, the number of common control channels (BS\_CC\_CHANS) and whether or not CCCH or SDCCH are combined (BS\_CCCH\_SDCCH\_COMB = true or false) are derived as follows:

CCCH_CONF	BS_CC_CHANS	BS_CCCH_SDCCH_COMB
000	1	false
001	1	true
010	2	false
100	3	false
110	4	false

 b) BS\_AG\_BLKS\_RES which indicates the number of blocks on each common control channel reserved for access grant messages:

3 bits (before channel coding) range 0 to 7.

c) BS\_PA\_MFRMS which indicates the number of 51-multiframes between transmission of paging messages to mobiles of the same paging group:

3 bits (before channel coding) range 2 to 9.

d) support of GPRS

The BCCH shall indicate whether or not packet switched traffic is supported. If packet switched traffic is supported and if the PBCCH exists, then the BCCH shall broadcast the position of the packet data channel (PDCH), as defined in subclause 6.3.2.1, carrying the PBCCH.

#### 3.3.2.4 Packet Broadcast Control Channels

#### 3.3.2.4.1 Packet Broadcast Control Channel (PBCCH)

The PBCCH broadcasts parameters used by the MS to access the network for packet transmission operation. In addition to those parameters the PBCCH reproduces the information transmitted on the BCCH to allow circuit switched operation, such that a MS in GPRS attached mode monitors the PBCCH only, if it exists. The existence of the PBCCH in the cell is indicated on the BCCH. In the absence of PBCCH, the BCCH shall be used to broadcast information for packet operation.

Of the many parameters contained in the PBCCH, the use of the following parameters, as defined in GSM 04.60 are referred to in subclauses 6.5 and 6.3.2:

- a) BS\_PBCCH\_BLKS (1,...,4) indicates the number of blocks allocated to the PBCCH in the multiframe. The position of the PBCCH blocks is based on the ordered list as defined in subclause 6.3.2.1.
- b) BS\_PCC\_CHANS indicates the number of physical channels carrying PCCCHs including the physical channel carrying the PBCCH
- c) BS\_PAG\_BLKS\_RES indicates the number of blocks on each PDCH carrying PCCCH per multiframe where neither packet paging nor PBCCH should appear. This number corresponds therefore to the number of blocks reserved for PAGCH, PNCH, PDTCH and PACCH. The position of these blocks is based on the ordered list as defined in subclause 6.3.2.1.

d) BS\_PRACH\_BLKS indicates the number of blocks reserved in a fixed way to the PRACH channel on any PDCH carrying PCCCH. The position of the PRACH blocks is based on the ordered list as defined in subclause 6.3.2.1.

#### 3.3.2.4.2 COMPACT Packet Broadcast Control Channel (CPBCCH)

The CPBCCH is a stand-alone packet control channel for COMPACT. The CPBCCH broadcasts parameters used by the MS to access the network for packet transmission operation.

Of the many parameters contained in the CPBCCH, the use of the following parameters, as defined in GSM 04.60 are referred to in subclauses 6.5 and 6.3.3:

- a) BS\_PBCCH\_BLKS (1,...,4) indicates the number of blocks allocated to the CPBCCH in the multiframe. The position of the CPBCCH blocks is based on the ordered list as defined in subclause 6.3.2.1.
- b) BS\_PCC\_CHANS indicates the number of radio frequency channels per cell carrying CPCCCHs including the radio frequency channel carrying the CPBCCH.
- c) BS\_PAG\_BLKS\_RES indicates the number of blocks on each radio frequency channel carrying CPCCCH per multiframe where neither packet paging nor CPBCCH should appear. This number corresponds therefore to the number of blocks reserved for CPAGCH, CPNCH, PDTCH, and PACCH. The position of these blocks is based on the ordered list as defined in subclause 6.3.2.1. BS\_PAG\_BLKS\_RES cannot be greater than 8.
- d) BS\_PRACH\_BLKS indicates the number of blocks reserved in a fixed way to the CPRACH channel on any radio frequency channel carrying CPCCCH. The position of the CPRACH blocks is based on the ordered list as defined in subclause 6.3.2.1.
- e) NIB\_CCCH\_0, NIB\_CCCH\_1, NIB\_CCCH\_2, and NIB\_CCCH\_3 indicate the number of downlink blocks per multiframe designated as idle to protect CPBCCH and CPCCCH blocks for non-serving time groups. The downlink position is based on the ordered list and rotation rule as defined in subclause 6.3.2.1.
- f) LARGE\_CELL\_OP indicates which type of cell size is used: nominal or large.

#### 3.3.3 Common control type channels

# 3.3.3.1 Common control type channels, known when combined as a common control channel (CCCH)

- i) Paging channel (PCH): Downlink only, used to page mobiles.
- ii) Random access channel (RACH): Uplink only, used to request allocation of a SDCCH.
- iii) Access grant channel (AGCH): Downlink only, used to allocate a SDCCH or directly a TCH.
- iv) Notification channel (NCH): Downlink only, used to notify mobile stations of voice group and voice broadcast calls.

#### 3.3.3.2 Packet Common control channels

#### 3.3.3.2.1 Packet Common Control Channels (PCCCH)

- i) Packet Paging channel (PPCH): Downlink only, used to page MS.
- ii) Packet Random access channel (PRACH): Uplink only, used to request allocation of one or several PDTCHs (for uplink or downlink direction).
- iii) Packet Access grant channel (PAGCH): Downlink only, used to allocate one or several PDTCH.
- iv) Packet Notification channel (PNCH): Downlink only, used to notify MS of PTM-M call.

If a PCCCH is not allocated, the information for packet switched operation is transmitted on the CCCH. If a PCCCH is allocated, it may transmit information for circuit switched operation.

#### 3.3.3.2.2 COMPACT Common Control Channels (CPCCCH)

- i) Packet Paging channel (CPPCH): Downlink only, used to page MS.
- ii) Packet Random access channel (CPRACH): Uplink only, used to request allocation of one or several PDTCHs (for uplink or downlink direction).
- iii) Packet Access grant channel (CPAGCH): Downlink only, used to allocate one or several PDTCH.
- iv) Packet Notification channel (CPNCH): Downlink only, used to notify MS of PTM-M call.

## 3.3.4 Dedicated control channels

#### 3.3.4.1 Circuit switched dedicated control channels

- i) Slow, TCH/F or E-TCH/F associated, control channel (SACCH/TF).
- ii) Fast, TCH/F associated, control channel (FACCH/F).
- iii) Slow, TCH/H associated, control channel (SACCH/TH).
- iv) Fast, TCH/H associated, control channel (FACCH/H).
- v) Stand alone dedicated control channel (SDCCH/8).
- vi) Slow, SDCCH/8 associated, control channel (SACCH/C8)
- vii) Stand alone dedicated control channel, combined with CCCH (SDCCH/4).
- viii) Slow, SDCCH/4 associated, control channel (SACCH/C4).
- ix) slow, TCH/F or E-TCH/F associated, control channel for multislot configurations (SACCH/M).
- x) slow, TCH/F associated, control channel for CTS (SACCH/CTS).
- xi) Fast, E-TCH/F associated, control channel (E-FACCH/F).
- xii) Inband, E-TCH/F associated, control channel (E-IACCH/F)

All associated control channels have the same direction (bi-directional or unidirectional) as the channels they are associated to. The unidirectional SACCH/MD is defined as the downlink part of SACCH/M.

#### 3.3.4.2 Packet dedicated control channels

- i) The Packet Associated Control channel (PACCH): The PACCH is bi-directional. For description purposes PACCH/U is used for the uplink and PACCH/D for the downlink.
- ii) Packet Timing advance control channel uplink (PTCCH/U): Used to transmit random access bursts to allow estimation of the timing advance for one MS in packet transfer mode.
- iii) Packet Timing advance control channel downlink (PTCCH/D): Used to transmit timing advance updates for several MS. One PTCCH/D is paired with several PTCCH/U's.

# 3.3.5 Cell Broadcast Channel (CBCH)

The CBCH, downlink only, is used to carry the short message service cell broadcast (SMSCB). The CBCH uses the same physical channel as the SDCCH.

# 3.3.6 CTS control channels

Four types of CTS control channels are defined:

## 3.3.6.1 CTS beacon channel (BCH)

The BCH is used to provide frequency and synchronization information in the downlink. It is made up of a pair of CTSBCH-SB (Synchronization burst) and CTSBCH-FB (Frequency correction burst).

The CTSBCH-FB carries information for frequency correction of the mobile station. It is required only for the operation of the radio sub-system.

The CTSBCH-SB carries signalling information and identification of a CTS-FP. Specifically the CTSBCH-SB shall contain five encoded parameters:

- a) status of the CTS-FP radio resources : 1 bit (before channel coding;
- b) flag indicating the presence of CTSPCH in the next 52-multiframe : 1 bit (before channel coding);
- c) flag indicating whether the CTS-FP is currently performing timeslot shifting on CTSBCH: 1 bit (before channel coding);
- d) CTS control channels (except CTSBCH) timeslot number for the next 52-multiframe (TNC): 3 bits (before channel coding);
- e) CTS-FP beacon identity (FPBI) : 19 bits (before channel coding), as defined in GSM 03.03.

GSM 04.56 specifies the precise bit ordering and GSM 05.03 the channel coding of the above parameters.

#### 3.3.6.2 CTS paging channel (CTSPCH)

Downlink only, used to broadcast information for paging.

## 3.3.6.3 CTS access request channel (CTSARCH)

Uplink only, used to request allocation of a dedicated RR connection.

#### 3.3.6.4 CTS access grant channel (CTSAGCH)

Downlink only, used to grant a dedicated RR connection.

# 3.4 Combination of channels

Only certain combinations of channels are allowed as defined in GSM 04.03. Subclause 6.4 lists the combinations in relation to basic physical channels.

# 4 The physical resource

# 4.1 General

The physical resource available to the radio sub-system is an allocation of part of the radio spectrum. This resource is partitioned both in frequency and time. Frequency is partitioned by radio frequency channels (RFCHs) divided into bands as defined in GSM 05.05. Time is partitioned by timeslots, TDMA frames, and (for COMPACT) time groups and 52-multiframe number as defined in subclause 4.3 of this EN.

# 4.2 Radio frequency channels

# 4.2.1 Cell allocation and mobile allocation

GSM 05.05 defines radio frequency channels (RFCHs), and allocates numbers to all the radio frequency channels available to the system. Each cell is allocated a subset of these channels, defined as the cell allocation (CA). One radio frequency channel of the cell allocation shall be used to carry synchronization information and the BCCH, this shall be known as BCCH carrier. The subset of the cell allocation, allocated to a particular mobile, shall be known as the mobile allocation (MA).

For COMPACT, one radio frequency channel of the cell allocation shall be used to carry synchronization information and the CPBCCH, this shall be known as the primary COMPACT carrier. All other radio frequency channels of the cell allocation shall be known as secondary COMPACT carriers.

# 4.2.2 Downlink and uplink

The downlink comprises radio frequency channels used in the base transceiver station to Mobile Station direction.

The uplink comprises radio frequency channels used in the mobile station to base transceiver station direction.

# 4.3 Timeslots, TDMA frames, and time groups

# 4.3.1 General

A timeslot shall have a duration of 3/5 200 seconds ( $\approx$  577 µs). Eight timeslots shall form a TDMA frame ( $\approx$  4,62 ms in duration).

At the base transceiver station the TDMA frames on all of the radio frequency channels in the downlink shall be aligned. The same shall apply to the uplink (see GSM 05.10).

At the base transceiver station the start of a TDMA frame on the uplink is delayed by the fixed period of 3 timeslots from the start of the TDMA frame on the downlink (see figure 2).

At the mobile station this delay will be variable to allow adjustment for signal propagation delay. The process of adjusting this advance is known as adaptive frame alignment and is detailed in GSM 05.10.

The staggering of TDMA frames used in the downlink and uplink is in order to allow the same timeslot number to be used in the downlink and uplink whilst avoiding the requirement for the mobile station to transmit and receive simultaneously. The period includes time for adaptive frame alignment, transceiver tuning and receive/transmit switching (see figure 4).

# 4.3.2 Timeslot number

The timeslots within a TDMA frame shall be numbered from 0 to 7 and a particular timeslot shall be referred to by its timeslot number (TN).

# 4.3.3 TDMA frame number

TDMA frames shall be numbered by a frame number (FN). The frame number shall be cyclic and shall have a range of 0 to FN\_MAX where FN\_MAX =  $(26 \times 51 \times 2048) - 1 = 2715647$  as defined in GSM 05.10. For COMPACT, FN\_MAX =  $(52 \times 51 \times 1024) - 1 = 2715647$ . The frame number shall be incremented at the end of each TDMA frame.

The complete cycle of TDMA frame numbers from 0 to FN\_MAX is defined as a hyperframe. A hyperframe consists of 2048 superframes where a superframe is defined as 26 x 51 TDMA frames. For COMPACT, a hyperframe consists of 1024 superframes where a superframe is defined as 52 x 51 TDMA frames. A 26-multiframe, comprising 26 TDMA frames, is used to support traffic and associated control channels and a 51- multiframe, comprising 51 TDMA frames, is used to support broadcast, common control and stand alone dedicated control (and their associated control) channels. Hence a superframe may be considered as 51 traffic/associated control multiframes or 26 broadcast/common control multiframes, is used to support packet data traffic and control channels.

The need for a hyperframe of a substantially longer period than a superframe arises from the requirements of the encryption process which uses FN as an input parameter.

# 4.3.4 Time group

Used for COMPACT, time groups shall be numbered from 0 to 3 and a particular time group shall be referred to by its time group number (TG) (see subclause 3.3.2.2.2). At block B0 and frame number (FN) mod 208 = 0, time group numbers (TG) are associated with timeslot numbers (TN) as follows:

	TG	TN
0		1
1		3
2		5
3		7

For COMPACT, a cell is assigned one time group number (TG) on a primary COMPACT carrier. This is known as the serving time group. Other cells may be assigned other time groups on the same carrier.

# 5 Physical channels

# 5.1 General

A physical channel uses a combination of frequency and time division multiplexing and is defined as a sequence of radio frequency channels and time slots. The complete definition of a particular physical channel consists of a description in the frequency domain, and a description in the time domain.

The description in the frequency domain is addressed in subclause 5.4; the description in the time domain is addressed in subclause 5.5.

# 5.2 Bursts

# 5.2.1 General

A burst is a period of RF carrier which is modulated by a data stream. A burst therefore represents the physical content of a timeslot.

# 5.2.2 Types of burst and burst timing

A timeslot is divided into 156.,25 symbol periods.

For GMSK modulation (see 05.04) a symbol is equivalent to a bit. A particular bit period within a timeslot is referenced by a bit number (BN), with the first bit period being numbered 0, and the last (1/4) bit period being numbered 156.

For 8PSK modulation (see 05.04) one symbol corresponds to three bits. A particular bit period within a timeslot is referenced by a bit number (BN), with the first bit being numbered 0, and the last (3/4) bit being numbered 468. The bits are mapped to symbols in ascending order according to 05.04.

In the subclauses following the transmission timing of a burst within a timeslot is defined in terms of bit number. The bit with the lowest bit number is transmitted first.

Different types of burst exist in the system. One characteristic of a burst is its useful duration. This document, in the subclauses following, defines full bursts of 147 symbols useful duration, and a short burst of 87 symbols useful duration. The useful part of a burst is defined as beginning from half way through symbol number 0. The definition of the useful part of a burst needs to be considered in conjunction with the requirements placed on the phase and amplitude characteristics of a burst as specified in GSM 05.04 and 05.05.

The period between bursts appearing in successive timeslots is termed the guard period. Subclause 5.2.8 details constraints which relate to the guard period.

# 5.2.3 Normal burst (NB)

#### Normal burst for GMSK

Bit Number (BN)	Length of field	Contents of field	Definition
0 - 2	3	tail bits	(below)
3 - 60	58	encrypted bits (e0 . e57)	05.03
61 - 86	26	training sequence bits	(below)
87 - 144	58	encrypted bits (e58 . e115)	05.03
145 - 147	3	tail bits	(below)
(148 - 156	8,25	guard period (bits)	subclause 5.2.8)

- where the "tail bits" are defined as modulating bits with states as follows:

(BN0, BN1, BN2) = (0, 0, 0) and (BN145, BN146, BN147) = (0, 0, 0)

- where the "training sequence bits" are defined as modulating bits with states as given in the following table according to the training sequence code, TSC. For broadcast and common control channels, the TSC must be equal to the BCC, as defined in GSM 03.03 and as described in this technical specification in subclause 3.3.2. In networks supporting E-OTD Location services (see GSM 03.71 Annex C), the TSC shall be equal to the BCC for all normal bursts on BCCH frequencies.

NOTE: For COMPACT, for PDTCH/PACCH on primary and secondary carriers that are indicated in EXT\_FREQUENCY\_LIST by parameter INT\_FREQUENCY and in INT\_MEAS\_CHAN\_LIST (see subclauses 10.1.5 and 10.2.3.2.2 of GSM 05.08), the TSCs should be equal to the BCC, as defined in GSM 03.03 and as described in this technical specification in subclause 3.3.2, otherwise the accuracy of interference measurement reporting may be compromised.

- For CTS control channels, the TSC shall be defined by the 3 LSBs (BN3, BN2, BN1) of the FPBI (specified in GSM 03.03).

Training Sequence Code (TSC)	Training sequence bits (BN61, BN62 BN86)
0	(0,0,1,0,0,1,0,1,1,1,0,0,0,0,1,0,0,0,1,0,0,1,0,1,1,1)
1	(0,0,1,0,1,1,0,1,1,1,0,1,1,1,1,0,0,0,1,0,1,1,0,1,1,1)
2	(0,1,0,0,0,0,1,1,1,0,1,1,1,0,1,0,0,1,0,0,0,0,1,1,1,0)
3	(0,1,0,0,0,1,1,1,1,0,1,1,0,1,0,0,0,1,0,0,0,1,1,1,1,0)
4	(0,0,0,1,1,0,1,0,1,1,1,0,0,1,0,0,0,0,0,1,1,0,1,0,1,1)
5	(0,1,0,0,1,1,1,0,1,0,1,1,0,0,0,0,0,1,0,0,1,1,1,0,1,0)
6	(1,0,1,0,0,1,1,1,1,1,0,1,1,0,0,0,1,0,1,0
7	(1,1,1,0,1,1,1,1,0,0,0,1,0,0,1,0,1,1,1,0,1,1,1,1,0,0)

Under certain circumstances only half the encrypted bits present in a normal burst will contain complete information. For downlink DTX operation on TCH-FS and TCH-HS, when a traffic frame (as defined in GSM 06.31) is scheduled for transmission and one of its adjacent traffic frames is not scheduled for transmission, the other half of the encrypted bits in the normal bursts associated with the scheduled traffic frame shall contain partial SID information from any associated SID frame, with the appropriate stealing flags BN60 or BN87 set to 0. In other cases the binary state of the remaining bits is not specified.

#### Normal burst for 8PSK

Bit Number (BN)	Length of field (bits)	Contents of field	Definition
 0 - 8	9	tail bits	(below)
9 - 182	174	encrypted bits (e0 . e173)	05.03
183 – 260	78	training sequence bits	(below)
261 - 434	174	encrypted bits (e174 . e347)	05.03
435 - 443	9	tail bits	(below)
444 - 468	24.75	guard period	subclause 5.2.8

- where the "tail bits" are defined as modulating bits with states as follows (bits are grouped in symbols separated by ;):

(BN0, BN1 .. BN8) = (1,1,1;1,1,1;1,1,1) and

(BN435, BN436 .. BN443) = (1,1,1;1,1,1;1,1,1)

- where the "training sequence bits" are defined as modulating bits with states as given in the following table according to the training sequence code, TSC. For broadcast and common control channels, the TSC must be equal to the BCC, as defined in GSM 03.03 and as described in this technical specification in subclause 3.3.2. In networks supporting E-OTD Location services (see GSM 03.71 Annex C), the TSC shall be equal to the BCC for all normal bursts on BCCH frequencies.

Training Sequence Code (TSC)	Training sequence symbols (BN183, BN184 BN260)
0	
1	1,1,1;0,0,1;1,1,1;1,1,1;1,0,0,1;1,1,1;1,1;
2	$\begin{array}{c} 0,0,1;0,0,1;1,1,1;1,1,1;1,1,1;0,0,1;1,1,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;0,0,1;\\ (1,1,1;0,0,1;1,1,1;1,1,1;1,1,1;1,1,1;0,0,1;0,0,1;0,0,1;1,1,1;0,0,0;0,0,0;0,0,0,0,$
3	$1,1,1;0,0,1;1,1,1;1,1,1;0,0,1;1,1,1;1,1,1;1,1,1;1,1,1;0,0,1;0,0,1;0,0,1;1,1,1) \\ (1,1,1;0,0,1;1,1,1;1,1,1;1,1,1;0,0,1;0,0,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;1,1,1;1,1,1;0,0,1;0,0,1;1,1,1;1,1,1;1,1,1;0,0,0,1;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0,0;0,0,0,0;0,0,0,0;0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,0,0;0,$
4	0,0,1;1,1,1;1,1,1;1,1;0,0,1;1,1,1;1,1,1;1,1;
5	0,0,1;1,1,1;1,1,1;1,1,1;1,1,1;0,0,1;0,0,1;1,1,1;0,0,1;1,1,1;0,0,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;0,0,1;1,1,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,0,0,
6	1,1,1;1,1,1;1,1,1;1,1,1;0,0,1;1,1,1;1,1,1;0,0,1;0,0,1;0,0,1;1,1,1;0,0,1;1,1,1;0,0,1;1,1,1;0,0,1;1,1,1;0,0,0;0,0;0,0,0;0,
7	1,1,1,1,1,1,1,1,1,1,0,0,1,1,1,1,0,0,1,1,1,1,1,1,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0,0,1,0
•	(1,1,1;0,0,1;1,1,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,1;0,0,1;1,1,1;1,1,1)

# 5.2.4 Frequency correction burst (FB)

Bit Number (BN)	length of field	Contents of field	Definition
0 - 2	3	tail bits	(below)
3 - 144	142	fixed bits	(below)
145 - 147	3	tail bits	(below)
(148 - 156	8,25	guard period (bits)	subclause 5.2.8)

- where the "tail bits" are defined as modulating bits with states as follows:

(BN0, BN1, BN2)	=(0, 0, 0)	and
(BN145, BN146, BN147)	=(0, 0, 0)	

- where the "fixed bits" are defined as modulating bits with states as follows:

(BN3, BN4 .. BN144) = (0, 0 .. 0)

except for COMPACT frequency correction bursts where states are as follows:

(BN3, BN4, BN5, BN6 ... BN143, BN144) = (1, 0, 1, 0, ... 1, 0)

NOTE: This burst is equivalent to unmodulated carrier with a +1 625/24 kHz frequency offset, above the nominal carrier frequency or for COMPACT, a -1 625/24 kHz frequency offset, below the nominal carrier frequency.

# 5.2.5 Synchronization Burst (SB)

	umber BN)	Length of field	Contents of field	Definition
0	- 2	3	tail bits	(below)
3	- 41	39	encrypted bits (e0 . e38)	05.03
42	- 105	64	extended training sequence bits	(below)
106	- 144	39	encrypted bits (e39 e77)	05.03
145	- 147	3	tail bits	(below)
(148	- 156	8,25	guard period (bits)	subclause 5.2.8)

- where the "tail bits" are defined as modulating bits with states as follows:

(BN0, BN1, BN2)	=(0, 0, 0)	and
(BN145, BN146, BN147)	=(0, 0, 0)	

- where the "extended training sequence bits" are defined as modulating bits with states as follows:

(BN42, BN43 BN105)	=	(1, 0, 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,				
		0, 0, 0, 0, 0, 1, 1, 1, 1, 0, 0, 1, 0, 1, 1, 0, 1, 0, 1, 0, 0, 0,				
		1, 0, 1, 0, 1, 1, 1, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0, 1, 1)				
except for CTS synchronisation bursts where states are as follows:						
(BN42, BN43 BN105)	=	(1, 1, 1, 0, 1, 1, 1, 0, 0, 1, 1, 0, 1, 0, 1, 1, 0, 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,				
0, 0, 1, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1, 0, 0, 0, 1, 1, 1, 1, 1, 0,						
1, 1, 0, 0, 1, 0, 1, 1, 0, 0, 0, 1, 0, 1, 0, 1)						
except for COMPACT synchronisation bursts furthermore, where states are as follows:						

## 5.2.6 Dummy burst

Bit Number (BN)	Length of field	Contents of field	Definition
0 - 2	3	tail bits	(below)
3 - 144	142	mixed bits	(below)
145 - 147	3	tail bits	(below)
(148 - 156	8,25	guard period (bits)	subclause 5.2.8)

- where the "tail bits" are defined as modulating bits with states as follows:

(BN0, BN1, BN2)	=(0, 0, 0)	and
(BN145, BN146, BN147)	=(0, 0, 0)	

- where the "mixed bits" are defined as modulating bits with states as follows:

(BN3, BN4 BN144)	=	(1, 1, 1, 1, 1, 0, 1, 1, 0, 1, 1, 1, 0, 1, 1, 0, 0, 0, 0, 0, 0, 1, 0, 1, 0, 0, 1, 0, 0, 1, 1, 1, 0, 0, 0, 0, 0, 1, 0, 0, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 1, 1, 1, 0, 0, 0, 1, 0, 1, 1, 1, 0, 0, 0, 1, 0, 1, 1, 1, 0, 0, 0, 1, 0, 1
		0, 1, 1, 1, 0, 1, 0, 0, 1, 0, 1, 0, 0, 0, 1, 1, 0, 0, 1, 1, 0, 0, 1, 1, 1, 0, 0, 1, 1, 1, 1, 0, 1, 0, 0, 1, 1, 1, 1, 1, 0, 0, 0, 1, 0, 0, 1, 0, 1, 1, 1, 1, 1, 0, 1, 0, 1, 0)

# 5.2.7 Access burst (AB)

Bit Number (BN)	Length of field	Contents of field	Definition
 0 - 7	8	extended tail bits	(below)
8 - 48	41	synch. sequence bits	(below)
49 - 84	36	encrypted bits (e0e35)	05.03
85 - 87	3	tail bits	(below)
(88 - 156	68,25	extended guard period (bits)	subclause 5.2.8)

- where the "extended tail bits" are defined as modulating bits with the following states:

(BN0, BN1, BN2 .. BN7) = (0, 0, 1, 1, 1, 0, 1, 0)

- where the "tail bits" are defined as modulating bits with the following states:

(BN85, BN86, BN87) = (0, 0, 0)

- where the "synch. sequence bits" are defined as modulating bits with the following states, unless explicitly stated otherwise (see GSM 04.60):

(BN8, BN9 .. BN48) = (0, 1, 0, 0, 1, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 1, 1, 0, 0, 1, 1, 0, 1, 0, 1, 0, 1, 0, 0, 0, 1, 1, 1, 1, 0, 0, 0)

in case alternative training (synchronization) sequence "TS1" is used, the "synch. sequence bits" shall be defined as modulating bits with the following states:

in case alternative training (synchronization) sequence "TS2" is used, the "synch. sequence bits" shall be defined as modulating bits with the following states:

# 5.2.8 Guard period

The guard period is provided because it is required for the MSs that transmission be attenuated for the period between bursts with the necessary ramp up and down occurring during the guard periods as defined in GSM 05.05. A base transceiver station is not required to have a capability to ramp down and up between adjacent bursts, but is required to have a capability to ramp down and up for non-used time-slots, as defined in GSM 05.05. In any case where the amplitude of transmission is ramped up and down, then by applying an appropriate modulation bit stream interference to other RF channels can be minimized.

# 5.3 Physical channels and bursts

The description of a physical channel will be made in terms of timeslots and TDMA frames and not in terms of bursts. This is because there is not a one to one mapping between a particular physical channel, and the use of a particular burst.

# 5.4 Radio frequency channel sequence

The radio frequency channel sequence is determined by a function that, in a given cell, with a given set of general parameters, (see subclause 5.6.2), with a given timeslot number (TN), a given mobile radio frequency channel allocation (MA) and a given mobile allocation index offset (MAIO), maps the TDMA frame number (FN) to a radio frequency channel.

In a given cell there is therefore, for a physical channel assigned to a particular mobile, a unique correspondence between radio frequency channel and TDMA frame number.

The detailed hopping generation algorithm is given in subclause 6.2.

# 5.5 Timeslot and TDMA frame sequence

A given physical channel shall always use the same timeslot number in every TDMA frame. Therefore a timeslot sequence is defined by:

- i) a timeslot number (TN); and
- ii) a TDMA frame number sequence.

The detailed definitions of TDMA frame number sequences are given in clause 7.

The physical channels where the TDMA frame number sequence is 0,1. . FN\_MAX (where FN\_MAX is defined in subclause 4.3.3) are called "basic physical channels".

# 5.6 Parameters for channel definition and assignment

# 5.6.1 General

This subclause describes the set of parameters necessary to describe fully the mapping of any logical channel onto a physical channel. These parameters may be divided into general parameters, that are characteristic of a particular base transceiver station, and specific parameters, that are characteristic of a given physical channel.

# 5.6.2 General parameters

These are:

- i) the set of radio frequency channels used in the cell (CA), together with the identification of the BCCH carrier.
- ii) the TDMA frame number (FN), which can be derived from the reduced TDMA frame number (RFN) which is in the form T1, T2, T3', see 3.3.2.

These parameters are broadcast (or derived from parameters broadcast) in the BCCH and SCH.

For COMPACT, these are:

- i) the set of radio frequency channels used in the cell (CA), together with the identification of the COMPACT CPBCCH carrier (primary COMPACT carrier).
- ii) the TDMA frame number (FN), which can be derived from the reduced TDMA frame number (RFN) which is in the form R1 and R2, see 3.3.2.
- iii) the time group number (TG)

These parameters are broadcast (or derived from parameters broadcast) in the COMPACT CPBCCH and CSCH.

# 5.6.3 Specific parameters

These parameters define a particular physical channel in a base transceiver station. They are:

- o) the training sequence Code (TSC);
- i) the timeslot number (TN);
- ii) the mobile radio frequency channel allocation (MA);
- iii) the mobile allocation index offset (MAIO);
- iv) the hopping sequence number (HSN);
- v) the type of logical channel;
- vi) the sub-channel number (SCN).

The last two parameters allow the determination of the frame sequence.

# 6 Mapping of logical channels onto physical channels

# 6.1 General

The detailed mapping of logical channels onto physical channels is defined in the following sections. Subclause 6.2 defines the mapping from TDMA frame number (FN) to radio frequency channel (RFCH). Subclause 6.3 defines the mapping of the physical channel onto TDMA frame number. Subclause 6.4 lists the permitted channel combinations and subclause 6.5 defines the operation of channels and channel combinations.

# 6.2 Mapping in frequency of logical channels onto physical channels

# 6.2.1 General

The parameters used in the function which maps TDMA frame number onto radio frequency channel are defined in subclause 6.2.2. The definition of the actual mapping function, or as it is termed, hopping sequence generation is given in subclause 6.2.3.

In CTS, the specific mapping in frequency depends on the start condition defined by the parameters given in subclause 6.2.2. The hopping sequence generation for CTS is given in subclause 6.2.3.

# 6.2.2 Parameters

The following parameters are required in the mapping from TDMA frame number to radio frequency channel for a given assigned channel.

General parameters of the BTS, specific to one BTS, and broadcast in the BCCH and SCH:

- i) CA: Cell allocation of radio frequency channels.
- ii) FN: TDMA frame number, broadcast in the SCH, in form T1, T2, T3' (see subclause 3.3.2). For COMPACT, FN is broadcast in the CSCH, in form R1, R2 (see subclause 3.2.2).

Specific parameters of the channel, defined in the channel assignment message:

i) MA: Mobile allocation of radio frequency channels, defines the set of radio frequency channels to be used in the mobiles hopping sequence. The MA contains N radio frequency channels, where  $1 \le N \le 64$ .

For COMPACT, the reduced MA (see GSM 04.60) shall be used for a fixed amount of data blocks, see section 6.2.4.

ii) MAIO: Mobile allocation index offset.(0 to N-1, 6 bits).

For COMPACT, MAIO\_2 shall be used for the data blocks using the reduced MA.

iii) HSN: Hopping sequence (generator) number (0 to 63, 6 bits).

In CTS, the following parameters are required in the mapping to radio frequency channel for a CTS-FP and CTS-MS pair. They are given by the CTS-FP to the CTS-MS during the non-hopping access procedure :

- i) VA: the vector <u>a</u> defines the elements which are used from the shift register to generate the codeword. The vector <u>a</u> shall be randomly chosen upon up to 16 non-repeating integer elements where  $0 \le a_i < 16$  and  $a_i \ne a_j$  for  $i \ne j$ .
- ii) VV: the elements of vector  $\underline{v}$  are added modulo 2 to the codeword from the shift register. For vector  $\underline{v}$ , up to 16 binary elements shall be chosen randomly.
- NOTE: The length of the vectors  $\underline{a}$  and  $\underline{v}$  is dependent on the number of frequencies used for the hopping and can be truncated according to the number of frequencies used (see vi) below).
- iii) CSR: current shift register contents. In order that a CTS-MS is able to synchronize on a running hopping sequence the CTS-FP transmits the CSR.
- iv) TFHC1: value of counter TFHC1.
- v) TFHC2: value of counter TFHC2.
- vi) TFH carrier list (see GSM 05.56) : ordered list of frequencies, with 1<sup>st</sup> freq referenced by the frequency index 1, 2<sup>nd</sup> frequency referenced by the frequency index 2, etc.

The number of frequencies in the TFH carrier list, NF shall be computed. The number of elements to be taken from the vectors <u>a</u> and <u>v</u> shall be determined by the function  $\lceil \log_2 NF \rceil$ 

vii)VC: the vector <u>c</u> is the base sequence to map the codeword. It shall be randomly chosen upon NF non-repeating integer elements:

 $c = \{c_0, c_1, ..., c_{NF-1}\}, 0 \le c_i < NF \text{ and } c_i \ne c_j \text{ for } i \ne j.$ 

## 6.2.3 Hopping sequence generation

For a given set of parameters, the index to an absolute radio frequency channel number (ARFCN) within the mobile allocation (MAI from 0 to N-1, where MAI=0 represents the lowest absolute radio frequency channel number (ARFCN) in the mobile allocation, ARFCN is in the range 0 to 7023 and the frequency value can be determined according to GSM 05.05 sec 2 with n= ARFCN), is obtained with the following algorithm:

**if** HSN = 0 (cyclic hopping) **then**:

MAI, integer (0 .. N-1) : MAI = (FN + MAIO) modulo N

else:

M, integer (0 .. 152) : M = T2 + RNTABLE((HSN xor T1R) + T3)

S, integer (0 .. N-1) :  $M' = M \mod (2^N BIN)$ 

 $T' = T3 \mod (2 \land NBIN)$ 

#### if M' < N then:

S = M'

#### else:

 $S = (M'+T') \mod N$ 

MAI, integer (0 .. N-1) : MAI = (S + MAIO) modulo N

NOTE: Due to the procedure used by the mobile for measurement reporting when DTX is used, the use of cyclic hopping where (N)mod 13 = 0 should be avoided.

where:

T1R: time parameter T1, reduced modulo 64 (6 bits)

T3: time parameter, from 0 to 50 (6 bits)

T2: time parameter, from 0 to 25 (5 bits)

NBIN: number of bits required to represent  $N = INTEGER(log_2(N)+1)$ 

^: raised to the power of

xor: bit-wise exclusive or of 8 bit binary operands

RNTABLE: Table of 114 integer numbers, defined below:

Address					Conten	ts				
000009:	48,	98,	63,	1,	36,	95,	78,	102,	94,	73,
010019:	0,	64,	25,	81,	76,	59,	124,	23,	104,	100,
020029:	101,	47,	118,	85,	18,	56,	96,	86,	54,	2,
030039:	80,	34,	127,	13,	6,	89,	57,	103,	12,	74,
040049:	55,	111,	75,	38,	109,	71,	112,	29,	11,	88,
050059:	87,	19,	З,	68,	110,	26,	33,	31,	8,	45,
060069:	82,	58,	40,	107,	32,	5,	106,	92,	62,	67,
070079:	77,	108,	122,	37,	60,	66,	121,	42,	51,	126,
080089:	117,	114,	4,	90,	43,	52,	53,	113,	120,	72,
090099:	16,	49,	7,	79,	119,	61,	22,	84,	9,	97,
100109:	91,	15,	21,	24,	46,	39,	93,	105,	65,	70,
110113:	125,	99,	17,	123,						

The hopping sequence generation algorithm is represented diagrammatically in figure 6.

This algorithm applies also to COMPACT, whereby the parameters T1, T2 and T3 shall be calculated from FN.

In CTS, the general structure of the hopping sequence generation algorithm is shown in figure 6a, with the example of vector  $\underline{a} = (a_0, a_1, a_2, a_3) = (5, 8, 2, 11)$  and NF = 9. It consists of a 16 bit linear feedback shift register and two counters. The shift register in the CTS-FP shall be initialized with a random number which shall not be zero. The counter TFHC1 counts modulo NF the number of TDMA frames. The overflow of this counter causes a shift in the shift register. The counter TFHC2 counts modulo NF the number of shifts.

The elements which are used from the shift register to generate the codeword are defined by the vector  $\underline{a}$ . The codeword is built using a modulo 2 addition of these elements and the elements of vector  $\underline{v}$ . Before mapping the codeword into a sequence, the value of the counter TFHC2 is added modulo NF. The mapping is done by a modulo NF addition to the base sequence  $\underline{c}$ . This results in a sequence containing NF elements, each element representing one frequency index in the TFH list. The value of counter TFHC1 points to the current frequency index to use.

## 6.2.4 Specific cases

On the RFCH carrying a BCCH (C0), frequency hopping is not permitted on any timeslot supporting a BCCH according to table 3 of clause 7. A non-hopping radio frequency channel sequence is characterized by a mobile allocation consisting of only one radio frequency channel, i.e. with N=1, MAIO=0. In this instance sequence generation is unaffected by the value of the value HSN.

For COMPACT, frequency hopping is not permitted on CPBCCH or CPCCCH for a specific amount of N\_CCCH\_NH blocks according to the ordered list described in subclause 6.3.2.1. If CPCCCH is defined as frequency hopping, those blocks use MAI = MAIO.

For COMPACT, on other frequency hopping channels, the reduced MA and MAIO\_2 shall be used for a specific amount of N\_CCCH\_NH blocks according to the ordered list described in subclause 6.3.2.1.

# 6.2.5 Change in the frequency allocation of a base transceiver station

The consequence of adding or removing a number of radio frequency channels in a base transceiver station is a modification of the cell allocation (CA) and the mobile allocation (MA). In order to achieve this without disruption to mobile stations with currently assigned channels it is necessary to send a message to all mobiles with assigned channels. The message, as defined in 04.08, will contain a new cell allocation (if necessary), mobile allocation and a time (in the form of a TDMA frame number) at which the change is to occur. A new cell allocation may not be necessary if channels are only being removed, and not added.

# 6.2.6 Frequency assignment in CTS

The CTSBCH (CTSBCH-FB and CTSBCH-SB) shall always be mapped on the CTSBCH RF channel (designated as C0 in clause 7 table 8).

The CTSPCH, CTSARCH and CTSAGCH shall be mapped on the predefined set of carriers called TFH carrier list (designated by C0... Cn in Clause 7 Table 8) by the CTS frequency hopping algorithm specified in subclauses 6.2.2 and 6.2.3. However, the CTSARCH and CTSAGCH shall be mapped on the CTSBCH RF channel for the specific case of the non-hopping access procedure specified in GSM 04.56; the block TDMA frame mapping for these exceptions is specified in clause 7 table 8. The methods for the determination of the CTSBCH RF channel and the TFH carrier list are defined in GSM 05.56.

The TCH, FACCH and SACCH used for a CTS dedicated connection shall always be mapped on the TFH carrier list (C0..Cn) by the CTS frequency hopping algorithm. However, one exception is specified in the case of the CTS enrolment and attachment of a CTS-MS (see GSM 04.56), where a non-hopping access procedure is used; in these particular cases, the dedicated connection shall be used in non-hopping mode and the TCH, FACCH and SACCH shall be mapped on the CTSBCH RF channel (C0).

# 6.3 Mapping in time of logical channels onto physical channels

# 6.3.1 Mapping in time of circuit switched logical channels onto physical channels

#### 6.3.1.1 General

The mapping in time of circuit switched logical channels is defined in the tables of clause 7, which also defines the relationship of the air interface frames to the multiframe.

#### 6.3.1.2 Key to the mapping table of clause 7

The following relates to the tables of clause 7. The columns headed:

- i) "Channel designation" gives the precise acronym for the channel to which the mapping applies.
- ii) "Sub-channel number" identifies the particular sub-channel being defined where a basic physical channel supports more than one channel of this type.
- iii) "Direction" defines whether the mapping given applies identically to downlink and uplink (D&U), or to downlink (D) or uplink (U) only.
- iv) "Allowable timeslots assignments" defines whether the channel can be supported on, or assigned to, any of the timeslots, or only on specific timeslots.
- v) "Allowable RF channel assignments" defines whether the channel can use any or all of the radio frequency channels in the cell allocation (CA), or only the BCCH carrier (C0). It should be noted that any allocated channel Cx within CA could be any radio frequency channel, and that no ordering of radio frequency channel number is implied. For example, allocated channel C0 need not have the lowest radio frequency channel number of the allocation.
- vi) "Burst type" defines which type of burst as defined in clause 5.2 is to be used for the physical channel.
- vii)"Repeat length in TDMA frames" defines how many TDMA frames occur before the mapping for the interleaved blocks repeats itself e.g. 51.
- viii) "Interleaved block TDMA frame mapping" defines, within the parentheses, the TDMA frames used by each interleaved block (e.g. 0..3). The numbers given equate to the TDMA frame number (FN) modulo the number of TDMA frames per repeat length; Therefore, the frame is utilized when:

TDMA frame mapping number = (FN)mod repeat length given

Where there is more than one block shown, each block is given a separate designation e.g. B0, B1. Where diagonal interleaving is employed then all of the TDMA frames included in the block are given, and hence the same TDMA frame number can appear more than once (see GSM 05.03). Also, for E-TCH/F28.8, E-TCH/F32.0 and E-TCH/F43.2, the same frame number appears for the inband signalling message and for several interleaved blocks. It should be noted that the frame mapping for the SACCH/T channel differs according to the timeslot allocated in order to lower the peak processing requirements of the BSS.

#### 6.3.1.3 Mapping of BCCH data

In order to facilitate the MS operation, it is necessary to transmit some System Information messages in defined multiframes and defined blocks within one multiframe, as follows (where  $TC = (FN DIV 51) \mod (8)$ ). Also for some System Information messages, the position where they are transmitted is contained in other System Information messages:

System Information Message Type 1 Type 2 Type 2 bis Type 2 ter Type 2 quater	Sent when TC = 0 1 5 5 or 4 5 or 4 or 5	Allocation BCCH Norm BCCH Norm BCCH Norm BCCH Norm BCCH Norm
Type 3 Type 4 Type 7 Type 8 Type 9 Type 13	2 and 6 3 and 7 7 3 4 4 4 or 0	BCCH Norm BCCH Norm BCCH Ext BCCH Ext BCCH Norm BCCH norm BCCH Ext
Type 16 Type 17 Type 18 Type 19 Type 20	6 2 Not fixed Not Fixed Not fixed	BCCH Ext BCCH Ext Not fixed Not Fixed Not fixed

This subclause defines requirements on minimum scheduling: the network may send any System Information message when sending of a specific System Information message is not required. The following rules apply:

- i) BCCH Ext may share the resource with PCH and AGCH (see subclause 6.5.1).
- ii) System Information Type 1 need only be sent if frequency hopping is in use or when the NCH is present in a cell. If the MS finds another message when TC = 0, it can assume that System Information Type 1 is not in use.
- iii) System information type 2 bis or 2 ter messages are sent if needed, as determined by the system operator. If only one of them is needed, it is sent when TC = 5. If both are needed, 2bis is sent when TC = 5 and 2ter is sent at least once within any of 4 consecutive occurrences of TC = 4. A SI 2 message will be sent at least every time TC = 1. System information type 2 quater is sent if needed, as determined by the system operator. If sent on BCCH Norm, it shall follow the same rules as System information type 2 ter. If sent on BCCH Ext, it is sent at each occurrence of TC = 5.
- iv) The definitions of BCCH Norm and BCCH Ext are given in clause 7 table 3 of 5.
- v) Use of System Information type 7 and 8 is not always necessary. It is necessary if System Information type 4 does not contain all information needed for cell selection and reselection.
- vi) System Information type 9 is sent in those blocks with TC = 4 which are specified in system information type 3 as defined in GSM 04.08.
- vii) System Information type 13 is only related to the GPRS service. System Information Type 13 need only be sent if GPRS support is indicated in one or more of System Information Type 3 or 4 or 7 or 8 messages. These messages also indicate if the message is sent on the BCCH Norm or if the message is transmitted on the BCCH

Ext. In the case that the message is sent on the BCCH Norm, it is sent at least once within any of 4 consecutive occurrences of TC=4.

- viii) System Information type 16 and 17 are only related to the SoLSA service.
- ix) System Information type 18 and 20 are sent in order to transmit non-GSM broadcast information. The frequency with which they are sent is determined by the system operator. System Information type 9 identifies the scheduling of System Information type 18 and 20 messages.
- x) System Information Type 19 is sent if COMPACT neighbours exist. If System Information Type 19 is present, then its scheduling shall be indicated in System Information Type 9.

All the allowable timeslot assignments in a frame (see table 3 of 7 in clause 7) shall contain the same information.

#### 6.3.1.4 Mapping of SID Frames

When the DTX mode of operation is active, it is required to transmit Silence Descriptor (SID) information, or equivalent dummy information, during the SACCH/T block period (104 TDMA frames). As the SID frames do not constitute a logical channel and their use is specific to DTX operation, the mapping of SID frames onto the TDMA frames is specified in GSM 05.08.

# 6.3.2 Mapping in time of packet logical channels onto physical channels

#### 6.3.2.1 General

A physical channel allocated to carry packet logical channels is called a packet switched channel (PDCH). A PDCH shall carry packet logical channels only.

Packet switched logical channels are mapped dynamically onto a 52-multiframe.

The 52-multiframe consists of 12 blocks of 4 consecutive frames, 2 idle frames and 2 frames used for the PTCCH (see GSM 05.10 and 03.64), as shown in Figure 9. A block allocated to a given logical channel comprises of one radio block or, in uplink only, 4 random access bursts. The type of channel may vary on a block by block basis. Table 6 in clause 7, indicates the frame numbers for each of the blocks (B0...B11) transmitted in the multiframe. The ordered list of block is defined as B0, B6, B3, B9, B1, B7, B4, B10, B2, B8, B5, B11.

In the downlink direction, the logical channel type shall be indicated by the message type contained in the block header part.

In the uplink part for channels other than PACCH transmitted as access bursts or PRACH or CPRACH, the logical channel type shall be indicated by the message type contained in the block header part. For PACCH transmitted as access bursts, the logical channel type is indicated by the corresponding polling message on the downlink (see 04.60). For the PRACH or CPRACH case the logical channel type is indicated by the USF (See GSM 04.60), set on the downlink on a block by block basis.

For COMPACT, timeslot mapping and rotation of the control channels is used such that control channels belonging to a serving time group are rotated over odd timeslot numbers as follows: 7, 5, 3, 1, 7, 5 ... The rotation occurs between frame numbers (FN) mod 52 = 3 and 4. The mapping of the control channels on timeslot numbers is defined by the following formula:

- for  $0 \le FN \mod 52 \le 3$ ,  $TN = ((6 \ x \ ((FN \ div \ 52) \ mod \ 4)) + 1 + (2 \ x \ TG)) \ mod \ 8;$
- for  $4 \le FN \mod 52 \le 51$ ,  $TN = ((6 \ x \ ((FN \ div \ 52) \ mod \ 4)) + 7 + (2 \ x \ TG)) \ mod \ 8$ .

Packet switched logical channels PDTCH, PACCH, and PTCCH are never rotated.

### 6.3.2.2 Mapping of the uplink channels

#### 6.3.2.2.1 Mapping of uplink packet traffic channel (PDTCH/U) and PACCH/U

The PDCH's where the MS may expect occurrence of its PDTCH/U(s) or PACCH/U for a mobile originated transfer is indicated in resource allocation messages (see GSM 04.60). PACCH/U shall be allocated respecting the resources allocated to the MS and the MS multislot class. For each PDCH allocated to the MS, an Uplink State Flag (R0... R7) is given to the MS.

The occurrence of the PDTCH/U and/or the PACCH/U at given block(s) Bx (where Bx = B0...B11) in the 52multiframe structure for a given MS on a given PDCH shall be indicated by the value of the Uplink State Flag (USF) contained in the header of the preceding block transmitted in the downlink of the same PDCH, that is to say B(x-1) in the same multiframe if  $x \ge 1$  or B(11) in the previous multiframe if x=0. If the USF in block B(x-1) indicates that block B(x) shall be used by an MS for which the USF\_GRANULARITY is set to 1 (corresponding to 4 blocks) in the last assignment message, that MS shall also use the three following blocks. The USF corresponding to the last three blocks shall be set to an unused value. The MS may transmit a PDTCH block or a PACCH block on any of the uplink blocks used by the MS. The occurrence of the PACCH/U associated to a PDTCH/D shall be indicated by the network by polling the MS (see GSM 04.60).

NOTE: This subclause specifies how the network shall signal that the MS is allowed to use the uplink. The operation of the MS is specified in GSM 04.60. In particular cases of fixed allocation or extended dynamic allocation the MS may not need to monitor the USF on all allocated PDCHs.

For COMPACT, USF\_GRANULARITY should be set to 0 (corresponding to 1 block) for dynamic allocation for the following cases:

- i) for odd timeslot numbers (TN) 1, 3, 5, and 7 in nominal and large cells;
- ii) for even timeslot numbers (TN) 0, 2, 4, and 6 in large cells.

#### 6.3.2.2.2 Mapping of the Packet Timing Advance Control Channel (PTCCH/U)

The PDCH carrying the PTCCH/U of one MS is defined in the resource allocation message (see GSM 04.60). PTCCH/U shall be mapped to one of the time slots where PDTCH(s) are allocated to the MS. PTCCH/U shall be allocated respecting the resources allocated to the MS and the MS multislot class. An MS shall be allocated a sub-channel of the PTCCH/U (0...15) as defined in clause 7 table 6, where the sub-channel number is equal to the Timing Advance Index (TAI) indicated in the resource allocation message (see GSM 04.60).

#### 6.3.2.2.3 Mapping of the uplink PCCCH i.e. PRACH

The mapping of the PRACH is defined in clause 7 table 6, where the possible blocks are indicated. The PRACH is dynamically allocated in groups of four PRACH blocks By (y=4x+i, i=0,..., 3) corresponding to one PDCH block Bx (x=0,...,11), indicated by USF=FREE in the same way as defined for PDTCH/U (see subclause 6.3.2.2.1).

Optionally, a subset of the blocks Bx can be allocated to PRACH in a fixed way. The number of allocated blocks is indicated by the parameter BS\_PRACH\_BLKS broadcast on the PBCCH, where BS\_PRACH\_BLKS=0...12. The blocks are allocated according to the ordered list defined in subclause 6.3.2.1. The blocks shall also be indicated by the USF=FREE. The MS may choose to use the BS\_PRACH\_BLKS or USF to determine the fixed allocated part of PRACH.

#### 6.3.2.2.3a Mapping of the COMPACT uplink CPCCCH i.e. CPRACH

The CPRACH is dynamically or fixed allocated in the same way as defined for PRACH (see subclause 6.3.2.2.3. USF should be set equal to FREE for downlink block B0 on a serving time group when 4 time groups are assigned. Uplink blocks (other than block B1 on a serving time group) that are preceded by CPBCCH and CPCCCH blocks should be prioritized for use as CPRACH.

See Annex D for examples based on sixteen prioritized CPRACH blocks.

#### 6.3.2.3 Mapping of the downlink channels

#### 6.3.2.3.1 Mapping of the (PDTCH/D) and PACCH/D

The PDCH where the MS may expect occurrence of its PDTCH/D(s) for a mobile terminated transfer or its PACCH/D, for both mobile originated and mobile terminated transfer are indicated in resource allocation messages (see GSM 04.60). The logical channel type shall be indicated in the block header. The mobile owner of the PDTCH/D or PACCH/D shall the indicated by the TFI (Temporary Frame Identifier) (see GSM 04.60).

#### 6.3.2.3.2 Mapping of the PTCCH/D

The PTCCH/D is mapped as defined in Clause 7 table 6. The PTCCH/D carries signalling messages including timing advance information for MSs sharing the PTCCH/U on the same PDCH.

#### 6.3.2.3.3 Mapping of the PBCCH

The PBCCH is mapped onto one PDCH only, indicated in the BCCH. The PBCCH is mapped on BS\_PBCCH\_BLKS blocks (where  $1 \le BS_PBCCH_BLKS \le 4$ ) per multiframe, according to the ordered list described in subclause 6.3.2.1. The blocks allocated are specified in Clause 7 table 6. The parameter BS\_PBCCH\_BLKS is broadcast on PBCCH in block B0 (see subclause 3.3.2.4).

#### 6.3.2.3.3a Mapping of the COMPACT CPBCCH

The CPBCCH is mapped onto a primary COMPACT carrier on the time group indicated by TG on CSCH (see subclause 3.3.2.2). This time group is known as the serving time group and rotates over odd timeslot numbers (see subclause 6.3.2.1). The CPBCCH is mapped on BS\_PBCCH\_BLKS blocks (where  $1 \le BS_PBCCH_BLKS \le 4$ ) per multiframe, according to the ordered list described in subclause 6.3.2.1. The blocks allocated are specified in clause 7 table 9. The parameters BS\_PBCCH\_BLKS is broadcast on CPBCCH in block B0 (see subclause 3.3.2.4).

See Annex D for examples based on one CPBCCH block.

When USF=FREE in downlink block B0 on a serving time group, the CPRACH is allocated in uplink block B1 after timeslot rotation. When USF has any other value in downlink block B0 on a serving time group, the uplink allocation of B1 is valid for the same timeslot, irrespective of timeslot rotation.

#### 6.3.2.3.4 Mapping of the PCCCH

The PCCCH and its different logical channels (PAGCH, PPCH, PNCH) and the PDTCH and PACCH can be mapped dynamically and are identified by the message header. The configuration is partly fixed by some parameters broadcast by the PBCCH and defined in subclause 3.3.2.4:

- a) BS\_PBCCH\_BLKS, that defines the number of PBCCH blocks per multiframe, according to the ordered list described in subclause 6.3.2.1, on the PDCH that carries PBCCH;
- b) BS\_PAG\_BLKS\_RES, that defines the number of blocks in addition to BS\_PBCCH\_BLKS, according to the ordered list described in subclause 6.3.2.1, where paging shall not occur on every PDCH that carries PCCCH.

If PBCCH is allocated on timeslot k, PCCCHs shall be allocated only on timeslots n where n>k-4 and  $0\le n\le 7$  in order to provide time for the MS to switch from PBCCH to PCCCH.

#### 6.3.2.3.4a Mapping of the COMPACT CPCCCH

The CPCCCH and its different logical channels (CPAGCH, CPPCH, CPNCH) and the PDTCH and PACCH can be mapped dynamically and are identified by the message header. The configuration is partly fixed by some parameters broadcast by the CPBCCH and defined in subclause 3.3.2.4:

a) BS\_PBCCH\_BLKS, that defines the number of CPBCCH blocks per multiframe, according to the ordered list described in subclause 6.3.2.1, on the radio frequency channel that carries CPBCCH;

b) BS\_PAG\_BLKS\_RES, that defines the number of blocks in addition to BS\_PBCCH\_BLKS, where paging shall not occur on every radio frequency channel that carries CPCCCH. These blocks without paging are allocated after CPPCH blocks according to the ordered list described in subclause 6.3.2.1.

For primary COMPACT carriers, CPCCCHs shall be allocated on the same time group as CPBCCH. CPCCCHs on secondary COMPACT carrier(s) shall be allocated on same time group as for primary COMPACT carrier.

See Annex D for examples based on three CPCCCH blocks.

### 6.3.2.4 Mapping of PBCCH data

In order to facilitate the MS operation, the network is required to transmit certain types of Packet System Information (PSI) messages in specific multiframes and specific PBCCH blocks within the multiframes. The occurrence of the PSI1 message is defined by TC = (FN DIV 52) mod PSI1\_REPEAT\_PERIOD, where PSI1\_REPEAT\_PERIOD (range 1 - 16) is indicated in the SI13 message on BCCH, the PSI 1 message on PBCCH and, if present, in the Neighbour Cell parameters in PSI3 and PSI3bis messages sent on serving cell PBCCH.

The PSI1 message is transmitted at TC = 0 according to rule i) and ii) below.

The PSI messages other than the PSI1 message are divided into two groups of PSI messages. One group of PSI messages is transmitted with a low repetition rate and a second group is transmitted with a high repetition rate.

The number of PSI message instances sent with high repetition rate is indicated by the parameter PSI\_COUNT\_HR (range 0 to 16) in the PSI1 message. The PSI messages in this group are sent according to rule iii) below.

The number of PSI message instances sent with low repetition rate is indicated by the parameter PSI\_COUNT\_LR (range 0 to 63) in the PSI1 message. The PSI messages in this group are sent according to rule iv) below.

The following rules apply:

- i) PSI1 shall be sent in block B0 when TC = 0;
- ii) if the value of the parameter BS\_PBCCH\_BLKS is greater than 1, the PSI1 shall also be sent in block B6 when TC = 0;
- iii) the PSI messages in the group sent with high repetition rate shall be sent in a sequence determined by the network and starting at TC = 0, using the PBCCH blocks within each multiframe, in the order of occurrence, which are not occupied according to rule i) or ii). The sequence of these PSI messages shall be repeated starting at each occurrence of TC = 0;
- iv) the PSI messages in the group sent with low repetition rate shall be sent in a sequence determined by the network and continuously repeated, using the PBCCH blocks within each multiframe, in the order of occurrence, which are not occupied according to rules i) to iii). The sequence of these PSI messages shall be restarting at FN = 0.

If there are multiple instances of a particular type of PSI message (See GSM 04.60), they shall all be sent within same group of PSI messages according to either rule iii) or iv) above. They shall be sent in a single sequence in the ascending order of the message instance number of that type of PSI message.

The same PSI message shall not occur twice within the lists defined by PSI\_COUNT\_LR and PSI\_COUNT\_HR

A full set of Packet System Information messages contains one consistent set of the messages included in PSI\_COUNT\_LR and one consistent set of the messages included in PSI\_COUNT\_HR plus the PSI1 message.

NOTE: The parameters BS\_PBCCH\_BLKS and PSI1\_REPEAT\_PERIOD\_shall be selected by the network such that all PSI message present in the cell can be sent according to rules i) to iv) above. It is the responsibility of the network to optimise the broadcast of the PSI messages so that the MS can find the important parameters for cell re-selection and access as fast as possible without unnecessary power consumption. The PSI mapping scheme information can be utilised by the MS to estimate the actual minimum cell reselection time.

### 6.3.2.4a Mapping of COMPACT CPBCCH data

See subclause 6.3.2.4, with the exception that the CPBCCH is a stand-alone packet control channel for COMPACT.

# 6.3.3 Mapping in time of CTS control channels onto physical channels

The mapping in time of CTS control channels is defined in the table 8 of clause 7, which also defines the relationship of the air interface TDMA frames to the multiframe.

The timeslot assignment of the CTS control channel is defined hereafter.

#### 6.3.3.1 CTSBCH timeslot assignment

For the CTSBCH, a procedure of timeslot shifting from one 52-multiframe to another is defined. The usage of this procedure is mandatory in CTS idle mode and optional in CTS dedicated mode. When the shifting procedure is not applied, the CTSBCH timeslot number shall be equal to the TNC broadcast in the current 52-multiframe CTSBCH-SB.

The following parameters are required for the timeslot shifting procedure.

Parameters broadcast in the CTSBCH-SB:

- a) TNI: initial timeslot number (0 to 7, 3 bits), defined by the three LSBs (BN3, BN2, BN1) of the FPBI (specified in GSM 03.03);
- b) TNSCN: timeslot number series couple number (0 to 31, 5 bits), defined by the 5 bits (BN8, ..., BN4) of the FPBI. Defines the couple of timeslot number circular series (TNS<sub>TNSCN,0</sub>, TNS<sub>TNSCN,1</sub>) to be used to form the timeslot shifting sequence. See timeslot number series (TNS) definition in table below.

TNSCN	TNS <sub>TNSCN,0</sub>	TNS <sub>TNSCN,1</sub>	TNSCN	TNS <sub>TNSCN,0</sub>	TNS <sub>TNSCN,1</sub>
0	(0, 1, 2, 4, 7, 5, 6, 3),	(0,3,5,7,6,2,1,4)	16	(0, 1, 5, 6, 7, 4, 3, 2),	(0,4,7,6,2,5,1,3)
1	(0, 1, 2, 5, 3, 6, 7, 4),	(0,4,1,5,7,6,3,2)	17	(0, 2, 1, 3, 6, 7, 5, 4),	(0,3,7,4,1,5,6,2)
2	(0, 1, 2, 6, 5, 3, 7, 4),	(0,3,6,7,5,2,4,1)	18	(0, 2, 1, 5, 6, 7, 4, 3),	(0,4,7,5,1,3,6,2)
3	(0, 1, 2, 6, 7, 5, 4, 3),	(0,3,7,4,6,2,5,1)	19	(0, 2, 3, 4, 7, 6, 5, 1),	(0,3,1,5,2,6,7,4)
4	(0, 1, 3, 2, 5, 6, 7, 4),	(0,4,7,6,2,1,5,3)	20	(0, 2, 3, 6, 7, 5, 1, 4),	(0,4,7,6,3,5,2,1)
5	(0, 1, 3, 6, 7, 5, 2, 4),	(0,3,7,4,2,6,5,1)	21	(0, 2, 3, 7, 5, 6, 4, 1),	(0,3,6,2,1,5,7,4)
6	(0, 1, 4, 2, 5, 6, 7, 3),	(0, 2, 6, 3, 7, 5, 4, 1)	22	(0, 2, 4, 7, 3, 6, 5, 1),	(0,3,5,6,7,4,1,2)
7	(0, 1, 4, 2, 5, 7, 6, 3),	(0,4,7,3,5,6,2,1)	23	(0, 2, 5, 3, 6, 7, 4, 1),	(0,3,7,6,5,1,2,4)
8	(0, 1, 4, 2, 6, 5, 7, 3),	(0,2,1,5,3,6,7,4)	24	(0, 2, 5, 3, 7, 6, 4, 1),	(0,3,5,1,2,6,7,4)
9	(0, 1, 4, 5, 7, 3, 6, 2),	(0,3,7,6,5,2,4,1)	25	(0, 2, 6, 3, 1, 5, 7, 4),	(0,3,4,7,6,5,1,2)
10	(0, 1, 4, 6, 5, 7, 3, 2),	(0,4,7,5,1,2,6,3)	26	(0, 2, 6, 5, 1, 4, 7, 3),	(0,4,5,7,6,3,1,2)
11	(0, 1, 4, 7, 3, 5, 6, 2),	(0,4,2,1,5,7,6,3)	27	(0, 2, 6, 5, 3, 7, 4, 1),	(0,3,6,7,5,1,2,4)
12	(0, 1, 4, 7, 6, 3, 5, 2),	(0,4,2,1,5,6,7,3)	28	(0, 3, 5, 1, 2, 6, 7, 4),	(0,4,7,6,5,2,3,1)
13	(0, 1, 5, 2, 4, 7, 6, 3),	(0,3,7,5,1,4,6,2)	29	(0, 3, 5, 2, 6, 7, 4, 1),	(0,4,7,3,6,5,1,2)
14	(0, 1, 5, 2, 6, 4, 7, 3),	(0,3,4,5,7,6,2,1)	30	(0, 3, 6, 7, 4, 2, 5, 1),	(0,4,1,2,6,5,7,3)
15	(0, 1, 5, 6, 2, 4, 7, 3),	(0,3,7,6,4,5,2,1)	31	(0, 3, 7, 5, 6, 2, 4, 1),	(0,4,7,6,3,5,1,2)

#### Table 1 (subclause 6.3.3): TNS<sub>i,j</sub> definition

Parameters sent on a dedicated connection during the CTS-MS attachment:

a) TNSCO : TNS couple order (1 bit), defines together with TNSCN the ordered couple (TNS1, TNS2).

if TNSCO = 0 then (TNS1, TNS2) = (TNS<sub>TNSCN,0</sub>, TNS<sub>TNSCN,1</sub>)

if TNSCO = 1 then (TNS1, TNS2) = (TNS<sub>TNSCN,1</sub>, TNS<sub>TNSCN,0</sub>)

- b) parameters to be used to form the timeslot shifting sequence.
  - x0 : 0 to 7, 3 bits x1 : 0 to 7, 3 bits x2 : 0 to 7, 3 bits x3 : 0 to 7, 3 bits

For a given set of parameters, a unique timeslot shifting sequence of length of 8 x 51 52-multiframes is defined. The shifting sequence is repeated 128 times over the duration of a GSM hyperframe. It is divided into 8 sets of 51 52-multiframes. The structure of a set is explicitly shown on figure below :




Figure 1 (subclause 6.3.3): Structure of timeslot shifting sequence

A set is formed by interleaving segments of TNS1 and TNS2. The mapping of TNS1 and TNS2 segments onto a set is defined by the parameters x0, x1, x2, x3 as follows :

for (FN div 52) mod $51 = 0$	to 7	a TNS1 segment is used
for (FN div 52) mod 51 = 8	to 7+x3	a TNS2 segment is used
for (FN div 52) mod 51 = 8+x3	to 7+x3+x2	a TNS1 segment is used
for (FN div 52) mod 51 = 8+x3+x2	to 7+x3+x2+x1 a	TNS2 segment is used
for (FN div 52) mod 51 = 8+x3+x2+x1	to 7+x3+x2+x1+x0	a TNS1 segment is used
for (FN div 52) mod $51 = 8+x3+x2+x1+x0$	to 15+x3+x2+x1+x0	a TNS2 segment is used
for (FN div 52) mod $51 = 16+x3+x2+x1+x0$	to 23+x3+x2+x1	a TNS1 segment is used
for (FN div 52) mod 51 = 24+x3+x2+x1	to 31+x3+x2	a TNS2 segment is used
for (FN div 52) mod 51 = 32+x3+x2	to 39+x3	a TNS1 segment is used
for (FN div 52) mod 51 = 40+x3	to 47	a TNS2 segment is used
for (FN div 52) mod 51 = 48	to 50	a TNS1 segment is used

The TNS1 and TNS2 segments are extracted from TNS1 and TNS2 according to the following rules :

- a) The first CTSBCH TN used in a shifting sequence shall be the TNI.
- b) Two consecutive CTSBCH TN shall be separated by single circular shifts along TNS1 and TNS2.
- c) When changing from a TNSi segment to a TNSj segment, the last timeslot obtained from TNSi shall be followed by its immediate successor in TNSj.
- NOTE: The first timeslot of a set is obtained by three circular shifts in TNS1 with regard to the first timeslot of the previous set.

An example of the mapping of TNS1 and TNS2 onto the first set of the generated shifting sequence is given in annex C.

#### 6.3.3.2 CTSPCH, CTSARCH and CTSAGCH timeslot assignment

For the CTSPCH, CTSARCH and CTSAGCH, the timeslot shall be assigned by the CTS-FP for each 52-multiframe. The timeslot number used for CTSPCH, CTSARCH and CTSAGCH shall be the TNC broadcast in the previous 52-multiframe CTSBCH-SB.

# 6.4 Permitted channel combinations

## 6.4.1 Permitted channel combinations onto a basic physical channel

The following are the permitted ways, as defined by GSM 04.03, in which channels can be combined onto basic physical channels (numbers appearing in parenthesis after channel designations indicate sub-channel numbers; channels and sub-channels need not necessarily be assigned):

- i) TCH/F + FACCH/F + SACCH/TF
- ii) TCH/H(0,1) + FACCH/H(0,1) + SACCH/TH(0,1)
- iii) TCH/H(0,0) + FACCH/H(0,1) + SACCH/TH(0,1) + TCH/H(1,1)
- iv) FCCH + SCH + BCCH + CCCH
- v) FCCH + SCH + BCCH + CCCH + SDCCH/4(0..3) + SACCH/C4(0..3)
- vi) BCCH + CCCH
- vii) SDCCH/8(0.7) + SACCH/C8(0.7)
- viii) TCH/F + FACCH/F + SACCH/M
- ix) TCH/F + SACCH/M
- x) TCH/FD + SACCH/MD
- xi) PBCCH+PCCCH+PDTCH+PACCH+PTCCH
- xii) PCCCH+PDTCH+PACCH+PTCCH
- xiii) PDTCH+PACCH+PTCCH

where CCCH = PCH + RACH + AGCH + NCH.

and PCCCH=PPCH+PRACH+PAGCH+PNCH.

- $xiv) \quad CTSBCH + CTSPCH + CTSARCH + CTSAGCH \\$
- xv) CTSPCH + CTSARCH + CTSAGCH
- xvi) CTSBCH
- xvii) CTSBCH + TCH/F + FACCH/F + SACCH/CTS
- xviii) E-TCH/F + E-IACCH/F + E-FACCH/F + SACCH/TF
- xix) E-TCH/F + E-IACCH/F + E-FACCH/F + SACCH/M
- xx) E-TCH/F + E-IACCH/F + SACCH/M
- xxi) E-TCH/FD + E-IACCH/F + SACCH/MD
- xxii) CFCCH + CSCH + CPBCCH + CPCCCH + PDTCH + PACCH + PTCCH
- xxiii) CPCCCH+PDTCH+PACCH+PTCCH
- NOTE 1: Where the SMSCB is supported, the CBCH replaces SDCCH number 2 in cases v) and vii) above.

- NOTE 2: A combined CCCH/SDCCH allocation (case v) above) may only be used when no other CCCH channel is allocated.
- NOTE 3: Combinations viii), ix) and x) are used in multislot configurations as defined in subclause 6.4.2.
- NOTE 4: Combinations xiv), xv), xvi) and xvii) shall be used in CTS ; combinations xiv), xvi) and xvii) shall be mutually exclusive ; combinations xiv) and xv) shall also be mutually exclusive.
- NOTE 5: Combinations xxii) and xxiii) shall be used for COMPACT on serving time groups.

# 6.4.2 Multislot configurations

A multislot configuration consists of multiple circuit or packet switched traffic channels together with associated control channels, allocated to the same MS. The multislot configuration occupies up to 8 basic physical channels, with different timeslots numbers (TN) but with the same frequency parameters (ARFCN or MA, MAIO and HSN) and the same training sequence (TSC).

#### 6.4.2.1 Multislot configurations for circuit switched connections

Two types of multislot configurations exists, symmetric and asymmetric. The symmetric case consists of only bidirectional channels. The asymmetric case consists of both bi-directional and unidirectional downlink channels.

The occupied physical channels shall consist of the following channel combinations as defined in subclause 6.4.1.

one main channel of type viii) +

x secondary channels of type ix) +

y secondary channels of type x)

where  $0 \le x \le 7$ , y = 0 for symmetric multislot configuration

 $0 \le x \le 6, 1 \le y \le 7, x+y \le 7$  for asymmetric multislot configuration

The main channel is the bi-directional channel that carries the main signalling (FACCH and SACCH) for the multislot configuration. The position of the main channel is indicated by the allocation message (GSM 04.08). Secondary channels may be added or removed without changing the main channel.

The allocation of channels to a Multislot Configuration must always consider the multislot capability of the MS, as defined by the multislot class described in annex B.

There is no limitation in this TS to the possible TCH types (see subclause 3.2) which may be used in a Multislot Configuration.

High Speed Circuit Switched Data (HSCSD) is one case of multislot configuration. The full rate traffic channels of a HSCSD configuration shall convey the same user bit rate (see subclause 3.2.3).

NOTE: For the maximum number of timeslots to be used for a HSCSD, see GSM 03.34.

#### 6.4.2.2 Multislot configurations for packet switched connections

An MS may be allocated several PDTCH/Us or PDTCH/Ds for one mobile originated or one mobile terminated communication respectively. In this context allocation refers to the list of PDCH that may dynamically carry the PDTCHs for that specific MS. The PACCH may be mapped onto any of the allocated PDCHs. If there are m timeslots allocated for reception and n timeslots allocated for transmission, there shall be Min(m,n) reception and transmission timeslots with the same TN. For a multislot class 1 to 12 MS for a packet switched connection, Tra (see appendix B) shall always apply.

The occupied physical channels shall consist a combination of configurations xi, xii and xiii as defined in subclause 6.4.1. For COMPACT, the occupied physical channels shall consist of a combination of configurations xiii), xxii), xxiii), and xxiv) as defined in subclause 6.4.1. The network shall leave a gap of at least one radio block between the old and the new configuration, when the allocation is changed and PDCHs with the lowest numbered timeslot are not the same in the old and new configuration. For multislot class type 1 MS, the gap shall be left in both uplink and downlink when the lowest numbered timeslot for the combined uplink and downlink configuration is changed. For multislot class type 2 MS, the gap shall be left in the link (uplink and/or downlink) where the lowest numbered timeslot has been changed.

# 6.5 Operation of channels and channel combinations

# 6.5.1 General

- i) A base transceiver station must transmit a burst in every timeslot of every TDMA frame in the downlink of radio frequency channel C0 of the cell allocation (to allow mobiles to make power measurements of the radio frequency channels supporting the BCCH, see GSM 05.08). In order to achieve this requirement a dummy burst is defined in subclause 5.2.6 which shall be transmitted by the base transceiver station on all timeslots of all TDMA frames of radio frequency channel C0 for which no other channel requires a burst to be transmitted.
- ii) Timeslot number 0 of radio frequency channel C0 of the cell allocation must support either channel combinations iv) or v) in subclause 6.4.1. No other timeslot or allocated channel from the cell allocation is allowed to support channel combinations iv) or v) in subclause 6.4.1.
- iii) The parameter BS\_CC\_CHANS in the BCCH defines the number of basic physical channels supporting common control channels (CCCHs). All shall use timeslots on radio frequency channel C0 of the cell allocation. The first CCCH shall use timeslot number 0, the second timeslot number 2, the third timeslot number 4 and the fourth timeslot number 6. Each CCCH carries its own CCCH\_GROUP of mobiles in idle mode. Mobiles in a specific CCCH\_GROUP will listen for paging messages and make random accesses only on the specific CCCH to which the CCCH\_GROUP belongs. The method by which a mobile determines the CCCH\_GROUP to which it belongs is defined in subclause 6.5.2.
- iv) The parameter BS\_CCCH\_SDCCH\_COMB in the BCCH (see subclause 3.3.2) defines whether the common control channels defined are combined with SDCCH/4(0.3) + SACCH/C4(0.3) onto the same basic physical channel. If they are combined then the number of available random access channel blocks (access grant channel blocks and paging channel blocks; see following), are reduced as defined in table 5 of clause 7.
- v) The PCH, AGCH, NCH and BCCH Ext may share the same TDMA frame mapping (considered modulo 51) when combined onto a basic physical channel. The channels are shared on a block by block basis, and information within each block, when de-interleaved and decoded allows a mobile to determine whether the block contains paging messages, system information messages or access grants. However, to ensure a mobile satisfactory access to the system a variable number of the available blocks in each 51-multiframe can be reserved for access grants and system information messages, only. The number of blocks not used for paging (BS\_AG\_BLKS\_RES) starting from, and including block number 0 is broadcast in the BCCH (see subclause 3.3.2). As above the number of paging blocks per 51-multiframe considered to be "available" shall be reduced by the number of blocks reserved for access grant messages.

If system information messages are sent on BCCH Ext, BS\_AG\_BLKS\_RES shall be set to a value greater than zero.

Table 5 of clause 7 defines the access grant blocks and paging blocks available per 51-multiframe.

vi) Another parameter in the BCCH, BS\_PA\_MFRMS indicates the number of 51-multiframes between transmissions of paging messages to mobiles in idle mode of the same paging group. The "available" paging blocks per CCCH are then those "available" per 51-multiframe on that CCCH (determined by the two above parameters) multiplied by BS\_PA\_MFRMS. Mobiles are normally only required to monitor every Nth block of their paging channel, where N equals the number of "available" blocks in total (determined by the above BCCH parameters) on the paging channel of the specific CCCH which their CCCH\_GROUP is required to monitor. Other paging modes (e.g. page reorganize or paging overload conditions described in GSM 04.08) may require the mobile to monitor paging blocks more frequently than this. All the mobiles listening to a particular paging block are defined as being in the same PAGING\_GROUP. The method by which a particular

mobile determines to which particular PAGING\_GROUP it belongs and hence which particular block of the available blocks on the paging channel is to be monitored is defined in subclause 6.5.2.

- vii) An MS which has its membership of at least one voice group or voice broadcast call group set to the active state shall, in addition to monitoring the paging blocks as described above, monitor the notification channel, NCH. This logical channel is always mapped onto contiguous blocks reserved for access grants, in a position and number as given by the parameter NCP, defined in GSM 04.08, broadcast on the BCCH. The channel may be present when a cell supports voice group or voice broadcast calls. The coding of the various structural parameters described above in this subclause is not changed. Information within a block, when deinterleaved and decoded, allows the MS to determine whether the block contains access grant messages or notification messages.
- viii) In presence of PCCCH, the parameter BS\_PCC\_CHANS in the PBCCH defines the number of physical channels for packet data (PDCH) carrying PCCCH. The (P)BCCH shall in addition indicate the physical description of those channels. Each PCCCH carries its own PCCCH\_GROUP of MSs in GPRS attached mode. MS in a specific PCCCH\_GROUP will listen for paging messages and make random accesses only on the specific PCCCH to which the PCCCH\_GROUP belongs. The method by which an MS determines the PCCCH\_GROUP to which it belongs is defined in subclause 6.5.6.
- ix) In CTS, the CTSBCH (CTSBCH-SB and CTSBCH-FB) shall always be transmitted by the CTS-FP according to the rules defined in Clause 6 and Clause 7 Table 8.

In CTS idle mode, a CTS-MS shall be assigned a CTS\_PAGING\_GROUP, as specified in subclause 6.5.7. Several CTS-MS can be assigned the same CTS\_PAGING\_GROUP. The CTS-MS shall determine the specific 52-multiframe where a paging block may be sent to it according to the rule defined in subclause 6.5.7, and shall listen to the CTSBCH of the previous 52-multiframe. In this 52-multiframe, the CTS-MS shall decode the CTSBCH-SB information bits : if the flag indicating the presence of a CTSPCH in the next 52-multiframe is properly set (see GSM 04.56), the CTS-MS shall listen to the next CTSPCH and read the paging block. With this method, it is not necessary to maintain on the physical channel the CTSPCH : the CTSPCH shall only be transmitted when a paging message shall be addressed to one or several CTS-MS in a CTS paging group.

When using the CTSARCH, the CTS-MS shall send two bursts on the CTSARCH: these two bursts shall be sent on two successive frames and shall fulfil the mapping defined in subclause 7 Table 8, with the requirement of the first burst being sent in a TDMA frame with even FN. They shall contain the same access request message, which is specified in GSM 04.56. The first sent burst can be used by the CTS-FP to assess the path loss between the CTS-MS and itself, in order to effectively decode the second burst.

- x) For COMPACT, the base transceiver station shall transmit a burst in a PDCH allocated to carry CPBCCH, in all TDMA Frames where CPBCCH, CFCCH, CSCH is allocated or where CPPCH can appear. In TDMA Frames where CPPCH can appear on the physical channel where CPBCCH is allocated, the base transceiver station shall transmit a dummy block in case no block is required to be transmitted.
- xi) For COMPACT, a base station does not transmit a burst in every timeslot of every TDMA frame in the downlink of the COMPACT control carrier (i.e., discontinuous transmission is used).
- xii) For COMPACT, inter base station time synchronization is required. Timeslot number (TN) = i (i = 0 to 7) and frame number (FN) with FN mod 208 =0 shall occur at the same time in all cells.
- xiii) For the primary COMPACT carrier, timeslot numbers (TN) 1, 3, 5, and 7 shall support channel combination xxii) in subclause 6.4.1. TNs 0, 2, 4, and 6 shall support channel combination xiii).
- xiv) For the secondary COMPACT carrier(s) carrying CPCCCH, timeslot numbers (TN) 1, 3, 5, and 7 shall support channel combination xxiii) in subclause 6.4.1. TNs 0, 2, 4, and 6 shall support channel combination xiii). CPCCCHs on secondary COMPACT carrier(s) shall be allocated on same time group as for primary COMPACT carrier.
- xv) For the secondary COMPACT carrier(s) not carrying CPCCCH, timeslot numbers (TN) 0 through 7 shall support channel combination xiii) in subclause 6.4.1.
- xvi) For COMPACT, BS\_PAG\_BLKS\_RES shall be less than or equal to 8 and less than or equal to 10-BS\_PBCCH\_BLKS.

- xvii) For COMPACT, CFCCH, CSCH, CPBCCH, and CPCCCH are rotated as described in subclause 6.3.2.1. PDTCH, PACCH, and PTCCH do not rotate.
- xviii) For COMPACT, the parameters NIB\_CCCH\_0, NIB\_CCCH\_1, NIB\_CCCH\_2, and NIB\_CCCH\_3 shall not be broadcast for a serving time group.
- xix) For the COMPACT, NIB\_CCCH\_0, NIB\_CCCH\_1, NIB\_CCCH\_2, and NIB\_CCCH\_3 blocks shall be idle for non-serving time groups and rotate in accordance with the non-serving time groups.

The downlink position of the NIB\_CCCH idle blocks is based on the ordered list as defined in subclause 6.3.2.1. The MS shall ignore these downlink idle blocks and shall interpret this action as not having detected an assigned USF value on an assigned PDCH.

xx) For COMPACT large cells, NIB\_CCCH\_0, NIB\_CCCH\_1, NIB\_CCCH\_2, and NIB\_CCCH\_3 blocks shall be idle on timeslots immediately preceding and succeeding non-serving time groups and rotate in accordance with the non-serving time groups. The MS shall ignore these downlink idle blocks and shall interpret this action as not having detected an assigned USF value on an assigned PDCH.

The downlink position of the NIB\_CCCH idle blocks is based on the ordered list as defined in subclause 6.3.2.1.

xxi) For COMPACT, the MS attempts uplink random access on its designated serving time group (TG) by monitoring for USF=FREE in every downlink block.

For dynamic allocation, while in the uplink transfer state, the MS monitors all of the downlink non-idle blocks of its assigned PDCH for uplink assignments. The MS shall ignore downlink idle blocks and shall interpret this action as not having detected an assigned USF value on an assigned PDCH.

USF should be set equal to FREE for downlink non-idle blocks B0 on timeslot numbers (TN) 1, 3, 5, and 7.

### 6.5.2 Determination of CCCH\_GROUP and PAGING\_GROUP for MS in idle mode

CCCH\_GROUP (0 .. BS\_CC\_CHANS-1) = ((IMSI mod 1000) mod (BS\_CC\_CHANS x N)) div N

PAGING\_GROUP (0 .. N-1) = ((IMSI mod 1000) mod (BS\_CC\_CHANS x N)) mod N

where

N = number of paging blocks "available" on one CCCH = (number of paging blocks "available" in a 51multiframe on one CCCH) x BS\_PA\_MFRMS.

IMSI = International Mobile Subscriber Identity, as defined in GSM 03.03.

mod = Modulo.

div = Integer division.

### 6.5.3 Determination of specific paging multiframe and paging block index

The required 51-multiframe occurs when:

```
PAGING_GROUP div (N div BS_PA_MFRMS) = (FN div 51) mod (BS_PA_MFRMS)
```

The index to the required paging block of the "available" blocks in the 51-multiframe:

Paging block index = PAGING\_GROUP mod (N div BS\_PA\_MFRMS)

where the index is then used with the look-up table 5 of clause 7 to determine the actual paging channel interleaved block to be monitored.

In GPRS non-DRX mode, the MS shall listen to all blocks of the CCCH channel.

### 6.5.4 Short Message Service Cell Broadcast (SMSCB)

When a short message service cell broadcast (SMSCB) message is to be sent, the message shall be sent on one of the two cell broadcast channels (CBCH): the basic and the extended cell broadcast channel in four consecutive multiframes using the block defined in table 3 of clause 7. The multiframes used for the basic cell broadcast channel shall be those in which TB = 0,1,2 and 3. The multiframes used for the extended cell broadcast channel shall be those in which TB = 4, 5, 6 and 7 where:

TB = (FN DIV 51)mod(8)

The SMSCB header shall be sent in the multiframe in which TB = 0 for the basic, and TB = 4 for the extended cell broadcast channel. When SMSCB is in use, this is indicated within the BCCH data (see GSM 04.08), and the parameter BS\_AG\_BLKS\_RES shall be set to one or greater. When the CBCH is mapped onto a CCCH+SDCCH/4 channel, use of SMSCB does not place any constraint on the value of BS\_AG\_BLKS\_RES.

- NOTE 1: The MS reading of the extended CBCH is occasionally interrupted by MS idle mode procedures.
- NOTE 2: For a certain network configuration the MS reading of the primary CBCH is occasionally interrupted by MS idle mode procedures when the MS is GPRS attached and in packet idle mode.

### 6.5.5 Voice group and voice broadcast call notifications

When mobile stations are to be alerted on a voice group or voice broadcast call, notification messages shall be sent on the notification channel (NCH), using the blocks defined in subclause 6.5.1.

When the NCH is in use, the parameter BS\_AG\_BLKS\_RES shall be set to a value not lower than the number of blocks used for the NCH, see subclause 6.5.1 vii).

## 6.5.6 Determination of PCCCH\_GROUP and PAGING\_GROUP for MS in GPRS attached mode

In absence of PCCCH, CCCH shall be used in the GPRS attached mode for paging and access. If the determination of the specific paging multiframe and paging block index as specified in this subclause is not supported on CCCH by both the MS and the BTS, the method defined in subclause 6.5.2 and 6.5.3 shall be used. This is negotiated at GPRS attach.

PCCCH\_GROUP (0 .. KC-1) = ((IMSI mod 1000) mod (KC\* N)) div N

PAGING\_GROUP (0 ... M-1) = ( ( (IMSI mod1000) div(KC\*N) ) \* N +

(IMSI mod 1000) mod N + Max((m \* M) div SPLIT\_PG\_CYCLE, m)) mod M for m = 0, ... , Min(M, SPLIT\_PG\_CYCLE) -1

where

KC = number of (P)CCCH in the cell =

BS\_PCC\_CHANS for PCCCH BS\_CC\_CHANS for CCCH

M = number of paging blocks "available" on one (P)CCCH = (12 - BS\_PAG\_BLKS\_RES - BS\_PBCCH\_BLKS) \* 64 for PCCCH (9 - BS\_AG\_BLKS\_RES) \* 64 for CCCH not combined (3 - BS\_AG\_BLKS\_RES) \* 64 for CCCH + SDCCH combined

N=

1 for PCCCH

(9 - BS\_AG\_BLKS\_RES)\*BS\_PA\_MFRMS for CCCH not combined (3 - BS\_AG\_BLKS\_RES)\*BS\_PA\_MFRMS for CCCH/SDCCH combined

SPLIT\_PG\_CYCLE is an MS specific parameter negotiated at GPRS attach (see GSM 04.60)

- IMSI = International Mobile Subscriber Identity, as defined in GSM 03.03.
- mod = Modulo.

div = Integer division.

The MS shall receive paging and perform access on a single (P)CCCH identified by the PCCCH\_GROUP parameter (see subclause 6.5.1).

In non-DRX mode, depending whether there is or not PCCCH channel(s) in the cell, the MS shall listen :

- to all M blocks per multiframe where paging may appear on a PCCCH channel, or
- to all blocks on a CCCH channel.

In DRX mode, the MS shall listen to the blocks corresponding to its paging group as defined by the different PAGING\_GROUP values.

The required multiframe occurs when:

PAGING\_GROUP div (M div 64) = (FN div MFL) mod 64

where

MFL = multiframe length = 51 for CCCH or 52 for PCCCH

The index to the required paging block of the "available" blocks in the multiframe:

Paging block index = PAGING\_GROUP mod (M div 64)

where the index is then used with look-up tables of clause 7 to determine the actual PPCH block to be monitored. Table 5 is used for CCCH and table 7 for PCCCH.

For CCCH, if SPLIT\_PG\_CYCLE>32 is negotiated, SPLIT\_PG\_CYCLE=32 shall be used, in order to provide the MS enough time for BSIC and System Information decoding.

NOTE: On BCCH, the operator should limit DRX\_TIMER\_MAX (see GSM 04.60) to 4 seconds of the same reason.

### 6.5.7 Determination of CTS\_PAGING\_GROUP and specific paging 52multiframe for MS in CTS mode

 $CTS_PAGING_GROUP = (CTS-MSI mod N)$ 

where:

CTS-MSI = CTS Mobile Subscriber Identity as defined in GSM 03.03

N = number of CTS paging groups defined in the CTS-FP and given to the CTS-MS during the attachment procedure (see GSM 04.56).

The required 52-multiframe where a paging message may be sent to the CTS-MS occurs when :

(FN div 52) mod N = CTS\_PAGING\_GROUP

Channel designation	Sub-channel number	Direction	Allowable time slot assignments	Allowable RF channel assignments	Burst type	Repeat length in TDMA frames	Interleaved block TDMA frame map	ping
TCH/FS, TCH/EFS TCH/AFS & TCH/I		D&U <sup>2</sup>	07	C0 Cn	NB <sup>1</sup>	13	B0(07),B1(411),B2(	811.03)
								····· ,···· ,
TCH/HS & TCH/A	HS 0 1	D&U <sup>2</sup>	07	C0 Cn	NB <sup>1</sup>	13	B0(0,2,4,6),B1(4,6,8,10) B0(1,3,5,7),B1(5,7,9,11)	
FACCH/F		D&U	0 7	C0 Cn	NB <sup>1</sup>	13	B0(07),B1(411),B2(4	811,03)
FACCH/H	0	U	0 7	C0 Cn	NB <sup>1</sup>	26	B0(0.2.4.6.8.10).B1(8.10	0,13,15,17,19),B2(17,19,21,23,0,2)
ACCH/H	Õ	D	07	C0 Cn	NB <sup>1</sup>	26		3,15,17,19,21,23),B2(21,23,0,2,4,6
ACCH/H	1	Ū	07	C0 Cn	NB <sup>1</sup>	26		1,14,16,18,20),B2(18,20,22,24,1,3)
ACCH/H	1	D	07	C0 Cn	$NB^1$	26		4,16,18,20,22,24),B2(22,24,1,3,5,7
E-FACCH/F		D&U	0 7	C0 Cn	$NB^1$	13	B0(03),B1(47),B2(8	11)
-IACCH/F		D&U	0 7	C0 Cn		26	B0(0 3)B1(4 7)B2(	8 11)B3(13 16)
							B4(17 20)B5(21 24	)
ACCH/TF		$D\&U^2$	0	C0 Cn	NB <sup>3</sup>	104	B(12, 38, 64, 90)	NOTE 1:
ACCH/TF		$D&U_2^2$	1	C0 Cn	NB <sup>3</sup>	104	B(25, 51, 77, 103)	An Access Burst (AB) is used
ACCH/TF		$D&U^2$	2	C0 Cn	NB <sup>3</sup>	104	B(38, 64, 90, 12)	on the uplink during handover
ACCH/TF		$D&U^2$	3	C0 Cn	NB <sup>3</sup>	104	B(51, 77, 103, 25)	and on channels used for voice
ACCH/TF		$D&U^2$	3	C0 Cn	NB <sup>3</sup>	104	B(64, 90, 12, 38)	group calls when a request to
		$D&U^2$	4		NB <sup>3</sup>			
ACCH/TF		$D&U^2$ $D&U^2$	•	C0 Cn	NB <sup>2</sup>	104	B(77, 103, 25, 51)	talk is made.
ACCH/TF		$D&U^2$	6	C0 Cn	NB <sup>3</sup>	104	B(90, 12, 38, 64)	
ACCH/TF		$D\&U^2$	7	C0 Cn	$NB_3^3$	104	B(103, 25, 51, 77)	
ACCH/M		$D\&U^2$	07	C0 Cn	NB <sup>3</sup>	104	B(12, 38, 64, 90)	
ACCH/CTS		D&U	0, 1	C0 Cn	NB	104	B(12, 38, 64, 90)	
ACCH/CTS		D&U	2, 3	C0 Cn	NB	104	B(38, 64, 90, 12)	
ACCH/CTS		D&U	4, 5	C0 Cn	NB	104	B(64, 90, 12, 38)	
ACCH/CTS		D&U	6, 7	C0 Cn	NB	104	B(90, 12, 38, 64)	
ACCH/TH	0	D&U <sup>2</sup>	0	C0 Cn	NB <sup>3</sup>	104	B(12, 38, 64, 90)	NOTE 2:
ACCH/TH	1 0	$D\&U^2$	1	C0 Cn	NB <sup>3</sup>	104	B(25, 51, 77, 103) B(12, 38, 64, 90)	The uplink of a channel used for voice broadcast
	1	D&U <sup>2</sup>	2		NB <sup>3</sup>		B(25, 51, 77, 103)	or a voice group call may
ACCH/TH	0 1		2	C0 Cn		104	B(38, 64, 90, 12) B(51, 77, 103, 25)	actually not be used.
ACCH/TH	0	D&U <sup>2</sup>	3	C0 Cn	NB <sup>3</sup>	104	B(38, 64, 90, 12) B(51, 77, 103, 25)	
ACCH/TH	0	$D\&U^2$	4	C0 Cn	NB <sup>3</sup>	104	B(64, 90, 12, 38)	
ACCH/TH	1 0	D&U <sup>2</sup>	5	C0 Cn	NB <sup>3</sup>	104	B(77, 103, 25, 51) B(64, 90, 12, 38)	
	1						B(77, 103, 25, 51)	
ACCH/TH	0 1	D&U <sup>2</sup>	6	C0 Cn	NB <sup>3</sup>	104	B(90, 12, 38, 64) B(103, 25, 51, 77)	
ACCH/TH	0	$D\&U^2$	7	C0 Cn	NB <sup>3</sup>	104	B(90, 12, 38, 64) B(103, 25, 51, 77)	

Clause 7 Table 1 of 9: Mapping of logical channels onto physical channels (see subclauses 6.3, 6.4, 6.5)

NOTE: An Access Burst (AB) may be used on the uplink during handover.

Channel designation	Sub- channel number	Direction	Allowable timeslot assignments	Allowable RF channel assignments	Burst type	Repeat length in TDMA frames	Interleaved block TDMA frame mapping
TCH/F4.8 TCH/F9.6 TCH/F14.4		D&U	0 7	C0 Cn	NB <sup>1</sup>	26	B0(0 11, 13 22) B1(4 11, 13 24, 0, 1) B2(8 11, 13 24, 0 5) B3(13 24, 0 9) B4(17 24, 0 11, 13, 14) B5(21 24, 0 11, 13 18)
E-TCH/F28.8 E-TCH/F32.0 E-TCH/F43.2		D&U	0 7	C0 Cn	NB (8PSK)	26	B0(0 11, 13 22) B1(4 11, 13 24, 0, 1) B2(8 11, 13 24, 0 5) B3(13 24, 0 9) B4(17 24, 0 11, 13, 14) B5(21 24, 0 11, 13 18)
TCH/H2.4 TCH/H4.8	0	D&U	0 7	C0 Cn	NB <sup>1</sup>	26	B0(0,2,4,6,8,10,13,15,17,19,21, 23,0,2,4,6,8,10,13,15,17,19) B1(8,10,13,15,17,19,21,23,0,2,4, 6,8,10,13,15,17,19,21,23,0,2), B2(17,19,21,23,0,2,4,6,8,10,13, 15,17,19,21,23,0,2,4,6,8,10)
	1						B0(1,3,5,7,9,11,14,16,18,20,22, 24,1,3,5,7,9,11,14,16,18,20), B1(9,11,14,16,18,20,22,24,1,3,5, 7,9,11,14,16,18,20,22,24,1,3), B2(18,20,22,24,1,3,5,7,9,11,14, 16,18,20,22,24,1,3,5,7,9,11)

Clause 7 Table 2 of 9: Mapping of logical channels onto physical channels (see subclauses 6.3, 6.4, 6.5)

NOTE: An Access Burst (AB) is used on the uplink during handover.

Channel designation	Sub- channel number	Direction	Allowable timeslot assignments	Allowable RF channel assignments	Burst type	Repeat length in TDMA frames	Interleaved block TDMA frame mapping
FCCH		D	0	C0	FB	51	B0(0),B1(10),B2(20),B3(30),B4(40)
SCH		D	0	C0	SB	51	B0(1),B1(11),B2(21),B3(31),B4(41)
BCCH Norm		D	0,2,4,6	C0	NB	51	B(25)
BCCH Ext		D	0,2,4,6	C0	NB	51	B(69)
PCH AGCH		D	0,2,4,6	C0	NB	51	B0(69),B1(1215),B2(1619) B3(2225),B4(2629),B5(3235), B6(3639),B7(4245),B8(4649)
NCH		D	0	C0	NB	51	B0(69),B1(1215),B2(1619) B3(2225),B4(2629),B5(3235), B6(3639)
RACH		U	0,2,4,6	C0	AB	51	B0(0),B1(1)B50(50)
CBCH(SDCCH/4)		D	0	C0	NB	51	B(3235)
CBCH(SDCCH/8)		D	03	C0 Cn	NB	51	B(811)
SDCCH/4	0 1 2 3	D U U D U U U	0	C0	NB <sup>1</sup>	51	B(2225)       NOTE 1:         B(3740)       An Access Burst (AB) is used         B(2629)       On the uplink during handover         B(4144)       B(3235)         B(4750)       B(3639)         B(03)       B(3235)
SACCH/C4	0 1 2 3	D U D U D U D U U	0	CO	NB <sup>3</sup>	102	B(4245) B(5760) B(4649) B(6164) B(9396) B(69) B(97100) B(1013)

### Clause 7 Table 3 of 9: Mapping of logical channels onto physical channels (see subclauses 6.3, 6.4, 6.5)

NOTE: An Access Burst (AB) may be used on the uplink during handover.

Channel designation	Sub- channel number	Direction	Allowable timeslot assignments	Allowable RF channel assignments	Burst type	Repeat length in TDMA frames	Interleaved block TDMA frame mapping
SDCCH/8	0	D U	0 7	C0 Cn	NB <sup>1</sup>	51	B(03)
	1	D					B (15 18) B (4 7)
	1	U U					B (19 22)
	2	D					B (8 11)
	-	Ũ					B (23 26)
	3	U D					B (12 15)
		U					B (27 30)
	4	D U					B (16 19)
	_	U					B (31 34)
	5	D					B (20 23)
	6	U D					B (35 38) B (24 27)
	6	U U					B (24 27) B (39 42)
	7	D					B(3942) B(2831)
	,	Ŭ					B (43 46)
SACCH/C8	0	D	07	C0 Cn	NB <sup>3</sup>	102	B (32 35)
		U					B (47 50)
	1	D					B (36 39)
	_	U					B (51 54)
	2	D					B (40 43)
	3	U					B (55 58) B (44 47)
	3	D U					B (44 47) B (59 62)
	4	D					B (83 86)
	-	Ŭ					B (98 101)
	5	D					B (87 90)
	-	U					B (0 3)
	6	D U					B (91 94)
		U					B (4 7)
	7	D					B (95 98)
		U	P.1.1.1.21				B (8 11)

Clause 7 Table 4 of 9: Mapping of logical channels onto physical channels (see subclauses 6.3, 6.4, 6.5)

NOTE 1: An Access Burst (AB) is used on the uplink during handover.

NOTE 2: An Access Burst (AB) may be used on the uplink during handover.

### Clause 7 Table 5 of 9: Mapping of logical channels onto physical channels (see subclauses 6.3, 6.4, 6.5)

### BS\_CCCH\_SDCCH\_COMB

	Random access channel blocks available				
		Access grant blocks ava	ailable	(NOTE: Some access g	rant blocks may also be used for the NCH)
			BS_4	AG_BLKS_RES	
				Number of paging bl	locks available per 51-multiframe
				(De sins ble shir	Paging channel blocks available
				(Paging block if	dex = 0, 1, 2, 3, 4, 5, 6, 7, 8
False	B0, B1 B50	B0, B1 B8	0	9	B0, B1, B2, B3, B4, B5, B6, B7, B8
False			1	8	B1, B2, B3, B4, B5, B6, B7, B8
False			2	7	B2, B3, B4, B5, B6, B7, B8
False			3	6	B3, B4, B5, B6, B7, B8
False			4	5	B4, B5, B6, B7, B8
False			5	4	B5, B6, B7, B8
False			6	3	B6, B7, B8
False			7	2	B7, B8
-			0	2	
True	B4, B5, B14, B15 B36, B45, B46	B0, B1, B2	0	3	B0, B1, B2
True			1	2	B1, B2
True			2	1	B2

Channel designation	Sub- channel number	Direction	Allowable time-slot assignment	Allowable RF channel assignment	Burst <b>type</b>	Repeat length in TDMA frames	Interleaved block TDMA frame mapping
PDTCH, PACCH		D&U	07	C0Cn	NB1	52	B0(03), B1(47), B2(811), B3(1316), B4(1720), B5(2124), B6(2629), B7(3033), B8(3437), B9(3942), B10(4346), B11(4750)
PBCCH		D	07	C0Cn	NB	52	B0(0 3), B3(1316), B6(2629), B9(3942)
PRACH		U	07	C0Cn	AB	52	B0(0)B11(11), B12(13)B23(24), B24(26)B35(37), B36(39)B47(50)
PPCH, PNCH		D	07	C0Cn	NB	52	B1(4 7), B2(811), B3(1316), B4(1720), B5(2124), B6(2629), B7(3033), B8(3437), B9(3942), B10(4346), B11(4750)
PAGCH		D	07	C0Cn	NB	52	B0(03), B1(4 7), B2(811), B3(1316), B4(1720), B5(2124), B6(2629), B7(3033), B8(3437), B9(3942), B10(4346), B11(4750)
PTCCH/D		D	07	C0Cn	NB	416	B0(12,38,64,90), B1(116,142,168,194), B2(220,246,272,298), B3(324,350,376,402)
PTCCH/U	0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15	U	07	C0Cn	AB	416	B0(12) B0(38) B0(64) B0(90) B0(116) B0(142) B0(168) B0(194) B0(220) B0(220) B0(246) B0(272) B0(298) B0(298) B0(350) B0(350) B0(376) B0(402)

### Clause 7 Table 7 of 9: Mapping of logical channels onto physical channels (see subclauses 6.3, 6.4, 6.5)

#### **Non-COMPACT :**

BS\_PAG\_BLKS\_RES + BS\_PBCCH\_BLKS

		Number of	paging blocks available per 52-multiframe
			Paging channel blocks available for 52-multiframe (Paging block index = 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10)
	1	11	B1, B2, B3, B4, B5, B6, B7, B8, B9, B10, B11
	2	10	B1, B2, B3, B4, B5, B7, B8, B9, B10, B11
	3	9	B1, B2, B4, B5, B7, B8, B9, B10, B11
	4	8	B1, B2, B4, B5, B7, B8, B10, B11
	5	7	B2, B4, B5, B7, B8, B10, B11
	6	6	B2, B4, B5, B8, B10, B11
	7	5	B2, B5, B8, B10, B11
	8	4	B2, B5, B8, B11
	9	3	B5, B8, B11
1	0	2	B5, B11
1	1	1	B11
>1	1	0	

### Clause 7 Table 7a of 9: Mapping of logical channels onto physical channels (see subclauses 6.3, 6.4, 6.5)

#### **COMPACT :**

	BS_PBCCH_BLKS = 1	BS_PBCCH_BLKS = 2
BS_PAG_	Paging channel blocks available for 52-multiframe	Paging channel blocks available for 52-multiframe
BLKS_RES	(Paging block index = 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10)	(Paging block index = 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10)
0	B1, B2, B3, B4, B5, B6, B7, B8, B9, B10, B11	B1, B2, B3, B4, B5, B7, B8, B9, B10, B11
1	B1, B2, B3, B4, B5, B6, B7, B8, B9, B10	B1, B2, B3, B4, B5, B7, B8, B9, B10
2	B1, B2, B3, B4, B6, B7, B8, B9, B10	B1, B2, B3, B4, B7, B8, B9, B10
3	B1, B2, B3, B4, B6, B7, B9, B10	B1, B2, B3, B4, B7, B9, B10
4	B1, B3, B4, B6, B7, B9, B10	B1, B3, B4, B7, B9, B10
5	B1, B3, B4, B6, B7, B9	B1, B3, B4, B7, B9
6	B1, B3, B6, B7, B9	B1, B3, B7, B9
7	B1, B3, B6, B9	B1, B3, B9
8	B3, B6, B9	B3, B9

	BS_PBCCH_BLKS = 3	BS_PBCCH_BLKS = 4
BS_PAG_	Paging channel blocks available for 52-multiframe	Paging channel blocks available for 52-multiframe
BLKS_RES	(Paging block index = 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10)	(Paging block index = 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10)
0	B1, B2, B4, B5, B7, B8, B9, B10, B11	B1, B2, B4, B5, B7, B8, B10, B11
1	B1, B2, B4, B5, B7, B8, B9, B10	B1, B2, B4, B5, B7, B8, B10
2	B1, B2, B4, B7, B8, B9, B10	B1, B2, B4, B7, B8, B10
3	B1, B2, B4, B7, B9, B10	B1, B2, B4, B7, B10
4	B1, B4, B7, B9, B10	B1, B4, B7, B10
5	B1, B4, B7, B9	B1, B4, B7
6	B1, B7, B9	B1, B7
7	B1, B9	B1
8	B9	

#### Clause 7 Table 8 of 9: Mapping of logical channels onto physical channels (see subclauses 6.3, 6.4, 6.5)

Channel designation	Sub- channel number	Direction	Allowable time-slot assignment	Allowable RF channel assignment	Burst <b>type</b>	Repeat length in TDMA frames	Interleaved block TDMA frame mapping
CTSBCH-FB		D	07	C0	FB	52	B(25)
CTSBCH-SB		D	07	C0	SB	52	B(51)
CTSPCH		D	07	C0Cn	NB	52	B(25)
CTSARCH		U	07	C0 C0Cn	SB	52	B0(2)B7(9) B8(10)B13(15)
CTSAGCH		D	07	C0 C0Cn	NB	52	B0(1619) B1(2023)

NOTE 1: In CTS, C0 shall be interpreted as CTSBCH RF channel and C0...Cn as the RF channels of the TFH carrier list (refer to GSM05.56).

NOTE 2: For the precise specification of the timeslot assignment, refer to subclause 6.3.3.1 and 6.3.3.2.

#### Clause 7 Table 9 of 9: Mapping of COMPACT logical channels onto physical channels (see subclauses 6.3, 6.4, and 6.5)

Channel Designation	Sub- Channel Number	Direction	Allowable Timeslot Alignment	Allowable RF Channel Assignment	Burst Type	Repeat Length in TDMA Frames	Interleaved Block TDMA Frame Mapping
CFCCH		D	1, 3, 5, 7	C0 Cn	FB	52	B0 (25)
CSCH		D	1, 3, 5, 7	C0 Cn	SB	52	B0 (51)
CPBCCH		D	1, 3, 5, 7	C0 Cn	NB	52	B0 (0 3), B6 (26 29), B3 (13 16), B9 (39 42)
CPRACH		U	1, 3, 5, 7	C0 Cn	AB	52	B0 (0) B11 (11), B12 (13) B23 (24), B24 (26) B35 (37), B36 (39) B47 (50)
CPAGCH, CPPCH, CPNCH		D	1, 3, 5, 7	C0 Cn	NB	52	B1 (4 7), B2 (8 11), B3 (13 16), B4 (17 20), B5 (21 24), B6 (26 29), B7 (30 33), B8 (34 37), B9 (39 42), B10 (43 46), B11 (47 50)




Figure 1: Mapping of logical channels onto physical channels based on the physical resource

**ETSI** 

51




Figure 2: The structure imposed on the physical resource: Timeslots, TDMA Frames and Radio Frequency channels (in this example the cell has an allocation of 4 RF Channels pairs






Figure 3: Timeslot and format of bursts



(This example of a physical channel is non-hopping using timeslot 0 of every TDMA frame)

Figure 4: Mobile Station usage of physical channel timeslots (For a full-rate hopping traffic channel assigned timeslot 3)

Draft ETSI EN 300 908 V8.4.0 (2000-05)



55

(This example of a physical channel is hopping using 3 of every other TDMA frame)

### Figure 5: Example of two different physical channels




Figure 6: Block diagram of the frequency hopping algorithm when HSN  $\neq 0$ 





Figure 6a: General structure of hopping sequence generation for CTS

NOTE: Example with vector  $\underline{a} = (a_0, a_1, a_2, a_3) = (5, 8, 2, 11).$ 








Figure 7b: TDMA frame mapping for TCH/HS + SACCH/HS sub-channels 0 and 1

Figure 7: Example of a TDMA frame mapping for traffic channels

FCCCH	8	BOCH	BOOH	HON S		8	8	Н000	H	8	HOCO	<del>1</del> 80	H80	88	H88	8	HOSO	8	Fach	8	HOSO	X		1	B	βI	000H	HOSO	88	E E	8 B	H	H	8	8	8	8	H000	8	FCCCH	Р В	88	HOSO	H200	X		H	H980	H000	8	ЦЕ	
-------	---	------	------	-------	--	---	---	------	---	---	------	-----------------	-----	----	-----	---	------	---	------	---	------	---	--	---	---	----	------	------	----	-----	--------	---	---	---	---	---	---	------	---	-------	--------	----	------	------	---	--	---	------	------	---	----	--

Figure 8a: TDMA frame mapping for FCCH + SCH + BCCH + CCCH

	B         B	SDCD+4(0) SDCD+4(0) SDCD+4(1) SDCD+4(1) SDCD+4(1) SDCD+4(1) SDCD+4(1) SDCD+4(1) SDCD+4(1) SDCD+4(2) SCD+4(	
--	---	--	--



Figure 8b: TDMA frame mapping for FCCH + SCH + BCCH + CCCH + SDCCH/4(0...3) + SACCH/4(0...3)

Figure 8: Example of TDMA Frame mapping for control channels


**52 TDMA Frames** 

#### 1 B10 B0 B1 B2 B3 Β4 B5 B6 B7 B8 В9 B11 Х X х

X = Idle frame B0 - B11 = Radio blocks



#### 52 TDMA Frames



### Annex A (normative): Phase 2 mobiles in a Phase 1 infrastructure

### A.1 Scope

Phase 2 mobiles are required to behave properly in a Phase 1 networks, when downlink DTX is used in conjunction with frequency hopping.

### A.2 Implementation options for TCH channels

### A.2.1 C0 filling on the TCH

When the TCH is active, and no associated traffic frame is scheduled for transmission, the following options apply for filling the burst on the C0 radio frequency channel.

## A.2.1.1 A dummy burst with (BN61, BN62, BN86) = training sequence bits of normal bursts

### A.2.1.2 A dummy burst with the "C0 filling training sequence

(BN61, BN62, BN86) = (0,1,1,1,0,0,0,1,0,1,1,1,0,0,0,1,0,1,1,1,0,0,0,1,0,1).

## A.2.1.3 A dummy burst with (BN61, BN62, BN86) mapped from the TSC bits of normal bursts according to the table

TSC for other bursts on TCH	Dummy bursts (BN61, BN62 BN86)	Corresponding TSC
0	(0,1,0,0,0,0,1,1,1,0,1,1,1,0,1,0,0,1,0,0,0,0,0,1,1,1,0)	2
1	(0,1,0,0,1,1,1,0,1,0,1,1,0,0,0,0,0,1,0,0,1,1,1,0,1,0)	5
2	(0,0,1,0,0,1,0,1,1,1,0,0,0,0,1,0,0,0,1,0,0,1,0,1,1,1)	0
3	(0,0,0,1,1,0,1,0,1,1,1,0,0,1,0,0,0,0,0,1,1,0,1,0,1,1)	4
4	(0,1,0,0,1,1,1,0,1,0,1,1,0,0,0,0,0,1,0,0,1,1,1,0,1,0)	5
5	(0,1,0,0,0,0,1,1,1,0,1,1,1,0,1,0,0,1,0,0,0,0,0,1,1,1,0)	2
6	(0,1,0,0,0,1,1,1,1,0,1,1,0,1,0,0,0,1,0,0,0,1,1,1,1,0)	3
7	(0,1,0,0,1,1,1,0,1,0,1,1,0,0,0,0,0,1,0,0,1,1,1,0,1,0)	5

### A.2.1.4 Partial SID information

The BTS transmits bursts containing parts of the SID frames provided by the speech encoder. The bits transmitted in such bursts on C0 carrier contain the same bits that would have been transmitted in those bursts in those if the associated traffic frames were scheduled for transmission.

### A.2.2 Half burst filling

For downlink DTX, when a given traffic frame is scheduled for transmission and one of its adjacent traffic frames is not scheduled for transmission, half of the "encrypted bits" belonging to the normal bursts associated with the scheduled traffic frame need to be filled. These bits are referred to as "half burst filling bits". These half bursts filling bits contain either.

### A.2.2.1 Partial SID information from any associated SID frame; or

### A.2.2.2 The mixed bits of the dummy bursts (encrypted or not encrypted)

### A.2.3 Dummy burst Stealing flag

The dummy burst stealing flag are set to either 1 or 0.

### A.2.4 Half burst Filling Stealing flag

BN60 or BN87 corresponding to the "encrypted bits" of a filled half burst, defined as the "half burst filling stealing flag", are jointly set to a value of either 1 or 0.

### A.2.5 Allowed combinations

Table A.2.5.1 below provides the allowed combinations for phase 1 networks supporting downlink DTX in conjunction with frequency hopping.

Combination	C0 filling on the TCH	Half Burst filling	Dummy Bursts Stealing Flag	Half Burst Filling Stealing Flag
1	Dummy bursts with (BN61-BN86) equal to the bits of the TSC of the other normal bursts (A 2.1.1)	not defined	0	0
2	Dummy burst with "C0 filling training sequence" (A 2.1.2)	Partial SID information (A 2.2.1)	0	0
3	Dummy burst with (BN61, BN62BN86) mapped from the TSC bits of normal bursts (A 2.1.3)	Partial SID information (A 2.2.1)	0	0
4	Partial SID information (A 2.1.4)	Partial SID information (A 2.2.1)	1	1
5	Dummy burst with "C0 filling training sequence" (A 2.1.2)	Dummy burst mixed bits (A 2.2.2)	1	1
6 (for DCS 1 800 only)	Partial SID information (A 2.1.4)	Partial SID information (A 2.2.1)	0	0

## Table A.2.5.1: Possible combinations for networks supporting downlink DT in conjunction with frequency hopping

### A.3 Idle Channels

When a channel is idle, a dummy burst may be transmitted on C0 frequency channel with any options described in subclauses A 2.1.1, A 2.1.2, A 2.1.3.

### Annex B (normative): Multislot capability

### B.1 MS classes for multislot capability

When an MS supports the use of multiple timeslots it shall belong to a multislot class as defined below:

Multislot class	Maximu	m number	of slots	Miı	nimum nu	mber of sl	ots	Туре
	Rx	Тх	Sum	T <sub>ta</sub>	T <sub>tb</sub>	T <sub>ra</sub>	T <sub>rb</sub>	
1	1	1	2	3	2	4	2	1
2	2	1	3	3	2	3	1	1
3	2	2	3	3	2	3	1	1
4	3	1	4	3	1	3	1	1
5	2	2	4	3	1	3	1	1
6	3	2	4	3	1	3	1	1
7	3	3	4	3	1	3	1	1
8	4	1	5	3	1	2	1	1
9	3	2	5	3	1	2	1	1
10	4	2	5	3	1	2	1	1
11	4	3	5	3	1	2	1	1
12	4	4	5	2	1	2	1	1
13	3	3	NA	NA	a)	3	a)	2
14	4	4	NA	NA	a)	3	a)	2
15	5	5	NA	NA	a)	3	a)	2
16	6	6	NA	NA	a)	2	a)	2
17	7	7	NA	NA	a)	1	0	2
18	8	8	NA	NA	0	0	0	2
19	6	2	NA	3	b)	2	c)	1
20	6	3	NA	3	b)	2	C)	1
21	6	4	NA	3	b)	2	C)	1
22	6	4	NA	2	b)	2	c)	1
23	6	6	NA	2	b)	2	c)	1
24	8	2	NA	3	b)	2	c)	1
25	8	3	NA	3	b)	2	c)	1
26	8	4	NA	3	b)	2	c)	1
27	8	4	NA	2	b)	2	c)	1
28	8	6	NA	2	b)	2	c)	1
29	8	8	NA	2	b)	2	c)	1

#### Table B.1

a) = 1 with frequency hopping.

= 0 without frequency hopping.

- b) = 1 with frequency hopping or change from Rx to Tx.
  - = 0 without frequency hopping and no change from Rx to Tx.
- c) = 1 with frequency hopping or change from Tx to Rx.
  - = 0 without frequency hopping and no change from Tx to Rx.

Type 1 MS are not required to transmit and receive at the same time.

Type 2 MS are required to be able to transmit and receive at the same time.

For HSCSD, only multislot classes 1 - 18 are recognised. An MS with a higher multislot class number shall indicate a suitable multislot class less than 19 for HSCSD applications (see GSM 04.08).

#### Rx:

Rx describes the maximum number of receive timeslots that the MS can use per TDMA frame. The MS must be able to support all integer values of receive TS from 0 to Rx (depending on the services supported by the MS). The receive TS need not be contiguous. For type 1 MS, the receive TS shall be allocated within window of size Rx, and no transmit TS shall occur between receive TS within a TDMA frame.

#### Tx:

Tx describes the maximum number of transmit timeslots that the MS can use per TDMA frame. The MS must be able to support all integer values of transmit TS from 0 to Tx (depending on the services supported by the MS). The transmit TS need not be contiguous. For type 1 MS, the transmit TS shall be allocated within window of size Tx, and no receive TS shall occur between transmit TS within a TDMA frame.

#### Sum:

Sum is the total number of uplink and downlink TS that can actually be used by the MS per TDMA frame. The MS must be able to support all combinations of integer values of Rx and Tx TS where  $1 \le Rx + Tx \le Sum$  (depending on the services supported by the MS). Sum is not applicable to all classes.

#### T<sub>ta</sub>:

 $T_{ta}$  relates to the time needed for the MS to perform adjacent cell signal level measurement and get ready to transmit.

For type 1 MS it is the minimum number of timeslots that will be allowed between the end of the previous transmit or receive TS and the next transmit TS when measurement is to be performed between. It should be noted that, in practice, the minimum time allowed may be reduced by amount of timing advance.

For type 1 MS that supports extended TA, the parameter  $T_{ta}$  is increased by 1 if TA > 63 and there is a change from RX to TX.

For type 2 MS it is not applicable.

For circuit switched multislot configurations as defined in subclause 6.4.2.1,  $T_{ta}$  is not applicable.

#### T<sub>tb</sub>:

 $T_{tb}$  relates to the time needed for the MS to get ready to transmit. This minimum requirement will only be used when adjacent cell power measurements are not required by the service selected.

For type 1 MS it is the minimum number of timeslots that will be allowed between the end of the last previous receive TS and the first next transmit TS or between the previous transmit TS and the next transmit TS when the frequency is changed in between. It should be noted that, in practice, the minimum time allowed may be reduced by the amount of the timing advance.

For type 1 MS that supports extended TA, the parameter  $T_{tb} = 2$  if TA > 63 and there is a change from RX to TX.

For type 2 MS it is the minimum number of timeslots that will be allowed between the end of the last transmit burst in a TDMA frame and the first transmit burst in the next TDMA frame.

#### T<sub>ra</sub>:

 $T_{ra}$  relates to the time needed for the MS to perform adjacent cell signal level measurement and get ready to receive.

For type 1 MS it is the minimum number of timeslots that will be allowed between the previous transmit or receive TS and the next receive TS when measurement is to be performed between.

For type 2 MS it is the minimum number of timeslots that will be allowed between the end of the last receive burst in a TDMA frame and the first receive burst in the next TDMA frame.

T<sub>rb</sub>:

 $T_{rb}$  relates to the time needed for the MS to get ready to receive. This minimum requirement will only be used when adjacent cell power measurements are not required by the service selected.

For type 1 MS it is the minimum number of timeslots that will be allowed between the previous transmit TS and the next receive TS or between the previous receive TS and the next receive TS when the frequency is changed in between.

For type 2 MS it is the minimum number of timeslots that will be allowed between the end of the last receive burst in a TDMA frame and the first receive burst in the next TDMA frame.

### B.2 Constraints imposed by the service selected

The service selected will impose certain restrictions on the allowed combinations of transmit and receive timeslots. Such restrictions are not imposed by this annex but should be derived from the description of the services. For example, in the case of circuit switched data the TS numbers used in the uplink will be a subset of those used in the downlink.

The service selected will determine whether or not adjacent cell power measurements are required and therefore whether  $T_{ra}$  or  $T_{rb}$  is allowed for.


### B.3 Network requirements for supporting MS multislot classes

The multislot class of the MS will limit the combinations and configurations allowed when supporting multislot communication.


GSM 400 network may support extended cell coverage utilising timing advance values greater than 63. This has an effect that the time for MS to change from RX to TX will be very short for distant MS. It is necessary for the network to decide whether requested or current multislot configuration can be supported by distant MS. If actual TA is great enough it may be necessary for network to downgrade requested resources or it may be necessary for network to downgrade current resources.

It is necessary for the network to decide whether the MS needs to perform adjacent cell power measurement for the type of multislot communication intended and whether the service imposes any other constraints before the full restrictions on TS assignments can be resolved. This is best shown by example:


For a multislot class 5 MS in circuit switched configuration (adjacent cell power measurements required) five basic configurations of channels are possible which can occur in six different positions in the TDMA frame. The service itself may determine that asymmetry must be downlink biased, in which case the last two solutions would not be allowed.




All possible timeslots used





Alternative downlink biased assymetry



(not prohibited by multislot class)








Uplink biased assymetry (not prohibited by multislot class)


These five combinations can be repeated at the six other positions that can be fitted within the same TDMA frame


#### Figure B.1

For a multislot class 13 MS when adjacent cell power measurements are not required and the service does not constrain the transmit and receive timeslots to use the same timeslot number. Many configurations of channels are possible so long as the 5 constraints of the MS are catered for. [Currently services envisaged only allow for the last example here.]





There is no requirement for relative timing of Tx timeslots in relation to Rx timeslots





Many configurations are possible





This configuration could be used for HSCSD or GPRS

Figure B.2

### Annex C (informative): CTSBCH Timeslot shifting example

With the following parameters :

- TNI = 4
- TNSCN = 9
  - TNSCO = 1 i.e.  $(TNS1 = TNS_{9,1} = (0, 3, 7, 6, 5, 2, 4, 1)$  and  $TNS2 = TNS_{9,0} = (0, 1, 4, 5, 7, 3, 6, 2)$

68

- x0 = 2
- x1 = 3
- x2 = 5
- x3 = 4

and the timeslot shifting algorithm defined in section 6.3.3, the CTSBCH TN used in set 0 of the shifting sequence is :

(FN div 52)	mod	51	0	1	2	3	4	5	б	7	8	9	10	11	12	13	14	15	16	17
TNS used			1	1	1	1	1	1	1	1	2	2	2	2	1	1	1	1	1	2
CTSBCH TN			4	1	0	3	7	б	5	2	0	1	4	5	2	4	1	0	3	6
(FN div 52)	mod	51	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35
TNS used			2	2	1	1	2	2	2	2	2	2	2	2	1	1	1	1	1	1
CTSBCH TN			2	0	3	7	3	б	2	0	1	4	5	7	б	5	2	4	1	0
(FN div 52)	mod	51	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50			
TNS used			2	2	2	2	2	1	1	1	2	2	2	2	1	1	1			
CTSBCH TN			1	4	5	7	3	7	б	5	7	3	6	2	4	1	0			

For the next sets, same mechanism applies, with

set 1 beginning with CTSBCH TN = 3

set 2 beginning with CTSBCH TN = 5

set 3 beginning with CTSBCH TN = 1

set 4 beginning with CTSBCH TN = 7

set 5 beginning with CTSBCH TN = 2

set 6 beginning with CTSBCH TN = 0

set 7 beginning with CTSBCH TN = 6

### Annex D (informative): COMPACT multiframe structure examples

In the figures, the 52-multiframe number (MFN) shall have a range of 0 to 3 and can be calculated from the TDMA frame number (FN) as follows:

 $MFN = (FN \text{ div } 52) \mod 4$ 

For COMPACT, timeslot mapping and rotation of the control channels is used such that control channels belonging to a serving time group are rotated over odd timeslot numbers as follows: 7, 5, 3, 1, 7, 5, ... The rotation occurs between frame numbers (FN) mod 52 = 3 and 4. The timeslot mapping and rotation of the control channels in this manner allows the mobile station to measure the received signal level from surrounding cells in its normal measurement window. Since the rotation repeats itself every 208 frames, the 52-multiframe number (MFN) allows the mobile station to determine its location in the time group rotation during selection and re-selection.

The following relates to Figures D.1 through D.7:

- i)  $B(x)^y$  = time group y uses CPBCCH in block x;
- ii)  $C(x)^y$  = time group y uses CPCCCH in block x;
- iii) PTCCH = PTCCH as norma;
- iv) CFCCH<sup>y</sup> = time group y uses CFCCH;
- v) CSCH<sup>y</sup> = time group y uses CSCH;
- vi) IDLE = idle burst;
- vii)  $X^{y}$  = block designated as idle for time group y;
- viii) Empty = used for traffic as normal.

	F	rames	s 0-5	MF	a 20 N = 0 3 = 0	0	ultif	frame		F	rames 0	Ν	of a 20 //FN = / TG = 1	0	ultif	ram	e		F	ram	es O	-51 of a MFN TG :	= 0	-multif	ram	Ð		I	Fram	es O	Ν	ofa //FN TG =		ltifra	ime
TS FN	0	1	2	3		5	6	7	TS FN	0	1	2	3	4	5	6	7	TS FN		1	2	3	4	5	6	7	TS FN		1	2		4	5	6	7
0		B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	0		X <sup>0</sup>		B(0) <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	0	-	X <sup>0</sup>		X <sup>1</sup>		B(0) <sup>2</sup>		X <sup>3</sup>	0		X <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>	Γ	B(0) <sup>3</sup>
1		B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	1		X <sup>0</sup>		B(0) <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	1		X <sup>0</sup>		X <sup>1</sup>		$B(0)^{2}$		X <sup>3</sup>	1		X <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		B(0) <sup>3</sup>
2		B(0) <sup>0</sup>		$X^1$		$X^2$		X <sup>3</sup>	2		X <sup>0</sup>		B(0) <sup>1</sup>		$\chi^2$		$X^3$	2	_	X <sup>0</sup>		X <sup>1</sup>		$B(0)^{2}$		$X^3$	2		X <sup>0</sup>		$X^1$		X <sup>2</sup>	L	$B(0)^{3}$
3		B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	3 4		X <sup>0</sup>		B(0) <sup>1</sup>		X <sup>2</sup>		X3	3		X <sup>0</sup>		X <sup>1</sup>		B(0) <sup>2</sup>		X <sup>3</sup>	3 4	-	X <sub>0</sub>		X <sup>1</sup>		X <sup>2</sup>	-	B(0) <sup>3</sup>
5									4 5									4 5							_		5							-	
6									6									6									6	_							
7									7									7									7								
8									8									8									8	_					ļ	L	
9 10									9 10									9 10									9 10	_							
11									11									11									11	_							
12				PT	CC⊦	ł			12			F	тсс⊦	1				12				PTC	СН				12	_			F	тсо	СН		
13		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(3)^{0}$	13		C(3) <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		X <sup>0</sup>	13		X <sup>1</sup>		$C(3)^{2}$		X <sup>3</sup>		X <sup>0</sup>	13	_	X <sup>1</sup>		X <sup>2</sup>		$C(3)^{3}$		X <sup>0</sup>
14		X <sup>1</sup>		$X^2$		X <sup>3</sup>		$C(3)^{0}$	14		C(3) <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		X <sup>0</sup>	14		X <sup>1</sup>		$C(3)^{2}$		X <sup>3</sup>		X <sup>0</sup>	14		X <sup>1</sup>		$X^2$		C(3) <sup>3</sup>		X <sup>0</sup>
15 16		X <sup>1</sup> X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>		X <sup>3</sup>		C(3) <sup>0</sup> C(3) <sup>0</sup>	15 16		C(3) <sup>1</sup> C(3) <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>		$\frac{X^3}{X^3}$		X <sup>0</sup>	15 16	_	X <sup>1</sup> X <sup>1</sup>		$C(3)^2$ $C(3)^2$	-	X <sup>3</sup> X <sup>3</sup>		X <sup>0</sup> X <sup>0</sup>	15 16		$X^1$ $X^1$		X <sup>2</sup> X <sup>2</sup>		C(3) <sup>3</sup> C(3) <sup>3</sup>	-	X <sup>0</sup>
17		^		^		^		0(3)	10		0(3)		^		^		^	17		^		C(3)		^		^	17		^		^		C(3)		
18									18									18									18	_						1	
19									19									19									19	_							
20									20									20									20	_					ļ	L	
21 22									21 22									21 22									21 22	_							
22									22									23									23								
24									24									24									24	-							
25		- 4	11	DLE		2		CFCCH <sup>0</sup>	25	ID	CFCCH <sup>1</sup>		2	IDLE			0	25	_	IDLE		CFCCH <sup>2</sup>		IDL		0	25			IDLE			CFCCH <sup>3</sup>	10	DLE
26 27		X <sup>1</sup> X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>		X <sup>3</sup> X <sup>3</sup>		C(6) <sup>0</sup> C(6) <sup>0</sup>	26 27		C(6) <sup>1</sup> C(6) <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>		X <sup>3</sup> X <sup>3</sup>		X <sup>0</sup>	26 27		X <sup>1</sup> X <sup>1</sup>		$C(6)^2$ C(6) <sup>2</sup>		X <sup>3</sup> X <sup>3</sup>		X <sup>0</sup> X <sup>0</sup>	26 27		X <sup>1</sup> X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>		C(6) <sup>3</sup> C(6) <sup>3</sup>		X <sup>0</sup> X <sup>0</sup>
27		X <sup>1</sup>		Λ X <sup>2</sup>		Λ X <sup>3</sup>		$C(6)^{0}$	27		$C(6)^{1}$		Λ X <sup>2</sup>		Λ X <sup>3</sup>		х <sup>0</sup>	27		л Х <sup>1</sup>		$C(6)^2$	-	Λ X <sup>3</sup>		х <sup>0</sup>	27		Λ X <sup>1</sup>		^ X <sup>2</sup>		$C(6)^{3}$	-	X <sup>0</sup>
29		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(6)^{0}$	29		C(6) <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		X <sup>0</sup>	29		X <sup>1</sup>		$C(6)^2$		X <sup>3</sup>		X <sup>0</sup>	29		X <sup>1</sup>		$\chi^2$		C(6) <sup>3</sup>		X <sup>0</sup>
30									30									30									30								
31									31									31									31	-							
32 33									32 33									32 33									32 33	_							
34									33									33									34	_						-	
35									35									35									35	-						1	
36									36									36									36								
37				DT					37									37				DTO					37								
38 39		X <sup>1</sup>		Ρ1 X <sup>2</sup>	CCF	1 X <sup>3</sup>		$C(9)^{0}$	38 39		C(9) <sup>1</sup>	ŀ	PTCCH		X3		X <sup>0</sup>	38 39		X <sup>1</sup>		PTC C(9) <sup>2</sup>	СН	X <sup>3</sup>		X <sup>0</sup>	38 39		X <sup>1</sup>		X <sup>2</sup>	тс	C(9) <sup>3</sup>	T	X <sup>0</sup>
40		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(9)^{0}$	40		C(9) <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		X <sup>0</sup>	40		X <sup>1</sup>		$C(9)^2$		X <sup>3</sup>		X <sup>0</sup>	40		X <sup>1</sup>		$X^2$		C(9) <sup>3</sup>	-	X <sup>0</sup>
41		X1		$X^2$		X <sup>3</sup>		C(9) <sup>0</sup>	41		C(9) <sup>1</sup>		X <sup>2</sup>		$X^3$		X <sub>0</sub>	41		X <sup>1</sup>		$C(9)^{2}$		X <sup>3</sup>		Xo	41		X <sup>1</sup>		$X^2$		$C(9)^{3}$		X
42		X <sup>1</sup>		X <sup>2</sup>		X3		$C(9)^{0}$	42		C(9) <sup>1</sup>		X <sup>2</sup>		X <sub>3</sub>		X <sup>0</sup>	42		X <sup>1</sup>		$C(9)^{2}$		X <sup>3</sup>		X <sup>0</sup>	42	_	X <sup>1</sup>		X <sup>2</sup>		C(9) <sup>3</sup>		X <sup>0</sup>
43									43 44									43 44									43	_					├────		
44 45									44 45									44 45		-			-				44 45	-	-					-	$\vdash$
46									46									46									46	_						+	
47									47									47									47								
48									48					$\square$				48									48	_	$\downarrow$					$\vdash$	
49 50			-						49 50									49 50	<u> </u>	<u> </u>			<u> </u>				49 50	_	+					┼──	+
50 51		L		DLE			L	CSCH <sup>0</sup>	50 51	ID	CSCH <sup>1</sup>	-		IDLE	-		1	50 51	$\vdash$	IDLE		CSCH <sup>2</sup>	-	IDL	E		50		1	IDLE			CSCH <sup>3</sup>	11	DLE

#### Figure D.1: COMPACT downlink 52-multiframe structure using 4 time groups for nominal cells (based on an assignment of 1 CPBCCH and 3 CPCCCHs with NIB\_CPBCCH\_0 = NIB\_CCCH\_1 = NIB\_CCCH\_2 = NIB\_CCCH\_3 = 4). NIB\_CCCH is not broadcast for serving cell time group

	F	rames	s 0-5	MF	a 20 N = G = (	0	nulti	frame		F	rames 0	N	ofa2 //FN= TG=1	0	nultif	ram	ie		F	ram	es (	)-51 of a MFN TG :	= 0	-multif	ram	e
TS FN	0	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7	TS FN		1	2	3	4	5	6	7
0		$B(0)^{0}$		X <sup>1</sup>		X <sup>2</sup>			0		X <sup>0</sup>		B(0) <sup>1</sup>		X <sup>2</sup>			0		X <sup>0</sup>		X <sup>1</sup>		$B(0)^{2}$		
1		B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>			1		X0		B(0) <sup>1</sup>		X <sup>2</sup>			1		X0		X <sup>1</sup>		$B(0)^{2}$		
2		$B(0)^{0}$		X <sup>1</sup>		X <sup>2</sup>			2		X <sup>0</sup>		B(0) <sup>1</sup>		X <sup>2</sup>			2		X <sup>0</sup>		X <sup>1</sup>		$B(0)^{2}$		
3		$B(0)^{0}$		X <sup>1</sup>		X <sup>2</sup>			3		X <sup>0</sup>		B(0) <sup>1</sup>		X <sup>2</sup>			3		X <sub>0</sub>		X <sup>1</sup>		$B(0)^{2}$		
4									4									4								
5									5 6									5 6								
6 7									6									5		-						
8						-			8									8								
9									9									9								
10									10									10		1						
11									11									11								
12			-		CCI	1	-		12			ŀ	PTCCH	1				12	_		-	PTC	СН			
13		X <sup>1</sup>		X <sup>2</sup>				C(3) <sup>0</sup>	13		C(3) <sup>1</sup>		X <sup>2</sup>				X <sup>0</sup>	13	_	X <sup>1</sup>		C(3) <sup>2</sup>				X <sup>0</sup>
14		X <sup>1</sup> X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>		<u> </u>		$C(3)^{0}$	14		$C(3)^{1}$		X <sup>2</sup> X <sup>2</sup>	<u> </u>	<u> </u>		X <sup>0</sup>	14		X <sup>1</sup> X <sup>1</sup>		$C(3)^2$	<u> </u>			X <sup>0</sup> X <sup>0</sup>
15 16		X <sup>1</sup>		$X^{-}$ $X^{2}$				$C(3)^{0}$ C(3) <sup>0</sup>	15 16		$C(3)^{1}$		X <sup>-</sup> X <sup>2</sup>				X <sup>-</sup>	15 16	_	X <sup>1</sup>		$C(3)^2$				X <sup>-</sup> X <sup>0</sup>
10		^		^				U(3)	10		C(3) <sup>1</sup>		^				^	10		^		C(3) <sup>2</sup>				^
18									18									18								
19									19									19								
20									20									20								
21									21									21								
22									22									22								
23									23									23	_							
24 25				DLE				CFCCH <sup>0</sup>	24 25	ID	CFCCH'			IDL				24 25				CFCCH <sup>2</sup>				
25 26		X <sup>1</sup>		X <sup>2</sup>		I I		C(6) <sup>0</sup>	25	U	$C(6)^1$		X <sup>2</sup>				X <sup>0</sup>	25		IDLE X <sup>1</sup>	_	$C(6)^2$		IDL		X <sup>0</sup>
20		X <sup>1</sup>		Λ X <sup>2</sup>				$C(6)^{0}$	20		$C(0)^{1}$		X <sup>2</sup>				х <sup>0</sup>	20		X <sup>1</sup>		$C(0)^{2}$				X <sup>0</sup>
28		X <sup>1</sup>		X <sup>2</sup>				$C(6)^{0}$	28		C(6) <sup>1</sup>		X <sup>2</sup>				X <sup>0</sup>	28	-	X <sup>1</sup>		$C(6)^2$				X <sup>0</sup>
29		X <sup>1</sup>		$X^2$				$C(6)^{0}$	29		C(6) <sup>1</sup>		X <sup>2</sup>				X <sup>0</sup>	29		X <sup>1</sup>		$C(6)^{2}$				X <sup>0</sup>
30									30									30								
31									31									31								
32									32									32								
33									33									33								
34 35									34 35									34 35								-
36			-	<u> </u>	-	<u> </u>	-		36	-					<del>  _</del>	-	$\vdash$	36		+	-				-	
37			-						37									37	⊢	1						
38					CCH	ł			38			I	PTCCH	H				38				PTC	СН			
39		X <sup>1</sup>		X <sup>2</sup>				$C(9)^{0}$	39		C(9) <sup>1</sup>		X <sup>2</sup>				X <sup>0</sup>	39		X <sup>1</sup>		C(9) <sup>2</sup>				X <sup>0</sup>
40		X <sup>1</sup>		X <sup>2</sup>				C(9) <sup>0</sup>	40		C(9) <sup>1</sup>		X <sup>2</sup>				X <sup>0</sup>	40		X <sup>1</sup>		C(9) <sup>2</sup>				X <sup>0</sup>
41		X <sup>1</sup>	L	$X^2$		<u> </u>	L	$C(9)^{0}$	41		C(9) <sup>1</sup>		X <sup>2</sup>	<u> </u>		L	$X^0$	41	$\vdash$	$X^1$	L	$C(9)^2$	<u> </u>			X <sup>0</sup>
42		X <sup>1</sup>		X <sup>2</sup>		├		C(9) <sup>0</sup>	42		C(9) <sup>1</sup>		X <sup>2</sup>	-	<u> </u>		X <sub>0</sub>	42	$\vdash$	X <sup>1</sup>		C(9) <sup>2</sup>	<u> </u>	<u> </u>		X <sup>0</sup>
43 44					-	$\vdash$			43 44	-				-	-		$\square$	43 44	$\vdash$				$\vdash$		-	$\vdash$
44 45				-		-			44 45	-				-	-	-	$\vdash$	44 45	_	-			-			$\vdash$
45			-						40							-		40		1						$\square$
47									47				1					47	$\square$			1				
48									48									48								
49									49									49								
50								0000	50	_	0.0.01.1				<u> </u>			50				a.a.a?	<u> </u>	L		
51			11	DLE				CSCH <sup>0</sup>	51	ID	CSCH <sup>1</sup>			IDL	.E			51	L	IDLE	-	CSCH <sup>2</sup>	I	IDL	F	

#### Figure D.2: COMPACT downlink 52-multiframe structure using 3 time groups for nominal cells (based on an assignment of 1 CPBCCH and 3 CPCCCHs with NIB\_CCCH\_0 = NIB\_CCCH\_1 = NIB\_CCCH\_2 = 4, NIB\_CCCH\_3 = 0). NIB\_CCCHis not broadcast for serving cell time group

	F	rame	s 0-5	MF	fa2 FN= G=(	0	nultif	frame		F	rames (	N	of a 20 IFN = TG = 1	0	nulti	fram	ne		I	-ran	nes O	-51 of a MFN TG	= 0	-multi	fram	e		F	ram	ies (	- 1	ofa MFN TG =		ıltifra	ame
TS FN	0	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7	TS FN		1	2	3	4	5	6	7	TS FN		1	2	3	4	5	6	7
	X <sup>0</sup>	B(0) <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>		X <sup>0</sup>	X <sup>0</sup>	X <sup>1</sup>	B(0) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X3	X <sup>3</sup>		X <sup>0</sup>	X <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	B(0) <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	0	0	X <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	B(0) <sup>3</sup>
1	X <sub>0</sub>	B(0) <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	1	X <sup>0</sup>	X <sup>0</sup>		B(0) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>		I X <sup>0</sup>	X <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	B(0) <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	1		X	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	B(0) <sup>3</sup>
2	X <sup>0</sup>	B(0) <sup>0</sup> B(0) <sup>0</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>		X <sup>3</sup> X <sup>3</sup>	X <sup>3</sup> X <sup>3</sup>		X <sup>0</sup> X <sup>0</sup>	X <sup>0</sup>	X <sup>1</sup> X <sup>1</sup>	B(0) <sup>1</sup> B(0) <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>3</sup> X <sup>3</sup>	$X^3$	-	2 X <sup>0</sup> 3 X <sup>0</sup>	X <sup>0</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	$B(0)^2$ $B(0)^2$	X <sup>3</sup> X <sup>3</sup>	$X^3$ $X^3$	2	~	X <sup>0</sup> X <sup>0</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>3</sup> X <sup>3</sup>	$B(0)^{3}$ $B(0)^{3}$
3	^	Б(0)	^	^	^	^	^	^	3	^	^	^	<b>Б(U)</b>	^	^	^	^			^	^	^	^	D(U)	^	^	3	^	^	^	^	^	^	<u>^</u>	Б(0)
5									5									5	5								5							1	
6									6									•	6								6							1	
7									7									7									7							4	
8 9					-	-			8 9									8		_			-				8							+	
9 10									9 10									10	· · · · ·		-						9 10							+	
11									11									11									11							1	
12	- 1								12	- 1			PTCCH					12	4			PTC		2			12					PTC			0
13	$\frac{X^1}{X^1}$	X <sup>1</sup> X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>3</sup>		X <sup>0</sup>	$C(3)^{0}$ C(3) <sup>0</sup>	13 14	_	C(3) <sup>1</sup> C(3) <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>3</sup> X <sup>3</sup>	X <sup>3</sup> X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	13 14		X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	$C(3)^2$ $C(3)^2$	X <sup>3</sup> X <sup>3</sup>	X <sup>3</sup> X <sup>3</sup>	X <sup>0</sup> X <sup>0</sup>	X <sup>0</sup> X <sup>0</sup>	13	4	X <sup>1</sup> X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>3</sup> X <sup>3</sup>	C(3) <sup>3</sup> C(3) <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup> X <sup>0</sup>
14 15	Λ X <sup>1</sup>	X <sup>1</sup>	^ X <sup>2</sup>	^ X <sup>2</sup>			х <sup>0</sup>	$C(3)^{0}$		Λ X <sup>1</sup>	C(3) <sup>1</sup>	Λ X <sup>2</sup>	X <sup>2</sup>	^ X <sup>3</sup>	л Х <sup>3</sup>	х <sup>0</sup>	х <sup>0</sup>		• ^	X <sup>1</sup>		$C(3)^2$	л Х <sup>3</sup>	X <sup>3</sup>	х <sup>о</sup>	х <sup>0</sup>	14 15		х <sup>1</sup>	Λ X <sup>2</sup>	Λ X <sup>2</sup>	Λ X <sup>3</sup>	$C(3)^{3}$	х <sup>0</sup>	X <sup>0</sup>
16	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>			X <sup>0</sup>	$C(3)^{0}$	16		C(3) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	16	_	X <sup>1</sup>		$C(3)^2$	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	16	_	X <sup>1</sup>	$\chi^2$	$X^2$	X <sup>3</sup>	C(3) <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>
17									17		. ,							17	7								17								
18									18									18									18							4	
19 20									19 20									19 20									19 20								
20									20									21	_		-						20							+	
22									22									22									22							1	
23									23									23									23								
24								CFCCH <sup>0</sup>	24	5	CFCCH <sup>1</sup>							24	_			CFCCH <sup>2</sup>					24						CFCCH	,	
25 26	X1	X <sup>1</sup>	11 X <sup>2</sup>	DLE X <sup>2</sup>		X <sup>3</sup>	X <sup>0</sup>	C(6) <sup>0</sup>	25 26		C(6) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	IDL X <sup>3</sup>	E X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	25 26	_	IDLI X <sup>1</sup>	E X <sup>2</sup>	C(6) <sup>2</sup>	X <sup>3</sup>	IDL X <sup>3</sup>	E X <sup>0</sup>	X <sup>0</sup>	25 26	X <sup>1</sup>			X <sup>2</sup>	X <sup>3</sup>	C(6) <sup>3</sup>	X <sup>0</sup>	DLE X⁰
27	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	$C(6)^{0}$	27	X <sup>1</sup>	C(6) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	27		X <sup>1</sup>	X <sup>2</sup>	$C(6)^2$	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	27	X <sup>1</sup>	X <sup>1</sup>	$\chi^2$	X <sup>2</sup>	X <sup>3</sup>	$C(6)^{3}$	X <sup>0</sup>	X <sup>0</sup>
28	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	$C(6)^{0}$	28	X <sup>1</sup>	C(6) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>		3 X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	$C(6)^{2}$	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	28		X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	$C(6)^{3}$	X <sup>0</sup>	X <sup>0</sup>
29	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X3	X3	X <sup>0</sup>	C(6) <sup>0</sup>	29	X <sup>1</sup>	C(6) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X3	X <sup>3</sup>	X <sup>0</sup>	X0	29		X <sup>1</sup>	X <sup>2</sup>	$C(6)^{2}$	X3	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	29	_	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	$C(6)^{3}$	X <sup>0</sup>	X <sup>0</sup>
30 31					-	-			30 31									30 31					-				30 31							+	
32									32	_					-			32									32			-				+	
33					1	1			33									33									33							1	
34									34									34	_								34								
35					-	-			35									35									35							—	
36 37					-	-	-		36 37						-			36		-			-				36 37			-				+	
38				PT	CCI	H			38			F	тссн	1	-			38				PTC	СН				38			-		PTC	СН	4	L
39	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>			X <sup>0</sup>	C(9) <sup>0</sup>	39	X <sup>1</sup>	C(9) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup>	X <sub>0</sub>	X <sub>0</sub>	39		X <sup>1</sup>	X <sup>2</sup>	$C(9)^{2}$	X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	39	-	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>3</sup>	C(9) <sup>3</sup>	X	X <sup>0</sup>
40	$X^1$	X <sup>1</sup>	$X^2$	$X^2$	$X^3$		X <sup>0</sup>	$C(9)^{0}$	40		C(9) <sup>1</sup>	$\chi^2$	X <sup>2</sup>	$X^3$	$X^3$	X <sup>0</sup>	X <sup>0</sup>	40	·	X <sup>1</sup>	$X^2$	$C(9)^2$	$X^3$	X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	40		X <sup>1</sup>	$X^2$	$X^2$	$X^3$	$C(9)^{3}$	X <sup>0</sup>	X <sup>0</sup>
41 42	X <sup>1</sup> X <sup>1</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>3</sup> X <sup>3</sup>	X <sup>3</sup>	X <sup>0</sup>	$C(9)^{0}$ C(9) <sup>0</sup>		$X^1$ $X^1$	C(9) <sup>1</sup> C(9) <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>3</sup>	X <sup>3</sup> X <sup>3</sup>	X <sup>0</sup>	X <sup>0</sup>	41		X <sup>1</sup>	X <sup>2</sup>	C(9) <sup>2</sup> C(9) <sup>2</sup>	X <sup>3</sup> X <sup>3</sup>	X <sup>3</sup> X <sup>3</sup>	X <sup>0</sup> X <sup>0</sup>	X <sup>0</sup> X <sup>0</sup>	41 42		X <sup>1</sup> X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	$X^3$ $X^3$	$C(9)^{3}$ $C(9)^{3}$	X <sup>0</sup>	X <sup>0</sup>
43	~	~	~	~	~	~	^	0(3)	43	^	0(3)	~	~	~	~	~	~	43		~	^	0(3)	~	~	~	~	43		~	~	~	~	0(3)	Ê	~
44									44									44	ı								44								
45									45									45									45								
46 47			<u> </u>	<u> </u>	┣	┣	<u> </u>		46 47	$\vdash$					├	<u> </u>	<u> </u>	46		-	-		$\vdash$		<u> </u>		46 47	⊢		├	<u> </u>			$\vdash$	
47			-	-	$\vdash$	$\vdash$	-		47	$\vdash$						-	-	4/		+	+		$\vdash$				47	⊢			$\vdash$			+	
49	_		t	t			1		49							t	t	49		1	1		$\uparrow$				49							1	
50									50									50									50	_							
51				DLE				CSCH <sup>0</sup>	51	ID	CSCH <sup>1</sup>			IDL	.E			51		IDLI	E	CSCH <sup>2</sup>		IDL	E		51	L		IDLE			CSCH <sup>3</sup>	11	DLE

# Figure D.3: COMPACT downlink 52-multiframe structure using 4 time groups for large cells (based on an assignment of 1 CPBCCH and 3 CPCCCHs with NIB\_CCCH\_0 = NIB\_CCCH\_1 = NIB\_CCCH\_2 = NIB\_CCCH\_3 = 4). NIB\_CCCH is not broadcast for serving cell time group

	F	rames	s 0-5	MF	a 20 N = G = (	0	nultif	rame		F	rames (	M	of a 2 //FN = TG = <sup>^</sup>	0	nultif	ram	ne		F	ram	es (	-51 of a MFN TG :	= 0	-multi	fram	e
TS FN	0	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7
0		$B(0)^{0}$	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		0	X	X <sup>0</sup>	X <sup>0</sup>	B(0) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		0	X	X <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	$B(0)^{2}$		
1		$B(0)^{0}$	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		1	X	X <sup>0</sup>	X <sup>0</sup>	B(0) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		1	X	X <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	$B(0)^{2}$		
2		$B(0)^{0}$	X <sup>1</sup>	X <sup>1</sup>	$X^2$	$X^2$	$X^2$		2	X <sup>0</sup>	X <sup>0</sup>	X <sup>0</sup>	B(0) <sup>1</sup>	X <sup>2</sup>	$X^2$	$X^2$		2	X <sup>0</sup>	X <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	$B(0)^{2}$		
3 4		B(0) <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		3 4	X <sup>0</sup>	X <sup>0</sup>	X <sup>0</sup>	B(0) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		3 4	X <sub>0</sub>	X <sup>0</sup>	X <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	B(0) <sup>2</sup>		
4 5					-				45			-						4 5								
6					-				6			-						6								
7									7									7								
8									8									8								
9									9									9								
10									10									10								
11 12		L	<u> </u>			<u> </u>			11 12			L	PTCCI	<u> </u>	I	I		11 12				DTO		L		
12 13	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	ΡI X <sup>2</sup>	CCI X <sup>2</sup>	-		C(3) <sup>0</sup>	12	X <sup>0</sup>	C(3) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	н Х <sup>2</sup>		X <sup>0</sup>	X <sup>0</sup>	12 13	X1	X <sup>1</sup>	X <sup>1</sup>	PTC C(3) <sup>2</sup>	СН	r	X <sup>0</sup>	X <sup>0</sup>
14	X <sup>1</sup>	X <sup>1</sup>	х <sup>2</sup>	Λ X <sup>2</sup>	х <sup>2</sup>	$\vdash$		C(3) <sup>0</sup>	13	X <sup>0</sup>	C(3) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	х <sup>2</sup>		х <sup>0</sup>	х <sup>0</sup>	13 14	х <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	$C(3)^2$			х <sup>0</sup>	X <sup>0</sup>
15	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>			C(3) <sup>0</sup>	15	X <sup>0</sup>	C(3) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		X <sup>0</sup>	X <sup>0</sup>	15	X <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	C(3) <sup>2</sup>			X <sup>0</sup>	X <sup>0</sup>
16	X1	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>			$C(3)^{0}$	16	X	C(3) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		X <sup>0</sup>	X <sup>0</sup>	16	X <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	$C(3)^{2}$			X <sup>0</sup>	X
17									17									17								
18									18									18								
19 20									19 20									19 20								
20					-				20			-						20 21								
22									22									22								
23									23									23								
24									24									24								
25				DLE				CFCCH	25	ID	CFCCH1			IDL	E			25		IDLE		CFCCH <sup>2</sup>		IDL	_	
26	X <sup>1</sup>	X <sup>1</sup>		$X^2$	$X^2$			$C(6)^{0}$	26	X <sup>0</sup>	C(6) <sup>1</sup>	$X^2$	X <sup>2</sup>	$X^2$		X <sup>0</sup>	X <sup>0</sup>	26	X1	X <sup>1</sup>	X <sup>1</sup>	$C(6)^{2}$			X <sup>0</sup>	X <sup>0</sup>
27 28	X <sup>1</sup> X <sup>1</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>			C(6) <sup>0</sup> C(6) <sup>0</sup>	27 28	X <sup>0</sup> X <sup>0</sup>	C(6) <sup>1</sup> C(6) <sup>1</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>	X <sup>2</sup> X <sup>2</sup>		X <sup>0</sup> X <sup>0</sup>	X <sup>0</sup> X <sup>0</sup>	27 28	X' X <sup>1</sup>	X <sup>1</sup> X <sup>1</sup>	X <sup>1</sup> X <sup>1</sup>	$C(6)^2$ C(6) <sup>2</sup>			X <sup>0</sup>	X <sup>0</sup> X <sup>0</sup>
20 29	Λ X <sup>1</sup>	X <sup>1</sup>	Λ X <sup>2</sup>	Λ X <sup>2</sup>	Λ X <sup>2</sup>			$C(6)^{\circ}$	20 29	х <sup>0</sup>	C(6) <sup>1</sup>	Λ X <sup>2</sup>	Λ X <sup>2</sup>	л Х <sup>2</sup>		л Х <sup>0</sup>	Λ X <sup>0</sup>	∠o 29	х <sup>1</sup>	 Х <sup>1</sup>	Λ X <sup>1</sup>	$C(6)^2$			х <sup>0</sup>	х°
30	~	~	~	~	~			0(0)	30	~	0(0)	~	~	~		~	~	30	~	~	~	0(0)			~	~
31									31									31								
32									32									32								
33									33									33								
34			<u> </u>		_	<u> </u>			34			_		-				34								
35 36							$\vdash$		35 36					-			$\vdash$	35 36								$\vdash$
30			<u> </u>		1	<u> </u>			30			1		1				30 37								$\vdash$
38				PT	CCH	ł			38			· · · ·	PTCCI	H				38				PTC	СН			•
39	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>			C(9) <sup>0</sup>	39	X <sup>0</sup>	C(9) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		X <sup>0</sup>	X <sup>0</sup>	39	X <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	C(9) <sup>2</sup>			X <sup>0</sup>	X <sup>0</sup>
40	X1	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>			C(9) <sup>0</sup>	40	X <sup>0</sup>	C(9) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		X <sup>0</sup>	X <sup>0</sup>	40	X1	X <sup>1</sup>	X <sup>1</sup>	$C(9)^{2}$			X <sup>0</sup>	X <sup>0</sup>
41	X <sup>1</sup>	X <sup>1</sup>	$X^2$	$X^2$	$X^2$	L		$C(9)^{0}$	41	X <sup>0</sup>	C(9) <sup>1</sup>	$X^2$	X <sup>2</sup>	$X^2$		X <sup>0</sup>	X <sup>0</sup>	41	$X^1$	$X^1$	$X^1$	$C(9)^2$	L		X <sup>0</sup>	X <sup>0</sup>
42	X <sup>1</sup>	X <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>	<u> </u>		C(9) <sup>0</sup>	42	X <sup>0</sup>	C(9) <sup>1</sup>	X <sup>2</sup>	X <sup>2</sup>	X <sup>2</sup>		X <sup>0</sup>	X <sub>0</sub>	42	X <sup>1</sup>	X <sup>1</sup>	X <sup>1</sup>	C(9) <sup>2</sup>			X <sup>0</sup>	X <sup>0</sup>
43 44			-	-	-	-	$\vdash$	$\vdash$	43 44			-			-			43 44		-	-				-	$\vdash$
44			$\vdash$		$\vdash$	$\vdash$		$\square$	44			$\vdash$		-			$\vdash$	44 45								
46									46							-		46					-			
47			L		L	L			47			L						47								
48									48									48								
49									49									49								
50		I	L		L	L		0000	50	15	00011	<u> </u>		<u> </u>			1	50				0001/2			<u> </u>	
51			11	DLE				CSCH <sup>0</sup>	51	ID	CSCH <sup>1</sup>	<u> </u>		IDL	. <b>C</b>			51		IDLE	-	CSCH <sup>2</sup>		IDL	c	

## Figure D.4: COMPACT downlink 52-multiframe structure using 3 time groups for large cells (based on an assignment of 1 CPBCCH and 3 CPCCCHs with NIB\_CCCH\_0 = NIB\_CCCH\_1 = NIB\_CCCH\_2 = 4, NIB\_CPBCCH\_3 = 0). NIB\_CCCH is not broadcast for serving cell time group

	F	rames	s 0-		a 2 N =		nultif	frame		Fr	ame	s 52		of a	a 208-m = 1	ultifi	rame		Fra	mes	s 104	4-155 of MFN		)8-mul	tifra	me		Fra	ames 156-		7 of a 2 IFN = 3		mult	tifram	ıe
TS ( FN	D	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7
0		B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	52		X <sup>1</sup>		X <sup>2</sup>		X3		$B(0)^{0}$	104		X <sup>2</sup>		X <sup>3</sup>		$B(0)^{0}$		X <sup>1</sup>	156		X <sup>3</sup>		$B(0)^{0}$		X <sup>1</sup>	2	$X^2$
1		B(0) <sup>0</sup>		X1		X <sup>2</sup>		X <sup>3</sup>	53		X <sup>1</sup>		$X^2$		X <sup>3</sup>		B(0) <sup>0</sup>	105		$X^2$		X <sup>3</sup>		B(0) <sup>0</sup>		X <sup>1</sup>	157		X <sup>3</sup>		B(0) <sup>0</sup>		X <sup>1</sup>		$X^2$
2		B(0) <sup>0</sup>		X <sup>1</sup>		$X^2$		X <sup>3</sup>	54		$X^1$		$\chi^2$		X <sup>3</sup>		$B(0)^{0}$	106		$X^2$		X <sup>3</sup>		$B(0)^{0}$		$X^1$	158		X <sup>3</sup>		$B(0)^{0}$		$X^1$		$X^2$
3 4	_	B(0) <sup>0</sup>	-	X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	55 56		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		B(0) <sup>0</sup>	107 108		X <sup>2</sup>		X <sup>3</sup>		B(0) <sup>0</sup>		X <sup>1</sup>	159 160		X <sup>3</sup>	-	B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>
5				-					57							-		109									161			-		_			-
6									58									110									162			-					_
7									59									111									163								
8									60									112									164								
9	_		_	_					61 62									113									165 166								
10 11				-					62									114 115									166			_					
12			1	PT	CCI	H			64		I	L	F	тсо	ЭН	ı	1	116				PTC	СН				168		I	F	тссн		l		
13		X <sup>1</sup>	L	X <sup>2</sup>		X <sup>3</sup>		C(3) <sup>0</sup>	65		X <sup>2</sup>		X <sup>3</sup>		C(3) <sup>0</sup>		X <sup>1</sup>	117		X <sup>3</sup>		$C(3)^{0}$		X <sup>1</sup>		$X^2$	169		$C(3)^{0}$		X <sup>1</sup>		X <sup>2</sup>		X3
14		X1		X <sup>2</sup>		X <sup>3</sup>		C(3) <sup>0</sup>	66		X <sup>2</sup>		X <sup>3</sup>		$C(3)^{0}$		X1	118		$X^3$		C(3) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>	170		C(3) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		$X^3$
15		X <sup>1</sup>	L	X <sup>2</sup>		$X^3$		$C(3)^{0}$	67		$X^2$		$X^3$		C(3) <sup>0</sup>	<u> </u>	X <sup>1</sup>	119		$X^3$		C(3) <sup>0</sup>		X <sup>1</sup>		$X^2$	171		$C(3)^{0}$	$ \downarrow$	X <sup>1</sup>		$X^2$		$X^3$
16 17		X <sup>1</sup>		X <sup>2</sup>		X3		C(3) <sup>0</sup>	68 69		X <sup>2</sup>		X <sup>3</sup>		C(3) <sup>0</sup>		X <sup>1</sup>	120 121		X3		C(3) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>	172 173		C(3) <sup>0</sup>	_	X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>
18				-					70							-		121									173			-		_			-
19				1					71									123									175								
20									72									124									176								_
21									73									125									177								
22			_	_					74									126									178			_					_
23 24	_		-	-		-			75 76		-					-		127 128									179 180			-		_			_
25				IDLE				CFCCH <sup>0</sup>	77		-	IDLE			CFCCH <sup>1</sup>	10	DLE	129		IDLE		CFCCH <sup>2</sup>		IDL	E		181	ID	CFCCH <sup>3</sup>			IDLE	-		-
26		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(6)^{0}$	78		X <sup>2</sup>		X <sup>3</sup>		$C(6)^{0}$		X <sup>1</sup>	130		X <sup>3</sup>		$C(6)^{0}$		X <sup>1</sup>		X <sup>2</sup>	182		$C(6)^{0}$		X <sup>1</sup>		X <sup>2</sup>	2	X <sup>3</sup>
27		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(6)^{0}$	79		X <sup>2</sup>		X <sup>3</sup>		$C(6)^{0}$		X <sup>1</sup>	131		X <sup>3</sup>		$C(6)^{0}$		X <sup>1</sup>		X <sup>2</sup>	183		$C(6)^{0}$		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>
28	_	X <sup>1</sup>		$\chi^2$		$X^3$		$C(6)^{0}$	80		$X^2$		$X^3$		C(6) <sup>0</sup>		X <sup>1</sup>	132		$\chi^3$		$C(6)^{0}$		X <sup>1</sup>		$\chi^2$	184		$C(6)^{0}$	_	X <sup>1</sup>		$X^2$		$X^3$
29 30	_	X <sup>1</sup>		X <sup>2</sup>		X3		C(6) <sup>0</sup>	81 82		X <sup>2</sup>		X <sup>3</sup>		C(6) <sup>0</sup>	_	X <sup>1</sup>	133 134		X <sub>3</sub>		C(6) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>	185 186		C(6) <sup>0</sup>	_	X <sup>1</sup>	_	X <sup>2</sup>		X <sup>3</sup>
31				-					83							-		134									187			-		_			-
32									84									136									188			-					-
33									85									137									189								
34			L	+		<u> </u>			86		<u> </u>					<u> </u>	ļ	138									190			_					
35 36	_		$\vdash$	+	-				87 88		<u> </u>		$\vdash$			<u> </u>		139 140									191 192			$\dashv$		_			-
37	_		-	-					89									140									192								
38				PT	CC	Н			90				F	тсо	ЭН	-		142				PTC	СН				194			F	тссн				_
39		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		C(9) <sup>0</sup>	91		X <sup>2</sup>		X <sup>3</sup>		$C(9)^{0}$		X <sup>1</sup>	143		X <sup>3</sup>		$C(9)^{0}$		X <sup>1</sup>		X <sup>2</sup>	195		C(9) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>
40		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(9)^{0}$	92		$X^2$		X <sup>3</sup>	]	$C(9)^{0}$		X <sup>1</sup>	144		X <sup>3</sup>		C(9) <sup>0</sup>		X <sup>1</sup>		$X^2$	196		C(9) <sup>0</sup>	┛	X <sup>1</sup>		$X^2$		$X^3$
41	_	X <sup>1</sup> X <sup>1</sup>	_	X <sup>2</sup> X <sup>2</sup>	-	X <sup>3</sup> X <sup>3</sup>		$C(9)^{0}$	93 94		X <sup>2</sup> X <sup>2</sup>		$X^3$ $X^3$		$C(9)^{0}$	_	X <sup>1</sup> X <sup>1</sup>	145		$X^3$ $X^3$		$C(9)^{0}$		X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>	197 198		$C(9)^{0}$	$\dashv$	X <sup>1</sup> X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>		$X^3$ $X^3$
42 43	_	^	$\vdash$	X	-	×'	-	C(9) <sup>0</sup>	94 95		^	-	<b>^</b>		C(9) <sup>0</sup>	-	^	146 147		<b>^</b>		C(9) <sup>0</sup>		X <sup>1</sup>		^	198 199	-	C(9) <sup>0</sup>	$\dashv$	^	_	^	-	$\sim$
43			$\vdash$	+	1	1	1		95								1	147									200		<u>├</u>	+					
45			1	1		1			97									149									201			$\neg$					
46									98									150									202								
47			L	+		<u> </u>			99		<u> </u>					<u> </u>	ļ	151									203			_					
48 49	_		$\vdash$	+	-				100 101		<u> </u>		$\vdash$			<u> </u>		152 153									204 205			$\dashv$		_			-
49 50			┢	+	-	┢──	-		101									153									205			┥		-	-		$\neg$
51			<u> </u>	IDLE	•	1		CSCH⁰	102			IDLE			CSCH <sup>1</sup>	11	DLE	155		IDLE		CSCH <sup>2</sup>		IDL	F			ID	CSCH <sup>3</sup>			IDLE	-	- 1	-

#### Figure D.5: Example of COMPACT downlink timeslot mapping and rotation of control channels using 4 time groups for nominal cells (based on an assignment of 1 CPBCCH and 3 CPCCCHs with NIB\_CCCH\_0 = NIB\_CCCH\_1 = NIB\_CCCH\_2 = NIB\_CCCH\_3 = 4). TG = 0 is illustrated. NIB\_CCCH is not broadcast for serving cell time group

Frames 0 E1 of a 208 multiframe

75

Frames 104 1EE of a 200 multiframe

Frames E2 102 of a 200 multiframe

Frames 156 207 of a 208 multiframe

FN         FN         FN         FN         FN         FN           1         Bi00 <sup>o</sup> X:         X:         X:         Bi00 <sup>o</sup> 105 $X''_{1}$ Bi00 <sup>o</sup> X:         Bi00 <sup>o</sup> X:         Bi00 <sup>o</sup> X:         X:         Bi00 <sup>o</sup> X:         Bi00 <sup>o</sup> X:         X:         Bi00 <sup>o</sup> X:         X:         Bi00 <sup>o</sup> X:         Sis         Sis         Sis         Sis		Fra	ames	0-5		a 20 N =		nulti	frame		F	ame	es 52		of a	a 208-m = 1	ultifi	ame		Fra	ames	s 104	I-155 of MFN		)8-mul	tifra	me		Fra	ames 156-		7 of a //FN =		muli	tifrai	ne
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $		D	1	2	3	4	5	6	7			1	2	3	4	5	6	7		0	1	2	3	4	5	6			0	1	2	3	4	5	6	7
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $		_	\ <u>/</u>																													· / .		X <sup>1</sup>		X <sup>2</sup>
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $																																		X <sup>1</sup>		$X^2$
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $																																· · / .		X <sup>1</sup> X <sup>1</sup>		$\chi^2$
5         1	-	E	s(0) ·		X		X					X		X				B(0)			X				B(0)		X				_	B(0)		X		X <sup>2</sup>
6       7       1       1       10       10       10       16       163         7       1       1       11       11       11       11       166       177       178	· · _	_						-				-																			-					
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $		-								-																		-			$\neg$			_		
6       7																															-					
0       2       62       1       14       14       16       166       167       168       178       178       178       178       178       178       171       173       173       173       173       173       173       173       173       173       173       174	8																																			
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $	9									61									113									165								
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																																				
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $																																				
14 $X'_{-}$ $X'_{-}$ $C(3)^{\circ}$ $X'_{-}$ $X$			v1			CCF	1	r	$C(2)^0$			V <sup>2</sup>	1	F	2TC			V1	-		-			CH	V1		$\sqrt{2}$			$C(2)^0$			1	V <sup>2</sup>		
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $							-						-								$\vdash$						× ×2							X <sup>2</sup> X <sup>2</sup>		
16 $X^1$ $X^2$ $C(3)^\circ$ $K^1$ $X^2$ $C(3)^\circ$ $X^1$ $X^2$ $X^1$ $X^1$ $X^2$ $X^1$ $X^2$ $X^1$ $X^2$ $X^1$ $X^2$ $X^1$							-	-					-																		-			Λ X <sup>2</sup>		
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																															$\neg$			X <sup>2</sup>		_
$\begin{array}{c c c c c c c c c c c c c c c c c c c $									•(•)							-(-)							-(-)							- (-)	-					
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $	18									70									122									174								
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																																				
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																																				
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																			-																	
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																															_					
$\begin{array}{c c c c c c c c c c c c c c c c c c c $		-																													$\neg$			_		
$\begin{array}{c c c c c c c c c c c c c c c c c c c $				IC	DLE			I	CFCCH <sup>0</sup>			I	IDLE			CFCCH1	1[	DLE			IDLE		CFCCH <sup>2</sup>		IDL	E			ID	CFCCH <sup>3</sup>			IDL	E	1	
28 $x^1$ $x^2$ $C(6)^0$ $x^1$ $x^2$ $C(6)^0$ $x^1$ $x^2$ $132$ $C(6)^0$ $x^1$ $x^2$ $133$ $C(6)^0$ $x^1$ $x^2$ $134$ $134$ $134$ $134$ $134$ $134$ $134$ $134$ $134$ $136$ $136$ $136$ $136$ $136$ $138$ $136$ $137$ $138$ $138$ $138$ $138$ $137$ $138$ $138$ $190$ $114$ $190$ $114$ $190$ $1141$ $191$ $1141$ $192$ $1141$ $192$ $1141$ $193$ $1141$	26		X <sup>1</sup>		X <sup>2</sup>				$C(6)^{0}$	78		X <sup>2</sup>				$C(6)^{0}$		X <sup>1</sup>	130				$C(6)^{0}$		X <sup>1</sup>		X <sup>2</sup>	182		$C(6)^{0}$		X <sup>1</sup>		X <sup>2</sup>		
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																																		X <sup>2</sup>		
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$																												-						$X^2$		
$\begin{array}{c c c c c c c c c c c c c c c c c c c $			Χ'		X²				C(6) <sup>0</sup>			X²				$C(6)^{0}$		Χ'					C(6) <sup>0</sup>		Χ'		X²			$C(6)^{0}$		Χ'		X <sup>2</sup>		
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																			-												_					
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																															_					
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $		-																													$\neg$			_		
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $																															-					
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																																				
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																																				
$\begin{array}{c c c c c c c c c c c c c c c c c c c $																																				
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $		1	V1			CCF	-	1	$C(0)^0$		_	V <sup>2</sup>	1	F	2TC			<b>v</b> 1			<b></b>			CH	V <sup>1</sup>		$\sqrt{2}$	-		$C(0)^0$			1	X <sup>2</sup>	1	
$\begin{array}{c c c c c c c c c c c c c c c c c c c $							-						-						-		$\vdash$						× ×2							X <sup>-</sup> X <sup>2</sup>		
$\begin{array}{c c c c c c c c c c c c c c c c c c c $							-	-					-																		-			Λ X <sup>2</sup>		
43     6     95     6     147     199     199       44     96     147     148     199     100       45     97     148     100     200     100       46     98     100     150     100     201     100																															-			X <sup>2</sup>		-
45         97         149         201         149           46         98         150         202         140									-(-)		_	1				-(-)							- (-)							-(-)	-					
46 98 150 202 202											_																									
47                 99             151                 203												<u> </u>																								
								<u> </u>					<u> </u>						-																	
48         100         152         204           49         101         101         153         205		_					-	<u> </u>			-	┢	-								$\vdash$										_					
49         101         101         103         205         205           50         102         154         206         206         1						-	-	-			⊢	$\vdash$	-		-						$\vdash$						-				-					
				IC	DLE				CSCH <sup>0</sup>				IDLE			CSCH <sup>1</sup>	10	DLE			IDLE		CSCH <sup>2</sup>	-	IDL	E			ID	CSCH <sup>3</sup>			IDL	E		_

#### Figure D.6: Example of COMPACT downlink timeslot mapping and rotation of control channels using 3 time groups for nominal cells (based on an assignment of 1 CPBCCH and 3 CPCCCHs with NIB\_CCCH\_0 = NIB\_CCCH\_1 = NIB\_CCCH\_2 = 4, NIB\_CCCH\_3 = 0). TG = 0 is illustrated. NIB\_CCCH is not broadcast for serving cell time group

NOTE: For uplink 52-multiframe structure (based on an assignment of 16 prioritized CPRACHs, see subclause 6.3.2.2.3a), replace B() by R() where R() denotes CPRACH, move down one block, and rotate according to subclause 6.3.2.1. Replace C() by R() and move down one block. CPRACH in general can be mapped as PRACH in Clause 7 Table 6.

ETSI

Frames 0-51 of a 208-multiframe

76

Eromos 104 1EE of a 200 multiframe

Frames E2 102 of a 200 multiframe

Frames 156-207 of a 208-multiframe

Frames 0-51 of a 208-multiframe MFN = 0					frame		Frames 52-103 of a 208-multiframe MFN = 1						Frames 104-155 of a 208-multiframe MFN = 2							Frames 156-207 of a 208-multiframe MFN = 3														
)	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7	TS FN	0	1	2	3	4	5	6	7
	B(0) <sup>0</sup>		X <sup>1</sup>	Γ	X <sup>2</sup>		X <sup>3</sup>	52	Γ	X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	1	$B(0)^{0}$	104		X <sup>2</sup>	T	X <sup>3</sup>		$B(0)^{0}$		X <sup>1</sup>	156		X <sup>3</sup>		B(0) <sup>0</sup>		X <sup>1</sup>		Х
	B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	53		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$B(0)^{0}$	105		X <sup>2</sup>		X3		B(0) <sup>0</sup>		X <sup>1</sup>	157		X <sup>3</sup>		B(0) <sup>0</sup>		$X^1$		Х
	B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	54		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$B(0)^{0}$	106		X <sup>2</sup>		X3		$B(0)^{0}$		X <sup>1</sup>	158		X <sup>3</sup>		$B(0)^{0}$		X <sup>1</sup>		Х
	B(0) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>	55		X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		B(0) <sup>0</sup>	107		X <sup>2</sup>		X <sup>3</sup>		B(0) <sup>0</sup>		X <sup>1</sup>	159		X <sup>3</sup>		B(0) <sup>0</sup>		X <sup>1</sup>		Х
	X <sup>1</sup>							56								X <sup>1</sup>	108						X <sup>1</sup>			160				X <sup>1</sup>				
	X <sup>1</sup>							57								X <sup>1</sup>	109						X <sup>1</sup>			161				X <sup>1</sup>				
	X <sup>1</sup> X <sup>1</sup>							58 59								X <sup>1</sup> X <sup>1</sup>	110 111						X <sup>1</sup> X <sup>1</sup>			162 163				X <sup>1</sup> X <sup>1</sup>				
_	~			-				59 60								^	112						^			163			_	^				
-								61									112									165			-			-		ŀ
								62									114									166			-					r
-								63									115									167			-					r
			PT	CCI	H			64				F	тсо	СН			116				PTC	СН				168			F	тсс⊦	1			
	X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(3)^{0}$	65		X <sup>2</sup>		X <sup>3</sup>		$C(3)^{0}$		X <sup>1</sup>	117		X <sup>3</sup>		$C(3)^{0}$		X <sup>1</sup>		X <sup>2</sup>	169		$C(3)^{0}$		X <sup>1</sup>		X <sup>2</sup>		
	X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(3)^{0}$	66		X <sup>2</sup>		X <sup>3</sup>		$C(3)^{0}$		X <sup>1</sup>	118		X <sup>3</sup>		$C(3)^{0}$		X <sup>1</sup>		X <sup>2</sup>	170		$C(3)^{0}$		X <sup>1</sup>		X <sup>2</sup>		
	X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		C(3) <sup>0</sup>	67		X <sup>2</sup>		X <sup>3</sup>		$C(3)^{0}$		X <sup>1</sup>	119		X <sup>3</sup>		C(3) <sup>0</sup>	L	X <sup>1</sup>		X <sup>2</sup>	171		C(3) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		
	X1		X <sup>2</sup>		X <sup>3</sup>		$C(3)^{0}$	68		X <sup>2</sup>		X <sup>3</sup>		C(3) <sup>0</sup>		X <sup>1</sup>	120		X <sup>3</sup>		$C(3)^{0}$		X <sup>1</sup>		X <sup>2</sup>	172		$C(3)^{0}$		X <sup>1</sup>		X <sup>2</sup>		
				-				69									121									173								ŀ
_			_	-	-			70 71									122 123									174 175								ŀ
-				-				72									123									175			-					ŀ
-								73									124									177			-					ŀ
								74									126									178			-					t
								75									127									179								r
								76									128									180								ľ
		I	DLE				CFCCH <sup>0</sup>	77			IDLE			CFCCH <sup>1</sup>		DLE	129		DLE		CFCCH <sup>2</sup>		IDL	E		-	ID	CFCCH <sup>3</sup>			IDL			
	X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(6)^{0}$	78		X <sup>2</sup>		X <sup>3</sup>		C(6) <sup>0</sup>		X <sup>1</sup>	130		X <sup>3</sup>		C(6) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>	182		$C(6)^{0}$		X <sup>1</sup>		X <sup>2</sup>		
	X1		X <sup>2</sup>		X <sup>3</sup>		$C(6)^{0}$	79		X <sup>2</sup>		X <sup>3</sup>		C(6) <sup>0</sup>		X <sup>1</sup>	131		X <sup>3</sup>		C(6) <sup>0</sup>		X <sup>1</sup>		$X^2$	183		$C(6)^{0}$		X <sup>1</sup>		X <sup>2</sup>		
	X <sup>1</sup>		$X^2$		$X^3$		$C(6)^{0}$	80		$X^2$		$X^3$		$C(6)^{0}$		X <sup>1</sup>	132		$X^3$		C(6) <sup>0</sup>		X <sup>1</sup>		$\chi^2$	184		$C(6)^{0}$		X <sup>1</sup>		$X^2$		
	X <sup>1</sup>		X <sup>2</sup>		X <sup>3</sup>		$C(6)^{0}$	81 82		X <sup>2</sup>		X3		$C(6)^{0}$		X <sup>1</sup>	133		X <sup>3</sup>		C(6) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>	185 186		C(6) <sup>0</sup>		X <sup>1</sup>		X <sup>2</sup>		
			_	-	-			83									134 135									187								ŀ
_				-	-			84							-		135						-			188								
								85									137									189			-					t
								86									138									190								r
								87									139									191								Γ
								88									140									192								
								89									141									193								
	11			CCI			a (a) 0	90		2			тс		1	1	142		3	-	PTC	СН	1		2	194		a (a) (	F	PTCCH	1	2		1
_	X <sup>1</sup>	<u> </u>	$\chi^2$	⊢	$X^3$		$C(9)^{0}$	91	L	$\chi^2$		$X^3$		$C(9)^{0}$	<u> </u>	X <sup>1</sup>	143		$X^3$		C(9) <sup>0</sup>	L	X <sup>1</sup>		$\chi^2$	195		$C(9)^{0}$		X <sup>1</sup>		$\chi^2$		
-	X <sup>1</sup> X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>	┢	X <sup>3</sup> X <sup>3</sup>		C(9) <sup>0</sup> C(9) <sup>0</sup>	92 93	<u> </u>	X <sup>2</sup> X <sup>2</sup>		X <sup>3</sup> X <sup>3</sup>		C(9) <sup>0</sup> C(9) <sup>0</sup>	-	X <sup>1</sup> X <sup>1</sup>	144 145		X <sup>3</sup> X <sup>3</sup>		C(9) <sup>0</sup> C(9) <sup>0</sup>		X <sup>1</sup> X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>	196 197		C(9) <sup>0</sup> C(9) <sup>0</sup>		X <sup>1</sup> X <sup>1</sup>		X <sup>2</sup> X <sup>2</sup>		
-	X <sup>1</sup>	-	Λ X <sup>2</sup>	$\vdash$	Λ X <sup>3</sup>	-	$C(9)^{0}$	93 94	-	Λ X <sup>2</sup>		Λ X <sup>3</sup>		C(9) <sup>0</sup>		X <sup>1</sup>	145		Λ X <sup>3</sup>	_	C(9) <sup>0</sup>	-	X <sup>1</sup>		Λ X <sup>2</sup>	197		C(9) <sup>0</sup>	_	х Х <sup>1</sup>		Λ X <sup>2</sup>	_	
-	^		^	$\vdash$	<u> </u>		0(9)	94 95	-	^		^		0(3)	-	^	140		^	-	0(9)		^		^	190		0(9)	-	^		^		┞
_			$\mathbf{t}$	$\vdash$	1			96	-								148									200			-					t
					1			97							1		149									201			$\neg$					t
-			1	1	1			98									150									202								t
			+	1	1	1		99		1					1		151					1				203								Í
																																	-	-
								100									152									204								L
								100 101 102									152 153 154									204 205 206								

#### Figure D.7: Example of COMPACT downlink timeslot mapping and rotation of control channels using 4 time groups for nominal cells (based on an assignment of 1 CPBCCH and 3 CPCCCHs with NIB\_CCCH\_0 = NIB\_CCCH\_2 = NIB\_CCCH\_3 = 4, NIB\_CCCH\_1 = 5). TG = 0 is illustrated. NIB\_CCCH is not broadcast for serving cell time group

### Annex E (informative): Change control history

SPEC	SMG #	CR	PHA SE	VERS	NEW_VE RS	SUBJECT
05.02	s24	A020	R97	5.5.0A	6.0.0	Corrections and clarifications to GPRS
05.02	s24	A021	R97	5.5.0A	6.0.0	Multislot classes for GPRS
05.02	s24	A022	R97	5.5.0A	6.0.0	System information for GPRS on BCCH
05.02	s24	A023	R97	5.5.0A	6.0.0	Alignment of 51- and 52-multiframe PCCCH
05.02	s25	A025	R97	6.0.1	6.1.0	Corrections to the GPRS sleep mode
05.02	s25	A026	R97	6.0.1	6.1.0	Clarification of the definition of multislot classes
05.02	s25	A030	R97	6.0.1	6.1.0	14.4kbps Data Service
05.02	s25	A034	R97	6.0.1	6.1.0	Indication of PACCH logical channel type
05.02	s25	A035	R97	6.0.1	6.1.0	Renaming of GPRS RR states
05.02	s25	A036	R97	6.0.1	6.1.0	USF granularity for dynamic allocation
05.02	s26	A033	R97	6.1.0	6.2.0	GPRS SI message mapping
05.02	s26	A037	R97	6.1.0	6.2.0	Mapping of PACCH
05.02	s26	A039	R97	6.1.0	6.2.0	Mapping of SI 2 and SI 2ter on BCCH
05.02	s27	A041	R97	6.2.0	6.3.0	Clarification on PTCCH/U mapping
05.02	s27	A042	R97	6.2.0	6.3.0	Clarification on mapping PCCCH
05.02	s27	A043	R97	6.2.0	6.3.0	MS multislot classes and GPRS dynamic allocations
05.02	s28	A045	R97	6.3.0	6.4.0	Removal of System Information Type 14
05.02	s28	A052	R97	6.3.0	6.4.0	Schedule for packet System Information message on PBCCH
05.02	s28	A054	R97	6.3.0	6.4.0	Editorial correction to 05.02
05.02	s28	A055	R97	6.3.0	6.4.0	Improvements of PRS paging blocks scheduling
05.02	s28	A057	R97	6.3.0	6.4.0	51-multiframe PBCCH
05.02	s28	A060	R97	6.3.0	6.4.0	Clarification to the multislot configurations for GPRS
05.02	s28	A061	R97	6.3.0	6.4.0	Clarification to the PTCCH mapping
05.02	s28	A064	R97	6.3.0	6.4.0	Removal of inconsistency in Table 7
05.02	s28	A048	R98	6.4.0	7.0.0	Introduction of specific training sequences for CTS Synchr. bursts
05.02	s28	A049	R98	6.4.0	7.0.0	Introduction of CTS in 05.02
05.02	s28	A050	R98	6.4.0	7.0.0	CTS Frequency Hopping Algorithm
05.02	s29	A047	R98	7.0.0	7.1.0	Addition of SoLSA functionality
05.02	s29	A065	R98	7.0.0	7.1.0	Editorial modification to GSM 05.02
05.02	s29	A066	R98	7.0.0	7.1.0	Correction of TFH carrier list
05.02	s29	A067	R98	7.0.0	7.1.0	Training sequence code of normal bursts for CTS control channel
05.02	s29	A070	R98	7.0.0	7.1.0	Removal of SI15 references
05.02	s29	A071	R98	7.0.0	7.1.0	Deleting 51-multiframe PBCCH
05.02	s29	A072	R98	7.0.0	7.1.0	Modification of CTSARCH operation
05.02	s29	A077	R98	7.0.0	7.1.0	Correction to non-drx period and SPLIT_PG_CYCLE limitations
05.02	s29	A046	R99	7.1.0	8.0.0	Introduction of 8-PSK burst format
05.02	s29	A074	R99	7.1.0	8.0.1	05.02 changes for ECSD FACCH
05.02	s30	A080	R99	8.0.1	8.1.0	Introduction of AMR and EFR Traffic Channels
05.02	s30	A081	R99	8.0.1	8.1.0	Non-GSM Broadcast Information
05.02	s30	A082	R99	8.0.1	8.1.0	EDGE Compact Cell Reselection
05.02	s30	A083	R99	8.0.1	8.1.0	New training sequences for Access Burst due to EGPRS
05.02	s30	A084	R99	8.0.1	8.1.0	Introduction of Fast Power Control for ECSD in 05.02
05.02	s30	A085	R99	8.0.1	8.1.0	EDGE Compact logical channels
05.02	s30	A098	R99	8.0.1	8.1.0	Mapping of PAGCH
05.02	s30	A101	R99	8.0.1	8.1.0	Clarification pf DRX
05.02	s30	A103	R99	8.0.1	8.1.0	Correction when sending SI 16 and 17
05.02	s30b	A095	R99	8.1.0	8.2.0	MS multislot resource restriction in extended TA cells
05.02	s30b	A106	R99	8.1.0	8.2.0	Clarification of fixed allocated PRACH
05.02	s30b	A107	R99	8.1.0	8.2.0	COMPACT Logical Channels
05.02	s30b	A109	R99	8.1.0	8.2.0	Extended Training Sequence Code C-ETSC specific to COMPACT synchronization bursts only
05.02	s30b	A110	R99	8.1.0	8.2.0	Support of Slow Frequency Hopping for COMPACT
05.02	s30b	A111		8.1.0	8.2.0	Synchronisation of 52-multiframes in EGPRS COMPACT
05.02	s30b	A114		8.1.0	8.2.0	Bi-directional channels in case of multi slot
05.02	s30b	A117	R99	8.1.0	8.2.0	Clarification of multislot configuration
05.02	s30b	A119	R99	8.1.0	8.2.0	Training Sequence to support LCS and specification of 8-PSK modulated normal bursts for compatibility with future releases, mirror CR to R'98

SPEC				SUBJECT		
	#		SE		RS	
05.02	s30b	A120	R99	8.1.0	8.2.0	Compact FCCH
05.02	s31	A123	R99	8.2.0	8.3.0	PTCCH block numbering
05.02	s31	A126	R99	8.2.0	8.3.0	Correction of BS_PRACH_BLKS range
05.02	s31	A127	R99	8.2.0	8.3.0	COMPACT interference measurements
05.02	s31	A128	R99	8.2.0	8.3.0	Timegroup rotation and NIB Clarification
05.02	s31	A129	R99	8.2.0	8.3.0	Clarifications in 05.02
05.02	s31	A133	R99	8.2.0	8.3.0	USF Handling in COMPACT
05.02	s31	A138	R99	8.2.0	8.3.0	Correction to non-DRX mode
05.02	s31	A142	R99	8.2.0	8.3.0	GPRS & SMS-CB interworking
05.02	s31	A143	R99	8.2.0	8.3.0	Complete Frequency Hopping on COMPACT
05.02	s31b	A148	R99	8.3.0	8.4.0	New measurement order – Idle mode
05.02	s31b	A147	R99	8.3.0	8.4.0	Clarification of PBCCH message scheduling
05.02	s31b	A157	R99	8.3.0	8.4.0	FCCH decoding problem for multislot MS
05.02	s31b	A144	R99	8.3.0	8.4.0	Correction of Figure D.4
05.02	s31b	A149	R99	8.3.0	8.4.0	Correction of NIB parameters

### History

		Document history		
V8.2.0	January 2000	One-step Approval Procedure	OAP 200019:	2000-01-12 to 2000-05-12
V8.3.0	April 2000	One-step Approval Procedure	OAP 20000825:	2000-04-26 to 2000-08-25
V8.4.0	May 2000	One-step Approval Procedure	OAP 20000929:	2000-05-31 to 2000-09-29