

# EN 301 005-2 V1.1.5 (1998-09)

---

*European Standard (Telecommunications series)*

**V interfaces at the digital Service Node (SN);  
Interfaces at the VB5.1 reference point for the support of  
broadband or combined narrowband and broadband  
Access Networks (ANs);  
Part 2: Protocol Implementation Conformance  
Statement (PICS) proforma specification**

---



---

**Reference**

DEN/SPS-09046-2 (9b0i0ifc.PDF)

---

**Keywords**

V interface, PSTN, ISDN, B-ISDN, AN, SN, PICS

**ETSI**

---

**Postal address**

F-06921 Sophia Antipolis Cedex - FRANCE

---

**Office address**

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16  
Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Internet**

secretariat@etsi.fr  
<http://www.etsi.fr>  
<http://www.etsi.org>

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.  
All rights reserved.

# Contents

Intellectual Property Rights.....	5
Foreword .....	5
Introduction .....	5
1 Scope.....	6
2 Normative references .....	6
3 Definitions and abbreviations .....	6
3.1 Definitions .....	6
3.2 Abbreviations.....	7
4 Conformance to this PICS proforma specification .....	8
<b>Annex A (normative): PICS proforma for EN 301 005-1 .....</b>	<b>9</b>
A.1 Guidance for completing the PICS proforma.....	9
A.1.1 Purposes and structure .....	9
A.1.2 Abbreviations and conventions .....	9
A.1.3 Instructions for completing the PICS proforma .....	11
A.2 Identification of the implementation.....	12
A.2.1 Date of the statement .....	12
A.2.2 Implementation Under Test (IUT) identification .....	12
A.2.3 System Under Test (SUT) identification.....	12
A.2.4 Product supplier .....	13
A.2.5 Client (if different from product supplier) .....	13
A.2.6 PICS contact person.....	14
A.3 Identification of the protocol .....	14
A.4 Global statement of conformance .....	14
A.5 Service node.....	15
A.5.1 Main features .....	15
A.5.1.1 General.....	15
A.5.1.2 ATM layer characteristics .....	15
A.5.1.2.1 Broadband access network connection types.....	15
A.5.1.2.2 ATM transfer characteristics .....	16
A.5.2 VB5.1 reference point.....	16
A.5.2.1 Basic characteristics .....	16
A.5.2.1.1 Support of a physical interface .....	16
A.5.2.1.2 Physical layer at the VB5.1 reference point.....	17
A.5.2.2 ATM layer functions .....	17
A.5.2.3 ATM adaptation layer .....	17
A.5.2.3.1 AAL for the RTMC protocol.....	17
A.5.2.3.2 AAL for circuit emulation of 2 048 kbit/s signals .....	18
A.5.2.4 RTMC function and protocol .....	18
A.5.2.4.1 RTMC main features .....	18
A.5.2.4.2 RTMC messages.....	18
A.5.2.4.2.1 RTMC messages received by the Service Node.....	18
A.5.2.4.2.2 RTMC messages transmitted by the Service Node .....	19
A.5.2.4.3 Timers used in RTMC procedures.....	19
A.5.2.4.4 RTMC function specific information elements.....	19
A.6 Access network .....	20
A.6.1 Main features .....	20
A.6.1.1 General.....	20
A.6.1.2 ATM layer characteristics .....	20
A.6.1.2.1 Broadband access network connection types.....	20

A.6.1.2.2	ATM transfer characteristics .....	21
A.6.2	Access types.....	21
A.6.2.1	Support of ATM based access types .....	21
A.6.2.1.1	Basic characteristics .....	21
A.6.2.1.2	Physical layer.....	22
A.6.2.1.3	ATM layer functions.....	22
A.6.2.2	Support of non B-ISDN access types .....	23
A.6.2.2.1	Narrowband access types.....	23
A.6.3	VB5.1 reference point.....	23
A.6.3.1	Basic characteristics .....	23
A.6.3.1.1	Support of a physical interface .....	23
A.6.3.2	Physical layer at the VB5.1 reference point .....	23
A.6.3.3	ATM layer functions .....	24
A.6.3.4	ATM adaptation layer .....	24
A.6.3.4.1	AAL for the RTMC protocol.....	24
A.6.3.4.2	AAL for circuit emulation of 2 048 kbit/s signals .....	24
A.6.3.5	RTMC function and protocol .....	25
A.6.3.5.1	RTMC main features .....	25
A.6.3.5.2	RTMC messages.....	25
A.6.3.5.2.1	RTMC messages received by the Access Network .....	25
A.6.3.5.2.2	RTMC messages transmitted by the Access Network.....	25
A.6.3.5.3	Timers used in RTMC procedures.....	26
A.6.3.5.4	RTMC function specific information elements.....	26
<b>Annex B (informative): Status of OAM functions based F4/F5 flows.....</b>		<b>27</b>
B.1	OAM functions at service port (SN-side) .....	28
B.2	OAM functions at user port .....	29
B.3	OAM functions at service port (AN-side).....	30
<b>Annex C (informative): Support of ATM transfer capabilities and QoS classes.....</b>		<b>31</b>
C.1	ATM transfer capabilities .....	31
C.2	QoS classes .....	32
History .....		33

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 2 of a multi-part standard covering the interfaces at the VB5.1 reference point as described below:

Part 1: "Interface specification";

**Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification".**

NOTE: Further parts covering conformance testing may be identified later.

<b>National transposition dates</b>	
Date of adoption of this EN:	18 September 1998
Date of latest announcement of this EN (doa):	31 December 1998
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 1999
Date of withdrawal of any conflicting National Standard (dow):	30 June 1999

---

## Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a telecommunication specification. Such a statement is called a Protocol Implementation Conformance Statement (PICS).

---

# 1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) proforma for the interfaces at the VB5.1 reference point for the support of broadband or combined narrowband and broadband Access Networks (ANs) as defined in EN 301 005-1 [1] in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-7 [4] and ETS 300 406 [2].

It details in tabular form the implementation options, i.e. the optional functions additional to those which are mandatory to implement.

---

# 2 Normative references

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply; or
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity); or
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] EN 301 005-1 (V1.1): "V interfaces at the digital Service Node (SN); Interfaces at the VB5.1 reference point for the support of broadband or combined narrowband and broadband Access Networks (ANs); Part 1: Interface specification".
- [2] ETS 300 406 (1995): "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [3] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [4] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the following definitions apply:

- terms defined in EN 301 005-1 [1];
- terms defined in ISO/IEC 9646-1 [3] and in ISO/IEC 9646-7 [4].

In particular, the following terms defined in ISO/IEC 9646-1 [3] apply:

**Protocol Implementation Conformance Statement (PICS):** a statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented. The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, information object ICS, etc.

**ICS proforma:** a document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS.

**Protocol ICS (PICS):** an ICS for an implementation or system claimed to conform to a given protocol specification.

**static conformance review:** a review of the extent to which the static conformance requirements are met by the Implementation Under Test (IUT), accomplished by comparing the PICS with the static conformance requirements expressed in the relevant standard(s) (see ISO/IEC 9646-1 [3]).

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAL1	ATM Adaptation Layer type 1
AAL5	ATM Adaptation Layer type 5
ABR	Available Bit Rate
ABT	ATM Block Transfer
AIS	Alarm Indication Signal
AN	Access Network
ATC	ATM Transfer Capability
ATM	Asynchronous Transfer Mode
B-AN	Broadband Access Network
B-ISDN	Broadband Integrated Services Digital Network
B-UNI	Broadband User Network Interface
DBR	Deterministic Bit Rate
DT	Delayed Transmission
EFCI	Explicit Forward Congestion Indication
GFC	Generic Flow Control
ICS	Implementation Conformance Statements
ID	Identification
IT	Immediate Transmission
IUT	Implementation Under Test
LSP	Logical Service Port
NNI	Network-to-Network Interface
NPC	Network Parameter Control
OAM	Operations Administration and Maintenance
PDH	Plesiochronous Digital Hierarchy
PICS	Protocol Implementation Conformance Statement
ptm	point to multipoint
ptp	point to point
QoS	Quality of Service
RDI	Remote Defect Indication
RTMC	Real Time Management Co-ordination (protocol)
SBR	Statistical Bit Rate
SCS	System Conformance Statement
SDH	Synchronous Digital Hierarchy
SN	Service Node
SSCF	Service Specific Co-ordination Function
SSCOP	Service Specific Connection Oriented Protocol
STM	Synchronous Transport Module
SUT	System Under Test
TC	Termination Convergence
UNI	User Network Interface
UPC	Usage Parameter Control
VC	Virtual Channel
VCCT	Virtual Channel Connection Termination
VCE	Virtual Channel Entity
VCI	Virtual Channel Identifier
VCME	Virtual Channel Multiplex Entity
VP	Virtual Path

VPC	Virtual Path Connection
VPCI	Virtual Path Connection Identifier
VPCT	Virtual Path Connection Termination
VPE	Virtual Path Entity
VPI	Virtual Path Identifier
VPME	Virtual Path Multiplex Entity

---

## 4 Conformance to this PICS proforma specification

If it claims to conform to the present document the actual PICS proforma to be filled in by a supplier shall be technically equivalent to the text of the PICS proforma given in annex A, and shall preserve the numbering/naming and ordering of the proforma items.

An PICS which conforms to the present document shall be a conforming PICS proforma completed in accordance with the guidance for completion given in annex A, clause A.1.



## Annex A (normative): PICS proforma for EN 301 005-1

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.

### A.1 Guidance for completing the PICS proforma

#### A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in EN 301 005-1 [1] may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into subclauses for the following categories of information:

- guidance for completing the PICS proforma;
- identification of the implementation;
- identification of the protocol;
- global statement of conformance.

#### A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [4].

##### **Item column**

The item column contains a number which identifies the item in the table.

##### **Item description column**

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

##### **Status column**

The following notations, defined in ISO/IEC 9646-7 [4], are used for the status column:

m	mandatory - the capability is required to be supported.
o	optional - the capability may be supported or not.
n/a	not applicable - in the given context, it is impossible to use the capability.
x	prohibited (excluded) - there is a requirement not to use this capability in the given context.
o.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table.
ci	conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table.

### Reference column

The reference column makes reference to EN 301 005-1 [1], except where explicitly stated otherwise.

### Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [4], are used for the support column:

- Y or y supported by the implementation.
- N or n not supported by the implementation.
- N/A, n/a or - no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

If this PICS proforma is completed in order to describe a multiple-profile support in a system, it is necessary to be able to answer that a capability is supported for one profile and not supported for another. In that case, the supplier shall enter the unique reference to a conditional expression, preceded by "?" (e.g. ?3). This expression shall be given in the space for comments provided at the bottom of the table. It uses predicates defined in the SCS, each of which refers to a single profile and which takes the value TRUE if and only if that profile is to be used.

EXAMPLE: ?3: IF prof1 THEN Y ELSE N

It is also possible to provide a comment to an answer in the space provided at the bottom of the table.

NOTE: As stated in ISO/IEC 9646-7 [4], support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

### Values allowed column

The values allowed column contains the type, the list, the range, or the length of values allowed. The following notations are used:

- range of values: <min value> .. <max value>  
example: 5 .. 20
- list of values: <value1>, <value2>, ....., <valueN>  
example: 2, 4, 6, 8, 9  
example: '1101'B, '1011'B, '1111'B  
example: '0A'H, '34'H, '2F'H
- list of named values: <name1>(<val1>), <name2>(<val2>), ....., <nameN>(<valN>)  
example: reject(1), accept(2)
- length: size (<min size> .. <max size>)  
example: size (1 .. 8)

### Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

### References to items

For each possible item answer (answer in the support column) within the PICS proforma a unique reference exists, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are discriminated by letters (a, b, etc.), respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table 5 of annex A.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table 6 of annex A.

### Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

## A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in subclause A.1.2.

However, the tables containing in "AN role" subclause shall only be completed for user implementations, and the tables containing in "SN role" subclause shall only be completed for network implementations.

If necessary, the supplier may provide additional comments in space at the bottom of the tables, or separately on sheets of paper.

More detailed instructions are given at the beginning of the different subclauses of the PICS proforma.

---

## A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

### A.2.1 Date of the statement

.....

### A.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

### A.2.3 System Under Test (SUT) identification

SUT name:

.....

.....

Hardware configuration:

.....

.....

.....

Operating system:

.....

### A.2.4 Product supplier

Name:

.....

Address:

.....  
.....  
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....  
.....  
.....

### A.2.5 Client (if different from product supplier)

Name:

.....

Address:

.....  
.....  
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....  
 .....  
 .....

## A.2.6 PICS contact person

(A person to contact if there are any queries concerning the content of the PICS)

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....  
 .....  
 .....

---

## A.3 Identification of the protocol

This PICS proforma applies to the following standard:

**EN 301 005-1 (V1.1):** "V interfaces at the digital Service Node (SN); Interfaces at the VB5.1 reference point for the support of broadband or combined narrowband and broadband Access Networks (ANs); Part 1: Interface specification".

---

## A.4 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No) .....

NOTE: Answering "No" to this question indicates non-conformance to the protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS proforma.

## A.5 Service node

In the tables below only those functions which have been specified as "mandatory" are required to be supported in order to ensure the proper operation of the VB5.1 interface. Functions marked as optional are not required by the VB5.1 interface itself but may be required by an AN or SN specification.

Subclauses shown in the "Reference" column of all following tables refer to EN 301 005-1 [1].

### A.5.1 Main features

#### A.5.1.1 General

**Table A.1: Main features**

Item	Feature	Reference (subclause)	Status	Support
1	RTMC function	11.1	m	

**Table A.2: Service types**

Item	Type	Reference (subclause)	Status	Support
1	B-ISDN services	7.1	o.201	
2	Non B-ISDN ATM based services	8.2	o.201	
3	narrowband services via V5.1	8.3.2.1	o.201	
4	narrowband services via V5.2	8.3.2.1	o.201	
5	narrowband services via V3	8.3.2.1	o.201	
6	other non ATM based services	8.3.3	o.201	

o.201: It is mandatory to support at least one of these items.

#### A.5.1.2 ATM layer characteristics

##### A.5.1.2.1 Broadband access network connection types

**Table A.3: B-AN connection types**

Item	Connection type	Reference (subclause)	Status	Support
1	Type A VP- ptp connections	7.5.1.1	o	
2	Type A VC- ptp connections	7.5.1.1	o	
3	Type A VP- ptm connections	7.5.1.2	o	
4	Type A VC- ptm connections	7.5.1.2	o	
5	Type B VP- ptp connections (note)	7.5.2	m	
6	Type B VC- ptp connections (note)	7.5.2	m	
7	Type D VP- ptp connections	7.6.1	o	
8	Type D VC- ptp connections	7.6.1	o	
9	Type D VP- ptm connections	7.6.2	o	
10	Type D VC- ptm connections	7.6.2	o	

NOTE: Mandatory because of RTMC channel.

## A.5.1.2.2 ATM transfer characteristics

**Table A.4: ATM transfer characteristics**

Item	Characteristics	Reference (subclause)	Status	Support
1	VP link interconnection function	9.7	c.401	
2	VC link interconnection function	9.7	c.402	
3	ATM transfer capabilities at the VP level (note 1)	5.1	m	
4	QoS classes at the VP level (note 2)	12.1	m	
5	Association of ATCs with QoS classes at the VP level (note 5)	5.1, 6.3, 12.1	m	
6	ATM transfer capabilities at the VC level (note 3)	5.1	m	
7	QoS classes at the VC level (note 4)	12.1	m	
8	Association of ATCs with QoS classes at the VC level (note 5)	5.1, 6.3, 12.1	m	

NOTE 1: The support of ATM transfer capabilities is specified in annex C, table C.1-1.  
NOTE 2: The support of QoS classes is specified in annex C, table C.2-1.  
NOTE 3: The support of ATM transfer capabilities is specified in annex C, table C.1-2.  
NOTE 4: The support of QoS classes is specified in annex C, table C.2-2.  
NOTE 5: The association of QoS classes with ATM transfer capabilities is specified in ITU-T Recommendation I.356.

c.401: IF A.3/1 OR A.3/3 OR A.3/7 OR A.3/9 THEN m ELSE n/a.

c.402: IF A.3/2 OR A.3/4 OR A.3/8 OR A.3/10 THEN m ELSE n/a.

## A.5.2 VB5.1 reference point

## A.5.2.1 Basic characteristics

**Table A.5: Basic characteristics of the VB5.1 interface**

Item	Characteristic	Reference (subclause)	Status	Support
1	one VB5.1 reference point via one TC function	6.2.2	o	
2	one VB5.1 reference point via multiple TC functions	6.2.2	o	
3	different VB5.1 reference points via common TC function(s)	6.2.2	o	

## A.5.2.1.1 Support of a physical interface

**Table A.6: Physical interface at the VB5.1 reference point**

Item	Characteristic	Reference (subclause)	Status	Support
1	physical interface(s) at the VB5.1 reference point	6.2.1	o	
2	a transmission path identification method	6.2.4.5	c.601	

c.601: IF A.6/1 THEN m ELSE n/a.



### A.5.2.1.2 Physical layer at the VB5.1 reference point

**Table A.7: Physical layer at the VB5.1 reference point**

Item	Physical layer options	Reference	Status	Support
1	PDH/Electrical (G.703)/E3	Annex F	c.701	
2	SDH/Electrical (G.703)/STM1	Annex F	c.701	
3	SDH/Optical (G.957 intra-office)/STM1	Annex F	c.701	
4	SDH/Optical (G.957 intra-office)/STM4	Annex F	c.701	
5	SDH/Optical (G.957 short haul)/STM1	Annex F	c.701	
6	SDH/Optical (G.957 short haul)/STM4	Annex F	c.701	
7	other (note)		c.701	

NOTE: Other physical layer options can be added if required.

c.701: IF A.6/1 THEN it is mandatory to support at least one of these items.

### A.5.2.2 ATM layer functions

**Table A.8: ATM layer at the VB5.1 reference point**

Item	ATM layer characteristics	Reference (subclause)	Status	Support
1	cell header format according to NNI specification	6.3.1	m	
2	provision of VPI and VCI values for the RTMC channel	6.3.1	m	
3	Selective cell discard at VPME level	9.9.2	o	
4	VP NPC	9.9.2	o	
5	VP traffic shaping	9.9.2	o	
6	VP resource management cells	9.9.2	o	
7	EFCI setting at VPE	9.9.2	o	
8	F4 OAM cells insertion/extraction at VPE level (note 1)	9.9.2	m	
9	F4 OAM non-intrusive monitoring at VPE level (note 1)	9.9.2	m	
10	F4 OAM cells insertion/extraction at VPCT level (note 1)	9.9.2	m	
11	Selective cell discard at VCME level	9.9.2	o	
12	VC UPC	9.9.2	c.801	
13	VC NPC	9.9.2	o	
14	VC traffic shaping	9.9.2	o	
15	VC resource management cells	9.9.2	o	
16	EFCI setting at VCE	9.9.2	o	
17	F5 OAM cells insertion/extraction at VCE level(note 2)	9.9.2	m	
18	F5 OAM non-intrusive monitoring at VCE level (note 2)	9.9.2	m	
19	F5 OAM cells insertion/extraction at VCCT level (note 2)	9.9.2	m	

NOTE 1: The status for the individual sub-functions is specified in annex B, table B.1-1.  
NOTE 2: The status for the individual sub-functions is specified in annex B, table B.1-2.

c.801: IF A.3/1 OR A.3/3 OR A.3/7 OR A.3/9 OR THEN m ELSE n/a.

### A.5.2.3 ATM adaptation layer

#### A.5.2.3.1 AAL for the RTMC protocol

**Table A.9: AAL functions for the RTMC protocol**

Item	Are the AAL functions for the RTMC protocol compliant with	Reference (subclause)	Status	Support
1	AAL5 specification	6.4.5.2	m	
2	SSCOP specification	6.4.5.3	m	
3	SSCF specification	6.4.5.4	m	

### A.5.2.3.2 AAL for circuit emulation of 2 048 kbit/s signals

**Table A.10: AAL functions for circuit emulation of 2 048 kbit/s signals**

Item	AAL type	Reference (subclause)	Status	Support
1	AAL1 for circuit emulation of 2 048 kbit/s signals	8.3.2.2	c.1001	

c.1001: IF A2/3 OR A2/4 OR A2/5 THEN m ELSE o.

### A.5.2.4 RTMC function and protocol

#### A.5.2.4.1 RTMC main features

**Table A.11: RTMC procedures**

Item	RTMC main features	Reference (subclause)	Status	Support
1	General error handling procedures	13.3.1.5	m	
2	Block and Unblock procedures	13.3.2.1	m	
3	Shutting down of resources	13.3.2.2	m	
4	VPCI consistency check procedures	13.3.3	o	
5	RTMC Start-up procedure	13.3.4.1	m	
6	Verify LSP ID procedure	13.3.4.2	m	
7	Reset complete LSP procedure	13.3.4.3	m	
8	Reset VPC procedure	13.3.4.4	o	
9	Compatibility instruction procedure	13.6.1.5.2	m	

#### A.5.2.4.2 RTMC messages

The tables in this subclause ask questions related to the supported RTMC messages in the service node role.

##### A.5.2.4.2.1 RTMC messages received by the Service Node

Indicating support for an item in table A.12 states that the implementation has the ability to recognize the messages listed in that item. Support for the receipt of a particular type of RTMC message means support for recognizing and acting upon all valid instances of that message type, including all valid message parameters, to the extent required by EN 301 005-1 [1].

**Table A.12: RTMC messages received by the Service node**

Item	message	Reference (subclause)	Status	Support
1	BLOCK_RSC	14.2.1.2.1	m	
2	AWAIT_CLEAR	14.2.1.2.3	m	
3	AWAIT_CLEAR_COMP_ACK	14.2.1.2.6	m	
4	UNBLOCK_RSC	14.2.1.2.7	m	
5	CONS_CHECK_REQ_ACK	14.2.1.3.2	c.1201	
6	CONS_CHECK_END_ACK	14.2.1.3.4	c.1201	
7	LSPID	14.2.1.4.1	m	
8	REQ_LSPID	14.2.1.4.2	m	
9	RESET_RSC	14.2.1.4.3	m	
10	RESET_RSC_ACK	14.2.1.4.4	m	
11	PROTOCOL_ERROR	14.2.1.4.5	m	

c.1201: IF A.11/4 THEN m ELSE n/a.

#### A.5.2.4.2.2 RTMC messages transmitted by the Service Node

Indicating support for an item in table A.13 states that the implementation has the ability to transmit the message listed in that item.

**Table A.13: RTMC messages transmitted by the Service Node**

Item	message	Reference (subclause)	Status	Support
1	BLOCK_RSC_ACK	14.2.1.2.2	m	
2	AWAIT_CLEAR_ACK	14.2.1.2.4	m	
3	AWAIT_CLEAR_COMP	14.2.1.2.5	m	
4	UNBLOCK_RSC_ACK	14.2.1.2.8	m	
5	CONS_CHECK_REQ	14.2.1.3.1	c.1301	
6	CONS_CHECK_END	14.2.1.3.3	c.1301	
7	LSPID	14.2.1.4.1	m	
8	REQ_LSPID	14.2.1.4.2	m	
9	RESET_RSC	14.2.1.4.3	m	
10	RESET_RSC_ACK	14.2.1.4.4	m	
11	PROTOCOL_ERROR	14.2.1.4.5	m	

c.1301: IF A.11/4 THEN m ELSE n/a.

#### A.5.2.4.3 Timers used in RTMC procedures

**Table A.14: Timers used in RTMC procedures**

Item	Timer	Reference	Status	Support	Value		Tolerance	
					default	supported	default	supported
1	T_start	Annex A	m		300 s		±10 %	
2	T_acl	Annex A	m		1 s		±10 %	
3	T_lspid	Annex A	m		1 s		±10 %	
4	T_reset	Annex A	m		60 s		±10 %	
5	T_consreq	Annex A	c.1401		10 s		±10 %	
6	T_consensd	Annex A	c.1401		10 s		±10 %	

c.1401: IF A.11/4 THEN m ELSE n/a.

#### A.5.2.4.4 RTMC function specific information elements

Table A.15 deals with the RTMC function specific information that may be transmitted or received in a RTMC message by the IUT in the service node role.

Indicating support for an item in table A.15 in this subclause states that the implementation has the ability:

- to process the information element when received in any of the RTMC messages for which the presence of this information element is specified;
- to generate and to transmit the information element in any of the RTMC messages for which the inclusion of this information element is specified.

Table A.15: RTMC Information elements

Item	Information elements	Reference (subclause)	Status	Support
1	Blocked resource identifier	14.2.2.2	m	
2	Protocol error cause	14.2.2.3	m	
3	Repeat indicator	14.2.2.4	m	
4	Result indicator	14.2.2.5	m	
5	Resource identifier	14.2.2.6	m	

## A.6 Access network

In the tables below only those functions which have been specified as "mandatory" are required to be supported in order to ensure the proper operation of the VB5.1 interface. Functions marked as optional are not required by the VB5.1 interface itself but may be required by an AN or SN specification.

Subclauses shown in the "Reference" column of all following tables refer to EN 301 005-1 [1].

### A.6.1 Main features

#### A.6.1.1 General

Table A.16: Main features

Item	Feature	Reference (subclause)	Status	Support
1	B-ISDN-Access types	7.1	o	
2	Narrowband access	7.6.3	o	
3	Non B-ISDN access, ATM-based	8.2	o	
4	Non B-ISDN access, non ATM-based	8.2	o	
5	RTMC function	11	m	
6	multiple VB5.1 reference points	10.2	o	

#### A.6.1.2 ATM layer characteristics

##### A.6.1.2.1 Broadband access network connection types

Table A.17: B-AN connection types

Item	Connection type	Reference (subclause)	Status	Support
1	Type A VP- ptp connections	7.5.1.1	o	
2	Type A VC- ptp connections	7.5.1.1	o	
3	Type A VP- ptm connections	7.5.1.2	o	
4	Type A VC- ptm connections	7.5.1.2	o	
5	Type B VP- ptp connections (note)	7.5.2	m	
6	Type B VC- ptp connections (note)	7.5.2	m	
7	Type D VP- ptp connections	7.6.1	o	
8	Type D VC- ptp connections	7.6.1	o	
9	Type D VP- ptm connections	7.6.2	o	
10	Type D VC- ptm connections	7.6.2	o	

NOTE: Mandatory because of RTMC.

## A.6.1.2.2 ATM transfer characteristics

**Table A.18: ATM transfer characteristics**

Item	Characteristics	Reference (subclause)	Status	Support
1	VP link interconnection function	9.7	c.1801	
2	VC link interconnection function	9.7	c.1802	
3	ATM transfer capabilities at the VP level (note 1)	5.1	m	
4	QoS classes at the VP level (note 2)	12.1	m	
5	Association of ATCs with QoS classes at the VP level (note 5)	5.1, 6.3, 12.1	m	
6	ATM transfer capabilities at the VC level (note 3)	5.1	m	
7	QoS classes at the VC level (note 4)	12.1	m	
8	Association of ATCs with QoS classes at the VC level (note 5)	5.1, 6.3, 12.1	m	
NOTE 1: The support of ATM transfer capabilities is specified in annex C, table C.1-1. NOTE 2: The support of QoS classes is specified in annex C, table C.2-1. NOTE 3: The support of ATM transfer capabilities is specified in annex C, table C.1-2. NOTE 4: The support of QoS classes is specified in annex C, table C.2-2. NOTE 5: The association of QoS classes with ATM transfer capabilities is specified in ITU-T Recommendation I.356.				

c.1801: IF A.17/1 OR A.17/3 OR A.17/7 OR A.17/9 THEN m ELSE n/a.

c.1802: IF A.17/2 OR A.17/4 OR A.17/8 OR A.17/10 THEN m ELSE n/a.

## A.6.2 Access types

## A.6.2.1 Support of ATM based access types

## A.6.2.1.1 Basic characteristics

**Table A.19: Basic characteristics of the UNI**

Item	Characteristic	Reference (subclause)	Status	Support
1	UNIs based on a single TC function	6.2.1	c.1901	
2	UNIs based on multiple TC functions	6.2.1	c.1902	
3	shared UNIs	6.2.1	c.1903	

c.1901: IF A.16/1 THEN m ELSE n/a.

c.1902: IF A.16/1 THEN o ELSE n/a.

c.1903: IF A.16/6 THEN o ELSE n/a.

## A.6.2.1.2 Physical layer

Table A.20: Physical layer of B-UNIs

Item	Physical layer	Reference (subclause)	Status	Support
1	E1 (2 048 kbit/s)	9.4	c.2001	
2	STM-1 (155,52 Mbit/s)	9.4	c.2001	
3	STM-4 (622,08 Mbit/s)	9.4	c.2001	
4	cell based (155,52 Mbit/s)	9.4	c.2001	
5	cell based (622,08 Mbit/s)	9.4	c.2001	
6	51,84 Mbit/s	1	c.2001	
7	25,6 Mbit/s	1	c.2001	
8	other (note)		c.2001	

NOTE: Other physical layer options can be added if required.

c.2001: IF A.16/1 THEN it is mandatory to support at least one of these items.

## A.6.2.1.3 ATM layer functions

Table A.21: ATM Layer of B-UNIs

Item	Function	Reference (subclause)	Status	Support
1	Generic flow control (GFC) (note 1)	9.4	c.2101	
2	Selective cell discard at VPME level	9.5.2	o	
3	VP UPC	9.5.2	c.2102	
4	VP traffic shaping	9.5.2	o	
5	VP resource management cells	9.5.2	c.2102	
6	EFCI setting at VPE level	9.5.2	o	
7	F4 OAM cells insertion/extraction at VPE level (note 2)	9.5.2	m	
8	F4 OAM non-intrusive monitoring at VPE level (note 2)	9.5.2	m	
9	F4 OAM cells insertion/extraction at a VPCT level (note 2)	9.5.2	c.2103	
10	Selective cell discard at VCME level	9.5.2	c.2104	
11	VC UPC	9.5.2	c.2103	
12	VC traffic shaping	9.5.2	c.2104	
13	VC resource management cells	9.5.2	c.2103	
14	EFCI setting at VCE level	9.5.2	o	
15	F5 OAM cells insertion/extraction at VCE level (note 3)	9.5.2	c.2104	
16	F5 OAM non-intrusive monitoring at VCE level (note 3)	9.5.2	c.2103	

NOTE 1: According to EN 301 005-1 only the "uncontrolled transmission" set of procedures shall be supported where the GFC is ignored.  
NOTE 2: The status for the individual sub-functions is specified in annex B, table B.2-1.  
NOTE 3: The status for the individual sub-functions is specified in annex B, table B.2-2.

c.2101: IF A.16/1 THEN m ELSE n/a.

c.2102: IF A.17/1 OR A.17/3 OR A.17/7 OR A.17/9 THEN m ELSE n/a.

c.2103: IF A.17/2 OR A.17/4 OR A.17/8 OR A.17/10 THEN m ELSE n/a.

c.2104: IF A.17/2 OR A.17/4 OR A.17/8 OR A.17/10 THEN o ELSE n/a.

## A.6.2.2 Support of non B-ISDN access types

### A.6.2.2.1 Narrowband access types

**Table A.22: Narrowband access types**

Item	Narrowband access type	Reference (subclause)	Status	Support
1	via V5.1 interface	8.3.2.1	c.2201	
2	via V5.2 interface	8.3.2.1	c.2201	
3	via V3 interface	8.3.2.1	c.2201	

c.2201: IF A.16 /2 THEN it is mandatory to support at least one of these items.

## A.6.3 VB5.1 reference point

### A.6.3.1 Basic characteristics

**Table A.23: Basic characteristics of the VB5.1 interface**

Item	Characteristic	Reference (subclause)	Status	Support
1	one VB5.1 reference point via one TC function	6.2.2	o	
2	one VB5.1 reference point via multiple TC functions	6.2.2	o	
3	different VB5.1 reference points via common TC function(s)	6.2.2	o	

#### A.6.3.1.1 Support of a physical interface

**Table A.24: Physical interface at the VB5.1 reference point**

Item	Characteristic	Reference (subclause)	Status	Support
1	physical interface(s) at the VB5.1 reference point	6.2.1	o	
2	a transmission path identification method	6.2.4.5	c.2401	

c.2401: IF A.24/1 THEN m ELSE n/a.

### A.6.3.2 Physical layer at the VB5.1 reference point

**Table A.25: Physical layer at the VB5.1 reference point**

Item	Physical layer options	Reference	Status	Support
1	PDH/Electrical (G.703)/E3	Annex F	c.2501	
2	SDH/Electrical (G.703)/STM1	Annex F	c.2501	
3	SDH/Optical (G.957 intra-office)/STM1	Annex F	c.2501	
4	SDH/Optical (G.957 intra-office)/STM4	Annex F	c.2501	
5	SDH/Optical (G.957 short haul)/STM1	Annex F	c.2501	
6	SDH/Optical (G.957 short haul)/STM4	Annex F	c.2501	
7	other		c.2501	

c.2501: IF A.24/1 THEN it is mandatory to support at least one of these items.

### A.6.3.3 ATM layer functions

**Table A.26: ATM layer at the VB5.1 reference point**

Item	ATM layer characteristics	Reference (subclause)	Status	Support
1	cell header format according to NNI specification	6.3.1	m	
2	provision of VPI and VCI values for the RTMC channel	6.3.1	m	
3	Selective cell discard at VPME level	9.9.2	o	
4	VP NPC	9.9.2	o	
5	VP traffic shaping	9.9.2	o	
6	VP resource management cells	9.9.2	o	
7	EFCI setting at VPE	9.9.2	o	
8	F4 OAM cells insertion/extraction at VPE level (note 1)	9.9.2	m	
9	F4 OAM non-intrusive monitoring at VPE level (note 1)	9.9.2	m	
10	F4 OAM cells insertion/extraction at VPCT level (note 1)	9.9.2	m	
11	Selective cell discard at VCME level	9.9.2	o	
12	VC NPC	9.9.2	o	
13	VC traffic shaping	9.9.2	o	
14	VC resource management cells	9.9.2	o	
15	EFCI setting at VCE	9.9.2	o	
16	F5 OAM cells insertion/extraction at VCE level(note 2)	9.9.2	m	
17	F5 OAM non-intrusive monitoring at VCE level (note 2)	9.9.2	m	
18	F5 OAM cells insertion/extraction at VCCT level (note 2)	9.9.2	m	

NOTE 1: The status for the individual sub-functions is specified in annex B, table B.3-1.  
NOTE 2: The status for the individual sub-functions is specified in annex B, table B.3-2.

### A.6.3.4 ATM adaptation layer

#### A.6.3.4.1 AAL for the RTMC protocol

**Table A.27: AAL functions for the RTMC protocol**

Item	Are the AAL functions for the RTMC protocol compliant with	Reference (subclause)	Status	Support
1	AAL5 specification	6.4.5.2	m	
2	SSCOP specification	6.4.5.3	m	
3	SSCF specification	6.4.5.4	m	

#### A.6.3.4.2 AAL for circuit emulation of 2 048 kbit/s signals

**Table A.28: AAL functions for circuit emulation of 2 048 kbit/s signals**

Item	AAL type	Reference (subclause)	Status	Support
1	AAL1 for circuit emulation of 2 048 kbit/s signals	8.3.2.2	c.2801	

c.2801: IF A.22/1 OR A.22/2 /OR A.22/3 THEN m ELSE o.



## A.6.3.5 RTMC function and protocol

### A.6.3.5.1 RTMC main features

**Table A.29: RTMC procedures**

Item	RTMC procedures	Reference (subclause)	Status	Support
1	General error handling procedures	13.3.1.5	m	
2	Block and Unblock procedures	13.3.2.1	m	
3	Shutting down of resources	13.3.2.2	m	
4	VPCI consistency check procedures	13.3.3	o	
5	Start-up procedure	13.3.4.1	m	
6	Verify LSP ID procedure	13.3.4.2	m	
7	Reset complete LSP procedure	13.3.4.3	m	
8	Reset VPC procedure	13.3.4.4	o	
9	Compatibility instruction procedure	13.6.1.5.2	m	

### A.6.3.5.2 RTMC messages

The tables in this subclause ask questions related to the supported RTMC messages in the Access network role.

#### A.6.3.5.2.1 RTMC messages received by the Access Network

Indicating support for an item in table A.30 states that the implementation has the ability to recognize the messages listed in that item. Support for the receipt of a particular type of RTMC message means support for recognizing and acting upon all valid instances of that message type, including all valid message parameters, to the extent required by EN 301 005-1 [1].

**Table A.30: RTMC messages received by the Access Network**

Item	message	Reference (subclause)	Status	Support
1	BLOCK_RSC_ACK	14.2.1.2.2	m	
2	AWAIT_CLEAR_ACK	14.2.1.2.4	m	
3	AWAIT_CLEAR_COMP	14.2.1.2.5	m	
4	UNBLOCK_RSC_ACK	14.2.1.2.8	m	
5	CONS_CHECK_REQ	14.2.1.3.1	c.3001	
6	CONS_CHECK_END	14.2.1.3.3	c.3001	
7	LSPID	14.2.1.4.1	m	
8	REQ_LSPID	14.2.1.4.2	m	
9	RESET_RSC	14.2.1.4.3	m	
10	RESET_RSC_ACK	14.2.1.4.4	m	
11	PROTOCOL_ERROR	14.2.1.4.5	m	

c.3001: IF A.29/4 THEN m ELSE n/a.

#### A.6.3.5.2.2 RTMC messages transmitted by the Access Network

Indicating support for an item in table A.31 states that the implementation has the ability to transmit the message listed in that item.

**Table A.31: RTMC messages transmitted by the Access Network**

Item	message	Reference (subclause)	Status	Support
1	BLOCK_RSC	14.2.1.2.1	m	
2	AWAIT_CLEAR	14.2.1.2.3	m	
3	AWAIT_CLEAR_COMP_ACK	14.2.1.2.6	m	
4	UNBLOCK_RSC	14.2.1.2.7	m	
5	CONS_CHECK_REQ_ACK	14.2.1.3.2	c.3101	
6	CONS_CHECK_END_ACK	14.2.1.3.4	c.3101	
7	LSPID	14.2.1.4.1	m	
8	REQ_LSPID	14.2.1.4.2	m	
9	RESET_RSC	14.2.1.4.3	m	
10	RESET_RSC_ACK	14.2.1.4.4	m	
11	PROTOCOL_ERROR	14.2.1.4.5	m	

c.3101: IF A.29/4 THEN m ELSE n/a.

#### A.6.3.5.3 Timers used in RTMC procedures

**Table A.32: Timers used in RTMC procedures**

Item	Timer	Reference	Status	Support	Value		Tolerance	
					default	supported	default	supported
1	T_start	Annex A	m		300 s		±10 %	
2	T_block	Annex A	m		1 s		±10 %	
3	T_unblock	Annex A	m		1 s		±10 %	
4	T_acl	Annex A	m		1 s		±10 %	
5	T_lspid	Annex A	m		1 s		±10 %	
6	T_reset	Annex A	m		60 s		±10 %	

#### A.6.3.5.4 RTMC function specific information elements

Table A.33 deals with the RTMC function specific information that may be transmitted or received in a RTMC message by the IUT in the access network role.

Indicating support for an item in table A.33 in this subclause states that the implementation has the ability:

- to process the information element when received in any of the RTMC messages for which the presence of this information element is specified;
- to generate and to transmit the information element in any of the RTMC messages for which the inclusion of this information element is specified.

**Table A.33: RTMC Information elements**

Item	Information elements	Reference (subclause)	Status	Support
1	Blocked resource identifier	14.2.2.2	m	
2	Protocol error cause	14.2.2.3	m	
3	Repeat indicator	14.2.2.4	m	
4	Result indicator	14.2.2.5	m	
5	Resource identifier	14.2.2.6	m	

---

## Annex B (informative): Status of OAM functions based F4/F5 flows

This annex provides information about the status of the individual sub-functions related to the application of OAM F4 and F5 flows.

The status of most of the F4/F5 OAM functions have been specified as "mandatory" within the relevant tables of the present document. However some of the individual sub-functions are considered as optional according to EN 301 005-1 [1] in conjunction with the ITU-T Recommendations I.610 and I.732. In the tables below only those sub-functions have been specified as "mandatory" which are required to be supported in order to ensure the proper operation of the VB5.1 interface. Functions marked as optional are not required by the VB5.1 interface itself but may be required by an AN or SN specification.

In tables B.1-1/2, B.2-1/2, B.3-1/2 item 2 "continuity check non intrusive monitoring" would be "mandatory" according to ETS 300 404, the ETSI version of I.610. However if the support of that capability is set to mandatory within the VB5 specification this would preclude the support of terminals which are not implemented according to the ETS 300 404.

## B.1 OAM functions at service port (SN-side)

**Table B.1-1: F4 OAM functions at service port (SN-side)**

Item	Function (note)	Status	
		VPE	VPCT
		Table A.8: items 8, 9	Table A.8: item 10
1	AIS/RDI non-intrusive monitoring	m	n/a
2	continuity check non-intrusive monitoring	o	n/a
3	performance monitoring non-intrusive monitoring	o	n/a
4	VP AIS insertion	m	n/a
5	VP RDI insertion	n/a	m
6	VP AIS/RDI extraction	n/a	m
7	end-to-end continuity check	n/a	o
8	segment continuity check	o	n/a
9	end-to-end performance monitoring	n/a	o
10	segment performance monitoring	o	n/a
11	end-to-end loopback at a source point	o	c.1-101
12	end-to-end loopback at a loopback point	n/a	o
13	segment loopback at a source point	o	n/a
14	segment loopback at a loopback point	o	n/a
15	end-to-end activation/deactivation	n/a	o
16	segment activation/deactivation	o	n/a

NOTE: Detailed description of the individual function listed in items 1 to 16 of this table is provided in ITU-T Recommendation I.732 clause 5.

c.1-101: IF A.11/5 THEN m ELSE o.

**Table B.1-2: F5 OAM functions at service port (SN-side)**

Item	Function (note)	Status	
		VCE	VCCT
		Table A.8: items 17,18	Table A.8: item 19
1	AIS/RDI non-intrusive monitoring	m	n/a
2	continuity check non-intrusive monitoring	o	n/a
3	performance monitoring non-intrusive monitoring	o	n/a
4	VC AIS insertion	m	n/a
5	VC RDI insertion	n/a	m
6	VC AIS/RDI extraction	n/a	m
7	end-to-end continuity check	n/a	o
8	segment continuity check	o	n/a
9	end-to-end performance monitoring	n/a	o
10	segment performance monitoring	o	n/a
11	end-to-end loopback at a source point	o	o
12	end-to-end loopback at a loopback point	n/a	o
13	segment loopback at a source point	o	n/a
14	segment loopback at a loopback point	o	n/a
15	end-to-end activation/deactivation	n/a	o
16	segment activation/deactivation	o	n/a

NOTE: Detailed description of the individual function listed in items 1 to 16 of this table is provided in ITU-T Recommendation I.732 clause 5.

## B.2 OAM functions at user port

**Table B.2-1: F4 OAM functions at user port**

Item	Function (note)	Status	
		VPE	VPCT
		Table A.21: items 7, 8	Table A.21: item 9
1	AIS/RDI non-intrusive monitoring	m	n/a
2	continuity check non-intrusive monitoring	o	n/a
3	performance monitoring non-intrusive monitoring	o	n/a
4	VP AIS insertion	m	n/a
5	VP RDI insertion	n/a	m
6	VP AIS/RDI extraction	n/a	m
7	end-to-end continuity check	n/a	o
8	segment continuity check	o	n/a
9	end-to-end performance monitoring	n/a	o
10	segment performance monitoring	o	n/a
11	end-to-end loopback at a source point	o	o
12	end-to-end loopback at a loopback point	n/a	o
13	segment loopback at a source point	o	n/a
14	segment loopback at a loopback point	o	n/a
15	end-to-end activation/deactivation	n/a	o
16	segment activation/deactivation	o	n/a

NOTE: Detailed description of the individual function listed in items 1 to 16 of this table is provided in ITU-T Recommendation I.732 clause 5.

**Table B.2-2: F5 OAM functions at user port**

Item	Function (note)	Status
		VCE
		Table A.21: items 15, 16
1	AIS/RDI non-intrusive monitoring	m
2	continuity check non-intrusive monitoring	m
3	performance monitoring non-intrusive monitoring	o
4	VC AIS insertion	m
5	VC RDI insertion	n/a
6	VC AIS/RDI extraction	n/a
7	end-to-end continuity check	n/a
8	segment continuity check	o
9	end-to-end performance monitoring	n/a
10	segment performance monitoring	o
11	end-to-end loopback at a source point	o
12	end-to-end loopback at a loopback point	n/a
13	segment loopback at a source point	o
14	segment loopback at a loopback point	o
15	end-to-end activation/deactivation	n/a
16	segment activation/deactivation	o

NOTE: Detailed description of the individual function listed in items 1 to 16 of this table is provided in ITU-T Recommendation I.732 clause 5.

## B.3 OAM functions at service port (AN-side)

**Table B.3-1: F4 OAM functions at service port (AN-side)**

Item	Function (note)	Status	
		VPE	VPCT
		Table A.26: items 8, 9	Table A.26: item 10
1	AIS/RDI non-intrusive monitoring	m	n/a
2	continuity check non-intrusive monitoring	o	n/a
3	performance monitoring non-intrusive monitoring	o	n/a
4	VP AIS insertion	m	n/a
5	VP RDI insertion	n/a	m
6	VP AIS/RDI extraction	n/a	m
7	end-to-end continuity check	n/a	o
8	segment continuity check	o	n/a
9	end-to-end performance monitoring	n/a	o
10	segment performance monitoring	o	n/a
11	end-to-end loopback at a source point	o	c.3-101
12	end-to-end loopback at a loopback point	n/a	o
13	segment loopback at a source point	o	n/a
14	segment loopback at a loopback point	o	n/a
15	end-to-end activation/deactivation	n/a	o
16	segment activation/deactivation	o	n/a
NOTE: Detailed description of the individual function listed in items 1 to 16 of this table is provided in ITU-T Recommendation I.732 clause 5.			

c.3-101: IF A.11/5 THEN m ELSE o.

**Table B.3-2: F5 OAM functions at service port (AN-side)**

Item	Function (note)	Status	
		VCE	VCCT
		Table A.26: items 16, 17	Table A.26: item 18
1	AIS/RDI non-intrusive monitoring	m	n/a
2	continuity check non-intrusive monitoring	o	n/a
3	performance monitoring non-intrusive monitoring	o	n/a
4	VC AIS insertion	m	n/a
5	VC RDI insertion	n/a	m
6	VC AIS/RDI extraction	n/a	m
7	end-to-end continuity check	n/a	o
8	segment continuity check	o	n/a
9	end-to-end performance monitoring	n/a	o
10	segment performance monitoring	o	n/a
11	end-to-end loopback at a source point	o	o
12	end-to-end loopback at a loopback point	n/a	o
13	segment loopback at a source point	o	n/a
14	segment loopback at a loopback point	o	n/a
15	end-to-end activation/deactivation	n/a	o
16	segment activation/deactivation	o	n/a
NOTE: Detailed description of the individual function listed in items 1 to 16 of this table is provided in ITU-T Recommendation I.732 clause 5.			

## Annex C (informative): Support of ATM transfer capabilities and QoS classes

This annex provides information about the support of I.371 ATM transfer capabilities and I.356 QoS classes at the VP sublayer and VC sublayer.

### C.1 ATM transfer capabilities

**Table C.1-1: ATM transfer capabilities at the VP sublayer**

Item	ATC at the VP sublayer (note 1)	Reference (subclause)	Status
1	DBR	5.1	o
2	SBR1	5.1	o
3	SBR2	5.1	o
4	SBR3	5.1	o
5	ABR	5.1	o
6	ABT-DT	5.1	o
7	ABT-IT	5.1	o
8	others (note 2)		o
NOTE 1: Detailed description of the individual ATC listed in items 1 to 7 of this table is provided in ITU-T Recommendation I.371.			
NOTE 2: This item may cover ATC as defined at ATM Forum traffic management specification (af-tm-0056.000).			

**Table C.1-2: ATM transfer capabilities at the VC sublayer**

Item	ATC at the VC sublayer (note 1)	Reference (subclause)	Status
1	DBR	5.1	o
2	SBR1	5.1	o
3	SBR2	5.1	o
4	SBR3	5.1	o
5	ABR	5.1	o
6	ABT-DT	5.1	o
7	ABT-IT	5.1	o
8	others (note 2)		o
NOTE 1: Detailed description of the individual ATC listed in items 1 to 7 of this table is provided in ITU-T Recommendation I.371.			
NOTE 2: This item may cover ATC as defined at ATM Forum traffic management specification (af-tm-0056.000).			

## C.2 QoS classes

**Table C.2-1: QoS classes at the VP sublayer**

Item	QoS classes at the VP sublayer (note 1)	Reference (subclause)	Status
1	Class 1	12.1	o
2	Class 2	12.1	o
3	Class 3	12.1	o
4	U Class	12.1	o
5	others (note 2)		o
NOTE 1: Detailed description of the individual QoS Class listed in items 1 to 4 of this table is provided in ITU-T Recommendation I.356.			
NOTE 2: This item may cover QoS classes as defined at ATM Forum traffic management specification.			

**Table C.2-2: QoS classes at the VC sublayer**

Item	Connection type (note 1)	Reference (subclause)	Status
1	Class 1	12.1	o
2	Class 2	12.1	o
3	Class 3	12.1	o
4	U Class	12.1	o
5	others (note 2)		o
NOTE 1: Detailed description of the individual QoS class listed in items 1 to 4 of this table is provided in ITU-T Recommendation I.356.			
NOTE 2: This item may cover QoS classes as defined at ATM Forum traffic management specification.			



## History

<b>Document history</b>				
V1.1.1	November 1997	Public Enquiry	PE 9813:	1997-11-28 to 1998-03-27
V1.1.4	July 1998	Vote	V 9837:	1998-07-14 to 1998-09-11
V1.1.5	September 1998	Publication		