

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
VHF radiotelephone equipment for general communications
and associated equipment for Class "D"
Digital Selective Calling (DSC);
Part 2: Harmonized EN under article 3.2
of the R&TTE Directive**



Reference

REN/ERM-TG26-074-2

Keywords

maritime, radio, regulation, traffic, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chairecor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2006.
All rights reserved.

DECTTM, **PLUGTESTSTM** and **UMTSTM** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations	8
4 Technical requirements specifications	8
4.1 Environmental profile.....	8
4.2 Conformance requirements	9
4.2.1 Transmitter frequency error	9
4.2.1.1 Definition	9
4.2.1.2 Limits	9
4.2.1.3 Conformance.....	9
4.2.2 Transmitter adjacent channel power	9
4.2.2.1 Definition	9
4.2.2.2 Limits	9
4.2.2.3 Conformance.....	9
4.2.3 Transmitter conducted spurious emissions conveyed to the antenna.....	9
4.2.3.1 Definition	9
4.2.3.2 Limit.....	9
4.2.3.3 Conformance.....	9
4.2.4 Transmitter cabinet radiation and conducted spurious emissions other than those conveyed to the antenna.....	9
4.2.4.1 Definitions.....	9
4.2.4.2 Limits	10
4.2.4.3 Conformance.....	10
4.2.5 Transient frequency behaviour of the transmitter	10
4.2.5.1 Definitions.....	10
4.2.5.2 Limits	10
4.2.5.3 Conformance.....	10
4.2.6 Transmitter carrier power	10
4.2.6.1 Definition	10
4.2.6.2 Limit.....	10
4.2.6.3 Conformance.....	10
4.2.7 Transmitter frequency deviation	10
4.2.7.1 Definition	10
4.2.7.2 Limit.....	10
4.2.7.3 Conformance.....	10
4.2.8 DSC frequency error (demodulated DSC signal).....	10
4.2.8.1 Definition	10
4.2.8.2 Limit.....	11
4.2.8.3 Conformance.....	11
4.2.9 DSC modulation index.....	11
4.2.9.1 Definition	11
4.2.9.2 Limit.....	11
4.2.9.3 Conformance.....	11
4.2.10 DSC modulation rate	11
4.2.10.1 Definition	11
4.2.10.2 Limit.....	11
4.2.10.3 Conformance.....	11
4.2.11 Receiver maximum usable sensitivity	11
4.2.11.1 Definition	11
4.2.11.2 Limits	11

4.2.11.3	Conformance	11
4.2.12	Receiver co-channel rejection	11
4.2.12.1	Definition	11
4.2.12.2	Limit	12
4.2.12.3	Conformance	12
4.2.13	Receiver adjacent channel selectivity	12
4.2.13.1	Definition	12
4.2.13.2	Limits	12
4.2.13.3	Conformance	12
4.2.14	Receiver spurious response rejection	12
4.2.14.1	Definition	12
4.2.14.2	Limit	12
4.2.14.3	Conformance	12
4.2.15	Receiver intermodulation response	12
4.2.15.1	Definition	12
4.2.15.2	Limit	12
4.2.15.3	Conformance	12
4.2.16	Receiver blocking or desensitization	13
4.2.16.1	Definition	13
4.2.16.2	Limit	13
4.2.16.3	Conformance	13
4.2.17	Receiver spurious emissions at the antenna	13
4.2.17.1	Definition	13
4.2.17.2	Limit	13
4.2.17.3	Conformance	13
4.2.18	Receiver cabinet radiated spurious emissions	13
4.2.18.1	Definition	13
4.2.18.2	Limit	13
4.2.18.3	Conformance	13
4.2.19	DSC receiver maximum usable sensitivity	13
4.2.19.1	Definition	13
4.2.19.2	Limits	13
4.2.19.3	Conformance	14
4.2.20	DSC receiver co-channel rejection	14
4.2.20.1	Definition	14
4.2.20.2	Limits	14
4.2.20.3	Conformance	14
4.2.21	DSC receiver spurious response and blocking immunity	14
4.2.21.1	Definition	14
4.2.21.2	Limits	14
4.2.21.3	Conformance	14
5	Testing for compliance with technical requirements	14
5.1	Test conditions, power supply and ambient temperatures	14
5.2	Interpretation of the measurement results	14
5.3	Essential radio test suites	15
5.3.1	Transmitter frequency error	15
5.3.2	Transmitter adjacent channel power	15
5.3.3	Transmitter conducted spurious emissions conveyed to the antenna	15
5.3.4	Transmitter cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	15
5.3.5	Transient behaviour of the transmitter	15
5.3.6	Transmitter carrier power	15
5.3.7	Transmitter frequency deviation	16
5.3.8	DSC frequency error (demodulated DSC signal)	16
5.3.9	DSC modulation index	16
5.3.10	DSC modulation rate	16
5.4	Other test suites	16
5.4.1	General	16
5.4.2	Receiver maximum usable sensitivity	16
5.4.3	Receiver co-channel rejection	16
5.4.4	Receiver adjacent channel selectivity	16

5.4.5	Receiver spurious response rejection.....	16
5.4.6	Receiver intermodulation response.....	16
5.4.7	Receiver blocking or desensitization	17
5.4.8	Receiver spurious emissions at the antenna.....	17
5.4.9	Receiver cabinet radiated spurious emissions.....	17
5.4.10	DSC receiver maximum usable sensitivity	17
5.4.11	DSC receiver co-channel rejection	17
5.4.12	DSC receiver spurious response and blocking immunity	17
Annex A (normative):	HS Requirement and conformance Test specifications Table (HS-RTT).....	18
Annex B (informative):	The EN title in the official languages	22
History		23

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 2 of a multi-part deliverable covering the Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF radiotelephone equipment for general communications and associated equipment for Class "D" Digital Selective Calling (DSC), as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN under article 3.2 of the R&TTE Directive".

Part 3: "Harmonized EN under article 3.3 (e) of the R&TTE Directive".

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [6] laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

1 Scope

The present document covers the minimum requirements for general communication for shipborne fixed installations using a VHF radiotelephone operating in certain frequency bands allocated to the maritime mobile service using both 25 kHz and 12,5 kHz channels with associated equipment for DSC - class D.

The present document is intended to cover the provisions of Directive 1999/5/EC [1] (R&TTE Directive) Article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of Article 3 of the R&TTE Directive [1] may apply to equipment within the scope of the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- | | |
|-----|---|
| [1] | Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive). |
| [2] | Council Directive 89/336/EEC of 3 May 1989 on the approximation of the laws of the Member States relating to electromagnetic compatibility (EMC Directive). |
| [3] | Council Directive 73/23/EEC of 19 February 1973 on the harmonization of the laws of Member States relating to electrical equipment designed for use within certain voltage limits (73/23/EEC) (LV Directive). |
| [4] | ETSI EN 301 025-1 (V1.3.1): "ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); VHF radiotelephone equipment for general communications and associated equipment for Class "D" Digital Selective Calling (DSC) with the use of 12,5 kHz channels; Part 1: Technical characteristics and methods of measurement". |
| [5] | ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics". |
| [6] | Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations. |
| [7] | EC decision 2004/71/EC of 4 September 2003 on essential requirements relating to marine radio communication equipment which is intended to be used on non-SOLAS vessels and to participate in the Global Maritime Distress and Safety System (GMDSS). |

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [1] and the following apply:

carrier frequency: frequency to which the transmitter or receiver is tuned

class D: class D equipment is intended to provide minimum facilities for VHF DSC distress, urgency and safety as well as routine calling and reception, not necessarily in full accordance with IMO GMDSS carriage requirements for VHF installations

environmental profile: range of environmental conditions under which equipment within the scope of EN 301 025-2 is required to comply with the provisions of EN 301 025-2

frequency deviation: difference between the instantaneous frequency of the modulated RF signal and the carrier frequency

G2B: phase-modulation with digital information, with a sub-carrier for DSC operation

G3E: phase-modulation (frequency modulation with a pre-emphasis of 6 dB/octave) for speech

modulation index: ratio between the frequency deviation and the frequency of the modulation signal

supplier: entity referred to in the R&TTE Directive [1] responsible for the placing on the market of an equipment within the scope of the Directive

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

DSC	Digital Selective Calling
EMC	Electro-Magnetic Compatibility
IMO	International Maritime Organization
LV	Low Voltage
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
VHF	Very High Frequency
SINAD	Signal, Noise And Distortion

4 Technical requirements specifications

4.1 Environmental profile

Tests defined in the present document shall be carried out at representative points within the boundary limits of the declared operational environmental profile which, as a minimum, shall be that specified in the test conditions contained in the present document.

As technical performance varies subject to environmental conditions, tests shall be carried out under a sufficient variety of environmental conditions as specified in the present document to give confidence of compliance for the affected technical requirements. These environmental conditions represent those required by Article 2 of EC decision 2004/71/EC [7] (which shall also be within the boundary limits of the declared operational environmental profile).

4.2 Conformance requirements

4.2.1 Transmitter frequency error

4.2.1.1 Definition

The frequency error is defined in EN 301 025-1 [4], clause 8.1.1.

4.2.1.2 Limits

The transmitter frequency error limit shall be as stated in EN 301 025-1 [4], clause 8.1.3.

4.2.1.3 Conformance

Conformance tests as defined in clause 5.3.1 shall be carried out.

4.2.2 Transmitter adjacent channel power

4.2.2.1 Definition

The adjacent channel power is defined in EN 301 025-1 [4], clause 8.7.1.

4.2.2.2 Limits

The transmitter adjacent channel power limit shall be as stated in EN 301 025-1 [4], clause 8.7.3.

4.2.2.3 Conformance

Conformance tests as defined in clause 5.3.2 shall be carried out.

4.2.3 Transmitter conducted spurious emissions conveyed to the antenna

4.2.3.1 Definition

Conducted spurious emissions conveyed to the antenna are defined in EN 301 025-1 [4], clause 8.8.1.

4.2.3.2 Limit

The transmitter conducted spurious emissions conveyed to the antenna limit shall be as stated in EN 301 025-1 [4], clause 8.8.3.

4.2.3.3 Conformance

Conformance tests as defined in clause 5.3.3 shall be carried out.

4.2.4 Transmitter cabinet radiation and conducted spurious emissions other than those conveyed to the antenna

4.2.4.1 Definitions

Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna are defined in EN 301 025-1 [4], clause 8.9.1.

4.2.4.2 Limits

The transmitter cabinet radiation and conducted spurious emissions other than those conveyed to the antenna limit shall be as stated in EN 301 025-1 [4], clause 8.9.3.

4.2.4.3 Conformance

Conformance tests as defined in clause 5.3.4 shall be carried out.

4.2.5 Transient frequency behaviour of the transmitter

4.2.5.1 Definitions

The transient frequency behaviour of the transmitter is defined in EN 301 025-1 [4], clause 8.10.1.

4.2.5.2 Limits

The transient frequency behaviour of the transmitter limit shall be as stated in EN 301 025-1 [4], clause 8.10.3.

4.2.5.3 Conformance

Conformance tests as defined in clause 5.3.5 shall be carried out.

4.2.6 Transmitter carrier power

4.2.6.1 Definition

The transmitter carrier power is defined in EN 301 025-1 [4], clause 8.2.1.

4.2.6.2 Limit

The transmitter carrier power limit shall be as stated in EN 301 025-1 [4], clause 8.2.3.

4.2.6.3 Conformance

Conformance tests as defined in clause 5.3.6 shall be carried out.

4.2.7 Transmitter frequency deviation

4.2.7.1 Definition

The transmitter frequency deviation is defined in EN 301 025-1 [4], clause 8.3.1.

4.2.7.2 Limit

The transmitter frequency deviation limit shall be as stated in EN 301 025-1 [4], clause 8.3.3.

4.2.7.3 Conformance

Conformance tests as defined in clause 5.3.7 shall be carried out.

4.2.8 DSC frequency error (demodulated DSC signal)

4.2.8.1 Definition

The DSC frequency error is defined in EN 301 025-1 [4], clause 8.12.1.

4.2.8.2 Limit

The DSC frequency error limit shall be as stated in EN 301 025-1 [4], clause 8.12.3.

4.2.8.3 Conformance

Conformance tests as defined in clause 5.3.8 shall be carried out.

4.2.9 DSC modulation index

4.2.9.1 Definition

The DSC modulation index is defined in EN 301 025-1 [4], clause 8.13.1.

4.2.9.2 Limit

The DSC modulation index limit shall be as stated in EN 301 025-1 [4], clause 8.13.3.

4.2.9.3 Conformance

Conformance tests as defined in clause 5.3.9 shall be carried out.

4.2.10 DSC modulation rate

4.2.10.1 Definition

The DSC modulation rate is defined in EN 301 025-1 [4], clause 8.14.1.

4.2.10.2 Limit

The DSC modulation rate limit shall be as stated in EN 301 025-1 [4], clause 8.14.3.

4.2.10.3 Conformance

Conformance tests as defined in clause 5.3.10 shall be carried out.

4.2.11 Receiver maximum usable sensitivity

4.2.11.1 Definition

The receiver maximum usable sensitivity of the receiver is defined in EN 301 025-1 [4], clause 9.3.1.

4.2.11.2 Limits

The receiver maximum usable sensitivity limit shall be as stated in EN 301 025-1 [4], clause 9.3.3.

4.2.11.3 Conformance

Conformance tests as defined in clause 5.4.2 may be carried out.

4.2.12 Receiver co-channel rejection

4.2.12.1 Definition

The receiver co-channel rejection is defined in EN 301 025-1 [4], clause 9.4.1.

4.2.12.2 Limit

The receiver co-channel rejection limit shall be as stated in EN 301 025-1 [4], clause 9.4.3.

4.2.12.3 Conformance

Conformance tests as defined in clause 5.4.3 may be carried out.

4.2.13 Receiver adjacent channel selectivity

4.2.13.1 Definition

The adjacent channel selectivity is in EN 301 025-1 [4], clause 9.5.1 for the receiver and in EN 301 025-1 [4], clause 10.3.1 for the DSC receiver.

4.2.13.2 Limits

The adjacent channel selectivity limit shall be as stated in EN 301 025-1 [4], clause 9.5.3 for the receiver and in EN 301 025-1 [4], clause 10.3.3 for the DSC receiver.

4.2.13.3 Conformance

Conformance tests as defined in clause 5.4.4 may be carried out.

4.2.14 Receiver spurious response rejection

4.2.14.1 Definition

The spurious response rejection is defined in EN 301 025-1 [4], clause 9.6.1.

4.2.14.2 Limit

The receiver spurious response rejection limit shall be as stated in EN 301 025-1 [4], clause 9.6.3.

4.2.14.3 Conformance

Conformance tests as defined in clause 5.4.5 may be carried out.

4.2.15 Receiver intermodulation response

4.2.15.1 Definition

The intermodulation response is defined in EN 301 025-1 [4], clause 9.7.1 for the receiver and in EN 301 025-1 [4], clause 10.5.3 for the DSC receiver.

4.2.15.2 Limit

The intermodulation response limit shall be as stated in EN 301 025-1 [4], clause 9.7.3 for the receiver and in EN 301 025-1 [4], clause 10.5.1 for the DSC receiver.

4.2.15.3 Conformance

Conformance tests as defined in clause 5.4.6 may be carried out.

4.2.16 Receiver blocking or desensitization

4.2.16.1 Definition

Blocking is defined in EN 301 025-1 [4], clause 9.8.1.

4.2.16.2 Limit

The receiver blocking or desensitization limit shall be as stated in EN 301 025-1 [4], clause 9.8.3.

4.2.16.3 Conformance

Conformance tests as defined in clause 5.4.7 may be carried out.

4.2.17 Receiver spurious emissions at the antenna

4.2.17.1 Definition

Spurious emissions are defined in EN 301 025-1 [4], clause 9.9.1 for the receiver and in EN 301 025-1 [4], clause 10.7.1 for the DSC receiver.

4.2.17.2 Limit

The spurious emissions at the antenna limit shall be as stated in EN 301 025-1 [4], clause 9.9.3 for the receiver and in EN 301 025-1 [4], clause 10.7.3 for the DSC receiver.

4.2.17.3 Conformance

Conformance tests as defined in clause 5.4.8 may be carried out.

4.2.18 Receiver cabinet radiated spurious emissions

4.2.18.1 Definition

The cabinet radiated spurious emissions are defined in EN 301 025-1 [4], clause 9.10.1 for the receiver and in EN 301 025-1 [4], clause 10.8.1 for the DSC receiver.

4.2.18.2 Limit

The cabinet radiated spurious emissions limit shall be as stated in EN 301 025-1 [4], clause 9.10.3 for the receiver and in EN 301 025-1 [4], clause 10.8.3 for the DSC receiver.

4.2.18.3 Conformance

Conformance tests as defined in clause 5.4.9 may be carried out.

4.2.19 DSC receiver maximum usable sensitivity

4.2.19.1 Definition

The maximum usable sensitivity of the DSC receiver is defined in EN 301 025-1 [4], clause 10.1.1.

4.2.19.2 Limits

The DSC receiver maximum usable sensitivity limit shall be as stated in EN 301 025-1 [4], clause 10.1.3.

4.2.19.3 Conformance

Conformance tests as defined in clause 5.4.10 may be carried out.

4.2.20 DSC receiver co-channel rejection

4.2.20.1 Definition

The co-channel rejection of the DSC receiver is defined in EN 301 025-1 [4], clause 10.2.1.

4.2.20.2 Limits

The DSC receiver co-channel rejection limit shall be as stated in EN 301 025-1 [4], clause 10.2.3.

4.2.20.3 Conformance

Conformance tests as defined in clause 5.4.11 may be carried out.

4.2.21 DSC receiver spurious response and blocking immunity

4.2.21.1 Definition

The spurious response and blocking immunity of the DSC receiver is defined in EN 301 025-1 [4], clause 10.4.1.

4.2.21.2 Limits

The DSC receiver spurious response and blocking immunity limit shall be as stated in EN 301 025-1 [4], clause 10.4.3.

4.2.21.3 Conformance

Conformance tests as defined in clause 5.4.12 may be carried out.

5 Testing for compliance with technical requirements

5.1 Test conditions, power supply and ambient temperatures

These shall be as described in EN 301 025-1 [4], clauses 6.1 to 6.9 and 6.11 to 6.14.

5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the recorded value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 1.

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028 [5] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 1 is based on such expansion factors.

Table 1: Maximum values of absolute measurement uncertainties

Parameter	Maximum uncertainty
Radio Frequency (RF)	$\pm 1 \times 10^{-7}$
RF power/level	$\pm 0,75$ dB
Maximum frequency deviation: - within 300 Hz to 6 kHz of modulation frequency - within 6 kHz to 25 kHz of modulation frequency	± 5 % ± 3 dB
Deviation limitation	± 5 %
Adjacent channel power	± 5 dB
Conducted spurious emission of transmitter	± 4 dB
Sensitivity at 20 dB SINAD	± 3 dB
Conducted emission of receiver	± 3 dB
Two-signal measurement	± 4 dB
Three-signal measurement	± 3 dB
Transmitter transient time	± 20 %
Transmitter transient frequency	± 250 Hz

5.3 Essential radio test suites

5.3.1 Transmitter frequency error

The test method specified in EN 301 025-1 [4], clause 8.1.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.1.2 in order to prove compliance with the requirement.

5.3.2 Transmitter adjacent channel power

The test method specified in EN 301 025-1 [4], clause 8.7.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.2.2 in order to prove compliance with the requirement.

5.3.3 Transmitter conducted spurious emissions conveyed to the antenna

The test method specified in EN 301 025-1 [4], clause 8.8.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.3.2 in order to prove compliance with the requirement.

5.3.4 Transmitter cabinet radiation and conducted spurious emissions other than those conveyed to the antenna

The test method specified in EN 301 025-1 [4], clause 8.9.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.4.2 in order to prove compliance with the requirement.

5.3.5 Transient behaviour of the transmitter

The test method specified in EN 301 025-1 [4], clause 8.10.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.5.2 in order to prove compliance with the requirement.

5.3.6 Transmitter carrier power

The test method specified in EN 301 025-1 [4], clause 8.2.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.6.2 in order to prove compliance with the requirement.

5.3.7 Transmitter frequency deviation

The test method specified in EN 301 025-1 [4], clause 8.3.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.7.2 in order to prove compliance with the requirement.

5.3.8 DSC frequency error (demodulated DSC signal)

The test method specified in EN 301 025-1 [4], clause 8.12.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.8.2 in order to prove compliance with the requirement.

5.3.9 DSC modulation index

The test method specified in EN 301 025-1 [4], clause 8.13.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.9.2 in order to prove compliance with the requirement.

5.3.10 DSC modulation rate

The test method specified in EN 301 025-1 [4], clause 8.14.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.10.2 in order to prove compliance with the requirement.

5.4 Other test suites

5.4.1 General

The requirements in clauses 4.2.11 to 4.2.21 inclusive have been set on the assumption that the test specifications in clauses 5.4.2 to 5.4.12 will be used to verify the performance of the equipment.

5.4.2 Receiver maximum usable sensitivity

The test method specified in EN 301 025-1 [4], clause 9.3.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.11.2 in order to prove compliance with the requirement.

5.4.3 Receiver co-channel rejection

The test method specified in EN 301 025-1 [4], clause 9.4.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.12.2 in order to prove compliance with the requirement.

5.4.4 Receiver adjacent channel selectivity

The test methods specified in EN 301 025-1 [4], clause 9.5.2 and 10.3.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.13.2 in order to prove compliance with the requirement.

5.4.5 Receiver spurious response rejection

The test method specified in EN 301 025-1 [4], clause 9.6.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.14.2 in order to prove compliance with the requirement.

5.4.6 Receiver intermodulation response

The test methods specified in EN 301 025-1 [4], clause 9.7.2 and 10.5.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.15.2 in order to prove compliance with the requirement.

5.4.7 Receiver blocking or desensitization

The test method specified in EN 301 025-1 [4], clause 9.8.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.16.2 in order to prove compliance with the requirement.

5.4.8 Receiver spurious emissions at the antenna

The test methods specified in EN 301 025-1 [4], clause 9.9.2 and 10.7.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.17.2 in order to prove compliance with the requirement.

5.4.9 Receiver cabinet radiated spurious emissions

The test methods specified in EN 301 025-1 [4], clause 9.10.2 and 10.8.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.18.2 in order to prove compliance with the requirement.

5.4.10 DSC receiver maximum usable sensitivity

The test method specified in EN 301 025-1 [4], clause 10.1.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.19.2 in order to prove compliance with the requirement.

5.4.11 DSC receiver co-channel rejection

The test method specified in EN 301 025-1 [4], clause 10.2.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.20.2 in order to prove compliance with the requirement.

5.4.12 DSC receiver spurious response and blocking immunity

The test method specified in EN 301 025-1 [4], clause 10.4.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.2.21.2 in order to prove compliance with the requirement.

Annex A (normative): HS Requirement and conformance Test specifications Table (HS-RTT)

The HS Requirements and conformance Test specifications Table (HS-RTT) in table A.1 serves a number of purposes, as follows:

- it provides a statement of all the essential requirements in words and by cross reference to a specific clause in the present document or to a specific clause in a specific referenced document;
- it provides a statement of all the test procedures corresponding to those essential requirements by cross reference to specific clause(s) in the present document or to a specific clause(s) in specific referenced document(s);
- it qualifies each requirement to be either:
 - Unconditional: meaning that the requirement applies in all circumstances, or
 - Conditional: meaning that the requirement is dependent on the manufacturer having chosen to support optional functionality defined within the schedule.
- in the case of Conditional requirements, it associates the requirement with the particular optional service or functionality;
- it qualifies each test procedure to be either:
 - Essential: meaning that it is included with the Essential Radio Test Suite and therefore the requirement shall be demonstrated to be met in accordance with the referenced procedures;
 - Other: meaning that the test procedure is illustrative but other means of demonstrating compliance with the requirement are permitted.

Table A.1: HS Requirements and conformance Test specifications Table (HS-RTT)

Harmonized Standard EN 301 025-2 The following technical requirements and test specifications are relevant to the presumption of conformity under Article 3.2 of the R&TTE Directive						
Technical Requirement reference			Technical Requirement Conditionality		Test Specification	
No	Description	Reference: Clause No	U/C	Condition	E/O	Reference: Clause No
1	Transmitter frequency error	4.2.1	U		E	5.3.1
2	Transmitter adjacent channel power	4.2.2	U		E	5.3.2
3	Transmitter conducted spurious emissions conveyed to the antenna	4.2.3	U		E	5.3.3
4	Transmitter cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	4.2.4	U		E	5.3.4
5	Transient frequency behaviour of the transmitter	4.2.5	U		E	5.3.5
6	Transmitter carrier power	4.2.6	U		E	5.3.6
7	Transmitter frequency deviation	4.2.7	U		E	5.3.7
8	DSC frequency error (demodulated DSC signal)	4.2.8	U		E	5.3.8

Harmonized Standard EN 301 025-2 (continued) The following technical requirements and test specifications are relevant to the presumption of conformity under Article 3.2 of the R&TTE Directive						
Technical Requirement reference			Technical Requirement Conditionality		Test Specification	
No	Description	Reference: Clause No	U/C	Condition	E/O	Reference: Clause No
9	DSC modulation index	4.2.9	U		E	5.3.9
10	DSC modulation rate	4.2.10	U		E	5.3.10
11	Receiver maximum useable sensitivity	4.2.11	U		O	5.4.2
12	Receiver co-channel rejection	4.2.12	U		O	5.4.3
13	Receiver adjacent channel selectivity	4.2.13	U		O	5.4.4
14	Receiver spurious response rejection	4.2.14	U		O	5.4.5
15	Receiver inter-modulation response	4.2.15	U		O	5.4.6
16	Receiver blocking or desen-sitization	4.2.16	U		O	5.4.7
17	Receiver spurious emissions at the antenna	4.2.17	U		O	5.4.8
18	Receiver cabinet radiated spurious emissions	4.2.18	U		O	5.4.9
19	DSC receiver maximum useable sensitivity	4.2.19	U		O	5.4.10
20	DSC receiver co-channel rejection	4.2.20	U		O	5.4.11
21	DSC receiver spurious response and blocking immunity	4.2.21	U		O	5.4.12

Key to columns:**Essential Requirement:**

No A unique identifier for one row of the table which may be used to identify an essential requirement or its test specification.

Description A textual reference to the requirement.

Clause Number Identification of clause(s) defining the essential requirement in the present document unless another document is referenced explicitly.

Conditionality:

U/C	Indicates whether the requirement is to be <i>unconditionally</i> applicable (U) or is <i>conditional</i> upon the suppliers claimed functionality of the equipment (C).
Condition	Explains the conditions when the requirement shall or shall not be applicable for a technical requirement which is classified "conditional".

Test Specification:

E/O	Indicates whether the test specification forms part of the <i>Essential Radio Test Suite</i> (E) or whether it is one of the Other Test Suite (O).
------------	--

NOTE: All tests whether "E" or "O" are relevant to the requirements. Rows designated "E" collectively make up the Essential Radio Test Suite; those designated "O" make up the Other Test Suite; for those designated "X" there is no test specified corresponding to the requirement. All tests classified "E" shall be performed as specified with satisfactory outcomes is a necessary condition for a presumption of conformity. Requirements associated with tests classified "O" or "X" must be complied with as a necessary condition for presumption of conformity, although conformance with the requirement may be claimed by an equivalent test or by manufacturer's assertion supported by appropriate entries in the technical construction file.

Clause Number Identification of clause(s) defining the test specification in the present, document unless another document is referenced explicitly. Where no test is specified (that is, where the previous field is "X") this field remains blank.

Annex B (informative): The EN title in the official languages

Language	EN title
Czech	
Danish	Elektromagnetisk kompatibilitet og Radiospektrum Anliggender (ERM); VHF radiotelefontil udstyr til generel kommunikation og tilknyttet udstyr til "Klasse D" Digitale, selektive opkald (DSC); Del 2: Harmoniseret EN, som dækker de væsentlige krav i R&TTE direktivets artikel 3.2
Dutch	Elektromagnetische compatibiliteit en radiospectrum zaken (ERM); VHF radiotelefonie apparatuur tbv algemene communicatie en bijbehorende apparatuur voor klasse "D" Digital Selective Calling (DSC); Deel 2: Geharmoniseerde EN welke invulling geeft aan de wezenlijke vereisten, neergelegd in artikel 3.2 van de R&TTE Directive
English	Electromagnetic compatibility and Radio spectrum Matters (ERM); VHF radiotelephone equipment for general communications and associated equipment for class "D" Digital Selective Calling (DSC); Part 2: Harmonized EN under article 3.2 of the R&TTE Directive
Estonian	
Finnish	Sähkömagneettinen yhteensopivuus ja radiospektriasiat (ERM); Yleisen liikenteen meri-VHF - radiopuhelimet ja D-luokan digitaalisen selektiivikutsun (DSC) lisälaitteet; Osa 2: Harmonisoitu EN R&TTE - direktiivin artiklan 3.2 olennaisten vaatimusten mukaisesti
French	CEM et spectre radioélectrique (ERM) - Appareils de radiotéléphone en VHF pour la téléphonie générale et appareils associés pour Appel numérique sélectif (DSC) de classe "D" - Partie 2: EN harmonisée de l'article 3.2 de la Directive R&TTE
German	Elektromagnetische Verträglichkeit und Funkspektrumangelegenheiten (ERM); UKW-Sprechfunkanlagen des mobilen Seefunkdienstes für "allgemeine Kommunikation" mit Zusatzeinrichtung für den digitalen Selektivruf (DSC) Klasse D; Teil 2: Harmonisierte Europäische Norm (EN) mit wesentlichen Anforderungen nach R&TTE-Richtlinie Artikel 3.2
Greek	Ηλεκτρομαγνητική συμβατότητα και θέματα Ραδιοφάσματος (ERM) - Συσκευή ραδιοτηλε-φώνου VHF γενικό επικοινωνιών και συσχετισμένο εξοπλισμό για Ψηφιακή Επιλεκτική Κλήση (DSC) κατηγορίας "D" - Μέρος 2: Εναρμονισμένο EN για την κάλυψη των ουσιο-δών απαιτήσεων του άρθρου 3.2 της οδηγίας R&TTE
Hungarian	
Icelandic	
Italian	Compatibilità elettromagnetica e Questioni relative allo spettro delle radiofrequenze (ERM); apparecchiature radiotelefoniche VHF per comunicazioni generiche ed apparecchiature associate per Chiamate Digitali Selettive (DSC) di Classe "D"; Part 2: Norma Europea armonizzata per l'articolo 3.2 della direttiva R&TTE
Latvian	
Lithuanian	
Maltese	
Norwegian	
Polish	Kompatybilność Elektromagnetyczna i Zagadnienia Widma Radiowego (ERM) - Urządzenia radiotelefoniczne VHF dla łączności ogólnej i związane wyposażenie do wywoływania selektywnego cyfrowego (DSC) "klasy D" - Część 2: Zharmonizowana EN zgodna z artykułem 3.2 dyrektywy R&TTE
Portuguese	Assuntos de Espectro Radioelétrico e Compatibilidade Electromagnética (ERM); Equipamento radiotelefónico VHF destinado a comunicações genéricas e equipamento associado para Chamada Seletiva Digital (DSC) de Classe "D"; Parte 2: EN harmonizada cobrindo os requisitos essenciais no âmbito do Artigo 3.2 da Directiva R&TTE
Slovak	Elektromagnetická kompatibilita a záležitosti rádiového spektra (ERM). Rádiotelefonné zariadenia VHF na všeobecné komunikácie a pridružené zariadenia triedy D digitálneho selektívneho volania (DSC). Časť 2: Harmonizovaná EN podľa článku 3.2 smernice R&TTE
Slovenian	
Spanish	Compatibilidad electromagnética y cuestiones de espectro de radiofrecuencia (ERM); Equipos radioteléfono VHF para comunicaciones generales y equipos asociados para clase "D" Llamada selectiva digital (DSC); Parte 2: EN armonizada cubriendo los requisitos esenciales según el artículo 3.2 de la directiva de R&TTE
Swedish	Elektromagnetisk kompatibilitet och radio-spektrumfrågor (ERM); Radiotelefonutrustning på VHF avsedd för allmänna kommunikationer och associerad utrustning för Klass "D" digitalt selektivt anrop (DSC); Del 2: Harmoniserad EN enligt artikel 3.2 i R&TTE-direktivet

History

Document history		
V1.1.1	August 1998	Publication as EN 301 025
V1.1.1	August 2000	Publication
V1.2.1	September 2004	Publication
V1.3.1	September 2006	One-step Approval Procedure OAP 20070119: 2006-09-20 to 2007-01-19