
EN 301 029-7 V1.1.3 (1998-10)

European Standard (Telecommunications series)

Broadband Integrated Services Digital Network (B-ISDN); Signalling System No.7; B-ISDN User Part (B-ISUP); Part 7: ATM end system address

[ITU-T Recommendation Q.2726.1 (1996)]



Reference DEN/SPS-01043-7 (9j1r0ie0.PDF)

Keywords B-ISDN, SS7, B-ISUP, NNI, ATM, ISDN, ISUP, broadband

ETSI

Postal address F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis Valbonne - FRANCE Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16 Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr http://www.etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 1998. All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 7 of a multi-part standard covering the Broadband Integrated Services Digital Network (B-ISDN) User Part (B-ISUP) signalling capability set 2, step 1, as identified below:

Part 1:	"Overview of the B-ISDN network node interface signalling capability set 2, step 1 [ITU-T Recommendation Q.2721.1 (1996)]";
Part 2:	"Network node interface specification for point-to-multipoint call/connection control [ITU-T Recommendation Q.2722.1 (1996)]";
Part 3:	"Support of additional traffic parameters for sustainable cell rate and quality of service [ITU-T Recommendations Q.2723.1 (1996), Q.2723.2 (1997), Q.2723.3 (1997), Q.2723.4 (1997)]";
Part 4:	"Look-ahead without state change for the network node interface [ITU-T Recommendation Q.2724.1 (1996)]";
Part 5:	"Support of negotiation during connection setup [ITU-T Recommendation Q.2725.1 (1996)]";
Part 6:	"Modification procedures [ITU-T Recommendation Q.2725.2 (1996)]";
Part 7:	"ATM end system address [ITU-T Recommendation Q.2726.1 (1996)]";
Part 8:	[Not issued].
Part 9:	"Network generated session identifier [ITU-T Recommendation 0.2726.3 (1996)]":

Part 10: "Support of frame relay [ITU-T Recommendation Q.2727 (1996)]".

National transposition dates						
Date of adoption of this EN:	30 October 1998					
Date of latest announcement of this EN (doa):	31 January 1999					
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 1999					
Date of withdrawal of any conflicting National Standard (dow):	31 July 1999					

Endorsement notice

All elements of ITU-T Recommendation Q.2726.1 (1996) apply.

4

History

		Document history		
V1.1.1	April 1997	Public Enquiry	PE 9733:	1997-04-18 to 1997-08-15
V1.1.2	August 1998	Vote	V 9843:	1998-08-25 to 1998-10-23
V1.1.3	October 1998	Publication		