

Final draft **ETSI EN 301 062-2** V1.1.1 (2000-04)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);
Signalling System No.7;
Support of Virtual Private Network (VPN)
applications with Private network Q reference point
Signalling System number 1 (PSS1) information flows;
Part 2: Protocol Implementation Conformance
Statement (PICS) proforma specification**



Reference

DEN/SPAN-01032-2

Keywords

ISDN, ISUP, PICS, SS7, VPN

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).

In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	4
1 Scope	5
2 References	5
3 Definitions and abbreviations	6
3.1 Definitions	6
3.2 Abbreviations	7
4 Conformance to the PICS proforma specification	7
Annex A (normative): PICS proforma.....	8
A.1 Instructions for completing the PICS proforma	8
A.1.1 Purposes and structure	8
A.1.2 Abbreviations and conventions.....	8
A.2 Identification of the implementation	9
A.2.1 Date of the statement	10
A.2.2 Implementation under test (IUT) identification	10
A.2.3 System under test (SUT) identification	10
A.2.4 Product supplier.....	10
A.2.5 Client	10
A.2.6 ICS contact person.....	10
A.3 Identification of the reference specification	10
A.4 PICS proforma tables	11
A.4.1 Global statement of conformance	11
A.4.2 Roles.....	11
A.4.3 Capabilities.....	11
Bibliography	12
History	13

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN), and is now submitted for the Voting phase of the ETSI standards Two-step Approval Procedure.

The present document is part 2 of a multi-part EN covering the Integrated Services Digital Network (ISDN); Signalling System No.7; Support of Virtual Private Network (VPN) applications with Private network Q reference point Signalling System number 1 (PSS1) information flows, as identified below:

- Part 1: "Protocol specification [ITU-T Recommendations Q.765.1 and Q.699.1, modified]";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";**
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) specification".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document contains the validation (conformance) test specification for the application transport mechanism, support of VPN applications with PSS1 information flows' defined in ITU-T Recommendation Q.765.1 [9]. The present document applies only to exchanges having implemented the ISUP v3 protocol specification for the Application Transport Mechanism and APM support of VPN applications for the exchange. It is applicable for validation testing of all types of exchanges as defined in the ISUP v3 protocol specification. The present document does not deal with compatibility testing.

The main body of the present document presents the protocol implementation conformance statements (PICS). The document EN 301 062-3 [1] presents the test suite structure and test purposes (TSS&TP) and the document EN 301 062-4 [2] presents the protocol implementation extra information for testing (PIXIT), protocol conformance test report (PCTR) and the ATS for the Application Transport Mechanism, support of VPN applications with PSS1 information flows' the last one being available on electronic media.

The supplier of an implementation that is claimed to conform to the reference specification for the Signalling System Number 7, Application Transport Mechanism, support of VPN applications with PSS1 information flows' ITU-T Recommendation Q.765.1 [9] is required to complete a copy of the PICS proforma provided in annex A in the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ETSI EN 301 062-3: "Integrated Services Digital Network (ISDN); Signalling System No.7; Support of Virtual Private Network (VPN) applications with Private network Q reference point Signalling System number 1 (PSS1) information flows; Part 3: Test Suite Structure and Test Purposes (TSS&TP) specification".
- [2] ETSI EN 301 062-4: "Integrated Services Digital Network (ISDN); Signalling System No.7; Support of Virtual Private Network (VPN) applications with Private network Q reference point Signalling System number 1 (PSS1) information flows; Part 4: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) specification".
- [3] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".
- [4] ITU-T Recommendation Q.761: "Signalling System No. 7 - ISDN User Part functional description".
- [5] ITU-T Recommendation Q.762: "Signalling System No. 7 - ISDN user part general functions of messages and signals".
- [6] ITU-T Recommendation Q.763: "Signalling System No. 7 - ISDN user part formats and codes".
- [7] ITU-T Recommendation Q.764: "Signalling System No. 7 - ISDN user part signalling procedures".
- [8] ITU-T Recommendation Q.765: "Signalling System No. 7 - Application transport mechanism".
- [9] ITU-T Recommendation Q.765.1: "Signalling System No. 7 - Application transport mechanism: Support of VPN applications with PSS1 information flows".

- [10] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [11] ISO/IEC 9646-3: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 3: The Tree and Tabular Combined Notation (TTCN)".
- [12] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

- terms defined in ISDN User Part (ISUP) reference specification in ITU-T Recommendations Q.765.1 [9], Q.765 [8], Q.763 [6] and Q.764 [7];
- terms defined in ISO/IEC 9646-1 [10], ISO/IEC 9646-3 [11] and in ISO/IEC 9646-7 [12].

In particular, the following terms apply:

Abstract Test Case (ATC): complete and independent specification of the actions required to achieve a specific test purpose, defined at the level of abstraction of a particular Abstract Test Method, starting in a stable testing state and ending in a stable testing state (see ISO/IEC 9646-1 [10], subclause 3.3.3).

Abstract Test Method (ATM): description of how an IUT is to be tested, given at an appropriate level of abstraction to make the description independent of any particular realization of a Means of Testing, but with enough detail to enable abstract test cases to be specified for this method (see ISO/IEC 9646-1 [10], subclause 3.3.5).

Abstract Test Suite (ATS): test suite composed of abstract test cases (see ISO/IEC 9646-1 [10], subclause 3.3.6).

Implementation Under Test (IUT): implementation of one or more OSI protocols in an adjacent user/provider relationship, being part of a real open system which is to be studied by testing (see ISO/IEC 9646-1 [10], subclause 3.3.43).

ISDN number: number conforming to the numbering and structure specified in ITU-T Recommendation E.164 [3].

Means of Testing (MOT): combination of equipment and procedures that can perform the derivation, selection, parameterization and execution of test cases, in conformance with a reference standardized ATS, and can produce a conformance log (see ISO/IEC 9646-1 [10], subclause 3.3.54).

PICS proforma: document, in the form of a questionnaire, which when completed for an implementation or system becomes the PICS.

PIXIT proforma: document, in the form of a questionnaire, which when completed for the IUT becomes the PIXIT.

Point of Control and Observation: point within a testing environment where the occurrence of test events is to be controlled and observed, as defined in an Abstract Test Method (see ISO/IEC 9646-1 [10], subclause 3.3.64).

Pre-test condition: setting or state in the IUT which cannot be achieved by providing stimulus from the test environment.

Protocol Implementation Conformance Statement (PICS): statement made by the supplier of a protocol claimed to conform to a given specification, stating which capabilities have been implemented (see ISO/IEC 9646-1 [10], subclause 3.3.39 and subclause 3.3.80).

Protocol Implementation eXtra Information for Testing (PIXIT): statement made by a supplier or implementor of an IUT (protocol) which contains or references all of the information related to the IUT and its testing environment, which will enable the test laboratory to run an appropriate test suite against the IUT (see ISO/IEC 9646-1 [10], subclause 3.3.41 and subclause 3.3.81).

System Under Test (SUT): real open system in which the IUT resides (see ISO/IEC 9646-1 [10], subclause 3.3.103).

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
DLE	Destination Local Exchange
ICS	Implementation Conformance Statement
ISDN	Integrated Services Digital Network
ISUP	ISDN User Part
IUT	Implementation Under Test
OLE	Originating Local Exchange
MOT	Means Of Testing
PAN	Public Addressed Node
PICS	Protocol Implementation Conformance Statement
PIN	Public Initiated Node
PINX	Private Integrated Services Network Exchange
PIXIT	Protocol Implementation eXtra Information for Testing
PSS1	Private network Q reference point Signalling System number 1
SUT	System Under Test
TP	Test Purpose (context dependent)
TSS	Test Suite Structure
TSS&TP	Test Suite Structure and Test Purposes
TTCN	Tree and Tabular Combined Notation
VPN	Virtual Private Network

The ISUP message acronyms can be found in table 2/ITU-T Recommendation Q.762 [5].

The APM primitives acronyms can be found in the different tables of ITU-T Recommendation Q.765 [8].

The VPN primitives acronyms can be found in the different tables of ITU-T Recommendation Q.765.1 [9].

The following abbreviations apply for ISUP parameters and parameter values.

AdSg	Address Signals
CgPN	Calling Party Number
GenNot	Generic Notification
TMR	Transmission Medium Requirement
USI	User Service Indicator

4 Conformance to the PICS proforma specification

A PICS proforma that conforms to this PICS proforma specification shall be technically equivalent to the present document.

Annex A, and shall preserve the numbering and ordering of the items in annex A.

A PICS that conforms to this PICS proforma specification shall:

- describe an implementation which is claimed to conform to ISDN User part (ISUP) v3 reference specification (ITU-T Recommendations Q.765.1 [9], Q.765 [8], Q.763 [6] and Q.764 [7]);
- be a conforming PICS proforma which has been completed in accordance with the instructions for completion given in clause the present document;
- include the information necessary to uniquely identify both the supplier and the implementation.

Annex A (normative): PICS proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.
--

A.1 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. If necessary, the supplier may provide additional comments separately.

More detailed instructions are given at the beginning of the different subclauses of the PICS proforma.

A.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in ISDN User Part (ISUP) v3 reference specification (ITU-T Recommendations Q.765.1 [9], Q.765 [8], Q.763 [6] and Q.764 [7]) may provide information about the implementation in a standardized manner.

The PICS proforma is subdivided into subclauses for the following categories of information:

- instructions for completing the PICS proforma;
- identification of the implementation;
- identification of the reference protocol specification;
- PICS proforma tables (containing the global statement of conformance).

A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is composed of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [12].

Item column

It contains a number that identifies the item in the table.

Item description column

It describes each respective item (e.g. parameters, timers, etc.).

Reference column

It gives reference to the ISUP v3 specification for the supplementary services (ITU-T Recommendations Q.765.1 [9] and Q.765 [8]), except where explicitly stated otherwise.

Status column

The following notations, defined in ISO/IEC 9646-7 [12], are used for the status column:

- m mandatory - the capability is required to be supported;
- n/a not applicable - in the given context, it is impossible to use the capability. No answer in the support column is required;
- o optional - the capability may be supported or not;
- o.i qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies a unique group of related optional items and the logic of their selection which is defined immediately following the table;
- ci conditional - the requirement on the capability ("m", "o" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression that is defined immediately following the table. For nested conditional expressions, the syntax "IF... THEN (IF... THEN... ELSE...) ELSE..." shall be used to avoid ambiguities. If an ELSE clause is omitted, "ELSE n/a" shall be implied.

NOTE: Support of a capability means that the capability is implemented in conformance to the ISUP v3 specification (ITU-T Recommendations Q.765.1 [9], Q.765 [8], Q.763 [6] and Q.764 [7]).

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [12], are used for the support column:

- Y or y supported by the implementation;
- N or n not supported by the implementation;
- N/A or - no answer required (allowed only if the status is N/A, directly or after evaluation of a conditional status).

Values allowed column

This column contains the values or the ranges of values allowed.

Values supported column

The support column shall be filled in by the supplier of the implementation. In this column the values or the ranges of values supported by the implementation shall be indicated.

References to items

For each possible item answer (answer in the support column) within the PICS proforma a unique reference exists. It is defined as the table identifier, followed by a slash character "/", followed by the item number in the table. If there is more than one support column in a table, the columns shall be discriminated by letters (a, b, etc.) respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table 5 of the present document.

EXAMPLE 2: 6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table 6 of the present document.

A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides - the System Under Test (SUT) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the ICS should be named as the contact person.

A.2.1 Date of the statement

Date of the statement:	
------------------------	--

A.2.2 Implementation under test (IUT) identification

IUT name:	
IUT version:	

A.2.3 System under test (SUT) identification

SUT name:	
Hardware configuration:	
Operating system:	

A.2.4 Product supplier

Name:	
Address:	
Telephone number:	
Facsimile number:	
Additional information:	

A.2.5 Client

Name:	
Address:	
Telephone number:	
Facsimile number:	
Additional information:	

A.2.6 ICS contact person

Name:	
Telephone number:	
Facsimile number:	
Additional information:	

A.3 Identification of the reference specification

This PICS proforma applies to the following standard ITU-T Recommendation Q.765.1 [9].

A.4 PICS proforma tables

A.4.1 Global statement of conformance

	(Yes/No)
Are all mandatory capabilities implemented?	

NOTE: Answering "No" to this question indicates non-conformance to the reference protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming.

A.4.2 Roles

Table A.1: Role of implementation

Item	Is the implementation an...	Reference	Status	Support
1	Local - Local exchange PIN or PAN	6.1/ITU-T Recommendation Q.765	o.1	
2	Terminating - Terminating exchange PIN or PAN	6.1/ITU-T Recommendation Q.765	o.1	
3	Transit - National transit exchange	ITU-T Recommendation Q.761	o.1	
4	DLE-Destination local exchange	ITU-T Recommendation Q.761	o.1	
5	OLE-Originating local exchange	ITU-T Recommendation Q.761	o.1	
o.1: It is mandatory to support at least one of these items.				

A.4.3 Capabilities

Table A.2: VPN Major Capabilities

Item	Is the exchange able to...	Reference	Status	Support
1	Support of GFP functionality at transit PINX nodes	ITU-T Recommendation Q.765.1		
2	Support of GFP functionality at gateway PINX nodes	ITU-T Recommendation Q.765.1		
3	Continuation of calls with no application association	ITU-T Recommendation Q.765.1		
4	Relocation of gateway function	ITU-T Recommendation Q.765.1		
5	Utilize the Corporate Telecommunications Network Identifier (CNID)	ITU-T Recommendation Q.765.1		
o.1: It is mandatory to support at least one of these items.				

Bibliography

The following material, though not specifically referenced in the body of the present document (or not publicly available), gives supporting information.

ISO/IEC 9646-2: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract Test Suite specification".

ISO/IEC 9646-5: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 5: Requirements on test laboratories and clients for the conformance assessment process".

ITU-T Recommendation Q.784.2: "ISUP basic call test specification: Abstract test suite for ISUP'92 basic call control procedures".

History

Document history			
V1.1.1	November 1999	Public Enquiry	PE 200013: 1999-12-01 to 2000-03-31
V1.1.1	April 2000	Vote	V 20000623: 2000-04-24 to 2000-06-23