

# EN 301 068-1 V1.2.4 (1998-11)

---

*European Standard (Telecommunications series)*

**Broadband Integrated Services Digital Network (B-ISDN);  
Digital Subscriber Signalling System No. two (DSS2) protocol;  
Connection characteristics;  
ATM transfer capability and traffic parameter indication;  
Part 1: Protocol specification**

[ITU-T Recommendations Q.2961.1 (1995), Q.2961.2 (1997), Q.2961.3 (1997),  
Q.2961.4 (1997), modified]

---



---

**Reference**

DEN/SPS-05081-1 (9w090iqo.PDF)

---

**Keywords**

B-ISDN, DSS2, UNI, layer 3, ATM

**ETSI**

---

**Postal address**

F-06921 Sophia Antipolis Cedex - FRANCE

---

**Office address**

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16  
Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Internet**

secretariat@etsi.fr  
Individual copies of this ETSI deliverable  
can be downloaded from  
<http://www.etsi.org>

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.  
All rights reserved.

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 1 of a multi-part standard covering the Digital Subscriber Signalling System No. two (DSS2) protocol specification for the Broadband Integrated Services Digital Network (B-ISDN) ATM transfer capability and traffic parameter indication, as described below:

- Part 1: "Protocol specification [ITU-T Recommendation Q.2961 Part 1 (1995), Part 2 (1997), Part 3 (1997), Part 4 (1997), modified]";**
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "TSS&TP specification for the network";
- Part 6: "ATS and partial PIXIT proforma specification for the network".

The present document details the access signalling system protocol aspects and switching functions required to support the ATM transfer capability and the related traffic parameter indication at call and/or connection establishment time.

<b>National transposition dates</b>	
Date of adoption of this EN:	6 November 1998
Date of latest announcement of this EN (doa):	28 February 1999
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 1999
Date of withdrawal of any conflicting National Standard (dow):	31 August 1999

## Endorsement notice

The text of ITU-T Recommendations Q.2961.1 (1995), Q.2961.2 (1997), Q.2961.3 (1997) and Q.2961.4 (1997) was approved by ETSI as an EN with agreed modifications as given below.

NOTE: New or modified text is indicated using sidebars. In addition, underlining and/or strike-out are used to highlight detailed modifications where necessary.

# Global modifications to ITU-T Recommendations Q.2961.1 to Q.2961.4

Insert the following clause (Scope).

## Scope

This first part of EN 301 068 covers the support of additional traffic parameters for the Broadband Integrated Services Digital Network (B-ISDN) at the  $T_B$  reference point or coincident  $S_B$  and  $T_B$  reference point as defined in ITU-T Recommendation I.413 by means of the Digital Subscriber Signalling System No. two (DSS2) protocol for the pan-European Broadband Integrated Services Digital Network (B-ISDN) as provided by European public telecommunication operators.

It defines the DSS2 protocol procedures, formats and functions needed to support the identified ATM transfer capabilities and the ATM traffic related additional capabilities.

The specifications provided by the present document allow for the signalling of the ATM transfer capabilities and of the additional traffic parameters beyond the ones already specified by EN 300 443-1 for B-ISDN basic call/connection control at the UNI. The additional traffic parameters support a Broadband Connection-Oriented Bearer Service (BCOB) as specified in ITU-T Recommendation F.811.

The present document forms part of the DSS2 family of standards; it specifies extensions to EN 300 443-1 which specifies the control protocol for point-to-point call/bearer connection, and does not repeat states, information elements, messages and procedures contained therein, but only specifies extensions related to additional traffic parameter indications.

This present document does not cover procedures for the negotiation and modification/re-negotiation of the ATM traffic parameters.

## Throughout the text of ITU-T Recommendations Q.2961.1 to Q.2961.4

Replace references as shown in the following table.

Reference in ITU-T Recommendations Q.2961.1 to Q.2961.4	Modified reference
ITU-T Recommendation Q.2931	ITU-T Recommendation Q.2931 as modified by EN 300 443-1
ITU-T Recommendation Q.2933	ITU-T Recommendation Q.2933 as modified by EN 301 174-1
ITU-T Recommendation I.371	ITU-T Recommendation I.371 as modified by ETS 300 301 edition 2
ITU-T Recommendation I.356	ITU-T Recommendation I.356 as modified by ETS 300 xxx
ITU-T Recommendation Q.2951, clause 1	ITU-T Recommendation Q.2951 as modified by ETS 300 661-1
ITU-T Recommendation Q.2951, clause 2	ITU-T Recommendation Q.2951 as modified by ETS 300 662-1
ITU-T Recommendation Q.2951, clause 3	ITU-T Recommendation Q.2951 as modified by ETS 300 663-1
ITU-T Recommendation Q.2951, clause 4	ITU-T Recommendation Q.2951 as modified by ETS 300 664-1
ITU-T Recommendation Q.2951, clause 5	ITU-T Recommendation Q.2951 as modified by ETS 300 665-1
ITU-T Recommendation Q.2951, clause 6	ITU-T Recommendation Q.2951 as modified by ETS 300 666-1
ITU-T Recommendation Q.2951, clause 8	ITU-T Recommendation Q.2951 as modified by ETS 300 667-1
ITU-T Recommendation Q.2955.1	ITU-T Recommendation Q.2955 as modified by ETS 300 770-1
ITU-T Recommendation Q.2957	ITU-T Recommendation Q.2957 as modified by ETS 300 668-1
ITU-T Recommendation Q.2962	ITU-T Recommendation Q.2962 as modified by EN 301 067-1
ITU-T Recommendation Q.2963.1	ITU-T Recommendation Q.2963.1 as modified by EN 301 003-1
ITU-T Recommendation F.811 (1992)	ITU-T Recommendation F.811 (1996)

---

## Modifications to ITU-T Recommendation Q.2961.1

Replace VBR (Variable Bit Rate) by SBR (Statistical Bit rate) ATM Transfer Capability.

### Appendix I

Appendix I is informative.

### Appendix II

Appendix II is informative.

### Appendix III

Appendix III is informative.

### Appendix IV

Appendix IV is not applicable.

---

## Modifications to ITU-T Recommendation Q.2961.2

Reference [6] (ITU-T Recommendation Q.2933) is not applicable.

NOTE: The use of the Frame Relay Bearer Class codepoint in octet 5 (bits 1 to 5) of the Broadband bearer capability information element (Figure 1/Q.2961.2) will be the subject of a separate standard defining the application of ITU-T Recommendation Q.2933.

### Annex A

Annex A is normative.

Replace TABLE A-1/Q.2961.2 by the following new one:

Table A-1 (Part 1/3)/Q.2961.2

## Valid combinations of Traffic related parameters in the SETUP message

<i>Broadband bearer capability</i>											
Bearer class	A	A	A	C	C	C	C		C	C	
BTC (value) (NOTE 1)	absent	absent	7	absent	absent	absent	absent		11	19	
<i>Traffic descriptor for a given direction</i>											
PCR (CLP=0)		S			S						
PCR (CLP=0+1)	S	S	S	S	S	S	S		S	S	
{SCR, MBS} (CLP=0)							S				
{SCR, MBS} (CLP=0+1)						S			S	S	
Tagging (NOTE 13)	N	Y/N	N	N	Y/N	N	Y/N		N	N	
End-to-end timing required	Y	Y	Y	N	N	N	N		N	Y	
<i>For the given direction:</i>											
<i>Requested I.371 ATC</i>	NOTE 2	NOTE 2	DBR	NOTE 2	NOTE 6, 14	NOTE 7	NOTE 14		SBR1	SBR1	
<i>Implicitly requested QoS when the QoS class is 0</i>	NOTE 3	NOTE 3	Class 1	NOTE 5	Class 3	NOTE 5	Class 3		Class 2	NOTE 10	
<i>For the given direction:</i>											
<i>I.371 ATC that supports the requested ATC</i>	DBR	DBR NOTE 4	DBR	DBR	NOTE 6, 14	SBR1	NOTE14		SBR1	SBR1	
<i>I.356 QoS class that supports the implicitly requested QoS</i>	Class 1	Class 1	Class 1	Class 2	Class 3	Class 2	Class 3		Class 2	Class 1	
	NOTE 11	NOTE 11	NOTE 12	NOTE 11	NOTE 11	NOTE 11	NOTE 11		NOTE 12	NOTE 12	

Table A-1 (Part 2/3)/Q.2961.2

## Valid combinations of Traffic related parameters in the SETUP message

<i>Broadband bearer capability</i>												
Bearer class	C	C	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR
BTC (value) (NOTE 1)	9	9	absent, 0, 2, 8 or 10	absent, 0, 2, 8 or 10	absent, 0, 2, 8 or 10	absent, 0, 2, 8 or 10	7	11	19	4, 5 or 6	4, 5 or 6	1 or 9
<i>Traffic descriptor for a given direction</i>												
PCR (CLP=0)				S							S	
PCR (CLP=0+1)	S	S	S	S	S	S	S	S	S	S	S	S
SCR , MBS (CLP=0)	S					S						
SCR , MBS (CLP=0+1)		S			S			S	S			
Tagging (NOTE 13)	Y/N	N	N	Y/N	N	Y/N	N	N	N	N	Y/N	N
End-to-end timing required	Y	Y	N	N	N	N	Y	N	Y	Y	Y	Y
<i>For the given direction:</i>												
<i>Requested I.371 ATC</i>	NOTE 14	NOTE 7	NOTE 2	NOTE 6, 14	NOTE 7	NOTE 14	DBR	SBR1	SBR1	NOTE 2	NOTE 2	NOTE 2
<i>Implicitly requested QoS when the QoS class is 0</i>	NOTE 8	NOTE 8	NOTE 5	Class 3	NOTE 5	Class 3	Class 1	Class 2	NOTE 10	NOTE 3	NOTE 3	NOTE 8
<i>For the given direction:</i>												
<i>I.371 ATC that supports the requested ATC</i>	NOTE 9	SBR1	DBR	NOTE 6, 14	SBR1	NOTE 14	DBR	SBR1	SBR1	DBR	DBR NOTE 4	DBR
<i>I.356 QoS class that supports the implicitly requested QoS</i>		Class 1	Class 2	Class 3	Class 2	Class3	Class 1	Class 2	Class 1	Class 1	Class 1	Class 1
			NOTE 11	NOTE 11	NOTE 11	NOTE 11	NOTE 12	NOTE 12	NOTE 12	NOTE 11	NOTE 11	NOTE 11

Table A-1 (Part 3/3)/Q.2961.2

## Valid combinations of Traffic related parameters in the SETUP message

Broadband bearer capability			
Bearer class	X or FR	X or FR	X or FR
BTC (value) (NOTE 1)	1 or 9	1 or 9	1 or 9
Traffic descriptor for a given direction			
PCR (CLP=0)	S		
PCR (CLP=0+1)	S	S	S
SCR , MBS (CLP=0)			S
SCR , MBS (CLP=0+1)		S	
Tagging (NOTE 13)	Y/N	N	Y/N
End-to-end timing required	Y	Y	Y
For the given direction:			
Requested I.371 ATC	NOTE 6, 14	NOTE 7	NOTE 14
Implicitly requested QoS when the QoS class is 0	NOTE 8	NOTE 8	NOTE 8
For the given direction:			
I.371 ATC that supports the requested ATC	NOTE 9	SBR1	NOTE 9
I.356 QoS class that supports the implicitly requested QoS		Class 1	
	NOTE 11	NOTE 11	NOTE 11



NOTE 1 - BTC values 0, 1, 2, 4, 6, 8 are not used on transmission but shall be understood on reception.

NOTE 2 - The requested capability in this case is not defined in Rec. I.371 and differs from the DBR ATM transfer capability (see Rec. I.371) only in that selective discardability of CLP=1 cells may apply.

NOTE 3 - The implicitly requested QoS class in this case is not defined in Rec. I.356 and differs from QoS class 1 (see Rec. I.356) in that the CLR commitment is only for CLP=0 cells.

NOTE 4 - PCR(CLP=0) is ignored and tagging is not performed.

NOTE 5 - The implicitly requested QoS class corresponds to QoS class 3 (see Rec. I.356).

NOTE 6 - This is provided by setting SCR(CLP=0) equal to specified PCR(CLP=0) and MBS(CLP=0) equal to 1.

NOTE 7 - The requested capability in this case is not defined in Rec. I.371 and differs from the SBR1 ATM transfer capability (see Rec. I.371) only in that selective discardability of CLP=1 cells may apply.

NOTE 8 - The implicitly requested QoS class in this case is not defined in Rec. I.356 and differs from QoS class 3 (see Rec. I.356) in that end-to-end timing is required.

NOTE 9 - There is no combination recommended in Rec. I.356.

NOTE 10 - The implicitly requested QoS class in this case is not defined in Rec. I.356.

NOTE 11 - This combination is supported in order to promote backward compatibility with the first edition of Recommendation Rec. Q.2931 (1995), with Recommendation Rec. Q.2961.1.

NOTE 12 - For this combination, the ATC and the QoS class is the same in both directions.

NOTE 13 - If tagging is not specified but requested by a user, or if tagging is specified for a combination but not supported by a network, the call shall proceed without tagging being applied.

Note 14 - The requested or provided capability in this case is not defined in Rec. I.371 and differs from the SBR2 ATM transfer capability as defined in Rec. I.371 in that tagging may be applied at the Usage Parameter Control function (UPC, as defined in Rec. I.371) according to the procedures described in Recommendation Rec. Q.2961.1. This combination of parameters does not support the SBR3 ATM transfer capability as defined in Rec. I.371.

A Blank in the Table means that the traffic parameter is not applicable for this combination.

PCR = Peak Cell Rate, SCR = Sustainable Cell Rate, MBS = Maximum Burst Size, S = Specified;

For the Tagging row, Y = Yes, N = No or No indication, Y/N = either "Yes" or "No" or "No Indication".

## Appendix I

Appendix I is informative.

---

## Modifications to ITU-T Recommendation Q.2961.3

### Appendix I

Appendix I is informative.

---

## Modifications to ITU-T Recommendation Q.2961.4

No modifications identified.

## History

<b>Document history</b>				
V1.1.1	December 1997	Public Enquiry	PE 9815:	1997-12-12 to 1998-04-10
V1.2.3	September 1998	Vote	V 9844:	1998-09-01 to 1998-10-30
V1.2.4	November 1998	Publication		