

**Integrated Services Digital Network (ISDN);
Digital Subscriber Signalling System No. one (DSS1)
and Signalling System No.7 protocols;
Signalling application for the mobility management service
on the alpha interface;
Part 3: Test Suite Structure and Test Purposes (TSS&TP)
specification for the user**



Reference

DEN/SPS-05121-3

Keywords

CTM, DSS1, ISDN, SS7, user, TSS&TP**ETSI**

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
<http://www.etsi.org>
If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	4
1 Scope	5
2 References	5
3 Definitions and abbreviations	5
3.1 Definitions	5
3.2 Abbreviations	6
4 Test Suite Structure (TSS)	7
5 Test Purposes (TP)	8
5.1 Introduction	8
5.1.1 TP naming convention	8
5.1.2 Source of TP definition	9
5.1.3 TP structure	9
5.1.4 Test strategy	9
5.2 CTM mode	9
5.2.1 Registration & deregistration	9
5.2.1.1 Subscription registration	9
5.2.1.2 Subscription deregistration	11
5.2.2 Activation and deactivation	11
5.2.2.1 Location registration	11
5.2.2.2 Location cancellation	13
5.2.3 Invocation and operation	13
5.2.3.1 Location registration suggest	13
5.2.3.2 Terminal authentication	14
5.2.3.3 Network authentication	14
5.2.3.4 Network initiated ciphering	15
5.2.3.5 Portable initiated ciphering	16
5.2.3.6 Key allocation	17
5.2.3.7 Identity request	18
5.2.4 Embedded procedures	19
5.2.5 Outgoing call	19
5.2.6 Incoming call	20
5.3 DECT access to GSM mode	21
5.3.1 Activation and deactivation	21
5.3.1.1 Location registration	21
5.3.1.2 Location cancellation	22
5.3.1.3 Detach	22
5.3.2 Invocation and operation	22
5.3.2.1 Terminal authentication	22
5.3.2.2 Network initiated ciphering	23
5.3.2.3 Temporary identity assignment	24
5.3.2.4 Identity request	25
5.3.3 Embedded procedures	26
5.3.4 Outgoing call	26
5.3.5 Incoming call	27
6 Compliance	28
7 Requirements for a comprehensive testing service	28
History	29

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN), and is now submitted for the Voting phase of the ETSI standards Two-step Approval Procedure.

The present document is part 3 of a multi-part EN covering the Integrated Services Digital Network (ISDN) Digital Subscriber Signalling System No. one (DSS1) and Signalling System No.7 (SS7) protocols; Signalling application for the mobility management service on the alpha interface as identified below:

Part 1: "Protocol specification";

Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";

Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";

Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";

Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document provides the Test Suite Structure and Test Purposes (TSS&TP) for the user of the Signalling application for the mobility management service on the alpha interface.

It is applicable to all types of exchanges as defined in the reference specification.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ETSI EN 301 144-1 (V.1.1): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) and Signalling System No.7 (SS7); Signalling application for the mobility management service on the alpha interface; Part 1: Protocol specification".
- [2] ETSI EN 301 144-2 (V1.1): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) and Signalling System No.7 protocols; Signalling application for the mobility management service on the alpha interface; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] ISO/IEC 9646-1: "Information Technology - Open Systems Interconnection - Conformance Testing Methodology and Framework; Part 1: General Concepts".
- [4] ISO/IEC 9646-2: "Information Technology - Open Systems Interconnection - Conformance Testing Methodology and Framework; Part 2: Abstract Test Suite Specification".
- [5] ISO/IEC 9646-3: "Information Technology - Open Systems Interconnection - Conformance Testing Methodology and Framework; Part 3: The Tree and Tabular Combined Notation".
- [6] ETSI EN 301 002-1: "Integrated Services Digital Network (ISDN); Security tools (SET) procedures; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 301 144-1 [1] and the following apply:

abstract test case: refer to ISO/IEC 9646-1 [3]

Abstract Test Method (ATM): refer to ISO/IEC 9646-1 [3]

Abstract Test Suite (ATS): refer to ISO/IEC 9646-1 [3]

active test: test case where the IUT is required to send a particular message, but not in reaction to a received message. This would usually involve the use of PIXIT information to see how this message can be generated and quite often is specified in an ATS using an implicit send event

Implementation Under Test (IUT): refer to ISO/IEC 9646-1 [3]

implicit send event: refer to ISO/IEC 9646-3 [5]

lower tester: refer to ISO/IEC 9646-1 [3]

passive test: test case where the IUT is required to respond to a protocol event (e.g. received message) with another protocol event (sends message) and which normally does not require any special operator intervention such as is associated with the implicit send event

point of control and observation: refer to ISO/IEC 9646-1 [3]

Protocol Implementation Conformance Statement (PICS): refer to ISO/IEC 9646-1 [3]

PICS proforma: refer to ISO/IEC 9646-1 [3]

Protocol Implementation eXtra Information for Testing (PIXIT): refer to ISO/IEC 9646-1 [3]

PIXIT proforma: refer to ISO/IEC 9646-1 [3]

system under test: refer to ISO/IEC 9646-1 [3]

Test Purpose (TP): refer to ISO/IEC 9646-1 [3]

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
CES	Connection Endpoint Suffix
CR	Call Reference
CTM	Cordless Terminal Mobility
DECT	Digital Enhanced Cordless Telecommunications
DSS1	Digital Subscriber Signalling System No. one
GSM	Global System for Mobile communications
I	Inopportune
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
S	Syntactically invalid stimulus
TP	Test Purpose
TSS	Test Suite Structure
V	Valid

4 Test Suite Structure (TSS)

CTM

Registration & deregistration (RD)
 Subscription registration (SR)
 Valid
 Invalid
 Subscription deregistration (SD)
 Valid
 Invalid
 Activation & deactivation (AD)
 Location registration (LR)
 Valid
 Invalid
 Location cancellation (LC)
 Valid
 Invalid
 Invocation & operation (IO)
 Location registration suggest (LRS)
 Valid
 Invalid
 Terminal authentication (TA)
 Valid
 Invalid
 Network authentication (NA)
 Valid
 Invalid
 Network initiated ciphering (NIC)
 Valid
 Invalid
 Portable initiated ciphering (PIC)
 Valid
 Invalid
 Key allocation (KA)
 Valid
 Invalid
 Identity request (IR)
 Valid
 Invalid
 Embedded procedure (EMB)
 Outgoing call (OC)
 Incoming call (IC)

Figure 1: Test suite structure (sheet 1 of 2)




Figure 1: Test suite structure (sheet 2 of 2)

5 Test Purposes (TP)

5.1 Introduction

For each test requirement, a TP is defined.

5.1.1 TP naming convention

Tps are numbered, starting at 001, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite and whether it applies to the network or the user (see table 1).

Table 1: TP identifier naming convention scheme

Identifier:	<mode>_<groupProcedure>_<procedure>_<group>_<nnn>
<mode>	= mode of the IUT: "CTM" for the CTM mode or "DG" for DECT/GSM access mode
<groupProcedure>	= group procedure: e.g. "IO" representing the group for the Invocation & Operation procedures
<procedure>	= procedure: e.g. "SR" representing the Subscription Registration procedure
<group>	= group: one character field representing the group reference according to TSS
V:	Valid stimulus
I:	Invalid stimulus
<nnn>	= sequential number: (01-99)

5.1.2 Source of TP definition

The TPs are based on EN 301 144-1 [1] and EN 301 144-2 [2].

5.1.3 TP structure

Each TP has been written in a manner which is consistent with all other TPs. The intention of this is to make the TPs more readable and checkable. A particular structure has been used which is illustrated in table 2. This table should be read in conjunction with any TP, i.e. please use a TP as an example to facilitate the full comprehension of table 2.

Table 2: Structure of a single TP

TP part	Text	Example
Header	<Identifier> <i>tab</i> <subclause number in EN 301 144-1 [1]> <i>tab</i> <type of test> <i>tab</i> <condition> <i>CR</i> .	see table 1 subclause 9.3.4 Valid, Invalid Mandatory, Optional, Conditional
Stimulus	Ensure that the IUT in the <state> <trigger> <i>see below for information structure</i> <i>or</i> <goal>	Idle, etc. on receipt of a XXXX information (see note 2) to request a ...
Reaction	<action> <conditions> <i>if the action is sending</i> <i>see below for information structure</i>	sends, saves, does, etc. using en bloc sending, etc.
Information structure	<information type> a) with the <parameter>	CTMAuthentication invoke component PortableIdentity, etc.
NOTE 1: Text in italics will not appear in TPs and text between < > is filled in for each TP and may differ from one TP to the next.		
NOTE 2: All information shall be considered as "valid and compatible" unless otherwise specified in the test purpose.		

5.1.4 Test strategy

As the base standard EN 301 144-1 [1] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the PICS specification EN 301 144-2 [2]. The criteria applied included the following:

- only the requirements from the point of view of the T or coincident S and T reference point are considered;
- whether or not a test case can be build from the TP is not considered.

5.2 CTM mode

Selection: Support of user requirements. PICS R2.1
AND
Support of the CTM mode. PICS R1.1

5.2.1 Registration & deregistration

5.2.1.1 Subscription registration

Selection: Support of the subscription registration procedure for CTM. PICS MC1.

CTM_RD_SR_V_01 subclause 9.1.1.1 Valid Optional

Ensure that the IUT in Idle state, to request a subscription registration,
sends a CTMAccessRightsRequest invoke component including the following parameters: cTMPortableIdentity,
cTMAuthType and cTMPortableCapabilities.

CTM_RD_SR_V_02 subclause 9.1.1.1 Valid Optional

Ensure that the IUT, having requested a subscription registration, on receipt of a valid CTMAccessRightsRequest return result component containing the cTMPortable Identity, the cTMFixedIdentity parameters
accepts the provided information and sends no message.

CTM_RD_SR_V_03 subclause 9.1.1.1 Valid Optional

Ensure that the IUT, having requested a subscription registration, on receipt of a valid CTMAccessRightsRequest return result component containing the cTMPortable Identity, the cTMFixedIdentity parameters and the optional parameter cTMSERVICECLASS
accepts the provided information and sends no message.

CTM_RD_SR_I_01 subclause 9.1.1.2 Invalid Optional

Ensure that the IUT, having requested a subscription registration, on receipt of a reject component
accepts the provided information.

CTM_RD_SR_I_02 subclause 9.1.1.2 Invalid Optional

Ensure that the IUT, having requested a subscription registration, on receipt of a return error component with the portableIdentityUnknown error
accepts the provided information.

CTM_RD_SR_I_03 subclause 9.1.1.2 Invalid Optional

Ensure that the IUT, having requested a subscription registration, on receipt of a return error component with the Unspecified error
accepts the provided information.

CTM_RD_SR_I_04 subclause 9.1.1.2 Invalid Optional

Ensure that the IUT, having requested a subscription registration, on receipt of a return error component with the congestion error
accepts the provided information.

CTM_RD_SR_I_05xx subclause 9.1.1.2 Invalid Optional

Ensure that the IUT, having requested a subscription registration, on receipt of a return error component with the networkRejected error with the reject reason value detailed in table 3
accepts the provided information.

Table 3: Reject reason values for test purposes CTM_RD_SR_I_0501 to CTM_RD_SR_I_0524

Test purpose	Reject reason value
CTM_RD_SR_I_0501	TPUI unknown
CTM_RD_SR_I_0502	IPUI unknown
CTM_RD_SR_I_0503	IPEI not accepted
CTM_RD_SR_I_0504	IPUI not accepted
CTM_RD_SR_I_0505	Authentication failed
CTM_RD_SR_I_0506	No authentication algorithm
CTM_RD_SR_I_0507	Authentication algorithm not supported
CTM_RD_SR_I_0508	Authentication key not supported
CTM_RD_SR_I_0509	No cipher algorithm
CTM_RD_SR_I_0510	Cipher algorithm not supported
CTM_RD_SR_I_0511	Cipher key not supported
CTM_RD_SR_I_0512	Incompatible service
CTM_RD_SR_I_0513	False LCE reply (no corresponding service)
CTM_RD_SR_I_0514	Late LCE reply (service already taken)
CTM_RD_SR_I_0515	Invalid TPUI
CTM_RD_SR_I_0516	TPUI assignment limits unacceptable
CTM_RD_SR_I_0517	Insufficient memory
CTM_RD_SR_I_0518	Overload
CTM_RD_SR_I_0519	Invalid message
CTM_RD_SR_I_0520	Information element error
CTM_RD_SR_I_0521	Invalid information element contents
CTM_RD_SR_I_0522	Timer expiry
CTM_RD_SR_I_0523	Location area not allowed
CTM_RD_SR_I_0524	-

5.2.1.2 Subscription deregistration

Selection: Support of the subscription deregistration procedure for CTM. PICS MC2.

CTM_RD_SD_V_01 subclause 9.1.2.1 Valid Optional

Ensure that the IUT in Idle state, having successfully registered, on receipt of a CTMAccessRightTerminate invoke component

sends back a CTMAccessRightTerminate return result component without parameter.

CTM_RD_SD_I_01 subclause 9.1.2.2 Invalid Optional

Ensure that the IUT, having received the CTMAccessRightTerminate invoke component and having sent the return result component, on receipt of a reject component,

does not take any action.

CTM_RD_SD_I_02 subclause 9.1.2.2 Invalid Optional

Ensure that the IUT in Idle state, having successfully registered, on receipt of a CTMAccessRightTerminate invoke component containing a wrong cTMPortableIdentity parameter,

sends back a return error component with the error value: portableIdentityUnknown.

CTM_RD_SD_I_03 subclause 9.1.2.2 Invalid Optional

Ensure that the IUT, having received the CTMAccessRightTerminate invoke component, if the signalling connection on the air interface is interrupted

sends back a return error component with the error value: radioConnectionFailure.

CTM_RD_SD_I_04 subclause 9.1.2.2 Invalid Optional

Ensure that the IUT, having received the CTMAccessRightTerminate invoke component, if the paging on the air interface fails

sends back a return error component with the error value: pagingFailure.

CTM_RD_SD_I_05 subclause 9.1.2.2 Invalid Optional

Ensure that the IUT, having received the CTMAccessRightTerminate invoke component, on receipt of a mobility management procedure request, while the ongoing procedure has not yet been finished

sends a return error component with the error value: priorityRuleViolation.

CTM_RD_SD_I_06 subclause 9.1.2.2 Invalid Optional

Ensure that the IUT, having received the CTMAccessRightTerminate invoke component, if fixed part is overloaded

sends back a return error component with the error value: congestion.

CTM_RD_SD_I_07 subclause 9.1.2.2 Invalid Optional

Ensure that the IUT, having received the CTMAccessRightTerminate invoke component, if a terminalRejected return error has been received from the air interface

sends back a return error component with the error value: terminalRejected.

CTM_RD_SD_I_08 subclause 9.1.2.2 Invalid Optional

Ensure that the IUT, having received the CTMAccessRightTerminate invoke component, if the supervision timer expires before a response has been received from the air interface

sends back a return error component with the error value: localTimerExpiry.

5.2.2 Activation and deactivation

5.2.2.1 Location registration

CTM_AD_LR_V_01 subclause 9.2.1.1 Valid Mandatory

Ensure that the IUT in Idle state, to request a location registration

sends a CTMLocationRegistration invoke component with the following parameters: cTMOldLocationAreaIdentity, cTMNewLocationAreaIdentity, cTMPortableCapabilities, cTMPortableIdentity.

CTM_AD_LR_V_02 subclause 9.2.1.1 Valid Mandatory

Ensure that the IUT having sent a CTMLocationRegistration invoke component, on receipt of the CTMLocationRegistration return result

does not take any action.

CTM_AD_LR_I_01 subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT having sent a CTMLocationRegistration invoke component, on receipt of a reject component does not take any action.

CTM_AD_LR_I_02 subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT having sent a CTMLocationRegistration invoke component, on receipt of a return result with the portableIdentityUnknown error accepts the provided information.

CTM_AD_LR_I_03 subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT having sent a CTMLocationRegistration invoke component, on receipt of a return result with the congestion error accepts the provided information.

CTM_AD_LR_I_04 subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT having sent a CTMLocationRegistration invoke component, on receipt of a return result with the unspecified error accepts the provided information.

CTM_AD_LR_I_05xx subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT, having requested a subscription registration, on receipt of a return error component with the networkRejected error with the reject reason value detailed in table 4 accepts the provided information.

Table 4: Reject reason values for test purposes CTM_AD_LR_I_0501 to CTM_AD_LR_I_0524

Test purpose	Reject reason value
CTM_AD_LR_I_0501	TPUI unknown
CTM_AD_LR_I_0502	IPUI unknown
CTM_AD_LR_I_0503	IPEI not accepted
CTM_AD_LR_I_0504	IPUI not accepted
CTM_AD_LR_I_0505	Authentication failed
CTM_AD_LR_I_0506	No authentication algorithm
CTM_AD_LR_I_0507	Authentication algorithm not supported
CTM_AD_LR_I_0508	Authentication key not supported
CTM_AD_LR_I_0509	No cipher algorithm
CTM_AD_LR_I_0510	Cipher algorithm not supported
CTM_AD_LR_I_0511	Cipher key not supported
CTM_AD_LR_I_0512	Incompatible service
CTM_AD_LR_I_0513	False LCE reply (no corresponding service)
CTM_AD_LR_I_0514	Late LCE reply (service already taken)
CTM_AD_LR_I_0515	Invalid TPUI
CTM_AD_LR_I_0516	TPUI assignment limits unacceptable
CTM_AD_LR_I_0517	Insufficient memory
CTM_AD_LR_I_0518	Overload
CTM_AD_LR_I_0519	Invalid message
CTM_AD_LR_I_0520	Information element error
CTM_AD_LR_I_0521	Invalid information element contents
CTM_AD_LR_I_0522	Timer expiry
CTM_AD_LR_I_0523	Location area not allowed
CTM_AD_LR_I_0524	-

5.2.2.2 Location cancellation

CTM_AD_LC_V_01 subclause 9.2.2.1 Valid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMLocationCancellation invoke component shall accept the provided information and shall respond to the network by sending a CTMLocationCancellation return result component without parameter.

CTM_AD_LC_I_01 subclause 9.2.2.2 Invalid Mandatory

Ensure that the IUT, having received a CTMLocationCancellation invoke component containing a wrong cTMPortableIdentity sends a CTMLocationCancellation return error with the portableIdentityUnknown error value.

CTM_AD_LC_I_02 subclause 9.2.2.2 Invalid Mandatory

Ensure that the IUT, having received a CTMLocationCancellation invoke component and when the fixed part is overloaded and the IUT cannot process the request sends a CTMLocationCancellation return error with the congestion error value.

CTM_AD_LC_I_03 subclause 9.2.2.2 Invalid Mandatory

Ensure that the IUT, having received a CTMLocationCancellation invoke component and having sent back the CTMLocationCancellation return result, on receipt of a reject component does not take any action.

5.2.3 Invocation and operation

5.2.3.1 Location registration suggest

CTM_IO_LRS_V_01 subclause 9.3.1.1 Valid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMLocationRegistrationSuggest invoke component accepts the provided information and does not respond or may initiate a location registration procedure.

CTM_IO_LRS_I_01 subclause 9.3.1.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMLocationRegistrationSuggest invoke component containing a wrong cTMPortableIdentity parameter, sends a CTMLocationRegistrationSuggest return result with the portableIdentityUnknown error value.

CTM_IO_LRS_I_02 subclause 9.3.1.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMLocationRegistrationSuggest invoke component and when the paging on the air interface fails, sends a CTMLocationRegistrationSuggest return result with the pagingFailure error value.

CTM_IO_LRS_I_03 subclause 9.3.1.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMLocationRegistrationSuggest invoke component and when the signalling connection on the air interface is interrupted, sends a CTMLocationRegistrationSuggest return result with the radioConnectionFailure error value.

CTM_IO_LRS_I_04 subclause 9.3.1.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMLocationRegistrationSuggest invoke component and when the fixed part is overloaded and the IUT cannot process the request sends a CTMLocationRegistrationSuggest return error with the congestion error value.

CTM_IO_LRS_I_05 subclause 9.3.1.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMLocationRegistrationSuggest invoke component and when a mobility procedure with of equal priority has been requested sends a CTMLocationRegistrationSuggest return error with the priorityRuleViolation error value.

5.2.3.2 Terminal authentication

CTM_IO_TA_V_01 subclause 9.3.2.1 Valid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMTerminalAuthentication invoke component,
sends the CTMTerminalAuthentication return result with the cTMRes parameter and optionally the
cTMServiceClass parameter.

CTM_IO_TA_I_01 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMTerminalAuthentication invoke component with a wrong cTMPortableIdentity
parameter
sends a CTMTerminalAuthentication return error component with the portableIdentityUnknown error value.

CTM_IO_TA_I_02 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMTerminalAuthentication invoke component when the fixed part is overloaded
and the IUT cannot process the request
sends a CTMTerminalAuthentication return error component with the congestion error value.

CTM_IO_TA_I_03 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMTerminalAuthentication invoke component and if the paging on the air
interface fails
sends a CTMTerminalAuthentication return error component with the pagingFailure error value.

CTM_IO_TA_I_04 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMTerminalAuthentication invoke component and if the signalling connection on
the air interface is interrupted
sends a CTMTerminalAuthentication return error component with the radioConnectionFailure error value.

CTM_IO_TA_I_05 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMTerminalAuthentication invoke component and if a mobility management
procedure of equal priority has been requested
sends a CTMTerminalAuthentication return error component with the priorityRuleViolation error value.

CTM_IO_TA_I_06 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMTerminalAuthentication invoke component and if the supervision timer expires
before a response has been received
sends a CTMTerminalAuthentication return error with the localTimerExpiry error value.

CTM_IO_TA_I_07 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMTerminalAuthentication invoke component and if a reject reason is received
from the air interface
sends the CTMTerminalAuthentication with the terminalRejected error value.

CTM_IO_TA_I_08 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, having received a CTMTerminalAuthentication invoke component and having sent a return result,
on receipt of a reject component
does not take any action.

5.2.3.3 Network authentication

CTM_IO_NA_V_01 subclause 9.3.3.1 Valid Mandatory

Ensure that the IUT in Idle state, to request a network authentication
sends the CTMNetworkAuthentication invoke component with the following parameter: cTMAuthenticationType,
cTMRand and the cTMPortableIdentity.

CTM_IO_NA_V_02 subclause 9.3.3.1 Valid Mandatory

Ensure that the IUT, having sent the CTMNetworkAuthentication invoke component and on receipt of the return result
accepts the provided information.

CTM_IO_NA_I_01 subclause 9.3.3.2 Invalid Mandatory

Ensure that the IUT, having sent the CTMNetworkAuthentication invoke component and on receipt of the return error
component with the portableIdentityUnknown value
accepts the provided information.

CTM_IO_NA_I_02 subclause 9.3.3.2 Invalid Mandatory

Ensure that the IUT, having sent the CTMNetworkAuthentication invoke component and on receipt of the return error component with the congestion value
accepts the provided information.

CTM_IO_NA_I_03 subclause 9.3.3.2 Invalid Mandatory

Ensure that the IUT, having sent the CTMNetworkAuthentication invoke component and on receipt of the return error component with the unspecified value
accepts the provided information.

CTM_IO_NA_I_04xx subclause 9.3.3.2 Invalid Mandatory

Ensure that the IUT, having sent the CTMNetworkAuthentication invoke component and on receipt of a return error component with the networkRejected error with the reject reason value detailed in table 5
accepts the provided information.

Table 5: Reject reason values for test purposes CTM_IO_NA_I_0401 to CTM_IO_NA_I_0424

Test purpose	Reject reason value
CTM_IO_NA_I_0401	TPUI unknown
CTM_IO_NA_I_0402	IPUI unknown
CTM_IO_NA_I_0403	IPUI not accepted
CTM_IO_NA_I_0404	IPUI not accepted
CTM_IO_NA_I_0405	Authentication failed
CTM_IO_NA_I_0406	No authentication algorithm
CTM_IO_NA_I_0407	Authentication algorithm not supported
CTM_IO_NA_I_0408	Authentication key not supported
CTM_IO_NA_I_0409	No cipher algorithm
CTM_IO_NA_I_0410	Cipher algorithm not supported
CTM_IO_NA_I_0411	Cipher key not supported
CTM_IO_NA_I_0412	Incompatible service
CTM_IO_NA_I_0413	False LCE reply (no corresponding service)
CTM_IO_NA_I_0414	Late LCE reply (service already taken)
CTM_IO_NA_I_0415	Invalid TPUI
CTM_IO_NA_I_0416	TPUI assignment limits unacceptable
CTM_IO_NA_I_0417	Insufficient memory
CTM_IO_NA_I_0418	Overload
CTM_IO_NA_I_0419	Invalid message
CTM_IO_NA_I_0420	Information element error
CTM_IO_NA_I_0421	Invalid information element contents
CTM_IO_NA_I_0422	Timer expiry
CTM_IO_NA_I_0423	Location area not allowed
CTM_IO_NA_I_0424	-

5.2.3.4 Network initiated ciphering**CTM_IO_NIC_V_01 subclause 9.3.4.1 Valid Mandatory**

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component, with valid cipher parameter
enables ciphering and sends the CTMCiphering return result.

CTM_IO_NIC_I_01 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component with an invalid portable identity parameter
sends a CTMCiphering return error component with the portableIdentityUnknown error value.

CTM_IO_NIC_I_02 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component and when the fixed part is overloaded
sends a CTMCiphering return error component with the congestion error value.

CTM_IO_NIC_I_03 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component and when the supervision timer expire before a response has been received

sends a CTMCiphering return error component with the localTimerExpiry error value.

CTM_IO_NIC_I_04 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component and when the paging fails on the air interface

sends a CTMCiphering return error component with the pagingFailure error value.

CTM_IO_NIC_I_05 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component and when the signalling connection is interrupted on the air interface

sends a CTMCiphering return error component with the radioConnectionFailure error value.

CTM_IO_NIC_I_06 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component and if the ciphering has already been requested for this connection

sends a CTMCiphering return error component with the incompatibleCipheringState error value.

CTM_IO_NIC_I_07 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component and a mobility management procedure of equal priority has been requested

sends a CTMCiphering return error component with the priorityRuleViolation error value.

CTM_IO_NIC_I_08 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a CTMCiphering invoke component and if a reject reason (detailed in table 8) is received from the air interface

sends the CTMCiphering return error component with the terminalRejected error value.

CTM_IO_NIC_I_09 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT, having received the CTMCiphering invoke component and having sent the return result component, on receipt of a reject component

does not take any action.

5.2.3.5 Portable initiated ciphering

Selection: Support the portable initiated ciphering procedure. PICS MC3.

CTM_IO_PIC_V_01 subclause 9.3.5.1 Valid Optional

Ensure that the IUT in Idle state, to request a ciphering procedure

sends a CTMCipheringSuggest invoke component with the following parameter: cTMCIpherInfo and cTMPortableIdentity.

CTM_IO_PIC_V_02 subclause 9.3.5.1 Valid Optional

Ensure that the IUT having sent the CTMCipheringSuggest invoke component, on receipt of a CTMCiphering invoke component to initiate a ciphering procedure

accepts the provided information continue the ciphering procedure by sending the return result.

CTM_IO_PIC_I_01 subclause 9.3.5.2 Invalid Optional

Ensure that the IUT having sent the CTMCipheringSuggest invoke component, on receipt of a return error component with the portableIdentityUnknown error

accepts the provided information and release the transaction or proceed in the existing mode.

CTM_IO_PIC_I_02 subclause 9.3.5.2 Invalid Optional

Ensure that the IUT having sent the CTMCipheringSuggest invoke component, on receipt of a return error component with the congestion error

accepts the provided information and release the transaction or proceed in the existing mode.

CTM_IO_PIC_I_03 subclause 9.3.5.2 Invalid Optional

Ensure that the IUT having sent the CTMCipheringSuggest invoke component, on receipt of a return error component with the unspecified error

accepts the provided information and release the transaction or proceed in the existing mode.

CTM_IO_PIC_I_04 subclause 9.3.5.2 Invalid Optional

Ensure that the IUT having sent the CTMCipheringSuggest invoke component, on receipt of a reject component accepts the provided information and release the transaction or proceed in the existing mode.

CTM_IO_PIC_I_05xx subclause 9.3.5.2 Invalid Optional

Ensure that the IUT having sent the CTMCipheringSuggest invoke component, on receipt of a return error component with the networkRejected error with the reject reason value detailed in table 6 accepts the provided information and release the transaction or proceed in the existing mode.

Table 6: Reject reason values for test purposes CTM_IO_PIC_I_0501 to CTM_IO_PIC_I_0524

Test purpose	Reject reason value
CTM_IO_PIC_I_0501	TPUI unknown
CTM_IO_PIC_I_0502	IPUI unknown
CTM_IO_PIC_I_0503	IPEI not accepted
CTM_IO_PIC_I_0504	IPUI not accepted
CTM_IO_PIC_I_0505	Authentication failed
CTM_IO_PIC_I_0506	No authentication algorithm
CTM_IO_PIC_I_0507	Authentication algorithm not supported
CTM_IO_PIC_I_0508	Authentication key not supported
CTM_IO_PIC_I_0509	No cipher algorithm
CTM_IO_PIC_I_0510	Cipher algorithm not supported
CTM_IO_PIC_I_0511	Cipher key not supported
CTM_IO_PIC_I_0512	Incompatible service
CTM_IO_PIC_I_0513	False LCE reply (no corresponding service)
CTM_IO_PIC_I_0514	Late LCE reply (service already taken)
CTM_IO_PIC_I_0515	Invalid TPUI
CTM_IO_PIC_I_0516	TPUI assignment limits unacceptable
CTM_IO_PIC_I_0517	Insufficient memory
CTM_IO_PIC_I_0518	Overload
CTM_IO_PIC_I_0519	Invalid message
CTM_IO_PIC_I_0520	Information element error
CTM_IO_PIC_I_0521	Invalid information element contents
CTM_IO_PIC_I_0522	Timer expiry
CTM_IO_PIC_I_0523	Location area not allowed
CTM_IO_PIC_I_0524	-

5.2.3.6 Key allocation**CTM_IO_KA_V_01 subclause 9.3.7.1 Valid Mandatory**

Ensure that the IUT on receipt of a CTMKeyAllocate invoke component initiates a network authentication procedure by sending a CTMNetworkAuthentication invoke component.

CTM_IO_KA_V_02 subclause 9.3.7.1 Valid Mandatory

Ensure that the IUT, having received a CTMKeyAllocate invoke component and having sent the CTMNetworkAuthentication invoke component accepts the CTMNetworkAuthentication return result component.

CTM_IO_KA_I_01 subclause 9.3.7.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMKeyAllocate invoke component with an invalid portableIdentity parameter sends a CTMKeyAllocate return error component with the portableIdentityUnknown error value.

CTM_IO_KA_I_02 subclause 9.3.7.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMKeyAllocate invoke component and when the fixed part is overloaded sends a CTMKeyAllocate return error component with the congestion error value.

CTM_IO_KA_I_03 subclause 9.3.7.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMKeyAllocate invoke component and when the supervision timer expire before a response has been received sends a CTMKeyAllocate return error component with the localTimerExpiry error value.

CTM_IO_KA_I_04 subclause 9.3.7.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMKeyAllocate invoke component and when the paging fails on the air interface sends a CTMKeyAllocate return error component with the pagingFailure error value.

CTM_IO_KA_I_05 subclause 9.3.7.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMKeyAllocate invoke component and when the signalling connection is interrupted on the air interface sends a CTMKeyAllocate return error component with the radioConnectionFailure error value.

CTM_IO_KA_I_06 subclause 9.3.7.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMKeyAllocate invoke component and a mobility management procedure of equal priority has been requested sends a CTMKeyAllocate return error component with the priorityRuleViolation error value.

CTM_IO_KA_I_07 subclause 9.3.7.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMKeyAllocate invoke component and if a reject reason is received from the air interface sends the CTMKeyAllocate return error component with the terminalRejected error value.

5.2.3.7 Identity request**CTM_IO_IR_V_01 subclause 9.3.8.1 Valid Mandatory**

Ensure that the IUT, on receipt of a CTMIdentityRequest invoke component sends a CTMIdentityRequest return result.

CTM_IO_IR_I_01 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMIdentityRequest invoke component with a portable identity not available parameter sends a CTMIdentityRequest return error component with the identityNotAvailable error value.

CTM_IO_IR_I_02 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMIdentityRequest invoke component with an invalid portable identity parameter sends a CTMIdentityRequest return error component with the portableIdentityUnknown error value.

CTM_IO_IR_I_03 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMIdentityRequest invoke component and when the fixed part is overloaded sends a CTMIdentityRequest return error component with the congestion error value.

CTM_IO_IR_I_04 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMIdentityRequest invoke component and when the supervision timer expires before a response has been received sends a CTMIdentityRequest return error component with the localTimerExpiry error value.

CTM_IO_IR_I_05 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMIdentityRequest invoke component and a mobility management procedure of equal priority has been requested sends a CTMIdentityRequest return error component with the priorityRuleViolation error value.

CTM_IO_IR_I_06 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMIdentityRequest invoke component and when the paging fails on the air interface sends a CTMIdentityRequest return error component with the pagingFailure error value.

CTM_IO_IR_I_07 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a CTMIdentityRequest invoke component and when the signalling connection is interrupted on the air interface sends a CTMIdentityRequest return error component with the radioConnectionFailure error value.

CTM_IO_IR_I_08 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, having received the CTMIdentityRequest invoke component and having sent the return result, on receipt of a reject component accepts the provided information and does not take any action.

5.2.4 Embedded procedures

CTM_EMB_V_01 subclauses 9.1.1.1 - 9.3.7.1 Valid Optional

Selection: support the subscription registration procedure for CTM. PICS MC1

Ensure that the IUT, having requested the subscription registration procedure by sending a CTMAccessRightsRequest invoke component and upon receiving a CTMKeyAllocate invoke component without cTMPortableIdentity parameter, sends the CTMNetworkAuthentication invoke component.

CTM_EMB_V_02 subclauses 9.1.1.1 - 9.3.2.1 Valid Optional

Selection: support the subscription registration procedure for CTM. PICS MC1

Ensure that the IUT, having requested the subscription registration procedure by sending a CTMAccessRightsRequest invoke component and upon receiving a CTMTerminalAuthentication invoke component without cTMPortableIdentity parameter, sends the CTMTerminalAuthentication return result.

CTM_EMB_V_03 subclauses 9.1.2.1 - 9.3.3.1 Valid Optional

Selection: support the subscription deregistration procedure for CTM. PICS MC1

AND

support the Network authentication procedure as an embedded procedure. PIXIT

Ensure that the IUT, having received the CTMAccessRightTerminate invoke component and in order to request the network authentication procedure as an embedded procedure sends a CTMNetworkAuthentication invoke component without the cTMPortableIdentity parameter.

CTM_EMB_V_04 subclauses 9.2.1.1 - 9.3.7.1 Valid Optional

Ensure that the IUT, having requested the location registration procedure by sending the CTMLocationRegistration invoke component and upon receiving a CTMKeyAllocate invoke component without cTMPortableIdentity parameter, sends the CTMNetworkAuthentication invoke component.

CTM_EMB_V_05 subclauses 9.2.1.1 - 9.3.2.1 Valid Optional

Ensure that the IUT, having requested the location registration procedure by sending the CTMLocationRegistration invoke component and upon receiving a CTMTerminalAuthentication invoke component without cTMPortableIdentity parameter, sends the CTMTerminalAuthentication return result.

5.2.5 Outgoing call

CTM_OC_V_01 subclause 9.3.9.1 Valid Mandatory

Ensure that the IUT when initiating an outgoing call, includes the CTMOutgoingCallMMInfo invoke component in the facility information element in the SETUP message.

CTM_OC_I_01 subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT, having sent the SETUP message with the CTMOutgoingCallMMInfo, when receiving a reject component does not take any action.

CTM_OC_I_02 subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT, having sent the SETUP message with the CTMOutgoingCallMMInfo, on receipt of a return error component with the portableIdentityUnknown error value does not take any action.

CTM_OC_I_03 subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT, having sent the SETUP message with the CTMOutgoingCallMMInfo, on receipt of a return error component with the congestionerror value does not take any action.

CTM_OC_I_04 subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT, having sent the SETUP message with the CTMOutgoingCallMMInfo, on receipt of a return error component with the unspecified error value does not take any action.

CTM_OC_I_05xx subclause 9.3.9.2 Invalid Optional

Ensure that the IUT, having sent the SETUP message with the CTMOutgoingCallMMInfo, on receipt of a return error component with the networkRejected error with the reject reason value detailed in table 7

accepts the provided information and release the transaction or proceed in the existing mode.

Table 7: Reject reason values for test purposes CTM_OC_I_0501 to CTM_OC_I_0524

Test purpose	Reject reason value
CTM_OC_I_0501	TPUI unknown
CTM_OC_I_0502	IPUI unknown
CTM_OC_I_0503	IPEI not accepted
CTM_OC_I_0504	IPUI not accepted
CTM_OC_I_0505	Authentication failed
CTM_OC_I_0506	No authentication algorithm
CTM_OC_I_0507	Authentication algorithm not supported
CTM_OC_I_0508	Authentication key not supported
CTM_OC_I_0509	No cipher algorithm
CTM_OC_I_0510	Cipher algorithm not supported
CTM_OC_I_0511	Cipher key not supported
CTM_OC_I_0512	Incompatible service
CTM_OC_I_0513	False LCE reply (no corresponding service)
CTM_OC_I_0514	Late LCE reply (service already taken)
CTM_OC_I_0515	Invalid TPUI
CTM_OC_I_0516	TPUI assignment limits unacceptable
CTM_OC_I_0517	Insufficient memory
CTM_OC_I_0518	Overload
CTM_OC_I_0519	Invalid message
CTM_OC_I_0520	Information element error
CTM_OC_I_0521	Invalid information element contents
CTM_OC_I_0522	Timer expiry
CTM_OC_I_0523	Location area not allowed
CTM_OC_I_0524	-

5.2.6 Incoming call

CTM_IC_V_01 subclause 9.3.10.1 Valid Mandatory

Ensure that the IUT when receiving a SETUP message including a CTMIncomingCallMMInfo invoke component, accepts the call request.

CTM_IC_I_01 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a CTMIncomingCallMMInfo invoke component and when a RejectReason is received from the air interface, sends the CTMIncomingCallMMInfo return result with the terminalRejected error value.

CTM_IC_I_02 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a CTMIncomingCallMMInfo invoke component with a portable Identity that is not known, sends the CTMIncomingCallMMInfo return result with the portableIdentityUnknown error value.

CTM_IC_I_03 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a CTMIncomingCallMMInfo invoke component and when the fixed part is overloaded, sends the CTMIncomingCallMMInfo return result with the congestion error value.

CTM_IC_I_04 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a CTMIncomingCallMMInfo invoke component and when the paging fails on the air interface, sends the CTMIncomingCallMMInfo return result with the pagingFailure error value.

CTM_IC_I_05 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a CTMIncomingCallMMInfo invoke component and when the signalling connection on the air interface is interrupted,
sends the CTMIncomingCallMMInfo return result with the pagingFailure error value.

5.3 DECT access to GSM mode

Selection: Support of user requirements. PICS R2.1

AND

Support of the DECT access to GSM mode. PICS R1.2

5.3.1 Activation and deactivation

5.3.1.1 Location registration

DG_AD_LR_V_01 subclause 9.2.1.1 Valid Mandatory

Ensure that the IUT in Idle state, to request a location registration
sends a GSMLocationRegistration invoke component with the following parameters: gSMPortableIdentity, gSMLocationRegistrationType, gSMLocationAreaIdentity identifying the old location area, gSMCipherInfo, gSMPortableCapabilities.

DG_AD_LR_V_02 subclause 9.2.1.1 Valid Mandatory

Ensure that the IUT having sent a GSMLocationRegistration invoke component, on receipt of the GSMLocationRegistration return result including the following parameter gSMLocationAreaIdentity, indicating the new location area
does not take any action.

DG_AD_LR_I_01 subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT having sent a GSMLocationRegistration invoke component, on receipt of a reject component
does not respond to a previously received GSMLinkedAssignIdentity invoke component.

DG_AD_LR_I_02 subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT having sent a GSMLocationRegistration invoke component, on receipt of a return result with the portableIdentityUnknown error
does not respond to a previously received GSMLinkedAssignIdentity invoke component.

DG_AD_LR_I_03 subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT having sent a GSMLocationRegistration invoke component, on receipt of a return result with the congestion error
does not respond to a previously received GSMLinkedAssignIdentity invoke component.

DG_AD_LR_I_04 subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT having sent a GSMLocationRegistration invoke component, on receipt of a return result with the unspecified error
does not respond to a previously received GSMLinkedAssignIdentity invoke component.

DG_AD_LR_I_05xx subclause 9.2.1.2 Invalid Mandatory

Ensure that the IUT, having sent a GSMLocationRegistration invoke component, on receipt of a return error component with the networkRejected error with the reject reason value detailed in table 4
does not respond to a previously received GSMLinkedAssignIdentity invoke component.

Table 8: Reject reason values for test purposes DG_AD_LR_I_0501 to DG_AD_LR_I_0519

Test purpose	Reject reason value
DG_AD_LR_I_0501	Authentication failed
DG_AD_LR_I_0502	No authentication algorithm
DG_AD_LR_I_0503	Authentication algorithm not supported
DG_AD_LR_I_0504	Authentication key not supported
DG_AD_LR_I_0505	UPI not entered
DG_AD_LR_I_0506	No cipher algorithm
DG_AD_LR_I_0507	Cipher algorithm not supported
DG_AD_LR_I_0508	Cipher key not supported
DG_AD_LR_I_0509	Incompatible service
DG_AD_LR_I_0510	Insufficient memory
DG_AD_LR_I_0511	Overload
DG_AD_LR_I_0512	Invalid message
DG_AD_LR_I_0513	Information element error
DG_AD_LR_I_0514	Invalid information element contents
DG_AD_LR_I_0515	Timer expiry
DG_AD_LR_I_0516	PLMN not allowed
DG_AD_LR_I_0517	Location area not allowed
DG_AD_LR_I_0518	National roaming not allowed in this location area
DG_AD_LR_I_0519	-

5.3.1.2 Location cancellation

Selection: Support of the subscription registration procedure for CTM. PICS MC4

DG_AD_LC_V_01 subclause 9.2.2.1 Valid Optional

Ensure that the IUT in Idle state, on receipt of a GSMLocationCancellation invoke component containing a gSMPortableIdentity,

shall accept the provided information and shall not respond to the network.

DG_AD_LC_I_01 subclause 9.2.2.2 Invalid Optional

Ensure that the IUT, having received a GSMLocationCancellation invoke component and cannot process the request does not take any action.

5.3.1.3 Detach

DG_AD_D_V_01 subclause 9.2.3.1 Valid Mandatory

Ensure that the IUT in Idle state, when it is unable to receive incoming calls (e.g. the cordless terminal is switched off), sends a GSMDetach invoke component with the following parameter: gSMPortableIdentity.

DG_AD_D_I_01 subclause 9.2.3.2 Invalid Mandatory

Ensure that the IUT having sent a GSMDetach invoke component, on receipt of a reject component considers the procedure as unsuccessful..

5.3.2 Invocation and operation

5.3.2.1 Terminal authentication

DG_IO_TA_V_01 subclause 9.3.2.1 Valid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMTerminalAuthentication invoke component including correct gSMRand, gSMCipherInfo, gSMPortableIdentity parameters,

sends the GSMTerminalAuthentication return result with the gSMRes parameter.

DG_IO_TA_I_01 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMTerminalAuthentication invoke component including correct gSMRand, gSMCipherInfo, gSMPortableIdentity parameters and if the identity of the cordless terminal included in the gSMPortableIdentity parameter is not known,

sends a GSMTerminalAuthentication return error component with the portableIdentityUnknown error value.

DG_IO_TA_I_02 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMTerminalAuthentication invoke component including correct gSMRand, gSMCipherInfo, gSMPortableIdentity parameters when the fixed part is overloaded and the IUT cannot process the request

sends a GSMTerminalAuthentication return error component with the congestion error value.

DG_IO_TA_I_03 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMTerminalAuthentication invoke component including correct gSMRand, gSMCipherInfo, gSMPortableIdentity parameters and if the paging on the air interface fails

sends a GSMTerminalAuthentication return error component with the pagingFailure error value.

DG_IO_TA_I_04 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMTerminalAuthentication invoke component including correct gSMRand, gSMCipherInfo, gSMPortableIdentity parameters and if the signalling connection on the air interface is interrupted

sends a GSMTerminalAuthentication return error component with the radioConnectionFailure error value.

DG_IO_TA_I_05 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMTerminalAuthentication invoke component including correct gSMRand, gSMCipherInfo, gSMPortableIdentity parameters and if a mobility management procedure of equal priority has been requested

sends a GSMTerminalAuthentication return error component with the priorityRuleViolation error value.

DG_IO_TA_I_06 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMTerminalAuthentication invoke component including correct gSMRand, gSMCipherInfo, gSMPortableIdentity parameters and if the supervision timer for the requested procedure expires before a response has been received

sends a GSMTerminalAuthentication return error component with the localTimerExpiry error value.

DG_IO_TA_I_07 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMTerminalAuthentication invoke component including correct gSMRand, gSMCipherInfo, gSMPortableIdentity parameters and if a reject reason is received from the air interface

sends a GSMTerminalAuthentication return error component with the terminalRejected error value.

DG_IO_TA_I_08 subclause 9.3.2.2 Invalid Mandatory

Ensure that the IUT, having received a GSMTerminalAuthentication invoke component and having sent a return result, on receipt of a GSMTerminalAuthenticationReject invoke component

does not take any action.

5.3.2.2 Network initiated ciphering**DG_IO_NIC_V_01 subclause 9.3.4.1 Valid Mandatory**

Ensure that the IUT in Idle state, on receipt of a GSMCiphering invoke component with valid gSMCipherKey, and gSMPortableIdentity parameters

enables ciphering and sends the GSMCiphering return result component.

DG_IO_NIC_I_01 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMCiphering invoke component with valid gSMCipherKey, and gSMPortableIdentity parameters and if the identity of the cordless terminal included in the gSMPortableIdentity parameter is not known,

sends a GSMCiphering return error component with the portableIdentityUnknown error value.

DG_IO_NIC_I_02 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMCiphering invoke component with valid gSMCipherKey, gSMPortableIdentity parameters and when the fixed part is overloaded

sends a GSMCiphering return error component with the congestion error value.

DG_IO_NIC_I_03 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMCiphering invoke component with valid gSMCipherKey, gSMPortableIdentity parameters and when the supervision timer for the requested procedure expires before a response has been received

sends a GSMCiphering return error component with the localTimerExpiry error value.

DG_IO_NIC_I_04 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMCIPHERING invoke component with valid gSMCIPHERKEY, gSMPORTABLEIDENTITY parameters and when the paging fails on the air interface
sends a GSMCIPHERING return error component with the pagingFailure error value.

DG_IO_NIC_I_05 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMCIPHERING invoke component with valid gSMCIPHERKEY, gSMPORTABLEIDENTITY parameters and when the signalling connection is interrupted on the air interface
sends a GSMCIPHERING return error component with the radioConnectionFailure error value.

DG_IO_NIC_I_06 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMCIPHERING invoke component with valid gSMCIPHERKEY, gSMPORTABLEIDENTITY parameters and if the ciphering has already been requested for this connection
sends a GSMCIPHERING return error component with the incompatibleCipheringState error value.

DG_IO_NIC_I_07 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMCIPHERING invoke component with valid gSMCIPHERKEY, gSMPORTABLEIDENTITY parameters and a mobility management procedure of equal priority has been requested
sends a GSMCIPHERING return error component with the priorityRuleViolation error value.

DG_IO_NIC_I_08 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMCIPHERING invoke component with valid gSMCIPHERKEY, and gSMPORTABLEIDENTITY parameters and if a reject reason is received from the air interface
sends the GSMCIPHERING return error component with the terminalRejected error value.

DG_IO_NIC_I_09 subclause 9.3.4.2 Invalid Mandatory

Ensure that the IUT, having received the GSMCIPHERING invoke component with valid gSMCIPHERKEY, and gSMPORTABLEIDENTITY parameters and having sent the return result component, on receipt of a reject component
does not take any action.

5.3.2.3 Temporary identity assignment**DG_IO_TIA_V_01 subclause 9.3.6.1.1 Valid Mandatory**

Ensure that the IUT in Idle state, on receipt of a GSMAssignIdentity invoke component with valid gSMNewTMSI, gSMLOCATIONAREAIDENTITY, gSMPORTABLEIDENTITY parameters
uses the received parameters and sends the GSMAssignIdentity return result component.

DG_IO_TIA_V_02 subclause 9.3.6.1.2 Valid Mandatory

Ensure that the IUT, having sent the GSMLocationRegistration invoke component and on receipt of a GSMLinkedAssignIdentity invoke component with valid gSMNewTMSI parameter
keeps the received parameter until reception of the GSMLocationRegistration return result component and sends the GSMLinkedAssignIdentity return result component.

DG_IO_TIA_I_01 subclause 9.3.6.2.1 Invalid Mandatory

Ensure that the IUT in Idle state, on receipt of a GSMAssignIdentity invoke component with valid gSMNewTMSI, gSMLOCATIONAREAIDENTITY, gSMPORTABLEIDENTITY parameters and if the IUT is unable to perform the assign identity procedure
does not take any action.

DG_IO_TIA_I_02 subclause 9.3.6.2.1 Invalid Mandatory

Ensure that the IUT, having received the GSMAssignIdentity invoke component with valid gSMNewTMSI, gSMLOCATIONAREAIDENTITY, gSMPORTABLEIDENTITY parameters and having sent the GSMAssignIdentity return result component, on receipt of a reject component
does not take any action.

DG_IO_TIA_I_03 subclause 9.3.6.2.2 Invalid Mandatory

Ensure that the IUT, having sent the GSMLocationRegistration invoke component, on receipt of a GSMLinkedAssignIdentity invoke component with valid gSMNewTMSI parameter and if the IUT is unable to perform the assign identity procedure
does not take any action.

DG_IO_TIA_I_04 subclause 9.3.6.2.2 Invalid Mandatory

Ensure that the IUT, having sent the GSMLocationRegistration invoke component, having received a GSMLinkedAssignIdentity invoke component with valid gSMNewTMSI parameter, and having sent the GSMLinkedAssignIdentity return result component, on receipt of a reject component does not take any action.

DG_IO_TIA_I_05 subclause 9.3.6.2.2 Invalid Mandatory

Ensure that the IUT, having sent the GSMLocationRegistration invoke component, having received a GSMLinkedAssignIdentity invoke component with valid gSMNewTMSI parameter, and if the linked GSMRegistration procedure fails
deletes the parameter received in the GSMLinkedAssignIdentity invoke component and does not respond to the network.

5.3.2.4 Identity request**DG_IO_IR_V_01 subclause 9.3.8.1 Valid Mandatory**

Ensure that the IUT, on receipt of a GSMIdentityRequest invoke component with valid gSMIdentityType indicating the identity requested, gSMPortableIdentity parameters
sends a GSMIdentityRequest return result component indicating the requested identity.

DG_IO_IR_I_01 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMIdentityRequest invoke component with gSMIdentityType parameter indicating a portable identity not available and a valid gSMPortableIdentity parameter
sends a GSMIdentityRequest return error component with the identityNotAvailable error value.

DG_IO_IR_I_02 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMIdentityRequest invoke component with valid gSMIdentityType parameter indicating the requested identity and a gSMPortableIdentity parameter indicating a not known cordless terminal
sends a GSMIdentityRequest return error component with the portableIdentityUnknown error value.

DG_IO_IR_I_03 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMIdentityRequest invoke component with valid gSMIdentityType parameter indicating the identity requested, valid gSMPortableIdentity parameter and when the fixed part is overloaded
sends a GSMIdentityRequest return error component with the congestion error value.

DG_IO_IR_I_04 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMIdentityRequest invoke component with valid gSMIdentityType parameter indicating the identity requested, valid gSMPortableIdentity parameter and when the supervision timer for the requested procedure expires before a response has been received
sends a GSMIdentityRequest return error component with the localTimerExpiry error value.

DG_IO_IR_I_05 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMIdentityRequest invoke component with valid gSMIdentityType parameter indicating the identity requested, valid gSMPortableIdentity parameter and a mobility management procedure of equal priority has been requested
sends a GSMIdentityRequest return error component with the priorityRuleViolation error value.

DG_IO_IR_I_06 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMIdentityRequest invoke component with valid gSMIdentityType parameter indicating the identity requested, valid gSMPortableIdentity parameter and when the paging fails on the air interface
sends a GSMIdentityRequest return error component with the pagingFailure error value.

DG_IO_IR_I_07 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, on receipt of a GSMIdentityRequest invoke component with valid gSMIdentityType parameter indicating the identity requested, valid gSMPortableIdentity parameter and when the signalling connection is interrupted on the air interface
sends a GSMIdentityRequest return error component with the radioConnectionFailure error value.

DG_IO_IR_I_08 subclause 9.3.8.2 Invalid Mandatory

Ensure that the IUT, having received the GSMIdentityRequest invoke component with valid gSMIdentityType parameter indicating the identity requested, valid gSMPortableIdentity parameter and having sent the GSMIdentityRequest return result component indicating the requested identity, on receipt of a reject component does not take any action.

5.3.3 Embedded procedures

DG_EMB_V_01 subclauses 9.2.1.1 - 9.3.2.1 Valid Optional

Ensure that the IUT, having requested the location registration procedure by sending the GSMLocationRegistration invoke component and upon receiving a GSMTerminalAuthentication invoke component, sends the GSMTerminalAuthentication return result with the gSMRes parameter.

DG_EMB_V_02 subclauses 9.2.1.1 - 9.3.4.1 Valid Optional

Ensure that the IUT, having requested the location registration procedure by sending the GSMLocationRegistration invoke component and upon receiving a GSMCipherring invoke component, enables cipherring and sends the GSMCipherring return result component.

DG_EMB_V_03 subclauses 9.2.1.1 - 9.3.6.1.1 Valid Optional

Ensure that the IUT, having requested the location registration procedure by sending the GSMLocationRegistration invoke component and upon receiving a GSMAssignIdentity invoke component, uses the received parameters and sends the GSMAssignIdentity return result component.

DG_EMB_V_04 subclauses 9.2.1.1 - 9.3.8.1 Valid Optional

Ensure that the IUT, having requested the location registration procedure by sending the GSMLocationRegistration invoke component and upon receiving a GSMIdentityRequest invoke component, sends a GSMIdentityRequest return result component indicating the requested identity.

5.3.4 Outgoing call

DG_OC_V_01 subclause 9.3.9.1 Valid Mandatory

Ensure that the IUT when initiating an outgoing call, sends a SETUP message including a GSMOutgoingCallMMInfo invoke component with valid gSMPortableIdentity parameter, and valid gSMBasicService parameter indicating a normal call-setup in a facility information element.

DG_OC_I_01 subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT, having sent the SETUP message with a GSMOutgoingCallMMInfo invoke component with valid gSMPortableIdentity parameter, and valid gSMBasicService parameter indicating a normal call-setup in a facility information element, when receiving a reject component does not take any action.

DG_OC_I_02xx subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT having sent a GSMOutgoingCallMMInfo invoke component, on receipt of a GSMOutgoingCallMMInfo return error component in a facility information element with the networkRejected error does not take any action.

Table 9: Reject reason values for test purposes DG_OC_I_0201 to DG_OC_I_0219

Test purpose	Reject reason value
DG_OC_I_0201	Authentication failed
DG_OC_I_0202	No authentication algorithm
DG_OC_I_0203	Authentication algorithm not supported
DG_OC_I_0204	Authentication key not supported
DG_OC_I_0205	UPI not entered
DG_OC_I_0206	No cipher algorithm
DG_OC_I_0207	Cipher algorithm not supported
DG_OC_I_0208	Cipher key not supported
DG_OC_I_0209	Incompatible service
DG_OC_I_0210	Insufficient memory
DG_OC_I_0211	Overload
DG_OC_I_0212	Invalid message
DG_OC_I_0213	Information element error
DG_OC_I_0214	Invalid information element contents
DG_OC_I_0215	Timer expiry
DG_OC_I_0216	PLMN not allowed
DG_OC_I_0217	Location area not allowed
DG_OC_I_0218	National roaming not allowed in this location area
DG_OC_I_0219	-

DG_OC_I_03 subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT having sent a GSMOutgoingCallMMInfo invoke component, on receipt of a GSMOutgoingCallMMInfo return error component in a facility information element with the portableIdentityUnknown error

does not take any action.

DG_OC_I_04 subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT having sent a GSMOutgoingCallMMInfo invoke component, on receipt of a GSMOutgoingCallMMInfo return error component in a facility information element with the congestion error

does not take any action.

DG_OC_I_05 subclause 9.3.9.2 Invalid Mandatory

Ensure that the IUT having sent a GSMOutgoingCallMMInfo invoke component, on receipt of a GSMOutgoingCallMMInfo return error component in a facility information element with the unspecified error

does not take any action.

5.3.5 Incoming call**DG_IC_V_01 subclause 9.3.10.1 Valid Mandatory**

Ensure that the IUT when receiving a SETUP message including a GSMIncomingCallMMInfo invoke component, with valid gSMPortableIdentity parameter, and valid gSMSignal parameter, in a facility information element,

accepts the call request.

DG_IC_I_01 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a GSMIncomingCallMMInfo invoke component, with valid gSMPortableIdentity parameter, and valid gSMSignal parameter, in a facility information element and when a RejectReason is received from the air interface,

sends the GSMIncomingCallMMInfo return error component within a Facility information element with the terminalRejected error value.

DG_IC_I_02 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a GSMIncomingCallMMInfo invoke component, with valid gSMPortableIdentity parameter, and valid gSMSignal parameter, in a facility information element and when the portableIdentity is not known,

sends the GSMIncomingCallMMInfo return error component within a Facility information element with the portableIdentityUnknown error value.

DG_IC_I_03 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a GSMIncomingCallMMInfo invoke component, with valid gSMPortableIdentity parameter, and valid gSMSignal parameter, in a facility information element and when the fixed part is overloaded,

sends the GSMIncomingCallMMInfo return error component within a Facility information element with the congestion error value.

DG_IC_I_04 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a GSMIncomingCallMMInfo invoke component, with valid gSMPortableIdentity parameter, and valid gSMSignal parameter, in a facility information element and when the paging fails on the air interface,

sends the GSMIncomingCallMMInfo return error component within a Facility information element with the pagingFailure error value.

DG_IC_I_05 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT when receiving a SETUP message including a GSMIncomingCallMMInfo invoke component, with valid gSMPortableIdentity parameter, and valid gSMSignal parameter, in a facility information element and when the signalling connection on the air interface is interrupted,

sends the GSMIncomingCallMMInfo return error component within a Facility information element with the radioConnectionFailure error value.

DG_IC_I_06 subclause 9.3.10.2 Invalid Mandatory

Ensure that the IUT, having sent the SETUP message including a GSMIncomingCallMMInfo invoke component, with valid gSMPortableIdentity parameter, and valid gSMSignal parameter, in a facility information element and when receiving a reject component

does not take any action.

6 Compliance

An ATS which complies with this TSS&TP specification shall:

- a) consist of a set of test cases corresponding to the set or to a subset of the TPs specified in clause 6;
- b) use a TSS which is an appropriate subset of the whole of the TSS specified in clause 4;
- c) use the same naming conventions for the test groups and test cases;
- d) maintain the relationship specified in clause 5 between the test groups and TPs and the entries in the PICS proforma to be used for test case deselection;
- e) comply with ISO/IEC 9646-2 [4].

In the case of a) or b) above, a subset shall be used only where a particular Abstract Test Method (ATM) makes some TPs untestable. All testable TPs from clause 5 shall be included in a compliant ATS.

7 Requirements for a comprehensive testing service

As a minimum the Remote test method, as specified in ISO/IEC 9646-2 [4], shall be used by any organization claiming to provide a comprehensive testing service for network equipment claiming conformance to EN 301 002-1 [6].

History

Document history		
V1.1.2	July 1999	Public Enquiry PE 9952: 1999-07-28 to 1999-11-26
V1.1.3	March 2000	Vote V 20000505: 2000-03-06 to 2000-05-05