

Draft **ETSI EN 301 453-1** V1.1.1 (2000-01)

European Standard (Telecommunications series)

**Private Integrated Services Network (PISN);
Inter-exchange signalling protocol;
Diversion supplementary services
[ISO/IEC 13873 (1995) modified];
Part 1: Test Suite Structure and Test Purposes (TSS&TP)
specification**



Reference

DEN/SPAN-05189-2

KeywordsPISN, QSIG, supplementary services, testing,
TSS&TP**ETSI**

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internetsecretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
<http://www.etsi.org>
If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	4
1 Scope	5
2 References	5
3 Definitions and abbreviations	6
3.1 Definitions	6
3.2 Abbreviations	6
4 Test Suite Structure (TSS)	6
5 Test Purpose (TP).....	7
5.1 Introduction	7
5.1.1 TP naming convention	7
5.1.2 Source of TP definition.....	7
5.1.3 TP structure.....	7
5.1.4 Test strategy.....	8
5.2 TPs for SS-CDIV	8
5.2.1 Signalling procedures at the Originating PINX	9
5.2.1.1 SS-CFU or SS-CFB.....	9
5.2.1.2 SS-CFNR	11
5.2.2 Signalling procedures at the Served User PINX.....	12
5.2.2.1 Activation.....	12
5.2.2.2 Deactivation	13
5.2.2.3 Interrogation.....	13
5.2.2.4 Invocation.....	13
5.2.2.4.1 SS-CFU or SS-CFB	13
5.2.2.4.2 SS-CFNR.....	14
5.2.3 Signalling procedures at the Rerouting PINX	14
5.2.3.1 SS-CFU or SS-CFB (Originating).....	15
5.2.3.2 SS-CFU or SS-CFB (Served User)	15
5.2.3.3 SS-CFNR (Originating).....	16
5.2.3.4 SS-CFNR (Served User)	18
5.2.4 Signalling procedures at the Diverted-to PINX	19
5.2.4.1 Invocation.....	19
5.2.4.2 Verification of the diverted-to user's number	19
5.2.5 Signalling procedures at the Activating PINX	20
5.2.6 Signalling procedures at the Deactivating PINX	20
5.2.7 Signalling procedures at the Interrogating PINX.....	21
5.2.8 Signalling Procedures for Protocol Interactions between SS-DIV and other supplementary services and ANFs.....	21
5.2.8.1 Procedures between SS-CFU/ SS-CFB and SS-CCBS.....	21
5.2.8.2 Procedures between SS-CFU/ SS-CFB/ SS-CFNR and SS-CCNR	22
5.2.8.3 Procedures between SS-CFNR and SS-CT	22
6 Compliance	23
7 Requirements for a comprehensive testing service.....	23
Bibliography	24
History	25

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document covers the Private Integrated Service Network (PISN) Inter-exchange signalling protocol -Advice of charge supplementary service - Test Suite Structure and Test Purposes (TSS&TP) specification.

The present document is part 1 of a multi-part EN covering the Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Diversion supplementary services [ISO/IEC 13873 (1995) modified], as identified below:

Part 1: "Test Suite Structure and Test Purposes (TSS&TP) specification";

Part 2: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document specifies the Test Suite Structure and Test Purposes (TSS&TP) for the Advice of charge supplementary services of the Interexchange signalling protocol for Private Integrated Services Networks (PISN).

The objective of this TSS and TPs specification is to provide conformance tests which give a greater probability of inter-operability. The TSS and TPs specification covers the procedures described in ETS 300 257 [1].

The ISO standard for the methodology of conformance testing (ISO/IEC 9646-1 [2], ISO/IEC 9646-2 [3] and ISO/IEC 9646-3 [7]) is used as basis for the test methodology.

The Test Suite Structure and Test Purposes specified in this standard are only intended for VPN scenarios at the "b" service entry point.

The VPN "b" service entry point is defined in EN 301 060-1 [4] and ETR 172 [5].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ETS 300 257 (1995): "Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Diversion supplementary services [ISO/IEC 13873 (1995) modified]".
- [2] ISO/IEC 9646-1 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 1: General concepts".
- [3] ISO/IEC 9646-2 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 2: Abstract test suite specification".
- [4] EN 301 060-1 (1998): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Basic call control; Enhancement at the "b" service entry point for Virtual Private Network (VPN) applications; Part 1: Protocol specification".
- [5] ETR 172: "Business TeleCommunications (BTC); Virtual Private Networking (VPN); Services and networking aspects; Standardization requirements and work items".
- [6] I-ETS 300 808: "Private Integrated Services Network (PISN); Cordless Terminal Mobility (CTM); Inter-exchange signalling protocol; Cordless terminal outgoing call additional network feature".
- [7] ISO/IEC 9646-3: "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; part 3:The Tree and Tabular Combined Notation (TTCN)".
- [8] ETS 300 406: "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Abstract Test Suite (ATS): refer to ISO/IEC 9646-1 [2].

Implementation Under Test (IUT): refer to ISO/IEC 9646-1 [2].

Protocol Implementation Conformance Statement (PICS): refer to ISO/IEC 9646-1 [2].

PICS proforma: refer to ISO/IEC 9646-1 [2].

Test Purpose (TP): refer to ISO/IEC 9646-1 [2].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

APDU	Application Protocol Data Unit
ASN.1	Abstract Syntax Notation no. 1
ATS	Abstract Test Suite
CDIV	Call DIVersion
CLIR	Calling/connected Line Identification restriction
CTM	Cordless Terminal Mobility
DTN	Diverted-to Number
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
NFE	Network Facility Extension
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
PINX	Private Integrated Services Network eXchange
PISN	Private Integrated Services Network
sc	call independent signalling connection
SS	Supplementary Service
SS-CDA	Call Deflection from Alert supplementary service
SS-CDI	Call Deflection Immediate supplementary service
SS-DIV	Call Diversion supplementary services
SS-CFB	Call Forwarding Busy supplementary service
SS-CFNR	Call Forwarding No reply supplementary service
TP	Test Purpose
TSS	Test Suite Structure

4 Test Suite Structure (TSS)

Signalling procedures at the Q Reference Point	Group
Signalling procedures at the Originating PINX	Orig01
Signalling procedures at the Served User PINX	
Activation	Served01
Deactivation	Served2
Interrogation	Served03

Invocation	Served04
Signalling procedures at the Rerouteing PINX	Rerout01
Signalling procedures at the Diverted-to PINX	
Invocation	Divert01
Verification of the diverted-to user	Divert02
Signalling procedures at the Activating PINX	Act01
Signalling procedures at the Deactivating PINX	Deact01
Signalling procedures at the Interrogating PINX	Inter01
Signalling Procedures for Protocol Interactions between SS-DIV and other supplementary services and ANFs	
Procedures between SS-CFU/ SS-CFB and SS-CCBS at the Originating PINX	Int01
Procedures between SS-CFU/ SS-CFB/ SS-CFNR and SS-CCNR at the Originating PINX	Int02
Procedures between SS-CFNR and SS-CT	Int03

5 Test Purpose (TP)

5.1 Introduction

For each requirement a TP is defined.

5.1.1 TP naming convention

TPs are numbered, starting at 001, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite and whether it applies to the network or the user (see table 1).

Table 1: TP identifier naming convention scheme

Identifier: <ss>_<group>_<nnn>			
<ss>	=	supplementary service:	"CDIV"
<group>	=	group	up to 8 digit field representing group reference according to TSS
<service>	=	service	CFU, CFB, CFNR
<nnn>	=	sequential number	(001-999)

5.1.2 Source of TP definition

The TPs are based on ETS 300 257 [1].

5.1.3 TP structure

Each TP has been written in a manner which is consistent with all other TPs. The intention of this is to make the TPs more readable and checkable. A particular structure has been used and this is illustrated in table 2. This table should be read in conjunction with any TP, i.e. use a TP as an example to fully understand the table.

Table 2: Structure of a single TP for SS-DIV

TP part	Text	Example
Header	<Identifier> <i>tab</i> <paragraph number in base ETS> <i>tab</i>	see table 1 subclause 0.0.0
Stimulus	Ensure that the IUT in the <basic call state> or <ANF-CTMO state> <trigger> <i>see below for message structure</i> or <goal>	N10 etc. receiving a XXXX message to request a...
Reaction	<action> <conditions> <i>if the action is sending</i> <i>see below for message structure</i> <next action>, etc. and remains in the same state or and enters state <state>	sends, saves, does, etc. using en bloc sending,...
Message structure	<message type> message containing a a) <info element> information element with b) a <field name> encoded as or including <coding of the field> and <i>back to a or b,</i>	SETUP, FACILITY, CONNECT,... Bearer capability, Facility,...
NOTE:	Text in italics will not appear in TPs and text between <> is filled in for each TP and may differ from one TP to the next.	

<service> = SS-CFU, SS-CFB, SS-CFNR

NOTE 1: As a large amount of the protocol for CFB, CFNR and CFU is independent of which of the three services is supported, the TPs have mostly been written in a general way. This ensures consistent TPs and should help in the development of consistent test cases and in their maintenance. Each TP containing "<service>" is in fact three TPs - one for each of the three services.

<service_UB> = SS-CFU, SS-CFB

NOTE 2: As a large amount of the protocol for CFB and CFU is independent of which of the three services is supported, the TPs have mostly been written in a general way. This ensures consistent TPs and should help in the development of consistent test cases and in their maintenance. Each TP containing "<service>" is in fact two TPs - one for CFU and one for CFB.

5.1.4 Test strategy

As the base standard ETS 300 257 [1] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the PICS specification ETS 300 257 [1].

The TPs are only based on conformance requirements related to the externally observable behaviour of the IUT, and are limited to conceivable situations to which a real implementation is likely to be faced (ETS 300 406 [8]).

5.2 TPs for SS-CDIV

All PICS items referred to in this subclause are as specified in ETS 300 257 [1] unless indicated otherwise by another numbered reference.

Unless specified:

- only the requirements from the point of view of the VPN "b" service entry point are considered. This implies that the interactions with other networks are out of scope of this specification and causes that the corresponding Test Purposes are not included in this specification;
- the messages indicated are valid and contain at least the mandatory information elements and possibly optional information elements;

- the information elements indicated are valid and contain at least the mandatory parameters and possibly optional parameters.

The following wording convention was defined to make the test purposes more readable:

- when a message is to be sent or received on a call independent signalling connection, the message name shall be followed by a '(sc)', e.g. CONNECT (sc) means that the CONNECT message is conveyed on a call independent signalling connection;
- all the test purposes are valid for both user and network side of the VPN b interface. In order to simplify the text and to make the test purposes more readable, only the User side Call states (Ux) are indicated in the test purposes. For the network side of the VPNb interface, the mapping table below indicates which network call state (Ny) corresponds to the user call state used in the test purpose. Equivalent call state means there that the same message flow applies from the IUT point of view (e.g. : IUT sends a SETUP message gives the call state U1 or N6).

User side call state	equivalent network side call state
U00	N00
U03	N09
U04	N07
U06	N01
U07	N04
U09	N03
U10	N10

Example :

Ensure that the IUT in the call state U1 ...

is equivalent to the following network side test purpose :

Ensure that the IUT in the call state N6 ...

5.2.1 Signalling procedures at the Originating PINX

Selection: IUT supports procedures at the Originating PINX (PICS A6).

Note : Rerouteing is executed by the Served User Pinx

5.2.1.1 SS-CFU or SS-CFB

Selection: IUT supports SS-CFU/ SS-CFB (PICS A1 and PICS A2)

CDIV_Orig01_<service_UB>_001 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Idle state, on receipt of a FACILITY PDU containing a divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB>, accepts the provided information and remains in call state U03 and enters CDO-Divert state.

CDIV_Orig01_<service_UB>_002 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Idle state, on receipt of a FACILITY PDU containing a divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB>, accepts the provided information and remains in call state U04 and enters CDO-Divert state.

CDIV_Orig01_<service_UB>_003 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Idle state, on receipt of a CONNECT PDU containing a divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB>, accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_<service_UB>_004 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Idle state, on receipt of a CONNECT PDU containing a divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB>, accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_<service_UB>_005 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Idle state, on receipt of a CONNECT PDU containing a divertingLeginformation1 invoke with a diversionReason set to <service_UB> and a divertingLeginformation3 invoke APDU,

accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and remains in CDO-Idle state.

CDIV_Orig01_<service_UB>_006 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Idle state, on receipt of a CONNECT PDU containing a divertingLeginformation1 invoke with a diversionReason set to <service_UB> and a divertingLeginformation3 invoke APDU,

accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and remains in CDO-Idle state.

CDIV_Orig01_<service_UB>_007 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt again of a FACILITY containing the divertingLeginformation1 invoke APDU,

accepts the provided information and remains in call state U03 and CDO-Divert state.

CDIV_Orig01_<service_UB>_008 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt again of a FACILITY containing the divertingLeginformation1 invoke APDU,

accepts the provided information and remains in call state U04 and CDO-Divert state.

CDIV_Orig01_<service_UB>_009 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU in a FACILITY message, on receipt of a CONNECT message containing the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB>,

accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_<service_UB>_010 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU in a FACILITY message, on receipt of a CONNECT message containing the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB>,

accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_<service_UB>_011 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt of a CONNECT message containing the divertingLeginformation1 and divertingLeginformation3 invoke APDU,

accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_<service_UB>_012 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt of a CONNECT message containing the divertingLeginformation1 and divertingLeginformation3 invoke APDU,

accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_<service_UB>_013 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt of an ALERTING message containing the divertingLeginformation3 invoke APDU,

accepts the provided information and enters call state U04 and remains in CDO-Divert state.

CDIV_Orig01_<service_UB>_014 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt of a FACILITY message containing the divertingLeginformation3 invoke APDU,

accepts the provided information and remains in call state U03 and CDO-Divert state.

CDIV_Orig01_<service_UB>_015 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLeginformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt of a FACILITY message containing the divertingLeginformation3 invoke APDU,

accepts the provided information and remains in call state U04 and CDO-Divert state.

CDIV_Orig01_<service_UB>_016 subclause 6.5.1

Ensure that the IUT, in call state U03 and CDO-Divert state, having received the divertingLegInformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt of a CONNECT message containing the divertingLegInformation3 invoke APDU,
 accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_<service_UB>_017 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLegInformation1 invoke APDU with a diversionReason set to <service_UB> in a FACILITY message, on receipt of a CONNECT message containing the divertingLegInformation3 invoke APDU,
 accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

5.2.1.2 SS-CFNR

Selection: IUT supports SS-CFNR (PICS A3)

CDIV_Orig01_CFNR_001 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Idle state, on receipt of a FACILITY PDU containing a divertingLegInformation1 invoke APDU with a diversionReason set to CFNR,
 accepts the provided information and remains in call state U04 and enters CDO-Divert state.

CDIV_Orig01_CFNR_002 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Idle state, on receipt of a CONNECT PDU containing a divertingLegInformation1 invoke APDU with a diversionReason set to CFNR,
 accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_CFNR_003 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Idle state, on receipt of a CONNECT PDU containing a divertingLegInformation1 invoke with a diversionReason set to CFNR and a divertingLegInformation3 invoke APDU,
 accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and remains in CDO-Idle state.

CDIV_Orig01_CFNR_004 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLegInformation1 invoke APDU with a diversionReason set to CFNR in a FACILITY message, on receipt again of a FACILITY containing the divertingLegInformation1 invoke APDU,
 accepts the provided information and remains in call state U04 and CDO-Divert state.

CDIV_Orig01_CFNR_005 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLegInformation1 invoke APDU with a diversionReason set to CFNR in a FACILITY message, on receipt of a CONNECT message containing the divertingLegInformation1 invoke APDU with a diversionReason set to CFNR,
 accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_CFNR_006 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLegInformation1 invoke APDU with a diversionReason set to CFNR in a FACILITY message, on receipt of a CONNECT message containing the divertingLegInformation1 and divertingLegInformation3 invoke APDU,
 accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

CDIV_Orig01_CFNR_007 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLegInformation1 invoke APDU with a diversionReason set to CFNR in a FACILITY message, on receipt of a FACILITY message containing the divertingLegInformation3 invoke APDU,
 accepts the provided information and remains in call state U04 and CDO-Divert state.

CDIV_Orig01_CFNR_008 subclause 6.5.1

Ensure that the IUT, in call state U04 and CDO-Divert state, having received the divertingLegInformation1 invoke APDU with a diversionReason set to CFNR in a FACILITY message, on receipt of a CONNECT message containing the divertingLegInformation3 invoke APDU,
 accepts the provided information sends back a CONNECT ACK PDU and enters call state U10 and CDO-Idle state.

5.2.2 Signalling procedures at the Served User PINX

5.2.2.1 Activation

Selection: IUT supports procedures at the Served User PINX activation (PICS B4)

CDIV_Served01_<service>_001 subclause 6.5.3.1.1

Ensure that the IUT, in call state U00, on receipt of a SETUP PDU (sc) containing an activateDiversionQ invoke APDU with the procedure set to <service>,

sends a CONNECT PDU containing an activateDiversionQ return result APDU to the activating PINX.

Selection: IUT does not support the procedures at the Served-User PINX verification of diverted-to number (PICS: NOT B7)

CDIV_Served01_<service>_002 subclause 6.5.3.2.1

Ensure that the IUT, in call state U00, on receipt of a SETUP PDU (sc) containing an activateDiversionQ invoke APDU with the procedure set to <service> and an invalid divertedToAddress,

sends a CONNECT PDU containing an activateDiversionQ return error APDU to the activating PINX.

Selection: IUT does not support the procedures at the Served-User PINX verification of diverted-to number (PICS: NOT B7)

CDIV_Served01_<service>_003 subclauses 6.5.3.1.1 and 6.5.3.1.4

Ensure that the IUT, in call state U00, on receipt of a SETUP PDU (sc) containing an activateDiversionQ invoke APDU with the procedure set to <service>,

sends a SETUP PDU containing a checkRestriction invoke APDU to the Diverted-to PINX(sc).

Selection: IUT supports the procedures at the Served-User PINX verification of diverted-to number (PICS: B7)

CDIV_Served01_<service>_004 subclauses 6.5.3.1.1 and 6.5.3.1.4

Ensure that the IUT, in call state U06, having received a SETUP PDU (sc) containing an activateDiversionQ invoke APDU with the procedure set to <service>, and having sent a SETUP PDU containing a checkRestriction invoke APDU to the Diverted-to PINX (sc), on receipt of a CONNECT PDU containing a checkRestriction return result APDU

sends a CONNECT PDU containing an activateDiversionQ return result APDU to the activating PINX,

clears the (sc) towards the diverted-to PINX.

Selection: IUT supports the procedures at the Served-User PINX verification of diverted-to number (PICS: B7)

CDIV_Served01_<service>_005 subclauses 6.5.3.1.1 and 6.5.3.2.4

Ensure that the IUT, in call state U06, having received a SETUP PDU (sc) containing an activateDiversionQ invoke APDU with the procedure set to <service> and an invalid divertedToAddress, and having sent a SETUP PDU containing a checkRestriction invoke APDU to the Diverted-to PINX (sc), on receipt of a CONNECT PDU containing a checkRestriction return error APDU

sends a CONNECT PDU containing an activateDiversionQ return error APDU to the activating PINX,

clears the (sc) towards the diverted-to PINX.

Selection: IUT supports the procedures at the Served-User PINX verification of diverted-to number (PICS: B7)

CDIV_Served01_<service>_006 subclauses 6.5.3.1.1 and 6.5.3.2.4

Ensure that the IUT, in call state U06, having received a SETUP PDU (sc) containing an activateDiversionQ invoke APDU with the procedure set to <service>, and having sent a SETUP PDU containing a checkRestriction invoke APDU to the Diverted-to PINX (sc), on expiry of timer T5

sends a CONNECT PDU containing an activateDiversionQ return error or return result APDU to the activating PINX,

clears the (sc) towards the diverted-to PINX.

Selection: IUT supports the procedures at the Served-User PINX verification of diverted-to number (PICS: B7)

CDIV_Served01_<service>_007 subclauses 6.5.3.1.1 and 6.5.3.2.4

Ensure that the IUT, in call state U06, having received a SETUP PDU (sc) containing an activateDiversionQ invoke APDU with the procedure set to <service>, and having sent a SETUP PDU containing a checkRestriction invoke APDU to the Diverted-to PINX (sc), on receipt of a CONNECT PDU containing a checkRestriction reject component

sends a CONNECT PDU containing an activateDiversionQ return error or return result APDU to the activating PINX,

clears the (sc) towards the diverted-to PINX.

Selection: IUT supports the procedures at the Served-User PINX verification of diverted-to number (PICS: B7)

5.2.2.2 Deactivation

Selection: IUT supports procedures at the Served User PINX deactivation (PICS B5)

CDIV_Served02_<service>_001 **subclause 6.5.3.1.2**

Ensure that the IUT, in call state U00 when <service> is activated, on receipt of a SETUP (sc) message containing a deactivateDiversionQ invoke APDU with the procedure set to <service>, sends a deactivateDiversionQ return result APDU to the activating PINX.

CDIV_Served02_<service>_002 **subclause 6.5.3.2.2**

Ensure that the IUT, in call state U00 when <service> is activated, on receipt of a SETUP (sc) message containing a deactivateDiversionQ invoke APDU with the procedure set to <service> and an invalid basicService value, sends a deactivateDiversionQ return error APDU to the activating PINX.

CDIV_Served02_<service>_003 **subclause 6.5.3.2.2**

Ensure that the IUT, in call state U00 when <service> is activated, on receipt of a SETUP (sc) message containing a deactivateDiversionQ invoke APDU with the procedure set to <service> and an invalid servedUserNr value, sends a deactivateDiversionQ return error APDU with the value invalidServedUserNr.

CDIV_Served02_<service>_004 **subclause 6.5.3.2.2**

Ensure that the IUT, in call state U00 when <service> is activated, on receipt of a SETUP (sc) message containing a deactivateDiversionQ invoke APDU with the procedure set to <service> and an invalid deactivatingUserNr value, sends a deactivateDiversionQ return error APDU to the activating PINX.

5.2.2.3 Interrogation

Selection: IUT supports procedures at the Served User PINX interrogation (PICS B6)

CDIV_Served03_<service>_001 **subclause 6.5.3.1.3**

Ensure that the IUT, in call state U00, when <service> is activated, on receipt of a SETUP (sc) message containing an interrogateDiversionQ invoke APDU with the <service> procedure, sends a interrogateDiversionQ return result APDU to the activating PINX, remains in call state U00.

CDIV_Served03_<service>_002 **subclause 6.5.3.2.3**

Ensure that the IUT, in call state U00, when <service> is not activated, on receipt of a SETUP (sc) message containing an interrogateDiversionQ invoke APDU, sends a interrogateDiversionQ return error APDU to the activating PINX, remains in call state U00.

5.2.2.4 Invocation

Selection: IUT supports the procedures at the Served User PINX invocation (PICS B8) and IUT does not support the procedures at the Rerouting PINX (NOT PICS B3)

5.2.2.4.1 SS-CFU or SS-CFB

Selection: IUT supports SS-CFU/ SS-CFB (PICS A1 and PICS A2)

CDIV_Served04_<service_UB>_001 **subclause 6.5.3.1.5**

Ensure that the IUT, in call state U09, when <service_UB> is activated and when the call diversion is detected, sends a callRerouting invoke APDU in a FACILITY message with the following mandatory parameter correctly encoded:

- the reroutingReason shall contain the value <service_UB>;
- the calledAddress shall contain the diverted-to number;
- the diversionCounter shall be set to 1;
- the pSS1InfoElement shall contain the Bearer capability information element as received in the SETUP message.

and remains in call state U09.

CDIV_Served04_<service_UB>_002 **subclause 6.5.3.1.5**

Ensure that the IUT, in call state U09, when <service_UB> is activated and when the call diversion is detected, sends a callRerouting invoke APDU in a FACILITY message with the following optional parameter correctly encoded:

- the pSS1InfoElement shall contain the High Layer Compatibility, Low layer Compatibility and progress indicator as received in the SETUP message;

the callingNumber and the callingPartySubaddress shall contain the value as received in the SETUP message.

and remains in call state U09.

CDIV_Served04_<service_UB>_003 **subclause 6.5.3.1.5**

Ensure that the IUT, in call state U09, when <service_UB> is activated and having received a SETUP message containing the divertingLegInformation2 invoke APDU,

sends a callRerouteing invoke APDU in a FACILITY message with the following parameter correctly encoded:

the originalRerouteingReason and originalCalledNr shall contain the value received in the

divertingLegInformation2 invoke APDU;

the lastRerouteingNr shall contain the number of the diverting user.

and remains in call state U09.

5.2.2.4.2 **SS-CFNR**

Selection: IUT supports SS-CFNR (PICS A3)

CDIV_Served04_CFNR_001 **subclause 6.5.3.1.5**

Ensure that the IUT, in call state U07, when CFNR is activated,

sends a callRerouteing invoke APDU in a FACILITY message with the following mandatory parameter correctly encoded:

the rerouteingReason shall contain the value CFNR;

the calledAddress shall contain the diverted-to number;

the diversionCounter shall be set to 1;

the pSS1InfoElement shall contain the Bearer capability information element as received in the SETUP message.

and remains in call state U07.

CDIV_Served04_CFNR_002 **subclause 6.5.3.1.5**

Ensure that the IUT, in call state U07, when CFNR is activated and when the call diversion is detected,

sends a callRerouteing invoke APDU in a FACILITY message with the following optional parameter correctly encoded:

the pSS1InfoElement shall contain the High Layer Compatibility, Low layer Compatibility and progress indicator as received in the SETUP message;

the callingNumber and the callingPartySubaddress shall contain the value as received in the SETUP message.

and remains in call state U07.

CDIV_Served04_CFNR_003 **subclause 6.5.3.1.5**

Ensure that the IUT, in call state U07, when CFNR is activated and having received a SETUP message containing the divertingLegInformation2 invoke APDU,

sends a callRerouteing invoke APDU in a FACILITY message with the following parameter correctly encoded:

the originalRerouteingReason and originalCalledNr shall contain the value received in the

divertingLegInformation2 invoke APDU;

the lastRerouteingNr shall contain the number of the diverting user.

and remains in call state U07.

CDIV_Served04_CFNR_004 **subclause 6.5.3.2.5**

Ensure that the IUT, in call state U07, when CFNR is activated and having received a SETUP message containing the divertingLegInformation2 invoke APDU with the diversionCounter set to the maximum value (15),

maintains the call and does not send the callRerouteing invoke APDU

and remains in call state U07.

CDIV_Served04_CFNR_005 **subclause 6.5.3.2.5**

Ensure that the IUT, in call state U07 and CDS-Inv-Idle, when CFNR is activated and having sent the callRerouteing invoke APDU and having received the callRerouteing return result, on receipt of the cfnrDivertedLegFail invoke APDU,

remains in call state U07 and CDS-Inv-Idle state

5.2.3 **Signalling procedures at the Rerouteing PINX**

Selection: IUT supports procedures at the Rerouteing PINX (PICS A3)

5.2.3.1 SS-CFU or SS-CFB (Originating)

Selection: IUT supports procedures at the Originating PINX (PICS B1) and IUT supports SS-CFU/SS-CFB (PICS A1 and PICS A2).

CDIV_Rerout01_<service_UB>_001 subclause 6.5.4.1

Ensure that the IUT, in call state U03 and CDR-Idle, on receipt of a FACILITY message containing a callRerouteing invoke APDU from the Served User PINX,

sends a callRerouteing return result APDU in a FACILITY message or in a DISCONNECT message to the Served user PINX and releases the call;

sends a SETUP message with the divertingLegInformation2 invoke APDU to the Diverted-to user PINX.

CDIV_Rerout01_<service_UB>_002 subclause 6.5.4.1

Ensure that the IUT, in call state U03 and CDR-Idle, on receipt of a FACILITY message containing a callRerouteing invoke APDU from the Served User PINX,

sends the SETUP message with the divertingLegInformation2 invoke APDU to the Diverted-to user PINX, with the following basic call information elements encoded as follows:

the calledPartyNumber shall contain the information received in the calledAddress of the callRerouteing invoke APDU;

the callingPartyNumber shall contain the information received in the callingAddress of the callRerouteing invoke APDU;

the Bearer capability shall contain the bearer capability embedded in the pSS1Element of the callRerouteing invoke APDU.

sends a callRerouteing return result APDU in a FACILITY message or in a DISCONNECT message to the Served user PINX and releases the call.

CDIV_Rerout01_<service_UB>_003 subclause 6.5.4.1

Ensure that the IUT, in call state U03 and CDR-Idle, on receipt of a FACILITY message containing a callRerouteing invoke APDU from the Served User PINX,

sends the SETUP message with the divertingLegInformation2 invoke APDU to the Diverted-to user PINX, with the following argument encoded as follows:

the diversionCounter shall contain the information received in the diversionCounter of the callRerouteing invoke APDU;

the diversionReason shall contain the value <service_UB> as received in the callRerouteing invoke APDU.

sends a callRerouteing return result APDU in a FACILITY message or in a DISCONNECT message to the Served user PINX and releases the call

CDIV_Rerout01_<service_UB>_004 subclause 6.5.4.1

Ensure that the IUT, in call state U03 and CDR-Idle, on receipt of a FACILITY message containing a callRerouteing invoke APDU from the Served User PINX,

sends the SETUP message with the divertingLegInformation2 invoke APDU to the Diverted-to user PINX, with the following optional argument encoded as follows:

the originalDiversionReason shall contain the information received in the originalDiversionReason of the callRerouteing invoke APDU;

the divertingNr shall contain the information received in the lastRerouteingNr of the callRerouteing invoke APDU;

the originalCalledNr shall contain the information received in the originalCalledNr of the callRerouteing invoke APDU.

sends a callRerouteing return result APDU in a FACILITY message or in a DISCONNECT message to the Served user PINX and releases the call

CDIV_Rerout01_<service_UB>_005 subclause 6.5.4.1

Ensure that the IUT, in call state U03, having received a FACILITY message containing a callRerouteing invoke APDU from the Served User PINX, and having sent a callRerouteing return result APDU in a FACILITY message or in a DISCONNECT message to the Served user PINX and released the call, and having sent the SETUP message with the divertingLegInformation2 invoke APDU,

establishes completely the call with the diverted-to PINX;

enters call state 10.

5.2.3.2 SS-CFU or SS-CFB (Served User)

Selection: IUT supports procedures at the Served User PINX invocation (PICS B8), and IUT supports SS-CFU/SS-CFB (PICS A1 and PICS A2)

CDIV_Rerout01_<service_UB>_006 subclause 6.5.4.1

Ensure that the IUT, in call state U09, when <service_UB> is activated, on detection of call forwarding, sends a divertingLegInformation1 invoke APDU in a FACILITY message to the Originating PINX, with the elements diversionReason, subscriptionOption and nominatedNr as received in the argument of the callRerouting invoke APDU in the elements reroutingReson, subscription option and calledAddress respectively;

sends a divertingLegInformation2 invoke APDU in a SETUP message to the Diverted-to user PINX with the following basic call information elements encoded as follows:

- the calledPartyNumber shall contain the information received in the calledAddress of the callRerouting invoke APDU;
- the callingPartyNumber shall contain the information received in the callingAddress of the callRerouting invoke APDU;
- the Bearer capability shall contain the bearer capability embedded in the pSS1Element of the callRerouting invoke APDU.

CDIV_Rerout01_<service_UB>_007 subclause 6.5.4.1

Ensure that the IUT, in call state U09, when <service_UB> is activated, on detection of call forwarding, sends a divertingLegInformation1 invoke APDU in a FACILITY message to the Originating PINX. sends a divertingLegInformation2 invoke APDU in a SETUP message to the Diverted-to user PINX with the following argument encoded as follows:

- the diversionCounter shall contain the information received in the diversionCounter of the callRerouting invoke APDU;
- the diversionReason shall contain the value <service_UB> as received in the callRerouting invoke APDU.

CDIV_Rerout01_<service_UB>_008 subclause 6.5.4.1

Ensure that the IUT, in call state U09, when <service_UB> is activated, on detection of call forwarding, sends a divertingLegInformation1 invoke APDU in a FACILITY message to the Originating PINX. sends a divertingLegInformation2 invoke APDU in a SETUP message to the Diverted-to user PINX with the following optional argument encoded as follows:

- the originalDiversionReason shall contain the information received in the originalDiversionReason of the callRerouting invoke APDU;
- the divertingNr shall contain the information received in the lastReroutingNr of the callRerouting invoke APDU;
- the originalCalledNr shall contain the information received in the originalCalledNr of the callRerouting invoke APDU.

CDIV_Rerout01_<service_UB>_009 subclause 6.5.4.1

Ensure that the IUT, in call state U09, when <service_UB> is activated, on detection of call forwarding, having sent a divertingLegInformation1 invoke APDU in a FACILITY message to the Originating PINX and having sent the SETUP message with the divertingLegInformation2 invoke APDU,

- establishes completely the call with the diverted-to PINX;
- enters call state 10.

5.2.3.3 SS-CFNR (Originating)

Selection: IUT supports procedures at the Originating PINX (PICS B1) and IUT supports SS-CFNR (PICS A3).

CDIV_Rerout01_CFNR_001 subclause 6.5.4.1

Ensure that the IUT, in call state U04 and CDR-Idle, on receipt of a FACILITY message containing a callRerouting invoke APDU from the Served User PINX,

- sends a callRerouting return result APDU in a FACILITY message;
- sends a SETUP message with the divertingLegInformation2 invoke APDU to the Diverted-to user PINX.

CDIV_Rerout01_CFNR_002 subclause 6.5.4.1

Ensure that the IUT, in call state U04 and CDR-Idle, on receipt of a FACILITY message containing a callRerouting invoke APDU from the Served User PINX,

- sends the SETUP message with the divertingLegInformation2 invoke APDU to the Diverted-to user PINX, with the following basic call information elements encoded as follows:
 - the calledPartyNumber shall contain the information received in the calledAddress of the callRerouting invoke APDU;
 - the callingPartyNumber shall contain the information received in the callingAddress of the callRerouting invoke APDU;

the Bearer capability shall contain the bearer capability embedded in the pSS1Element of the callRerouting invoke APDU.

sends a callRerouting return result APDU in a FACILITY.

CDIV_Rerout01_CFNR_003 **subclause 6.5.4.1**

Ensure that the IUT, in call state U04 and CDR-Idle, on receipt of a FACILITY message containing a callRerouting invoke APDU from the Served User PINX,

sends the SETUP message with the divertingLegInformation2 invoke APDU to the Diverted-to user PINX, with the following argument encoded as follows:

the diversionCounter shall contain the information received in the diversionCounter of the callRerouting invoke APDU;

the diversionReason shall contain the value <service_UB> as received in the callRerouting invoke APDU.

sends a callRerouting return result APDU in a FACILITY message.

CDIV_Rerout01_CFNR_004 **subclause 6.5.4.1**

Ensure that the IUT, in call state U04 and CDR-Idle, on receipt of a FACILITY message containing a callRerouting invoke APDU from the Served User PINX,

sends the SETUP message with the divertingLegInformation2 invoke APDU to the Diverted-to user PINX, with the following optional argument encoded as follows:

the originalDiversionReason shall contain the information received in the originalDiversionReason of the callRerouting invoke APDU;

the divertingNr shall contain the information received in the lastReroutingNr of the callRerouting invoke APDU;

the originalCalledNr shall contain the information received in the originalCalledNr of the callRerouting invoke APDU.

sends a callRerouting return result APDU in a FACILITY message

CDIV_Rerout01_CFNR_005 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of an ALERTING message from the Diverted-to PINX,

initiates call clearing towards the Served User PINX;

continues call establishment with the Diverted-to PINX.

CDIV_Rerout01_CFNR_006 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of a CONNECT message from the Diverted-to PINX,

initiates call clearing towards the Served User PINX;

continues call establishment with the Diverted-to PINX.

CDIV_Rerout01_CFNR_007 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of a CONNECT message from the Served User PINX,

initiates call clearing towards the Diverted-to PINX.

CDIV_Rerout01_CFNR_008 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of a DISCONNECT message from the Diverted-to PINX,

completes call clearing towards the Diverted-to PINX;

sends a cfnrDivertedLegFailed invoke APDU in a FACILITY message to the Served User PINX;

does not clear the original call.

CDIV_Rerout01_CFNR_009 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of a RELEASE message from the Diverted-to PINX,

completes call clearing towards the Diverted-to PINX;

sends a cfnrDivertedLegFailed invoke APDU in a FACILITY message to the Served User PINX;

does not clear the original call.

CDIV_Rerout01_CFNR_010 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of a RELEASE COMPLETE message from the Diverted-to PINX,

enters state U00 towards the Diverted-to PINX;

sends a cfnrDivertedLegFailed invoke APDU in a FACILITY message to the Served User PINX;

does not clear the original call.

CDIV_Rerout01_CFNR_011 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of a DISCONNECT message from the Served User PINX,

completes call clearing towards the Served User PINX;
 initiates call clearing towards the Diverted-to PINX.

CDIV_Rerout01_CFNR_012 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of a RELEASE message from the Served User PINX,

completes call clearing towards the Served User PINX;
 initiates call clearing towards the Diverted-to PINX.

CDIV_Rerout01_CFNR_013 **subclause 6.5.4.1**

Ensure that the IUT in call state U04 and in CDR-Invoked state, on receipt of a RELEASE COMPLETE message from the Served User PINX,

completes call clearing towards the Served User PINX;
 initiates call clearing towards the Diverted-to PINX.

5.2.3.4 SS-CFNR (Served User)

Selection: IUT supports procedures at the Served User PINX invocation (PICS B8), and IUT supports SS-CFNR (PICS A3)

CDIV_Rerout01_CFNR_014 **subclause 6.5.4.1**

Ensure that the IUT, in call state U07, when CFNR is activated, on detection of call forwarding,

sends a divertingLegInformation1 invoke APDU in a FACILITY message to the Originating PINX, with the elements diversionReason, subscriptionOption and nominatedNr as received in the argument of the callRerouteing invoke APDU in the elements rerouteingReson, subscription option and calledAddress respectively;

sends a divertingLegInformation2 invoke APDU in a SETUP message to the Diverted-to user PINX with the following basic call information elements encoded as follows:

the calledPartyNumber shall contain the information received in the calledAddress of the callRerouteing invoke APDU;

the callingPartyNumber shall contain the information received in the callingAddress of the callRerouteing invoke APDU;

the bearer capability shall contain the bearer capability embedded in the pSS1Element of the callRerouteing invoke APDU.

CDIV_Rerout01_CFNR_015 **subclause 6.5.4.1**

Ensure that the IUT, in call state U07, when CFNR is activated, on detection of call forwarding,

sends a divertingLegInformation1 invoke APDU in a FACILITY message to the Originating PINX.

sends a divertingLegInformation2 invoke APDU in a SETUP message to the Diverted-to user PINX with the following argument encoded as follows:

the diversionCounter shall contain the information received in the diversionCounter of the callRerouteing invoke APDU;

the diversionReason shall contain the value CFNR as received in the callRerouteing invoke APDU.

CDIV_Rerout01_CFNR_016 **subclause 6.5.4.1**

Ensure that the IUT, in call state U07, when CFNR is activated, on detection of call forwarding,

sends a divertingLegInformation1 invoke APDU in a FACILITY message to the Originating PINX.

sends a divertingLegInformation2 invoke APDU in a SETUP message to the Diverted-to user PINX with the following optional argument encoded as follows:

the originalDiversionReason shall contain the information received in the originalDiversionReason of the callRerouteing invoke APDU;

the divertingNr shall contain the information received in the lastRerouteingNr of the callRerouteing invoke APDU;

the originalCalledNr shall contain the information received in the originalCalledNr of the callRerouteing invoke APDU.

CDIV_Rerout01_CFNR_017 **subclause 6.5.4.1**

Ensure that the IUT in call state U07 and in CDR-Invoked state, on receipt of an ALERTING message from the Diverted-to PINX,

sends a divertingLegInformation1 invoke APDU in a FACILITY message to the Originated PINX.

CDIV_Rerout01_CFNR_018 **subclause 6.5.4.1**

Ensure that the IUT in call state U07 and in CDR-Invoked state, having received the ALERTING message, on receipt of a CONNECT message from the Diverted-to PINX,

sends a divertingLegInformation3 invoke APDU in a CONNECT message to the Originated PINX.

CDIV_Rerout01_CFNR_019 **subclause 6.5.4.2**

Ensure that the IUT in call state U07 and in CDR-Invoked state, on receipt of a DISCONNECT message from the Diverted-to PINX,

- completes call clearing towards the Diverted-to PINX;
- does not clear the original call.

CDIV_Rerout01_CFNR_020 **subclause 6.5.4.2**

Ensure that the IUT in call state U07 and in CDR-Invoked state, on receipt of a RELEASE message from the Diverted-to PINX,

- completes call clearing towards the Diverted-to PINX;
- does not clear the original call.

CDIV_Rerout01_CFNR_021 **subclause 6.5.4.2**

Ensure that the IUT in call state U07 and in CDR-Invoked state, on receipt of a RELEASE COMPLETE message from the Diverted-to PINX,

- enters state U00 towards the Diverted-to PINX;
- does not clear the original call.

CDIV_Rerout01_CFNR_022 **subclause 6.5.4.2**

Ensure that the IUT in call state U07 and in CDR-Invoked state, on receipt of a DISCONNECT message from the Originating PINX,

- completes call clearing towards the Originating PINX;
- initiates call clearing towards the Diverted-to PINX.

CDIV_Rerout01_CFNR_023 **subclause 6.5.4.2**

Ensure that the IUT in call state U07 and in CDR-Invoked state, on receipt of a RELEASE message from the Originating PINX,

- completes call clearing towards the Originating PINX;
- initiates call clearing towards the Diverted-to PINX.

CDIV_Rerout01_CFNR_024 **subclause 6.5.4.2**

Ensure that the IUT in call state U07 and in CDR-Invoked state, on receipt of a RELEASE COMPLETE message from the Originating PINX,

- enters state U00 towards the Originating PINX;
- initiates call clearing towards the Diverted-to PINX.

5.2.4 Signalling procedures at the Diverted-to PINX

5.2.4.1 Invocation

Selection: IUT supports procedures at the Diverted-to PINX invocation (PICS B9)

CDIV_Divert01_<service>_001 **subclause 6.5.5.1.1**

Ensure that IUT, in call state U00, on receipt of a SETUP message containing a divertingLegInformation2 invoke APDU with the diversionReason set to <service>,

- sends an CALL PROCEEDING or ALERTING message
- respectively enters call state U09 or U07.

CDIV_Divert01_<service>_002 **subclause 6.5.5.1.1**

Ensure that IUT, in call state U00 and when presentation restriction applies, on receipt of a SETUP message containing a divertingLegInformation2 invoke APDU with the diversionReason set to <service>,

- sends a divertingLegInformation3 invoke APDU in a FACILITY, ALERTING or CONNECT message.

CDIV_Divert01_<service>_003 **subclause 6.5.5.1.1**

Ensure that IUT, in call state U00 and when presentation restriction applies, on receipt of a SETUP message containing a divertingLegInformation2 invoke APDU with the diversionReason set to <service>,

- sends a divertingLegInformation3 invoke APDU with a FACILITY, ALERTING or CONNECT message.

Selection: IUT supports sending of redirectionName element in divertingLegInformation3 APDU (PICS C1)

5.2.4.2 Verification of the diverted-to user's number

Selection: IUT supports procedures at the Diverted-to PINX verification of the diverted-to number (PICS B10)

CDIV_Divert02_001 **subclause 6.5.5.1.2**

Ensure that IUT, in call state U00, on receipt of a SETUP message (sc) containing a checkRestriction invoke APDU,

- sends a checkRestriction return result APDU.

CDIV_Divert02_002 **subclause 6.5.5.2.2**

Ensure that IUT, in call state U00, on receipt of a SETUP message (sc) containing a checkRestriction invoke APDU with an invalid basic service,

sends a checkRestriction return error APDU.

CDIV_Divert02_003 **subclause 6.5.5.2.2**

Ensure that IUT, in call state U00, on receipt of a SETUP message (sc) containing a checkRestriction invoke APDU with an invalid diverted-to number,

sends a checkRestriction return error APDU with the error value invalidDivertedToNr.

CDIV_Divert02_004 **subclause 6.5.5.2.2**

Ensure that IUT, in call state U00, on receipt of a SETUP message (sc) containing a checkRestriction invoke APDU with an invalid Served User number,

sends a checkRestriction return error APDU with the error value invalidServedUserNr.

5.2.5 Signalling procedures at the Activating PINX

Selection: IUT supports procedures at the Activating PINX (PICS B11)

CDIV_Act01_<service>_001 **subclause 6.5.6.1**

Ensure that the IUT, in call state U00, to activate <service>,

sends an activateDiversionQ invoke APDU in a SETUP (sc) message.

CDIV_Act01_<service>_002 **subclause 6.5.6.1**

Ensure that the IUT, in CDA-Wait state, having sent an activateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of an activateDiversionQ return result APDU,

accepts the provided information and optionally clear the call.

CDIV_Act01_<service>_003 **subclause 6.5.6.2**

Ensure that the IUT, in CDA-Wait state, having sent an activateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of an activateDiversionQ return error APDU,

accepts the provided information and optionally clear the call.

CDIV_Act01_<service>_004 **subclause 6.5.6.2**

Ensure that the IUT, in CDA-Wait state, having sent an activateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of a reject APDU,

accepts the provided information and optionally clear the call.

CDIV_Act01_<service>_005 **subclause 6.5.6.2**

Ensure that the IUT, in CDA-Wait state, having sent an activateDiversionQ invoke APDU in a SETUP (sc) message, at expiry of timer T2,

does not take any action or clears the call.

5.2.6 Signalling procedures at the Deactivating PINX

Selection: IUT supports procedures at the Deactivating PINX (PICS B12)

CDIV_Deact01_<service>_001 **subclause 6.5.7.1**

Ensure that the IUT, in call state U00, to deactivate <service>,

sends an deactivateDiversionQ invoke APDU in a SETUP (sc) message.

CDIV_Deact01_<service>_002 **subclause 6.5.7.1**

Ensure that the IUT, in CDA-Wait state, having sent an deactivateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of an deactivateDiversionQ return result APDU,

accepts the provided information and optionally clears the call.

CDIV_Deact01_<service>_003 **subclause 6.5.7.2**

Ensure that the IUT, in CDA-Wait state, having sent an deactivateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of an deactivateDiversionQ return error APDU,

accepts the provided information and optionally clears the call.

CDIV_Deact01_<service>_004 **subclause 6.5.7.2**

Ensure that the IUT, in CDA-Wait state, having sent an deactivateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of a reject APDU,

accepts the provided information and optionally clears the call.

CDIV_Deact01_<service>_005 **subclause 6.5.7.2**

Ensure that the IUT, in CDA-Wait state, having sent an deactivateDiversionQ invoke APDU in a SETUP (sc) message, at expiry of timer T2,

does not take any action or clears the call.

5.2.7 Signalling procedures at the Interrogating PINX

Selection: IUT supports procedures at the Interrogating PINX (PICS B13)

CDIV_Inter01_<service>_001 **subclause 6.5.8.1**

Ensure that IUT, in call state U00, to interrogate <service>,

sends an interrogateDiversionQ invoke APDU in a SETUP (sc) message.

CDIV_Inter01_<service>_002 **subclause 6.5.8.1**

Ensure that IUT, in CDA-Wait state, having sent an interrogateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of an interrogateDiversionQ return result APDU,

accepts the provided information and optionally clears the call.

CDIV_Inter01_<service>_003 **subclause 6.5.8.2**

Ensure that IUT, in CDA-Wait state, having sent an interrogateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of an interrogateDiversionQ return error APDU,

accepts the provided information and optionally clears the call.

CDIV_Inter01_<service>_004 **subclause 6.5.8.2**

Ensure that IUT, in CDA-Wait state, having sent an interrogateDiversionQ invoke APDU in a SETUP (sc) message, on receipt of a reject APDU,

accepts the provided information and optionally clears the call.

CDIV_Inter01_<service>_005 **subclause 6.5.8.2**

Ensure that IUT, in CDA-Wait state, having sent an interrogateDiversionQ invoke APDU in a SETUP (sc) message, at expiry of timer T2,

does not take any action or clears the call.

5.2.8 Signalling Procedures for Protocol Interactions between SS-DIV and other supplementary services and ANFs

5.2.8.1 Procedures between SS-CFU/ SS-CFB and SS-CCBS

Selection: IUT supports Originating PINX procedures for invoking SS-CCBS at a SS-CFU/SS- CFB diverted-to User (PICS E2 or PICS G2).

CDIV_Int01_<service> **subclauses 6.8.1.3.1 and 6.8.1.3.2**

Ensure that the IUT in call state U00, receiving a FACILITY message for CR1 containing in the Facility IE a divertingLegInformation1 invoke APDU including in the element "nominatedNr" the party number of the diverted-to User,

sends a SETUP (sc) message reflecting in the called party number IE the "nominatedNr" and containing in the Facility IE a cbsRequest invoke APDU including in the element "numberB" the "nominatedNr".

5.2.8.2 Procedures between SS-CFU/ SS-CFB/ SS-CFNR and SS-CCNR

Selection: IUT supports Originating PINX procedures for invoking SS-CCNR at a SS-CFU/SS- CFB/SS-CFNR diverted-to User (PICS F2 or PICS H2 or PICS I2).

CDIV_Int02_<service> subclauses 6.8.1.4.1 and 6.8.2.4.1

Ensure that the IUT in call state U00, receiving a FACILITY message for CR1 containing in the Facility IE a divertingLegInformation1 invoke APDU including in the element "nominatedNr" the party number of the diverted-to User,

sends a SETUP (sc) message reflecting in the called party number IE the "nominatedNr" and containing in the Facility IE a ccnrRequest invoke APDU including in the element "numberB" the "nominatedNr".

5.2.8.3 Procedures between SS-CFNR and SS-CT

CDIV_Int03_CFNR_01 subclause 6.8.3.5.2

Ensure that the IUT in the state CT-Idle, while performing call forwarding by rerouteing and on receipt of a valid callTransferInvoke request from User A

does not take any action

remains in state CT-Idle.

Selection: IUT supports actions at a Transferring PINX for join or rerouteing and SS-CFNR Originating PINX (PICS J5).

CDIV_Int03_CFNR_02 subclause 6.8.3.5.3

Ensure that the IUT in the state CT-Idle, and protocol control state is Active, after initiating a call forwarding by Callrerouteing on receiving a FACILITY message containing a callTransferIdentify invoke APDU from the Transferring PINX,

sends a FACILITY message containing a callTransferIdentify return error APDU to the Transferring PINX containing error value supplementaryServiceInteractionNotAllowed,

remains in state CT-Idle.

Selection: IUT supports actions at a Secondary PINX for rerouteing and SS-CFNR Served User PINX (PICS J6).

CDIV_Int03_CFNR_03 subclause 6.8.3.5.4

Ensure that the IUT in the state CT-Idle, and protocol control state is Active, after initiating a call forwarding by forward switching on receiving a FACILITY message containing a callTransferIdentify invoke APDU from the Transferring PINX,

sends a FACILITY message containing a callTransferIdentify return error APDU to the Transferring PINX containing error value supplementaryServiceInteractionNotAllowed,

remains in state CT-Idle.

Selection: IUT supports actions at a Secondary PINX for rerouteing and SS-CFNR Served User/Rerouteing PINX (PICS J7).

CDIV_Int03_CFNR_04 subclause 6.8.3.5.5

Ensure that the IUT in the state CT-Idle, and protocol control state is Active, after initiating a call forwarding by forward switching on receiving a FACILITY message containing a callTransferComplete invoke APDU from the Transferring PINX,

does not take any action,

remains in state CT-Idle.

Selection: IUT supports actions at a Secondary PINX for join and SS-CFNR Served User/Rerouteing PINX (PICS J8).

6 Compliance

An ATS which complies with this TSS&TP specification shall:

- a) consist of a set of test cases corresponding to the set or to a subset of the TPs specified in clause 5;
- b) use a TSS which is an appropriate subset of the whole of the TSS specified in clause 4;
- c) use the same naming conventions for the test groups and test cases;
- d) maintain the relationship specified in clause 5 between the test groups and TPs and the entries in the PICS proforma to be used for test case deselection;
- e) comply with ISO/IEC 9646-2 [3].

In the case of a) or b) above, a subset shall be used only where a particular Abstract Test Method (ATM) makes some TPs untestable. All testable TPs from clause 5 shall be included in a compliant ATS.

7 Requirements for a comprehensive testing service

As a minimum the Remote test method, as specified in ISO/IEC 9646-2 [3], shall be used by any organization claiming to provide a comprehensive testing service for network equipment claiming conformance to I-ETS 300 808 [6].

Bibliography

The following material, though not specifically referenced in the body of the present document (or not publicly available), gives supporting information.

- EN 300 172: "Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Circuit-mode basic services [ISO/IEC 11572 (1996) modified]" Version 1.4.1.
- ETS 300 239 (1995): "Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Generic functional protocol for the support of supplementary services [ISO/IEC 11582 (1995), modified]" 2nd edition.
- ITU-T Recommendation I.112 (1993): "Vocabulary of terms for ISDNs".
- ITU-T Recommendation I.210 (1993): "Principles of the telecommunication services supported by an ISDN and the means to describe them".

History

Document history			
V1.1.1	January 2000	Public Enquiry	PE 200018: 2000-01-05 to 2000-05-05