

Final draft **ETSI EN 301 489-5** V1.2.1 (2000-05)

Candidate Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
ElectroMagnetic Compatibility (EMC) standard
for radio equipment and services;
Part 5: Specific conditions for Private land Mobile
Radio (PMR) and ancillary equipment
(speech and non-speech)**



Reference

DEN/ERM-EMC-219-5

Keywords

EMC, PMR, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).

In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights.....	5
Foreword	5
1 Scope	7
2 References	7
3 Definitions and abbreviations	8
3.1 Definitions	8
3.2 Abbreviations	8
4 Test conditions	8
4.1 General	8
4.2 Arrangements for test signals	8
4.2.1 Arrangements for test signals at the input of transmitters	9
4.2.2 Arrangements for test signals at the output of transmitters	9
4.2.3 Arrangements for test signals at the input of receivers	9
4.2.4 Arrangements for test signals at the output of receivers	9
4.2.5 Arrangements for testing transmitter and receiver together (as a system).....	9
4.3 Exclusion bands.....	9
4.3.1 Receiver and receivers of transceivers exclusion band	9
4.3.2 Transmitter exclusion band.....	9
4.4 Narrow band responses of receivers	9
4.5 Normal test modulation	10
5 Performance assessment.....	10
5.1 General	10
5.2 Equipment which can provide a continuous communications link	10
5.3 Equipment which does not provide a continuous communications link	11
5.4 Ancillary equipment	11
5.5 Equipment classification.....	11
6 Performance criteria	11
6.1 General	11
6.2 Performance criteria for Continuous phenomena applied to Transmitters (CT).....	11
6.3 Performance criteria for Transient phenomena applied to Transmitters (TT)	12
6.4 Performance criteria for Continuous phenomena applied to Receivers (CR)	12
6.5 Performance criteria for Transient phenomena applied to Receivers (TR)	12
6.6 Performance criteria for ancillary equipment tested on a stand alone basis	12
7 Applicability overview.....	12
7.1 Emission.....	12
7.1.1 General.....	12
7.1.2 Special conditions.....	12
7.2 Immunity	13
7.2.1 General.....	13
7.2.2 Special conditions.....	13
Annex A (informative): Examples of PMR equipment within the scope of the present document	14
A.1 Non-integral antenna PMR equipment.....	14
A.2 Integral antenna PMR equipment.....	14
A.3 Narrowband channel non-integral PMR equipment	14

Bibliography	15
History	17

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Candidate Harmonized European Standard (Telecommunications series) has been produced by the ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Voting phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under the Council Directive 98/34/EC [4] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulation.

The present document covers both analogue and digital Private land Mobile Radio (PMR) equipment.

The present document, together with EN 301 489-1 [1], is intended to become a Harmonized EMC Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Council Directive on the approximation of the laws of the Member States relating to electromagnetic compatibility (the "EMC Directive" 89/336/EEC [3] as amended), and the Council Directive on the approximation of the laws of the Member States relating to radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (the "R&TTE Directive" 1999/5/EC [2]).

The present document is part 1 of a multi-part EN covering the ElectroMagnetic Compatibility (EMC) standard for radio equipment and services, as identified below:

- Part 1: "Common technical requirements";
- Part 2: "Specific conditions for radio paging equipment";
- Part 3: "Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 40 GHz";
- Part 4: "Specific conditions for fixed radio links and ancillary equipment and services";
- Part 5: "Specific conditions for Private land Mobile Radio (PMR) and ancillary equipment (speech and non-speech)";**
- Part 6: "Specific conditions for Digital Enhanced Cordless Telecommunications (DECT) equipment";
- Part 7: "Specific conditions for mobile and portable radio and ancillary equipment of digital cellular radio telecommunications systems (GSM and DCS)";
- Part 8: "Specific requirements for GSM base stations";
- Part 9: "Specific conditions for wireless microphones and similar Radio Frequency (RF) audio link equipment";
- Part 10: "Specific conditions for First (CT1 and CT1+) and Second Generation Cordless Telephone (CT2) equipment";
- Part 11: "Specific conditions for FM broadcasting transmitters";

- Part 12: "Specific conditions for Earth Stations operated in the frequency ranges between 4 GHz and 30 GHz in the Fixed Satellite Service (FSS)";
- Part 13: "Specific conditions for Citizens' Band (CB) radio and ancillary equipment (speech and non-speech)";
- Part 15: "Specific conditions for commercially available amateur radio equipment";
- Part 16: "Specific conditions for analogue cellular radio communications equipment, mobile and portable";
- Part 17: "Specific requirements for Wideband data and HIPERLAN";
- Part 18: "Specific requirements for Terrestrial Trunked Radio (TETRA)";
- Part 19: "Specific conditions for Receive Only Mobile Earth Stations (ROMES) operating in the 1,5 GHz band providing data communications";
- Part 20: "Specific conditions for Mobile Earth Stations (MES) used in the Mobile Satellite Services (MSS)";
- Part 22: "Specific requirements for VHF aeronautical mobile and fixed radios".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	36 months after doa

1 Scope

The present document, together with EN 301 489-1 [1], covers the assessment of Private land Mobile Radio (PMR) and associated ancillary equipment, in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port and emissions from the enclosure port of Private land Mobile Radio (PMR) equipment are not included in the present document. Such technical specifications are found in the relevant product standards for the effective use of the radio spectrum.

The present document specifies the applicable test conditions, performance assessment and performance criteria for Private land Mobile Radio (PMR) equipment and associated ancillary equipment.

Examples of Private Mobile Radio equipment are given in annex A.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and EN 301 489-1 [1], the provisions of the present document take precedence.

The environmental classification and the emission and immunity requirements used in the present document are as stated in EN 301 489-1 [1], except for any special conditions included in the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ETSI EN 301 489-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements".
- [2] 1999/5/EC: "Council Directive on the approximation of the laws of the Member States relating to radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity".
- [3] 89/336/EEC: "Council Directive on the approximation of the laws of the Member States relating to electromagnetic compatibility".
- [4] Council Directive 98/34/EC: "Council Directive on laying down a procedure for the provision of information in the field of technical standards and regulations".
- [5] ETSI ETS 300 086: "Radio Equipment and Systems (RES); Land mobile group; Technical characteristics and test conditions for radio equipment with an internal or external RF connector intended primarily for analogue speech".
- [6] ETSI I-ETS 300 219: "Radio Equipment and Systems (RES); Land mobile service; Technical characteristics and test conditions for radio equipment transmitting signals to initiate a specific response in the receiver".

- [7] ETSI ETS 300 113: "Radio Equipment and Systems (RES); Land mobile service; Technical characteristics and test conditions for radio equipment intended for the transmission of data (and speech) and having an antenna connector".
- [8] ETSI ETS 300 296: "Radio Equipment and Systems (RES); Land mobile service; Technical characteristics and test conditions for radio equipment using integral antennas intended primarily for analogue speech".
- [9] ETSI ETS 300 341: "Radio Equipment and Systems (RES); Land mobile service; Technical characteristics and test conditions for radio equipment using an integral antenna transmitting signals to initiate a specific response in the receiver".
- [10] ETSI ETS 300 390: "Radio Equipment and Systems (RES); Land mobile service; Technical characteristics and test conditions for radio equipment intended for the transmission of data (and speech) and using an integral antenna".
- [11] ETSI EN 301 166: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Technical characteristics and test conditions for radio equipment for analogue and/or digital communication (speech and/or data) and operating on narrowband channels and having an antenna connector".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions of EN 301 489-1 [1], clause 3, apply as appropriate.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BER	Bit Error Ratio
CR	Continuous phenomena applied to Receivers
CT	Continuous phenomena applied to Transmitters
EUT	Equipment Under Test
PMR	Private land Mobile Radio
TR	Transient phenomena applied to Receivers
TT	Transient phenomena applied to Transmitters

4 Test conditions

For the purposes of the present document, the test conditions of EN 301 489-1 [1], clause 4, shall apply as appropriate. Further product related test conditions for PMR equipment are specified in the present document.

4.1 General

For emission and immunity tests the test modulation, test arrangements, etc., as specified in the present document, subclauses 4.1 to 4.5, shall apply.

4.2 Arrangements for test signals

The provisions of EN 301 489-1 [1], subclause 4.2 shall apply.

4.2.1 Arrangements for test signals at the input of transmitters

The provisions of EN 301 489-1 [1], subclause 4.2.1 shall apply.

4.2.2 Arrangements for test signals at the output of transmitters

The provisions of EN 301 489-1 [1], subclause 4.2.2 shall apply with the following modification.

The transmitter shall be operated at its maximum rated RF output power, modulated with normal test modulation (subclause 4.5).

4.2.3 Arrangements for test signals at the input of receivers

The provisions of EN 301 489-1 [1], subclause 4.2.3 shall apply with the following modification.

A communication link shall be established at the start of the test and maintained during the test.

4.2.4 Arrangements for test signals at the output of receivers

The provisions of EN 301 489-1 [1], subclause 4.2.4 shall apply.

4.2.5 Arrangements for testing transmitter and receiver together (as a system)

The provisions of EN 301 489-1 [1], subclause 4.2.5 shall apply with the following modification.

For the immunity tests of duplex transceivers, the EUT may be configured in the repeater mode, consistent with the conditions given above.

4.3 Exclusion bands

The provisions of EN 301 489-1 [1], subclause 4.3 shall apply.

4.3.1 Receiver and receivers of transceivers exclusion band

The exclusion band for receivers and receivers of transceivers is the frequency range determined by the switching range, as declared by the manufacturer, extended as follows:

- the lower frequency of the exclusion band is the lower frequency of the switching range, minus 5 % of the centre frequency of the switching range, or minus 10 MHz, whichever will result in the lowest frequency;
- the upper frequency of the exclusion band is the upper frequency of the switching range, plus 5 % of the centre frequency of the switching range, or plus 10 MHz, which ever will result in the highest frequency.

The switching range is the maximum frequency range over which the receiver can be operated without reprogramming or realignment.

4.3.2 Transmitter exclusion band

The exclusion band for transmitters extends ± 25 kHz from the nominal operating frequency of the transmitter.

4.4 Narrow band responses of receivers

The provision of EN 301 489-1 [1], subclause 4.4 shall apply.

4.5 Normal test modulation

For analogue speech equipment:

Angle modulated equipment:

- the receiver wanted input signal shall be set to the nominal frequency of the receiver modulated with a sinusoidal audio frequency of 1 000 Hz to a deviation of 60 % peak system;
- the transmitter of the EUT shall be modulated with a sinusoidal audio frequency of 1 000 Hz at a deviation of 60 % peak system deviation.

Non-angle modulated equipment:

- the receiver wanted input signal shall be set to the nominal frequency of the receiver suitably modulated with a sinusoidal audio frequency of 1 000 Hz, which represents normal operation;
- the transmitter of the EUT shall be suitably modulated with a sinusoidal audio frequency of 1 000 Hz, which represents normal operation;
- details concerning the modulation used shall be recorded in the test report.

For digital speech equipment:

- the receiver wanted input signal shall be set to the nominal frequency of the receiver modulated with a test signal specified by the manufacturer which represents normal operation which is in accordance with the appropriate radio product standard;
- the transmitter shall be modulated with a test signal which represents normal operation as specified by the manufacturer which is in accordance with the appropriate radio product standard;
- the manufacturer may have to supply the test modulation/de-modulation equipment;
- details concerning the modulation used shall be recorded in the test report.

For non-speech equipment (data, specific response, etc.):

- the receiver wanted input signal shall be set to the nominal frequency of the receiver modulated with a test signal specified by the manufacturer which represents normal operation which is in accordance with the appropriate radio product standard;
- the transmitter shall be modulated with a test signal which represents normal operation as specified by the manufacturer which is in accordance with the appropriate radio product standard;
- the manufacturer may have to supply the test modulation/de-modulation equipment;
- details concerning the modulation used shall be recorded in the test report.

The test signal generator (modulation) shall be able to produce a continuous stream of data or a repetitive message.

The test signal receiver (de-modulator) shall be, where appropriate, able to produce a readout of Bit Error Ratio (BER) of a continuous data stream or a repetitive readout of message acceptance.

5 Performance assessment

5.1 General

The provision of EN 301 489-1 [1], subclause 5.1 shall apply.

5.2 Equipment which can provide a continuous communications link

The provision of EN 301 489-1 [1], subclause 5.2 shall apply.

5.3 Equipment which does not provide a continuous communications link

The provision of EN 301 489-1 [1], subclause 5.3 shall apply.

5.4 Ancillary equipment

The provision of EN 301 489-1 [1], subclause 5.4 shall apply.

5.5 Equipment classification

The provision of EN 301 489-1 [1], subclause 5.5 shall apply.

6 Performance criteria

6.1 General

The equipment shall meet the minimum performance criteria as specified in subclauses 6.2, 6.3, 6.4 and 6.5.

The establishment of the communication link at the start of the test, its maintenance and the assessment of the recovered signal are used as the performance criteria for the evaluation of the essential functions of the equipment during and after the test.

If an equipment is of a specialized nature and the performance criteria specified in the table are not appropriate the manufacturer shall declare a substituted specification for an acceptable performance level or performance degradation as required by the present document. The performance specification shall be included in the test report and the product description and documentation.

The performance criteria specified by the manufacturer shall give the same degree of immunity protection as called for in the following subclauses.

6.2 Performance criteria for Continuous phenomena applied to Transmitters (CT)

For speech equipment, the distortion of the audio signal shall be measured during each individual exposure in the test sequence and shall not exceed 25 % measured in a post detection bandwidth determined by a first order band pass filter with a 3 dB bandwidth of 300 Hz to 3 kHz, without the use of psophometrical weighting filter.

For equipment which can be measured using continuous bit streams, a bit error shall not exceed 1×10^{-2} .

For other non-speech equipment four messages out of five or 90 % of the transmitted symbols shall be received correctly.

At the conclusion of the test the EUT shall operate as intended with no loss of user control functions or stored data, and the communication link shall have been maintained during the test.

Where the EUT is a transmitter only and can be operated in standby mode, tests shall be repeated with the EUT in this mode to ensure that unintentional transmission does not occur.

6.3 Performance criteria for Transient phenomena applied to Transmitters (TT)

At the conclusion of each exposure the EUT shall operate with no user noticeable loss of the communication link.

At the conclusion of the total test comprising the series of individual exposures the EUT shall operate as intended with no loss of user control functions or stored data, as declared by the manufacturer, and the communication link shall have been maintained during the test.

Where the EUT is a transmitter only and can be operated in standby mode, tests shall be repeated with the EUT in this mode to ensure that unintentional transmission does not occur.

6.4 Performance criteria for Continuous phenomena applied to Receivers (CR)

For speech equipment, the distortion of the audio signal shall be measured during each individual exposure in the test sequence and shall not exceed 25 % measured in a post detection bandwidth determined by a first order band pass filter with a 3 dB bandwidth of 300 Hz to 3 kHz, without the use of psophometrical weighting filter.

For equipment which can be measured using continuous bit streams, the bit error rate shall not exceed 10^{-2} .

For other non-speech equipment four messages out of five or 90 % of the transmitted symbols shall be received correctly.

At the conclusion of the test the EUT shall operate as intended with no loss of user control functions or stored data, and the communication link shall have been maintained during the test.

Where the EUT is a transceiver, under no circumstances shall the transmitter operate unintentionally during the test.

6.5 Performance criteria for Transient phenomena applied to Receivers (TR)

At the conclusion of each exposure the EUT shall operate with no user noticeable loss of the communication link.

At the conclusion of the total test comprising the series of individual exposures the EUT shall operate as intended with no loss of user control functions or stored data, as declared by the manufacturer, and the communication link shall have been maintained during the test.

Where the EUT is a transceiver, under no circumstances shall the transmitter operate unintentionally during the test.

6.6 Performance criteria for ancillary equipment tested on a stand alone basis

The provision of EN 301 489-1 [1], subclause 6.4 shall apply.

7 Applicability overview

7.1 Emission

7.1.1 General

The table 2 in EN 301 489-1 [1], contains the applicability of EMC emission measurements to the relevant ports of radio and/or associated ancillary equipment.

7.1.2 Special conditions

No special conditions shall apply to Private land Mobile Radio (PMR) equipment in the scope of the present document.

7.2 Immunity

7.2.1 General

The table 3 of EN 301 489-1 [1], contains the applicability of EMC immunity measurements to the relevant ports of radio and/or associated ancillary equipment.

7.2.2 Special conditions

No special conditions shall apply to Private land Mobile Radio (PMR) equipment in the scope of the present document.

Annex A (informative): Examples of PMR equipment within the scope of the present document

The provisions of the present document apply to radio and associated ancillary equipment intended for use in the land mobile service, that means to Private/Professional land Mobile Radio (PMR) equipment as set out in the following clauses.

A.1 Non-integral antenna PMR equipment

The present document applies in particular to angle modulated (constant envelope) radio equipment, operating on radio frequencies between 30 MHz and 1 000 MHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, and associated ancillary equipment. It applies to:

- PMR equipment primarily intended for transmission of analogue speech, as defined in ETS 300 086 [5];
- PMR equipment and the non-speech part of combined speech/non-speech radio equipment, intended for transmission of non-speech information to initiate a specific response in the receiver, as defined in I-ETS 300 219 [6].
- digital and combined analogue and digital PMR equipment and parts thereof, intended for transmission of data and/or speech as defined in ETS 300 113 [7].

A.2 Integral antenna PMR equipment

The present document applies also to angle modulated (constant envelope) radio equipment, operating on radio frequencies between 30 MHz and 1 000 MHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, and associated ancillary equipment. It applies to:

- PMR equipment intended for transmission of analogue speech, as defined in ETS 300 296 [8];
- PMR equipment and the non-speech part of combined speech/non-speech radio equipment, intended for transmission of non-speech information to initiate a specific response in the receiver, as defined in ETS 300 341 [9];
- digital and combined analogue and digital PMR equipment and parts thereof, intended for transmission of data and/or speech as defined in ETS 300 390 [10].

A.3 Narrowband channel non-integral PMR equipment

The present document applies also to radio equipment, operating on radio frequencies between 30 MHz and 3 GHz, with narrow channel separations (less than 10 kHz, and associated ancillary equipment). It applies to:

- PMR equipment intended for transmission of digitized speech and/or data, with narrow channel separation (less than 10 kHz and permitted by CEPT), and using constant or non-constant envelope type of modulation as defined in EN 301 166 [11].

Bibliography

The following material although not referenced in the main body of the present document, gives supporting information in respect of PMR equipment.

- EN 300 086-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech; Part 1: Technical characteristics and test conditions".
- EN 300 086-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".
- EN 300 113-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and speech) and having an antenna connector; Part 1: Technical characteristics and methods of measurement".
- EN 300 113-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and speech) and having an antenna connector; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".
- EN 300 219-1: "Electronic compatibility and Radio spectrum Matters (ERM); Land Mobile Service (Technical characteristics and test conditions for radio equipment transmitting signals to initiate a specific response in the receiver and having an antenna connector; Part 1: Technical characteristics and methods of measurement".
- EN 300 219-2: "Electronic compatibility and Radio spectrum Matters (ERM); Land Mobile Service (Technical characteristics and test conditions for radio equipment transmitting signals to initiate a specific response in the receiver and having an antenna connector; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".
- EN 300 296-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment using integral antennas intended primarily for analogue speech; Part 1: Technical characteristics and methods of measurement".
- EN 300 296-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment using integral antennas intended primarily for analogue speech; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".
- EN 300 341-1: "Electronic compatibility and Radio spectrum Matters (ERM); Land Mobile Service (Technical characteristics and test conditions for radio equipment using an integral antenna transmitting signals to initiate a specific response in the receiver; Part 1: Technical characteristics and methods of measurement".
- EN 300 341-2: "Electronic compatibility and Radio spectrum Matters (ERM); Land Mobile Service (Technical characteristics and test conditions for radio equipment using an integral antenna transmitting signals to initiate a specific response in the receiver; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".
- EN 300 390-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment intended for the transmission of data (and speech) and using an integral antenna; Part 1: Technical characteristics and test conditions".
- EN 300 390-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment intended for the transmission of data (and speech) and using an integral antenna; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".

- EN 301 166-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Technical characteristics and test conditions for radio equipment for analogue and/or digital communication (speech and/or data) and operating on narrowband channels and having an antenna connector; Part 1: Technical characteristics and methods of measurement".
- EN 301 166-2: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Technical characteristics and test conditions for radio equipment for analogue and/or digital communication (speech and/or data) and operating on narrowband channels and having an antenna connector; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".

History

Document history			
V1.1.1	December 1999	Public Enquiry	PE 200015: 1999-12-15 to 2000-04-14
V1.2.1	May 2000	Vote	V 20000714: 2000-05-15 to 2000-07-14