

**Private Integrated Service Network (PISN);
Inter-exchange signalling protocol;
Call offer supplementary service;
Part 2: Abstract Test Suite (ATS) and partial Protocol
Implementation eXtra Information for Testing (PIXIT) proforma**



Reference

DEN/SPAN-05191-3

KeywordsATS, CCS, PISN, PIXIT, QSIG, stage 3,
supplementary service**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).

In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword	5
1 Scope	6
2 References	6
3 Definitions and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Abstract Test Method (ATM)	8
4.1 Description of ATM used	8
5 Untestable test purposes	8
6 ATS conventions	8
6.1 Version of TTCN used	8
6.2 Use of ASN.1	9
6.2.1 Situations where ASN.1 is used	9
6.2.2 Specification of encoding rules	9
7 ATS to TP map	10
8 PCTR conformance	10
9 PIXIT conformance	10
10 ATS conformance	10
Annex A (normative): Protocol Conformance Test Report (PCTR) proforma	11
A.1 Identification summary	11
A.1.1 Protocol conformance test report	11
A.1.2 IUT identification	11
A.1.3 Testing environment	11
A.1.4 Limits and reservations	12
A.1.5 Comments	12
A.2 IUT conformance status	12
A.3 Static conformance summary	12
A.4 Dynamic conformance summary	12
A.5 Static conformance review report	13
A.6 Test campaign report	14
A.7 Observations	16
Annex B (normative): Partial PIXIT proforma	17
B.1 Identification summary	17
B.2 Abstract test suite summary	17
B.3 Test laboratory	18
B.4 Client (of the test laboratory)	19
B.5 System Under Test (SUT)	19
B.6 Protocol information	20
B.6.1 Protocol identification	20

B.6.2	IUT information	20
B.6.2.1	Parameter values	20
B.6.2.2	Timer values	20
B.6.2.3	Information parameter values	21
B.7	Basic call PIXIT items	22
B.7.1	Parameter values - information element coding.....	22
Annex C (normative):	Abstract Test Suite (ATS).....	23
C.1	The TTCN Graphical form (TTCN.GR).....	23
C.2	The TTCN Machine Processable form (TTCN.MP)	23
History	24

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

This document is part 2 for a multi-part-standard covering the Private Integrated Service Network (PISN) Inter-exchange signalling protocol for Call Offer supplementary service for the VPN "b" service entry point, as described:

Part 1: "Test Suite Structure and Test Purposes (TSS&TP) specification";

Part 2: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the VPN "b" entry point of implementations conforming to the standard for the Call offer supplementary service (SS-CO) as described in EN 300 362 [1].

EN 301 491-1 [6] specifies the Test Suite Structure and Test Purposes (TSS&TP) related to this ATS and partial PIXIT proforma specification.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, subsequent revisions do apply.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ETSI EN 300 362 (V1.2): "Private Integrated Services Network (PISN); Inter-exchange signalling protocol; Call offer supplementary service [ISO/IEC 14843 (1996), modified]".
- [2] ISO/IEC 9646: "Information technology - OSI Conformance Testing Methodology and Framework" (all parts).
- [3] ETSI TR 101 101 (V1.1): "Methods for Testing and Specification (MTS); TTCN interim version including ASN.1 1994 support [ISO/IEC 9646-3] (Second Edition Mock-up for JTC1/SC21 Review)".
- [4] ISO/IEC 8825-1: "Information technology - Encoding Rules for Abstract Syntax Notation One (ASN.1) - Part 1: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)" (See also ITU-T Recommendation X.690): 1994.
- [5] ETSI EN 301 491-2: "Private Integrated Service Network (PISN); Inter-exchange signalling protocol; Call offer supplementary service; Part 2: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma".
- [6] ETSI EN 301 491-1: "Private Integrated Service Network (PISN); Inter-exchange signalling protocol; Call offer supplementary service; Part 1: Test Suite Structure and Test Purposes (TSS&TP) specification".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ISO/IEC 9646 [2] shall apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

APDU	Application Protocol Data Unit
ATM	Abstract Test Method
ATS	Abstract Test Suite
BER	Basic Encoding Rules
DNDO	Do Not Disturb Override
CFB	Call Forwarding Busy
CFU	Call Forwarding Unconditional
CI	Call Intrusion
CO	Call Offer
CT	Call Transfer
ETS	Executable Test Suite
IUT	Implementation Under Test
MOT	Means Of Testing
MTC	Main Test Component
PCO	Point of Control and Observation
PCTR	Protocol Conformance Test Report
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
PTC	Parallel Test Component
SUT	System Under Test
TP	Test Purpose
TTCN	Tree and Tabular Combined Notation
VPN	Virtual Private Network

4 Abstract Test Method (ATM)

4.1 Description of ATM used

The multi-party test method is applied for testing the IUT. The Originating configuration used is shown in Figure 1.

A Point of Control and Observation (PCO) resides at the service access point between layers 2 and 3 in the test system. The PCO used by the MTC is named "L0" (for Lower). This PCO is used to control and observe the behaviour of the Implementation Under Test (IUT) and test case verdicts are assigned depending on the behaviour observed at this PCO.

A second "informal" PCO, called "O" (for Operator) is used to specify control but not observation concerning the IUT; events at this PCO are never used to generate test case verdicts. Messages sent by the tester at this PCO explicitly indicate to the operator actions which are to be performed on the SUT. This is regarded as a preferred alternative to the use of the implicit send event.

The relationship between the IUT and the tester is as follows:




Figure 1: Multi-party test method

Not all components are used in every test case and the relationship between the IUT and the tester depends on the test group.

5 Untestable test purposes

There are no untestable test cases associated with this ATS and ATM.

6 ATS conventions

6.1 Version of TTCN used

The version of TTCN used is that defined in TR 101 101 [3].

6.2 Use of ASN.1

6.2.1 Situations where ASN.1 is used

ASN.1 has been used for three major reasons. First, types defined in ASN.1 can model problems that "pure" TTCN cannot. For instance, data structures modelling ordered or unordered sequences of data are preferably defined in ASN.1. Second, ASN.1 provides a better restriction mechanism for type definitions by using sub-type definitions. Third, it is necessary to use ASN.1 to reproduce the type definitions for remote operation components as specified in the base standards in ASN.1.

The possibility to use TTCN and ASN.1 in combination is used, i.e. referring to an ASN.1 type from a TTCN type.

6.2.2 Specification of encoding rules

There is a variation in the encoding rules applied to ASN.1 types and constraints specified in this ATS and therefore a mechanism is needed to differentiate the encoding rules. However the mechanism specified in ISO/IEC 9646-3/AM2 [2] and in TR 101 101 [3] does not facilitate definition of the encoding rules as needed for this ATS. A solution is therefore used which is broadly in the spirit of ISOIEC 9646-3/AM2 [2] in which comment fields have been used as a means of encoding rules.

For ASN.1 used in this ATS, two variations of encoding rules are used. One is the commonly known Basic Encoding Rules (BER) as specified in ISO/IEC 8825-1 [4]. In the second case the encoding is according to ISDN, i.e. the ASN.1 data types are a representation of structures contained within the ISDN specification (basic call, Generic functional protocol or individual supplementary service). For example, if octets of an information element are specified in ASN.1 as a SEQUENCE then this should be encoded in an Executable Test Suite (ETS) as any other ISDN information element specified using tabular TTCN. This ISDN encoding variation is the default encoding rule for this ATS. This means that all ASN.1 constraint tables are encoded using ISDN (non-BER) encoding unless stated otherwise. BER encoding should never be applied to an ASN.1 constraint where BER encoding has not been specified. This encoding rule is sometimes named "Direct Encoding".

For BER encoding, an indication is given in the comments field of the table header. For this ATS such indications appear in the ASN.1 type constraint declaration tables only. In the table header comment field, the notation "ASN1_Encoding: BER" is used.

In this particular ATS all ASN.1 type constraints which are of type "Component" are to be encoded using BER.

Table 1 shows an example of a ASN.1 type Constrained Declaration used in this ATS.

Table 1: ASN.1 type constraint declaration showing use of encoding variation

ASN.1 Type Constraint Declaration	
Constraint Name:	CORequestInv_S1 (INV_ID: InvokeIDType)
ASN.1 Type	: Component
Derivation Path:	
Comments	: Sent Component: CORequest Invoke component. ASN1_Encoding: BER
Description	
callOfferRequest_Comp	
callOfferRequest_InvokeComp	
{ invokeID	INV_ID, -- the invoke identifier
operation_value	localValue 34, -- value for operation
argument	OMIT}
Detailed comments:	

7 ATS to TP map

The identifiers used for the TPs are reused as test case names. Thus there is a straightforward one-to-one mapping.

8 PCTR conformance

A test laboratory, when requested by a client to produce a PCTR, is required, as specified in ISO/IEC 9646-5 [2], to produce a PCTR conformant with the PCTR template given in annex B of ISO/IEC 9646-5 [2].

Furthermore, a test laboratory, offering testing for the ATS specification contained in annex C, when requested by a client to produce a PCTR, is required to produce a PCTR conformant with the PCTR proforma contained in annex A.

A PCTR which conforms to this PCTR proforma specification shall preserve the content and ordering of the clauses contained in annex A. clause A.6 of the PCTR may contain additional columns. If included, these shall be placed to the right of the existing columns. Text in italics may be retained by the test laboratory.

9 PIXIT conformance

A test realizer, producing an executable test suite for the ATS specification contained in annex C, is required, as specified in ISO/IEC 9646-4 [2], to produce an augmented partial PIXIT proforma conformant with this partial PIXIT proforma specification.

An augmented partial PIXIT proforma which conforms to this partial PIXIT proforma specification shall, as a minimum, have contents which are technically equivalent to annex B. The augmented partial PIXIT proforma may contain additional questions that need to be answered in order to prepare the Means Of Testing (MOT) for a particular IUT.

A test laboratory, offering testing for the ATS specification contained in annex C, is required, as specified in ISO/IEC 9646-5 [2], to further augment the augmented partial PIXIT proforma to produce a PIXIT proforma conformant with this partial PIXIT proforma specification.

A PIXIT proforma which conforms to this partial PIXIT proforma specification shall, as a minimum, have contents which are technically equivalent to annex B. The PIXIT proforma may contain additional questions that need to be answered in order to prepare the test laboratory for a particular IUT.

10 ATS conformance

The test realizer, producing MOT and ETS for this ATS specification, shall comply with the requirements of ISO/IEC 9646-4 [2]. In particular, these concern the realization of an ETS based on each ATS. The test realizer shall provide a statement of conformance of the MOT to this ATS specification.

An ETS which conforms to this ATS specification shall contain test groups and test cases which are technically equivalent to those contained in the ATS in annex C. All sequences of test events comprising an abstract test case shall be capable of being realized in the executable test case. Any further checking which the test system might be capable of performing is outside the scope of this ATS specification and shall not contribute to the verdict assignment for each test case.

Test laboratories running conformance test services using this ATS shall comply with ISO/IEC 9646-5 [2].

A test laboratory which claims to conform to this ATS specification shall use an MOT which conforms to this ATS.

Annex A (normative): Protocol Conformance Test Report (PCTR) proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PCTR proforma in this annex so that it can be used for its intended purposes and may further publish the completed PCTR.

A.1 Identification summary

A.1.1 Protocol conformance test report

PCTR number:	
PCTR date:	
Corresponding SCTR number:	
Corresponding SCTR date:	
Test laboratory identification:	
Test laboratory manager:	
Signature:	

A.1.2 IUT identification

Name:	
Version:	
Protocol specification:	EN 300 362 [1]
PICS:	
Previous PCTRs (if any):	

A.1.3 Testing environment

PIXIT reference number:	
ATS specification:	EN 301 491-2 [5]
Abstract test method:	Multi-party test method (see ISO/IEC 9646-2)
Means of testing identification:	
Dates of testing:	
Conformance log reference(s):	
Retention date for log reference(s):	

A.1.4 Limits and reservations

Additional information relevant to the technical contents or further use of the test report, or to the rights and obligations of the test laboratory and the client, may be given here. Such information may include restriction on the publication of the report.

.....

.....

.....

.....

A.1.5 Comments

Additional comments may be given by either the client or the test laboratory on any of the contents of the PCTR, for example, to note disagreement between the two parties.

.....

.....

.....

.....

A.2 IUT conformance status

This IUT has / has not been shown by conformance assessment to be non-conforming to the specified protocol specification.

Strike the appropriate words in this sentence. If the PICS for this IUT is consistent with the static conformance requirements (as specified in clause A.3 of this report) and there are no "FAIL" verdicts to be recorded (in clause A.6) strike the words "has", otherwise strike the words "has not".

A.3 Static conformance summary

The PICS for this IUT is / is not consistent with the static conformance requirements in the specified protocol.

Strike the appropriate words in this sentence.

A.4 Dynamic conformance summary

The test campaign did / did not reveal errors in the IUT.

Strike the appropriate words in this sentence. If there are no "FAIL" verdicts to be recorded (in clause A.6 of this report) strike the word "did", otherwise strike the words "did not".

Summary of the results of groups of tests:

.....

.....

.....

.....

A.5 Static conformance review report

If clause A.3 indicates non-conformance, this clause itemizes the mismatches between the PICS and the static conformance requirements of the specified protocol specification.

.....

.....

.....

.....

.....

.....

A.6 Test campaign report

ATS reference	Selected? (Y/N)	Run? (Y/N)	Verdict	Observations
Group Orig01				
CO_Orig01_001				
CO_Orig01_002				
CO_Orig01_003				
CO_Orig01_004				
CO_Orig01_005				
CO_Orig01_006				
CO_Orig01_007				
CO_Orig01_008				
Group Orig02				
CO_Orig02_001				
CO_Orig02_002				
CO_Orig02_003				
CO_Orig02_004				
CO_Orig02_005				
CO_Orig02_006				
Group Term01				
CO_Term01_001				
CO_Term01_002				
CO_Term01_003				
CO_Term01_004				
CO_Term01_005				
CO_Term01_006				
CO_Term01_007				
Group Term02				
CO_Term02_001				
CO_Term02_002				
CO_Term02_003				
Group CO_CT_Orig				
CO_CT_Orig_001				
CO_CT_Orig_002				
Group CO_CT_Term				
CO_CT_Term_001				
CO_CT_Term_002				
CO_CT_Term_003				
CO_CT_Term_004				
CO_CT_Term_005				
CO_CT_Term_006				
Group CO_CFU_Orig				
CO_CFU_Orig_001				
CO_CFU_Orig_002				
CO_CFU_Orig_003				
CO_CFU_Orig_004				
Group CO_CFU_Term				
CO_CFU_Term_001				
CO_CFU_Term_002				
CO_CFU_Term_003				
Group CO_CFB_Orig				
CO_CFB_Orig_001				
CO_CFB_Orig_002				
CO_CFB_Orig_003				
CO_CFB_Orig_004				
CO_CFB_Orig_005				
CO_CFB_Orig_006				
Group CO_CFB_Term				
CO_CFB_Term_001				

ATS reference	Selected? (Y/N)	Run? (Y/N)	Verdict	Observations
CO_CFB_Term_002				
CO_CFB_Term_003				
CO_CFB_Term_004				
CO_CFB_Term_005				
Group CO_DNDO_Term				
CO_DNDO_Term_001				
CO_DNDO_Term_002				
Group CO_CI_Orig				
CO_CI_Orig_001				
Group CO_CI_Term				
CO_CI_Term_001				

Annex B (normative): Partial PIXIT proforma

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the partial PIXIT proforma in this annex so that it can be used for its intended purposes and may further publish the completed PIXIT.

B.1 Identification summary

PIXIT number:

.....

Test laboratory name:

.....

Date of issue:

.....

Issued to:

.....

B.2 Abstract test suite summary

Protocol specification:	EN 300 362 [1]
ATS specification:	EN 301 491-2 [5]
Abstract test method:	Multi-party test method (see ISO/IEC 9646-2)

B.3 Test laboratory

Test laboratory identification:

.....

Accreditation status of the test service:

.....

Accreditation reference:

.....

Test laboratory manager:

.....

Test laboratory contact:

.....

Means of testing:

.....

Test laboratory instructions for completion:

.....

B.4 Client (of the test laboratory)

Client identification:

.....

Client test manager:

.....

Client contact:

.....

Test facilities required:

.....

B.5 System Under Test (SUT)

Name:

.....

Version:

.....

SCS reference:

.....

Machine configuration:

.....

Operating system identification:

.....

IUT identification:

.....

PICS (all layers):

.....

.....

Limitations of the SUT:

.....

Environmental conditions:

.....

B.6 Protocol information

B.6.1 Protocol identification

Specification reference: EN 300 362 [1]

Protocol version: 1.2.1

PICS reference:

NOTE: The PICS reference should reference a completed PICS which is conform with the PICS proforma contained in EN 301 491-2 [5].

B.6.2 IUT information

B.6.2.1 Parameter values

Table B.1: Parameter values

Item	Question	Supported? (Y/N)	Allowed values	Value
1.1	A value for the length of the Business Group Identification.			
1.2	A value for the Business Group Identifier.			
1.3	A value for the Business Group Identification.			

B.6.2.2 Timer values

Table B.2: Timer values

Item	Timer duration	Supported? (Y/N)	Allowed values	Value
2.1	Wait for the test operator to perform an implicit send action or to wait for a PTC to react (T _{WAIT}). Duration in s.		integer	
2.2	Wait for the IUT to respond to a stimulus sent by the tester (T _{AC}). Duration in s.		integer	
2.3	Control that the IUT does not respond to a stimulus sent by the tester (T _{N_OAC}). Duration in s.		integer	
2.4	Timer that is used to wait for a RESTART PDU(T _{RESTART}). Duration in s		integer	
2.5	Timer that is started if a DISCONNECT message is received (T ₃₀₅). Duration in s.		integer	
2.6	Timer that is started if a RELEASE message is received (T ₃₀₈). Duration in s.		integer	

NOTE: The IUT provider fill in a value range rather than a fixed value for the test management timers. During test execution the test laboratory will choose specific values for the timers dependant on the means of testing used. These specific values may even be beyond the range given by the IUT provider, if this is necessary for achieving satisfactory test results.

B.6.2.3 Information parameter values

Table B.3: Information parameter values

Item	Question	Supported? (Y/N)	Value
3.1	A value for the length of the Called Party Number information element of the called user B.		
3.2	Coding of the octet 3 of the Called Party Number information element of the called user B.		
3.3	Number digits of the Called Party Number information element of the called user B.		
3.4	A value of the address of the diverted-to user.		
3.5	A value of the Party Number of the last rerouteing user.		
3.6	A value of the Calling Party information element of the calling user A.		
3.7	A value to select that the timeout of timer TNOAC (see item 2.3) is higher then the timeout of T1.		
3.8	A value to select if the IUT sends a NOTIFY message with "call is a waiting call" after receipt of a callTransferComplete invoke APDU.		
3.9	A value to select if the IUT has activated DND for the called user B.		

B.7 Basic call PIXIT items

B.7.1 Parameter values - information element coding

Table B.4: Coding of information elements

Item	Information element: provide, if possible,...	Supported? (Y/N)	Value
4.1	A value for the length of the Call Reference (bitstring).		
4.2	A value to select if the IUT sends RESTART PDUs after re-establishment of the multiple frame operation.		
4.3	A value to select if the IUT initiates release of the multiple frame established operation after entering U00/N00.		
4.4	A value for the length of the Bearer Capability information element.		
4.5	A coding of the content of the Bearer Capability information element.		
4.6	A value for the preferred channel number.		
4.7	A value for the preferred channel number for the second call.		
4.8	A value for the length of the High Layer Compatibility information element.		
4.9	A coding of the content of the High Layer Compatibility information element.		
4.10	A value for the length of the Low Layer Compatibility information element.		
4.11	A coding of the content of the Low Layer Compatibility information element.		

Annex C (normative): Abstract Test Suite (ATS)

This ATS has been produced using the Tree and Tabular Combined Notation (TTCN) according to ISO/IEC 9646-3.

The ATS was developed on a separate TTCN software tool and therefore the TTCN tables are not completely referenced in the contents table. The ATS itself contains a test suite overview part which provides additional information and references.

C.1 The TTCN Graphical form (TTCN.GR)

The TTCN.GR representation of this ATS is contained in a PDF file (sp519132.pdf) contained in archive en_30149102v010101c0.ZIP which accompanies the present document.

C.2 The TTCN Machine Processable form (TTCN.MP)

The TTCN.MP representation corresponding to this ATS is contained in an ASCII file (sp519132.mp) contained in archive en_30149102v010101c0.ZIP which accompanies the present document.

History

Document history		
V1.1.1	May 2000	Public Enquiry PE 20000922: 2000-05-24 to 2000-09-22