



**ElectroMagnetic Compatibility (EMC) standard
for marine radio equipment and services;
Harmonised Standard for electromagnetic compatibility;
Part 7: Specific conditions for
Maritime Broadband Radiolink equipment**

Reference

DEN/ERM-EMC-391

Keywords

broadband, EMC, harmonised standard,
maritime, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members
GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	5
3 Definitions, symbols and abbreviations	6
3.1 Definitions	6
3.2 Symbols.....	6
3.3 Abbreviations	6
4 Test conditions	6
4.0 Test conditions requirements.....	6
4.1 General	6
4.2 Arrangements for test signals	7
4.2.0 General.....	7
4.2.1 Arrangements for test signals at the input of the transmitter	7
4.2.2 Arrangements for test signals at the output of the transmitter	7
4.2.3 Arrangements for test signals at the input of the receiver.....	7
4.2.4 Arrangements for test signals at the output of the receiver.....	7
4.2.5 Arrangements for testing transmitter and receiver together (as a system)	7
4.3 Exclusion bands.....	7
4.4 Narrow band responses on receivers	7
4.5 Normal test modulation	7
5 Performance assessment.....	7
5.1 General	7
5.2 Equipment which can provide a continuous communication link	8
5.3 Equipment which does not provide a continuous communication link	8
5.4 Ancillary equipment	8
5.5 Equipment classification	8
6 Performance criteria	8
6.0 General	8
6.1 Performance criteria A for continuous phenomena applied to transmitters and receivers.....	8
6.2 Performance criteria B for transient phenomena applied to transmitters and receivers	8
6.3 Performance criteria C applied to power supply failure	8
6.4 Performance check	8
6.5 Performance criteria for equipment which does not provide a continuous communication link.....	9
6.6 Performance criteria for ancillary equipment tested on a stand alone basis	9
7 Applicability overview	9
7.1 Emission	9
7.2 Immunity	9
7.2.1 General.....	9
7.2.2 Special conditions.....	9
8 Methods of measurement and limits for EMC emissions	9
8.1 Test configuration.....	9
9 Test methods and levels for immunity tests	10
Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU	11
Annex B (informative): Change history	13
History	14

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

The present document is part 7 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document together with ETSI EN 301 843-1 [1], covers the assessment of Maritime Broadband Radiolink equipment (MBR) for the maritime mobile service, and ancillary equipment in respect of ElectroMagnetic Compatibility (EMC).

Technical specifications related to the antenna port and emissions from the enclosure port of MBR are not included in the present document. Such technical specifications are found in the related product standards for the effective use of the radio spectrum.

The present document specifies the applicable test conditions, performance assessment, and performance criteria for MBR equipment for the maritime mobile service, and the associated ancillary equipment.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and ETSI EN 301 843-1 [1], the provisions of the present document take precedence.

The electromagnetic environment used in the present document to develop the technical specifications encompasses the electromagnetic environment on board ships as identified in IEC EN 60945 [i.1].

NOTE: The relationship between the present document and essential requirements of article 3.1b of Directive 2014/53/EU [i.2] is given in annex A.

2 References

2.1 Normative references

References are specific, identified by date of publication and/or edition number or version number. Only the cited version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 843-1 (V2.2.0) (07-2017): "ElectroMagnetic Compatibility (EMC) standard for marine radio equipment and services; Harmonised Standard for electromagnetic compatibility; Part 1: Common technical requirements".
- [2] Recommendation ITU-T O.153 (1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] IEC EN 60945 (2002) + Corrigendum 1 (2008): "Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results".

- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 301 843-1 [1] apply.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

emf	electromotive force
rms	root mean square

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 301 843-1 [1] and the following apply:

BER	Bit Error Rate
EMC	ElectroMagnetic Compatibility
EN	European Norm
EUT	Equipment Under Test
MBR	Maritime Broadband Radiolink
RF	Radio Frequency

4 Test conditions

4.0 Test conditions requirements

For the purposes of the present document, the test conditions of ETSI EN 301 843-1 [1], clause 4, shall apply as appropriate. Further product related test conditions for MBR are specified in the present document.

4.1 General

The provisions of ETSI EN 301 843-1 [1], clause 4.1 shall apply with the following modifications.

For emission and immunity tests the normal test modulation, test arrangements, etc., as specified in the present document, clauses 4.1 to 4.5, shall apply.

The test shall be carried out at a point within the specified normal operating environmental range of temperature and humidity with the equipment connected to the normal power supply voltage.

4.2 Arrangements for test signals

4.2.0 General

The provisions of ETSI EN 301 843-1 [1], clause 4.2 shall apply.

4.2.1 Arrangements for test signals at the input of the transmitter

The provisions of ETSI EN 301 843-1 [1], clause 4.2.1 shall apply.

4.2.2 Arrangements for test signals at the output of the transmitter

The provisions of ETSI EN 301 843-1 [1], clause 4.2.2 shall apply.

4.2.3 Arrangements for test signals at the input of the receiver

The provisions of ETSI EN 301 843-1 [1], clause 4.2.3 shall apply with the following modifications:

In the 3rd paragraph of clause 4.2.3, the last sentence: "This antenna shall be connected to the external RF signal source by a coaxial cable", should be replaced with: "The wanted RF signal shall be generated by an MBR transmitter".

4.2.4 Arrangements for test signals at the output of the receiver

The provisions of ETSI EN 301 843-1 [1], clause 4.2.4 shall apply as appropriate.

4.2.5 Arrangements for testing transmitter and receiver together (as a system)

The provisions of ETSI EN 301 843-1 [1], clause 4.2.5 shall apply as appropriate.

4.3 Exclusion bands

The provisions of ETSI EN 301 843-1 [1], clause 4.3 are not applicable.

4.4 Narrow band responses on receivers

The provisions of ETSI EN 301 843-1 [1], clause 4.4 shall apply

4.5 Normal test modulation

The provisions of ETSI EN 301 843-1 [1], clause 4.5 shall apply as applicable using an MBR message consisting of a pseudo-random bit sequence of at least 8 192 payload bits according to Recommendation ITU-T O.153 [2]. The bit modulation rate over the air shall be 10 Mb/s. The message contains a header targeting the targeted receiver identity.

5 Performance assessment

5.1 General

The provisions of ETSI EN 301 843-1 [1], clause 5.1 shall apply.

5.2 Equipment which can provide a continuous communication link

The provisions of ETSI EN 301 843-1 [1], clause 5.2 shall apply.

5.3 Equipment which does not provide a continuous communication link

The provisions of ETSI EN 301 843-1 [1], clause 5.3 shall apply.

5.4 Ancillary equipment

The provisions of ETSI EN 301 843-1 [1], clause 5.4 shall apply.

5.5 Equipment classification

Maritime mobile broadband radiolink equipment belong solely to the category of mobile marine radio equipment as defined in ETSI EN 301 843-1 [1], clause 3.1.

6 Performance criteria

6.0 General

The provisions of ETSI EN 301 843-1 [1], clause 6 shall apply.

The equipment shall meet the special performance criteria set out in clauses 6.1 to 6.4, as appropriate.

6.1 Performance criteria A for continuous phenomena applied to transmitters and receivers

The provisions of ETSI EN 301 843-1 [1], clause 6.1 shall apply.

6.2 Performance criteria B for transient phenomena applied to transmitters and receivers

The provisions of ETSI EN 301 843-1 [1], clause 6.2 shall apply with the following modifications.

During the test sequence, degradation or loss of function or performance which is self-recoverable is allowed, but the EUT shall not unintentionally transmit or change actual operating state or stored data.

6.3 Performance criteria C applied to power supply failure

The provisions of ETSI EN 301 843-1 [1], clause 6.3 shall apply.

6.4 Performance check

The provisions of ETSI EN 301 843-1 [1], clause 6.4 shall apply. The performance check consists of transmitting and receiving the test signal 2 and measuring the BER. The signal level at the receiving antenna shall be above - 80 dBm and the receiver BER shall be better than 10^{-5} .

6.5 Performance criteria for equipment which does not provide a continuous communication link

The provisions of ETSI EN 301 843-1 [1], clause 6.5 shall apply.

6.6 Performance criteria for ancillary equipment tested on a stand alone basis

The provisions of ETSI EN 301 843-1 [1], clause 6.6 shall apply.

7 Applicability overview

7.1 Emission

ETSI EN 301 843-1 [1], table 1, contains the applicability of EMC emission measurements to the relevant ports of marine radio and/or associated ancillary equipment.

7.2 Immunity

7.2.1 General

ETSI EN 301 843-1 [1], table 2, contains the applicability of EMC immunity measurements to the relevant ports of marine radio and/or associated ancillary equipment.

7.2.2 Special conditions

The following special conditions set out in table 1 shall apply in addition to the immunity test methods and performance criteria used in ETSI EN 301 843-1 [1], clause 9. The wanted signal shall be generated by an MBR transmitter modulated as described in clause 4.5.

Table 1: Special conditions for EMC immunity tests

Reference to clauses in ETSI EN 301 843-1 [1]	Special product-related conditions, additional to or modifying the test conditions in ETSI EN 301 843-1 [1], clause 9
9.2.2: Test method; Radio frequency electromagnetic field	Wanted RF input signal for the receiver under test: A wanted receiver RF input level of -80 dBm shall be used during the test.
9.5.2: Test method; Radio frequency, Common mode	Wanted RF input signal for the receiver under test: A wanted receiver RF input level of -80 dBm shall be used during the test.

8 Methods of measurement and limits for EMC emissions

8.1 Test configuration

The provisions of ETSI EN 301 843-1 [1], clause 8.1 shall apply.

8.2 Enclosure of ancillary equipment measured on a stand alone basis

The provisions of ETSI EN 301 843-1 [1], clause 8.2, are not applicable.

8.3 DC power input/output ports

The provisions of ETSI EN 301 843-1 [1], clause 8.3 shall apply.

8.4 AC mains power input/output ports

The provisions of ETSI EN 301 843-1 [1], clause 8.4 shall apply.

9 Test methods and levels for immunity tests

9.1 Test configuration

The provisions of ETSI EN 301 843-1 [1], clause 9.1 shall apply.

9.2 Radio frequency electromagnetic field (80 MHz to 2 700 MHz)

The provisions of ETSI EN 301 843-1 [1], clause 9.2 shall apply.

9.3 Electrostatic discharge

The provisions of ETSI EN 301 843-1 [1], clause 9.3 shall apply but particular care shall be taken with respect to the minimum safe distance from the antenna.

9.4 Fast transients, differential and common mode

The provisions of ETSI EN 301 843-1 [1], clause 9.4 shall apply.

9.5 Radio frequency, common mode

The provisions of ETSI EN 301 843-1 [1], clause 9.5 shall apply.

9.6 Power supply variations

The provisions of ETSI EN 301 843-1 [1], clause 9.6 shall apply.

9.7 Surges

The provisions of ETSI EN 301 843-1 [1], clause 9.7 shall apply.

Annex A (informative): Relationship between the present document and the essential requirements of Directive 2014/53/EU

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.3] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive, and associated EFTA regulations.

Table A.1: Relationship between the present document and the essential requirements of Directive 2014/53/EU

Harmonised Standard ETSI EN 301 843-7					
Requirement				Requirement Conditionality	
No	Description	Essential requirements of Directive	Clause(s) of the present document	U/C	Condition
1	Emmission: Enclosure of ancillary equipment measured on a stand alone basis	3.1b	8.2 of ETSI EN 301 843-1 [1]	U	
2	Emmission: DC power input/output ports	3.1b	8.3 of ETSI EN 301 843-1 [1]	C	DC powered equipment with cables > 3 m
3	Emmission: AC mains power input/output ports	3.1b	8.4 of ETSI EN 301 843-1 [1]	C	AC powered equipment
4	Immunity: Radio frequency electromagnetic field (80 MHz to 2,7 GHz)	3.1b	9.2 of ETSI EN 301 843-1 [1] and 7.2.2	U	
5	Immunity: Electrostatic discharge	3.1b	9.3 of ETSI EN 301 843-1 [1]	U	
6	Immunity: Fast transients, differential and common mode AC ports	3.1b	9.4 of ETSI EN 301 843-1 [1]	C	AC powered equipment
7	Immunity: Fast transients, differential and common mode DC ports	3.1b	9.4 of ETSI EN 301 843-1 [1]	C	DC powered equipment with cables > 3 m
8	Immunity: Fast transients, differential and common mode Signal and control ports	3.1b	9.4 of ETSI EN 301 843-1 [1]	C	Cables > 3 m
9	Immunity: Radio frequency, common mode AC ports	3.1b	9.5 of ETSI EN 301 843-1 [1]	C	AC powered equipment
10	Immunity: Radio frequency, common mode DC ports	3.1b	9.5 of ETSI EN 301 843-1 [1] and 7.2.2	C	DC powered equipment with cables > 3 m
11	Immunity: Radio frequency, common mode signal and control ports	3.1b	9.5 of ETSI EN 301 843-1 [1] and 7.2.2	C	Cables > 3 m
12	Immunity: Power supply short term variations	3.1b	9.6.1 of ETSI EN 301 843-1 [1]	C	AC powered equipment
13	Immunity: Power supply failure	3.1b	9.6.2 of ETSI EN 301 843-1 [1]	C	Not for battery powered or equipment with back-up batteries
14	Immunity: Surges	3.1b	9.7 of ETSI EN 301 843-1 [1]	C	AC powered equipment

Key to columns:**Requirement:**

No A unique identifier for one row of the table which may be used to identify a requirement.

Description A textual reference to the requirement.

Essential requirements of Directive

Identification of article(s) defining the requirement in the Directive.

Clause(s) of the present document

Identification of clause(s) defining the requirement in the present document unless another document is referenced explicitly.

Requirement Conditionality:

U/C Indicates whether the requirement is unconditionally applicable (U) or is conditional upon the manufacturer's claimed functionality of the equipment (C).

Condition Explains the conditions when the requirement is or is not applicable for a requirement which is classified "conditional".

Presumption of conformity stays valid only as long as a reference to the present document is maintained in the list published in the Official Journal of the European Union. Users of the present document should consult frequently the latest list published in the Official Journal of the European Union.

Other Union legislation may be applicable to the product(s) falling within the scope of the present document.

Annex B (informative): Change history

Version	Information about changes
1.1.1	First version under the Radio Equipment Directive

History

Document history				
V1.1.0	July 2017	EN Approval Procedure	AP 20171017:	2017-07-19 to 2017-10-17