

Final draft **ETSI EN 302 093-3** V1.1.2 (2000-03)

European Standard (Telecommunications series)

**Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling System No. two (DSS2) protocol;
Point-to-point multiconnection bearer control specification
in a separated call and bearer environment;
Part 3: Test Suite Structure and Test Purposes (TSS&TP)
specification**



Reference

DEN/SPS-05155-3

Keywords

bearer, B-ISDN, DSS2, layer 3, TSS&TP, uni,
user**ETSI**

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
<http://www.etsi.org>
If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	4
1 Scope	5
2 References	5
3 Definitions and abbreviations	6
3.1 Definitions	6
3.2 Abbreviations	6
4 Test Suite Structure (TSS)	6
5 Test Purposes (TP)	7
5.1 Introduction	7
5.1.1 TP naming convention	7
5.1.2 Source of TP definition	7
5.1.3 Test strategy	7
5.2 TPs for the bearer control, layer 3	7
5.2.1 Signalling procedures at the coincident S_B/T_B and at the T_B reference points	7
5.2.1.1 Preceding side	7
5.2.1.2 Succeeding side	8
5.2.1.3 Error handling	8
6 Compliance	9
7 Requirements for a comprehensive testing service	9
Bibliography	10
History	11

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services Protocols for Advanced Networks (SPAN), and is now submitted for the Voting phase of the ETSI standards Two-step Approval Procedure.

The present document is part 3 of a multi-part EN covering the Digital Subscriber Signalling System No. two (DSS2) protocol; Point-to-point multiconnection bearer control specification in a separated call and bearer environment, as identified below:

- Part 1: "Protocol specification";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification";**
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document specifies the Test Suite Structure and Test Purposes (TSS&TP) for the T_B reference point or coincident S_B and T_B reference point (as defined in ITU-T Recommendation I.413 [5]) of implementations conforming to the standards for the signalling user-network layer 3 specification for the bearer control protocol for point-to-point multiconnection calls of the Digital Subscriber Signalling System No. two (DSS2) protocol for the pan-European Broadband Integrated Services Digital Network (B-ISDN), EN 302 093-1 [1].

A further part of the present document specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma based on the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] EN 302 093-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Point-to-point multiconnection bearer control specification in a separated call and bearer environment; Part 1: Protocol specification".
- [2] EN 302 093-2: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Point-to-point multiconnection bearer control specification in a separated call and bearer environment; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] ISO/IEC 9646-1 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 1: General concepts".
- [4] ISO/IEC 9646-2 (1994): "Information technology; Open Systems Interconnection; Conformance testing methodology and framework; Part 2: Abstract Test Suite specification".
- [5] ITU-T Recommendation I.413 (1993): "B-ISDN user-network interface".
- [6] ETS 300 406: "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [7] EN 300 443-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply, in addition to those given in EN 302 093-1 [1].

Abstract test case: refer to ISO/IEC 9646-1 [3].

Abstract Test Method (ATM): refer to ISO/IEC 9646-1 [3].

Abstract Test Suite (ATS): refer to ISO/IEC 9646-1 [3].

Implementation Under Test (IUT): refer to ISO/IEC 9646-1 [3].

Lower tester: refer to ISO/IEC 9646-1 [3].

Protocol Implementation Conformance Statement (PICS): refer to ISO/IEC 9646-1 [3].

PICS proforma: refer to ISO/IEC 9646-1 [3].

Protocol Implementation eXtra Information for Testing (PIXIT): refer to ISO/IEC 9646-1 [3].

PIXIT proforma: refer to ISO/IEC 9646-1 [3].

Test Purpose (TP): refer to ISO/IEC 9646-1 [3].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
DSS2	Digital Subscriber Signalling System No. two
B-ISDN	Broadband Integrated Services Digital Network
IUT	Implementation Under Test
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
TP	Test Purpose
TSS	Test Suite Structure

4 Test Suite Structure (TSS)

- Signalling procedures at the coincident S_B/T_B and at the T_B reference points
- Preceding side..... (01)
- Succeeding side (02)
- Error handling..... (03)

Figure 1: Test suite structure

5 Test Purposes (TP)

5.1 Introduction

For each test requirement a TP is defined.

5.1.1 TP naming convention

Tps are numbered, starting at 01, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite (see table 1).

Table 1: TP identifier naming convention scheme

Identifier:	<suite_id>_<group>_<nnn>	
<suite_id>	= layer + type of IUT:	"L3BC" for Layer 3 Bearer Control
<group>	= group number:	two character field representing the group reference according to TSS
<nn>	= sequential number:	(01-99)

5.1.2 Source of TP definition

The TPs are based on EN 302 093-1 [1].

5.1.3 Test strategy

As the base standard EN 302 093-1 [1] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the PICS specification EN 302 093-2 [2].

The TPs are only based on conformance requirements related to the externally observable behaviour of the IUT, and are limited to conceivable situations to which a real implementation is likely to be faced (ETS 300 406 [6]).

5.2 TPs for the bearer control, layer 3

The separated bearer control is based on the procedures for basic call connection control as defined in EN 300 443-1 [7]. Test purposes have been written only for the additional procedures required to handle the separated bearer control functions of a multiconnection call.

Unless specified:

- the messages indicated are valid and contain at least the mandatory information elements and possibly optional information elements;
- the information elements indicated are valid and contain at least the mandatory parameters and possibly optional parameters.

5.2.1 Signalling procedures at the coincident S_B/T_B and at the T_B reference points

Test purposes for EN 302 093-1 [1], subclause 9.2.

5.2.1.1 Preceding side

L3BC_01_01

Ensure that the IUT, to request the addition of a bearer to a Multiconnection call, sends a SETUP message (Called party number, Call association, Bearer identifier present).

L3BC_01_02

Ensure that the IUT, to request the addition of a bearer to a Multiconnection call, sends a SETUP message (Called party number, Call association, Bearer identifier as received from the previous point of call/bearer co-ordination).

Selection: IUT is not a point of call/bearer co-ordination.

5.2.1.2 Succeeding side**L3BC_02_01**

Ensure that the IUT, on receipt of a SETUP message (Call association, Bearer identifier present), accepts the message and continues normal call handling.

L3BC_02_02

Ensure that the IUT, on receipt of a SETUP message (Call association indicating an unrecognized call association value) sends a RELEASE COMPLETE message (Cause value = 101).

5.2.1.3 Error handling**L3BC_03_01**

Ensure that the IUT, on receipt of a SETUP message (Call association information element missing), sends a RELEASE COMPLETE message (Cause value = 96).

L3BC_03_02

Ensure that the IUT, on receipt of a SETUP message (Bearer identifier information element missing), sends a RELEASE COMPLETE message (Cause value = 96).

L3BC_03_03

Ensure that the IUT, on receipt of a SETUP message (Call association information element with content error present, IE instruction field flag = IE instruction field not significant), sends a RELEASE COMPLETE message (Cause value = 100).

L3BC_03_04

Ensure that the IUT, on receipt of a SETUP message (Call association information element with content error present, IE instruction field flag = follow explicit instructions, IE action indicator = clear call), sends a RELEASE COMPLETE message (Cause value = 100).

L3BC_03_05

Ensure that the IUT, on receipt of a SETUP message (Call association information element with content error present, IE instruction field flag = follow explicit instructions, IE action indicator = discard message and report status), sends a STATUS message (Cause value = 100, call state value = 0).

L3BC_03_06

Ensure that the IUT, on receipt of a SETUP message (Call association information element with content error present, IE instruction field flag = follow explicit instructions, IE action indicator = discard message), sends no message.

6 Compliance

An ATS which complies with this TSS&TP specification shall:

- a) consist of a set of test cases corresponding to the set or to a subset of the TPs specified in clause 5;
- b) use a TSS which is an appropriate subset of the whole of the TSS specified in clause 4;
- c) use the same naming conventions for the test groups and test cases;
- d) maintain the relationship specified in clause 5 between the test groups and TPs and the entries in the PICS proforma to be used for test case deselection;
- e) comply with ISO/IEC 9646-2 [4].

In the case of a) or b) above, a subset shall be used only where a particular Abstract Test Method (ATM) makes some TPs untestable. All testable TPs from clause 5 shall be included in a compliant ATS.

7 Requirements for a comprehensive testing service

As a minimum the Remote test method, as specified in ISO/IEC 9646-2 [4], shall be used by any organization claiming to provide a comprehensive testing service for user equipment claiming conformance to EN 302 093-1 [1].

Bibliography

The following material, though not specifically referenced in the body of the present document (or not publicly available), gives supporting information.

- ISO/IEC 9646-3 (1998): "Information Technology; Open Systems Interconnection; Conformance Testing Methodology and Framework; Part 3: The Tree and Tabular Combined Notation (TTCN)".

History

Document history			
V1.1.1	July 1999	Public Enquiry	PE 9952: 1999-07-28 to 1999-11-26
V1.1.2	March 2000	Vote	V 20000505: 2000-03-06 to 2000-05-05