

Draft **ETSI EN 302 454-2** V1.1.1 (2006-02)

Candidate Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Meteorological Aids (Met Aids);
Radiosondes to be used in the
1 668,4 MHz to 1 690 MHz frequency range;
Part 2: Harmonized EN covering essential requirements
under article 3.2 of the R&TTE Directive**



ReferenceDEN/ERM-TG25-024-2

Keywordsradio, regulation, SRD, testing, UHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2006.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	4
Foreword.....	4
Introduction	5
1 Scope	7
2 References	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions	7
3.2 Symbols.....	7
3.3 Abbreviations	8
4 Technical requirements specifications	8
4.1 Transmitter requirements	8
4.1.1 Frequency error or frequency drift.....	8
4.1.2 Carrier power (conducted)	8
4.1.3 Effective radiated power	8
4.1.4 Transmission spectrum	8
4.1.5 Range of modulation bandwidth	8
4.1.6 Spurious emissions	8
4.1.7 Frequency stability under low-voltage conditions	8
5 Testing for compliance with technical requirements.....	9
5.1 Essential radio test suites.....	9
5.1.1 Environmental conditions for testing	9
5.1.1.1 Normal and extreme test-conditions.....	9
5.1.1.2 Test power source	9
5.1.2 Choice of samples for test suites.....	9
5.1.3 Transmitter test suites	9
5.1.3.1 Frequency error or drift.....	9
5.1.3.2 Carrier power (conducted)	9
5.1.3.3 Effective radiated power	9
5.1.3.4 Range of modulation bandwidth	9
5.1.3.5 Transmission spectrum.....	9
5.1.3.6 Spurious emissions.....	9
5.1.3.7 Frequency stability under low-voltage conditions	10
6 Interpretation of measurement results	10
Annex A (normative): The EN Requirements Table (EN-RT)	11
Annex B (informative): The EN title in the official languages	12
History	14

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Candidate Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [3] laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive") [1].

The present document is part 2 of a multi-part deliverable, covering digitally modulated radiosonde transmitters in the Meteorological Aids frequency band from 1 668,4 MHz to 1 690 MHz, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".

Technical specifications relevant to Directive 1999/5/EC [1] are given in annex A.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	36 months after doa

Introduction

The present document is part of a set of standards designed to fit in a modular structure to cover all radio and telecommunications terminal equipment under the R&TTE Directive [1]. Each standard is a module in the structure. The modular structure is shown in figure 1.




Figure 1: Modular structure for the various standards used under the R&TTE Directive [1]

The left hand edge of the figure 1 shows the different clauses of article 3 of the R&TTE Directive [1].

For article 3.3 various horizontal boxes are shown. Dotted lines indicate that at the time of publication of the present document essential requirements in these areas have to be adopted by the Commission. If such essential requirements are adopted, and as far and as long as they are applicable, they will justify individual standards whose scope is likely to be specified by function or interface type.

The vertical boxes show the standards under article 3.2 for the use of the radio spectrum by radio equipment. The scopes of these standards are specified either by frequency (normally in the case where frequency bands are harmonized) or by radio equipment type.

For article 3.1b figure 1 shows EN 301 489, the multi-part product EMC standard for radio used under the EMC Directive [3].

For article 3.1a figure 1 shows the existing safety standards currently used under the LV Directive and new standards covering human exposure to electromagnetic fields. New standards covering acoustic safety may also be required.

The bottom of figure 1 shows the relationship of the standards to radio equipment and telecommunications terminal equipment. A particular equipment may be radio equipment, telecommunications terminal equipment or both. A radio spectrum standard will apply if it is radio equipment. An article 3.3 standard will apply as well only if the relevant essential requirement under the R&TTE Directive [1] is adopted by the Commission and if the equipment in question is covered by the scope of the corresponding standard. Thus, depending on the nature of the equipment, the essential requirements under the R&TTE Directive [1] may be covered in a set of standards.

The modularity principle has been taken because:

- it minimizes the number of standards needed. Because equipment may, in fact, have multiple interfaces and functions it is not practicable to produce a single standard for each possible combination of functions that may occur in an equipment;
- it provides scope for standards to be added:
 - under article 3.2 when new frequency bands are agreed; or
 - under article 3.3 should the Commission take the necessary decisions;without requiring alteration of standards that are already published;
- it clarifies, simplifies and promotes the usage of Harmonized Standards as the relevant means of conformity assessment.

1 Scope

The present document applies to Radiosondes in the Meteorological Aids service as described in the scope of EN 302 454-1 [2].

The present document is intended to cover the provisions of article 3.2 of Directive 1999/5/EC (R&TTE Directive) [1], which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [2] ETSI EN 302 454-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Meteorological Aids (Met Aids); Radiosondes to be used in the 1 668,4 MHz to 1 690 MHz frequency range; Part 1: Technical characteristics and test methods".
- [3] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations (EMC Directives).
- [4] ETSI ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".
- [5] ETSI EN 301 489 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [1] and EN 302 454-1 [2] apply.

3.2 Symbols

For the purposes of the present document, the symbols defined in EN 302 454-1 [2] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations defined in EN 302 454-1 [2] apply.

4 Technical requirements specifications

4.1 Transmitter requirements

4.1.1 Frequency error or frequency drift

The following shall be met:

- the frequency error or frequency drift, as defined in EN 302 454-1 [2], clause 8.1.1, shall not exceed the limits given in EN 302 454-1 [2] in clause 8.1.2.

This requirement applies to all transmitters.

4.1.2 Carrier power (conducted)

The carrier power (conducted), as defined in EN 302 454-1 [2], clause 8.2.1, shall not exceed the limits in EN 302 454-1 [2], clause 8.2.3.

This requirement applies to transmitters, which may be used without an integral or dedicated antenna.

4.1.3 Effective radiated power

The effective radiated power, as defined in EN 302 454-1 [2], clause 8.3.1, shall not exceed the limits given in EN 302 454-1 [2], clause 8.3.3.

This requirement applies to transmitters with an integral or dedicated antenna.

4.1.4 Transmission spectrum

The transmission spectrum, as defined in EN 302 454-1 [2], clause 8.4.1, shall not exceed the limits in EN 302 454-1 [2], clause 8.4.3.

This requirement applies to all transmitters employing digital (non- analogue FM) modulation.

4.1.5 Range of modulation bandwidth

The modulation bandwidth, as defined in EN 302 454-1 [2], clause 8.5.1, shall not exceed the limits in EN 302 454-1 [2], clause 8.5.3.

This requirement applies to all transmitters if assigned frequency band has been subdivided into channels.

4.1.6 Spurious emissions

The spurious emissions, as defined in EN 302 454-1 [2], clause 8.6.1, shall not exceed the limits given in EN 302 454-1 [2], clause 8.6.5.

This requirement applies to all transmitters employing digital (non-analogue FM) modulation.

4.1.7 Frequency stability under low-voltage conditions

The frequency stability under low-voltage conditions, as defined in EN 302 454-1 [2], clause 8.7.1, shall comply conditions given in EN 302 454-1 [2], clause 8.7.3.

5 Testing for compliance with technical requirements

5.1 Essential radio test suites

5.1.1 Environmental conditions for testing

5.1.1.1 Normal and extreme test-conditions

Type tests shall be made under normal test conditions, and also, where stated, under extreme test conditions.

The test procedures shall be as specified in EN 302 454-1 [2], clauses 5.3 to 5.4.

5.1.1.2 Test power source

The test power source shall meet the requirements of EN 302 454-1 [2], clause 5.2.

5.1.2 Choice of samples for test suites

Measurement shall be performed, according to the present document, on samples of equipment defined in EN 302 454-1 [2], clauses 4.1.1 to 4.1.4.

5.1.3 Transmitter test suites

5.1.3.1 Frequency error or drift

The test specified in EN 302 454-1 [2], clause 8.1 shall be carried out.

5.1.3.2 Carrier power (conducted)

The test specified in EN 302 454-1 [2], clause 8.2 shall be carried out.

This test suite applies to Radiosondes which may be used without an integral or dedicated antenna.

5.1.3.3 Effective radiated power

The test specified in EN 302 454-1 [2], clause 8.3 shall be carried out.

This test suite applies to Radiosondes with an integral or dedicated antenna.

5.1.3.4 Range of modulation bandwidth

The tests specified in EN 302 454-1 [2], clause 8.5 1 shall be carried out.

This test suite applies to all transmitters if the assigned frequency band is divided into channels.

5.1.3.5 Transmission spectrum

The test specified in EN 302 454-1 [2], clause 8.4 shall be carried out.

This test suite applies to transmitters if the assigned frequency band is not divided into channels.

5.1.3.6 Spurious emissions

The test specified in EN 302 454-1 [2], clause 8.6 shall be carried out.

This test suite applies to all transmitters.

5.1.3.7 Frequency stability under low-voltage conditions

The test specified in EN 302 454-1 [2], clause 8.7 shall be carried out.

6 Interpretation of measurement results

The interpretation of the results recorded in the test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit shall be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be separately included in the test report;
- the value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 2.

Table 2: Measurement uncertainty

RF frequency	$\pm 1 \times 10^{-7}$
RF power, conducted	$\pm 0,75$ dB
Maximum frequency deviation:	
- within 300 Hz and 6 kHz of audio frequency	± 5 %
- within 6 kHz and 25 kHz of audio frequency	± 3 dB
Adjacent channel power	± 3 dB
Conducted emission of transmitter, valid up to 12,75 GHz	± 4 dB
Conducted emission of receivers	± 3 dB
Radiated emission of transmitter, valid up to 12,75 GHz	± 6 dB
Radiated emission of receiver, valid up to 12,75 GHz	± 6 dB

For the test methods, according to the present document the uncertainty figures shall be calculated according to the methods described in the ETR 028 [4] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 2 is based on such expansion factors.

The particular expansion factor used for the evaluation of the measurement uncertainty shall be stated.

Annex A (normative): The EN Requirements Table (EN-RT)

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the EN-RT proforma in this annex so that it can be used for its intended purposes and may further publish the completed EN-RT.

The EN Requirements Table (EN-RT) serves a number of purposes, as follows:

- it provides a tabular summary of all the requirements;
- it shows the status of each EN-R, whether it is essential to implement in all circumstances (Mandatory), or whether the requirement is dependent on the supplier having chosen to support a particular optional service or functionality (Optional). In particular it enables the EN-Rs associated with a particular optional service or functionality to be grouped and identified;
- when completed in respect of a particular equipment it provides a means to undertake the static assessment of conformity with the EN.

Table A.1: EN Requirements Table (EN-RT)

EN Reference		EN 302 454-2		Comment
No.	Reference	EN-R (see note)	Status	
1	4.1.1	Frequency error or frequency drift	M	
2	4.1.2	Carrier power (conducted)	M	
3	4.1.3	Effective radiated power	M	
4	4.1.4	Transmission spectrum	M	
5	4.1.5	Range of modulation bandwidth	M	
6	4.1.6	Spurious emissions	M	
7	4.1.7	Frequency stability under low-voltage conditions	M	

NOTE: These EN-Rs are justified under article 3.2 of the R&TTE Directive.

Key to columns:

No Table entry number.

Reference Clause reference number of conformance requirement within the present document.

EN-R Title of conformance requirement within the present document.

Status Status of the entry as follows:

M Mandatory, shall be implemented under all circumstances.

O Optional, may be provided, but if provided shall be implemented in accordance with the requirements.

O.n this status is used for mutually exclusive or selectable options among a set. The integer "n" shall refer to a unique group of options within the EN-RT. A footnote to the EN-RT shall explicitly state what the requirement is for each numbered group. For example, "It is mandatory to support at least one of these options", or, "It is mandatory to support exactly one of these options".

Comments To be completed as required.

Annex B (informative): The EN title in the official languages

Language	EN title
Czech	Elektromagnetická kompatibilita a rádiové spektrum (ERM); Pomocné prostředky pro meteorologii (Met Aids); Radiosondy jsou používány v kmitočtovém rozsahu 1 668,4 MHz až 1 690 MHz; Část 2: Harmonizovaná norma pokrývající hlavní požadavky článku 3.2 Směrnice R&TTE
Danish	Elektromagnetisk kompatibilitet og radiospektrumanliggender (ERM); Meteorologiske hjælpemidler (Met Aids); Radiosonder, som benytter frekvenser fra 1 668,4 kHz til 1 690 MHz. Del 2: Harmoniseret EN, som dækker de væsentlige krav i R og TTE-direktivets artikel 3.2.
Dutch	Elektromagnetische compatibiliteit en radiospectrumzaken (ERM); Meteorologische hulpmiddelen (Met Aids); te gebruiken in de frequentieband van 1 668,4 MHz tot 1 690 MHz; Deel 2: Geharmoniseerde Europese norm welke invulling geeft aan de wezelijke vereisten, neergelegd in artikel 3, lid 2, van Richtlijn 1999/5/EG Artikel 3, lid 2
English	Electromagnetic Compatibility and Radio spectrum Matters (ERM); Meteorological Aids (Met Aids); Radiosondes to be used in the 1 668,4 MHz to 1 690 MHz frequency band; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive
Estonian	Elektromagnetiline vastavus ja raadiospektri-alased küsimused (ERM); Meteoroloogilised vahendid (Met. vahendid); raadiosondid kasutamiseks sagedusalal 1 668,4 MHz kuni 1 690 MHz; 2. osa: Kooskõlastatud EN, mis reguleerib olulisimad nõuded vastavalt R&TTE direktiivi punktile 3.2.
Finnish	Sähkömagneettinen yhteensopivuus ja radiospektriasiat (ERM); Meteorologian apulaitteet (Met Aids); Taajuusalueella 1 668,4 MHz - 1 690 MHz toimivat radiosondit; Osa 2: Yhdenmukaistettu standardi (EN), joka kattaa R&TTE-direktiivin artiklan 3.2 mukaiset olennaiset vaatimukset
French	Compatibilité électromagnétique et spectre radioélectrique (ERM); Auxiliaires de la Météorologie (Met Aids); Les radiosondes fonctionnant dans la gamme de fréquences 1 668,4 MHz à 1 690 MHz; Partie 2: Norme harmonisée couvrant les exigences essentielles de l'article 3.2 de la directive R&TTE Article 3, paragraphe 2
German	Electromagnetic Compatibility and Radio spectrum Matters (ERM); Wetterhilfenfunk; Radiosonden im Frequenzbereich von 1 668,4 MHz bis 1 690 MHz; Teil 2: Harmonisierte Europäische Norm mit den wesentlichen Anforderungen gemäß Artikel 3.2 der R&TTE Richtlinie
Greek	Ηλεκτρομαγνητική συμβατότητα και Θέματα Ραδιοφάσματος (ERM): Μετεωρολογικά βοηθήματα (Met Aids): Ραδιοβολίδες που προορίζονται να χρησιμοποιηθούν στην περιοχή συχνοτήτων 1 668,4 MHz ως 1 690 MHz; Μέρος 2: Εναρμονισμένο πρότυπο EN για την κάλυψη ουσιαστών απαιτήσεων του Άρθρου 3.2 της Οδηγίας R&TTE
Hungarian	Elektromágneses kompatibilitás és rádió spektrum ügyek (ERM); Meteorológiai Segély (Met Segély); 1 668,4 MHz és 1 690 MHz közötti sávszélességben használható rádiószonda, 2. rész: Az R&TTE irányelv 3.2 cikke szerinti alapvető követelményekre vonatkozó összehangolt EN.
Italian	Compatibilità Elettromagnetica e Spettro Radio (ERM); Sistemi Ausiliari della Meteorologia (Met Aids); Apparati radiosonde operanti nella banda di frequenza da 1 668,4 MHz a 1 690 MHz; Parte 2: Norma europea armonizzata relativa ai requisiti essenziali di cui all'articolo 3, paragrafo 2, della direttiva R & TTE Articolo 3, paragrafo 2
Lettish	Elektromagnētiskā saderība un radio spektra jautājumi (ERM); Meteoroloģiskie līdzekļi (Met līdzekļi); radiosondes, kas lietojamas 1 668,4 MHz līdz 1 690 MHz frekvences joslā; 2. daļa: Saskaņots EN, kas regulē svarīgākās prasības saskaņā ar R&TTE Direktīvas 3.2. punktu
Lithuanian	Elektromagnetinio suderinamumo ir radijo dažnių spektro dalykai. Meteorologinės priemonės. Radijo zondai, naudojami nuo 1 668,4 MHz iki 1 690 MHz dažnių diapazone. 2 dalis. Darnusis Europos standartas, apimantis esminius reikalavimus pagal R&TTE direktyvos 3.2 straipsnį
Maltese	Kompatibilità elettromanjetika u materji relatati ma' spettru radjofoniku (ERM); Mezzi Meteorologiċi (Met Aids); Radjusondi li għandhom jintużaw fil-faxxa ta" frekwenzi 1668.4 MHz sa 1690 MHz; Parti 2: EN armonizzata li jkopri r-rekwiziti essenzjali taħt l-Artikolu 3.2 tad-Direttiva dwar R&TTE.
Polish	Kompatybilność Elektromagnetyczna i Zagadnienia Widma Radiowego (ERM); Urządzenia Meteorologiczne (Met Aids); Sondy radiowe używane w zakresie częstotliwości od 1 668,4 MHz do 1 690 MHz; Część 2: Zharmonizowana EN zawierająca zasadnicze wymagania zgodnie z art. 3.2 Dyrektywy R&TTE
Portuguese	Assuntos de Espectro Radioelétrico e Compatibilidade Electromagnética (ERM); Apoio à Meteorologia (Met Aids); Radiossondas para a faixa dos 1 668,4 MHz a 1 690 MHz; Parte 2: EN harmonizada cobrindo os requisitos essenciais no âmbito do artigo 3.2 da Directiva R&TTE Artigo 3.2
Slovakian	Elektromagnetická kompatibilita a otázky rádiového spektra (ERM); Meteorologické pomôcky (Met Aids); Rádiosondy určené pre frekvenčné pásmo od 1 668,4 MHz do 1 690 MHz; Časť 2: Harmonizovaná norma EN upravujúca základné požiadavky podľa článku 3.2 Smernice R&TTE"
Slovenian	Elektromagnetna združljivost (EMC) in zadeve v zvezi z radijskim spektrom (ERM) - Meteorološki pripomočki (Met Aids) - Radiosonde za uporabo v frekvenčnem območju od 1 668,4 MHz do 1 690 MHz - 2. del: Harmonizirani evropski standard (EN), ki zajema bistvene zahteve člena 3.2 direktive o radijski in telekomunikacijski terminalski opremi R&TTE

Language	EN title
Spanish	Compatibilidad Electromagnética y Cuestiones de Espectro de Radiofrecuencia (ERM); Ayudas a la Meteorología (Met Aids); Las radiosondas para ser usadas en el rango de frecuencia entre 1 668,4 MHz y 1 690 MHz; Parte 2: EN armonizada cubriendo los requisitos esenciales según el apartado 2 del artículo 3 de la Directiva de R&TTE Apartado 2 del artículo 3
Swedish	Elektromagnetisk kompatibilitet och radiospektrumfrågor (ERM); Meteorologiska hjälpanordningar (Met Aids); Radiosonder för användning i frekvensbandet 1 668,4 till MHz 1 690 MHz ; Del 2: Harmoniserad EN omfattande väsentliga krav enligt artikel 3.2 i R&TTE-direktivet

History

Document history			
V1.1.1	February 2006	Public Enquiry	PE 20060623: 2006-02-22 to 2006-06-23