

Final draft **ETSI EN 302 617-2** V1.1.1 (2010-06)

---

*Harmonized European Standard (Telecommunications series)*

**Electromagnetic compatibility  
and Radio spectrum Matters (ERM);  
Ground-based UHF radio  
transmitters, receivers and transceivers for the UHF  
aeronautical mobile service using amplitude modulation;  
Part 2: Harmonized EN covering the essential requirements  
of article 3.2 of the R&TTE Directive**

---



---

Reference

DEN/ERM-JTFEA-002-2

---

Keywords

aeronautical, AM, DSB, radio, testing, UHF

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Introduction .....	5
1 Scope .....	6
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	6
3 Definitions and abbreviations.....	7
3.1 Definitions .....	7
3.2 Abbreviations .....	7
4 Technical requirements specifications .....	7
4.1 Environmental profile.....	7
4.2 Conformance requirements .....	8
4.2.1 Transmitter requirements .....	8
4.2.1.1 Frequency error .....	8
4.2.1.2 Carrier power (conducted) .....	8
4.2.1.3 Adjacent channel power .....	8
4.2.1.4 Conducted spurious emissions .....	8
4.2.1.5 Intermodulation attenuation .....	8
4.2.1.6 Keying transient frequency behaviour .....	8
4.2.1.7 Cabinet Radiation.....	8
4.2.2 Receiver requirements .....	8
4.2.2.1 Sensitivity .....	8
4.2.2.2 Adjacent channel rejection.....	8
4.2.2.3 Spurious response rejection.....	9
4.2.2.4 Intermodulation response rejection .....	9
4.2.2.5 Blocking or desensitisation .....	9
4.2.2.6 Conducted spurious emissions .....	9
4.2.2.7 Cross modulation rejection .....	9
4.2.2.8 Cabinet radiation .....	9
5 Testing for compliance with technical requirements.....	9
5.1 Environmental conditions for testing .....	9
5.2 Interpretation of the measurement results .....	9
5.3 Essential radio test suites.....	10
5.3.1 Transmitter test specifications .....	10
5.3.1.1 Frequency error .....	10
5.3.1.2 Carrier power (conducted) .....	10
5.3.1.3 Adjacent channel power .....	10
5.3.1.4 Conducted spurious emissions .....	10
5.3.1.5 Intermodulation attenuation .....	10
5.3.1.6 Keying transient frequency behaviour .....	10
5.3.1.7 Cabinet Radiation.....	11
5.3.2 Receiver test specifications.....	11
5.3.2.1 Sensitivity .....	11
5.3.2.2 Adjacent channel rejection.....	11
5.3.2.3 Spurious response rejection.....	11
5.3.2.4 Intermodulation response rejection .....	11
5.3.2.5 Blocking or desensitisation .....	11
5.3.2.6 Conducted spurious emissions .....	11
5.3.2.7 Cross modulation rejection .....	11
5.3.2.8 Cabinet Radiation.....	11

<b>Annex A (normative):</b>	<b>HS Requirements and conformance Test specifications Table (HS-RTT) .....</b>	<b>12</b>
<b>Annex B (informative):</b>	<b>The EN title in the official languages .....</b>	<b>14</b>
<b>Annex C (informative):</b>	<b>Bibliography .....</b>	<b>15</b>
History .....		16

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.5] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.2] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 2 of a multi-part deliverable covering Ground-based UHF radio transmitters, receivers and transceivers for the UHF aeronautical mobile service using amplitude modulation, as identified below:

Part 1: "Technical characteristics and methods of measurement";

**Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".**

<b>Proposed national transposition dates</b>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.4].

---

# 1 Scope

The present document applies to DSB AM ground base stations, with channel separations of 25 kHz intended for analogue speech. The scope of the present document is limited to ground based transmitters, receivers and transceivers. These radio equipment types are capable of operating in all or any part of the aeronautical frequency band between 225 MHz and 399,975 MHz.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive), article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive as well as essential requirements under the Single European Sky Interoperability Regulation (as amended) [i.3] and related implementing rules may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

---

# 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 302 617-1 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Ground-based UHF radio transmitters, receivers and transceivers for the UHF aeronautical mobile service using amplitude modulation; Part 1: Technical characteristics and methods of measurement".
- [2] ETSI EN 300 113-1 (V1.6.2): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive) as amended by Regulation (EC) 1882/2003 of the European Parliament and of the Council of 29 March 2003.

- [i.3] Regulation (EC) 552/2004 of the European Parliament and Council of 10 March 2004 on the interoperability of the European Air Traffic Management network (the interoperability Regulation), OJEU L96, 31.03.2004, p. 26-42 as amended by Regulation (EC) 1070/2009 of the European Parliament and of the Council of 21 October 2009, OJEU L300/34, 14/11/2009.
- [i.4] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [i.5] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations and of rules on information society services.

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.2] and the following apply:

**aeronautical mobile service:** mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

**conducted measurements:** measurements which are made using a direct RF connection to the equipment under test

**environmental profile:** range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

**ground base station:** aeronautical station equipment, in the aeronautical mobile service, for use with an external antenna and intended for use at a fixed location

**radiated measurements:** measurements which involve the measurement of a radiated field

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AM	Amplitude Modulation
DSB	Double Side Band
RF	Radio Frequency
R&TTE	Radio and Telecommunications Terminal Equipment

## 4 Technical requirements specifications

### 4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

## 4.2 Conformance requirements

### 4.2.1 Transmitter requirements

#### 4.2.1.1 Frequency error

The frequency error as defined in clause 7.2 of EN 302 617-1 [1] shall not exceed the values shown in table 1 of EN 302 617-1 [1].

#### 4.2.1.2 Carrier power (conducted)

The carrier power as defined in clause 7.3.1 of EN 302 617-1 [1] shall conform to the requirements in clause 7.3.3 of EN 302 617-1 [1].

#### 4.2.1.3 Adjacent channel power

Adjacent channel power as defined in clause 7.5.1 of EN 302 617-1 [1] shall conform to the requirements in clause 7.5.3 of EN 302 617-1 [1].

#### 4.2.1.4 Conducted spurious emissions

Conducted spurious emissions as defined in clause 7.7.1 of EN 302 617-1 [1] shall conform to the limits in clause 7.7.3, table 3 of EN 302 617-1 [1].

#### 4.2.1.5 Intermodulation attenuation

Intermodulation attenuation as defined in clause 7.8.1 of EN 302 617-1 [1] shall conform to the limits in clause 7.8.3 of EN 302 617-1 [1].

#### 4.2.1.6 Keying transient frequency behaviour

Keying transient frequency behaviour as defined in clause 7.10.1 of EN 302 617-1 [1] shall conform to the limits in clause 7.10.3 of EN 302 617-1 [1].

#### 4.2.1.7 Cabinet Radiation

Cabinet radiation as defined in clause 7.12 of EN 302 617-1 [1] shall conform to the limits in clause 7.5.4 of EN 300 113-1 [2].

### 4.2.2 Receiver requirements

NOTE: These aspects and parameters are considered essential to ensure immediate and successful ground to air communication. Inadequate performance in any of these aspects may lead to retransmission with consequential inefficient use of the spectrum.

#### 4.2.2.1 Sensitivity

Sensitivity as defined in clause 8.1.1 of EN 302 617-1 [1] shall conform to the limits in clause 8.1.3 of EN 302 617-1 [1].

#### 4.2.2.2 Adjacent channel rejection

Adjacent channel rejection as defined in clause 8.6.1 of EN 302 617-1 [1] shall conform to the limits in clause 8.6.3 of EN 302 617-1 [1].



#### 4.2.2.3 Spurious response rejection

Spurious response rejection as defined in clause 8.7.1 of EN 302 617-1 [1] shall conform to the limits in clause 8.7.5 of EN 302 617-1 [1].

#### 4.2.2.4 Intermodulation response rejection

Intermodulation response rejection as defined in clause 8.8.1 of EN 302 617-1 [1] shall conform to the limits in clause 8.8.3 of EN 302 617-1 [1].

#### 4.2.2.5 Blocking or desensitisation

Blocking or desensitisation as defined in clause 8.9.1 of EN 302 617-1 [1] shall conform to the limits in clause 8.9.3 of EN 302 617-1 [1].

#### 4.2.2.6 Conducted spurious emissions

Conducted spurious emissions as defined in clause 8.10.1 of EN 302 617-1 [1] shall conform to the limits in clause 8.10.3 (table 4) of EN 302 617-1 [1].

#### 4.2.2.7 Cross modulation rejection

Cross modulation rejection as defined in clause 8.12.1 of EN 302 617-1 [1] shall conform to the limits in clause 8.12.3 of EN 302 617-1 [1].

#### 4.2.2.8 Cabinet radiation

Cabinet radiation as defined in clause 8.16 of EN 302 617-1 [1] shall conform to the limits in clause 8.10.4 of EN 300 113-1 [2].

---

## 5 Testing for compliance with technical requirements

### 5.1 Environmental conditions for testing

Tests defined in the present document shall be carried out at representative points within the boundary limits of the declared operational environmental profile.

The test conditions and procedures shall be as defined in clauses 5 and 6 of EN 302 617-1 [1].

### 5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the recorded value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 1.

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028 [i.1] and shall correspond to an expansion factor (coverage factor)  $k = 1,96$  or  $k = 2$  (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 1 is based on such expansion factors.

**Table 1: Measurement uncertainty: maximum values**

Measurement uncertainties	Maximum values
Adjacent channel power	±2,5 dB
Adjacent channel rejection	±4 dB
Blocking and desensitization	±4 dB
Carrier power (normal and extreme test conditions)	±0,75 dB
Conducted spurious emissions: below 1 GHz	±3 dB
between 1 GHz and 4 GHz	±6 dB
Conducted spurious radiation: below 1 GHz	±3 dB
between 1 GHz and 4 GHz	±6 dB
Cabinet radiation	
Cross modulation rejection	±4 dB
Effective acceptance bandwidth	±3 dB
Frequency error	±1 x 10 <sup>-9</sup>
Intermodulation	±3 dB
Intermodulation response rejection	±3 dB
Keying transient frequency behaviour	±3 dB
Receiver dynamic range	±2 dB
Receiver sensitivity	±3 dB
Spurious response rejection	±4 dB
Transient frequency behaviour	±250 Hz

For the test methods according to the present document the uncertainty figures are valid to a confidence level of 95 % calculated according to the methods described in TR 100 028 [i.1].

## 5.3 Essential radio test suites

### 5.3.1 Transmitter test specifications

#### 5.3.1.1 Frequency error

The test procedure specified in clause 7.2.2 of EN 302 617-1 [1] shall be carried out.

#### 5.3.1.2 Carrier power (conducted)

The test procedure specified in clause 7.3.2 of EN 302 617-1 [1] shall be carried out.

#### 5.3.1.3 Adjacent channel power

The test procedure specified in clause 7.5.2 of EN 302 617-1 [1] shall be carried out.

#### 5.3.1.4 Conducted spurious emissions

The test procedure specified in clause 7.7.2 of EN 302 617-1 [1] shall be carried out.

#### 5.3.1.5 Intermodulation attenuation

The test procedure specified in clause 7.8.2 of EN 302 617-1 [1] shall be carried out.

#### 5.3.1.6 Keying transient frequency behaviour

The test procedure specified in clause 7.10.2 of EN 302 617-1 [1] shall be carried out.

### 5.3.1.7 Cabinet Radiation

The test procedure specified in clause 7.5.3 of EN 300 113-1 [2] shall be carried out.

## 5.3.2 Receiver test specifications

### 5.3.2.1 Sensitivity

The test procedure specified in clause 8.1.2 of EN 302 617-1 [1] shall be carried out.

### 5.3.2.2 Adjacent channel rejection

The test procedure specified in clause 8.6.2 of EN 302 617-1 [1] shall be carried out.

### 5.3.2.3 Spurious response rejection

The test procedures specified in clauses 8.7.3 and 8.7.4 of EN 302 617-1 [1] shall be carried out.

### 5.3.2.4 Intermodulation response rejection

The test procedure specified in clause 8.8.2 of EN 302 617-1 [1] shall be carried out.

### 5.3.2.5 Blocking or desensitisation

The test procedure specified in clause 8.9.2 of EN 302 617-1 [1] shall be carried out.

### 5.3.2.6 Conducted spurious emissions

The test procedure specified in clause 8.10.2 of EN 302 617-1 [1] shall be carried out.

### 5.3.2.7 Cross modulation rejection

The test procedure specified in clause 8.12.2 of EN 302 617-1 [1] shall be carried out.

### 5.3.2.8 Cabinet Radiation

The test procedure specified in clause 8.10.3 of EN 300 113-1 [2] shall be carried out.

## Annex A (normative): HS Requirements and conformance Test specifications Table (HS-RTT)

The HS Requirements and conformance Test specifications Table (HS-RTT) in table A.1 serves a number of purposes, as follows:

- it provides a statement of all the requirements in words and by cross reference to (a) specific clause(s) in the present document or to (a) specific clause(s) in (a) specific referenced document(s);
- it provides a statement of all the test procedures corresponding to those requirements by cross reference to (a) specific clause(s) in the present document or to (a) specific clause(s) in (a) specific referenced document(s);
- it qualifies each requirement to be either:
  - Unconditional: meaning that the requirement applies in all circumstances, or
  - Conditional: meaning that the requirement is dependant on the manufacturer having chosen to support optional functionality defined within the schedule.
- in the case of Conditional requirements, it associates the requirement with the particular optional service or functionality;
- it qualifies each test procedure to be either:
  - Essential: meaning that it is included with the Essential Radio Test Suite and therefore the requirement shall be demonstrated to be met in accordance with the referenced procedures;
  - Other: meaning that the test procedure is illustrative but other means of demonstrating compliance with the requirement are permitted.

**Table A.1: HS Requirements and conformance Test specifications Table (HS-RTT)**

<b>Harmonized Standard EN 302 617-2</b>						
The following requirements and test specifications are relevant to the presumption of conformity under the article 3.2 of the R&TTE Directive [i.2]						
<b>Requirement</b>			<b>Requirement Conditionality</b>		<b>Test Specification</b>	
<b>No</b>	<b>Description</b>	<b>Reference: Clause No</b>	<b>U/C</b>	<b>Condition</b>	<b>E/O</b>	<b>Reference: Clause No</b>
1	Frequency error	4.2.1.1	U		E	5.3.1.1
2	Carrier power	4.2.1.2	U		E	5.3.1.2
3	Adjacent channel power	4.2.1.3	U		E	5.3.1.3
4	Conducted spurious emissions (TX)	4.2.1.4	U		E	5.3.1.4
5	Intermodulation attenuation	4.2.1.5	U		E	5.3.1.5
6	Keying transient behaviour	4.2.1.6	U		E	5.3.1.6
7	Cabinet radiation	4.2.1.7	U		E	5.3.1.7
8	Sensitivity	4.2.2.1	U		E	5.3.2.1
9	Adjacent channel rejection	4.2.2.2	U		E	5.3.2.2
10	Spurious response rejection	4.2.2.3	U		E	5.3.2.3
11	Intermodulation response rejection	4.2.2.4	U		E	5.3.2.4
12	Blocking or desensitisation	4.2.2.5	U		E	5.3.2.5
13	Conducted spurious emissions	4.2.2.6	U		E	5.3.2.6

Harmonized Standard EN 302 617-2						
The following requirements and test specifications are relevant to the presumption of conformity under the article 3.2 of the R&TTE Directive [i.2]						
Requirement			Requirement Conditionality		Test Specification	
No	Description	Reference: Clause No	U/C	Condition	E/O	Reference: Clause No
14	Cross modulation rejection	4.2.2.7	U		E	5.3.2.7
15	Cabinet radiation	4.2.2.8	U		E	5.3.2.8

**Key to columns:****Requirement:**

**No** A unique identifier for one row of the table which may be used to identify a requirement or its test specification.

**Description** A textual reference to the requirement.

**Clause Number** Identification of clause(s) defining the requirement in the present document unless another document is referenced explicitly.

**Requirement Conditionality:**

**U/C** Indicates whether the requirement is to be *unconditionally* applicable (U) or is *conditional* upon the manufacturers claimed functionality of the equipment (C).

**Condition** Explains the conditions when the requirement shall or shall not be applicable for a technical requirement which is classified "conditional".

**Test Specification:**

**E/O** Indicates whether the test specification forms part of the Essential Radio Test Suite (E) or whether it is one of the Other Test Suite (O).

**NOTE:** All tests whether "E" or "O" are relevant to the requirements. Rows designated "E" collectively make up the Essential Radio Test Suite; those designated "O" make up the Other Test Suite; for those designated "X" there is no test specified corresponding to the requirement. The completion of all tests classified "E" as specified with satisfactory outcomes is a necessary condition for a presumption of conformity. Compliance with requirements associated with tests classified "O" or "X" is a necessary condition for presumption of conformity, although conformance with the requirement may be claimed by an equivalent test or by manufacturer's assertion supported by appropriate entries in the technical construction file.

**Clause Number** Identification of clause(s) defining the test specification in the present document unless another document is referenced explicitly. Where no test is specified (that is, where the previous field is "X") this field remains blank.

---

## Annex B (informative): The EN title in the official languages

The enlargement of the European Union (EU) resulted in a requirement from the EU for a larger number of languages for the translation of the titles of Harmonized Standards and mandated ENs that are to be listed in the Official Journal to support the implementation of this legislation.

For this reason the title translation concerning the present document can be consulted via the [e-approval](#) application.

---

## Annex C (informative): Bibliography

- Commission Regulation (EC) No 1265/2007 of 26 October 2007 laying down requirements on air-ground voice channel spacing for the single European sky (Text with EEA relevance), OJEU L283, 27.10.2007, p. 25-36.

---

## History

<b>Document history</b>		
V1.1.1	June 2010	One-step Approval Procedure OAP 20101020: 2010-06-22 to 2010-10-20