



Harmonized European Standard

**Electromagnetic compatibility and
Radio spectrum Matters (ERM);
Portable Very High Frequency (VHF) radiotelephone
equipment for the maritime mobile service operating
in the VHF bands with integrated handheld class D DSC;
Part 3: Harmonized EN covering the essential requirements
of article 3.3(e) of the R&TTE Directive**

Reference

REN/ERM-TG26-104-3

Keywords

DSC, maritime, radio, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations	9
4 Technical requirements specifications	9
4.1 Environmental profile.....	9
4.2 General, operational and technical requirements.....	10
4.2.1 General and operational requirements	10
4.2.1.1 Requirements	10
4.2.1.2 Conformance.....	10
4.2.2 Technical requirements.....	10
4.2.2.1 Requirements	10
4.2.2.2 Conformance.....	10
4.3 Environmental requirements	10
4.3.1 Drop test	10
4.3.1.1 Definition	10
4.3.1.2 Requirement	10
4.3.1.3 Conformance.....	10
4.3.2 Temperature tests.....	10
4.3.2.1 Definition	10
4.3.2.2 Dry heat.....	11
4.3.2.2.1 Definition.....	11
4.3.2.2.2 Requirement	11
4.3.2.2.3 Conformance	11
4.3.2.3 Damp heat	11
4.3.2.3.1 Definition.....	11
4.3.2.3.2 Requirement	11
4.3.2.3.3 Conformance	11
4.3.2.4 Low temperature	11
4.3.2.4.1 Definition.....	11
4.3.2.4.2 Requirement	11
4.3.2.4.3 Conformance	11
4.4 Conformance requirements	11
4.4.1 Sensitivity of the modulator, including microphone.....	11
4.4.1.1 Definition	11
4.4.1.2 Limit.....	11
4.4.1.3 Conformance.....	12
4.4.2 Audio frequency response	12
4.4.2.1 Definition	12
4.4.2.2 Limit.....	12
4.4.2.3 Conformance.....	12
4.4.3 Audio frequency harmonic distortion of the emission.....	12
4.4.3.1 Definition	12
4.4.3.2 Limit.....	12
4.4.3.3 Conformance.....	12
4.4.4 Residual modulation of the transmitter	12
4.4.4.1 Definition	12

4.4.4.2	Limit.....	12
4.4.4.3	Conformance.....	12
4.4.5	Harmonic distortion and rated audio-frequency output power	12
4.4.5.1	Definition	12
4.4.5.2	Limit.....	12
4.4.5.3	Conformance.....	13
4.4.6	Receiver audio frequency response	13
4.4.6.1	Definition	13
4.4.6.2	Limit.....	13
4.4.6.3	Conformance.....	13
4.4.7	Receiver noise and hum level	13
4.4.7.1	Definition	13
4.4.7.2	Limit.....	13
4.4.7.3	Conformance.....	13
4.4.8	Squelch operation	13
4.4.8.1	Definition	13
4.4.8.2	Limit.....	13
4.4.8.3	Conformance.....	13
4.4.9	Squelch hysteresis.....	13
4.4.9.1	Definition	13
4.4.9.2	Limit.....	13
4.4.9.3	Conformance.....	14
4.4.10	Receiver scanning efficiency	14
4.4.10.1	Definition	14
4.4.10.2	Limit.....	14
4.4.10.3	Conformance.....	14
4.5	DSC Signalling.....	14
4.5.1	DSC Call Validation	14
4.5.2	Display.....	14
4.5.3	GNSS receiver	14
4.5.4	Individual DSC calls.....	14
4.5.5	All ships calls.....	14
4.5.6	DSC call functionality	14
4.5.7	DSC message composition	14
4.5.8	Prioritized wait.....	14
4.5.9	Alarms	15
4.5.10	Standby	15
4.5.11	GNSS fix - sending distress	15
4.5.12	Tasks - sending distress	15
4.5.13	Display - sending distress	15
4.5.14	Distress button sub procedure	15
4.5.15	Transmission of the alert attempt.....	15
4.5.16	Updating position.....	15
4.5.17	Handling received DSC messages - sending distress.....	15
4.5.18	Alarms - sending distress	15
4.5.19	Determining subsequent communications - sending distress.....	15
4.5.20	Automated tuning - sending distress	15
4.5.21	Cancelling the distress alert	16
4.5.22	Acknowledgements - sending distress	16
4.5.23	Termination - sending distress	16
4.5.24	Warnings - sending distress	16
4.5.25	Tasks - receiving distress	16
4.5.26	Display - receiving distress.....	16
4.5.27	Handling received DSC messages - receiving distress	16
4.5.28	Alarms - receiving distress	16
4.5.29	Determining subsequent communications - receiving distress	16
4.5.30	Automated tuning - receiving distress	16
4.5.31	Acknowledgements - receiving distress.....	16
4.5.32	Termination - receiving distress.....	16
4.5.33	Warnings - receiving distress.....	16
4.5.34	Tasks - sending non distress	17
4.5.35	Display - sending non distress	17

4.5.36	Handling received DSC messages - sending non distress	17
4.5.37	Alarms - sending non distress	17
4.5.38	Automated tuning - sending non distress	17
4.5.39	Delayed acknowledgements - sending non distress	17
4.5.40	Termination - sending non distress	17
4.5.41	Warnings - sending non distress	17
4.5.42	Tasks - receiving non distress	17
4.5.43	Display - receiving non distress	17
4.5.44	Handling received DSC messages - receiving non distress	17
4.5.45	Alarms - receiving non distress	17
4.5.46	Automated tuning - receiving non distress	17
4.5.47	Acknowledgements - receiving non distress	18
4.5.48	Termination - receiving non distress	18
4.5.49	Warnings - receiving non distress	18
4.5.50	Communication automated procedure	18
4.5.51	Tasks - communication	18
4.5.52	Display - communication	18
4.5.53	Handling received DSC messages - communication	18
4.5.54	Tuning of the receiver and transmitter - communication	18
4.5.55	Termination - communication	18
4.5.56	Tasks of handling incoming calls while engaged	18
4.5.57	Termination of automated procedures	18
4.5.58	Actions after termination of an automated procedure	18
4.5.59	Putting automated procedures on hold	18
4.5.60	Controlling non-terminated automated procedures on hold	19
4.5.61	Sending and receiving distress alert scanning	19
4.5.62	Normal scan	19
4.5.63	Multiple watch scan	19
5	Testing for compliance with technical requirements	19
5.1	Test conditions, power supply and ambient temperatures	19
5.2	Interpretation of the measurement results	19
5.3	Essential radio test suites	20
5.3.1	Environmental tests	20
5.3.1.1	Introduction	20
5.3.1.2	Procedure	20
5.3.1.3	Performance check	20
5.3.1.4	Drop test	20
5.3.1.4.1	Definition	20
5.3.1.4.2	Limit	20
5.3.1.4.3	Conformance	20
5.3.1.5	Temperature tests	21
5.3.1.5.1	Dry heat	21
5.3.1.5.2	Damp heat	21
5.3.1.5.3	Low temperature	21
5.3.2	Conformance tests	21
5.3.2.1	Sensitivity of the modulator, including microphone	21
5.3.2.2	Audio frequency response	21
5.3.2.3	Audio frequency harmonic distortion of the emission	22
5.3.2.4	Residual modulation of the transmitter	22
5.4	Other test suites	22
5.4.1	General	22
5.4.2	Harmonic distortion and rated audio-frequency output power	22
5.4.3	Receiver audio frequency response	22
5.4.4	Receiver noise and hum level	22
5.4.5	Squelch operation	22
5.4.6	Squelch hysteresis	22
5.4.7	Receiver scanning efficiency	22
Annex A (normative):	HS Requirements and conformance Test specifications Table	
	(HS-RTT)	23

Annex B: Void27
History28

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This draft Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document has been produced by ETSI in response to the European Commission mandate M/357 issued under Directive 98/34/EC [i.2] as amended by Directive 98/48/EC [i.5].

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.1].

See article 5.1 of Directive 1999/5/EC [i.1] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.1] are summarized in annex A.

The present document is part 3 of a multi-part deliverable covering the Electromagnetic compatibility and Radio spectrum Matters (ERM); Portable Very High Frequency (VHF) radiotelephone equipment for the maritime mobile service operating in the VHF bands with integrated handheld class D DSC, as identified below:

- Part 1: "Technical characteristics and methods of measurement";
- Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 3: "Harmonized EN covering the essential requirements of article 3.3(e) of the R&TTE Directive".**

National transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.1]. The modular structure is shown in EG 201 399 [i.4].

1 Scope

The present document states the minimum technical characteristics and methods of measurement required for portable Very High Frequency (VHF) radiotelephones with integrated handheld class D DSC operating in certain frequency bands allocated to the maritime mobile service using either 25 kHz channels or 25 kHz and 12,5 kHz channels.

The present document also specifies technical characteristics, methods of measurement and required test results.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.1] (R&TTE Directive) article 3.3(e), which states that radio equipment within the scope of the present document "*...shall be so constructed that:.... (e) it supports certain features ensuring access to emergency services;....*".

In addition to the present document, other European Norms (ENs) that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.1] will apply to equipment within the scope of the present document.

NOTE: A list of such European Norms is included on the web site <http://www.newapproach.org/>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 302 885-1 (V1.3.0) (05-2013): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Portable Very High Frequency (VHF) radiotelephone equipment for the maritime mobile service operating in the VHF bands with integrated handheld class D DSC; Part 1: Technical characteristics and methods of measurement".
- [2] ETSI TR 100 028-1 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [3] ETSI EN 300 338-5 (V1.1.1) (02-2011): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 5: Handheld VHF Class D DSC".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).

- [i.2] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.3] EC decision 2004/71/EC of 4 September 2003 on essential requirements relating to marine radio communication equipment which is intended to be used on non-SOLAS vessels and to participate in the Global Maritime Distress and Safety System (GMDSS).
- [i.4] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.5] Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 amending Directive 98/34/EC laying down a procedure for the provision of information in the field of technical standards and regulations.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.1] and the following apply:

class D: intended to provide minimum facilities for VHF DSC distress, urgency and safety as well as routine calling and reception, not necessarily in full accordance with IMO GMDSS carriage requirements for VHF installations

NOTE: For handheld VHF a reduced functionality is permitted compared to a fixed VHF class D.

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

G2B: phase-modulation with digital information, with a sub-carrier for DSC operation

G3E: phase-modulation (Frequency modulation with a pre-emphasis of 6 dB/octave) for speech

modulation index: ratio between the frequency deviation and the frequency of the modulation signal

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

DSC	Digital Selective Calling
GMDSS	Global Maritime Distress and Safety System
IMO	International Maritime Organization
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
SOLAS	Safety Of Life And Sea
VHF	Very High Frequency

4 Technical requirements specifications

4.1 Environmental profile

Tests defined in the present document shall be carried out at representative points within the boundary limits of the declared operational environmental profile which, as a minimum, shall be that specified in the test conditions contained in the present document.

As technical performance varies subject to environmental conditions, tests shall be carried out under a sufficient variety of environmental conditions as specified in the present document to give confidence of compliance for the affected technical requirements. These environmental conditions represent those required by article 2 of EC Decision 2004/71/EC [i.3] (which shall also be within the boundary limits of the declared operational environmental profile).

4.2 General, operational and technical requirements

4.2.1 General and operational requirements

4.2.1.1 Requirements

The general and operational requirements are defined in EN 302 885-1 [1], clause 4.

4.2.1.2 Conformance

The manufacturer shall declare that compliance to these requirements is achieved and shall provide relevant documentation.

4.2.2 Technical requirements

4.2.2.1 Requirements

The technical requirements are defined in EN 302 885-1 [1], clause 5.

4.2.2.2 Conformance

The manufacturer shall declare that compliance to these requirements is achieved and shall provide relevant documentation.

4.3 Environmental requirements

4.3.1 Drop test

4.3.1.1 Definition

This test is defined in EN 302 885-1 [1], clause 7.3.1.

4.3.1.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 302 885-1 [1], clause 7.3.3.

4.3.1.3 Conformance

Relevant environment tests as defined in clause 5.3.1.4 shall be carried out.

4.3.2 Temperature tests

4.3.2.1 Definition

This series of tests is defined in EN 302 885-1 [1], clause 7.4.1.

4.3.2.2 Dry heat

4.3.2.2.1 Definition

This test is defined in EN 302 885-1 [1], clause 7.4.2.1.

4.3.2.2.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 302 885-1 [1], clause 7.2.

4.3.2.2.3 Conformance

Relevant environment tests as defined in clause 5.3.1.5.1 shall be carried out.

4.3.2.3 Damp heat

4.3.2.3.1 Definition

This test is defined in EN 302 885-1 [1], clause 7.4.3.1.

4.3.2.3.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 302 885-1 [1], clause 7.2.

4.3.2.3.3 Conformance

Relevant environment tests as defined in clause 5.3.1.5.2 shall be carried out.

4.3.2.4 Low temperature

4.3.2.4.1 Definition

This test is defined in EN 302 885-1 [1], clause 7.4.4.1.

4.3.2.4.2 Requirement

The equipment shall meet the requirements of the performance check defined in EN 302 885-1 [1], clause 7.2.

4.3.2.4.3 Conformance

Relevant environment tests as defined in clause 5.3.1.5.3 shall be carried out.

4.4 Conformance requirements

4.4.1 Sensitivity of the modulator, including microphone

4.4.1.1 Definition

This test is defined in EN 302 885-1 [1], clause 8.4.1.

4.4.1.2 Limit

The frequency deviation shall be as stated in EN 302 885-1 [1], clause 8.4.3.

4.4.1.3 Conformance

Conformance tests as defined in clause 5.3.2.1 shall be carried out.

4.4.2 Audio frequency response

4.4.2.1 Definition

This test is defined in EN 302 885-1 [1], clause 8.5.1.

4.4.2.2 Limit

The audio frequency response shall lie within the limits shown in EN 302 885-1 [1], clause 8.5.3, figure 2.

4.4.2.3 Conformance

Conformance tests as defined in clause 5.3.2.2 shall be carried out.

4.4.3 Audio frequency harmonic distortion of the emission

4.4.3.1 Definition

This test is defined in EN 302 885-1 [1], clause 8.6.1.

4.4.3.2 Limit

The harmonic distortion limit shall be as stated in EN 302 885-1 [1], clause 8.6.3.

4.4.3.3 Conformance

Conformance tests as defined in clause 5.3.2.3 shall be carried out.

4.4.4 Residual modulation of the transmitter

4.4.4.1 Definition

This test is defined in EN 302 885-1 [1], clause 8.10.1.

4.4.4.2 Limit

The residual modulation shall not exceed the limit stated in EN 302 885-1 [1], clause 8.10.3.

4.4.4.3 Conformance

Conformance tests as defined in clause 5.3.2.4 shall be carried out.

4.4.5 Harmonic distortion and rated audio-frequency output power

4.4.5.1 Definition

This test is defined in EN 302 885-1 [1], clause 9.1.1.

4.4.5.2 Limit

The rated audio-frequency output power shall comply with the limits stated in EN 302 885-1 [1], clause 9.1.3.

4.4.5.3 Conformance

Conformance tests as defined in clause 5.4.2 may be carried out.

4.4.6 Receiver audio frequency response

4.4.6.1 Definition

This test is defined in EN 302 885-1 [1], clause 9.2.1.

4.4.6.2 Limit

The audio frequency response shall lie within the limits shown in EN 302 885-1 [1], clause 9.2.3, figure 5.

4.4.6.3 Conformance

Conformance tests as defined in clause 5.4.3 may be carried out.

4.4.7 Receiver noise and hum level

4.4.7.1 Definition

This test is defined in EN 302 885-1 [1], clause 9.11.1.

4.4.7.2 Limit

The receiver residual noise level shall not exceed the limit stated in EN 302 885-1 [1], clause 9.11.3.

4.4.7.3 Conformance

Conformance tests as defined in clause 5.4.4 may be carried out.

4.4.8 Squelch operation

4.4.8.1 Definition

This test is defined in EN 302 885-1 [1], clause 9.12.1.

4.4.8.2 Limit

The squelch operation shall comply with the limits stated in EN 302 885-1 [1], clause 9.12.3.

4.4.8.3 Conformance

Conformance tests as defined in clause 5.4.5 may be carried out.

4.4.9 Squelch hysteresis

4.4.9.1 Definition

This test is defined in EN 302 885-1 [1], clause 9.13.1.

4.4.9.2 Limit

The squelch hysteresis shall comply with the limits stated in EN 302 885-1 [1], clause 9.13.3.

4.4.9.3 Conformance

Conformance tests as defined in clause 5.4.6 may be carried out.

4.4.10 Receiver scanning efficiency

4.4.10.1 Definition

This test is defined in EN 302 885-1 [1], clause 9.14.1.

4.4.10.2 Limit

The scanning efficiency shall meet the limit stated in EN 302 885-1 [1], clause 9.14.3.

4.4.10.3 Conformance

Conformance tests as defined in clause 5.4.7 may be carried out.

4.5 DSC Signalling

4.5.1 DSC Call Validation

The radio shall comply with the requirements in EN 302 885-1 [1], clause 8.16.

4.5.2 Display

The radio shall comply with the display requirements given in clause 4.1 of EN 300 338-5 [3].

4.5.3 GNSS receiver

The radio shall comply with the GNSS receiver requirements given in clause 5.1.1 of EN 300 338-5 [3].

4.5.4 Individual DSC calls

The radio shall comply with the individual calls requirements given in clause 5.2.2 of EN 300 338-5 [3].

4.5.5 All ships calls

The radio shall comply with the all ships calls requirements given in clause 5.2.3 of EN 300 338-5 [3].

4.5.6 DSC call functionality

The radio shall comply with the DSC call functionality requirements given in clause 5.2.4 of EN 300 338-5 [3], except for transmission of all ships Urgency and Safety RT calls.

4.5.7 DSC message composition

The radio shall comply with the DSC message composition requirements given in clause 6.2.1 of EN 300 338-5 [3].

4.5.8 Prioritized wait

The radio shall comply with the prioritized wait requirements given in clause 6.2.2 of EN 300 338-5 [3].

4.5.9 Alarms

The radio shall comply with the alarms requirements given in clause 6.2.3 of EN 300 338-5 [3].

4.5.10 Standby

The radio shall comply with the standby requirements given in clause 6.3 of EN 300 338-5 [3].

4.5.11 GNSS fix - sending distress

The radio shall comply with the sending distress automated procedure requirements for acquiring GNSS fix as given in clause 6.4.1 of EN 300 338-5 [3].

4.5.12 Tasks - sending distress

The radio shall comply with the task requirements given in clause 6.4.2 of EN 300 338-5 [3] except that Figure 1 should be treated as an example and not as a mandatory requirement.

4.5.13 Display - sending distress

The radio shall comply with the display requirements given in clause 6.4.3 of EN 300 338-5 [3].

4.5.14 Distress button sub procedure

The radio shall comply with the dedicated distress button sub procedure requirements given in clause 6.4.4 of EN 300 338-5 [3] except for bullet (c) where the requirement "(when releasing the button the radio shall return to its previous state)" need not apply.

4.5.15 Transmission of the alert attempt

The radio shall comply with the transmission of the alert attempt requirements given in clause 6.4.5 of EN 300 338-5 [3].

4.5.16 Updating position

The radio shall comply with the updating position requirements given in clause 6.4.6 of EN 300 338-5 [3].

4.5.17 Handling received DSC messages - sending distress

The radio shall comply with the requirements for handling received DSC messages given in clause 6.4.7 of EN 300 338-5 [3].

4.5.18 Alarms - sending distress

The radio shall comply with the alarms requirements given in clause 6.4.8 of EN 300 338-5 [3].

4.5.19 Determining subsequent communications - sending distress

The radio shall comply with the requirements given in clause 6.4.9 of EN 300 338-5 [3].

4.5.20 Automated tuning - sending distress

The radio shall comply with the requirements given in clause 6.4.10 of EN 300 338-5 [3].

4.5.21 Cancelling the distress alert

The radio shall comply with the distress cancel requirements given in clause 6.4.11 of EN 300 338-5 [3].

4.5.22 Acknowledgements - sending distress

The radio shall comply with the acknowledgements requirements given in clause 6.4.12 of EN 300 338-5 [3].

4.5.23 Termination - sending distress

The radio shall comply with the termination requirements given in clause 6.4.13 of EN 300 338-5 [3].

4.5.24 Warnings - sending distress

The radio shall comply with the warnings requirements given in clause 6.4.14 of EN 300 338-5 [3].

4.5.25 Tasks - receiving distress

The radio shall comply with the task requirements given in clause 6.5.2 of EN 300 338-5 [3] except that figure 4 should be treated as an example and not as a mandatory requirement.

4.5.26 Display - receiving distress

The radio shall comply with the display requirements given in clause 6.5.3 of EN 300 338-5 [3].

4.5.27 Handling received DSC messages - receiving distress

The radio shall comply with the requirements for handling received DSC messages given in clause 6.5.4 of EN 300 338-5 [3].

4.5.28 Alarms - receiving distress

The radio shall comply with the alarms requirements given in clause 6.5.5 of EN 300 338-5 [3].

4.5.29 Determining subsequent communications - receiving distress

The radio shall comply with the requirements given in clause 6.5.6 of EN 300 338-5 [3].

4.5.30 Automated tuning - receiving distress

The radio shall comply with the requirements given in clause 6.5.7 of EN 300 338-5 [3].

4.5.31 Acknowledgements - receiving distress

The radio shall comply with the acknowledgements requirements given in clause 6.5.8 of EN 300 338-5 [3].

4.5.32 Termination - receiving distress

The radio shall comply with the termination requirements given in clause 6.5.9 of EN 300 338-5 [3].

4.5.33 Warnings - receiving distress

The radio shall comply with the warnings requirements given in clause 6.5.10 of EN 300 338-5 [3].

4.5.34 Tasks - sending non distress

The radio shall comply with the task requirements given in clause 6.6.2 of EN 300 338-5 [3] except that Figure 6 should be treated as an example and not as a mandatory requirement.

4.5.35 Display - sending non distress

The radio shall comply with the display requirements given in clause 6.6.3 of EN 300 338-5 [3].

4.5.36 Handling received DSC messages - sending non distress

The radio shall comply with the requirements for handling received DSC messages given in clause 6.6.4 of EN 300 338-5 [3].

4.5.37 Alarms - sending non distress

The radio shall comply with the alarms requirements given in clause 6.6.5 of EN 300 338-5 [3].

4.5.38 Automated tuning - sending non distress

The radio shall comply with the requirements given in clause 6.6.6 of EN 300 338-5 [3].

4.5.39 Delayed acknowledgements - sending non distress

The radio shall comply with the acknowledgements requirements given in clause 6.6.7 of EN 300 338-5 [3].

4.5.40 Termination - sending non distress

The radio shall comply with the termination requirements given in clause 6.6.8 of EN 300 338-5 [3].

4.5.41 Warnings - sending non distress

The radio shall comply with the warnings requirements given in clause 6.6.9 of EN 300 338-5 [3].

4.5.42 Tasks - receiving non distress

The radio shall comply with the task requirements given in clause 6.7.2 of EN 300 338-5 [3] except that figure 8 should be treated as an example and not as a mandatory requirement.

4.5.43 Display - receiving non distress

The radio shall comply with the display requirements given in clause 6.7.3 of EN 300 338-5 [3].

4.5.44 Handling received DSC messages - receiving non distress

The radio shall comply with the requirements for handling received DSC messages given in clause 6.7.4 of EN 300 338-5 [3].

4.5.45 Alarms - receiving non distress

The radio shall comply with the alarms requirements given in clause 6.7.5 of EN 300 338-5 [3].

4.5.46 Automated tuning - receiving non distress

The radio shall comply with the requirements given in clause 6.7.6 of EN 300 338-5 [3].

4.5.47 Acknowledgements - receiving non distress

The radio shall comply with the acknowledgements requirements given in clause 6.7.7 of EN 300 338-5 [3].

4.5.48 Termination - receiving non distress

The radio shall comply with the termination requirements given in clause 6.7.8 of EN 300 338-5 [3].

4.5.49 Warnings - receiving non distress

The radio shall comply with the warnings requirements given in clause 6.7.9 of EN 300 338-5 [3].

4.5.50 Communication automated procedure

The radio shall comply with the requirements given in clause 6.8.1 of EN 300 338-5 [3] except that the bullets (i)-(iii) describing which specific events should result in the communication automated procedure need not apply.

4.5.51 Tasks - communication

The radio shall comply with the task requirements given in clause 6.8.2 of EN 300 338-5 [3].

4.5.52 Display - communication

The radio shall comply with the display requirements given in clause 6.8.3 of EN 300 338-5 [3].

4.5.53 Handling received DSC messages - communication

The radio shall comply with the requirements for handling received DSC messages given in clause 6.8.4 of EN 300 338-5 [3].

4.5.54 Tuning of the receiver and transmitter - communication

The radio shall comply with the requirements given in clause 6.8.5 of EN 300 338-5 [3].

4.5.55 Termination - communication

The procedure shall be able to be terminated either by the user or automatic timeout.

4.5.56 Tasks of handling incoming calls while engaged

The radio shall comply with the task requirements given in clause 6.9.2 of EN 300 338-5 [3], except that clauses 6.9.2.1 and 6.9.2.2 need not apply.

4.5.57 Termination of automated procedures

The radio shall comply with the requirements given in clause 6.9.2.3 of EN 300 338-5 [3].

4.5.58 Actions after termination of an automated procedure

The radio shall comply with the requirements given in clause 6.9.2.4 of EN 300 338-5 [3] except that bullet (b) need not apply.

4.5.59 Putting automated procedures on hold

The radio may comply with the requirements given in clause 6.9.2.5 of EN 300 338-5 [3].

4.5.60 Controlling non-terminated automated procedures on hold

The radio may comply with the requirements given in clause 6.9.2.6 of EN 300 338-5 [3].

4.5.61 Sending and receiving distress alert scanning

The radio shall comply with the requirements given in clause 6.10.1 of EN 300 338-5 [3], except if the equipment has the facility for continuous monitoring of channel 70 as described in clause 5.4 of EN 302 885-1 [1].

4.5.62 Normal scan

The radio shall comply with the requirements given in clause 6.10.2 of EN 300 338-5 [3], except if the has the facility for continuous monitoring of channel 70 as described in clause 5.4 of EN 302 885-1 [1].

4.5.63 Multiple watch scan

The radio shall comply with the requirements given in clause 6.10.3 of EN 300 338-5 [3], except if the equipment has the facility for continuous monitoring of channel 70 as described in clause 5.4 of EN 302 885-1 [1].

5 Testing for compliance with technical requirements

5.1 Test conditions, power supply and ambient temperatures

The general conditions for measurement as stated in EN 302 885-1 [1], clause 6 shall apply.

5.2 Interpretation of the measurement results

The interpretation of the results recorded in a test report for the measurements described in the present document shall be as follows:

- the measured value related to the corresponding limit will be used to decide whether an equipment meets the requirements of the present document;
- the value of the measurement uncertainty for the measurement of each parameter shall be included in the test report;
- the recorded value of the measurement uncertainty shall be, for each measurement, equal to or lower than the figures in table 1.

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028-1 [2] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 1 is based on such expansion factors.

Table 1: Maximum measurement uncertainty

Parameter	Maximum uncertainty
RF frequency	$\pm 1 \times 10^{-7}$
RF power	$\pm 0,75$ dB
Maximum frequency deviation: - within 300 Hz to 6 kHz of modulation frequency - within 6 kHz to 25 kHz of modulation frequency	± 5 % ± 3 dB
Deviation limitation	± 5 %
Adjacent channel power	± 5 dB
Conducted spurious emission of transmitter	± 4 dB
Conducted emission of receiver	± 3 dB
Two-signal measurement	± 4 dB
Three-signal measurement	± 3 dB
Radiated emission of transmitter	± 6 dB
Radiated emission of receiver	± 6 dB
Transmitter transient time	± 20 %
Transmitter transient frequency	± 250 Hz
Receiver desensitization (duplex operation)	$\pm 0,5$ dB

5.3 Essential radio test suites

5.3.1 Environmental tests

5.3.1.1 Introduction

Environmental tests shall be carried out before tests are performed on the same equipment with respect to the other requirements of the present document.

5.3.1.2 Procedure

This test procedure is defined in EN 302 885-1 [1], clause 7.1.

5.3.1.3 Performance check

The "performance check" series of tests are defined in EN 302 885-1 [1], clause 7.2.

5.3.1.4 Drop test

5.3.1.4.1 Definition

This test is defined in EN 302 885-1 [1], clause 7.3.1.

5.3.1.4.2 Limit

The equipment shall comply with the requirements defined in EN 302 885-1 [1], clause 7.3.3.

5.3.1.4.3 Conformance

The test shall be performed as defined in EN 302 885-1 [1], clause 7.3.2.

5.3.1.5 Temperature tests

5.3.1.5.1 Dry heat

5.3.1.5.1.1 Definition

This test is defined in EN 302 885-1 [1], clause 7.4.2.1.

5.3.1.5.1.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 302 885-1 [1], clause 7.2.

5.3.1.5.1.3 Conformance

The test shall be performed as defined in EN 302 885-1 [1], clause 7.4.2.2.

5.3.1.5.2 Damp heat

5.3.1.5.2.1 Definition

This test is defined in EN 302 885-1 [1], clause 7.4.3.1.

5.3.1.5.2.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 302 885-1 [1], clause 7.2.

5.3.1.5.2.3 Conformance

The test shall be performed as defined in EN 302 885-1 [1], clause 7.4.3.2.

5.3.1.5.3 Low temperature

5.3.1.5.3.1 Definition

This test is defined in EN 302 885-1 [1], clause 7.4.4.1.

5.3.1.5.3.2 Limit

The equipment shall comply with the limits of the performance check defined in EN 302 885-1 [1], clause 7.2.

5.3.1.5.3.3 Conformance

The test shall be performed as defined in EN 302 885-1 [1], clause 7.4.4.2.

5.3.2 Conformance tests

5.3.2.1 Sensitivity of the modulator, including microphone

The test specified in EN 302 885-1 [1], clause 8.4.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.1.2 in order to prove compliance with the requirement.

5.3.2.2 Audio frequency response

The test specified in EN 302 885-1 [1], clause 8.5.2 shall be carried out.

The results obtained shall be compared to the limits in clause 4.4.2.2 in order to prove compliance with the requirement.

5.3.2.3 Audio frequency harmonic distortion of the emission

The test specified in EN 302 885-1 [1], clause 8.6.2 shall be carried out. The results obtained under each of the stated test conditions shall be compared to the limits in clause 4.4.3.2 in order to prove compliance with the requirement.

5.3.2.4 Residual modulation of the transmitter

The test specified in EN 302 885-1 [1], clause 8.10.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.4.2 in order to prove compliance with the requirement.

5.4 Other test suites

5.4.1 General

The requirements in clauses 4.4.5 to 4.4.10 inclusive have been set on the assumption that the test specifications in clauses 5.4.2 to 5.4.7 will be used to verify the performance of the equipment.

5.4.2 Harmonic distortion and rated audio-frequency output power

The test specified in EN 302 885-1 [1], clause 9.1.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.5.2 in order to prove compliance with the requirement.

5.4.3 Receiver audio frequency response

The test specified in EN 302 885-1 [1], clause 9.2.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.6.2 in order to prove compliance with the requirement.

5.4.4 Receiver noise and hum level

The test specified in EN 302 885-1 [1], clause 9.11.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.7.2 in order to prove compliance with the requirement.

5.4.5 Squelch operation

The test specified in EN 302 885-1 [1], clause 9.12.2 shall be carried out. The results obtained in each of the tests shall be compared to the appropriate limits in clause 4.4.8.2 in order to prove compliance with the requirement.

5.4.6 Squelch hysteresis

The test specified in EN 302 885-1 [1], clause 9.13.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.9.2 in order to prove compliance with the requirement.

5.4.7 Receiver scanning efficiency

The test specified in EN 302 885-1 [1], clause 9.14.2 shall be carried out. The results obtained shall be compared to the limits in clause 4.4.10.2 in order to prove compliance with the requirement.

Annex A (normative): HS Requirements and conformance Test specifications Table (HS-RTT)

The HS Requirements and conformance Test specifications Table (HS-RTT) in table A.1 serves a number of purposes, as follows:

- it provides a statement of all the technical requirements in words and by cross reference to (a) specific clause(s) in the present document or to (a) specific clause(s) in (a) specific referenced document(s);
- it provides a statement of all the test procedures corresponding to those technical requirements by cross reference to (a) specific clause(s) in the present document or to (a) specific clause(s) in (a) specific referenced document(s);
- it qualifies each technical requirement to be either:
 - Unconditional: meaning that technical the requirement applies in all circumstances; or
 - Conditional: meaning that the technical requirement is dependent on the manufacturer having chosen to support optional functionality defined within the schedule.
- in the case of Conditional technical requirements, it associates the technical requirement with the particular optional service or functionality;
- it qualifies each test procedure to be either:
 - Essential: meaning that it is included with the Essential Radio Test Suite and therefore the technical requirement shall be demonstrated to be met in accordance with the referenced procedures;
 - Other: meaning that the test procedure is illustrative but other means of demonstrating compliance with the technical requirement are permitted.

Table A.1: HS Requirements and conformance Test specifications Table (HS-RTT)

Harmonized Standard EN 302 885-3						
The following technical requirements and test specifications are relevant to the presumption of conformity under article 3.3(e) of the R&TTE Directive [i.1]						
Technical Requirement			Technical Requirement Conditionality		Test Specification	
No	Description	Reference: Clause No	U/C	Condition	E/O	Reference: Clause No
1	General and operational requirements	4.2.1	U		X	
2	Technical requirements	4.2.2	U		X	
3	Drop test	4.3.1	U		E	5.3.1.4
4	Dry heat	4.3.2.2	U		E	5.3.1.5.1
5	Damp heat	4.3.2.3	U		E	5.3.1.5.2
6	Low temperature	4.3.2.4	U		E	5.3.1.5.3
18	Sensitivity of the modulator, including microphone	4.4.1	U		E	5.3.2.1
19	Audio frequency response	4.4.2	U		E	5.3.2.2
20	Audio frequency harmonic distortion of the emission	4.4.3	U		E	5.3.2.3
21	Residual modulation of the transmitter	4.4.4	U		E	5.3.2.4
22	Harmonic distortion and rated audio-frequency output power	4.4.5	U		O	5.4.2
23	Receiver audio frequency response	4.4.6	U		O	5.4.3
24	Receiver noise and hum level	4.4.7	U		O	5.4.4
25	Squelch operation	4.4.8	U		O	5.4.5
26	Squelch hysteresis	4.4.9	U		O	5.4.6

Harmonized Standard EN 302 885-3						
The following technical requirements and test specifications are relevant to the presumption of conformity under article 3.3(e) of the R&TTE Directive [i.1]						
Technical Requirement			Technical Requirement Conditionality		Test Specification	
27	Receiver scanning efficiency	4.4.10	U		O	5.4.7
28	DSC call validation	4.5.1	U		X	
29	DSC Display	4.5.2	U		X	
30	GNSS Receiver	4.5.3	U		X	
31	Individual DSC calls	4.5.4	U		X	
32	All ships calls	4.5.5	U		X	
33	DSC call functionality	4.5.6	U		X	
34	DSC message composition	4.5.7	U		X	
35	Prioritized wait	4.5.8	U		X	
36	Alarms	4.5.9	U		X	
37	Standby	4.5.10	U		X	
38	GNSS fix requirements - sending distress	4.5.11	U		X	
39	Tasks - sending distress	4.5.12	U		X	
40	Display - sending distress	4.5.13	U		X	
41	Distress button sub-procedure	4.5.14	U		X	
42	Transmission of alert attempt	4.5.15	U		X	
43	Updating position	4.5.16	U		X	
44	Handling received DSC messages - sending distress	4.5.17	U		X	
45	Alarms - sending distress	4.5.18	U		X	
46	Determining subsequent communication - sending distress	4.5.19	U		X	
47	Automated tuning - sending distress	4.5.20	U		X	
48	Cancelling the distress alert	4.5.21	U		X	
49	Acknowledgement - sending distress	4.5.22	U		X	
50	Terminating - sending distress	4.5.23	U		X	
51	Warnings - sending distress	4.5.24	U		X	
52	Tasks - receiving distress	4.5.25	U		X	
53	Display - receiving distress	4.5.26	U		X	
54	Handling received DSC messages - receiving distress	4.5.27	U		X	
55	Alarms - receiving distress	4.5.28	U		X	
56	Determining subsequent communication - receiving distress	4.5.29	U		X	
57	Automated tuning - receiving distress	4.5.30	U		X	
58	Acknowledgement - receiving distress	4.5.31	U		X	
59	Terminating - receiving distress	4.5.32	U		X	
60	Warnings - receiving distress	4.5.33	U		X	
61	Tasks - sending non distress	4.5.34	U		X	
62	Display - sending non distress	4.5.35	U		X	
63	Handling received DSC messages - sending non distress	4.5.36	U		X	
64	Alarms - sending non distress	4.5.37	U		X	
65	Automated tuning - sending non distress	4.5.38	U		X	
66	Delayed acknowledgement - sending non distress	4.5.39	U		X	
67	Terminating - sending non distress	4.5.40	U		X	
68	Warnings - sending non distress	4.5.41	U		X	
69	Tasks - receiving non distress	4.5.42	U		X	
70	Display - receiving non distress	4.5.43	U		X	
71	Handling received DSC messages - receiving non distress	4.5.44	U		X	
72	Alarms - receiving non distress	4.5.45	U		X	

Harmonized Standard EN 302 885-3						
The following technical requirements and test specifications are relevant to the presumption of conformity under article 3.3(e) of the R&TTE Directive [i.1]						
Technical Requirement			Technical Requirement Conditionality		Test Specification	
73	Automated tuning - receiving non distress	4.5.46	U		X	
74	Acknowledgement - receiving non distress	4.5.47	U		X	
75	Terminating - receiving non distress	4.5.48	U		X	
76	Warnings - receiving non distress	4.5.49	U		X	
77	Communication automated procedure	4.5.50	U		X	
78	Tasks - communication	4.5.51	U		X	
79	Display - communication	4.5.52	U		X	
80	Handling received DSC messages - communication	4.5.53	U		X	
81	Tuning of the receiver and transmitter - communication	4.5.54	U		X	
82	Termination - communication	4.5.55	U		X	
83	Handling incoming calls while engaged	4.5.56	U		X	
84	Termination of automated procedures	4.5.57	U		X	
85	Actions after termination of an automated procedure	4.5.58	U		X	
86	Putting automated procedures on hold	4.5.59	C	If the equipment is designed for handling procedures on hold	X	
87	Controlling non-terminated automatic procedures	4.5.60	C		X	
88	Sending and receiving distress alert scanning	4.5.61	C	where the equipment does not have the facility for channel 70 continuous monitoring	X	
89	Normal scan	4.5.62	C		X	
90	Multiple watch scan	4.5.63	C		X	

Key to columns:**Technical Requirement:**

No A unique identifier for one row of the table which may be used to identify a technical requirement or its test specification.

Description A textual reference to the technical requirement.

Clause Number Identification of clause(s) defining the technical requirement in the present document unless another document is referenced explicitly.

Technical Requirement Conditionality:

U/C Indicates whether the technical requirement is to be *unconditionally* applicable (U) or is *conditional* upon the manufacturers claimed functionality of the equipment (C).

Condition Explains the conditions when the technical requirement shall or shall not be applicable for a technical requirement which is classified "conditional".

Test Specification:

E/O Indicates whether the test specification forms part of the Essential Radio Test Suite (E) or whether it is one of the Other Test Suite (O).

NOTE: All tests whether "E" or "O" are relevant to the technical requirements. Rows designated "E" collectively make up the Essential Radio Test Suite; those designated "O" make up the Other Test Suite; for those designated "X" there is no test specified corresponding to the technical requirement. The completion of all tests classified "E" as specified with satisfactory outcomes is a necessary condition for a presumption of conformity. Compliance with technical requirements associated with tests classified "O" or "X" is a necessary condition for presumption of conformity, although conformance with the technical requirement may be claimed by an equivalent test or by manufacturer's assertion supported by appropriate entries in the technical construction file.

Clause Number Identification of clause(s) defining the test specification in the present document unless another document is referenced explicitly. Where no test is specified (that is, where the previous field is "X") this field remains blank.

Annex B:
Void

History

Document history		
V1.1.1	September 2011	Publication
V1.2.0	May 2013	EN Approval Procedure AP 20130913: 2013-05-16 to 2013-09-13