

ETSI ES 201 488-1 V1.2.2 (2003-10)

ETSI Standard

Access and Terminals (AT); Data Over Cable Systems; Part 1: General



Reference

RES/AT-020045-1

Keywords

access, broadband, cable, data, IP, IPCable,
modem

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2003.
All rights reserved.

DECT™, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
4 Overview of the multi-part ETSI Standard	6
4.1 Part 1: General.....	6
4.2 Part 2: Radio Frequency Interface Specification	6
4.3 Part 3: Baseline Privacy Plus Interface Specification.....	6
Annex A (informative): Bibliography	7
History	8

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Access and Terminals (AT).

NOTE: An earlier version of the present document was produced by JTC Broadcast.

The present document is part 1 of a multi-part deliverable covering Data Over Cable Systems, as identified below:

- Part 1: "General";**
- Part 2: "Radio Frequency Interface Specification";
- Part 3: "Baseline Privacy Plus Interface Specification".

1 Scope

The present document is part 1, a listing of the parts comprising ES 201 488 (see bibliography).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] ETSI ES 201 488-2: "Access and Terminals (AT); Data Over Cable Systems; Part 2: Radio Frequency Interface Specification".
- [2] ETSI ES 201 488-3: "Access and Terminals (AT); Data Over Cable Systems; Part 3: Baseline Privacy Plus Interface Specification".
-

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

access node: layer two termination device that terminates the network end of a Data Over Cable System

NOTE: It is also called an INA or a CMTS.

cable modem: layer two termination device that terminates the customer end of a Data Over Cable System

IPCablecom: ETSI deliverables including an architecture and a series of specifications that enable the delivery of real time services (such as telephony) over the cable television networks using cable modems

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BPI+	Baseline Privacy Plus Interface
CM	Cable Modem
CMTS	Cable Modem Termination System
DOCS	Data Over Cable Systems
HFC	Hybrid Fibre Coax
INA	Interactive Network Adapter
IP	Internet Protocol
MAC	Media Access Control
MSO	Multiple System Operator
QoS	Quality of Service

4 Overview of the multi-part ETSI Standard

4.1 Part 1: General

The present document.

4.2 Part 2: Radio Frequency Interface Specification

ES 201 488-2 [1] defines the radio-frequency interface specifications for high-speed Data Over Cable Systems. The intended service will allow transparent bi-directional transfer of Internet Protocol (IP) traffic, between the cable system headend and customer locations, over an all-coaxial or Hybrid-Fibre/Coax (HFC) cable network. The transmission path over the cable system is realized at the headend by a Cable Modem Termination System (CMTS), and at each customer location by a Cable Modem (CM).

There are differences in the cable spectrum planning practices adopted for different networks in the world. Therefore two options for physical layer technology are included, which have equal priority and are not required to be inter-operable. One technology option is based on the downstream multi-programme television distribution that is deployed in North America using 6 MHz channelling, and supports upstream transmission in the region 5 MHz to 42 MHz. The other technology option is based on the corresponding European multi-programme television distribution and supports upstream in the region 5 MHz to 65 MHz.

4.3 Part 3: Baseline Privacy Plus Interface Specification

ES 201 488-3 [2], the Baseline Privacy Plus Interface (BPI+), describes MAC layer security services for Data Over Cable Systems (DOCS) CMTS - CM communications. BPI+ security goals are twofold:

- provide cable modem users with data privacy across the cable network; and
- provide MSOs with service protection; i.e. prevent unauthorized users from gaining access to the network's RF MAC services.

BPI+ provides a level of data privacy across the shared medium cable network equal to or better than that provided by dedicated line network access services (analogue modems or digital subscriber lines).

The protected radio frequency MAC data communications services fall into three categories:

- best-effort, high-speed, IP data services;
- QoS (e.g. constant bit rate) data services; and
- IP multicast group services.

Annex A (informative): Bibliography

- ETSI TS 101 909-1: "Access and Terminals (AT); Digital Broadband Cable Access to the Public Telecommunications Network; IP Multimedia Time Critical Services; Part 1: General".
- ETSI ES 201 488: "Data-Over-Cable Service Interface Specifications Radio Frequency Interface Specification".

History

Document history		
V1.1.1	November 2000	Publication as ES 201 488
V1.2.1	January 2003	Publication
V1.2.2	August 2003	Membership Approval Procedure MV 20031010: 2003-08-12 to 2003-10-10
V1.2.2	October 2003	Publication