

# ETSI ES 202 196-8 V1.2.1 (2005-02)

---

*ETSI Standard*

**Open Service Access (OSA);  
Application Programming Interface (API);  
Test Suite Structure and Test Purposes (TSS&TP);  
Part 8: Data session control SCF  
(Parlay 3)**

---



---

Reference

RES/TISPAN-06005-08-OSA

---

Keywords

API, OSA, TSS&TP

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.  
All rights reserved.

**DECT™**, **PLUGTESTS™** and **UMTS™** are Trade Marks of ETSI registered for the benefit of its Members.  
**TIPHON™** and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.  
**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

---

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
1 Scope .....	5
2 References .....	5
3 Definitions and abbreviations.....	5
3.1 Definitions .....	5
3.2 Abbreviations .....	6
4 Test Suite Structure (TSS).....	6
5 Test Purposes (TP) .....	6
5.1 Introduction .....	6
5.1.1 TP naming convention .....	6
5.1.2 Source of TP definition.....	7
5.1.3 Test strategy.....	7
5.2 TPs for the Data Session Control SCF .....	7
5.2.1 Data Session Control, SCF side .....	7
5.2.1.1 IpDataSessionControlManager .....	7
5.2.1.2 IpDataSession.....	15
5.2.2 Data Session Control, application side .....	27
5.2.2.1 IpAppDataSessionControlManager .....	27
5.2.2.2 IpAppDataSession.....	33
5.2.2.2.1 General tests, Active state .....	34
5.2.2.2.2 Active state, Setup Sub-state .....	39
5.2.2.2.2a Active state, Established Sub-state .....	44
5.2.2.2.3 Network Released and Finished state .....	47
5.2.2.2.4 Application Released state.....	50
History .....	52

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN).

The present document is part 8 of a multi-part deliverable covering Open Service Access (OSA); Application Programming Interface (API); Test Suite Structure and Test Purposes (TSS&TP) for Parlay 3, as identified below:

- Part 1: "Overview";
- Part 2: "Common data definitions";
- Part 3: "Framework";
- Part 4: "Call control SCF";
- Part 5: "User interactions SCF";
- Part 6: "Mobility SCF";
- Part 7: "Terminal capabilities SCF";
- Part 8: "Data session control SCF";**
- Part 9: "Generic messaging SCF";
- Part 10: "Connectivity manager SCF";
- Part 11: "Account management SCF";
- Part 12: "Charging SCF".

To evaluate conformance of a particular implementation, it is necessary to have a set of test purposes to evaluate the dynamic behaviour of the Implementation Under Test (IUT). The specification containing those test purposes is called a Test Suite Structure and Test Purposes (TSS&TP) specification.

---

# 1 Scope

The present document provides the Test Suite Structure and Test Purposes (TSS&TP) specification for the Data Session Control SCF of the Application Programming Interface (API) for Open Service Access (OSA) defined in ES 201 915-8 [1] in compliance with the relevant requirements, and in accordance with the relevant guidance given in ISO/IEC 9646-2 [4] and ETS 300 406 [5].

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

- [1] ETSI ES 201 915-8: "Open Service Access (OSA); Application Programming Interface (API); Part 8: Data Session Control SCF (Parlay 3)".
- [2] ETSI ES 202 170: "Open Service Access (OSA); Application Programming Interface (API); Implementation Conformance Statement (ICS) proforma specification (Parlay 3)".
- [3] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [4] ISO/IEC 9646-2: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract Test Suite specification".
- [5] ETSI ETS 300 406: "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the terms and definitions given in ES 201 915-8 [1], ISO/IEC 9646-1 [3], ISO/IEC 9646-2 [4] and the following apply:

**abstract test case:** Refer to ISO/IEC 9646-1 [3].

**Abstract Test Method (ATM):** Refer to ISO/IEC 9646-1 [3].

**Abstract Test Suite (ATS):** Refer to ISO/IEC 9646-1 [3].

**ICS proforma:** Refer to ISO/IEC 9646-1 [3].

**Implementation Conformance Statement (ICS):** Refer to ISO/IEC 9646-1 [3].

**Implementation eXtra Information for Testing (IXIT):** Refer to ISO/IEC 9646-1 [3].

**Implementation Under Test (IUT):** Refer to ISO/IEC 9646-1 [3].

**IXIT proforma:** Refer to ISO/IEC 9646-1 [3].

**Lower Tester (LT):** Refer to ISO/IEC 9646-1 [3].

**Test Purpose (TP):** Refer to ISO/IEC 9646-1 [3].

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

API	Application Programming Interface
ATM	Abstract Test Method
ATS	Abstract Test Suite
CM	Control Manager
DS	Data Session
DSC	Data Session Control
ICS	Implementation Conformance Statement
IUT	Implementation Under Test
IXIT	Implementation eXtra Information for Testing
LT	Lower Tester
OSA	Open Service Access
TP	Test Purpose
TSS	Test Suite Structure

---

## 4 Test Suite Structure (TSS)

Data Session Control SCF:

- IpDataSessionControlManager (CM).
- IpDataSession (DS).

---

## 5 Test Purposes (TP)

### 5.1 Introduction

For each test requirement a TP is defined.

#### 5.1.1 TP naming convention

Tps are numbered, starting at 01, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite (see table 1).

**Table 1: TP identifier naming convention scheme**

Identifier: <suite_id>_<group>_<nnn>	
<suite_id>	= SCF name: "DSC" for Data Session Control SCF
<group>	= group number: two character field representing the group reference according to TSS
<nn>	= sequential number: (01 to 99)

## 5.1.2 Source of TP definition

The TPs are based on ES 201 915-8 [1].

## 5.1.3 Test strategy

As the base standard ES 201 915-8 [1] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the ICS specification ES 202 170 [2].

The TPs are only based on conformance requirements related to the externally observable behaviour of the IUT and are limited to conceivable situations to which a real implementation is likely to be faced (see ETS 300 406 [5]).

## 5.2 TPs for the Data Session Control SCF

All ICS items referred to in this clause are as specified in ES 202 170[2] unless indicated otherwise by another numbered reference.

All parameters specified in method calls are valid unless specified.

The procedures to trigger the SCF to call methods in the application are dependant on the underlying network architecture and are out of the scope of this test specification. Those method calls are preceded by the words "Triggered action".

### 5.2.1 Data Session Control, SCF side

#### 5.2.1.1 IpDataSessionControlManager

##### Test DSC\_CM\_01

Summary: **IpDataSessionControlManager**, mandatory methods, successful

Reference: ES 201 915-8 [1], clause 8.4

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
Check: valid value of TpAssignmentID is returned
2. Triggered Action: cause IUT to call **reportNotification()** method on the tester's (application's) IpAppDataSessionControlManager interface.  
Parameters: dataSessionReference, eventInfo, assignmentID
3. Method call **destroyNotification()**  
Parameters: assignmentID  
Check: no exception is returned



### Test DSC\_CM\_02

Summary: **IpDataSessionControlManager**, all methods, successful

Reference: ES 201 915-8 [1], clause 8.4


Precondition: **changeNotification()** and **getNotifications()** implemented

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
Check: valid value of TpAssignmentID is returned
2. Method call **getNotifications()**  
Parameters: none  
Check: value of TpDataSessionEventCriteriaResultSet containing event criteria as specified in 1. is returned
3. Method call **changeNotification()**  
Parameters: assignmentID, eventCriteria (different to 1.)  
Check: no exception is returned
4. Method call **getNotifications()**  
Parameters: none  
Check: value of TpDataSessionEventCriteriaResultSet containing event criteria as specified in 3. is returned
5. Method call **destroyNotification()**  
Parameters: assignmentID  
Check: no exception is returned
6. Method call **destroyNotification()**  
Parameters: assignmentID as received in 1. and destroyed in 5.  
Check: P\_INVALID\_ASSIGNMENT\_ID is returned





**Test DSC\_CM\_03**

Summary: **IpDataSessionControlManager**, createNotification(), P\_INVALID\_CRITERIA exception

Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3


Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**

Parameters: appDataSessionControlManager (non-NULL), invalid eventCriteria

Check: P\_INVALID\_CRITERIA is returned



**Test DSC\_CM\_04**


Summary: **IpDataSessionControlManager**, destroyNotification(), P\_INVALID\_ASSIGNMENT\_ID exception

Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Check: valid value of TpAssignmentID is returned
2. Method call **destroyNotification()**  
 Parameters: invalid assignmentID  
 Check: P\_INVALID\_ASSIGNMENT\_ID is returned



**Test DSC\_CM\_05**

Summary: **IpDataSessionControlManager**, changeNotification(), P\_INVALID\_ASSIGNMENT\_ID exception


Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Precondition: **changeNotification()** implemented

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Check: valid value of TpAssignmentID is returned
2. Method call **changeNotification()**  
 Parameters: invalid assignmentID, eventCriteria  
 Check: P\_INVALID\_ASSIGNMENT\_ID is returned



**Test DSC\_CM\_06**

Summary: **IpDataSessionControlManager**, changeNotification(), P\_INVALID\_CRITERIA exception


Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Precondition: **changeNotification()** implemented

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Check: valid value of TpAssignmentID is returned
2. Method call **changeNotification()**  
 Parameters: assignmentID, invalid eventCriteria  
 Check: P\_INVALID\_CRITERIA is returned



**Test DSC\_CM\_07**

Summary: all methods, successful, two createNotification() method calls


Reference: ES 201 915-8 [1], clause 8.4

Precondition: **getNotifications()** implemented

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
Check: valid value of TpAssignmentID is returned
2. Method call **getNotifications()**  
Parameters: none  
Check: value of TpDataSessionEventCriteriaResultSet containing event criteria as specified in 1. is returned
3. Method call **createNotification()**  
Parameters: appDataSessionControlManager (non-NULL) different from 1., eventCriteria same as in 1.  
Check: same value of TpAssignmentID as in 1. is returned
4. Triggered Action: cause IUT to call **reportNotification()** method on the tester's (application's) IpAppDataSessionControlManager interface  
Parameters: dataSessionReferencer, eventInfo, assignmentID  
Check: The interface given in 3. receives the event
5. Triggered action: Kill the appDataSessionControlManager item referenced in 3.
6. Triggered Action: cause IUT to call **reportNotification()** method on the tester's (application's) IpAppDataSessionControlManager interface.  
Parameters: dataSessionReference, eventInfo, assignmentID  
Check: The interface given in 1. receives the event.



## 5.2.1.2 IpDataSession

### Test DSC\_DS\_01

Summary: **IpDataSession**, release after `connectReq()`, successful with interrupt after `reportNotification()`


Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the `IpDataSessionControlManager` interface through selecting that service and signing the required service agreement.

Test Sequence:

- Method call **createNotification()**  
 Parameters: `appDataSessionControlManager` (non-NULL), `eventCriteria`  
 Parameter values: `eventCriteria.DataSessionEventName = P_EVENT_DSCS_SETUP`  
`eventCriteria.MonitorMode = P_DATA_SESSION_MONITOR_MODE_INTERRUPT`  
 Check: valid value of `TpAssignmentID` is returned
- Triggered action: cause IUT to call **reportNotification()** method on the tester's (application's) **IpAppDataSessionControlManager** interface, i.e. start to set-up data session  
 Parameters: `dataSessionReference`, `eventInfo`, `assignmentID`

3. Method call **connectReq()**  
 Parameters: dataSessionID, responseRequested, targetAddress  
 Parameter values: responseRequested.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_CONNECTED  
 Check: valid value of TpAssignmentID is returned
4. Triggered action: cause IUT to call **connectRes()** method on the tester's (application's) **IpAppDataSession** interface, i.e. accept the data session on the destination side  
 Parameters: dataSessionID, eventReport, assignmentID
5. Method call **release()**  
 Parameters: dataSessionID, cause  
 Check: no exception is returned





**Test DSC\_DS\_02**


Summary: **IpDataSession**, deassignDataSession() after connectReq(), successful.

Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Parameter values: eventCriteria.DataSessionEventName = P\_EVENT\_DSCS\_SETUP  
 eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 Check: valid value of TpAssignmentID is returned
2. Triggered action: cause IUT to call **reportNotification()** method on the tester's (application's) **IpAppDataSessionControlManager** interface, i.e. start to set-up data session  
 Parameters: dataSessionReference, eventInfo, assignmentID
3. Method call **connectReq()**  
 Parameters: dataSessionID, responseRequested, targetAddress  
 Parameter values: responseRequested.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_NOTIFY  
 responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_CONNECTED  
 Check: valid value of TpAssignmentID is returned
4. Triggered action: cause IUT to call **connectRes()** method on the tester's (application's) **IpAppDataSession** interface, i.e. accept the data session on the destination side  
 Parameters: dataSessionID, eventReport, assignmentID
5. Method call **deassignDataSession()**  
 Parameters: dataSessionID  
 Check: no exception is returned



**Test DSC\_DS\_03**


Summary: **IpDataSession**, connectReq() with two trigger events, successful with interrupt after reportNotification()

Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Parameter values: eventCriteria.DataSessionEventName = P\_EVENT\_DSCS\_SETUP  
 eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 Check: valid value of TpAssignmentID is returned
2. Triggered action: cause IUT to call **reportNotification()** method on the tester's (application's) **IpAppDataSessionControlManager** interface, i.e. start to set-up data session  
 Parameters: dataSessionReference, eventInfo, assignmentID
3. Method call **connectReq()**  
 Parameters: dataSessionID, responseRequested, targetAddress  
 Parameter values:  
     1st set  
         responseRequested.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_NOTIFY  
         responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_CONNECTED  
     2nd set  
         responseRequested.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_NOTIFY  
         responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_DISCONNECT  
 Check: valid value of TpAssignmentID is returned
4. Triggered action: cause IUT to call **connectRes()** method on the tester's (application's) **IpAppDataSession** interface, i.e. accept the data session on the destination side  
 Parameters: dataSessionID, eventReport, assignmentID
5. Triggered action: cause IUT to call **connectRes()** method on the tester's (application's) **IpAppDataSession** interface, i.e. release the data session  
 Parameters: dataSessionID, eventReport, assignmentID
6. Method call **deassignDataSession()**  
 Parameters: dataSessionID  
 Check: no exception is returned



**Test DSC\_DS\_04**

Summary: **IpDataSession**, superviseDataSessionReq()


Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Precondition: **superviseDataSessionReq()** implemented

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Parameter values: eventCriteria.DataSessionEventName = P\_EVENT\_DSCS\_SETUP  
 eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 Check: valid value of TpAssignmentID is returned
2. Triggered action: cause IUT to call **reportNotification()** method on the tester's (application's) **IpAppDataSessionControlManager** interface, i.e. start to set-up data session  
 Parameters: dataSessionReference, eventInfo, assignmentID
3. Method call **superviseDataSessionReq()**  
 Parameters: dataSessionID, treatment, bytes  
 Check: no exception is returned
4. Method call **connectReq()**  
 Parameters: dataSessionID, responseRequested, targetAddress  
 Parameter values: responseRequested.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_CONNECTED  
 Check: valid value of TpAssignmentID is returned
5. Triggered action: cause IUT to call **connectRes()** method on the tester's (application's) **IpAppDataSession** interface, i.e. accept the data session on the destination side  
 Parameters: dataSessionID, eventReport, assignmentID
6. Method call **continueProcessing()**  
 Parameters: dataSessionID  
 Check: no exception is returned
7. Triggered action: cause IUT to call **superviseDataSessionRes()** method on the tester's (application's) **IpAppDataSession** interface, i.e. use up the granted number of bytes for that data session  
 Parameters: dataSessionID, report, usedVolume, qualityOfService
8. Method call **release()**  
 Parameters: dataSessionID, cause  
 Check: no exception is returned



**Test DSC\_DS\_05**

Summary: **IpDataSession**, setDataSessionChargePlan()


Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Precondition: **setDataSessionChargePlan()** implemented

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Parameter values: eventCriteria.DataSessionEventName = P\_EVENT\_DSCS\_SETUP  
 eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 Check: valid value of TpAssignmentID is returned
2. Triggered action: cause IUT to call **reportNotification()** method on the tester's (application's) **IpAppDataSessionControlManager** interface, i.e. start to set-up data session  
 Parameters: dataSessionReference, eventInfo, assignmentID
3. Method call **setDataSessionChargePlan()**  
 Parameters: dataSessionID, dataSessionChargePlan  
 Check: no exception is returned
4. Method call **connectReq()**  
 Parameters: dataSessionID, responseRequested, targetAddress  
 Parameter values: responseRequested.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_CONNECTED  
 Check: valid value of TpAssignmentID is returned
5. Triggered action: cause IUT to call **connectRes()** method on the tester's (application's) **IpAppDataSession** interface, i.e. accept the data session on the destination side  
 Parameters: dataSessionID, eventReport, assignmentID
6. Method call **release()**  
 Parameters: dataSessionID, cause  
 Check: no exception is returned





**Test DSC\_DS\_06**

Summary: **IpDataSession**, setAdviceOfCharge()


Reference: ES 201 915-8 [1], clauses 7.4.1 and 8.3

Precondition: **setAdviceOfCharge()** implemented

Preamble: Registration of the IUT (Data Session Control SCF) and the tester (application) to the framework. The tester must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Test Sequence:

1. Method call **createNotification()**  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Parameter values: eventCriteria.DataSessionEventName = P\_EVENT\_DSCS\_SETUP  
 eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 Check: valid value of TpAssignmentID is returned
2. Triggered action: cause IUT to call **reportNotification()** method on the tester's (application's) **IpAppDataSessionControlManager** interface, i.e. start to set-up data session  
 Parameters: dataSessionReference, eventInfo, assignmentID
3. Method call **setAdviceOfCharge()**  
 Parameters: dataSessionID, aoCInfo, tariffswitch  
 Check: no exception is returned
4. Method call **connectReq()**  
 Parameters: dataSessionID, responseRequested, targetAddress  
 Parameter values: responseRequested.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_CONNECTED  
 Check: valid value of TpAssignmentID is returned
5. Triggered action: cause IUT to call **connectRes()** method on the tester's (application's) **IpAppDataSession** interface, i.e. accept the data session on the destination side  
 Parameters: dataSessionID, eventReport, assignmentID
6. Method call **release()**  
 Parameters: dataSessionID, cause  
 Check: no exception is returned



## 5.2.2 Data Session Control, application side

In performing the tests for the application, it may be necessary to permit the application to perform any valid set of method exchanges with the tester in between the triggered actions or method calls indicated in the tests below. The tester shall respond to the application's method calls in conformance to the API specification and as required by the application. The requirements of the application should be made known to the tester's operator in advance.

### 5.2.2.1 IpAppDataSessionControlManager

#### Test DSC\_APP\_CM\_01

Summary: **IpAppDataSessionControlManager**, mandatory methods, successful


Reference: ES 201 915-8 [1], clause 8.2, 8.4

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria
2. Method call **reportNotification()**  
Parameters: dataSessionReference, value depending on monitor mode of notification request, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned, depending on monitor mode of notification request



**Test DSC\_APP\_CM\_02**

Summary: **IpAppDataSessionControlManager**, interrupt and continue data session notification, successful

Reference: ES 201 915-8 [1], clause 8.2

Precondition: **dataSessionNotificationInterrupted()** and **dataSessionNotificationContinued()** implemented

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:


1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria

Delay between createNotification and Interrupted

2. Method call **dataSessionNotificationInterrupted()**  
Parameters: none  
Check: no exception is returned

NOTE: Delay between Interrupted and Continued.

3. Method call **dataSessionNotificationContinued()**  
Parameters: none  
Check: no exception is returned
4. Method call **reportNotification()**  
Parameters: dataSessionReference, value depending on monitor mode of notification request, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned, depending on monitor mode of notification request



**Test DSC\_APP\_CM\_03**

Summary: **IpAppDataSessionControlManager**, abort data session, successful

Reference: ES 201 915-8 [1], clause 8.2


Precondition: **dataSessionAborted()** implemented

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned
3. Method call **dataSessionAborted()**  
Parameters: dataSessionID with same value as supplied in reportNotification.  
Check: no exception is returned



**Test DSC\_APP\_CM\_04**

Summary: **IpAppDataSessionControlManager**, change event criteria, successful

Reference: ES 201 915-8 [1], clause 8.4


Precondition: IUT capable of invoking **changeNotification()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria
2. Triggered Action: cause IUT to call **changeNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: assignmentID, eventCriteria



**Test DSC\_APP\_CM\_05**

Summary: **IpAppDataSessionControlManager**, disable data session notifications, successful

Reference: ES 201 915-8 [1], clause 8.4


Precondition: IUT capable of invoking **destroyNotification()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria
2. Triggered Action: cause IUT to call **destroyNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: assignmentID





**Test DSC\_APP\_CM\_06**

Summary: **IpAppDataSessionControlManager**, query event criteria set, successful

Reference: ES 201 915-8 [1], clause 8.4


Precondition: IUT capable of invoking **getNotifications()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria
2. Triggered Action: cause IUT to call **getNotifications()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: none

**5.2.2.2 IpAppDataSession**

Applications need not be capable of performing each of the sequences below, even if they support the methods indicated below.

Reference: ES 201 915-8 [1], clauses 9.1

Precondition: **IpAppDataSession** interface implemented

### 5.2.2.2.1 General tests, Active state

NOTE: Tests DSC\_APP\_DS\_01 to 05 do not specify the values of DataSessionEventName field in the eventCriteria parameter of the createNotification() method expected from the IUT. This has been done intentionally to keep these basic tests simple. Note that the tester has to answer with parameter values that make sense in relation to the parameter values received from the IUT.

#### Test DSC\_APP\_DS\_01

Summary: **IpAppDataSession**, supervise data session

Reference: ES 201 915-8 [1], clauses 8.1 and 8.3


Precondition: IUT capable of invoking **superviseDataSessionReq()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned
3. Triggered Action: cause IUT to call **superviseDataSessionReq()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, treatment, bytes



**Test DSC\_APP\_DS\_02**

Summary: **IpAppDataSession**, indication of a data session fault

Reference: ES 201 915-8 [1], clauses 8.1 and 8.3


Precondition: **dataSessionFaultDetected()** implemented

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned
3. Method call **dataSessionFaultDetected()**  
Parameters: dataSessionID, fault  
Check: no exception is returned



**Test DSC\_APP\_DS\_03**

Summary: **IpAppDataSession**, determine charging information

Reference: ES 201 915-8 [1], clauses 8.1 and 8.3


Precondition: IUT capable of invoking **setAdviceOfCharge()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned
3. Triggered Action: cause IUT to call **setAdviceOfCharge()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, aoCInfo, tariffSwitch



**Test DSC\_APP\_DS\_04**

Summary: **IpAppDataSession**, include charging information

Reference: ES 201 915-8 [1], clauses 8.1 and 8.3


Precondition: IUT capable of invoking **setDataSessionChargePlan()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned
3. Triggered Action: cause IUT to call **setDataSessionChargePlan()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, dataSessionChargePlan



**Test DSC\_APP\_DS\_05**

Summary: **IpAppDataSession**, release data session

Reference: ES 201 915-8 [1], clauses 8.1 and 8.3


Precondition: IUT capable of invoking **release()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned
3. Triggered Action: cause IUT to call **release()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, cause



## 5.2.2.2.2 Active state, Setup Sub-state

NOTE: It will be necessary to create some kind of 'PIXIT' items to check, if the sending of the distinct parameter values in the following tests is supported by the IUT.

**Preamble DSC\_APP\_DS\_Active\_Setup**


Reference: ES 201 915-8 [1], clauses 9.1

Pre-preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Preamble Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
Parameter values: eventCriteria.DataSessionEventName = P\_EVENT\_DSCS\_SETUP or P\_EVENT\_DSCS\_QOS\_CHANGE  
eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Parameter values: eventInfo.DataSessionEventName = P\_EVENT\_DSCS\_SETUP or P\_EVENT\_DSCS\_QOS\_CHANGE depending on value received from the IUT  
eventInfo.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
Check: valid value of IpAppDataSessionRef is returned



**Test DSC\_APP\_DS\_06**

Summary: **IpAppDataSession**, connect interrupted data session, wait for connected, successful


Reference: ES 201 915-8 [1], clauses 8.1 and 8.3

Precondition: IUT capable of invoking **connectReq()**

Preamble: **DSC\_APP\_DS\_Active\_Setup**

Test Sequence:

1. Triggered Action: cause IUT to call **connectReq()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, responseRequested, targetAddress  
Parameter values: responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_CONNECTED
2. Method call **connectRes()**  
Parameters: dataSessionID, eventReport, assignmentID  
Parameter values: eventReport.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_CONNECTED  
Check: no exception is returned





**Test DSC\_APP\_DS\_07**

Summary: **IpAppDataSession**, connect interrupted data session, wait for connected, unsuccessful


Reference: ES 201 915-8 [1], clauses 8.1 and 8.3

Precondition: IUT capable of invoking **connectReq()**

Preamble: **DSC\_APP\_DS\_Active\_Setup**

Test Sequence:

1. Triggered Action: cause IUT to call **connectReq()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, responseRequested, targetAddress  
Parameter values:
2. Method call **connectErr()**  
Parameters: dataSessionID, errorIndication, assignmentID  
Check: no exception is returned



**Test DSC\_APP\_DS\_08**

Summary: **IpAppDataSession**, connect interrupted data session, wait for disconnected, successful


Reference: ES 201 915-8 [1], clauses 8.1 and 8.3

Precondition: IUT capable of invoking **connectReq()**

Preamble: **DSC\_APP\_DS\_Active\_Setup**

Test Sequence:

1. Triggered Action: cause IUT to call **connectReq()** method on the tester's (SCF's) IpDataSession interface.  
 Parameters: dataSessionID, responseRequested, targetAddress  
 Parameter values: responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_DISCONNECT
2. Method call **connectRes()**  
 Parameters: dataSessionID, eventReport, assignmentID  
 Parameter values: eventReport.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_DISCONNECT  
 Check: no exception is returned



**Test DSC\_APP\_DS\_09**

Summary: **IpAppDataSession**, continue interrupted data session

Reference: ES 201 915-8 [1], clauses 8.1 and 8.3

Precondition: IUT capable of invoking **continueProcessing()**

Preamble: **DSC\_APP\_DS\_Active\_Setup**

Test Sequence:

1. Triggered Action: cause IUT to call **continueProcessing()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID



## 5.2.2.2.2a Active state, Established Sub-state

**Preamble DSC\_APP\_DS\_Active\_Established**


Reference: ES 201 915-8 [1], clauses 9.1

Pre-preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Preamble Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
 Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
 Parameter values: eventCriteria.DataSessionEventName = P\_EVENT\_DSCS\_ESTABLISHED  
 eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
 Parameters: dataSessionReference, eventInfo, assignmentID  
 Parameter values: eventInfo.DataSessionEventName = P\_EVENT\_DSCS\_ESTABLISHED  
 eventInfo.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
 Check: valid value of IpAppDataSessionRef is returned



**Test DSC\_APP\_DS\_10**

Summary: **IpAppDataSession**, supervise data session, successful


Reference: ES 201 915-8 [1], clauses 8.1 and 8.3

Precondition: IUT capable of invoking **superviseDataSessionReq()**

Preamble: **DSC\_APP\_DS\_Active\_Established**

Test Sequence:

1. Triggered Action: cause IUT to call **superviseDataSessionReq()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, treatment, bytes
2. Method call **superviseDataSessionRes()**  
Parameters: dataSessionID, report, usedVolume, qualityOfService  
Check: no exception returned



**Test DSC\_APP\_DS\_11**

Summary: **IpAppDataSession**, supervise data session, unsuccessful


Reference: ES 201 915-8 [1], clauses 8.1 and 8.3

Precondition: IUT capable of invoking **superviseDataSessionReq()**

Preamble: **DSC\_APP\_DS\_Active\_Established**

Test Sequence:

1. Triggered Action: cause IUT to call **superviseDataSessionReq()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, treatment, bytes
2. Method call **superviseDataSessionErr()**  
Parameters: dataSessionID, erroIndication  
Check: no exception returned



### 5.2.2.2.3 Network Released and Finished state

NOTE: The following test is testing both the Network Released and the Finished state, as there is a direct state transition from the first to the latter state, when no supervision request has been sent by the application or when a sent supervision request is answered by the SCF.

#### Test DSC\_APP\_DS\_12

Summary: **IpAppDataSession**, de-assign data session that has been released by the network for reasons of fault

Reference: ES 201 915-8 [1], clauses 8.1, 8.3 and 9.1


Precondition: **dataSessionFaultDetected()** implemented, IUT capable of invoking **deassignDataSession()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Test Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Check: valid value of IpAppDataSessionRef is returned
3. Method call **dataSessionFaultDetected()**  
Parameters: dataSessionID, fault  
Check: no exception is returned
4. Triggered Action: cause IUT to call **deassignDataSession()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID



**Test DSC\_APP\_DS\_13**

Summary: **IpAppDataSession**, de-assign network released data session **after** receipt of supervision result

Reference: ES 201 915-8 [1], clauses 8.1, 8.3, and 9.1

Precondition: IUT capable of invoking **connectReq()**, **superviseDataSessionReq()** and **deassignDataSession()**


Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the IpDataSessionControlManager interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its IpAppDataSessionControlManager interface reference in the createNotification() method, the application is permitted to provide the IpAppDataSessionControlManager interface reference in a setCallback() method which it calls prior to invoking createNotification().

Preamble Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) IpDataSessionControlManager interface.  
Parameters: appDataSessionControlManager (non-NULL), eventCriteria  
Parameter values: eventCriteria.DataSessionEventName = P\_EVENT\_DSCS\_SETUP  
eventCriteria.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT
2. Method call **reportNotification()**  
Parameters: dataSessionReference, eventInfo, assignmentID  
Parameter values: eventInfo.DataSessionEventName = P\_EVENT\_DSCS\_SETUP  
eventInfo.MonitorMode = P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT  
Check: valid value of IpAppDataSessionRef is returned
3. Triggered Action: cause IUT to call **superviseDataSessionReq()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, treatment, bytes
4. Triggered Action: cause IUT to call **connectReq()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID, responseRequested, targetAddress  
Parameter values: responseRequested.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_DISCONNECT
5. Method call **connectRes()**  
Parameters: dataSessionID, eventReport, assignmentID  
Parameter values: eventReport.DataSessionReportType = P\_DATA\_SESSION\_REPORT\_DISCONNECT  
Check: no exception is returned
6. Method call **superviseDataSessionRes()**  
Parameters: dataSessionID, report, usedVolume, qualityOfService  
Check: no exception returned
7. Triggered Action: cause IUT to call **deassignDataSession()** method on the tester's (SCF's) IpDataSession interface.  
Parameters: dataSessionID





#### 5.2.2.2.4 Application Released state

##### Test DSC\_APP\_DS\_14

Summary: **IpAppDataSession**, accept receipt of supervision result **after** release of data session by application

Reference: ES 201 915-8 [1], clauses 8.1, 8.3, and 9.1


Precondition: IUT capable of invoking **connectReq()**, **superviseDataSessionReq()** and **release()**

Preamble: Registration of the IUT (application) and the tester (Data Session Control SCF) to the framework. The IUT must have obtained a reference to an instance of the **IpDataSessionControlManager** interface through selecting that service and signing the required service agreement.

Instead of providing a valid value of its **IpAppDataSessionControlManager** interface reference in the **createNotification()** method, the application is permitted to provide the **IpAppDataSessionControlManager** interface reference in a **setCallback()** method which it calls prior to invoking **createNotification()**.

Preamble Sequence:

1. Triggered Action: cause IUT to call **createNotification()** method on the tester's (SCF's) **IpDataSessionControlManager** interface.  
Parameters: **appDataSessionControlManager** (non-NULL), **eventCriteria**  
Parameter values: **eventCriteria.DataSessionEventName** = **P\_EVENT\_DSCS\_SETUP**  
**eventCriteria.MonitorMode** = **P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT**
2. Method call **reportNotification()**  
Parameters: **dataSessionReference**, **eventInfo**, **assignmentID**  
Parameter values: **eventInfo.DataSessionEventName** = **P\_EVENT\_DSCS\_SETUP**  
**eventInfo.MonitorMode** = **P\_DATA\_SESSION\_MONITOR\_MODE\_INTERRUPT**  
Check: valid value of **IpAppDataSessionRef** is returned
3. Triggered Action: cause IUT to call **superviseDataSessionReq()** method on the tester's (SCF's) **IpDataSession** interface.  
Parameters: **dataSessionID**, **treatment**, **bytes**
4. Triggered Action: cause IUT to call **connectReq()** method on the tester's (SCF's) **IpDataSession** interface.  
Parameters: **dataSessionID**, **responseRequested**, **targetAddress**  
Parameter values: **responseRequested.DataSessionReportType** = **P\_DATA\_SESSION\_REPORT\_CONNECT**
5. Method call **connectRes()**  
Parameters: **dataSessionID**, **eventReport**, **assignmentID**  
Parameter values: **eventReport.DataSessionReportType** = **P\_DATA\_SESSION\_REPORT\_CONNECT**  
Check: no exception is returned
6. Triggered Action: cause IUT to call **release()** method on the tester's (SCF's) **IpDataSession** interface.  
Parameters: **dataSessionID**, **cause**
7. Method call **superviseDataSessionRes()**  
Parameters: **dataSessionID**, **report**, **usedVolume**, **qualityOfService**  
Check: no exception returned



---

## History

<b>Document history</b>		
V1.1.1	August 2003	Publication
V1.2.1	December 2004	Membership Approval Procedure    MV 20050211: 2004-12-14 to 2005-02-11
V1.2.1	February 2005	Publication