



GSM **T**ECHNICAL **S**PECIFICATION

GSM 02.97

July 1996

Version 5.0.0

Source: ETSI TC-SMG

Reference: TS/SMG-010297Q

ICS: 33.060.50

Key words: Digital cellular telecommunications system, Global System for Mobile communications (GSM)



Digital cellular telecommunications system (Phase 2+); Multiple Subscriber Profile (MSP) Service description, Stage 1 (GSM 02.97)

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

Contents

Foreword.....	5
1 Scope	7
2 Normative references	7
3 Definitions and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	8
4 Description	8
4.1 Applicability to telecommunication services.....	8
4.2 Mobile Originated Activities.....	8
4.3 Mobile Terminated Activities	8
5 Functional requirements.....	9
5.1 Handling of the MSP Service	9
5.1.1 Provision.....	9
5.1.2 Withdrawal.....	9
5.1.3 Activation	9
5.1.4 Deactivation.....	9
5.1.5 Invocation	9
5.2 Handling of the Profile.....	9
5.2.1 Provision.....	9
5.2.2 Withdrawal.....	9
5.2.3 Registration	9
5.2.4 Erasure	10
5.2.5 Interrogation	10
5.2.6 Handling of the MSP Password.....	10
5.3 Normal operation with successful outcome	10
5.3.1 Mobile Originating Activities	10
5.3.2 Mobile Terminating Traffic.....	10
5.4 Exceptional procedures or unsuccessful outcome	10
5.4.1 Roaming into networks not supporting MSP	10
6 Interaction between Profiles	10
7 Interaction with supplementary services	11
7.1 Line Identification Services	11
7.2 Call Hold (CH).....	11
7.3 Call Waiting (CW)	11
7.4 Call Forwarding.....	11
7.4.1 Call forwarding unconditional (CFU).....	11
7.4.2 Call Forwarding on busy (CFB)	11
7.4.3 Call forwarding on No Reply (CFNRy).....	11
7.4.4 Call forwarding on not reachable (CFNR)	11
7.5 Multi Party Service (MPTY).....	11
7.6 Closed User Group (CUG).....	12
7.7 Advice of Charge (AoC)	12
7.8 Call Barring	12
7.9 Explicit Call Transfer (ECT)	12
7.10 CCBS	12
7.11 Operator Determined Barring.....	12
7.12 Roaming restrictions	12
8 Interaction with other services	12

8.1	The Multi-Numbering Scheme	12
8.2	The Short Message Service	12
9	Cross-Phase Compatibility	12
	History	13

Foreword

This Global System for Mobile communications Technical Specification (GTS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI).

This GTS gives an overall view of how this service shall operate both in the PLMN and within the Mobile Station (MS) within the digital cellular telecommunications system (Phase 2/Phase 2+).

GTS are produced by TC-SMG to enable the GSM Phase 2+ specifications to become publicly available, prior to submission for the formal ETSI standards approval procedure to become European Telecommunications Standards (ETS). This ensures the earliest possible access to GSM Phase 2+ specifications for all Manufacturers, Network operators and implementors of the Global System for Mobile communications.

The contents of this GTS are subject to continuing work within TC-SMG and may change following formal TC-SMG approval. Should TC-SMG modify the contents of this GTS it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version 5.x.y

where:

- y the third digit is incremented when editorial only changes have been incorporated in the specification;
- x the second digit is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.

Reference is made within this GTS to GSM-TSs (note).

NOTE: TC-SMG has produced documents which give the technical specifications for the implementation of the digital cellular telecommunications system. Historically, these documents have been identified as GSM Technical Specifications (GSM-TSs). These TSs may have subsequently become I-ETSs (Phase 1), or ETSs/ETSI Technical Reports (ETRs) (Phase 2). TC-SMG has also produced ETSI GSM TSs which give the technical specifications for the implementation of Phase 2+ enhancements of the digital cellular telecommunications system. These version 5.x.x GSM Technical Specifications may be referred to as GTSS.

Blank page

1 Scope

This European Telecommunication Standard (ETS) gives an overall view of how this service shall operate both in the PLMN and within the Mobile Station (MS). This ETS defines functionality and is not intended to constrain implementation.

2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] GSM 01.04 (ETR 100): "European digital cellular telecommunication system (Phase 2); Abbreviations and acronyms".
- [2] GSM 02.01 (ETS 300 500): "European digital cellular telecommunication system (Phase 2); Principles of telecommunication services supported by a GSM Public Land Mobile Network (PLMN)".
- [3] GSM 02.30 (ETS 300 511): "European digital cellular telecommunication system (Phase 2); Man-machine Interface (MMI) of the mobile station (MS)".
- [4] GSM 03.40 (ETS 300 536): "European digital cellular telecommunication system (Phase 2); Technical realization of the Short Message Service (SMS) Point to Point (PP)"

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this ETS the following definitions apply:

default profile: Profile to be used when roaming to non-supporting network

MSP password: The password is specific to the MSP service and provides the means to allow authorized change of profiles only. There shall be one password for use by all profiles

Profile Identification (PROFILE ID): The profile IDs allow unambiguous identification of each profile. This will allow the subscriber to select the preferred profile for outgoing calls and for subscriber actions. For terminating calls the profile ID shall be part of the notification of the profile.

profile: A profile consists of a set of telecommunications services for the subscriber. In the case of the single numbering scheme there is a unique MSISDN associated with each profile. In the multi-numbering scheme there is the ability to have a unique MSISDN associated with each basic service in each profile.

[profile data: A profile is a set of subscriber data (identified by an unique MSISDN in the case of single-numbering scheme , or several MSISDNs in the case of multi-numbering scheme) which may include the following information:

- Operator determined barring data
- Roaming restriction data
- Subscription restriction data
- Basic service data
- Supplementary service data]

registered profile: The registered profile is that registered by/for the subscriber

selected profile: This is the registered profile unless an alternative profile is selected by the subscriber on a per call basis and used for outgoing calls and supplementary service activation

Service Provider (SP): The organization through which the subscriber obtains GSM telecommunication services. This may be the network operator or possibly a separate body.

subscriber: The user who is provisioned with the MSP service

3.2 Abbreviations

For the purposes of this ETS the following abbreviations apply. In addition, abbreviations used in this ETS are listed in GSM 01.04 (ETR 100) [1].

MSP Multiple Subscriber Profile

4 Description

Multiple Subscriber Profile is an optional service to enable mobile subscribers to have several profiles associated with a single SIM and a single IMSI, with each profile being a subscription option. Each profile may be used for mobile originated and mobile terminated calls.

Up to four different profiles can be provisioned against a subscriber using the MSP feature. This will allow the subscriber to separate her telecommunication service needs into different identities (e.g. business and home).

NOTE: SMG1 believe that 4 profiles is the minimum but would prefer more. Guidance from SMG3 is required once the extent of data to be stored and/or transferred can be identified.

The charges accrued for services shall be associated with the appropriate profile, allowing separate charging for each profile.

A supporting visited network shall indicate [on the billing record] for charging purposes the profile used.

4.1 Applicability to telecommunication services

The applicability of this supplementary service is defined in GSM 02.04 (ETS 300 503).

4.2 Mobile Originated Activities

The subscriber shall be able to select which profile shall be used for mobile originated activities. This shall be the registered profile unless an alternative is selected by the subscriber on a per call basis.

4.3 Mobile Terminated Activities

The profile used for mobile terminated activities is that associated with the called MSISDN. If the MS is busy in a call, further incoming call attempts shall be rejected or busy, even if they were on a different profile. This shall not prevent the normal operation of Call Waiting or Call Forwarding if appropriate.

Each profile may employ the single-numbering scheme or the multi-numbering scheme (as defined in GSM 02.01 [2]), as supported by the subscriber's home network, for specifying different bearer services when calling from the PSTN.

5 Functional requirements

5.1 Handling of the MSP Service

This section describes the normal procedures for the handling of the MSP service.

5.1.1 Provision

The MSP service shall be provided after prior arrangement with the service provider. If the MSP service is provisioned for the subscriber at the first time the subscriber shall also be provisioned with a least two profiles.

5.1.2 Withdrawal

Withdrawal of the MSP service shall be done by either the service provider at the subscriber's request or for administrative reasons. The MSP service shall be withdrawn when there is only one profile remaining.

5.1.3 Activation

The MSP service is activated by the service provider as a result of provision.

5.1.4 Deactivation

The MSP service is deactivated by the service provider as a result of withdrawal.

5.1.5 Invocation

The MSP service is invoked by mobile originated activities and mobile terminated traffic.

5.2 Handling of the Profile

This section describes the normal procedures for selecting the registered profile for outgoing calls and supplementary service related activities. For mobile terminated calls the profile is automatically selected by the profile associated with the called MSISDN.

5.2.1 Provision

The provision of profiles (up to a maximum of four) is provided by prior arrangement with the service provider. The subscriber may select any provisioned profile on a per call basis or register to it. The subscriber will nominate one profile as the default profile to be used when roaming to non-supporting network. The roaming profile can only be changed by the service provider

5.2.2 Withdrawal

The Service Provider shall be able to withdraw profiles. The registered profile shall never be withdrawn, and consequently if the registered profile needs to be withdrawn the service provider shall first register the subscriber onto another profile.

5.2.3 Registration

Registration is the procedure by which information is written to the network to allocate a particular profile to be used for all outgoing calls and supplementary service related activities. Registration to a profile shall take place either by the service provider or with an appropriate control procedure by the subscriber as defined in GSM 02.30 [3]. At all times only one profile shall be registered.

5.2.4 Erasure

A previous registration can be erased in the following ways:

- the subscriber can register to another profile which causes the previous registration to be overridden;
- the registered profile is erased as a result of withdrawal of the MSP service.

5.2.5 Interrogation

The subscriber shall be able to interrogate which profile is the registered profile and all other available profile IDs, with an appropriate control procedure as defined in GSM 02.30 [3].

5.2.6 Handling of the MSP Password

The MSP password can be used to register a profile or select an alternative profile on a per call basis. There will be one password for all profiles. The value of the password is under subscriber control, and shall either take the value "null" (i.e. the password does not exist) or be registered to a 4 digit number.

The control procedures for registration and erasure of the password are defined in GSM 02.30 [3].

5.3 Normal operation with successful outcome

5.3.1 Mobile Originating Activities

The activity shall be handled according to the selected profile.

Any activity that is normally chargeable shall be identified against the selected profile.

5.3.2 Mobile Terminating Traffic

The called MSISDN shall be used to determine the profile to be used. If there are any active supplementary services, which are applicable to the telecommunication service within the profile, then those supplementary services shall apply.

The serving network shall indicate the profile towards the mobile station. The mobile station may use this information to indicate to the user the profile used for the mobile terminating traffic.

Any activity that is normally chargeable shall be identified against the profile used for the mobile terminating traffic.

5.4 Exceptional procedures or unsuccessful outcome

5.4.1 Roaming into networks not supporting MSP

The default profile shall be used for outgoing traffic when the subscriber roams to a non-supporting network.

Incoming calls to non-default profiles when roaming to a non-supporting network will be treated as though the subscriber was not reachable.

NOTE: If the subscriber is to roam and knows/believes that the roaming network is non-supporting, then the subscriber can use call forward not reachable to forward calls to the default profile. This will allow incoming calls to be received from other profiles.

6 Interaction between Profiles

For parallel transactions, different profiles can be used e.g. outgoing calls and incoming short messages.

7 Interaction with supplementary services

Supplementary services shall be provisioned on a subscriber basis. Therefore all provisioned subscription options will be the same for all profiles. Registration and activation data that can be different for different basic service groups can also be different in different profiles. The subscriber shall be able to make SS operation apply across all profiles, e.g. register/activate SS for all profiles. This shall only be performed if the MSP password is set to "NULL".

The profile used when a supplementary service is invoked will be subject to the charging principles and invocation requirements relevant to that supplementary service. The service provider may decide which profiles to charge for the service provision.

7.1 Line Identification Services

The profile used for the incoming or outgoing call shall be used for the line identification services.

7.2 Call Hold (CH)

If subscribed to, the CH service will be available to all profiles within a subscription.

7.3 Call Waiting (CW)

If subscribed to, the CW service will be available to all profiles within a subscription. CW for an incoming call will only be invoked if the profile for the ongoing call has the CW service active; although the incoming call may be on any profile

7.4 Call Forwarding

Each profile shall have the ability independently to register and activate call forwarding.

The subscriber shall be able to forward calls to from one profile to another profile.

NOTE: This allows the possibility when roaming to a non-supporting network to forward calls from the non-default profiles to the default profile to ensure the calls can be received.

7.4.1 Call forwarding unconditional (CFU)

If the requested telecommunications service in the profile used for the incoming call has an active and operative call forwarding, the call forwarding shall be invoked in the normal way.

7.4.2 Call Forwarding on busy (CFB)

If the requested telecommunications service in the profile used for the incoming call has an active and operative call forwarding on mobile subscriber busy (CFB), the call forwarding shall be invoked in the normal way if the subscriber is busy in any profile.

7.4.3 Call forwarding on No Reply (CFNRy)

If the requested telecommunications service in the profile used for the incoming call has an active and operative call forwarding, the call forwarding on no reply (CFNRy) shall be invoked in the normal way.

7.4.4 Call forwarding on not reachable (CFNR)

If the requested telecommunications service in the profile used for the incoming call has an active and operative call forwarding, the call forwarding on not reachable (CFNRc) shall be invoked in the normal way.

7.5 Multi Party Service (MPTY)

If subscribed to, the MPY service will be available to all profiles within a subscription.

7.6 Closed User Group (CUG)

If subscribed to, the CuG service shall be applicable to the selected profile.

7.7 Advice of Charge (AoC)

If subscribed to, AoCI or AoCC shall be applicable to the selected profile. Each profile shall have a separate meter (ACM) and a separate upper limit (ACMmax) when AoCC is subscribed. There shall be an overall meter for all profiles, with its own upper limit for AoCC if subscribed.

7.8 Call Barring

Barring options shall be applicable on a per profile basis.

7.9 Explicit Call Transfer (ECT)

If subscribed to, the ECT service shall be available on a per profile basis.

7.10 CCBS

If subscribed to, the CCBS shall be applicable to all profiles within a subscription. If the subscriber is informed of CCBS recall, the profile in use when the CCBS was activated shall be used for the call. If the subscriber has registered onto a different profile from that originally used for the CCBS activation, then this profile shall be automatically selected for the CCBS call, and the registered profile is not changed.

7.11 Operator Determined Barring

ODB shall apply on a per profile basis.

7.12 Roaming restrictions

These will apply on a per subscriber basis.

8 Interaction with other services

8.1 The Multi-Numbering Scheme

The multi-numbering scheme is described in GSM 02.01 [2]. For each of the profile defined above, it shall be possible for the subscriber to be allocated different MSISDNs for different basic services and supplementary services.

8.2 The Short Message Service

The Short Message Service is described in GSM 03.40 [4]. For incoming short messages, the profile used shall be clearly indicated to the user. This indication to the user shall be retained with the message and made available if it is subsequently read from the SIM. For outgoing short messages, indication of the profile used is included in the message by the network.

9 Cross-Phase Compatibility

The default profile will be sent to the visited network and can be addressed by non-supporting networks.

Mobile terminated calls to a non-supporting MS shall still be accepted but the indication of profile will not be supported.

History

Date	Version	New version	Section Affected	SMG1	Doc	Subject
07/02/96	1.0.0	1.1.0	Various			
23/04/96	1.1.0	1.2.0	Various			
25/04/96	1.2.0	1.3.0	Various			
26/04/96	1.3.0	2.0.0	Title page & 5.1.2			

Change history					
SMG No.	TDoc. No.	CR. No.	Section affected	New version	Subject/Comments
SMG#19	367/96	None		2.0.0	Submitted for approval

Document history	
June 1996	Creation of Version 5.0.0
July 1996	Publication of Version 5.0.0