

ETSI/TC SMG
Released by : ETSI/PT 12
Release date: February 1992

RELEASE NOTE

Recommendation GSM 09.03

Requirements on Interworking between the ISDN or PSTN and the PLMN

Previously distributed version : 3.0.1 (Release 1/90)
New Released version February 92 : 3.0.1 (Release 92, Phase 1)

1. Reason for changes

No changes since the previously distributed version.

Blank page

ETSI-GSM
Technical
Specification

GSM 09.03

Version 3.0.1

UDC: 621.396.21

Key words: European Digital Cellular Telecommunications System, Global System for Mobile Communications (GSM)

**European digital cellular
telecommunication system (phase 1);
Requirements on Interworking between the ISDN or PSTN and
the PLMN**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat: B.P.152 . F - 06561 Valbonne Cedex . France

TP. + 33 92 94 42 00 TF. + 33 93 65 47 16 Tx. 47 00 40 F

Copyright European Telecommunications Standards Institute 1992.
All rights reserved.

No part may be reproduced or used except as authorised by contract or other written permission. The copyright and the foregoing restriction on reproduction and use extend to all media in which the information may be embodied.

PREFATORY NOTE

ETSI has constituted stable and consistent documents which give specifications for the implementation of the European Cellular Telecommunications System. Historically, these documents have been identified as "GSM recommendations".

Some of these recommendations may subsequently become Interim European Telecommunications Standards (I-ETTs) or European Telecommunications Standards (ETTs), whilst some continue with the status of ETSI-GSM Technical Specifications. These ETSI-GSM Technical Specifications are for editorial reasons still referred to as GSM recommendations in some current GSM documents.

The numbering and version control system is the same for ETSI-GSM Technical Specifications as for "GSM recommendations".

1. INTRODUCTION	2
2. GENERAL SIGNALLING REQUIREMENTS	2
2.1 Requirements for the mobile network	2
2.2 Requirements for the fixed network	3
3. INTERWORKING WITH THE PSTN FOR CALL SET-UP	3
4. INTERWORKING WITH THE ISDN FOR CALL SET-UP	4
5. IMPACT OF THE OFF-AIR CALL SET-UP ON THE INTERWORKING	5
5.1 Definition of the off-air call set-up	5
5.2 Outgoing call from a mobile station	5
5.3 Incoming call to a mobile station	6
6. SPECIAL ARRANGEMENTS	6
6.1. Control of speech processing and echo control devices	6

Blank page

1. INTRODUCTION

The purpose of this Recommendation is to present the general requirements for the PSTN and the ISDN as well as for the mobile network to be met in order to ensure a correct integration of the mobile service in the fixed network.

This Recommendation covers only the signalling aspects of the interworking. The service requirements have to be covered in a specific Recommendation: only the signalling impacts have to be dealt with here.

2. GENERAL SIGNALLING REQUIREMENTS

2.1 Requirements for the mobile network

In order to be integrated in the fixed network the PLMN must comply with the following requirements:

- a) The MAP which supports information exchanges between the nodes of the mobile service uses the facilities of Transactions Capabilities of Signalling System NO 7. Therefore the equipments of the mobile network must comply with the specifications of the interface between TCAP and the application user. If TCAP functions are integrated in the mobile network equipments, the latter must comply with the relevant specifications (C.C.I.T.T Recommendations Q 771 to Q 774).
- b) For MAP messages routing purpose, the mobile nodes must provide the SCCP via TCAP with an address complying with the relevant specifications (C.C.I.T.T Recommendations Q 711 to Q 714).
- c) For call set-up, the MSCs must interface with the fixed exchanges. In the detailed interworking recommendations, the fixed network signalling considered are the Signalling system NO 7 and its User Parts (TUP or ISUP). The MSCs must comply with the same signalling interface specifications as the fixed exchanges.
- d) The PLMN and the signalling on the radio path must provide the information needed to ensure a correct interworking with the fixed network. The interworking in the MSCs must occur with a minimum loss of information.
- e) The PLMN nodes must interface with the NO 7 signalling network. For that, they must comply with the MTP specifications (C.C.I.T.T Recommendations Q701 to Q 707).

2.2 Requirements for the fixed network

The adaptations of the fixed network needed for the integration of the mobile service have to be minimized. The minimum requirements in the case of a fixed network completely separate from the PLMN is for the provision of suitable facilities to carry Signalling System No 7 messages between PLMNs. In other cases where the PLMN is integrated to a greater or lesser extent with the fixed network, some facilities could be provided to facilitate access to the mobile service or the operation of the PLMN.

- a) The implementation of the NO 7 signalling network could be useful for the mobile service. Before NO 7 Signalling System is implemented, a dedicated signalling network using a subset of N07 could be used as an interim solution for transfer of the data between functional units of PLMNs.
- b) It will be useful that, in addition to the signalling network, the SCCP facilities be available in order to avoid a specific implementation of such a service in the PLMN equipments.
- c) The interrogation procedure based on TCAP prior to connection set up to a mobile would save circuits resources in the network and would increase the service quality provided to the fixed calling subscriber by eg. reducing the post dialling delay in such kinds of calls. The best way is to introduce this procedure as near as possible to the local originating exchanges.

3. INTERWORKING WITH THE PSTN FOR CALL SET-UP

The interworking with the Telephone User Part of the signalling system NO 7 is the only case considered here.

Particular aspects:

- a) The fixed telephone network provides an end to end transparent link at least for speech use. It is then possible to have a data transmission communication on a telephone call. This would not be the case with a mobile subscriber: the radio path would not be transparent. Therefore, if a calling subscriber wishes to have a data transmission call with a mobile it would be necessary to inform the network and precise the characteristics of this transmission: the mobile PLMN will then be able to replace the speech coder by a data coder adapted to the type of transmission modem used. One solution could be that the mobile has one telephone number per type of data transmission service he can use.

- b) The usual routing of a call to a mobile includes a rerouting according to the roaming number allocated to this mobile. This number is temporary allocated and difficulties could appear in some cases such as a failure of a register.
- c) To remove the need for multiple Roaming Numbers (e.g. in the case of data transmission from the PSTN) it may be possible, if the implementation allows, to include the called party address in the Initial Address Message sent to the MSC. Alternatively, an indicator specifying the service required could be employed.

4. INTERWORKING WITH THE ISDN FOR CALL SET-UP

Since the radio path could not economically provide a transparent 64 kb/s channel to mobile subscriber all the time, all the ISDN services foreseen in the fixed network will not be available to the mobile subscribers. The quality of service in land mobile networks may also in some cases not meet the quality of service requirements for certain ISDN services . Therefore some service limitations need to be introduced in the access to mobile stations.

Different methods may be foreseen to implement this limitation:

- a) The interrogation is used also to check the service capabilities of the mobile access. This procedure can also be used to perform a compatibility check between the parties. But this test is only possible if the HLR knows the relevant characteristics of the mobile station and cannot be used with card operated stations; in that case a mobile subscriber can use different stations.
- b) The simplest solution is that normal mobile call set-up be processed and controlled by the incoming MSC. As such the incoming MSC can also provide a compatibility check for card operate stations.
- c) The call is set up in the normal way up to the mobile. The IAM contains the characteristics of the service requested and on the terminal needed by the call. The network, MSC included, is transparent in the compatibility check. This method is the same as this defined in the ISDN.

5. IMPACT OF THE OFF-AIR CALL SET-UP ON THE INTERWORKING

The use of the off-air call set-up in the PLMN has an impact on the interworking with the fixed network. Both outgoing and incoming calls have to be considered: the consequences are not the same.

As it was stated before, the use of the Off-Air Call Set-Up procedure is optional and must be limited to national telephone calls only (see Recommendation GSM 03.01).

5.1 Definition of the off-air call set-up

To save the radio resources, the radio traffic channel may be allocated to the communication only when both calling and called parties are present ie. at the answer instant. This method called

"Off-Air Call Set-Up" (OACSU) has some implication on the interworking with the fixed network. But the consequences are not the same whether the mobile subscriber is the calling or the called party.

5.2 Outgoing call from a mobile station

Upon initiation of an outgoing call, a traffic channel is allocated to the communication when the called subscriber answer is received in the MSC. In some cases, no idle traffic channel may be available when necessary. Therefore an appropriate announcement must be given to the called party when no idle traffic channel is available within a certain interval upon receipt of the called party's answer.

Whenever the announcement is used, it must always be played through in its entirety, even if a traffic channel becomes available before it is completed, except if the called party clears, in which case the call should be cleared forward.

If the ADDRESS COMPLETE message indicates that there will possibly be no ANSWER message upon the connection of the called party (e.g. ADC without any information), the radio path must be established immediately upon receipt of the ADC.

Due to interworking constraints coming from the characteristics of the different signalling systems used in the countries, the OACSU technique should only be used for national calls.

5.3 Incoming call to a mobile station

For incoming calls, the impact is not so important, but some rules must be applied in order to limit the influence on the service quality.

Concerning the sending instant of the answer message, the normal operating rules apply. If the call is successfully set up to the mobile station, the answer message must be sent to the originating exchange only when the traffic channel is established upon recognition of the called party connection.

6. SPECIAL ARRANGEMENTS

6.1. Control of speech processing and echo control devices

For further study

