



**E**UROPEAN  
**T**ELECOMMUNICATION  
**S**TANDARD

**DRAFT**  
pr **ETS 300 098-5**

March 1996

---

Source: ETSI TC-SPS

Reference: DE/SPS-05061-M-5

ICS: 33.080

**Key words:** ISDN, DSS1, supplementary service, TSS&TP, testing, network

**Integrated Services Digital Network (ISDN);  
Connected Line Identification Restriction (COLR)  
supplementary service;  
Digital Subscriber Signalling System No. one (DSS1) protocol;  
Part 5: Test Suite Structure and Test Purposes (TSS&TP)  
specification for the network**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

\*

---

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.



## Contents

Foreword .....	5
1 Scope .....	7
2 Normative references .....	7
3 Definitions .....	7
3.1 Definitions related to conformance testing .....	7
3.2 Definitions related to ETS 300 098-1 .....	8
4 Abbreviations .....	9
5 Test Suite Structure (TSS) .....	9
6 Test Purposes (TP) .....	9
6.1 Introduction .....	9
6.1.1 Test purpose (TP) naming convention .....	9
6.1.2 Source of TP definition .....	9
6.1.3 TP structure .....	10
6.1.4 Test strategy .....	10
6.1.5 Test of call states .....	10
6.2 Network TPs for COLR .....	11
6.2.1 Called user .....	11
7 Compliance .....	12
8 Requirements for a comprehensive testing service .....	12
History .....	13

Blank page

## Foreword

This draft European Telecommunication Standard (ETS) has been produced by the Signalling Protocols and Switching (SPS) Technical Committee of the European Telecommunications Standards Institute (ETSI), and is now submitted for the Public Enquiry phase of the ETSI standards approval procedure.

This ETS is part 5 of a multi-part standard covering the Digital Subscriber Signalling System No. one (DSS1) protocol specification for the Integrated Services Digital Network (ISDN) Connected Line Identification Restriction (COLR) supplementary service, as described below:

- Part 1: "Protocol specification";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "TSS&TP specification for the network";**
- Part 6: "ATS and partial PIXIT proforma specification for the network".

<b>Proposed transposition dates</b>	
Date of latest announcement of this ETS (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Blank page

## 1 Scope

This fifth part of ETS 300 098 specifies the Test Suite Structure and Test Purposes (TSS&TP) for the Network side of the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [6]) of implementations conforming to the stage three standard for the Connected Line Identification Restriction (COLR) supplementary service for the pan-European Integrated Services Digital Network (ISDN) by means of Digital Subscriber Signalling System No. one (DSS1) protocol.

A further part of this ETS specifies the Abstract Test Suite (ATS) and partial PIXIT proforma based on this ETS. Other parts specify the TSS&TP and the ATS and partial PIXIT proforma for the User side of the T reference point or coincident S and T reference point of implementations conforming to ETS 300 098-1 [1].

## 2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] ETS 300 098-1: "Integrated Services Digital Network (ISDN); Connected Line Identification Restriction (COLR) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".

NOTE: ETS 300 098-1 was initially published as ETS 300 098.

- [2] ETS 300 098-2: "Integrated Services Digital Network (ISDN); Connected Line Identification Restriction (COLR) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] ISO/IEC 9646-1: "Information Technology - OSI Conformance Testing Methodology and Framework; Part 1: General Concepts".
- [4] ISO/IEC 9646-2: "Information Technology - OSI Conformance Testing Methodology and Framework; Part 2: Abstract Test Suite specification".
- [5] ISO/IEC 9646-3: "Information Technology - OSI Conformance Testing Methodology and Framework; Part 3: The Tree and Tabular Combined Notation".
- [6] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces - Reference configurations".
- [7] ETS 300 102-1: "Integrated Services Digital Network (ISDN); User-network interface layer 3; Specifications for basic call control".
- [8] ITU-T Recommendation I.112 (1993): "Vocabulary and terms for ISDNs".
- [9] CCITT Recommendation E.164 (1991): "Numbering plan for the ISDN era".
- [10] ITU-T Recommendation I.210 (1993): "Principles of the telecommunication services supported by an ISDN and the means to describe them".

## 3 Definitions

For the purposes of this ETS, the following definitions apply:

### 3.1 Definitions related to conformance testing

**abstract test case:** Refer to ISO/IEC 9646-1 [3].

**Abstract Test Suite (ATS):** Refer to ISO/IEC 9646-1 [3].

**active test:** A test case where the IUT is required to send a particular message, but not in reaction to a received message. This would usually involve the use of PIXIT information to see how this message can be generated and quite often is specified in an ATS using an Implicit Send event.

**implementation under test:** Refer to ISO/IEC 9646-1 [3].

**implicit send event:** Refer to ISO/IEC 9646-3 [5].

**lower tester:** Refer to ISO/IEC 9646-1 [3].

**passive test:** A test case where the IUT is required to respond to a protocol event (e.g. received message) with another protocol event (sends message) and normally does not require any special operator intervention such as is associated with the Implicit Send event.

**point of control and observation:** Refer to ISO/IEC 9646-1 [3].

**Protocol Implementation Conformance Statement (PICS):** Refer to ISO/IEC 9646-1 [3].

**PICS proforma:** Refer to ISO/IEC 9646-1 [3].

**Protocol Implementation eXtra Information for Testing (PIXIT):** Refer to ISO/IEC 9646-1 [3].

**PIXIT proforma:** Refer to ISO/IEC 9646-1 [3].

**system under test:** Refer to ISO/IEC 9646-1 [3].

**Test Purpose (TP):** Refer to ISO/IEC 9646-1 [3].

### 3.2 Definitions related to ETS 300 098-1

**Integrated Services Digital Network (ISDN):** See ITU-T Recommendation I.112 [8], definition 308.

**ISDN number:** A number conforming to the numbering and structure specified in CCITT Recommendation E.164 [9].

**international number:** An ISDN number structured as specified in subclause 3.2 (in the paragraphs relating to international number) of CCITT Recommendation E.164 [9].

**national number; national significant number:** An ISDN number structured as specified in subclause 3.2 (in the paragraphs relating to national significant number) of CCITT Recommendation E.164 [9].

**network:** The DSS1 protocol entity at the Network side of the user-network interface where a T reference point or coincident S and T reference point applies.

**network (S/T):** The DSS1 protocol entity at the network side of the user-network interface where a coincident S and T reference point applies.

**network (T):** The DSS1 protocol entity at the Network side of the user-network interface where a T reference point applies (Network connected to Private ISDN).

**service; telecommunication service:** See ITU-T Recommendation I.112 [8], definition 201.

**subscriber number:** An ISDN number structured as specified in subclause 3.2 (in the paragraphs relating to subscriber number) of CCITT Recommendation E.164 [9].

**supplementary service:** See ITU-T Recommendation I.210 [10], subclause 2.4.




## 4 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
COLR	Connected Line Identification Restriction
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
N01	Call Initiated Call state
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
TP	Test Purpose
TSS	Test Suite Structure

## 5 Test Suite Structure (TSS)



NOTE: Numbers in brackets represent group numbers and are used in Test purpose identifiers.

**Figure 1: Test suite structure**

## 6 Test Purposes (TP)

### 6.1 Introduction

For each test requirement a TP is defined.

#### 6.1.1 Test purpose (TP) naming convention

The TPs are numbered, starting at 001, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual Test Suite and whether it applies to the Network or the User side (see table 1).

**Table 1: TP identifier naming convention scheme**

Identifier:	<b>&lt;ss&gt;_&lt;iut&gt;&lt;group&gt;_&lt;nnn&gt;</b>		
<ss> =	supplementary service:	e.g. "COLR_"	
<iut> =	type of IUT:	U	User
		N	Network
<group>	group	2 digit field representing group reference according to TSS	
<nnn> =	sequential number	(001-999)	

#### 6.1.2 Source of TP definition

The TPs are based on ETS 300 098-1 [1].

### 6.1.3 TP structure

Each TP has been written in a manner which is consistent with all other TPs. The intention of this is to make the TPs more readable and checkable. A particular structure has been used and this is illustrated in table 2. This table should be read in conjunction with any TP i.e. use a TP as an example to fully understand the table.

**Table 2: Structure of a single TP for COLR**

TP Part	Text	Example
<b>Header</b>	<Identifier> <i>tab</i> <paragraph number in base ETS> <i>tab</i> <PICS reference> <i>tab</i> <condition> <i>CR</i> .	see table 1 <b>subclause 0.0.0</b> <b>XY 0.0</b> <b>mandatory, optional,</b> <b>conditional</b>
<b>Stimulus</b>	Ensure that the IUT in the <basic call state> <trigger> <i>see below for message structure</i> <i>or</i> <goal>	N00, N10, etc. receiving a XXXX message to request a ....
<b>Reaction</b>	<action> <conditions> <i>if the action is sending</i> <i>see below for message structure</i> <next action>, <i>etc.</i> and enters <supplementary service state> <i>and/or</i> and remains in the same state(s) <i>or</i> and enters state <state> with CR<number(s)>	sends, saves, does, etc. using en bloc sending, ...
<b>Message structure</b>	<message type> message containing a a) <info element> information element with b) a <field name> encoded as <i>or</i> including <coding of the field> and <i>back to a or b</i> ,	SETUP, FACILITY, CONNECT,  Bearer capability, Facility, ....
<b>NOTE:</b>	Text in italics will not appear in TPs and text between <> is filled in for each TP and may differ from one TP to the next.	

### 6.1.4 Test strategy

As the base standard contained no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and PICS. The criteria applied included the following:

- only the requirements from the point of view of the T or coincident S and T reference point are considered;
- whether or not a test case can be built from the TP is not considered.

### 6.1.5 Test of call states

Many TPs include a reference to the IUT's final call state after the realization of the TP. In these cases the TP includes the requirement to ensure that the IUT has entered this particular final call state. Ensuring that the IUT is in a particular call state shall be realized by following the procedures described in subclause 5.8.10 of ETS 300 102-1 [7]. According to these procedures, the IUT on receipt of a STATUS ENQUIRY message, shall respond with a STATUS message indicating, in the third octet of the Call state information element, the current call state of the IUT. This exchange of messages is not mentioned explicitly in each TP but is considered to be implicit in the reference to the final call state. This way of phrasing the TPs has been used to avoid over complicating the text and structure of the TPs and to improve the readability.

## 6.2 Network TPs for COLR

All PICS items referred to in this subclause are as specified in ETS 300 098-2 [2] unless indicated otherwise by another numbered reference.

### 6.2.1 Called user

#### **COLR\_N01\_001**                      **subclause 9.3.1, first paragraph**                      **optional**

Ensure that the IUT in the Call Present call state N06, with the called user access configured for subscription to the COLR supplementary service permanent mode, on receipt of a CONNECT containing a Connected number information element with the Presentation indicator set to "presentation allowed", ignores the Presentation indicator (resulting in the sending of a CONNECT message containing a Connected number information element with the Presentation indicator value "presentation restricted" and without connected party number to the calling user) and sends a CONNECT ACKNOWLEDGE message and enters the Active call state N10.

**Selection:** IUT supports the provision of COLR on a permanent mode basis. PICS: MC 4.4.

#### **COLR\_N01\_002**                      **subclause 9.3.1, second paragraph**                      **mandatory**

Ensure that the IUT in the Call Present call state N06, with the called user access configured for subscription to the COLR supplementary service temporary mode (per-call basis), on receipt of a CONNECT containing a Connected number information element with the Presentation indicator set to "presentation allowed",

accepts the Presentation indicator value (resulting in the sending of a CONNECT message containing a Connected number information element with the Presentation indicator value "presentation allowed" and with connected party number to the calling user) and sends a CONNECT ACKNOWLEDGE message and enters the Active call state N10.

#### **COLR\_N01\_003**                      **subclause 9.3.1, second paragraph**                      **mandatory**

Ensure that the IUT in the Call Present call state N06, with the called user access configured for subscription to the COLR supplementary service temporary mode (per-call basis), on receipt of a CONNECT containing a Connected number information element with the Presentation indicator set to "presentation restricted",

accepts the Presentation indicator value (resulting in the sending of a CONNECT message containing a Connected number information element with the Presentation indicator value "presentation restricted" and without connected party number to the calling user) and sends a CONNECT ACKNOWLEDGE message and enters the Active call state N10.

#### **COLR\_N01\_004**                      **subclause 9.3.1, third paragraph**                      **optional**

Ensure that the IUT in the Call Present call state N0p, with the called user access configured for subscription to the COLR supplementary service temporary mode (per-call basis), default value presentation restricted, on receipt of a CONNECT containing a Connected number information element with no Presentation indicator,

accepts the message (resulting in the sending of a CONNECT message containing a Connected number information element with the Presentation indicator value "presentation restricted" and without connected party number to the calling user) and sends a CONNECT ACKNOWLEDGE message and enters the Active call state N10.

**Selection:** IUT supports the provision of COLR temporary mode basis, default value presentation restricted. PICS: MC 4.2.

#### **COLR\_N01\_005**                      **subclause 9.3.1, third paragraph**                      **optional**

Ensure that the IUT in the Call Present call state N06, with the called user access configured for subscription to the COLR supplementary service temporary mode (per-call basis), default value presentation not restricted, on receipt of a CONNECT containing a Connected number information element with no Presentation indicator,

accepts the message (resulting in the sending of a CONNECT message containing a Connected number information element with the Presentation indicator value "presentation allowed" and with connected party number to the calling user) and sends a CONNECT ACKNOWLEDGE message and enters the Active call state N10.

**Selection:** IUT supports the provision of COLR temporary mode basis, default value presentation not restricted. PICS: MC 4.3.

## **7 Compliance**

An ATS which complies with this TSS&TP specification shall:

- a) consist of a set of test cases corresponding to the set or to a subset of the TPs specified in clause 6;
- b) use a TSS which is an appropriate subset of the whole of the TSS specified in clause 5;
- c) use the same naming conventions for the test groups and test cases;
- d) maintain the relationship specified in clause 6 between the test groups and TPs and the entries in the PICS proforma to be used for test case deselection;
- e) comply with ISO/IEC 9646-2 [4].

In the case of a) or b) above, a subset shall be used only where a particular Abstract Test Method (ATM) makes some TPs untestable. All testable TPs from clause 6 shall be included in a compliant ATS.

## **8 Requirements for a comprehensive testing service**

As a minimum the Remote test method, as specified in ISO/IEC 9646-2 [4], shall be used by any organization claiming to provide a comprehensive testing service for network equipment claiming conformance to ETS 300 098-1 [1].

**History**

<b>Document history</b>	
March 1996	Public Enquiry PE 103: 1996-03-04 to 1996-06-28