

EUROPEAN TELECOMMUNICATION STANDARD

DRAFT pr **ETS 300 133-2**

April 1996

Second Edition

Source: ETSI TC-RES Reference: RE/RES-04007-2

ICS: 33.060.20 33.060.50

Key words: ERMES, paging, service, system

Radio Equipment and Systems (RES); European Radio MEssage System (ERMES); Part 2: Service aspects

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - Internet: secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

*

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

Page 2 Draft prETS 300 133-2: April 1996		
Draft prETS 300 133-2: April 1996		

Whilst every care has been taken in the preparation and publication of this document, errors in content, typographical or otherwise, may occur. If you have comments concerning its accuracy, please write to "ETSI Editing and Committee Support Dept." at the address shown on the title page.

Contents

For	eword					7
1	Scope					9
2	Norma	ative referen	ces			9
3	Definit	ions				9
_	3.1					
	3.2					
	3.3					
4	Comic	oo and facili	tion			10
4	4.1					
	4.1	4.1.1				
		4.1.1				
					services	
	4.2	4.1.3			S	
	4.2					
		4.2.1		~ ~		
		4.2.2				
		4.2.3	•			
	4.0	4.2.4				
	4.3					
		4.3.1			rvices	
			4.3.1.1		ments	
				4.3.1.1.1	Valid input acknowledgements	
				4.3.1.1.2	Subscriber feature acknowledger	
			4.3.1.2		ry services related to the destination of	
				4.3.1.2.1	Roaming service	
				4.3.1.2.2	Diversion of traffic	
				4.3.1.2.3	Choice of destination	
			4.3.1.3		ry services related to protection against	
				4.3.1.3.1	Repetition	
				4.3.1.3.2	Message storing and retrieval	18
				4.3.1.3.3	Automatic retransmission of the I number	
			4.3.1.4	Bureau servic	es	
		4.3.2	-		ed to priority	
			4.3.2.1		y	
			4.3.2.2		y	
			4.3.2.3		y	
		4.3.3			nentary services	
		4.0.0	4.3.3.1		Group	
			4.3.3.2			
			4.0.0.2	4.3.3.2.1	Group calls to mobile subscribers	
				4.3.3.2.1	common RIC	
				42222		
				4.3.3.2.2	Group calls to mobile subscribers	
			4000	NA. 14:	individual RIC	
			4.3.3.3		calls to mobile subscribers	
			4.3.3.4		indication	
		40.	4.3.3.5		ramming of RIC	
		4.3.4			ces	
			4.3.4.1		rging	
			4.3.4.2		ging acceptance	
			4.3.4.3	Charging info	rmation for fixed subscribers	29

		4.3.5	• •	tary services related to the restriction of calls	
			4.3.5.1	Temporary barring of incoming traffic	29
		4.0.0	4.3.5.2	Restriction on all calls	
		4.3.6		ementary services	
			4.3.6.1 4.3.6.2	Urgent message indication	
				Deferred delivery	
			4.3.6.3	Standard texts	
			4.3.6.3.1	Standard texts defined by the network operator	
	4.4	0	4.3.6.3.2	Standard texts defined by fixed subscribers	
	4.4.				
		4.4.1		4	
		4.4.2 4.4.3		of messageson code	
		4.4.3 4.4.4	•	on	
		4.4.4	4.4.4.1	Authentication by use of passwords	
			4.4.4.2	Authentication by use of passwords Authentication by reverse calling	
			4.4.4.3	Authentication by use of certificate	
	4.5	Subcerik		Authentication by use of certificate	
	4.5	Subscrit	ber directory		50
5					
	5.1				
	5.2				
		5.2.1			
		5.2.2			
		5.2.3		ric	
		5.2.4		t data	
		5.2.5		S	
	- 0	5.2.6		ne message	
	5.3	Supplen 5.3.1		features	
		5.3.1	Indication of	all indicationf lost message/message number control	oo
		5.3.3			
		5.3.4		gramming of RIC	
		5.3.5		sage indicator	
	5.4			es	
	5.4	5.4.1		es	
		5.4.1		indication	
		5.4.3		orage and retrieval	
		5.4.4		orage and remeval	
		5.4.5		anipulation	
		5.4.6		anpulation	
		5.4.7		face	
		5.4.8		Ce	
		5.4.9		dication	
		5.4.10		of messages	
		5.4.10	Liferyption	, mossages	
6					
	6.1				
	6.2	Quality of		eters	
		6.2.1		oonse delay	
		6.2.2	Input blockir	ng probability (input grade of service)	40
		6.2.3	Call accepte	ed acknowledgement delay	40
		6.2.4		ted acknowledgement delay	
		6.2.5		eature acknowledgement delay	
		6.2.6		elivery time	
		6.2.7	Call success	s rate	41
		6.2.8		ite	
		6.2.9	Correct mes	ssage transmitted probability	42
Ann	ex A (nor	mative):	Essential and o	pptional supplementary services	43
Ann	ex B (nor	mative):	Character sets	in the ERMES system	45
	~~ - (1101		Unandoloi deld	· · · · · · · · · · · · · · · · · · ·	🛨

B.1	Charact	ters for numeric paging	45
B.2	Charact	ters for alphanumeric paging	45
	B.2.1	Optional character set for Chinese Characters	48
Annex C (norm	native):	The concept of radiodistribution	77
Annex D (norm	native):	Essential and optional receiver features	78
History			79

Blank page

Foreword

This draft second edition European Telecommunication Standard (ETS) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI), and is now submitted for the Public Enquiry phase of the ETSI standards approval procedure.

This ETS comprises seven parts with the generic title "Radio Equipment and Systems (RES); European Radio Message System (ERMES)". The title of each part is listed below:

- ETS 300 133-1: "Part 1: General aspects"
- ETS 300 133-2: "Part 2: Service aspects"
- ETS 300 133-3: "Part 3: Network aspects"
- ETS 300 133-4: "Part 4: Air interface specification"
- ETS 300 133-5: "Part 5: Receiver conformance specification"
- ETS 300 133-6: "Part 6: Base station specification"
- ETS 300 133-7: "Part 7: Operation and maintenance aspects"

This part, ETS 300 133-2, specifies the services and facilities of the European Radio Message System (ERMES). This part also defines the quality of service aspects and describes the receiver features.

ETSI Interim Intellectual Property Rights (IPR) Policy

The attention of ETSI has been drawn to the IPRs listed below which are, or may become, Essential to this ETS. The IPR owner has undertaken to grant irrevocable licences on fair, reasonable and non-discriminatory terms and conditions under these IPRs pursuant to the ETSI Interim IPR Policy. Further details pertaining to these IPRs can be obtained directly from the IPR owner.

The information presently submitted is accurate to the best of ETSI's knowledge. Pursuant to the ETSI Interim IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can thus be given as to the existence of other IPRs, which are, or may become, Essential to this ETS.

IPRs:

EP Patent No. 0090851: Decoder for Transmitted Message Activation Codes;

EP App. No. 89909668,9: Multiple Frequency Message System;

EP App. No. 89913131,2: Power Conservation Method and Apparatus for a Portion of Information

Signal;

EP App. No. 92901376,1: Multiple Format Signalling Protocol for a Selective Call Receiver;

EP App. No. 90915018,7: Nationwide Paging with Local Modes of Operation;

EP App. No. 91904526,0 Multiple Frequency Scanning.

IPR owner: MOTOROLA Ltd, 110 Bath Road, Slough, GB-BERKSHIRE SL1 3SZ

Proposed transposition dates			
Date of latest announcement of this ETS (doa):	3 months after ETSI publication		
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	6 months after doa		
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa		

1 Scope

This part of the seven part European Telecommunication Standard (ETS) 300 133, describes the service aspects of the European Radio Message System (ERMES). In particular, a recommended set of basic and supplementary services is defined and described. The features that should be considered for implementation in the paging receivers are also described. Finally, the quality of service that is offered to the users of the system is defined.

2 **Normative references**

This ETS incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references subsequent amendments to, or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

[1]	prETS 300 133-1 (1996): "Radio Equipment and Systems (RES); European Radio Message System (ERMES); Part 1: General aspects".
[2]	prETS 300 133-3 (1996): "Radio Equipment and Systems (RES); European Radio Message System (ERMES); Part 3: Network aspects".
[3]	prETS 300 133-5 (1996): "Radio Equipment and Systems (RES); European Radio Message System (ERMES); Part 5: Receiver conformance specification".
[4]	ISO 1073, parts 1 & 2: "Alphanumeric character sets for optical recognition".
[5]	prETS 300 133-4 (1996): "Radio Equipment and Systems (RES); European Radio Message System (ERMES); Part 4: Air interface specification".

3 **Definitions**

3.1 **Definitions**

For the purposes of this part of this ETS the following definitions apply:

authentication: a function which enables the Paging Network Controller (PNC) to ensure that the identity stated by a fixed or a mobile subscriber is true (subclause 4.4.1).

legitimisation: a function which ensures that a calling party trying to carry out a restricted operation (an operation which is not allowed to all calling parties) is authorised to do this (subclause 4.4.1).

essential service or facility: A service or facility which is implemented and provided in all operator networks in the system.

optional service or facility: An optional service or facility is provided at the discretion of the network operators. If implemented it conforms with this standard.

essential receiver feature: A receiver feature that is implemented in all receivers (if it is relevant to the paging category of a specific receiver).

optional receiver feature: A receiver feature which may be implemented at the manufacturers' discretion. If implemented it conforms with this standard.

For the definitions of the other terms used in this standard see ETS 300 133-1 [1], clause 3.3, "Vocabulary".

3.2 **Abbreviations**

For the purposes of this part of this ETS the following abbreviations apply:

AdC Address Code

Draft prETS 300 133-2: April 1996

ACK/NACK Positive/Negative Acknowledgement

BVR Basic Version Receiver
CUG Closed User Group
DTMF Dual Tone Multi-Frequency

EOM End of Message

ERMES European Radio Message System

GAdC Group Address Code
PNC Paging Network Controller

PNC-H Home PNC
PNC-I Input PNC
PNC-T Transmitting PNC

PSTN Public Switched Telephone Network

RIC Radio Identity Code

3.3 Symbols

C Network status (subclause 4.3.1.1.1) UC Network status (subclause 4.3.1.1.1)

4 Services and facilities

4.1 General

4.1.1 Introduction

In this clause the set of basic and supplementary services that may be supported by an ERMES network is defined and described. Some services are specified as essential to enable operation of an international paging system. A number of optional services are also described, which operators may include in their systems.

The security aspects of the system are also included in this clause.

4.1.2 Framework for describing the services

The text associated with each service is structured in the following way:

Definition

This paragraph provides a general definition and description of the service as it is seen by the user.

Procedures

provision;

This paragraph indicates if the service should be essential or optional for the network operators of the ERMES system.

- normal procedures.

This paragraph gives an indication of who (calling party, fixed or mobile subscriber) is supposed to activate the service and on what conditions it is made available to the users (e.g. per call basis or by registration).

Network capabilities for charging

This paragraph gives an indication of what charging arrangements the system shall be able to support.

Interworking requirements

This paragraph describes the interworking requirements between the different ERMES networks in order to implement a service.

Interaction with other services

This paragraph describes the interactions with other ERMES services when the service being described is activated.

4.1.3 Essential and optional services

Each service shall be considered as essential or optional for the network operator. In table A.1, the essential and optional supplementary services and facilities for each paging category is given.

4.2 Basic services

The system shall offer mobile subscribers levels of basic paging services according to the receiver capabilities. The system shall check that paging calls are not accepted to higher levels than the one corresponding to the subscription. This check shall also take place on activation of a supplementary service, e.g. diversion of traffic.

The ERMES system provides two kinds of call in each basic service:

- individual calls that are initiated by using one Address Code (AdC) and are intended for only one mobile subscriber;
- group calls that are initiated by using one Group Address Code (GAdC) and are intended for two or more mobile subscribers.

4.2.1 Tone-only paging

Definition

Tone-only paging is the first basic service level and simplest kind of paging service, corresponding to the traditional type of radio paging. The tone-only service means that paging signals to a particular receiver shall cause the receiver to generate a simple alert signal. The system shall support up to 8 different alert signals per Radio Identity Code (RIC). The system shall transmit the message within a message delivery time depending on the level of priority (subclause 6.2).

Procedures

provision;

This essential service shall be provided by all network operators. It shall be implemented in the Paging Network Controller (PNC) and all types of receivers, except transparent data receivers. The service may be implemented in the transparent data receiver.

normal procedures.

Tone-only paging can be activated by the calling party by any Public Switched Telephone Network (PSTN) telephone on a per call basis to a mobile subscriber in the system. It may also be activated by other terminal equipment.

Network capabilities for charging

The service should be charged on subscription and/or on a per call basis according to the network operator's policy.

Interworking requirements

None.

Interaction with other services

A number of supplementary services can not be activated when tone-only calls are sent (table A.1).

4.2.2 Numeric paging

Definition

Numeric paging is the second service level. It allows transmission of up to at least 20 numeric or special characters. This service is intended for mobile subscribers using pagers with the capability to receive, store and display numeric information in addition to tone-only paging. The character set is included in table B.1. The system shall transmit the message within a message delivery time depending on the level of priority (subclause 6.2). The maximum message length that the ERMES system can support is 16 000 numeric characters. The network operators shall provide for a maximum message length between 20 and 16 000 numeric characters. Messages longer than the maximum message length that a specific receiver can accept shall not be delivered. The calling party shall be informed that the message is too long (see also subclause 4.2.4 for very long messages).

Procedures

provision;

This essential service shall be provided by all network operators. It shall be implemented in the PNC as well as in numeric and alphanumeric receivers. The service may be implemented in the transparent data receiver.

normal procedures.

The service can be activated by the calling party on a per call basis to a mobile subscriber in the system.

Network capabilities for charging

The service should be charged on subscription and/or on a per call basis according to the network operator's policy.

Interworking requirements

None.

Interaction with other services

None.

4.2.3 Alphanumeric paging

Definition

Alphanumeric paging is the third service level. It allows transmission of text information with up to at least 400 alphanumeric characters. This service is for mobile subscribers using receivers with the capability to receive, store and display text information in addition to tone-only and numeric paging. The basic character set is defined in table B.3. The system shall transmit the message within a message delivery time depending on the level of priority (subclause 6.2). The maximum message length that the ERMES system can support is 9 000 alphanumeric characters. The network operators shall provide for a maximum message length between 400 and 9 000 alphanumeric characters. Messages longer than the maximum message length that a specific receiver can accept shall not be delivered. The calling party shall be informed that the message is too long (see also subclause 4.2.4 for very long messages).

Procedures

provision;

This essential service shall be provided by all network operators. It shall be implemented in the PNC and in alphanumeric receivers. The service may be implemented in the transparent data receiver.

normal procedures.

The service can be activated by the calling party on a per call basis to a mobile subscriber in the system.

Network capabilities for charging

The service should be charged on subscription and/or on a per call basis according to the network operator's policy.

Interworking requirements

None.

Interaction with other services

None.

4.2.4 Transparent data paging

Definition

Transparent data paging is a service allowing transmission of an arbitrary data stream to the receiver. The system shall transmit the message within a message delivery time depending on the level of priority (subclause 6.2). The use of the data stream is determined by the application chosen by the subscriber. Only the part of the radio channel dedicated to the message allows a full bit transparency. The maximum message length that the ERMES system can support is 64 kbits. The network operators may provide for a maximum message length of less than 64 kbits. Messages longer than the maximum message length that a specific receiver can accept shall not be delivered. The calling party shall be informed that the message is too long.

Very long messages (longer than the defined maximum) can be sent through the ERMES system only if they are split into messages shorter than the maximum length. Users who wish to send such messages, may define a method of linking the parts of the messages together, between calling party and receiver. This method shall be transparent to the ERMES system, i.e. the parts shall be transmitted as separate messages.

Procedures

provision;

Provision of this service shall be optional for the network operators. Restrictions on the message length can be imposed by the network operator according to his policy. It shall be implemented in the PNC as well as in the receiver. Lower categories may be implemented in the transparent data receiver.

- normal procedures.

The service can be activated by the calling party on a per call basis to a mobile subscriber in the system.

Network capabilities for charging

The service should be charged on subscription and/or on a per call basis according to the network operator's policy.

Interworking requirements

None.

Interaction with other services

The bureau service can not be activated when the transparent data service is used.

4.3 Supplementary services

A supplementary service modifies or supplements a basic service. The offered supplementary services may be used by the subscribers/users at their discretion.

4.3.1 Call related supplementary services

4.3.1.1 Acknowledgements

4.3.1.1.1 Valid input acknowledgements

Definition

During the input of a call, acknowledgements shall be generated by the system to the calling party indicating the call status. At least the following three types of acknowledgements shall be provided:

a) call accepted acknowledgement;

The called AdC (individual or GAdC) is (is not) valid and the system is (is not) ready to accept the call. The calling party is invited to enter data referring to additional information or the required supplementary service(s) or to enter the message.

A call shall be treated as unconditionally accepted when the home operator is able to guarantee a network status better than a threshold C in the areas in which the page is destined for transmission (for the calculation of network status see ETS 300 133-3 [2]).

A call shall be treated as partially accepted when the network operator is only able to guarantee a network status between a threshold UC and a threshold C in the areas in which the page is destined for transmission.

The call shall be rejected when the network operator cannot guarantee a network status greater than a threshold UC in the areas in which the page is destined for transmission.

Each network operator shall define its own thresholds C and UC, which can be identical if only two call acceptance conditions are to be given to the calling party.

b) supplementary service acknowledgement;

The supplementary service required is (is not) valid. The calling party is invited to enter data referring to additional supplementary services or to enter the message.

c) page accepted acknowledgement.

The message is (is not) valid. The call shall (shall not) be transmitted.

Procedures

provision;

This essential service shall be provided by all network operators.

- normal procedures.

The service shall apply to all calls. Restrictions due to the access method used are described in ETS 300 133 3 [2].

Network capabilities for charging

There shall be no charging for this service.

Interworking requirements

In the case of a roaming subscriber and/or if diversion of traffic outside home network is activated the PNC shall be informed on the status of transmission networks involved.

Draft prETS 300 133-2: April 1996

Interaction with other services

None.

4.3.1.1.2 Subscriber feature acknowledgement

Definition

The generation of an acknowledgement from the system to the fixed or mobile subscriber indicating whether or not a feature, such as a supplementary service control operation, has been successfully completed.

Procedures

provision:

This essential service shall be offered by all network operators for the subscriber features provided. An all feature reset facility should be provided.

normal procedures.

The service shall apply to all features accessible to the subscriber. Service to the fixed subscriber can only be provided in the subscribed network. Restrictions due to the access method used are described in ETS 300 133-3 [2].

Network capabilities for charging

There shall be no charging for this service.

Interworking requirements

In the case of a roaming subscriber and/or if diversion of traffic outside home network is activated, the PNC shall be informed if the service is offered by the transmitting network.

Interaction with other services

None.

4.3.1.2 Supplementary services related to the destination of the call

4.3.1.2.1 Roaming service

Definition

Roaming is the service which enables the mobile subscriber to choose, for a specific period, in which country(ies) and geographical area(s), outside his service area, he wants his calls transmitted. The subscriber can also roam within his home network. If the requested area is served by several operators the choice of network is according to inter-operator agreements, influenced by tariffs, supplementary services etc. The mobile subscriber shall have the possibility to define the duration of roaming.

Procedures

provision;

This essential service shall be provided by all network operators.

normal procedures.

The service shall be made available to the mobile subscriber on demand. Roaming shall be activated by the subscriber after authentication. Activation shall be for a specific period of time. It can be de-activated either automatically by the PNC when activation time has expired or by the subscriber (after authentication) before the activation time has expired. The service can be activated/de-activated through the home PNC or a visited

Draft prETS 300 133-2: April 1996

PNC. In the case that service area and roaming area are adjacent or overlapping the calls shall be transmitted in both areas. According to the network operator's policy the calls may also be transmitted to both areas even if they are not adjacent. A test call may automatically be generated by the system immediately after the start time of roaming, to confirm to the mobile subscriber that roaming has been activated successfully.

Network capabilities for charging

According to the policy of the network operator. Inter-operator charging for this feature shall be according to inter-operator agreements.

Interworking requirements

See subclauses 4.3.1.1.1 and 4.3.1.1.2.

Interaction with other services

When the subscriber is roaming to another network it shall be impossible to use priority 1 service. Level 3 priority and urgent message indication can only be activated if the visited networks offer these services. Activation of diversion of traffic or temporary barring shall suspend provision of the roaming service.

4.3.1.2.2 Diversion of traffic

Definition

The possibility of a mobile subscriber to have his calls diverted to another receiver registered in the same network, or in another network within the ERMES system, or to another telecommunication system for a period of time. Diversion can be made only to individual AdCs provided that the AdC is not already diverted. If the divert recipient wishes to activate diversion for his own AdC, he shall be warned that suspension of the already activated diversion of calls to his AdC shall occur. During this period the calls to the originally diverted AdC shall be rejected (ETS 300 133-3 [2], subclause 6.2).

Procedures

provision;

Provision of this service shall be optional for the network operators. Diversion outside home network can only be provided if there is an agreement between the network operators and/or the operators of other systems involved.

normal procedures.

The service should be made available to mobile subscribers on a registration basis or on demand, according to the network operator's policy. Diversion shall be activated by the subscriber after authentication. Activation shall be for a specific period of time. It can be de-activated either automatically by the PNC when activation time has expired or by the subscriber (after authentication) before the activation time expires.

Network capabilities for charging

According to the policy of the network operator.

In the case of diversion outside the home network, data regarding this feature shall be recorded in both PNCs. Inter-operator charging for this feature shall be according to inter-operator agreements.

Interworking requirements

None.

Interaction with other services

A check shall be made to avoid diversion to AdCs having lower categories of subscriptions. Only those supplementary services supported by the divert recipient's Home PNC (PNC-H) and the divert recipient's receiver can be provided during the period of diversion. The mobile subscriber can not activate any supplementary service, except temporary barring, after activation of diversion of traffic. Request for diversion to another AdC shall suspend the previous divert request. The supplementary services that the mobile subscriber has already activated shall be suspended.

Activation for a group using common RIC will affect the whole group. In the case of Closed User Groups (CUGs) it shall be possible to divert the call only within the CUG.

The diverted messages shall follow the message numbering of the divert recipient.

Calls shall be accepted and processed even if the divert recipient does not have all the supplementary services of the subscriber who has activated the service. The calling party shall not be informed that these supplementary services are not supported by the divert recipient.

4.3.1.2.3 Choice of destination

Definition

A service to give the calling party the possibility to choose the geographical areas that he wants the call to be transmitted in. The calling party has the following alternatives:

- transmission according to the mobile subscriber location register;
- transmission in one or more areas in addition to the location register.

Procedures

provision;

Provision of this service shall be optional for the network operators. Subject to the policy of the network operator, the service may have restrictions on the number of geographical areas.

normal procedures.

The service shall be provided to the calling party on a per call basis.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

When choice of destination is activated and transmission outside home network of the subscriber is requested, level 1 priority can not be used. Level 3 priority and urgent message indication can only be activated if they are provided in the requested geographical areas.

If the called mobile subscriber has activated diversion of calls this service can not be activated.

4.3.1.3 Supplementary services related to protection against loss of messages

The method used by the system to indicate the loss of a message to the receiver or the mobile subscriber is to allocate a number to each message before transmission. The system shall have one message counter (1 to 31) per

Draft prETS 300 133-2: April 1996

RIC. A message number (modulo 32) shall be allocated sequentially in increasing order from 1 to 31 to all messages.

The message number may be provided by the network operator.

The receiver shall have the capability to detect the message number and may take appropriate action (according to receiver specification).

If the message number is not provided with a paging message, the dummy value (00000) shall be used in the message header.

4.3.1.3.1 Repetition

Definition

The possibility of the calling party and/or the mobile subscriber to request automatic message repetition. The message shall be repeated once after a 5 minute interval. The repeated messages shall have the same message number (see message number control in the receivers).

Procedures

provision;

Provision of this service shall be optional for the network operators.

normal procedures.

The service should be available on a registration basis for the mobile subscribers and shall affect all messages addressed to them. The calling parties can activate the service on a per call basis. Only one repetition shall be activated if the service is requested from both mobile subscribers and calling parties.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

4.3.1.3.2 Message storing and retrieval

a) Message storing

Definition

Message storing enables the mobile subscriber to have all messages stored for a minimum of 24 hours after submission to the radio path. Together with the actual message, the message number and the date and time of submission to the radio path, or to another PNC, shall be stored.

Procedures

provision;

Provision of this service shall be optional for the network operators.

normal procedures.

The service should be made available to the mobile subscriber on a registration basis if required.

Network capabilities for charging

The mobile subscriber should be charged according to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

b) Message retrieval and retransmission

Definition

The message retrieval service offers the mobile subscriber the possibility to retrieve a message. The message shall be presented to the subscriber together with the message number and the stored date/time. Network operators shall provide for one or more of the following ways to present the retrieved message. The subscriber shall have the possibility to choose among the offered alternatives:

- retransmission via the radio path;
- displaying on a specified terminal.

The message retrieval procedure shall offer the possibility to retrieve several messages in one operation (by identifying lowest and highest message number or last received message number). This operation can be repeated several times.

Procedures

provision;

Provision of this service shall be optional for the network operators.

- normal procedures.

The service shall be activated by the mobile subscriber after authentication.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

4.3.1.3.3 Automatic retransmission of the last message number

Definition

This service offers the receiver the possibility to detect a loss of a message by comparing the received last message number with the stored number of the last correctly received message. Retransmission of the last message number is assumed to take place during low traffic time.

Procedures

provision;

Provision of this service shall be optional for the network operators.

normal procedures.

The service should be made available to the mobile subscriber on a registration basis if required.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

The service can only be activated when the message number is provided.

The service can not operate when one of the following services is activated:

- diversion of traffic;
- temporary barring of incoming traffic.

4.3.1.4 Bureau services

Definition

The service offered by a bureau which enables a request for a paging call or a subscriber feature initiated via the telephone system to be input by an operator to the paging system. The bureau cannot provide additional features, it can only enable those already subscribed.

Procedures

provision;

The service and terms of provision shall be optional for the network operators.

- normal procedures.

This service should be available to all users.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

When a calling party uses bureau services it cannot access recipients within a CUG.

4.3.2 Supplementary services related to priority

The priority function enables certain messages to be sent before or after other messages in a queueing situation. Three different levels of priority are described here.

4.3.2.1 Level 1 priority

Definition

Traffic having level 1 priority shall be sent on the radio path before traffic having lower priority. A level 1 priority message with a message length of less than 400 alphanumeric characters (2800 bits) shall be sent within one minute after page accepted acknowledgement is sent (see also subclause 6.2).

The service is intended mainly for short messages carrying alarm information or radiodistribution traffic consisting, for example, of particularly urgent news. The concept of radiodistribution services is defined in annex C.

Traffic having level 1 priority in the home network shall receive level 2 priority when routed to a visited network.

Procedures

- provision;

The service and the terms of provision shall be optional for the network operators. Subject to the policy of the network operator the use of the service may be linked to a restriction on the maximum message length.

normal procedures.

Level 1 priority shall be made available in one or more of the following ways:

- to all calling parties, activated on a per call basis;
- on registration to fixed subscribers, activated on a per call basis;
- on registration to the mobile subscriber, affecting all messages;
- on registration to the mobile subscriber, activated on a per call basis by the calling party.

Legitimisation may be required for the calling party.

Network capabilities for charging

The service should be charged on a subscription basis, on a per call basis, and/or based on the amount of traffic according to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

Priority 1 can not be activated when deferred delivery is activated. When roaming, choice of destination and diversion of traffic are activated outside home network, priority 1 can not be activated.

Draft prETS 300 133-2: April 1996

4.3.2.2 Level 2 priority

Definition

This service is intended for the standard calling party generated traffic of normal length and with moderate requirements on the message throughput. This throughput shall not be greater than the message delivery time of between 2,5 minutes and 10 minutes (see also subclause 6.2).

Traffic having level 2 priority shall be sent after sending traffic having level 1 priority and before sending traffic having level 3 priority.

Traffic having level 2 priority in its home network shall be guaranteed level 2 priority in a visited network.

Procedures

provision;

This essential service shall be provided by all network operators.

normal procedures.

Level 2 priority shall be the normal priority level unless Level 1 or 3 is indicated.

Network capabilities for charging

The service should be charged according to standard charging (subclause 4.3.4.1).

Interworking requirements

None.

Interaction with other services

None.

4.3.2.3 Level 3 priority

Definition

The service is intended for users sending information that is not time sensitive. Traffic having level 3 priority shall be handled in such a way that the quality of service limits for traffic of level 1 and level 2 priority are not degraded.

Procedures

- provision;

The service and terms of provision shall be optional for the network operators.

- normal procedures.

Level 3 priority shall be made available in one or more of the following ways:

- to all calling parties, activated on a per call basis;
- on registration to fixed subscribers, activated on a per call basis;
- on registration to the mobile subscriber, affecting all messages;
- on registration to the mobile subscriber, activated on a per call basis by the calling party.

Legitimisation may be required for the calling party.

Network capabilities for charging

A lower charge should be assumed for this service. It may not be possible for traffic having level 3 priority in the home network to be sent with the same priority in a visited network, thus the cost reduction need not be guaranteed.

Interworking requirements

None.

Interaction with other services

When roaming, choice of destination requiring transmission outside the home network or diversion of traffic outside the home network are activated, level 3 priority can be offered only if provided by the visited networks.

4.3.3 Community of interest supplementary services

4.3.3.1 Closed User Group

Definition

The possibility for a number of mobile subscribers and fixed subscribers to establish a group with only internal communication possibilities. The fixed subscribers within the group shall only be able to call mobile subscribers within the group. The mobile subscribers can receive calls only from the fixed subscribers in the group. A mobile or fixed subscriber can be a member in one or more CUG. In the CUG, one representative shall be appointed to be responsible for the management of the group.

Procedures

provision;

Provision of this service shall be optional for the network operators.

- normal procedures.

The service should be made available to mobile and fixed subscribers on a registration basis.

Network capabilities for charging

The mobile and fixed subscribers in the CUG should be charged for the subscription in addition to normal traffic charges according to the network operator's policy.

Interworking requirements

None.

Interaction with other services

See subclauses 4.3.1.2.2 and 4.3.1.4.

4.3.3.2 Group calls

A group call is a call intended for two or more mobile subscribers.

Group calls can be realised using one of the supplementary services specified in subclauses 4.3.3.2.1 and 4.3.3.2.2.

4.3.3.2.1 Group calls to mobile subscribers using common RIC

Definition

The means to send messages to a group of receivers having one RIC in common.

The common RIC may be in addition to an individual RIC, provided that it complies with the receiver specifications.

This type of group call service can be used as a means of providing radiodistribution services (annex C).

Procedures

provision;

This essential service shall be provided by all network operators. Terms of provision depend on network operator's policy.

normal procedures.

Only one subscription should be needed for the AdC.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

4.3.3.2.2 Group calls to mobile subscribers using individual RIC

Definitions

A call intended for a group of subscribers which do not have a common RIC. All individual RICs shall be able to receive calls of the same service category and may belong to different networks.

Group address code

Each group shall be given a GAdC with which the group is called.

Address list

The address list identifies a number of mobile subscribers, with individual AdCs and/or GAdCs, enabling them to receive the same calls. The address lists can be programmed by the network operator or by the fixed subscriber.

a) Address list programmed by the network operator

Procedures

provision;

Provision of this service shall be optional for the network operators. Subject to the policy of the network operator the service may be provided with a restriction on number of group members and/or message length.

normal procedures.

This service should be available on a registration basis to the mobile subscribers. The network operator shall be responsible for programming in the PNC.

One representative shall be appointed to be responsible for the management of the group.

Group calls may be placed by any calling party or may be restricted to fixed subscribers according to the network operator's policy. The call shall be processed even if some of the AdCs are not valid. The network operator may send an acknowledgement with all the non-valid AdCs.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

It shall be optional for the network operator to decide about combinations with other services, e.g. level 1 priority. Reverse charging shall only be applicable on the GAdC.

b) Address list programmed by the fixed subscriber

Procedures

provision;

The service and terms of provision shall be optional for the network operators. Subject to the policy of the network operator the service may have restrictions on the number of GAdCs and individual AdCs per address list and on the number of address lists allocated to a fixed subscriber.

normal procedures.

This service should be available on a registration basis to the fixed and mobile subscriber. A certain memory capacity for storing address lists shall be allocated to the subscribers. Within this memory capacity they are given the possibility of editing the address list.

Group calls may be placed by any calling party or may be restricted to fixed subscribers according to the network operator's policy. The call shall be processed even if some of the AdCs are not valid. The calling party shall receive an acknowledgement with all the non-valid AdCs.

Network capabilities for charging

According to the policy of the network operator.

The memory storage capacity can be charged for in addition to the normal charging of the service, according to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

It shall be optional for the network operator to decide about combinations with other services, e.g. level 1 priority. Reverse charging shall only be applicable on the GAdC.

4.3.3.3 Multi-address calls to mobile subscribers

Definition

The calling party may enter two or more individual AdCs, GAdCs, or any combination of these, per call. The mobile subscribers identified by the AdCs given shall receive the call.

Procedures

provision;

Provision of this service shall be optional for the network operators. Subject to the policy of the network operator, the service may have restrictions on the number of AdCs or GAdCs per call.

normal procedures.

The multi-address call service can be available to any calling party.

The calling party shall receive an acknowledgement with all the non-valid AdCs. In the case that some AdCs are not valid the calling party shall be given the possibility to abandon the call.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

It shall be optional for the network operator to decide about combinations with other services, e.g. level 1 priority. Reverse charging cannot be activated together with this service.

4.3.3.4 Called group indication

Definition

A mobile subscriber may belong to several groups. The called group indication informs the mobile subscriber which group was called by the calling party. The service can not be offered to pagers without a display.

- provision;

Provision of this service shall be optional for the network operators.

normal procedures.

The service shall be available to the subscriber responsible for the group. All members in the group shall receive the same indication. If called group indication is included in the mobile subscribers group registration or the fixed subscribers address list registration, the PNC shall forward the actual group indication to the receivers.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Draft prETS 300 133-2: April 1996

Interaction with other services

None.

4.3.3.5 Remote programming of RIC

Definition

The possibility for a network operator to program new RICs from a remote terminal via the radio path. The new RICs are additional to the basic RIC of the receiver. Receivers are addressed with the basic RIC. This service may be a means to establish group calls with common RICs to existing mobile subscribers.

Procedures

provision;

Provision of this service shall be optional for the network operators.

- normal procedures.

The facilities to implement this service shall be available only to the network operator.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

This service shall only be available in the home network.

Interaction with other services

None.

4.3.4 Charging supplementary services

4.3.4.1 Standard charging

Definition

Generation by the system of subscription and/or registration information to enable the following charging methods to be implemented, if required:

- mobile subscriber:
 - a) initial registration charges:
 - basic charge;
 - charges for supplementary services;
 - b) subscription charges:
 - basic charge;
 - charges for supplementary services;
 - c) traffic charges:
 - charges for use of supplementary services.

Draft prETS 300 133-2: April 1996

- calling party:
 - a) initial registration charges (fixed subscriber):
 - basic charge;
 - charges for supplementary services;
 - b) subscription charges (fixed subscriber):
 - basic charge;
 - charges for supplementary services;
 - c) traffic charges:
 - basic traffic charges;
 - charges for use of supplementary service.

Traffic registration may be on a toll-ticketing basis.

Procedures

provision:

Provision of this service shall be optional for the network operators. It shall also be optional for the network operators to have toll-ticketing registration.

Interworking requirements

Each network shall provide means for collecting traffic information for accounting purposes. Thus traffic information for accounting purposes can be exchanged between network operators.

Interaction with other services

None.

4.3.4.2 Reverse charging acceptance

Definition

This service enables the mobile subscriber to pay the charges of the calls he receives. Charges for the connection in the access network may be excluded.

Two variations should be provided:

- unconditional: all incoming calls are accepted;
- conditional: only incoming calls from calling parties who state a certain legitimisation code are accepted.

The network operator may offer other possibilities with regard to the restricted operation of this service.

Procedures

provision;

Provision of this service shall be optional for the network operators.

normal procedures.

The service should be made available to the mobile subscriber on a registration basis.

Network capabilities for charging

The call charge and the subscription charge should be paid by the mobile subscriber according to the network operator's policy.

Interworking requirements

None.

Interaction with other services

Reverse charging cannot be activated in the case of multi-address calls.

4.3.4.3 Charging information for fixed subscribers

Definition

The possibility of a fixed subscriber to obtain the accumulated charges of his account in the ERMES network.

Charging information provided to the fixed subscriber by this procedure shall be consistent with ordinary charging specification.

Procedures

provision;

Provision of this service shall be optional for the network operators.

normal procedures.

The service can be activated by the fixed subscriber.

Network capabilities for charging

The service should be charged according to the network operator's policy.

Interworking requirements

None.

Interaction with other services

None.

4.3.5 Supplementary services related to the restriction of calls

4.3.5.1 Temporary barring of incoming traffic

Definition

Allows a mobile subscriber to temporarily avoid receiving any call regardless of their origin.

The system shall inform the calling party that temporary barring is activated and it shall offer a facility to give suitable information, e.g. duration, to the calling party. This information may be a standard message stored in the system or a message programmed by the mobile subscriber. The mobile subscriber when asking for activation of

Draft prETS 300 133-2: April 1996

this service shall be informed if any deferred calls are waiting to be delivered to him. These calls shall be delivered after the de-activation of the temporary barring.

Procedures

provision;

Provision of this service shall be optional for the network operators. It shall be also optional to provide the possibility to mobile subscribers to give their own information.

normal procedures.

The service should be made available to mobile subscribers on a registration basis or on demand, according to the network operator's policy. It shall be activated by the subscriber after authentication. Activation shall be for a specific period of time. It can be de-activated either automatically by the PNC when activation time has expired or by the subscriber (after authentication) before the activation time has expired.

Network capabilities for charging

The service should be charged to the mobile subscriber on a subscription basis and/or based on use of the service according to the network operator policy.

Interworking requirements

None.

Interaction with other services

The system shall not accept any calls for AdCs that have this service activated. Messages received before the activation of this service can be retrieved. Activation of this service shall suspend all the supplementary services that the mobile subscriber has already activated.

4.3.5.2 Restriction on all calls

Definition

This subscriber feature enables the mobile subscriber to restrict the input of calls to authorised calling parties only. The use of a legitimisation code is expected.

Procedures

- provision;

Provision of this service shall be optional for the network operators.

normal procedures.

Service should be made available on a registration basis.

Network capabilities for charging

The service should be charged to the mobile subscriber according to the network operator policy.

Interworking requirements

None.

Interaction with other services

Limitations may occur with group calls using individual RICs and multi-address calls.

Draft prETS 300 133-2: April 1996

4.3.6 Other supplementary services

4.3.6.1 Urgent message indication

Definition

The service gives the calling party the possibility to activate an urgent message indicator in the receiver. The receiver shall indicate reception of a message having the urgent message indicator activated.

The service can be used on all RICs and AdCs.

Procedures

provision:

Provision of this service shall be optional for the network operators.

normal procedures.

The service may be available to all calling parties or to calling parties having the authority to use urgent message indication under the control of the mobile subscriber (e.g. legitimisation code, membership in a CUG).

Network capabilities for charging

According to policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

4.3.6.2 Deferred delivery

Definition

The possibility of a calling party or a mobile subscriber to instruct the PNC that any message being submitted should be delivered no sooner than a specified date and time. Delivery shall take place as close as possible to the specified date and time, but not before. The possibility to specify date and time for deferred delivery may be subject to limitations set by the network operator. If the mobile subscriber has activated the service he may choose to programme a message containing information about this activation. This message shall be sent to the calling party on a per call basis.

Procedures

provision;

Provision of this service shall be optional for the network operators.

normal procedures.

The service should be available to all calling parties and all mobile subscribers. Fixed and mobile subscribers can activate this service after authentication.

Network capabilities for charging

According to the policy of the network operator.

Draft prETS 300 133-2: April 1996

Interworking requirements

None.

Interaction with other services

When deferred delivery is activated, priority 1 service cannot be activated. If deferred delivery has been activated by the mobile subscriber, the calling party can activate it only if the deferred delivery time defined by the calling party exceeds that defined by the mobile subscriber.

4.3.6.3 Standard texts

4.3.6.3.1 Standard texts defined by the network operator

Definition

This service offers to a calling party the possibility to send a predefined text message simply by stating the identification number of the desired message. A message bank of this type is contained in the PNC. The texts are defined by the network operator. The purpose is to enable use of simple terminal equipment such as Dual Tone Multi-Frequency (DTMF) telephone for message entry.

Procedures

provision;

The service and terms of provision shall be optional for the network operators. The texts and number of messages that are available shall be determined by the operator. The standard texts provided to the calling party shall be those contained in the accessed PNC and the home PNC of the called mobile subscriber. The service shall only be applicable to the alphanumeric service.

normal procedures.

The service should be available to all calling parties. Simple means should be provided to enable calling parties to obtain accurate and up-to-date information on the content of the standard message bank.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

4.3.6.3.2 Standard texts defined by fixed subscribers

Definition

This service offers the same possibilities as under subclause 4.3.6.3.1 with the difference that the texts are defined by a fixed subscriber.

Procedures

provision;

The service and terms of provision shall be optional for the network operators. Subject to the policy of the network operator the service may have restrictions on maximum message length and on number of texts

allocated to a fixed subscriber. The service shall only be applicable to the transparent data and alphanumeric services

normal procedures.

The service should be available to calling parties defined by the fixed subscriber who controls the actual message bank. Access and use of the message bank can be controlled by a CUG membership, a legitimisation code or an equivalent arrangement.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

4.4. Security aspects

4.4.1 General

The security features are designed to protect the subscribers of the system from illegal activities which may either compromise the integrity of their communication (e.g. interception of communication, false calls, penetration into CUGs), or give rise to false traffic charges.

Authentication is a function which enables the PNC to ensure that the identity stated by a fixed or a mobile subscriber is true. Subscribers shall be authenticated each time they access the system in order to activate a supplementary service or a restricted operation. Authentication is used both in the interest of the network operator and the subscriber. Examples of the two cases are:

- to ensure that the correct subscriber is charged;
- to protect information from being retrieved by unauthorised persons.

Several authentication methods exist. Subclauses 4.4.4.1 to 4.4.4.3 list a number of options from which the subscriber can make a choice depending on the technical capabilities of his terminal equipment, his requirements on the strength of the authentication and the capabilities offered by the network operator.

Legitimisation is a function which ensures that a calling party trying to carry out a restricted operation (an operation which is not allowed to all calling parties) is authorised to do this.

Legitimisation differs from authentication in that it refers to calling parties that are not necessarily identified, but they merely prove their right to carry out the restricted operation, for instance by stating a secret code. This code can be known by several other calling parties which are also authorised (by the subscriber) to carry out the restricted operation. The PNC need not know which calling parties are in possession of the secret code. The secret code is only linked to the restricted operation.

Legitimisation is in most cases used in the interest of the subscriber. An example of a restricted operation suitable for protection by legitimisation is the transmission of messages to a mobile subscriber who needs to be protected from malicious calls.

4.4.2 Encryption of messages

Definition

Encryption of messages is the possibility to have the message encrypted by the network and transmitted via the transparent data paging facility.

Procedures

provision;

The facility shall be optional for the network operators. Implementation of the feature in receivers shall be optional. Manufacturers shall have to follow the decisions of the network operators.

normal procedures.

Encryption shall be made available on a registration basis.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

Some restrictions in connection with group call messages may arise if the receivers have different facilities.

4.4.3 Legitimisation code

Definition

The legitimisation code is stated by the calling party to prove that he is authorised to carry out a particular restricted operation.

A legitimisation code may be known by several calling parties and should not be confused with the password (subclause 4.4.4.1) which is used for secure identification of a subscriber. In contrast to the password the legitimisation code is linked to the restricted operation and not to the subscriber.

Procedures

provision;

This essential facility shall be provided by all network operators who provide services that need such legitimisation code. A facility shall be provided to enable the subscriber to change the legitimisation code using any appropriate access method defined by the network operator.

The following supplementary services may be activated with the use of a legitimisation code:

- level 1 and level 3 priority available on a registration basis to the mobile subscribers and activated on a per call basis by the calling party;
- reverse charging acceptance conditional;
- standard texts defined by the fixed subscriber;
- urgent message indication when controlled by the mobile subscriber.
- normal procedures:

The calling parties asking for a restricted operation shall state the relevant legitimisation code. Changes of a legitimisation code can be initiated by the subscriber who controls the restricted operation.

Network capabilities for charging

According to the policy of the network operator.

Draft prETS 300 133-2: April 1996

Interworking requirements

None.

Interaction with other services

None.

4.4.4 Authentication

4.4.4.1 Authentication by use of passwords

Definition

The authenticity of the subscriber is ensured by requesting a password known only by the correct, registered subscriber. This password can be changed any time by the registered subscriber.

Procedures

provision;

This essential facility shall be provided by all network operators who provide services that need authentication. A facility shall be provided to enable the subscriber to change the password using any appropriate access method defined by the network operator.

normal procedures.

This facility shall be provided to all fixed and mobile subscribers.

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

4.4.4.2 Authentication by reverse calling

Definition

The authenticity of the subscriber accessing the network is ensured by disconnecting the call immediately after identification of the subscriber and setting up a new call in the reverse direction for completion of the transaction. The security of this method is based on the assumption that the subscriber always accesses the PNC from the same, physically protected terminal (in the subscriber's judgement), the address of which needs to be known by the PNC.

Procedures

provision;

Provision of this facility shall be optional for the network operators.

normal procedures.

This facility should be provided to the subscriber on a registration basis if required.

Draft prETS 300 133-2: April 1996

Network capabilities for charging

According to the policy of the network operator.

Interworking requirements

None.

Interaction with other services

None.

4.4.4.3 Authentication by use of certificate

Definition

The authenticity of the subscriber accessing the network is ensured by the subscriber sending a certificate together with the claimed identity, e.g. by using a smart card.

Procedures

provision;

Provision of this facility shall be optional for the network operators.

- normal procedures.

This service should be provided to the subscriber on a registration basis if required. The terminal used by the subscriber shall have facilities for generation of the certificate.

Network capabilities for charging

According to the network operator's policy.

Interworking requirements

None.

Interaction with other services

None.

4.5 Subscriber directory

Definition

The facility offering public access to a hard copy catalogue or a database containing information about subscribers. The directory shall be controlled by the network operator and should contain information such as subscriber number, name, address, country and paging category for all subscribers, except those who may explicitly demand to be excluded.

Tone-only subscribers shall not be included in the subscriber directory.

Information in the directory should be a subset of the subscriber register and may also include additional information.

Procedures

provision;

The facility and the terms of provision shall be optional for the network operators.

normal procedures.

The subscriber directory should be implemented off line and may be accessed through the PNC.

The method of access to the facility shall be determined by the network operator. The subscriber directory can only be changed by the network operator.

Network capabilities for charging

The facility should be charged according to the network operator's policy.

Interworking requirements

None.

Interaction with other services

None.

5 Receiver features

5.1 Introduction

This clause describes the features that should be considered for implementation in the ERMES receivers and classifies them according to their type. Three types of features are considered:

- basic features, which are directly related to the basic services;
- supplementary features, which are directly related to the supplementary services;
- additional features, which are neither basic nor supplementary.

A complete definition and description of the receiver features is given in ETS 300 133-5 [3].

References are given to the relevant services defined in clause 4. Table D.1 divides the essential and optional receiver features.

5.2 Basic receiver features

5.2.1 Tone-only

The tone-only feature enables the receiver to receive paging signals without any additional information (numeric, alphanumeric or data) and generate the appropriate alert signal (subclause 4.2.1).

5.2.2 Numeric

The numeric feature enables the receiver to receive paging signals with numeric additional information consisting of up to at least 20 characters and generate the appropriate alert signal (subclause 4.2.2). The numeric character set is given in table B.1.

5.2.3 Alphanumeric

The alphanumeric feature enables the receiver to receive paging signals with additional text information consisting of up to at least 400 alphanumeric characters and generate the appropriate alert signal (subclause 4.2.3). The basic alphanumeric character set is given in table B.3.

As an optional feature, the pager may also use any additional character sets, as defined in annex B.

5.2.4 Transparent data

The transparent data feature enables the receiver to receive paging signals with additional information in the form of an arbitrary data stream (subclause 4.2.4).

5.2.5 Alert signals

This feature offers the capability of transmission of up to 8 different alert signal indicators per RIC. Each alert signal indicator corresponds to a different AdC.

5.2.6 Access to the message

All receivers may have a feature (e.g. display, printer or synthesised voice) that enables the user to access the received messages and/or other information.

5.3 Supplementary receiver features

5.3.1 Repeated call indication

A message may be transmitted more than once. In such a case the message shall have the same message number. The repeated call indication feature enables the receiver to detect duplicated messages and indicate to the mobile subscriber accordingly (subclause 4.3.1.3.1).

5.3.2 Indication of lost message/message number control

The purpose of this indication is to inform the mobile subscriber that a message has been lost. This gives the mobile subscriber the possibility to retrieve lost messages (subclause 4.3.1.3).

5.3.3 Remote programming of RIC

The receivers may have the capability to be remotely programmed by the network operator for the additional RIC(s) via the radio path.

The purpose is to establish groups of receivers with common RIC remotely (subclause 4.3.3.5).

5.3.4 Out of range indication

The purpose of this feature is to give the user an indication if the receiver is not able to receive the paging signal.

5.3.5 Urgent message indicator

This feature enables the receiver to indicate that an urgent message has been received when it detects the urgent message indicator in the message header (subclause 4.3.6.1).

5.4 Additional receiver features

5.4.1 Silent mode

The audible alert receiver shall have a switch by which the alert tone can be set to silent mode. The receiver shall still receive and store paging calls.

5.4.2 Low battery indication

All types of receivers shall give a low battery indication before the receiver performance is significantly impaired.

5.4.3 Message storage and retrieval

All types of receivers shall have a memory, which at minimum can support the Basic Version Receiver (BVR) requirements. Additionally they may have more memory space to store the messages they receive. In this case the messages can be retrieved at a later time by the mobile subscriber.

5.4.4 Memory full

If the receiver memory is full, the oldest message not being protected against deleting shall be erased, to enable the receiver to continue receiving new messages.

5.4.5 Message manipulation

Receivers can have some features for message manipulation and reading.

5.4.6 Display

Receivers may have a display where the message(s) and/or other useful information can be displayed.

5.4.7 Printer interface

A facility to connect a printing device to the receiver (except tone-only) may be available. The purpose is:

- to enable the user to have a print out of the stored messages;
- to have messages printed automatically after reception.

The user should have the choice of printing all messages in memory or selecting single messages for printing.

5.4.8 Data interface

Receivers may have a data interface giving the possibility for connection to other equipment for transfer of the received data and/or the alert signal.

5.4.9 Date/time indication

Receivers may be able to generate date/time information which may be stored together with the received message. The possibility can be given to the mobile subscriber to have this information shown on the display on request.

5.4.10 Encryption of messages

Encryption of messages may be performed by the PNC-H on forwarding the message. The receivers (except tone-only), may have the capability to decipher encrypted messages.

6 Quality of service

6.1 General

In the following subclause the parameters that affect the quality of service and the limits that shall apply to these parameters are defined. The values of several of these parameters depend also on the performance of the access network used. The values that are specified in this subclause relate only to time limits and performance in the ERMES network and ERMES PNC without taking into account the influence of the access network. Except otherwise noted in this clause all limits specified are based on the performance measured at the busy hour over a one hour period such that the limit is met on 90 % or more occasions. Any contributions from an access network shall be added to the relevant ERMES network values to obtain the "real" values perceived by the user.

6.2 Quality of service parameters

6.2.1 System response delay

The system response delay is the delay experienced by the calling party when waiting for a response from the PNC. This delay is valid only for the interactive access mode and the same value shall apply for both page input and subscriber features.

The system response delay shall be less than two seconds.

6.2.2 Input blocking probability (input grade of service)

The input blocking probability is the probability that a paging network can not accept a call request.

The blocking event can be caused either by a lack of incoming channels from the access network to the paging network, or by an overload in the Input PNC (PNC-I) or other parts of the paging network.

This parameter is only related with two-stage selection access type. The same value shall apply for both page input and subscriber features. This applies to both interactive and automatic access mode.

The input blocking probability shall be less than 3 %

6.2.3 Call accepted acknowledgement delay

The call accepted acknowledgement delay is the time elapsing between the sending instant of the AdC to the PNC and the reception of the call accepted (or not accepted) Acknowledgement (ACK).

This parameter is the sum of the transmission time of an AdC message to the PNC-H, its validation and checking and the time for receiving back (at PNC-I) the instruction reply message. This shall apply to both interactive and automatic access mode.

When PNC-I is the PNC-H the call accepted acknowledgement delay shall be less than 2 seconds.

When PNC-I is not the PNC-H the call accepted acknowledgement delay shall be less than 6 seconds.

6.2.4 Page accepted acknowledgement delay

The page accepted acknowledgement delay is the time elapsing between the sending instant of the End of Message (EOM) characters and the reception of a page accepted (or not accepted) ACK.

The page accepted acknowledgement delay shall be less than the following limits:

- interactive mode: 2 seconds:

NOTE: It is assumed that all information of the subscription is available in PNC-I.

automatic mode:

when PNC-I is the PNC-H 3 seconds;

when PNC-I is not the PNC-H 7 seconds.

6.2.5 Subscriber feature acknowledgement delay

The subscriber feature acknowledgement delay is the time elapsing between the sending instant of the EOM characters and the reception of a subscriber feature accepted (or not accepted) ACK.

The subscriber feature acknowledgement delay shall be less than the following limits:

- interactive mode: 2 seconds;

NOTE: It is assumed that all information of the subscription is available in PNC-I.

automatic mode:

- when PNC-I is the PNC-H 3 seconds;

- when PNC-I is not the PNC-H 7 seconds.

6.2.6 Message delivery time

The message delivery time is the time elapsing between the page accepted ACK message sent to the calling party and the complete transmission of the paging call within the required paging area (or paging areas).

This is a basic quality of service parameter even if not directly perceived by the paging user. Its value depends on transmission times, processing delays and database access and searching times.

The message delivery time shall be less than the following limits:

- priority 1: < 1 minute;

NOTE 1: this is only relevant within home network and for message lengths less than 400 alphanumeric characters (2 800 bits).

priority 2:

PNC-I = PNC-H = PNC-T 2,5 minutes;

- PNC-I ≠ PNC-H = PNC-T 7 minutes;

- PNC-I = PNC-H ≠ PNC-T 7 minutes;

- PNC-I ≠ PNC-H ≠ PNC-T 10 minutes;

- priority 3: 24 hours.

NOTE 2: PNC-T = Transmitting PNC.

6.2.7 Call success rate

The call success rate is the number of successful calls divided by the number of transmitted calls for one receiver. This parameter refers to the quality of service at the boundary of a coverage area.

A tone-only call is considered to be successful if the addressed receiver is able to generate the appropriate alert signal.

A numeric call is considered to be successful if the addressed receiver is able to display a complete message of up to 20 characters (and nothing else) containing no errors. For numeric messages longer than 20 characters the definition of successful calls for alphanumeric calls shall apply.

An alphanumeric call is considered to be successful if the addressed receiver is able to display the complete message that has been sent without extra characters and if the improperly displayed characters do not exceed the 5 % of the total number of characters in the actual message. The average number of characters which may be in error shall not exceed 1 %.

The call success rate shall be greater than 95 %

Page 42

Draft prETS 300 133-2: April 1996

6.2.8 False call rate

A call is considered to be false if it is received by a pager with an AdC different to that transmitted, or if a message or part of a message is received by a pager other than that for which it was intended.

There shall be les than one false call per pager per year.

6.2.9 Correct message transmitted probability

The correct message transmitted probability is the probability that a message, regularly accepted by the ERMES network is correctly transmitted.

The correct message transmitted probability shall be greater than 99,9 % (i.e. 1 of 1000 may be lost or corrupted within the ERMES network).

Essential and optional supplementary services Annex A (normative):

In table A.1 a summary of the essential and optional supplementary services and facilities for each basic service is given.

In table A.2 a summary of access authority to services and facilities for different categories of users is given.

Table A.1: Essential and optional supplementary services and facilities

	Tone only	Numeric	Alpha numeric	Transparent data
Valid input acknowledgement	E	Е	E	E
Subscriber feature acknowledge.	Ē	Ē	Ē	Ē
Roaming	E E	E	Ē	E
Diversion of traffic	0	0	0	0
Choice of destination	0	Ō	Ō	Ö
Message number	E	E	Ē	Ē
Repetition	0	0	0	0
Message storing - retrieval		0	0	0
Aut.retrans.last message No.	0	0	0	0
Bureau services	0	0	0	
Priority 1	0	0	0	0
Priority 2	E	Е	E	E
Priority 3	0	0	0	0
Closed user group	0	0	0	0
Group calls/common RIC	E	E	E	E
Group calls/individual RIC	0	0	0	0
Multi-address calls	0	0	0	0
Called group indication		0	0	0
Remote programming of RIC	0	0	0	0
Standard charging	0	0	0	0
Reverse charging acceptance	0	0	0	0
Charging information	0	0	0	0
Temporary barring	0	0	0	0
Urgent message indication	0	0	0	0
Deferred delivery			0	0
Standard texts		_	0	0
Encryption	_	O	O	O
Authentication by password	E	E	E	E
Authentication by reverse call	0	0	0	0
Authentication by certificate	0	Ō	0	ō
Legitimisation	E	E	E	E
Subscriber directory NOTE: E: indicates that the ser	1	0	0	0

O: indicates that the service is optional.

Table A.2: Summary of access authority to services and facilities for different categories of users

Service or facility	Calling party	Mobile	Fixed
Convide on radinary	ounning party	subscriber.	subscriber.
Tone-only paging	*	-	*H
Numeric paging	*	-	*H
Alphanumeric paging	*	_	*H
Transparent data paging	*	_	*H
Valid input acknowledgement	*	_	*H
Subscriber feature ACK.	_	*H	*H
Roaming	_	*	_
Diversion of traffic	_	*H	_
Choice of destination	*	-	*H
Repetition	*	*H	*H
Message storing and retrieval	_	*H	-
Automatic retransmission			
of last message number	_	*H	_
Bureau services	*	*H	*H
Priority 1	*	*H	*H
Priority 2	*	-	*H
Priority 3	*	*H	*H
Closed user group	_	*H	*H
Group calls/common RIC	*	_	*H
Group calls/individual RIC	*	_	*H
Multi-address calls	*	_	*H
Called group indication	_	*H	*H
Standard charging	*	*H	*H
Reverse charging acceptance	_	*H	-
Reverse charging call	*		*H
Charging information	-	-	*H
Temporary barring of incoming			
traffic	_	*H	_
Restriction on all calls	_	*H	_
Urgent message indication	*	-	*H
Deferred delivery	*	*H	*H
Standard texts defined by			
the network operator	*	-	*H
Standard texts defined by			
the fixed subscriber	*	-	*H
Encryption	-	*H	-
Authentication by passwords	-	*H	*H
Authentication by reverse call	-	*H	*H
Authentication by certificate	-	*H	*H
Legitimisation	*	-	-
Subscriber directory	*	*H	*H
All features reset	-	*H	-

NOTE:

- *: indicates that the service can be accessed;
- -: indicates that the service cannot be accessed;
- H: indicates that the service can only be accessed via the home PNC.

Annex B (normative): Character sets in the ERMES system

B.1 Characters for numeric paging

Numerical messages are coded with 4 bits per character. A numeric or alphanumeric receiver shall be capable of presenting the characters of table B.1.

Table B.1

b4	b3	b2	b1	Character	
0	0	0	0	0	
0	0	0	1	1	
0	0	1	0	2	
0	0	1	1	3	
0	1	0	0	4	
0	1	0	1	5	
0	1	1	0	6	
0	1	1	1	7	
1	0	0	0	8	
1	0	0	1	9	
1	0	1	0	/	
1	0	1	1	(space)	
1	1	0	0	U	
1	1	0	1	- (hyphen)	
1	1	1	0	.(full stop)	
1	1	1	1	%	

NOTE:

The characters of this set, when displayed, should approximate to the appearance of the relevant characters specified in ISO standard 1073. For a simple seven segment display the symbols "/", "." and "%" should be represented in the following way:

Table B.2

b4	b3	b2	b1	Character	Representatio n		
1	0	1	0	/			
1	1	1	0	.(full stop)	I		
1	1	1	1	%	P		
NOTE: Better representations of these characters may be used.							

B.2 Characters for alphanumeric paging

Alphanumeric characters shall be coded with 7 bits per character.

All alphanumeric receivers shall use the character set in table B.3.

Table B.3: The ERMES character set for alphanumeric paging (character set indicator 00000)

				b7	0	0	0	0	1	1	1	1
				b6	0	0	1	1	0	0	1	1
				b5	0	1	0	1	0	1	0	1
b4	b3	b2	b1		0	1	2	3	4	5	6	7
0	0	0	0	0	@	Δ	SP	0	i	Р	j	р
0	0	0	1	1	£	DC1	!	1	Α	Q	а	q
0	0	1	0	2	\$	Φ	"	2	В	R	b	r
0	0	1	1	3	¥	Γ	#	3	С	S	С	S
0	1	0	0	4	è	Λ	¤	4	D	T	d	t
0	1	0	1	5	é	Ω	%	5	Е	U	е	u
0	1	1	0	6	ù	П	&	6	F	V	f	V
0	1	1	1	7	ì	Ψ	1	7	G	W	g	W
1	0	0	0	8	Ò	Σ	(8	Н	Х	h	Х
1	0	0	1	9	Ç	θ)	9	I	Υ	i	У
1	0	1	0	10	LF	Ξ	*	:	J	Z	j	Z
1	0	1	1	11	Ø	ESC	+	,	K	Ä	k	ä
1	1	0	0	12	Ø	Æ	,	<	L	Ö	I	Ö
1	1	0	1	13	CR	æ	ı	=	М	Ž	m	ñ
1	1	1	0	14	Å	ß		>	N	Ü	n	ü
1	1	1	1	15	å	É	/	?	0	Ø	0	à

NOTE 1: DC1 shall be used only as the End Of Message (EOM) character.

NOTE 2: The characters of this set, when displayed, should approximate to the appearance of the relevant characters specified in ISO 1073 [4] and the corresponding national standards.

Table B.4: Optional character set for alphanumeric paging (character set indicator 00001)

				b7	0	0	0	0	1	1	1	1
				b6	0	0	1	1	0	0	1	1
				b5	0	1	0	1	0	1	0	1
b4	b3	b2	b1		0	1	2	3	4	5	6	7
0	0	0	0	0	@	Δ	SP	0	i	Р	j	р
0	0	0	1	1	£	DC1	!	1	Α	Q	а	q
0	0	1	0	2	\$	Ф	"	2	В	R	b	r
0	0	1	1	3	¥	Ğ	#	3	С	S	С	S
0	1	0	0	4	è	ğ	¤	4	D	Т	d	t
0	1	0	1	5	é	Ş	%	5	Е	U	е	u
0	1	1	0	6	ù	ə	&	6	F	V	f	V
0	1	1	1	7	I	Ì	'	7	G	W	g	W
1	0	0	0	8	Ò	X	(8	Η	Х	h	Х
1	0	0	1	9	Ç	ç)	9		Υ	i	у
1	0	1	0	10	LF	Ş	*	:	J	Z	j	Z
1	0	1	1	11	Ø	ESC	+	;	K	Ä	k	ä
1	1	0	0	12	X	Æ	,	٧	L	Ö	ı	Ö
1	1	0	1	13	CR	æ	-	=	М	Ñ	m	ñ
1	1	1	0	14	Å	ß		^	N	Ü	n	ü
1	1	1	1	15	å	É	/	?	0	§	0	à

NOTE 1: DC1 shall be used only as the End Of Message (EOM) character.

NOTE 2: The characters of this set, when displayed, should approximate to the appearance of the relevant characters specified in ISO 1073 [4] and the corresponding national standards.

Table B.5: Optional character set for alphanumeric paging (character set indicator 00010)

				b7	0	0	0	0	1	1	1	1
				b6	0	0	1	1	0	0	1	1
				b5	0	1	0	1	0	1	0	1
b4	b3	b2	b1		0	1	2	3	4	5	6	7
0	0	0	0	0	@	Δ	SP	0	i	Р	j	р
0	0	0	1	1	£	DC1	!	1	Α	Q	а	q
0	0	1	0	2	\$	Á	"	2	В	R	b	r
0	0	1	1	3	ð	á	#	3	С	S	С	S
0	1	0	0	4	è	ĺ	¤	4	D	Т	d	t
0	1	0	1	5	é	ĺ	%	5	Е	U	е	u
0	1	1	0	6	ù	Ó	&	6	F	V	f	٧
0	1	1	1	7	ì	ó	'	7	G	W	g	W
1	0	0	0	8	Ò	Þ	(8	Н	Х	h	Х
1	0	0	1	9	Ç	þ)	9	ı	Υ	i	у
1	0	1	0	10	LF	Ð	*	:	J	Z	j	Z
1	0	1	1	11	Ý	ESC	+		K	Ä	k	ä
1	1	0	0	12	ý	Æ	,	<	L	Ö	I	Ö
1	1	0	1	13	CR	æ	-	=	М	Ñ	m	ñ
1	1	1	0	14	Å	ß		>	N	Ú	n	ú
1	1	1	1	15	å	É	/	?	0	§	0	à

NOTE 1: DC1 shall be used only as the End Of Message (EOM) character.

NOTE 2: The characters of this set, when displayed, should approximate to the appearance of the relevant characters specified in ISO 1073 [4] and the corresponding national standards.

Table B.6: Optional character set for alphanumeric paging (character set indicator 00011)

			b7	0	0	0	0	1	1	1	1
			b6	0	0	1	1	0	0	1	1
			b5	0	1	0	1	0	1	0	1
b3	b2	b1		0	1	2	3	4	5	6	7
0	0	0	0	@	Δ	SP	0	i	Р	خ	р
0	0	1	1	£	DC1	!	1	Α	Q	а	q
0	1	0	2	\$	À	"	2	В	R	b	r
0	1	1	3	ü	á	#	3	С	S	С	S
1	0	0	4	è	ĺ	¤	4	D	Т	d	t
1	0	1	5	é	ĺ	%	5	Е	U	е	u
1	1	0	6	ù	Ó	&	6	F	V	f	٧
1	1	1	7	I	ó	'	7	G	W	g	W
0	0	0	8	Ò	ő	(8	Н	Χ	h	Х
0	0	1	9	ç)	9	I	Υ	i	у
0	1	0	10	LF	Ü	*	:	J	Z	j	Z
0	1	1	11	Ű	ESC	+	,	K		k	ä
1	0	0	12	Ű	Æ	,	<	L	Ö	I	Ö
1	0	1	13	CR	æ	_	=	М	Ñ	m	ñ
1	1	0	14	Å	ß		^	N	Ú	n	ú
1	1	1	15	-a		/	?	0	§	0	à
	0 0 0 1 1 1 1 0 0 0	0 0 0 0 0 0 1 1 0 1 1 0 0 0 0 1 1 0 1 1 1 0 1 1 1 1 0 1	0 0 0 0 0 1 0 1 1 0 1 0 1 1 1 1 0 0 0 0 0 1 0 1 1 0 0 1 1 0 1 0 1 1 1 1 1 1 1 1 1 1	b3 b2 b1 0 0 0 0 0 0 1 1 0 1 0 2 0 1 1 3 1 0 0 4 1 0 1 5 1 1 0 6 1 1 1 7 0 0 0 8 0 0 1 9 0 1 0 10 0 1 1 11 1 0 1 13 1 0 1 13 1 1 0 14 1 1 1 15	b6 0 b3 b2 b1 0 0 0 0 @ 0 0 0 @ 0 0 1 1 £ 0 1 0 2 \$ 0 1 1 3 ü 1 0 0 4 è 1 0 0 4 è 1 1 0 6 ù 1 1 0 6 ù 1 1 1 7 1 0 0 0 8 ò 0 0 1 9 ç 0 1 1 1 1 1 0 1 1 1 1 0 1 1 1 1 1 1 0 1 1 1 1 1 0 <td> b6</td> <td> b6 0 0 1 0 b5 0 1 0 0 0 0 0 0 0 0</td> <td> b6 0 0 1 1 1 b5 0 1 0 1 1 1 b5 0 1 0 1 1 1 1 1 1 1</td> <td> b6</td> <td> b6 0 0 1 1 0 0 1 b3 b2 b1 0 1 2 3 4 5 5 0 0 0 0 0 0 0 0</td> <td>$\begin{array}{c ccccccccccccccccccccccccccccccccccc$</td>	b6	b6 0 0 1 0 b5 0 1 0 0 0 0 0 0 0 0	b6 0 0 1 1 1 b5 0 1 0 1 1 1 b5 0 1 0 1 1 1 1 1 1 1	b6	b6 0 0 1 1 0 0 1 b3 b2 b1 0 1 2 3 4 5 5 0 0 0 0 0 0 0 0	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$

NOTE 1: DC1 shall be used only as the End Of Message (EOM) character.

NOTE 2: The characters of this set, when displayed, should approximate to the appearance of the relevant characters specified in ISO 1073 [4] and the corresponding national standards.

B.2.1 Optional character set for Chinese Characters

Each of the pictograms and characters in this character set are to be represented as a sequence of two 7-bit information units. Each of these information units shall be considered as representing an alphanumeric character and all rules and techniques associated with alphanumeric characters shall be followed.

Supported Chinese pictograms are in the attached Chinese character set GB 2312-80. This standard contains 87 tables of characters indexed from 1 to 87. The table index is printed in bold face type in the uppermost left corner of each table. Each character in the table is referenced by a character index from 1 to 94.

Each pictogram or character is represented by a sequence of two 7 bit information units. The first information unit is generated from the addition of the table index and decimal 32. The second information unit is generated by the addition of the character index and decimal 32. For example, the \$ symbol is contained in the table number 1 as character index 71. It will therefore be represented by the information units with decimal value 33 and 103, or in hexadecimal format \$21 and \$67.

Table B.7: Optional character set for Chinese Characters (character set indicator 10000)

```
1区
                                                  15
                                                           18
                                                              19
      01
         02
                     06
                            08
                               09
                                  10
                                     11
                                        12
                                            13
                                                     16
            03
               04
                  05
01
                                                            ( )
     (SP)
19
20
                            \pm
          (( )
                         j
                                           X
39
                        \angle \cap \odot \int A \equiv \cong \approx \emptyset \propto \neq 4 \Rightarrow
                  \perp \parallel
                                  °C $ ○ ¢ £ % § № ☆ ★
                  ♦
                  01 02 03 04 05 06 07 08 09 10 11 12 13 14
                                                 15 16 17
01
                                                        1. 2. 3.
19
20
   4. 5. 6. 7. 8. 9. 10.11.12.13.14.15.16.17.18.19.20.(1) (2) (3)
39
   (4) (5) (6) (7) (8) (9) (10) (11) (12) (13) (14) (15) (16) (17) (18) (19) (20) ① ② ③
59
   ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ (一) (二) (三) (四) (五) (七) (九) (十)
80
         II III IV V VI VII VII IX X XI XII
94
3区
      01
                               09
                                     11
                         07
                            80
                                  10
                                        12 13 14
01
               Y % & '
       1
                             ( )
                                  * + ,
                                                         1
                                                           2
                                                     0
19
20
                8 9 : ; < = > ? @ A B C D E F G
         6
          J K L M N O P Q R S T U V W X Y Z
≀
59
                     bcdefghijklmno
79
80
    pqr
                t u
                      v w x y z
```

continued

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

continued

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

```
17
                                   15
                                     16
                                14
7区
                      09
                        10
                          11
                            12
                               13
                 07
                    80
             05
               06
    а Б В Г Д Е Ё Ж З И Й К Л М Н О П Р C
01
19
  туфхцчшщъыьэюя
39
40
                      абвгде ё ж з
                                          И Й
59
    лмнопрстуфхичшшъ
                                            Э
80
}
  к о
                                      16
                                            19
8区
                      09
                        10
                             12
                               13
                                 14
                                   15
               06
                  07
                    08
             05
         03
           04
01
                                             ŭ
                             ì
                               ō
                                 6
                                   Ŏ
                                      Ò
                                        ū
                  ě
                      Ĭ
                         ĺ
                           ľ
                    è
                é
     ā
       á
         ă
           à
             ē
19
20
                                        5 タロ
    ü
       û
         ŭ
           Ù
             ü
                е
  ù
39
  こ 力 去 ろ 为 以 万 厂 山 く 丁 业 彳 戸 日 ア 方 ム 丫 さ
40
59
  させあて幺ヌ马与九ムルーメム
80
94
                                      16 17
     01 02 03 04 05 06 07 08 09 10 11 12 13 14
                                    15
01
                  --- ---
                           ----
19
   ┐┑┒┑ └ ┕ ┖ ┗┘┙┘┙ ├ ┝ ┞ ┟ ┡ ┢ ┢
   79
 80
 94
                     continued
```

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

17区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 19 01 薄雹保堡饱宝抱报暴豹鲍爆杯碑悲卑北辈背见钡倍狈备惫焙被奔苯本笨崩绷甭泵蹦进逼鼻 比鄙笔彼碧蓖蔽毕毙毖币庇痹闭敝弊必辟壁臀 遊晚 鏡 编贬扁便变 卞辨辩 遍标 態 聽表 憋 腳 穆兴 别瘪彬斌濒滨宾摈兵冰柄丙秉饼炳

21区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 01 20 20 20 20 20 20 39 第 20 20 39 2

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

H

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

28区 15 12 13 05 01 02 03 04 01 肌饥迹激讥鸡姬绩缉吉极棘辑籍集及急疾汲 19 即嫉级挤几脊己蓟技冀季伎祭剂悸济寄寂计记 既忌际妓继纪嘉枷夹佳家加荚颊贾甲钾假稼价 40 架驾嫁歼监坚尖笺间煎兼肩艰奸缄茧检柬碱硷 拣捡简俭剪减荐槛鉴践贱见键箭件

29区 12 13 14 15 09 10 11 02 03 06 04 05 01 健舰剑饯渐溅涧建僵姜将浆江疆蒋桨奖讲匠 19 **酱降蕉椒礁焦胶交郊浇骄娇嚼搅铰矫侥脚狡角** 饺缴绞剿教酵轿较叫窖揭接皆秸街阶截劫节桔 杰捷睫竭洁结解姐戒藉芥界借介疥诫届巾筋斤 金今津襟紧锦仅谨进靳晋禁近烬浸

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

35区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 01 20 漫芒注盲氓忙莽猫茅锚毛矛铆卯茂冒帽貌贸 20 公 枚梅酶霉煤没眉媒镁每美昧寐妹媚门闷们 40 men 蒙檬盟锰猛梦孟眯醚靡糜迷谜弥米秘觅泌蜜 60 容幂棉眠绵冕免勉娩缅面苗描额秒渺庙妙蔑 80 灭民抿血敏悯闽明螟鸣铭名命谬摸

38区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 四 牌 疲皮 匹 痞 僻 尼 譬 篇 偏 片 骗 漂 漂 澌 幣 瞥 即 疲 皮 匹 痞 僻 尼 譬 篇 偏 片 骗 漂 漂 澌 幣 瞥 節 頻 贫 品 聘 乒 坪 苹 萍 平 凭 瓶 评 屏 坡 泼 颇 婆 破 魄 和 韵 扑 铺 仆 莆 葡 菩 蒲 埔 朴 圃 普 浦 谱 曝 瀑 期 欺 Q 60 ~79 栖 戚 妻 七 凄 漆 柒 沏 其 棋 奇 歧 畦 崎 脐 齐 旗 祈 祁 骑 起 岂 乞 企 启 契 砌器 气 迄 弃 汽 泣 讫 掐

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

40 区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 19 取 要 龋 趣 去 圈 鞭 权 醛 泉 全 痊 拳 犬 券 劝 缺 炔 瘸 ²⁰ 动 鹊 榷 确 雀 裙 群然 燃 冉 染 瓤 壤 瓖 课 让 饶 扰 绕 惹 R ⁴⁰ 孙 千 仁 人 忍 韧 任 认 刃 妊 纫 扔 仍 日 戎 茸 蓉 荣 融 熔 ⁶⁰ 冷 容 绒 冗 揉 柔 肉 茹 蠕 儒 孺 如 辱 乳 汝 入 褥 软 阮 蕊 ⁸⁰ 瑞 锐 闰 润 若 弱 撒 洒 萨 腮 鳃 塞 赛 三 叁 S

42区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 01 省盛剩胜圣师失狮施湿诗尸虱十石拾时什食 20 实识史矢使屎驶始式示士世柿事拭誓逝势是 嗜噬适仕侍释饰氏市恃室视试览手首守寿授售 受瘦兽蔬枢梳殊抒输叔舒淑疏书赎孰熟薯暑曙 80 署蜀黍鼠属术述树束戍竖墅庶数漱

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

49区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19
01 选癣眩绚靴薛学穴雪血勋熏循旬询寻驯巡殉
20 汛训讯逊迅压押鸦鸭呀丫芽牙蚜崖衙涯雅哑亚Y
40 등 60 行演艳堰燕厌砚雁唁彦焰宴谚验殃央鸯秧杨扬
80 佯疡羊洋阳氧仰痒养样漾邀腰妖瑶

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

54区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 01 20 帧症郑证芝枝支吱蜘知肢脂汁之织职直植殖物 执值侄址指止趾只旨纸志挚掷至致置帜峙制智 20 秩稚质炙痔滞治窒中盅忠钟衷终种肿重仲众 60 79 周州洲诌粥轴肘帚咒皱宙昼骤珠株蛛朱猪诸诛 逐竹烛煮挂瞩嘱主著柱助蛀贮铸筑

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

58 × 松一冢冥讠讦讧讪讴讵讷诂诃诋诏诎诒诓诔 违 诘 诙 诜 诟 诠 净 诨 诩 诮 诰 诳 诶 诹 诼 诿 谀 谂 谄 谇 谌谏谑谒谔谕谖谙谛谘谝谟谠谡谥滥谪谫谮谯 谲谳 " 谶 D 卺 B 阢 阡 阱 阪 阽 阼 陂 陉 陔 陟 陧 陬 陲 💢 🗀 陴 隈 隍 隗 隰 邗 邛 邝 邙 邬 邡 邴 邳 邶 邺 🗵 01 02 03 邸邰郏郅邾郐郄郇郓酃郢郜郗郛郫郯郾鄄鄢 鄞鄣鄱鄯鄹酃豐刍奂劢劬劭劾哿勐勖勰叟燮矍沉 **廴山凼鬯** ム弁 畚硫 盆垩 堡 塾 墾 壅 堡 圩 圬 圪 圳 圹 Ḥtto 圮 圯 坜 圻 坂 坩 垅 坫 垆 坼 坻 坨 坭 坶 坳 垭 垤 垌 垲 埏 垧垴垓垠埕埘埚埙埒垸埴埯埸埤埝 60区 02 03 堋 堍 埽 埭 堀 堞 堙 塄 堠 塥 塬 墁 墉 墚 墀 馨 鼙 懿 艹 ** **艽艿** 芊芊 芨 芄 芎 芑 芗 芙 芫 芸 芾 芰 苈 苊 苣 芘 芷 芮 苋苌苁芩芴芡芪芟苄苎芤苡茉苷苤茏茇苜苴苒 苘在苻苓茑茚茆茔茕莨苕茜荑荛荜茈莒茼茴茱

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

 ⊠ 14 15 荨 茛 荩 荚 荪 荭 荮 莰 荸 莳 莴 莠 莪 莓 莜 莅 荼 莶 莩 荽 莸 荻 莘 莞 莨 莺 莼 菁 萁 菥 菘 堇 萘 萋 菝 苺 菖 萜 萸 在 革 菔 菟 萏 萃 菸 菹 菪 菅 菀 萦 菰 菡 葜 葑 葚 葙 葳 蒇 蒈 葺 蒉 葸 萼 葆 葩 葶 蒌 蒎 萱 葭 蓁 蓍 蓐 蓦 蒽 蓓 蓊 蒿 蒺蓠蒡蒹蒴蒗莹蓣蔌甍蔸蓰蔹蔟蔺

62区 01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19

□ 葉蔻蓿蓼蔥蘑藤蕤蕞蕺膏蕃蕲蕻薤薨薇薏蕹
□ 薮薜薅薹薷薰藓藁藜藿蘧蘅蘩蘖蘼升弈夼奁耷***
□ 突奚奘匏尢尬尬尴扌扪抟抻拊拚拗拮挢拶挹捋**□
□ 指掭揶捱捺掎掴捭掬掊捩掮掼揲揸揠揿揄掊揎
□ 摒揆掾摅摁搋搛搠搌搦搡摞撄摭撖

63区 11 12 摺撷撸撙撺擀擐擗擤擢攉攥攮弋忒甙弑卟叱节 叽叩叨叻吒吖吆呋呒呓呔呖呃吡呗呙吣吲咂咔 呷呱呤咚咛咄呶呦咝哐咭哂咴哒咧咦哓哔呲咣 哕 咻 咿 哌 唉 哚 哜 咩 咪 咤 哝 哏 哞 唛 哧 唠 哽 唔 哳 唢 鸣 唏 哗 唧 唪 晴 喏 喵 啉 啭 啁 啕 唿 啐 唼

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

64 × 01 02 03 唷啖啵啶啷唳唰啜喋嗒喃喱喹喈喁喟啾嗖喑 啻 嗟 喽 喾 喔 喙 嗪 嗷 嗉 嘟 嗑 嗫 嗬 嗔 嗦 嗝 嗄 嗯 嗥 嗲 嗳嗌嗍嗨嗵嗤辔嘞嘈嘌嘁嘤嘣嗾嘀嘧嘭噘嘹噗 ≀ 59 嘬 噍 噢 噙 噜 噌 噔 嚆 噤 噱 噫 噻 噼 嚅 嚓 嚯 囔 囗 囝 囡 **囵囫囹囿圄圊圉圆帏帙帔帑畴帻帼** 帷幄幔幛幞幡岌屺岍岐岖岈岘岙岑岚岜岵岢 岩岬岫岱岣峁岷峄峒峤峋峥崂崃 崧崦 崮崤 崞崆 崛嵘崾崴崽嵬嵛嵯嵝嵫嵋嵊嵩嵴嶂嶙嶝豳嶷巅 **彳彷徂徇徉後徕徙徜徨徭徵徼衢彡犭犰犴犷犸** 扭 狁 狎 狍 狒 狨 狯 狩 狲 狴 狷 猁 狳 猃 狺 **66区** 後 猗 猓 猡 猊 猞 猝 猕 猢 猹 猥 猬 猸 猱 獐 獍 獗 獠 獬 獯獾舛夥飧夤又饣饧饨饩饪饫饬饴饷饽馀馄馇 馊馍馐馑馓馔馕庀庑庋庖庥庠庹庵庾庳赓廒廑广 廛廨廪膺忄忉忖忏怃忮怄忡忤忾怅怆忪忭忸怙 *** 忧 怦 怛 快 作 怩 怫 怊 怿 怡 恸 恹 恻 恺 恂

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

67区 16 09 11 12 13 14 15 08 01 恪恽悖悚悭悝悃悒悌悛惬悻悱惝惘惆惚悴愠 19 愦愕愣惴愀愎愫慊慵憬憔懂憷懔懵忝隳闩闫闱ⁿ 因闵闶闼闾阃阄阆阈阊阋阌阍阏阒阕阖阗阙阚 60 爿 戕 ; 汔 氾 汊 沣 沅 沐 沔 沌 汨 汩 汴 汶 沆 沩 泐 泔 ; (*) 沭 泷 泸 泱 泗 沲 泠 泖 泺 泫 泮 沱 泓 泯 泾

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

70区 妗 姊 妫 妞 妤 姒 妲 妯 姗 妾 娅 娆 姝 娈 姣 姘 姹 娌 娉 娲娲娑娣娓婀婧婊婕娟婢婵胬媪媛婷婺媾嫫嫓 ,40 媛嫔媸嫠嫣嫱嫖嫦嫘嫜嬉嬗嬖嬲嬷孀尕尜孚孥ฐ 孳孑孓孢驵驷驸驺驿驽骀骁骅骈骊骐骒骓骖骘" 骛 骜 骝 骟 骠 骢 骣 骥 骧 纟 纡 纣 纥 纨 纩 **71区** 纭 纰 纾 绀 绁 绂 绉 绋 绌 绐 绔 绗 绛 绠 绡 绨 绫 绮 绯 绱 绲 缍 绶 绺 绻 绾 缁 缂 缃 缇 缈 缋 缌 缏 缑 缒 缗 缙 缜 缛 缟 缡 缢 缣 缤 缥 缦 缧 缪 缫 缬 缭 缯 缰 缱 缲 缳 缵 幺 畿《甾邕打玑玮玢玟珏珂珑玷玳珀珉珈珥珙顼 琊珩珧珞玺珲琏琪瑛琦琥琨琰琮琬 72区 琛 琚 瑁 瑜 瑗 瑕 瑙 瑷 瑭 瑾 璜 璎 璀 璁 璇 璋 璞 璨 璩 璐 襞 瓒 嬰 韪 韫 韬 杌 杓 杞 杈 杩 枥 枇 杪 杳 枘 枧 杵 枨 枞枭枋杷杼柰栉柘栊柩枰栌柙枵柚枳柝栀柃枸 抵 栎 柁 柽 栲 栳 桠 桡 桎 桢 桄 桤 梃 栝 桕 桦 桁 桧 桀 栾 ₹ 79 券 桉 栩 梵 梏 桴 桷 梓 桫 棂 楮 棼 椟 椠 棹

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

区 椤棰椋椁楗棣椐楱椹楠楂楝榄楫榀榘楸椴槌 榇榈槎榉楦楣楹榛榧榻榫榭槔榱槁槊槟榕槠榍 槿樯槭樗樘橥槲橄樾檠橐橛樵檎橹樽樨橘橼檑 檐檩檗檫猷獒殁殂殇殄殒殓殍殚殛殡殪轫轭轱ඐ 轲轳轵轶轸轷轹轺轼轾辁辂辄辇辋 **74区** 辍 辎 揍 辘 辚 害 戋 戗 戛 戟 戢 戡 戥 戳 戳 瓯 瓴 瓿 甏甑甓支旮旯旰昊昙杲昃昕昀炅曷咎昴昱昶昵如明 者 晟 晔 晁 晏 晖 晡 晗 晷 暄 暌 暧 暝 暾 曛 曜 曦 曩 贲 贳 贶贻贽赀赅赆赈赉财赍赕赙觇觊觋觌觎觏觐觑 牛(1) 华犟牝牦牯牾牿犄犋犍犏犒挈挲掰 **75区** 掰擘 耄 毪 毳 毽 毵 毹 氅 氇 氆 氍 氕 氘 氙 氚 氡 氩 氤 氪 氲 女 敕 敫 牍 牒 牖 爰 號 刖 肟 肜 肓 肼 朊 肽 肱 肫 肭 絹 "" 肴 肷 胧 胨 胩 胪 胛 胂 胄 胙 胍 胗 朐 胝 胫 胱 胴 胭 脍 脎 腽腭腧塍媵膈膂膑滕膣膪臌朦臊膻

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

76区 11 12 13 14 80 09 10 06 07 01 臁膦欤欷欹歃歆歙飑飒飓飕飙飚殳彀毂觳斐 19 面斓於旆旄旃旌旎旒旖炀炜炖炝炻烀炷炫炱烨 烊 焐 焓 焖 焯 焱 煳 煜 煨 煅 煲 煊 煸 煺 熘 熳 熵 熨 熠 燠 燔燧燹爝爨灬焘煦熹戾戽扃扈扉礻祀祆祉祛祜 祓 祚 祢 祗 祠 祯 祧 祺 禅 禊 禚 禧 穰 忑 忐 12 13 **怼** 恝 恚 恧 恁 恙 恣 悫 愆 愍 慝 憩 憝 懋 懑 戆 肀 聿 沓 ╬ **** 01 19 20 砣 砩 硎 硭 硖 硗 砦 硐 硇 硌 硪 碛 碓 碚 碇 碜 碡 碣 碲 碹 59 偏 磔 磙 磉 磬 磲 礅 磴 礓 礤 礞 礴 龛 黹 黻 黼 盱 眄 眍 盹 🚏 眇眈告智胎眭眦眵眸睐睑睇睃睚睨 13 78区 12 10 09 睢睥睿瞍睽瞀瞌瞑瞟瞠瞰瞵瞽町畀畎畋畈畛 19 會畹疃 罘罡 罟 詈 罨 罴 罱 罹 羁 罾 盍 盥 蠲 钅 钆 钇 钋 📆 钊钌钍钏钐钔钗钕钚钛钜钣钤钫钪钭钬钯钰钲 钴钶钷铈钹钺钼钽钿铄铈铉铊铋铌铍铎铐铑铒 铕铖铗铙铘铛铞铟铠铢铤铥铧铨铪

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

10 11 12 13 08 09 **79** 🗵 07 铩铫铮铯铳铴铵铷铹铼铽铿锃锂锆锇锉锊锍 01 19 锎锏锒锓锔锕锖锘锛锝锞锟锢锪锫锩锬锱锲锴 锶锷锸锼锾锿镂锵镄镅镆镉镌镎镏镒镓镔镖镗 59 慢镙镛镞镟镝镡镢镤镥镦镧镨镩镪镫镬镯镱镲 矢禾 镳鍾矧矬雉秕秭秣秫稆嵇稃稂稞稔 15 13 12 80 区 積 稷 穑 黏 馥 穰 皈 皎 皓 皙 皤 瓞 瓠 甬 鸠 鸢 鸨 鸩 鸪 鸫鸬鸲鸱鸶鸸鸷鸹鸺鸾鹁鹂鹄鹆鹇鹈鹉鹋鹌鹎 鹑鹕鹗鹚鹛鹜鹞鹣鹦鹧鹮鹩鹪鹫鹬鹱鹭鹳广疔' 疖疠疝疬疣疳疴疸痄疱疰痃痂痖痍痣痨痦痤痫 痧瘃痱痼痿瘐瘀瘅瘌瘗瘊瘥瘘瘕瘙 14 1.5 11 12 13 81区 09 10 瘛 瘼 瘢 瘠 癀 瘭 瘰 瘿 瘵 癃 瘾 瘳 癍 癞 癔 癜 癖 癲 癯 19 翊竦 穸穹窀窆窈窕窦窠窬窨窭窳衤衩衲衽衿袂 ‡☆ 袢裆袷袼裉裢裎裣裥裱褚裼裨裾裰褡褙褓褛褊 褴 褫 褶 襁 襦 襻 疋 胥 皲 皴 矜 耒 耔 耖 耜 耠 耢 耥 耦 耧 *** ₽It 耩 耨 耱 耋 耵 聃 聆 聍 聒 聩 聱 覃 顸 颀 颃 西页

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

12 13 11 **82**区 05 02 03 04 颉颌颍颏颔颚颛颞颟颡颢颥颦庀虔虬虮虿虺 01 19 蛇虻蚨蚍蚋蚬蚝蚧蚣蚪蚓蚩蚶蛄蚵蛎蛐蚺蚱蚯 蛉 蛏 蚴 蛩 蛱 蛲 蛭 蛳 蛐 蜓 蛞 蛴 蛟 蛘 蛑 蜃 蜇 蛸 蜈 蜊 59 蜍蜉蜣蜻蜞蜥蜮蜚蜾蝈蜴蜱蜩蜷蜿螂蜢蝽蝾蝻 79 蝠蝰蝌蝮螋蝓蝣蝼蝤蝙蝥螓螯螨蟒 80 94 12 13 14 08 09 10 03 05 06 07 螃螯蟥螬螵螳蟋蟓螽蟑蟀蟊蟛蟪 01螭 螗 蟆螈螅 19 蟠蟮蠖蠓蟾蠊蠛蠡蠹蠼缶罂罄罅舐竺竽笈笃笄ः 39 笕笊笫笏筇笸笪笙笮笱笠笥笤笳笾笞筘筚筅筵 筌筝筠筮筻筢筲筱箐箦箧箸箬箝箨箅箪箜箢箫 箴篑篁篌篝篚篥篦篪簌篾篼簏簖簋 94 12 84 区 08 09 02 簟簪簪簸籁籀 臾异春舄 臬衄 舡舢 舣 舭 舯 舨 舫 01 19 舸舻舳舴舾艄艉艋艏艚艟艨衾袅袈裘裟襞羝羟 5年 羧 揭 羰 羲 籼 敉 杷 粝 粜 栖 粢 粲 鄰 粽 糁 糇 糌 糍 糈 糅 * 糗 糨 艮 暨 羿 翎 翕 翥 翡 翦 翩 翮 翳 糸 絷 綦 綮 繇 纛 麸 上东 麴 赳 趄 趔 趑 趱 赧 赭 豇 豉 酊 酐 酎 酏 酤 g 📆

Table B.7 (continued): Optional character set for Chinese Characters (character set indicator 10000)

85 区 12 10 (1) 酢 酡 酰 酩 酯 酽 酾 酲 酴 酹 醌 醅 醐 醍 醑 醢 醣 醪 醭 19 醮 醯 醵 醴 醺 豕 鹾 趸 跫 踅 蹙 蹩 趵 趿 趼 趺 跄 跖 跗 跚 39 40 59 60 踯踺蹀踹踵踽踱蹉蹁蹂蹑蹒蹊蹰蹶蹼蹯蹴躅躏 79 寄柏 躔 躐 躜 躞 豸 貂 貊 貅 貘 貔 斛 觖 觞 觚 觜 03 觥練觯訾聲靓雩雳雯霆霁霈霏霎霪霭霰霾龀 龃龅龆龇龈龉龊龌黾鼋鼍隹隼隽雎雒瞿雠銎銮 鋈錾鏊鎏鐾蠢鱿鲂鲅鲆鲇鲈稣鲋鲎鲐鲑鲒鲔 鲕鲚鲛鲞鲟鲠鲡鲢鲣鲥鲦鲧鲨鲩鲫鲭鲮鲰鲱鲲 鲳鲴鲵鲶鲷鲺鲻鲼鲽鳄鳅鳆鳇鳊鳋 87区 02 03 0.107 鳌鳍鳎鳏鳐鳓鳔鳕鳗鳘鳙懸鳝鳟鳢靼鞅鞑鞒 19 鞔鞯 鞫鞣 鞲 鞴 骱 骰 骷 鹘 骶 骺 骼 髁 髀 髅 髂 髋 髌 髑 39 魅魃魇魎魈魍魎飨餍餮饕饔髟髡髦髯髫髻髭髹 59 鬈鬏鬓鬟鬣麽麾縻麂麇麋麒鏖麝麟黛黜黝黠 79 80 MA 黟 黢 黩 黧 黥 黪 黯 鼢 鼬 鼯 鼹 鼷 鼽 鼾 凡

Page 76

Draft prETS 300 133-2: April 1996

Table B.7 (concluded): Optional character set for Chinese Characters (character set indicator 10000)

NOTE 1: The 7 bit information unit 0010001 (DC1) (see table B.3) shall be used only as the End Of Message (EOM) character.

NOTE 2: The characters of this set, when presented, should approximate to the appearance of the relevant

characters in table B.7.

Annex C (normative): The concept of radiodistribution

The term "radiodistribution" has been used without definition in this standard. This annex describes radiodistribution as applied in the ERMES system.

Radiodistribution is the possibility of a calling party, restricted to the information supplier, to broadcast messages to a large but selective group of receivers. Radiodistribution services may be used for selling public information (such as weather forecasts, stock market information, etc.) to groups of people who have signed a subscription for this service, with the information supplier entering the messages into the system. The information supplier would normally be a fixed subscriber.

The radiodistribution service is not a supplementary service of the paging network but an external service using the paging network as a transport link. Radiodistribution messages can be sent in one or more paging areas defined by the information supplier. For implementation of a radiodistribution service in the ERMES system the "group call to mobile subscribers using a common RIC" supplementary service should be used to obtain better spectrum efficiency.

Annex D (normative): Essential and optional receiver features

Table D.1: Essential and optional receiver features

Receiver feature	Tone only	Numeric	Alpha numeric	Transpar ent data
Tone-only	Е	E	E	0
Numeric	-	Е	Е	0
Alphanumeric	-	-	Е	0
Transparent data	-	-	-	E
Alert signals	Е	E	E	0
Access to the message	-	0	0	0
Repeated call indication	0	E	Е	0
Lost message indication	-	0	0	0
Remote programming of RIC	0	0	0	0
Out of range indication	0	0	0	0
Urgent message indicator	0	0	0	0
Silent mode	Ш	Е	E	0
Battery low indication	Е	Е	Е	E
Message storage / retrieval	0	0	0	0
Memory full	0	0	0	0
Message manipulation	0	0	0	0
Display	0	0	0	0
Printer interface	-	0	0	0
Data interface	0	0	0	0
Date/time indication	0	0	0	0
Encryption	-	0	0	0

NOTE: E: Essential

O: Optional
-: Not applicable

History

	Document history						
July 1992	First Edition						
April 1996	Public Enquiry	PE 105:	1996-04-08 to 1996-08-30				