



# AMENDMENT

**I-ETS 300 219**  
pr **A1**

June 1996

---

Source: ETSI TC-RES

Reference: RI/RES-02023

ICS: 33.060.20, 33.060.50

**Key words:** Mobile, radio, testing

**This draft amendment A1, if approved, will modify  
the European Telecommunication Standard ETS 300 219 (1993)**

**Radio Equipment and Systems (RES);  
Land Mobile Service;  
Technical characteristics and test conditions for  
radio equipment transmitting signals to initiate  
a specific response in the receiver**

## ETSI

European Telecommunications Standards Institute

### ETSI Secretariat

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

\*

---

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.



## Foreword

This draft amendment to I-ETS 300 219 (1993) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI), and is now submitted for the Unified Approval Procedure phase of the ETSI standards approval procedure.

<b>Proposed announcement date</b>	
Date of latest announcement of this amendment (doa):	3 months after ETSI publication

## Amendments

### Page 7, Foreword

Replace fifth paragraph with:

Channel separations, maximum transmitter output power / effective radiated power, class of transmitter intermodulation attenuation and the inclusion of automatic transmitter shut-off facility may all be conditions required for the issue of a licence by the appropriate regulatory authority.

### Page 22, subclause 7.4.1

Replace entire subclause with:

For tests at extreme temperatures, measurements shall be made in accordance with the procedures specified in subclause 7.5, at the upper and lower temperatures of the following range:

-20 °C to + 55 °C.

For the purpose of note (a) to table 1 in subclause 6.1.1, an additional reduced extreme temperature range of 0 °C to + 30 °C shall be used when appropriate.

Type test reports shall state the temperature range used.

**History**

<b>Document history</b>			
February 1992	Public Enquiry	PE 26:	1992-02-04 to 1992-06-05
February 1993	Vote	V 32:	1993-02-15 to 1993-04-09
October 1993	First Edition		
June 1996	Unified Approval Procedure	UAP 49:	1996-06-24 to 1996-10-18